



FCC RF Exposure Test Report

Report No. : PSU-NQN2504020112SA01
Applicant : InHand Networks, Inc.
Address : 43671 Trade Center Place, Suite 100, Dulles, VA 20166 United States
Product : Edge Computer
Brand Name : inhand
Model Name : EC3320,EC3310,EC3340
FCC ID : 2BPWU-EC3320
Standards : FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

Date of Testing : Mar.31, 2025 ~ Apr.30, 2025

The FCC Site Registration No. : 434559

The Designation No. : CN1325

CERTIFICATION: The above equipment have been tested by **Huarui 7Layers High Technology (Suzhou) Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

Chang Gao

(Chang Gao / Engineer)

Approved By :

Simfei bo

(Peibo Sun /Manager)

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Table of Contents

RELEASE CONTROL RECORD	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST	4
2. MPE(MAXIMUM PERMISSIBLE EXPOSURE) ASSESSMENT	5
2.1 INTRODUCTION	5
2.2 RF RADIATION EXPOSURE LIMITS	5
2.3 MPE ASSESSMENT METHOD	6
2.4 MPE CALCULATION FOR STANDALONE OPERATIONS	6
3. INFORMATION ON THE TESTING LABORATORIES.....	8



Release Control Record



1. Description of Equipment Under Test

EUT Type	Edge Computer
Brand Name	inhand
Model Name	EC3320,EC3310,EC3340
Tx Frequency Bands (Unit: MHz)	LTE: Band2/4/5/7/12/13/14/17/25/26/30/38/41/42/43/48/66/70/71 WIFI2.4G:2.412GHz~2.462GHz WIFI5G:5180 ~ 5240MHz, 5745 ~ 5825MHz
Uplink Modulations	LTE: QPSK, 16QAM, 64QAM,256 QAM WIFI2.4G: DSSS, OFDM WIFI5G: OFDM
HW VERSION	V2.2
SW VERSION	V2.0
Antenna Type	Sucker Antenna with 1.25dBi gain for LTE B5/LTE B26 Sucker Antenna with 2.94dBi gain for LTE B2/ LTE B25 Sucker Antenna with 2.6 dBi gain for LTE B7/30 Sucker Antenna with 1.25 dBi gain for LTE B12/13/17/71 Sucker Antenna with 2.94dBi gain for LTE B4/66 Sucker Antenna with 2.6dBi gain for LTE B38/41 Sucker Antenna with -2.0dBi gain for LTE B42/43 Sucker Antenna with 1.25 dBi for LTE Band 14/ LTE Band 26 Sucker Antenna with -2.0dBi gain for LTE B42/43/48 Sucker Antenna with 3.0dBi gain for WIFI2.4G Sucker Antenna with 0.02dBi for WIFI5G (5180 ~ 5240MHz/5745 ~ 5825MHz)

Note:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



Certificate #6613.01

2. MPE(Maximum Permissible Exposure) Assessment

2.1 Introduction

According to 47 CFR §2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitting antenna and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 cm separation requirement. The limits to be used for MPE evaluation are specified in §1.1310. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population/uncontrolled exposure.

2.2 RF Radiation Exposure Limits

According to 47 CFR §1.1310, the criteria listed in below table shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093.

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (min)
(A) Limits for Occupational / Controlled Exposures				
0.3 – 3.0	614	1.63	100	6
3.0 – 30	1842/f	4.89/f	900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	-	-	f/300	6
1500 – 100000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposures				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	-	-	f/1500	30
1500 – 100000	-	-	1.0	30

Limits for maximum permissible exposure (MPE)

Notes:

1. f = frequency in MHz
2. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided they are made aware of the potential for exposure.
3. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



2.3 MPE Assessment Method

Calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations below. This equation is generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction.

$$\text{Power Density (S)} = \frac{PG}{4\pi R^2} = \frac{\text{EIRP}}{4\pi R^2}$$

Where

S = Power Density, unit in mW/cm²

P = Power input to the antenna, unit in mW

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna, unit in cm

EIRP = Effective isotropically radiated power

2.4 MPE Calculation for Standalone Operations

The manufacturer expects that the radiated component of this device will not close to the human body during normal usage and the warning statement was also stated in the user instruction. Since the transmitting antenna will be kept at least 20 cm away from the human body, the MPE level is calculated based on this condition and the result is listed in below table.



RF Exposure Evaluation Results:

Band	Freq. (MHz)	Maximum Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP(mW)	Power Density (mW/cm^2)	Power Density/ Limit
LTE B2	1882.5	23.76	2.94	26.70	467.735	0.093	0.093
LTE B4	1777.5	23.75	2.94	26.69	466.659	0.093	0.093
LTE B5	846.5	23.75	1.25	25.00	316.228	0.063	0.113
LTE B7	2565	23.35	2.60	25.95	393.550	0.078	0.078
LTE B12	711	23.58	1.25	24.83	304.089	0.060	0.130
LTE B13	779.5	23.76	1.25	25.01	316.957	0.063	0.121
LTE B14	793	23.67	1.25	24.92	310.456	0.062	0.117
LTE B17	713.5	23.58	1.25	24.83	304.089	0.060	0.127
LTE B25	1882.5	23.76	2.94	26.70	467.735	0.093	0.093
LTE B26	819	23.75	1.25	25.00	316.228	0.063	0.115
LTE B28	2307.5	22.10	2.60	24.70	295.121	0.059	0.059
LTE B30	2687.5	23.56	2.60	26.16	413.048	0.082	0.082
LTE B38	2687.5	23.56	2.60	26.16	413.048	0.082	0.082
LTE B41	3597.5	21.46	-2.00	19.46	88.308	0.018	0.018
LTE B48	3795	21.56	-2.00	19.56	90.365	0.018	0.018
LTE B66	3552.5	21.45	-2.00	19.45	88.105	0.018	0.018
LTE B71	1777.5	23.75	2.94	26.69	466.659	0.093	0.093
WIFI 2.4G	2437	14.78	3.00	17.78	59.979	0.012	0.012
WIFI 5.2G	5190	19.70	0.02	19.72	93.756	0.019	0.019
WIFI 5.8G	5825	18.63	0.02	18.65	73.282	0.015	0.015

Simultaneous Transmission Result

Power Density1(LTE12) / Limit	Powe Density2(WIFI 5.2G) / Limit	Σ (Power Density / Limit)
0.130	0.019	0.149

Note: Simultaneous Transmission Limit = Power_1 / Limit_1 + Power_2 / Limit_2 < 1.



3. Information on the Testing Laboratories

We, Huarui 7Layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

Suzhou EMC/RF Lab:

Tel: +86 (0557) 368 1008

---END---