



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01



Certificate #6613.01

EMC TEST REPORT

Applicant:	InHand Networks, Inc.
Address:	43671 Trade Center Place, Suite 100, Dulles, VA 20166 United States

Manufacturer or Supplier:	InHand Networks, Inc.
Address:	43671 Trade Center Place, Suite 100, Dulles, VA 20166 United States
Product:	Industrial Cellular Router
Brand Name:	inhand
Model Name:	IR302-FQ38-WLAN v2, IR352-FQ38-WLAN v2, IR392-FQ38-WLAN v2
FCC ID:	2BPWU-IR302
Date of tests:	May. 8, 2025~ May. 21, 2025

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

FCC Part 15, Subpart B, Class A
 FCC Part 15, Subpart B, Class B
 ANSI C63.4:2014

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department

Date: May. 21, 2025

Date: May. 21, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION	4
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 SUMMARY OF TEST RESULTS	5
1.3 MEASUREMENT UNCERTAINTY	6
1.4 DESCRIPTION OF TEST MODES	7
1.5 DESCRIPTION OF SUPPORT UNITS	8
2 EMISSION TEST	9
2.1 CONDUCTED EMISSION MEASUREMENT	9
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
2.1.2 TEST INSTRUMENTS	10
2.1.3 TEST PROCEDURES	11
2.1.4 DEVIATION FROM TEST STANDARD	11
2.1.5 TEST SETUP	11
2.1.6 EUT OPERATING CONDITIONS	12
2.1.7 TEST RESULTS	13
2.2 RADIATED EMISSION MEASUREMENT	15
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
2.2.2 TEST INSTRUMENTS	16
2.2.3 TEST PROCEDURE	17
2.2.4 DEVIATION FROM TEST STANDARD	18
2.2.5 TEST SETUP	19
2.2.6 EUT OPERATING CONDITIONS	19
2.2.7 TEST RESULTS	20
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	23



**BUREAU
VERITAS** Test Report No.: PSU-NQN2505120312EM01

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-NQN2505120312EM01	Original release	May. 21, 2025



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Industrial Cellular Router		
BRAND NAME	inhand		
MODEL NAME	IR302-FQ38-WLAN v2, IR352-FQ38-WLAN v2, IR392-FQ38-WLAN v2		
NOMINAL VOLTAGE	DC 12V		
IMEI	863890057551630		
OPERATING FREQUENCY	WLAN	2.412GHz~2.462GHz	
	LTE	1850.7MHz ~ 1909.3MHz	(FOR LTE Band2)
		1710.7MHz ~ 1754.3MHz	(FOR LTE Band4)
		824.7MHz ~ 848.3MHz	(FOR LTE Band5))
		699.7MHz ~ 715.3MHz	(FOR LTE Band12)
		779.5MHz ~ 784.5MHz	(FOR LTE Band13)
		790.5MHz ~ 795.5MHz	(FOR LTE Band14)
1710.7MHz ~ 1779.3MHz	(FOR LTE Band66)		
	665.5MHz ~ 695.5MHz	(FOR LTE Band71)	

HW VERSION	V1.5
SW VERSION	V3.5
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A
ACCESSORY DEVICES	Refer to note as below

NOTE:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Test Model No.: IR302-FQ38-WLAN v2
Series Models NO: IR352-FQ38-WLAN v2, IR392-FQ38-WLAN v2
These three models are the same in these: appearance, PCB layout and basic software function;
The only difference is that the products are used in different markets.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

List of Accessory:

AE (Auxiliary Equipment) 1#: AC Adaptor

Manufacturer	SHENZHEN KUANTEN LIMITED
Model Number	KT241120200CHL
Input Voltage	100V-240V AC
Output Voltage	12V /2A

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B		
Standard Section	Test Item	Result
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance
	Radiated Emission Test (Above 1GHz)	Compliance

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.



BUREAU
VERITAS


Test Report No.: PSU-NQN2505120312EM01

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	LTE /WLAN receiver
Conducted emission test	
1	LTE /WLAN receiver

NOTE:

1. For conducted emission test, Pre-scan all mode, mode 1 was the worst case and only this mode was presented in this report.
2. For radiated emission test, Pre-scan all mode, test mode 1 was the worst case and only this mode was presented in this report



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	---	---	---	---	---



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.107 A CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.107 B CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2.1.2 TEST INSTRUMENTS

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mSe mi-AnechoicChamber	FRANKONIA	-----	2028.09.05	2023.09.05
2	ESW EMI test receiver	R&S	101574	2026.03.06	2025.03.06
3	ESR3 EMI test receiver	R&S	102361	2026.03.06	2025.03.06
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	2027.03.25	2022.03.25
5	VULB 9163 Ultra log test antenna	schwarzbeck	727	2027.05.28	2025.05.28
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2025.07.20	2023.07.20
7	SAS-574 Horn Antenna	schwarzbeck	535	2027.05.12	2025.05.12
8	ENV216 AMN	R&S	101881	2025.06.21	2024.06.21
9	EMC32EMI test software	R&S	V10	-----	-----

NOTE: 1. The test was performed in CE shielded room.



2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD


No deviation.

2.1.5 TEST SETUP



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS


- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	22.2deg. C, 40.3%RH	TESTED BY	Hanwen Xu



Pic1. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak	Pmea Average
							(dB μ V)	(dB μ V)
0.20117	34.24	---	63.56	29.32	L1	29.60	4.64	---
0.35895	---	18.91	48.75	29.84	L1	29.60	---	-10.69
0.54231	---	27.88	46.00	18.12	L1	29.60	---	-1.72
0.54231	34.19	---	56.00	21.81	N	29.60	4.59	---
1.14358	28.29	---	56.00	27.71	N	29.60	-1.31	---
2.07319	---	17.33	46.00	28.67	L1	29.60	---	-12.27
2.22671	28.00	---	56.00	28.00	N	29.60	-1.60	---
3.55716	---	17.57	46.00	28.43	L1	29.60	---	-12.03
7.94085	---	17.74	50.00	32.26	N	29.80	---	-12.06
9.33527	27.94	---	60.00	33.06	L1	29.80	-1.86	---
28.14077	---	18.66	50.00	31.34	N	30.60	---	-11.94
28.70366	27.81	---	60.00	32.19	N	30.60	-2.79	---

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Sample calculation: $(34.24\text{dB}\mu\text{V}) = (4.64\text{dB}\mu\text{V}) + (29.6 \text{ dB})$, the corresponding frequency is 0.20117MHz.




BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

TEST VOLTAGE	Input 240 Vac, 50 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	22.2deg. C, 40.3%RH	TESTED BY	Hanwen Xu

Full Spectrum



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dB μ V)	Pmea Average (dB μ V)
0.25234	30.43	---	61.68	31.25	L1	29.60	0.83	---
0.33336	---	20.56	49.37	28.81	L1	29.60	---	-9.04
0.54658	29.61	---	56.00	26.39	L1	29.60	0.01	---
0.55937	---	24.77	46.00	21.23	L1	29.60	---	-4.83
1.39944	---	17.14	46.00	28.86	L1	29.60	---	-12.46
1.51884	26.33	---	56.00	28.67	L1	29.60	-3.27	---
4.60618	---	17.93	46.00	28.07	N	29.60	---	-11.67
4.94732	25.99	---	56.00	30.01	N	29.60	-3.61	---
6.55496	---	18.19	50.00	31.81	N	29.70	---	-11.51
11.70621	24.64	---	60.00	35.36	L1	29.90	-5.26	---
28.71645	26.02	---	60.00	33.98	L1	30.70	-4.68	---
28.94672	---	19.34	50.00	30.66	L1	30.70	---	-11.36

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Presult=Pmea+ Corr.(dB).



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC PART 15, SUBPART B (SECTION: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B, Class A	FCC 15B, Class B
30-88	49	40
88-216	53.5	43.5
216-960	56	46
960-1000	59.5	54
Above 1000	Avg: 59.5 Peak: 79.5	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. QP detector shall be applied if not specified.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2.2.2 TEST INSTRUMENTS

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mSe mi-AnechoicChamber	FRANKONIA	-----	2028.09.05	2023.09.05
2	ESW EMI test receiver	R&S	101574	2026.03.06	2025.03.06
3	ESR3 EMI test receiver	R&S	102361	2026.03.06	2025.03.06
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	2027.03.25	2022.03.25
5	VULB 9163 Ultra log test antenna	schwarzbeck	727	2027.05.28	2025.05.28
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2025.07.20	2023.07.20
7	SAS-574 Horn Antenna	schwarzbeck	535	2027.05.12	2025.05.12
8	ENV216 AMN	R&S	101881	2025.06.21	2024.06.21
9	EMC32EMI test software	R&S	V10	-----	-----

NOTE: 1. The test was performed in 10m chamber.

2. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Result= $P_{mea} + A_{Rpl}$.
3. A_{Rpl} (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. A_{Rpl} (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:


- . The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz.
- . For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
- . $Result = P_{mea} + A_{Rpl}$.
- . $A_{Rpl} (dB/m) = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
- . $A_{Rpl} (dB/m) = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)

2.2.4 DEVIATION FROM TEST STANDARD


No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.



BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

2.2.7 TEST RESULTS

Note: For frequency above 18GHz, the emission was tested 20db below the limit so not recorded.


Acceleromete alternative worst case:

TEST VOLTAGE	Input 240 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	22.2deg. C, 40.3%RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Hanwen Xu		

Frequency(MHz)	Result(dB μ V/m)	Limit (dB μ V/m)	ARpl (dB)	Pmea (dB μ V/m)	Polarity
36.208	24.17	40.0	-18.2	42.37	V
56.1415	21.83	40.0	-15.7	37.53	V
139.998	27.76	43.5	-20.6	48.36	V
189.468	25.33	43.5	-17.7	43.03	V
394.235	20.30	46.0	-11.6	31.90	V
958.339	22.92	46.0	-2.0	24.92	V

REMARKS: 1. Result= $P_{mea} + A_{Rpl}$.

2. Sample calculation: $(24.17 \text{ dB } \mu \text{ V/m}) = (42.37 \text{ dB } \mu \text{ V/m}) + (-18.2 \text{ dB})$, the corresponding frequency is 36.208MHz.



Note: The test data in the graph includes two polarizations: horizontal and vertical




BUREAU
VERITAS

Test Report No.: PSU-NQN2505120312EM01

TEST VOLTAGE	Input 240 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	22.2deg. C, 40.3%RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Jace Hu		


Full Spectrum



Radiated emission (1GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum





**BUREAU
VERITAS** Test Report No.: **PSU-NQN2505120312EM01**

Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.



Test Report No.: PSU-NQN2505120312EM01

3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---