




11.Install the large seat, first place one side of the large seat into the slot of the right seat, and the other side is too high, and then lower it into the slot of the rear seat after pushing.

12.Install the small seat, insert the small seat into the right seat slot, and put it down.

13.Install the roof of the sauna,stick the top slot into the front and back left and right pieces, pay attention to the connection line should pass through the top line slot.Put the top back on.



14.To install the handle of the sauna door, first remove the handle from the top inner power box, and then remove the screw, from the door to the outside, pay attention to put the round plastic pad into the glass hole, the screw tip comes out a little, and finally align the screw hole of the outer handle, and tighten the screw.



15.Connect the connecting wires on the top , power test, pay attention to the power supply voltage between 110V~130V.

### 3. Installation Notes

- 3.1 Tightly fasten all room plate fasteners during installation and be sure the plug under the seat plate is installed correctly.
- 3.2 The product must be placed away from heat sources and moisture, and at least 20 cm away from walls or other objects.
- 3.3 A three-hole socket with a reliable grounding terminal must be used to plug in the device.
- 3.4 The power supply voltage used must be consistent with the voltage value indicated on the product nameplate.
- 3.5 Don't let the power cord be crushed under the room base or other heavy objects, and do not forcibly pull or squeeze the power cord.

## Application Method of Product

### 1. Instructions

- 1.1 Preheating
  - 1.1.1 Close the air hole on the top of the product.
  - 1.1.2 Start operation by pushing the power button on the control panel.
  - 1.1.3 Press TEMP adjustment button to set temperature, temperature can be set up to 40-50℃.
  - 1.1.4 Press the time adjustment button to set the required time (about 20-30 min) and enter the preheating state. After about 20 min, the room reaches the set temperature and keeps constant automatically.
  - 1.1.5 Please don't open the product door frequently.
  - 1.1.6 After the temperature is constant, change the set temperature and open the product door temporarily to accelerate cooling while reducing the internal temperature of product.
- 1.2 Timing

After preheating to the set temperature, adjust the timing switch to adjust to the preset time; Close the product door after entering.
- 1.3 Finish using. Press the power switch to turn off the power supply.

### 2. Precautions During Use

- 2.1 When using the product, please check whether the power supply meets the requirement (whether there is a grounding device).
- 2.2 Please don't take clothes, shoes, metal jewelry, watches and other items into the product.
- 2.3 Don't put combustibles such as a lighter, liquified gas, gasoline and alcohol and corrosive products such as strong acid and alkaline in the product.
- 2.4 Please don't stretch fingers into the heating plate's protective cover in the hot product.
- 2.5 Don't smoke in the product or bring any fire.
- 2.6 The product may not be made so hot during use in wintertime or cold weather or low indoor temperature (lower than 10℃). To ensure the internal temperature of the product, please keep the indoor temperature at about 20℃.
- 2.7 In principle, don't use the product immediately after a meal, but actually one hour after the meal.
- 2.8 In principle, don't take a shower immediately after using the product, but two hours after using.
- 2.9 When using the product, please drink more warm water to supplement the water lost during perspiration.
- 2.10 Stop using if it is uncomfortable when using the product.
- 2.11 Please wipe sweat after using, keep warm to avoid catching a cold.
- 2.12 Don't remove the parts such as a control panel and heating plate arbitrarily.
- 2.13 It is suggested that the product shall not be used continuously for more than 2 hours.

### 3. Power Safety

- 3.1 The power supply and power circuit must be provided with reliable grounding during use; the power cord is equipped with a reliable grounding wire to avoid excessive use of product producing a large amount of water vapor and causing electrostatic induction, voltage increase, short circuit, smoking, tripping and other phenomena.
- 3.2 Please don't use the power supply beyond the national standard voltage (e.g. 220V for China, 240V for Malaysia and 120V for America) to avoid fire and electric shock.
- 3.3 Do not work on, curl, or damage the power cord to avoid sparking and electric shock.
- 3.4 Make sure that there is no water or debris in the plug or in the gap to avoid electric shock or other malfunctions.
- 3.5 When plugging in or unplugging the power cord, please hold the head of the plug and ensure your hands are dry to avoid the risk of electric shock.

- 3.6 Families with pets should pay attention to prevent the pets from biting the power cord or urinating on the plug, which may cause fire or other accidents. When going out, be sure to unplug the device and place the product in a place beyond reach of pets.
- 3.7 Replacement of the power cord other than by professionals is strictly prohibited. Please contact professional maintenance service or electricians for replacement or maintenance.

#### 4. Unsuitable Users

The following groups are strictly prohibited from using the product:

- 4.1 Patients with diabetic foot, severe cardiovascular and cerebrovascular disease.
- 4.2 Patients with cancer in the process of radiotherapy and chemotherapy.
- 4.3 Infants and young children, pregnant women, and menstruating women.
- 4.4 Patients with glaucoma, cataract and bleeding tendencies.
- 4.5 Patients with active tuberculosis, severe arteriosclerosis, malignant tumor, and blood coagulation disorders.
- 4.6 Patients wearing pacemakers, or with steel plates or other metal inside the body.
- 4.7 Patients with burns and fractures.
- 4.8 People with electromagnetic sensitivity.
- 4.9 People with a history of cerebral infarction or myocardial infarction.
- 4.10 People with the lower than normal blood platelets.
- 4.11 People requiring frequent infusions within 2-5 years owing to cardiovascular and cerebrovascular diseases or easily damaged blood vessels.
- 4.12 People drinking a lot of alcohol or taking sleeping pills within the last 24 hours.
- 4.13 Patients with mental disorders, patients who can not take care of themselves, have no self-awareness, and have no independent behavioral ability.

✂ If you are not physically healthy, please use this device under the guidance of a professional!

## Product Cleaning and Maintenance

### 1. Cleaning Method of Product

- 1.1 Open the product door and remove the dust, hair and small sundries in the room with a duster or soft hair brush; wipe the whole room, seat and frame feet with a dry towel that has strong water absorption, discharge the moisture in the room and disinfect and sterilize. Power cords should be routed so as not to be stepped on or pinched by any object that may be resting on them.
- 1.2 Enable the machine to run idle at least once a week (30 min each time), so as to keep the dryness of the inner room and reduce the electrostatic induction.
- 1.3 If the room is frequently used, dehumidify it as stated above after each use. A thorough cleaning is also required after each day of use.
- 1.4 If the room is not used or you plan to be away for long periods, ensure that the power is unplugged to avoid potential safety risks.
- Please clean after the product is powered off.
- Please maintain the product when the temperature of the inner room is reduced to the indoor temperature.

### 2. Precautions for Product Maintenance

- 2.1 Overall movement
  - 2.1.1 Pull out the power plug and arrange the power line.
  - 2.1.2 Close and fix the room door.
  - 2.1.3 When moving the product, please lift the base of the room body rather than push the vertical plate of the room forcibly.
  - 2.1.4 Handle with care during movement to avoid room damage.
- 2.2 Equipment cleaning
  - 2.2.1 When wiping the room wall and protective cover, please avoid touching the frequency spectrum plate.
  - 2.2.2 Don't wipe the product with a chemical cleaner.
  - 2.2.3 Don't wash and sprinkle the interior and exterior of the product or wipe the control panel and knob with alcohol or other solvent.
  - 2.2.4 Don't dismount, repair and transform the product on its own; if it is necessary to change the controller, please operate when the product is powered off.
  - 2.2.5 Don't use the product as storage space.

# Specifications

## Technical Data

This product is designed and manufactured according to the safety requirements of relevant standards.

Technical Data

Type: HBU001C

## Working Conditions

Ambient temperature: -5°C ~ +40°C

Relative humidity: ≤75%

Rated power: 50-60Hz

☐ AC100V

☐ AC110V

☐ AC120V

☐ AC220V

☐ AC230V

☐ AC240V

Data:

Type	Rated power	Overall dimension
HBU001C	1980W	1200*1200*1920mm

## Note

- Improvements and changes to the data may be made without further notice.
- Damaged parts or expired components should be disposed of according to the regulations for disposal of general electrical waste.
- In case of any problems, please contact the local dealer or manufacturer.

# After-sales Service Guide

## 1.Free warranty period of product:

12 months or accumulated use of 2000 hours

The free warranty period starts from the date of receipt. Users can enjoy 12 months of free warranty and life-long paid maintenance (during the free warranty period, if the accumulated use time reaches 2000 hours, then the accumulated use time shall prevail).

## 2. The following conditions are excluded from the scope of the warranty:

- 2.1 Failure caused by force majeure factors (such as war, earthquake, flooding, mudslide, typhoon, lightning, etc.), improper use/maintenance, abnormal operation and modification, or other accidents.
- 2.2 Failure to provide the warranty card and proof of purchase, and product damage caused by disassembly without consent of our technical service personnel.
- 2.3 After the warranty period expires, the Company will provide lifetime paid maintenance and will only charge the maintenance costs.

## 3. Maintenance Method

- 3.1Warranty service: Within the free warranty period, in case of a malfunction caused by the product itself, customers can get in touch with our service staff to help you solve problems. Meanwhile, the detailed reasons you should provide so that we can better to assist you in dealing with your issues. If needed, we will send the relevant replacements for troubleshooting. Please feel free to contact us for any issues it may cause before or after your purchase through our website. We are here glad to serve you all the time! (sincereservice@hotmail.com)

**FCC Warning:**

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

**Caution:** Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.



*Share the warmth with family*