

TEST REPORT

FCC ID. :	2BQAD-SNR001	
Test Report No..... :	TCT250625E035	
Date of issue..... :	Jul. 14, 2025	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	WuLu Networks Pty Ltd	
Address..... :	135 Coal Point Road, Coal Point, NSW, 2283 Austria	
Manufacturer's name ... :	WuLu Networks Pty Ltd	
Address..... :	135 Coal Point Road, Coal Point, NSW, 2283 Austria	
Standard(s)	FCC CFR Title 47 Part 15 Subpart C Section 15.247 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10:2020	
Product Name..... :	WLNW-AP1 Router	
Trade Mark	N/A	
Model/Type reference..... :	S-NR001	
Rating(s)..... :	Adapter Information: MODEL: BS12A-1201000US Input: AC 100-240V, 50-60Hz, 0.4A Max Output: DC 12V, 1000mA	
Date of receipt of test item	Jun. 25, 2025	
Date (s) of performance of test..... :	Jun. 25, 2025 ~ Jul. 14, 2025	
Tested by (+signature) ... :	Rleo LIU	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Operation Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units.....	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
5. Measurement Uncertainty	8
6. Test Results and Measurement Data	9
6.1. Antenna requirement	9
6.2. Conducted Emission.....	10
6.3. Maximum Conducted (Peak) Output Power	14
6.4. Emission Bandwidth	16
6.5. Power Spectral Density.....	17
6.6. Conducted Band Edge and Spurious Emission Measurement	19
6.7. Radiated Spurious Emission Measurement.....	21
Appendix A: Test Result of Conducted Test	
Appendix B: Photographs of Test Setup	
Appendix C: Photographs of EUT	

1. General Product Information

1.1. EUT description

Product Name.....:	WLNW-AP1 Router
Model/Type reference.....:	S-NR001
Sample Number.....:	TCT250625E035-0101
Operation Frequency	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20)) 2422MHz~2452MHz (802.11n(HT40))
Channel Separation	5MHz
Number of Channel	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Modulation Technology	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n: Orthogonal Frequency Division Multiplexing(OFDM)
Data speed	802.11b: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps 802.11g: 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps 802.11n: Up to 150Mbps
Antenna Type.....:	External Antenna
Antenna Gain.....:	Antenna 0: 4.71dBi Antenna 1: 4.71dBi
Rating(s).....:	Adapter Information: MODEL: BS12A-1201000US Input: AC 100-240V, 50-60Hz, 0.4A Max Output: DC 12V, 1000mA

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Operation Frequency

For 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	--	--

For 802.11n (HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
--	--	4	2427MHz	7	2442MHz	--	--
--	--	5	2432MHz	8	2447MHz	--	--
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

802.11b/802.11g/802.11n (HT20)

Channel	Frequency
The lowest channel	2412MHz
The middle channel	2437MHz
The Highest channel	2462MHz

802.11n (HT40)

Channel	Frequency
The lowest channel	2422MHz
The middle channel	2437MHz
The Highest channel	2452MHz

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247(b)(4)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3)	PASS
6dB Emission Bandwidth	§15.247 (a)(2)	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d)	PASS
Spurious Emission	§15.205/§15.209	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	22.8 °C	22.8 °C
Humidity:	49 % RH	51 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Software:		
Software Information:	MT7628 QA	
Power Level:	802.11b: 1E 802.11g: 1B 802.11n(HT20): 1B 802.11n(HT40): 20/20/19	
Test Mode:		
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max duty cycle	
The sample was placed 0.8m & 1.5m for the measurement below & above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.		

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps
802.11n(HT40)	13.5Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

5. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	6dB Emission Bandwidth	± 57.75 KHz
5	Power Spectral Density	± 1.46 dB
6	Duty Cycle	± 0.62 dB
7	All emissions, radiated(<1 GHz)	± 4.56 dB
8	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
9	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:

FCC Part15 C Section 15.203 /15.247(b)(4)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b)(4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

E.U.T Antenna:

The WIFI antennas are External antennas, and the best case gains of the both antennas are 4.71dBi.



6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2020														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm E.U.T AC power 80cm LISN Filter AC power EMI Receiver Test table/Insulation plane Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.														
Test Result:	PASS														


6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025	Jun. 25, 2026
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 21, 2025	Jan. 20, 2026
Attenuator	N/A	10dB	164080	Jun. 26, 2025	Jun. 25, 2026
Line-5	TCT	CE-05	/	Jun. 26, 2025	Jun. 25, 2026
EMI Test Software	EZ_EMG	EMEC-3A1	1.1.4.2	/	/

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1539	39.68	9.96	49.64	65.79	-16.15	QP	
2		0.1539	29.74	9.96	39.70	55.79	-16.09	AVG	
3		0.4580	31.17	9.91	41.08	56.73	-15.65	QP	
4		0.4580	23.42	9.91	33.33	46.73	-13.40	AVG	
5		0.8219	21.55	9.92	31.47	56.00	-24.53	QP	
6		0.8219	14.13	9.92	24.05	46.00	-21.95	AVG	
7		3.1579	17.72	10.08	27.80	56.00	-28.20	QP	
8		3.1579	6.22	10.08	16.30	46.00	-29.70	AVG	
9		16.2300	36.14	10.48	46.62	60.00	-13.38	QP	
10	*	16.2300	30.91	10.48	41.39	50.00	-8.61	AVG	
11		26.4860	30.96	10.81	41.77	60.00	-18.23	QP	
12		26.4860	26.38	10.81	37.19	50.00	-12.81	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: AC 120 V/60 Hz

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	38.89	9.94	48.83	65.79	-16.96	QP	
2		0.1539	18.63	9.94	28.57	55.79	-27.22	AVG	
3		0.4580	28.24	9.93	38.17	56.73	-18.56	QP	
4		0.4580	21.64	9.93	31.57	46.73	-15.16	AVG	
5		0.8259	20.89	9.96	30.85	56.00	-25.15	QP	
6		0.8259	11.18	9.96	21.14	46.00	-24.86	AVG	
7		2.3340	16.60	10.04	26.64	56.00	-29.36	QP	
8		2.3340	6.50	10.04	16.54	46.00	-29.46	AVG	
9		4.5658	15.30	10.14	25.44	56.00	-30.56	QP	
10		4.5658	2.08	10.14	12.22	46.00	-33.78	AVG	
11		16.2300	36.14	10.52	46.66	60.00	-13.34	QP	
12	*	16.2300	29.20	10.52	39.72	50.00	-10.28	AVG	

Note:

1. Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. = Quasi-Peak

AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (Lowest channel and 802.11b) transmit with antenna 0 was submitted only.

6.3. Maximum Conducted (Peak) Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB 558074 D01 v05r02, KDB662911 D01 Multiple Transmitter Output v02r01
Limit:	30dBm
Test Setup:	 The diagram illustrates the test setup. On the left is a green rectangular box labeled 'Power meter'. A black line representing an RF cable connects it to a yellow rectangular box on the right labeled 'EUT'.
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Measure the Peak output power and record the results in the test report.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Power Sensor	Agilent	8184A	MY41096530	Jun. 26, 2024	Jun. 25, 2026
Power Meter	Agilent	E4418B	MY45100357	Jun. 26, 2024	Jun. 25, 2026

6.3.3. Test Data

Configuration IEEE 802.11b/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Peak) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	14.28	13.65	30	PASS
Middle	14.19	13.93	30	PASS
Highest	14.08	13.97	30	PASS

Configuration IEEE 802.11g/ Antenna 0+Antenna 1				
Test channel	Maximum Conducted (Peak) Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	11.73	11.39	30	PASS
Middle	11.75	11.30	30	PASS
Highest	12.04	11.31	30	PASS

Configuration IEEE 802.11n(HT20)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Peak) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	11.53	11.04	14.30	30	PASS
Middle	11.56	11.06	14.33	30	PASS
Highest	12.03	11.19	14.64	30	PASS

Configuration IEEE 802.11n(HT40)/ Antenna 0+Antenna 1					
Test channel	Maximum Conducted (Peak) Output Power (dBm)			Limit (dBm)	Result
	Antenna 0	Antenna 1	Total		
Lowest	10.69	10.24	13.48	30	PASS
Middle	10.63	10.16	13.41	30	PASS
Highest	10.32	9.79	13.07	30	PASS

Note:

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

Because $N_{ANT}=2$, so Array Gain = 0, Directional gain = $G_{ANT} + \text{Array Gain} = 4.71\text{dBi} < 6\text{dBi}$, power limit = 30dBm.

6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	FCC KDB 558074 D01 15.247 Meas Guidance v05r02
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set to the maximum power setting and enable the EUT transmit continuously. 2. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 3. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFtest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	FCC KDB 558074 D01 15.247 Meas Guidance v05r02
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. Set the span to at least 1.5 times the OBW. 4. Detector = Peak, Sweep time = auto couple. 5. Trace mode =max hold. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFTest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026

6.5.3. Test data

Configuration IEEE 802.11b/ Antenna 0, Antenna 1				
Test channel	Peak Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-7.73	4.79	6.28	PASS
Middle	-7.66	-7.18	6.28	PASS
Highest	-8.75	1.99	6.28	PASS

Configuration IEEE 802.11g/ Antenna 0, Antenna 1				
Test channel	Peak Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-11.71	-12.41	6.28	PASS
Middle	-11.70	-11.61	6.28	PASS
Highest	-10.48	-11.35	6.28	PASS

Configuration IEEE 802.11n(HT20)/ Antenna 0, Antenna 1					
Test channel	Peak Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-11.78	-12.30	-9.02	6.28	PASS
Middle	-11.23	-10.56	-7.87	6.28	PASS
Highest	-11.19	-10.79	-7.98	6.28	PASS

Configuration IEEE 802.11n(HT40)/ Antenna 0, Antenna 1					
Test channel	Peak Power Spectral Density (dBm/3kHz)			Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1	Total		
Lowest	-14.85	-15.04	-11.93	6.28	PASS
Middle	-13.96	-14.73	-11.32	6.28	PASS
Highest	-13.96	-14.72	-11.31	6.28	PASS

Note:

$G_{ANT} = 4.71\text{dBi}$, Array Gain= $10\log(N_{ANT}) = 3.01\text{dBi}$

Directional Gain= $G_{ANT} + \text{Array Gain} = 7.72\text{dBi} > 6\text{dBi}$, So limit= $8 - (7.72 - 6) = 6.28\text{dBm/3kHz}$

Refer to Appendix A: Test Result of Conducted Test

6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	FCC KDB 558074 D01 15.247 Meas Guidance v05r02
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 The diagram illustrates the test setup. On the left is a green Spectrum Analyzer with a blue screen. A black RF cable connects its right side to a yellow rectangular box on the right, labeled 'EUT' (Equipment Under Test).
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS


6.6.2. Test Instruments

Equipment	Manufacturer	Model No.	Serial Number	Date of Cal.	Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025	Jun. 25, 2026
Power detector box	MWRFtest	MW100-RFCB	MW210531TCT	Jan. 21, 2025	Jan. 20, 2026


6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10:2020			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Operation mode:	Transmitting mode with modulation			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	120KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:	Remark			
	Quasi-peak Value			
	Quasi-peak Value			
	Quasi-peak Value			
	Peak Value			
	Average Value			
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	
	0.009-0.490	2400/F(KHz)	300	
	0.490-1.705	24000/F(KHz)	30	
	1.705-30	30	30	
Test setup:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz	500	3	Average
		5000	3	Peak
	For radiated emissions below 30MHz			
				



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:

The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.

For the radiated emission test above 1GHz:

Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which

	maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 5. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test results:	PASS


6.7.2. Test Instruments

Radiated Emission Test Site (966)					
Equipment	Manufacturer	Model	Serial Number	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCI7	100529	Jan. 21, 2025	Jan. 20, 2026
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025	Jun. 25, 2026
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 21, 2025	Jan. 20, 2026
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025	Jun. 25, 2026
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025	Jun. 25, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 26, 2025	Jun. 25, 2026
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 26, 2025	Jun. 25, 2026
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 23, 2025	Jan. 22, 2026
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025	Jun. 25, 2026
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025	Jun. 25, 2026
Antenna Mast	Keleto	RE-AM	/	/	/
EMI Test Software	EZ EMC	FA-03A2 RE+	1.1.4.2	/	/

6.7.3. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber2

Polarization: **Horizontal**


Temperature: 22.8(C) Humidity: 51 %

Limit: FCC Part 15C RE_3m

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	32.5197	39.80	-19.42	20.38	40.00	-19.62	QP	P	
2	68.1512	43.55	-20.10	23.45	40.00	-16.55	QP	P	
3	102.0013	50.57	-21.09	29.48	43.50	-14.02	QP	P	
4	139.3610	40.76	-18.01	22.75	43.50	-20.75	QP	P	
5 *	246.8147	54.37	-19.61	34.76	46.00	-11.24	QP	P	
6	455.9057	35.54	-13.41	22.13	46.00	-23.87	QP	P	

Vertical:



Site 3m Anechoic Chamber2

Polarization: **Vertical**

Temperature: 22.8(C)

Humidity: 51 %

Limit: FCC Part 15C RE_3m

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	32.5197	56.23	-19.42	36.81	40.00	-3.19	QP	P	
2 !	40.2754	54.87	-18.43	36.44	40.00	-3.56	QP	P	
3 !	50.4089	54.33	-18.81	35.52	40.00	-4.48	QP	P	
4	81.2116	54.06	-22.40	31.66	40.00	-8.34	QP	P	
5 !	108.6470	59.94	-20.56	39.38	43.50	-4.12	QP	P	
6	157.5586	54.32	-17.04	37.28	43.50	-6.22	QP	P	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode (Lowest channel and 802.11b) transmit with antenna 0 was submitted only.

3. Freq. = Emission frequency in MHz

Measurement (dBuV/m) = Reading level (dBuV) + Corr. Factor (dB)

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Measurement (dBuV/m) – Limits (dBuV/m)

* is meaning the worst frequency has been tested in the test frequency range.

Test Result of Radiated Spurious at Band edges

Lowest channel 2412:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 24.3(°C)

Humidity: 52 %

Limit: FCC part 15.247 bandedge(peak)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2390.000	60.08	-16.26	43.82	74.00	-30.18	peak	P	
2 *	2390.000	48.37	-16.26	32.11	54.00	-21.89	AVG	P	

Vertical:



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 24.3(°C)

Humidity: 52 %

Limit: FCC part 15.247 bandedge(peak)


Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2390.000	83.98	-16.26	67.72	74.00	-6.28	peak	P	
2 *	2390.000	67.29	-16.26	51.03	54.00	-2.97	AVG	P	

Note: Measurements were conducted in all two channels (high, low) and all modulation (802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode 802.11n (HT20)) was submitted only.

Highest channel 2462:

Horizontal:



Site: 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 24.3(°C)


Humidity: 52 %

Limit: FCC part 15.247 bandedge(peak)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2483.500	68.85	-15.91	52.94	74.00	-21.06	peak	P	
2 *	2483.500	60.83	-15.91	44.92	54.00	-9.08	AVG	P	

Vertical:



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 24.3(°C)

Humidity: 52 %

Limit: FCC part 15.247 bandedge(peak)

Power: AC 120 V/60 Hz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	2483.500	78.45	-15.91	62.54	74.00	-11.46	peak	P	
2 *	2483.500	68.67	-15.91	52.76	54.00	-1.24	AVG	P	

Note:

1. Peak Final Emission Level=Peak Reading + Correction Factor;
2. Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
3. Measurements were conducted in all modulation(802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)), and the worst case Mode 802.11n(HT20)) was submitted only.

Above 1GHz

Modulation Type: 802.11b

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	54.56	---	-9.48	45.08	---	74	54	-8.92
7236	H	45.01	---	-1.34	43.67	---	74	54	-10.33
---	H	---	---	---	---	---	---	---	---
4824	V	54.69	---	-9.48	45.21	---	74	54	-8.79
7236	V	46.11	---	-1.34	44.77	---	74	54	-9.23
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	55.36	---	-9.37	45.99	---	74	54	-8.01
7311	H	46.81	---	-1.17	45.64	---	74	54	-8.36
---	H	---	---	---	---	---	---	---	---
4874	V	53.20	---	-9.37	43.83	---	74	54	-10.17
7311	V	46.61	---	-1.17	45.44	---	74	54	-8.56
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	53.92	---	-9.26	44.66	---	74	54	-9.34
7386	H	45.33	---	-1.01	44.32	---	74	54	-9.68
---	H	---	---	---	---	---	---	---	---
4924	V	55.39	---	-9.26	46.13	---	74	54	-7.87
7386	V	46.22	---	-1.01	45.21	---	74	54	-8.79
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11g

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	55.94	---	-9.48	46.46	---	74	54	-7.54
7236	H	46.50	---	-1.34	45.16	---	74	54	-8.84
---	H	---	---	---	---	---	---	---	---
4824	V	55.33	---	-9.48	45.85	---	74	54	-8.15
7236	V	47.98	---	-1.34	46.64	---	74	54	-7.36
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	54.78	---	-9.37	45.41	---	74	54	-8.59
7311	H	47.33	---	-1.17	46.16	---	74	54	-7.84
---	H	---	---	---	---	---	---	---	---
4874	V	54.50	---	-9.37	45.13	---	74	54	-8.87
7311	V	45.01	---	-1.17	43.84	---	74	54	-10.16
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	53.31	---	-9.26	44.05	---	74	54	-9.95
7386	H	46.55	---	-1.01	45.54	---	74	54	-8.46
---	H	---	---	---	---	---	---	---	---
4924	V	55.74	---	-9.26	46.48	---	74	54	-7.52
7386	V	45.20	---	-1.01	44.19	---	74	54	-9.81
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11n (HT20)

Low channel: 2412 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4824	H	54.41	---	-9.48	44.93	---	74	54	-9.07
7236	H	46.33	---	-1.34	44.99	---	74	54	-9.01
---	H	---	---	---	---	---	---	---	---
4824	V	54.96	---	-9.48	45.48	---	74	54	-8.52
7236	V	46.57	---	-1.34	45.23	---	74	54	-8.77
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	54.11	---	-9.37	44.74	---	74	54	-9.26
7311	H	46.66	---	-1.17	45.49	---	74	54	-8.51
---	H	---	---	---	---	---	---	---	---
4874	V	52.70	---	-9.37	43.33	---	74	54	-10.67
7311	V	46.26	---	-1.17	45.09	---	74	54	-8.91
---	V	---	---	---	---	---	---	---	---

High channel: 2462 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4924	H	54.78	---	-9.26	45.52	---	74	54	-8.48
7386	H	46.66	---	-1.01	45.65	---	74	54	-8.35
---	H	---	---	---	---	---	---	---	---
4924	V	53.90	---	-9.26	44.64	---	74	54	-9.36
7386	V	45.14	---	-1.01	44.13	---	74	54	-9.87
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Modulation Type: 802.11n (HT40)

Low channel: 2422 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4844	H	54.52	---	-9.43	45.09	---	74	54	-8.91
7266	H	45.14	---	-1.28	43.86	---	74	54	-10.14
---	H	---	---	---	---	---	---	---	---
4824	V	54.28	---	-9.43	44.85	---	74	54	-9.15
7236	V	45.66	---	-1.28	44.38	---	74	54	-9.62
---	V	---	---	---	---	---	---	---	---

Middle channel: 2437 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4874	H	54.33	---	-9.37	44.96	---	74	54	-9.04
7311	H	46.25	---	-1.17	45.08	---	74	54	-8.92
---	H	---	---	---	---	---	---	---	---
4874	V	54.44	---	-9.37	45.07	---	74	54	-8.93
7311	V	45.15	---	-1.17	43.98	---	74	54	-10.02
---	V	---	---	---	---	---	---	---	---

High channel: 2452 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
4904	H	54.23	---	-9.30	44.93	---	74	54	-9.07
7356	H	45.66	---	-1.08	44.58	---	74	54	-9.42
---	H	---	---	---	---	---	---	---	---
4904	V	55.47	---	-9.30	46.17	---	74	54	-7.83
7356	V	45.59	---	-1.08	44.51	---	74	54	-9.49
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 25GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. All the restriction bands are compliance with the limit of 15.209.

Appendix A: Test Result of Conducted Test


Antenna 0:

Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)
NVNT	b	2412	Ant0	99.9	0
NVNT	b	2437	Ant0	99.8	0
NVNT	b	2462	Ant0	99.9	0
NVNT	g	2412	Ant0	99.9	0
NVNT	g	2437	Ant0	98.9	0
NVNT	g	2462	Ant0	99.0	0
NVNT	n20	2412	Ant0	99.4	0
NVNT	n20	2437	Ant0	98.7	0
NVNT	n20	2462	Ant0	99.2	0
NVNT	n40	2422	Ant0	97.8	0.10
NVNT	n40	2437	Ant0	98.1	0
NVNT	n40	2452	Ant0	98.3	0

Test Graphs


Duty Cycle NVNT b 2412MHz Ant0




Duty Cycle NVNT b 2437MHz Ant0




Duty Cycle NVNT b 2462MHz Ant0




Duty Cycle NVNT g 2412MHz Ant0




Duty Cycle NVNT g 2437MHz Ant0




Duty Cycle NVNT g 2462MHz Ant0




Duty Cycle NVNT n20 2412MHz Ant0




Duty Cycle NVNT n20 2437MHz Ant0




Duty Cycle NVNT n20 2462MHz Ant0




Duty Cycle NVNT n40 2422MHz Ant0



Duty Cycle NVNT n40 2437MHz Ant0



Duty Cycle NVNT n40 2452MHz Ant0



Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant0	14.28	30	Pass
NVNT	b	2437	Ant0	14.19	30	Pass
NVNT	b	2462	Ant0	14.08	30	Pass
NVNT	g	2412	Ant0	11.73	30	Pass
NVNT	g	2437	Ant0	11.75	30	Pass
NVNT	g	2462	Ant0	12.04	30	Pass
NVNT	n20	2412	Ant0	11.53	30	Pass
NVNT	n20	2437	Ant0	11.56	30	Pass
NVNT	n20	2462	Ant0	12.03	30	Pass
NVNT	n40	2422	Ant0	10.69	30	Pass
NVNT	n40	2437	Ant0	10.63	30	Pass
NVNT	n40	2452	Ant0	10.32	30	Pass

-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant0	10.111	0.5	Pass
NVNT	b	2437	Ant0	10.128	0.5	Pass
NVNT	b	2462	Ant0	10.105	0.5	Pass
NVNT	g	2412	Ant0	15.693	0.5	Pass
NVNT	g	2437	Ant0	15.982	0.5	Pass
NVNT	g	2462	Ant0	15.927	0.5	Pass
NVNT	n20	2412	Ant0	16.909	0.5	Pass
NVNT	n20	2437	Ant0	16.926	0.5	Pass
NVNT	n20	2462	Ant0	15.957	0.5	Pass
NVNT	n40	2422	Ant0	34.800	0.5	Pass
NVNT	n40	2437	Ant0	35.066	0.5	Pass
NVNT	n40	2452	Ant0	35.079	0.5	Pass

Test Graphs


-6dB Bandwidth NVNT b 2412MHz Ant0




-6dB Bandwidth NVNT b 2437MHz Ant0




-6dB Bandwidth NVNT b 2462MHz Ant0




-6dB Bandwidth NVNT g 2412MHz Ant0




-6dB Bandwidth NVNT g 2437MHz Ant0




-6dB Bandwidth NVNT g 2462MHz Ant0





-6dB Bandwidth NVNT n20 2412MHz Ant0




-6dB Bandwidth NVNT n20 2437MHz Ant0






-6dB Bandwidth NVNT n40 2437MHz Ant0




-6dB Bandwidth NVNT n40 2452MHz Ant0




Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant0	-7.73	8	Pass
NVNT	b	2437	Ant0	-7.66	8	Pass
NVNT	b	2462	Ant0	-8.75	8	Pass
NVNT	g	2412	Ant0	-11.71	8	Pass
NVNT	g	2437	Ant0	-11.70	8	Pass
NVNT	g	2462	Ant0	-10.48	8	Pass
NVNT	n20	2412	Ant0	-11.78	8	Pass
NVNT	n20	2437	Ant0	-11.23	8	Pass
NVNT	n20	2462	Ant0	-11.19	8	Pass
NVNT	n40	2422	Ant0	-14.85	8	Pass
NVNT	n40	2437	Ant0	-13.96	8	Pass
NVNT	n40	2452	Ant0	-13.96	8	Pass


Test Graphs
PSD NVNT b 2412MHz Ant0




PSD NVNT b 2437MHz Ant0




PSD NVNT b 2462MHz Ant0




PSD NVNT g 2412MHz Ant0




PSD NVNT g 2437MHz Ant0




PSD NVNT g 2462MHz Ant0




PSD NVNT n20 2412MHz Ant0




PSD NVNT n20 2437MHz Ant0




PSD NVNT n20 2462MHz Ant0




PSD NVNT n40 2422MHz Ant0



PSD NVNT n40 2437MHz Ant0



PSD NVNT n40 2452MHz Ant0




Band Edge


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant0	-55.45	-20	Pass
NVNT	b	2462	Ant0	-58.51	-20	Pass
NVNT	g	2412	Ant0	-42.97	-20	Pass
NVNT	g	2462	Ant0	-45.87	-20	Pass
NVNT	n20	2412	Ant0	-39.77	-20	Pass
NVNT	n20	2462	Ant0	-43.59	-20	Pass
NVNT	n40	2422	Ant0	-28.74	-20	Pass
NVNT	n40	2452	Ant0	-33.11	-20	Pass

Test Graphs


Band Edge NVNT b 2412MHz Ant0 Ref




Band Edge NVNT b 2412MHz Ant0 Emission




Band Edge NVNT b 2462MHz Ant0 Ref




Band Edge NVNT b 2462MHz Ant0 Emission




Band Edge NVNT g 2412MHz Ant0 Ref



Band Edge NVNT g 2412MHz Ant0 Emission




Band Edge NVNT g 2462MHz Ant0 Ref




Band Edge NVNT g 2462MHz Ant0 Emission




Band Edge NVNT n20 2412MHz Ant0 Ref




Band Edge NVNT n20 2412MHz Ant0 Emission




Band Edge NVNT n20 2462MHz Ant0 Ref




Band Edge NVNT n20 2462MHz Ant0 Emission



Band Edge NVNT n40 2422MHz Ant0 Ref




Band Edge NVNT n40 2422MHz Ant0 Emission



Band Edge NVNT n40 2452MHz Ant0 Ref



Band Edge NVNT n40 2452MHz Ant0 Emission




Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant0	-41.21	-20	Pass
NVNT	b	2437	Ant0	-40.62	-20	Pass
NVNT	b	2462	Ant0	-41.65	-20	Pass
NVNT	g	2412	Ant0	-44.41	-20	Pass
NVNT	g	2437	Ant0	-45.33	-20	Pass
NVNT	g	2462	Ant0	-44.91	-20	Pass
NVNT	n20	2412	Ant0	-43.60	-20	Pass
NVNT	n20	2437	Ant0	-44.67	-20	Pass
NVNT	n20	2462	Ant0	-45.36	-20	Pass
NVNT	n40	2422	Ant0	-41.89	-20	Pass
NVNT	n40	2437	Ant0	-41.64	-20	Pass
NVNT	n40	2452	Ant0	-42.12	-20	Pass

Test Graphs


Tx. Spurious NVNT b 2412MHz Ant0 Ref




Tx. Spurious NVNT b 2412MHz Ant0 Emission




Tx. Spurious NVNT b 2437MHz Ant0 Ref




Tx. Spurious NVNT b 2437MHz Ant0 Emission




Tx. Spurious NVNT b 2462MHz Ant0 Ref




Tx. Spurious NVNT b 2462MHz Ant0 Emission




Tx. Spurious NVNT g 2412MHz Ant0 Ref




Tx. Spurious NVNT g 2412MHz Ant0 Emission




Tx. Spurious NVNT g 2437MHz Ant0 Ref




Tx. Spurious NVNT g 2437MHz Ant0 Emission





Tx. Spurious NVNT g 2462MHz Ant0 Ref




Tx. Spurious NVNT g 2462MHz Ant0 Emission







Tx. Spurious NVNT n20 2437MHz Ant0 Ref




Tx. Spurious NVNT n20 2437MHz Ant0 Emission




Tx. Spurious NVNT n20 2462MHz Ant0 Ref




Tx. Spurious NVNT n20 2462MHz Ant0 Emission




Tx. Spurious NVNT n40 2422MHz Ant0 Ref




Tx. Spurious NVNT n40 2422MHz Ant0 Emission




Tx. Spurious NVNT n40 2437MHz Ant0 Ref




Tx. Spurious NVNT n40 2437MHz Ant0 Emission



Tx. Spurious NVNT n40 2452MHz Ant0 Ref



Tx. Spurious NVNT n40 2452MHz Ant0 Emission




Antenna 1:

Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)
NVNT	b	2412	Ant1	100	0
NVNT	b	2437	Ant1	99.8	0
NVNT	b	2462	Ant1	100	0
NVNT	g	2412	Ant1	98.7	0
NVNT	g	2437	Ant1	99.3	0
NVNT	n20	2412	Ant1	98.8	0
NVNT	n20	2437	Ant1	96.2	0
NVNT	n20	2462	Ant1	98.7	0
NVNT	n40	2422	Ant1	97.9	0.09
NVNT	n40	2437	Ant1	98.1	0
NVNT	n40	2452	Ant1	98.1	0

Test Graphs


Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1




Duty Cycle NVNT b 2462MHz Ant1



Duty Cycle NVNT g 2412MHz Ant1



Duty Cycle NVNT g 2437MHz Ant1



Duty Cycle NVNT n20 2412MHz Ant1

