



13. Radiated Emission

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2026/03/28
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/03/28
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/11
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

13.2. Block diagram of test setup





13.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m

1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-07-15

Tested By: Nan Zhong

EUT: Receiver

Model Number: AIM-10

Test Mode: TX N20 5745MHz Mode


Power Supply: DC 12V

Condition: Temp:22.8°C;Humi:57.5%

Test Site: DDT 3# Chamber

File Path: d:\ts\2025 report date\Q25062523-2E\FCC BELOW 1G\20250715-183646_H

Memo: Number:S25062523-002




Final Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.585	46.66	11.28	3.78	30.62	40.00	9.38	QP	Horizontal
2	55.994	30.52	12.30	3.93	15.65	40.00	24.35	QP	Horizontal
3	110.617	34.18	11.98	4.28	19.33	43.50	24.17	QP	Horizontal
4	173.752	40.1	9.30	4.62	22.85	43.50	20.65	QP	Horizontal
5	307.904	46.19	13.47	5.25	33.51	46.00	12.49	QP	Horizontal
6	736.083	37.89	19.96	6.78	33.30	46.00	12.70	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-07-15**Tested By:** Nan Zhong**EUT:** Receiver**Model Number:** AIM-10**Test Mode:** TX N20 5745MHz Mode**Power Supply:** DC 12V**Condition:** Temp:22.8°C;Humi:57.5%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2025 report date\Q25062523-2E\FCC BELOW 1G\20250715-183709_V**Memo:** Number:S25062523-002

Final Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.632	44.22	11.31	3.78	28.21	40.00	11.79	QP	Vertical
2	58.154	40.16	12.72	3.95	25.73	40.00	14.27	QP	Vertical
3	172.538	39.95	9.42	4.61	22.81	43.50	20.69	QP	Vertical
4	468.290	37	15.83	5.88	27.23	46.00	18.77	QP	Vertical
5	707.741	31.05	19.32	6.71	25.62	46.00	20.38	QP	Vertical
6	950.102	31.63	22.68	7.33	31.31	46.00	14.69	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\1
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1345.100	58.01	24.78	3.18	-37.24	48.73	74.00	25.27	PK	Horizontal
2	3650.300	48.59	30.20	5.20	-39.60	44.39	74.00	29.61	PK	Horizontal
3	3946.100	45.69	31.11	5.29	-39.67	42.42	74.00	31.58	PK	Horizontal
4	7500.800	42.96	36.50	7.55	-40.55	46.46	74.00	27.54	PK	Horizontal
5	11334.300	40.62	39.23	8.62	-39.33	49.14	74.00	24.86	PK	Horizontal
6	12107.800	40.97	39.30	9.07	-39.98	49.36	74.00	24.64	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\2
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2354.900	53.03	27.12	4.30	-38.63	45.82	74.00	28.18	PK	Vertical
2	3767.600	49.24	30.57	5.24	-39.62	45.43	74.00	28.57	PK	Vertical
3	7516.100	44.99	36.47	7.56	-40.54	48.48	74.00	25.52	PK	Vertical
4	11500.900	42.53	39.20	8.72	-39.50	50.95	74.00	23.05	PK	Vertical
5	12291.400	42.03	39.30	9.15	-39.94	50.54	74.00	23.46	PK	Vertical
6	15869.900	39.17	38.16	10.18	-39.40	48.11	74.00	25.89	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\3
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1323.000	53.93	24.69	3.15	-37.21	44.56	74.00	29.44	PK	Horizontal
2	3650.300	48.51	30.20	5.20	-39.60	44.31	74.00	29.69	PK	Horizontal
3	4087.200	46.40	31.07	5.41	-39.67	43.21	74.00	30.79	PK	Horizontal
4	7567.100	42.74	36.43	7.59	-40.49	46.27	74.00	27.73	PK	Horizontal
5	11162.600	41.19	39.24	8.52	-39.16	49.79	74.00	24.21	PK	Horizontal
6	12296.500	41.28	39.30	9.16	-39.94	49.80	74.00	24.20	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\4
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1345.100	55.72	24.78	3.18	-37.24	46.44	74.00	27.56	PK	Vertical
2	3997.100	48.77	30.91	5.31	-39.68	45.31	74.00	28.69	PK	Vertical
3	7463.400	43.53	36.57	7.53	-40.58	47.05	74.00	26.95	PK	Vertical
4	11145.600	41.14	39.25	8.51	-39.15	49.75	74.00	24.25	PK	Vertical
5	11808.600	41.82	38.90	8.91	-39.81	49.82	74.00	24.18	PK	Vertical
6	15710.100	39.29	38.48	10.11	-39.40	48.48	74.00	25.52	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\5
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1321.300	54.09	24.69	3.15	-37.20	44.73	74.00	29.27	PK	Horizontal
2	3805.000	46.72	30.72	5.25	-39.63	43.06	74.00	30.94	PK	Horizontal
3	7339.300	42.81	36.82	7.45	-40.69	46.39	74.00	27.61	PK	Horizontal
4	11443.100	41.48	39.26	8.69	-39.44	49.99	74.00	24.01	PK	Horizontal
5	12339.000	41.47	39.30	9.18	-39.93	50.02	74.00	23.98	PK	Horizontal
6	15767.900	39.28	38.36	10.14	-39.40	48.38	74.00	25.62	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\6
Memo: Sample Number:S25031304-001



Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	1345.100	55.48	24.78	3.18	-37.24	46.20	74.00	27.80	PK	Vertical
2	3997.100	49.72	30.91	5.31	-39.68	46.26	74.00	27.74	PK	Vertical
3	7407.300	42.90	36.69	7.49	-40.63	46.45	74.00	27.55	PK	Vertical
4	11312.200	41.39	39.21	8.61	-39.31	49.90	74.00	24.10	PK	Vertical
5	12240.400	40.82	39.30	9.13	-39.95	49.30	74.00	24.70	PK	Vertical
6	15769.600	39.40	38.36	10.14	-39.40	48.50	74.00	25.50	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Band Edge Compliance

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2026/03/28
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/03/28
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/08/25
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/11
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

14.2. Block diagram of test setup



14.3. Limits

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

Same with Emissions in Restricted Frequency Bands except change investigated frequency range from 5.15-5.25 GHz, 5250-5350 GHz, 5470-5725 GHz, 5.725-5.85 GHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.


14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\15
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5724.370	43.86	33.75	5.66	-29.60	53.67	123.49	69.82	PK	Horizontal
2	5725.000	41.10	33.75	5.66	-29.60	50.91	125.30	74.39	PK	Horizontal
3	5743.693	84.23	33.86	5.67	-29.60	94.16	125.30	31.14	PK	Horizontal
4	5850.000	40.61	34.00	5.74	-29.60	50.75	125.30	74.55	PK	Horizontal
5	5862.548	43.31	34.03	5.75	-29.60	53.49	108.79	55.30	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\16
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5705.343	44.50	33.63	5.65	-29.60	54.18	106.80	52.62	PK	Vertical
2	5725.000	42.40	33.75	5.66	-29.60	52.21	125.30	73.09	PK	Vertical
3	5743.781	83.94	33.86	5.67	-29.60	93.87	125.30	31.43	PK	Vertical
4	5850.000	41.57	34.00	5.74	-29.60	51.71	125.30	73.59	PK	Vertical
5	5884.054	44.28	34.07	5.76	-29.60	54.51	98.58	44.07	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\17
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5680.887	44.27	33.52	5.63	-29.60	53.82	91.12	37.30	PK	Horizontal
2	5725.000	41.03	33.75	5.66	-29.60	50.84	125.30	74.46	PK	Horizontal
3	5783.636	81.71	34.10	5.70	-29.60	91.91	125.30	33.39	PK	Horizontal
4	5850.000	41.48	34.00	5.74	-29.60	51.62	125.30	73.68	PK	Horizontal
5	5882.520	43.11	34.07	5.76	-29.60	53.34	99.72	46.38	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\18
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5690.593	43.58	33.56	5.64	-29.60	53.18	98.32	45.14	PK	Vertical
2	5725.000	40.77	33.75	5.66	-29.60	50.58	125.30	74.72	PK	Vertical
3	5781.807	85.05	34.09	5.70	-29.60	95.24	125.30	30.06	PK	Vertical
4	5850.000	39.64	34.00	5.74	-29.60	49.78	125.30	75.52	PK	Vertical
5	5870.484	43.73	34.04	5.75	-29.60	53.92	106.56	52.64	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\13
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5693.808	45.45	33.58	5.64	-29.60	55.07	100.71	45.64	PK	Horizontal
2	5725.000	41.14	33.75	5.66	-29.60	50.95	125.30	74.35	PK	Horizontal
3	5823.313	80.98	34.11	5.72	-29.60	91.21	125.30	34.09	PK	Horizontal
4	5850.000	40.83	34.00	5.74	-29.60	50.97	125.30	74.33	PK	Horizontal
5	5890.780	43.25	34.08	5.77	-29.60	53.50	93.59	40.09	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX 11A 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\14
Memo: Sample Number:S25031304-001




Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5676.403	43.79	33.51	5.63	-29.60	53.33	87.79	34.46	PK	Vertical
2	5725.000	41.12	33.75	5.66	-29.60	50.93	125.30	74.37	PK	Vertical
3	5824.051	84.82	34.10	5.72	-29.60	95.04	125.30	30.26	PK	Vertical
4	5850.000	41.18	34.00	5.74	-29.60	51.32	125.30	73.98	PK	Vertical
5	5879.009	42.93	34.06	5.76	-29.60	53.15	102.33	49.18	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31**Tested By:** Nan Zhong**EUT:** Receiver**Model Number:** AIM-10**Test Mode:** TX N20 5745MHz Mode**Power Supply:** DC 12V**Condition:** Temp:24.1°C;Humi:49.4%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\9**Memo:** Sample Number:S25031304-001**Data List**


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5682.834	43.60	33.53	5.63	-29.60	53.16	92.56	39.40	PK	Horizontal
2	5725.000	41.96	33.75	5.66	-29.60	51.77	125.30	73.53	PK	Horizontal
3	5739.710	81.54	33.84	5.67	-29.60	91.45	125.30	33.85	PK	Horizontal
4	5850.000	39.99	34.00	5.74	-29.60	50.13	125.30	75.17	PK	Horizontal
5	5892.314	43.27	34.08	5.77	-29.60	53.52	92.45	38.93	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\10
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5679.088	44.13	33.52	5.63	-29.60	53.68	89.78	36.10	PK	Vertical
2	5725.000	42.36	33.75	5.66	-29.60	52.17	125.30	73.13	PK	Vertical
3	5745.817	83.54	33.87	5.67	-29.60	93.48	125.30	31.82	PK	Vertical
4	5850.000	40.74	34.00	5.74	-29.60	50.88	125.30	74.42	PK	Vertical
5	5864.879	43.09	34.03	5.75	-29.60	53.27	108.13	54.86	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\7
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5685.489	44.59	33.54	5.63	-29.60	54.16	94.53	40.37	PK	Horizontal
2	5725.000	40.96	33.75	5.66	-29.60	50.77	125.30	74.53	PK	Horizontal
3	5783.370	80.56	34.10	5.70	-29.60	90.76	125.30	34.54	PK	Horizontal
4	5850.000	40.69	34.00	5.74	-29.60	50.83	125.30	74.47	PK	Horizontal
5	5853.964	43.31	34.01	5.74	-29.60	53.46	113.89	60.43	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\8
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5693.425	43.98	33.57	5.64	-29.60	53.59	100.42	46.83	PK	Vertical
2	5725.000	40.55	33.75	5.66	-29.60	50.36	125.30	74.94	PK	Vertical
3	5788.267	85.33	34.13	5.70	-29.60	95.56	125.30	29.74	PK	Vertical
4	5850.000	39.95	34.00	5.74	-29.60	50.09	125.30	75.21	PK	Vertical
5	5896.798	43.15	34.09	5.77	-29.60	53.41	89.13	35.72	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\11
Memo: Sample Number:S25031304-001

**Data List**


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5717.497	44.15	33.70	5.65	-29.60	53.90	110.20	56.30	PK	Horizontal
2	5725.000	41.24	33.75	5.66	-29.60	51.05	125.30	74.25	PK	Horizontal
3	5822.517	80.85	34.11	5.72	-29.60	91.08	125.30	34.22	PK	Horizontal
4	5850.000	40.99	34.00	5.74	-29.60	51.13	125.30	74.17	PK	Horizontal
5	5865.528	43.29	34.03	5.75	-29.60	53.47	107.95	54.48	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\12
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5711.213	45.34	33.67	5.65	-29.60	55.06	108.44	53.38	PK	Vertical
2	5725.000	41.26	33.75	5.66	-29.60	51.07	125.30	74.23	PK	Vertical
3	5826.381	85.76	34.09	5.73	-29.60	95.98	125.30	29.32	PK	Vertical
4	5850.000	42.47	34.00	5.74	-29.60	52.61	125.30	72.69	PK	Vertical
5	5901.901	44.38	34.10	5.78	-29.60	54.66	85.34	30.68	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\21
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5709.561	44.49	33.66	5.65	-29.60	54.20	107.98	53.78	PK	Horizontal
2	5725.000	41.71	33.75	5.66	-29.60	51.52	125.30	73.78	PK	Horizontal
3	5745.699	82.32	33.87	5.67	-29.60	92.26	125.30	33.04	PK	Horizontal
4	5850.000	39.61	34.00	5.74	-29.60	49.75	125.30	75.55	PK	Horizontal
5	5874.024	43.23	34.05	5.76	-29.60	53.44	105.57	52.13	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC20 5745MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\22
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5704.871	44.06	33.63	5.65	-29.60	53.74	106.66	52.92	PK	Vertical
2	5725.000	42.77	33.75	5.66	-29.60	52.58	125.30	72.72	PK	Vertical
3	5746.023	83.22	33.88	5.67	-29.60	93.17	125.30	32.13	PK	Vertical
4	5850.000	40.20	34.00	5.74	-29.60	50.34	125.30	74.96	PK	Vertical
5	5877.652	43.89	34.06	5.76	-29.60	54.11	103.33	49.22	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\19
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5681.064	44.23	33.52	5.63	-29.60	53.78	91.25	37.47	PK	Horizontal
2	5725.000	40.63	33.75	5.66	-29.60	50.44	125.30	74.86	PK	Horizontal
3	5786.822	81.53	34.12	5.70	-29.60	91.75	125.30	33.55	PK	Horizontal
4	5850.000	40.41	34.00	5.74	-29.60	50.55	125.30	74.75	PK	Horizontal
5	5873.375	43.48	34.05	5.76	-29.60	53.69	105.76	52.07	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC20 5785MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\20
Memo: Sample Number:S25031304-001




Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5696.227	44.90	33.58	5.64	-29.60	54.52	102.50	47.98	PK	Vertical
2	5725.000	42.05	33.75	5.66	-29.60	51.86	125.30	73.44	PK	Vertical
3	5782.102	84.94	34.09	5.70	-29.60	95.13	125.30	30.17	PK	Vertical
4	5850.000	41.32	34.00	5.74	-29.60	51.46	125.30	73.84	PK	Vertical
5	5895.323	42.88	34.09	5.77	-29.60	53.14	90.22	37.08	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31**Tested By:** Nan Zhong**EUT:** Receiver**Model Number:** AIM-10**Test Mode:** TX AC20 5825MHz Mode**Power Supply:** DC 12V**Condition:** Temp:24.1°C;Humi:49.4%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\23**Memo:** Sample Number:S25031304-001**Data List**


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5723.249	43.65	33.74	5.66	-29.60	53.45	120.26	66.81	PK	Horizontal
2	5725.000	40.43	33.75	5.66	-29.60	50.24	125.30	75.06	PK	Horizontal
3	5827.060	81.46	34.09	5.73	-29.60	91.68	125.30	33.62	PK	Horizontal
4	5850.000	41.48	34.00	5.74	-29.60	51.62	125.30	73.68	PK	Horizontal
5	5900.633	44.12	34.10	5.77	-29.60	54.39	86.28	31.89	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC20 5825MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\24
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5723.574	44.30	33.74	5.66	-29.60	54.10	121.19	67.09	PK	Vertical
2	5725.000	40.98	33.75	5.66	-29.60	50.79	125.30	74.51	PK	Vertical
3	5822.930	86.02	34.11	5.72	-29.60	96.25	125.30	29.05	PK	Vertical
4	5850.000	44.23	34.00	5.74	-29.60	54.37	125.30	70.93	PK	Vertical
5	5917.566	43.98	34.14	5.79	-29.60	54.31	73.72	19.41	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N40 5755MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\33
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5720.004	49.60	33.72	5.66	-29.60	59.38	110.91	51.53	PK	Horizontal
2	5725.000	47.08	33.75	5.66	-29.60	56.89	125.30	68.41	PK	Horizontal
3	5758.826	79.23	33.95	5.68	-29.60	89.26	125.30	36.04	PK	Horizontal
4	5850.000	40.18	34.00	5.74	-29.60	50.32	125.30	74.98	PK	Horizontal
5	5887.328	43.28	34.07	5.77	-29.60	53.52	96.15	42.63	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N40 5755MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\34
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5723.308	52.22	33.74	5.66	-29.60	62.02	120.43	58.41	PK	Vertical
2	5725.000	50.00	33.75	5.66	-29.60	59.81	125.30	65.49	PK	Vertical
3	5757.528	83.17	33.95	5.68	-29.60	93.20	125.30	32.10	PK	Vertical
4	5850.000	40.01	34.00	5.74	-29.60	50.15	125.30	75.15	PK	Vertical
5	5907.890	43.28	34.12	5.78	-29.60	53.58	80.90	27.32	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N40 5795MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\31
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5699.708	44.83	33.60	5.64	-29.60	54.47	105.08	50.61	PK	Horizontal
2	5725.000	42.25	33.75	5.66	-29.60	52.06	125.30	73.24	PK	Horizontal
3	5791.807	79.05	34.15	5.70	-29.60	89.30	125.30	36.00	PK	Horizontal
4	5850.000	39.84	34.00	5.74	-29.60	49.98	125.30	75.32	PK	Horizontal
5	5894.025	43.55	34.09	5.77	-29.60	53.81	91.18	37.37	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX N40 5795MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\32
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5684.752	44.82	33.54	5.63	-29.60	54.39	93.99	39.60	PK	Vertical
2	5725.000	41.89	33.75	5.66	-29.60	51.70	125.30	73.60	PK	Vertical
3	5799.920	83.34	34.20	5.71	-29.60	93.65	125.30	31.65	PK	Vertical
4	5850.000	40.89	34.00	5.74	-29.60	51.03	125.30	74.27	PK	Vertical
5	5871.251	43.23	34.04	5.76	-29.60	53.43	106.35	52.92	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC40 5755MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\27
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5712.128	46.24	33.67	5.65	-29.60	55.96	108.70	52.74	PK	Horizontal
2	5725.000	47.67	33.75	5.66	-29.60	57.48	125.30	67.82	PK	Horizontal
3	5749.829	80.42	33.90	5.67	-29.60	90.39	125.30	34.91	PK	Horizontal
4	5850.000	39.37	34.00	5.74	-29.60	49.51	125.30	75.79	PK	Horizontal
5	5883.228	43.34	34.07	5.76	-29.60	53.57	99.20	45.63	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC40 5755MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\28
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5711.213	51.85	33.67	5.65	-29.60	61.57	108.44	46.87	PK	Vertical
2	5725.000	50.47	33.75	5.66	-29.60	60.28	125.30	65.02	PK	Vertical
3	5754.047	82.50	33.92	5.68	-29.60	92.50	125.30	32.80	PK	Vertical
4	5850.000	42.62	34.00	5.74	-29.60	52.76	125.30	72.54	PK	Vertical
5	5896.650	43.49	34.09	5.77	-29.60	53.75	89.24	35.49	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC40 5795MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\29
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5692.805	44.22	33.57	5.64	-29.60	53.83	99.96	46.13	PK	Horizontal
2	5725.000	42.21	33.75	5.66	-29.60	52.02	125.30	73.28	PK	Horizontal
3	5788.179	78.58	34.13	5.70	-29.60	88.81	125.30	36.49	PK	Horizontal
4	5850.000	40.37	34.00	5.74	-29.60	50.51	125.30	74.79	PK	Horizontal
5	5891.753	43.04	34.08	5.77	-29.60	53.29	92.87	39.58	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC40 5795MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\30
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5694.782	43.96	33.58	5.64	-29.60	53.58	101.43	47.85	PK	Vertical
2	5725.000	39.84	33.75	5.66	-29.60	49.65	125.30	75.65	PK	Vertical
3	5798.445	83.81	34.19	5.71	-29.60	94.11	125.30	31.19	PK	Vertical
4	5850.000	39.94	34.00	5.74	-29.60	50.08	125.30	75.22	PK	Vertical
5	5898.863	43.79	34.10	5.77	-29.60	54.06	87.59	33.53	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC80 5775MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\25
Memo: Sample Number:S25031304-001



Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5720.594	50.27	33.72	5.66	-29.60	60.05	112.61	52.56	PK	Horizontal
2	5725.000	47.00	33.75	5.66	-29.60	56.81	125.30	68.49	PK	Horizontal
3	5767.942	76.64	34.01	5.69	-29.60	86.74	125.30	38.56	PK	Horizontal
4	5850.000	45.51	34.00	5.74	-29.60	55.65	125.30	69.65	PK	Horizontal
5	5856.737	44.62	34.01	5.75	-29.60	54.78	110.41	55.63	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-03-31 **Tested By:** Nan Zhong
EUT: Receiver **Model Number:** AIM-10
Test Mode: TX AC80 5775MHz Mode **Power Supply:** DC 12V
Condition: Temp:24.1°C;Humi:49.4% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25031304-2E\FCC ABOVE1G 5G\26
Memo: Sample Number:S25031304-001



Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5720.476	52.79	33.72	5.66	-29.60	62.57	112.27	49.70	PK	Vertical
2	5725.000	48.11	33.75	5.66	-29.60	57.92	125.30	67.38	PK	Vertical
3	5771.511	81.03	34.03	5.69	-29.60	91.15	125.30	34.15	PK	Vertical
4	5850.000	47.43	34.00	5.74	-29.60	57.57	125.30	67.73	PK	Vertical
5	5857.474	48.39	34.01	5.75	-29.60	58.55	110.21	51.66	PK	Vertical

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15. Power Line Conducted Emissions

15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
/	/	/	/	/

15.2. Block diagram of test setup



15.3. Limits

Frequency	Quasi-Peak Level dB(uV)	Average Level dB(uV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

15.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

15.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

15.6. Test result

Not applicable. EUT is DC powered.

17. Photos of the EUT

Please refer to DDT-Q25062523-1E appendix I

-----End Report-----