

# FCC RF Exposure

EUT Description: Fieldy

Model No.: FL1B

FCC ID: 2BQG7-FL1B

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{(max power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

Where:

Result =  $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

| Frequency (MHz) | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power dBm/mW | Min test separation distance mm | Result | Limit | SAR Test Exclusion |
|-----------------|--------------------|---------------------|--------------------------|---------------------------------|--------|-------|--------------------|
| 2402            | -0.55              | -1.3 $\pm$ 1(-0.3)  | 0.933                    | 5                               | 0.289  | 3.0   | Pass               |

Note:

PK Output power = conducted power.

Conducted power see the test report HK2506093036-E, antenna gain=2dBi;

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.289 which is  $\leq 3$ , SAR testing is not required.

Note: Exclusion Thresholds Results =  $\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$

f(GHz) is the RF channel transmit frequency in GHz

Distance = 5mm