

TEST REPORT

Applicant: Xtra Technology LLC
Address: 3422 Old Capitol Trail, Suite 700, Wilmington, DE
19808-6124, USA
Equipment Type: XTRA EDGE
Model Name: XCAMC01
Brand Name: Xtra
FCC ID: 2BQH2-XCAMC01
Test Standard: FCC 47 CFR Part 2.1093
(refer to section 3.1)
Maximum SAR: Head wear(1 g@5mm): 1.13 W/kg
Body (1 g@5mm): 1.13 W/kg
Limbs (10 g@0mm): 1.44 W/kg
Sample Arrival Date: Jul. 10, 2025
Test Date: Jul. 15, 2025 - Jul. 16, 2025
Date of Issue: Aug. 01, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Guo Guangwei**Checked by:** Xu Rui**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Jul. 31, 2025</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Aug. 01, 2025</u>	<u>Head and updated to Head wear, Update data on the report homepage and chapters 3.3, 10, and 12, as well as the description of chapter 6.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Ancillary Equipment	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	8
3.3	Test Result Summary	9
3.4	Test Uncertainty	10
4	MEASUREMENT SYSTEM	11
4.1	Specific Absorption Rate (SAR) Definition	11
4.2	DASY SAR System	12
5	SYSTEM VERIFICATION	19
5.1	Purpose of System Check	19
5.2	System Check Setup	19
6	TEST POSITION CONFIGURATIONS	20

6.1	Head-wear&Body-wear Position Conditions	20
6.2	Hand-held Position Conditions	20
7	MEASUREMENT PROCEDURE	21
7.1	Measurement Process Diagram	21
7.2	SAR Scan General Requirement	22
7.3	Measurement Procedure	23
7.4	Area & Zoom Scan Procedure	23
8	CONDUCTED RF OUPUT POWER	24
9	TEST EXCLUSION CONSIDERATION	25
10	TEST RESULT	26
10.1	Bluetooth	26
10.2	WIFI 2.4GHz.....	27
10.3	WIFI 5GHz.....	28
11	SAR Measurement Variability	29
12	SAR Measurement Variability	30
12.1	Simultaneous Transmission Mode Consider	30
12.2	Sum SAR of Simultaneous Transmission	31
13	TEST EQUIPMENTS LIST	32
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	33
ANNEX B	SYSTEM CHECK RESULT	34
ANNEX C	TEST DATA.....	35
ANNEX D	EUT EXTERNAL PHOTOS	35
ANNEX E	SAR TEST SETUP PHOTOS.....	35
ANNEX F	CALIBRATION REPORT	35
ANNEX G	TUNE-UP PROCEDURE	35

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Xtra Technology LLC
Address	3422 Old Capitol Trail, Suite 700, Wilmington, DE 19808-6124, USA

2.2 Manufacturer Information

Manufacturer	Xtra Technology LLC
Address	3422 Old Capitol Trail, Suite 700, Wilmington, DE 19808-6124, USA

2.3 General Description for Equipment under Test (EUT)

EUT Name	XTRA EDGE
Model Name Under Test	XCAMC01
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V1.0.0
Software Version	01.00.00.00
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery 1	
	Brand Name	N/A
	Model No.	BC2501-1900-3.87
	Serial No.	N/A
	Capacity	1900mAh
	Rated Voltage	3.87V
	Max Charge Voltage	4.45V
Ancillary Equipment 2	Battery 2	
	Brand Name	N/A
	Model No.	ML414H IV01E
	Serial No.	N/A
	Capacity	1.0mAh
	Rated Voltage	3.0V
	Limit Charge Voltage	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n and 802.11ac
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WIFI, Bluetooth	
Frequency Range	802.11b/g	2412 ~ 2462 MHz
	802.11n(HT20/HT40)	2412 ~ 2462 MHz
	802.11a	5150 ~ 5250 MHz
		5725 ~ 5850 MHz
	802.11n(HT20/HT40)	5150 ~ 5250 MHz
		5725 ~ 5850 MHz
	802.11ac (VHT20/VHT40/VHT80)	5150 ~ 5250 MHz
		5725 ~ 5850 MHz
Antenna Type	Bluetooth	2402 ~ 2480 MHz
	WIFI	Metal Shrapnel Antenna
Antenna Type	Bluetooth	Metal Shrapnel Antenna
DTM	N/A	
Hotspot Function	N/A	
Power Reduction	N/A	
Exposure Category	General Population/Uncontrolled exposure	
Product Type	Portable Device	
EUT Type	☒ Production unit	☐ Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI/IEEE C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate(SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01
5	KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ ControlledExposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR Values

Equipment Class	Band	Maximum Scaled SAR (W/kg)			Maximum Report SAR (W/kg)		
		Head wear	Body	Limbs	Head wear	Body	Limbs
		(5mm)	(5mm)	(0mm)	(5mm)	(5mm)	(0mm)
		1g SAR	1g SAR	10g SAR	1g SAR	1g SAR	10g SAR
DTS	2.4G WIFI	0.72	0.72	1.44	1.13	1.13	1.44
NII	5.2G WIFI	1.13	1.13	0.58			
	5.8G WIFI	0.17	0.17	0.16			
DSS	Bluetooth	0.25	0.25	0.34			
Limit (W/kg)		1.60	1.60	4.00	1.60	1.60	4.00
Verdict		PASS					

3.3.2 Highest Simultaneous Transmission SAR Values

Equipment Class	Maximum Scaled SAR (W/kg)		
	Head wear 1g (5mm)	Body 1g (5mm)	Limbs 10g (0mm)
NII	1.38	1.38	0.92
DSS	1.38	1.38	0.92
Limit (W/Kg)	1.60	1.60	4.00
Verdict	Pass		

Note: The highest simultaneous SAR please refer section 12.2.

3.4 Test Uncertainty

According to KDB 865664 D01, When the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.13 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

The maximum 10 g SAR for the EUT in this report is 1.44 W/kg, which is lower than 3.75 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)

E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left head
- Right head
- Flat phantom

Photo of Phantom SN1859



Serial Number	Material	Length	Height
SN 1859 SAM	Vinylester, glass fiber reinforced	1000	500

4.2.6 Device Holder


The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA"s only. If necessary an additional support of polystyrene material is used. Larger DUT"s (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth**Body Liquid Depth**

The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS

According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head-wear&Body-wear Position Conditions


This DUT is a hand-held Sports Camera, it was tested in six different positions. It supports body wear and Head wear use, When in use, there will be a certain distance from the human body and head, So Head wear & Body SAR is tested SAR with 5mm

6.2 Hand-held Position Conditions

When SAR measurement is necessary for hand-held devices that do not transmit while at the head or torso, a flat phantom may be used. To assess this type of device, the device shall be placed directly against the flat phantom, for the sides of the device that are in contact with the hand for the intended use

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

- δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
- * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure


First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUPUT POWER

Please refer the document “BL-SZ2570508-AP.pdf”.

9 TEST EXCLUSION CONSIDERATION



Antenna	Support Bands
Ant.1	WiFi 2.4/5G; Bluetooth

10 TEST RESULT

10.1Bluetooth

Mode	Antenn a	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Head wear&Body														
DH5	Ant.1	Front Side	5	78	2480	-0.07	0.011	11.52	12.00	1.117	77.69	1.287	0.016	/
		Back Side	5	78	2480	0.04	0.006	11.52	12.00	1.117	77.69	1.287	0.009	/
		Left Edge	5	78	2480	-0.02	0.172	11.52	12.00	1.117	77.69	1.287	0.247	1#
		Right Edge	5	78	2480	0.17	0.003	11.52	12.00	1.117	77.69	1.287	0.004	/
		Top Edge	5	78	2480	0.09	0.062	11.52	12.00	1.117	77.69	1.287	0.089	/
		Bottom Edge	5	78	2480	-0.09	0.002	11.52	12.00	1.117	77.69	1.287	0.003	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

Mode	Antenn a	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs														
DH5	Ant.1	Front Side	0	78	2480	-0.02	0.016	11.52	12.00	1.117	77.69	1.287	0.023	/
		Back Side	0	78	2480	-0.17	0.008	11.52	12.00	1.117	77.69	1.287	0.012	/
		Left Edge	0	78	2480	0.05	0.238	11.52	12.00	1.117	77.69	1.287	0.342	2#
		Right Edge	0	78	2480	0.09	0.004	11.52	12.00	1.117	77.69	1.287	0.006	/
		Top Edge	0	78	2480	-0.01	0.078	11.52	12.00	1.117	77.69	1.287	0.112	/
		Bottom Edge	0	78	2480	0.14	0.003	11.52	12.00	1.117	77.69	1.287	0.004	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

10.2WIFI 2.4GHz

Mode	Antenn a	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Head wear&Body														
802.11 b	Ant.1	Front Side	5	6	2437	0.15	0.056	16.14	17.00	1.219	94.54	1.058	0.072	/
		Back Side	5	6	2437	-0.17	0.096	16.14	17.00	1.219	94.54	1.058	0.124	/
		Left Edge	5	6	2437	0.13	0.560	16.14	17.00	1.219	94.54	1.058	0.722	3#
		Right Edge	5	6	2437	-0.18	0.016	16.14	17.00	1.219	94.54	1.058	0.021	/
		Top Edge	5	6	2437	-0.03	0.269	16.14	17.00	1.219	94.54	1.058	0.347	/
		Bottom Edge	5	6	2437	-0.19	0.005	16.14	17.00	1.219	94.54	1.058	0.006	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

Mode	Antenn a	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs														
802.11 b	Ant.1	Front Side	0	6	2437	0.10	0.058	16.14	17.00	1.219	94.54	1.058	0.075	/
		Back Side	0	6	2437	0.04	0.035	16.14	17.00	1.219	94.54	1.058	0.045	/
		Left Edge	0	6	2437	-0.04	1.120	16.14	17.00	1.219	94.54	1.058	1.444	4#
		Right Edge	0	6	2437	-0.07	0.023	16.14	17.00	1.219	94.54	1.058	0.030	/
		Top Edge	0	6	2437	0.18	0.405	16.14	17.00	1.219	94.54	1.058	0.522	/
		Bottom Edge	0	6	2437	-0.10	0.011	16.14	17.00	1.219	94.54	1.058	0.014	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

10.3WIFI 5GHz

Fre. Band	Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Scaled SAR (W/kg)	Meas. No.
Head wear&Body															
5.2G	802.11 ac80	Ant.1	Front Side	5	42	5210	-0.01	0.042	14.71	15.00	1.069	69.26	1.444	0.065	/
			Back Side	5	42	5210	0.06	0.235	14.71	15.00	1.069	69.26	1.444	0.363	/
			Left Edge	5	42	5210	0.02	0.733	14.71	15.00	1.069	69.26	1.444	1.131	5#
			Right Edge	5	42	5210	0.18	0.013	14.71	15.00	1.069	69.26	1.444	0.020	/
			Top Edge	5	42	5210	0.14	0.335	14.71	15.00	1.069	69.26	1.444	0.517	/
			Bottom Edge	5	42	5210	0.16	0.006	14.71	15.00	1.069	69.26	1.444	0.009	/
5.8G	802.11 ac80	Ant.1	Front Side	5	155	5775	-0.06	0.006	12.14	12.50	1.086	69.26	1.444	0.009	/
			Back Side	5	155	5775	0.05	0.063	12.14	12.50	1.086	69.26	1.444	0.099	/
			Left Edge	5	155	5775	0.00	0.109	12.14	12.50	1.086	69.26	1.444	0.171	6#
			Right Edge	5	155	5775	-0.19	0.002	12.14	12.50	1.086	69.26	1.444	0.003	/
			Top Edge	5	155	5775	0.00	0.084	12.14	12.50	1.086	69.26	1.444	0.132	/
			Bottom Edge	5	155	5775	0.03	0.001	12.14	12.50	1.086	69.26	1.444	0.002	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

Fre. Band	Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Scaled SAR (W/kg)	Meas. No.
Limbs															
5.2G	802.11 ac80	Ant.1	Front Side	0	42	5210	0.00	0.035	14.71	15.00	1.069	69.26	1.444	0.054	/
			Back Side	0	42	5210	-0.16	0.064	14.71	15.00	1.069	69.26	1.444	0.099	/
			Left Edge	0	42	5210	-0.10	0.374	14.71	15.00	1.069	69.26	1.444	0.577	7#
			Right Edge	0	42	5210	-0.01	0.023	14.71	15.00	1.069	69.26	1.444	0.036	/
			Top Edge	0	42	5210	-0.01	0.237	14.71	15.00	1.069	69.26	1.444	0.366	/
			Bottom Edge	0	42	5210	0.05	0.008	14.71	15.00	1.069	69.26	1.444	0.012	/
5.8G	802.11 ac80	Ant.1	Front Side	0	155	5775	0.10	0.019	12.14	12.50	1.086	69.26	1.444	0.030	/
			Back Side	0	155	5775	-0.06	0.018	12.14	12.50	1.086	69.26	1.444	0.028	/
			Left Edge	0	155	5775	0.07	0.102	12.14	12.50	1.086	69.26	1.444	0.160	8#
			Right Edge	0	155	5775	-0.18	0.003	12.14	12.50	1.086	69.26	1.444	0.005	/
			Top Edge	0	155	5775	0.18	0.071	12.14	12.50	1.086	69.26	1.444	0.111	/
			Bottom Edge	0	155	5775	-0.04	0.002	12.14	12.50	1.086	69.26	1.444	0.003	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement

Note 1: For product Head wear&Body 1g SAR, the highest measured 1g SAR is $0.733 < 0.800$ W/kg, repeated measurement is not required.

Note 2: For product Limbs 10g SAR, the highest measured 10g SAR is $1.12 < 2.00$ W/kg, repeated measurement is not required.

12 SAR Measurement Variability

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Consider

No.	Simultaneous Tx Combination	Head wear	Body	Limbs
1	WIFI5G+BT	Yes	Yes	Yes
Note: 1. WiFi 2.4G and Bluetooth share the same antenna, and can't transmit simultaneously. 2. The maximum SAR summation is calculated based on the same configuration and test position.				

12.2 Sum SAR of Simultaneous Transmission

12.2.1 Head wear&Body Simultaneous Transmission SAR Evaluation

Position	Stand alone SAR		SUM SAR
	1	2	
	Max. 5G WIFI	BT	WIFI 5G+BT (1+2)
Front Side 5mm	0.065	0.016	0.081
Back Side 5mm	0.363	0.009	0.372
Left Edge 5mm	1.131	0.247	1.378
Right Edge 5mm	0.020	0.004	0.024
Top Edge 5mm	0.517	0.089	0.606
Bottom Edge 5mm	0.009	0.003	0.012

Note:

1: The highest Summed 10g SAR is 1.378 W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.

12.2.2 Limbs Simultaneous Transmission SAR Evaluation

Position	Stand alone SAR		SUM SAR
	1	2	
	Max. 5G WIFI	BT	WIFI 5G+BT (1+2)
Front Side 0mm	0.054	0.023	0.077
Back Side 0mm	0.099	0.012	0.111
Left Edge 0mm	0.577	0.342	0.919
Right Edge 0mm	0.036	0.006	0.042
Top Edge 0mm	0.366	0.112	0.478
Bottom Edge 0mm	0.012	0.004	0.016

Note:

1: The highest Summed 10g SAR is 0.919 W/Kg < 4.0 W/kg, so Simultaneous Transmission SAR test is not required.

13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY8	16.2.2.1588	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2024/05/07	2027/05/06
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2024/05/09	2027/05/08
Data Acquisition Electronics	Speag	DAE4	SN: 878	2025/03/05	2026/03/04
E-Field Probe	Speag	EX3DV4	SN: 7893	2024/09/05	2025/09/04
Signal Generator	Keysight	N5173B	MY62150163	2024/08/12	2025/08/11
Power Meter	R&S	NRVD-B2	835843/014	2024/08/08	2025/08/07
Power Sensor	R&S	NRV-Z4	100381	2024/08/08	2025/08/07
Power Sensor	R&S	NRV-Z2	100211	2024/08/08	2025/08/07
Network Analyzer	Agilent	E5071C	MY46103472	2024/09/11	2025/09/10
Thermometer	Elitech	RC-4HC	EF7239002655	2024/10/31	2025/10/30
Thermometer	Elitech	RC-4HC	EF7216002974	2024/10/31	2025/10/30
Power Amplifier	Mini-Circuits	ZVA-183W-S+	932502132	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	SAM	SN: 1859	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK 3.5 Dielectric Probe Kit.

Head Liquid 1g

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2025.07.15	Head	2450	21.3	1.80	40.28	1.80	39.20	0.00	2.76
2025.07.16	Head	5250	21.1	4.87	35.46	4.71	35.93	3.40	-1.31
2025.07.16	Head	5750	21.1	5.12	35.12	5.22	35.36	-1.92	-0.68
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Head Liquid 1g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2025.07.15	Head	2450	100	5.310	53.10	52.60	0.95
2025.07.16	Head	5250	100	7.590	75.90	77.70	-2.32
2025.07.16	Head	5750	100	7.790	77.90	77.60	0.39

Note: The tolerance limit of System validation $\pm 10\%$.

Head Liquid 10g

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2025.07.15	Head	2450	100	2.390	23.90	24.70	-3.24
2025.07.16	Head	5250	100	2.130	21.30	22.00	-3.18
2025.07.16	Head	5750	100	2.130	21.30	21.90	-2.74

Note: The tolerance limit of System validation $\pm 10\%$.

Please refer the document "BL-SZ2570508-ASC.pdf".

ANNEX C TEST DATA

Please refer the document “BL-SZ2570508-ATD.pdf”.

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2570508-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “BL-SZ2570508-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “BL-SZ2570508-AC.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “BL-SZ2570508-AT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--