

RF Exposure evaluation

Product Name : Wireless camera
Brand Name : N/A
Model : IPC03
Series Model : N/A
FCCID : 2BQJT-IPC03
Applicant : **DONGGUAN DERUICHENG VIDEO EQUIPMENT CO.,LTD**
Room 401, Building 5, No.106 Changdong Road, Changping
Address : Town, Dongguan, Guangdong, China
Manufacturer : **DONGGUAN DERUICHENG VIDEO EQUIPMENT CO.,LTD**
Room 401, Building 5, No.106 Changdong Road, Changping
Address : Town, Dongguan, Guangdong, China
Standard(s) : 47CFR §1.1310, 47CFR §2.1091
KDB447498 D01 General RF Exposure Guidance v06
Date of Receipt : June 18, 2025
Date of Test : June 18, 2025~July 04, 2025
Issued Date : July 07, 2025

Issued By:**Dongguan Yaxu (AiT) Technology Limited**

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

Tel.: +86-769-8202 0499 Fax.: +86-769-8202 0495

Reviewed by: Emiya Lin
Emiya Lin**Approved by:** Simba Huang
Simba Huang

Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Dongguan Yaxu (AiT) Technology Limited. If there is a need to alter or revise this document, the right belongs to Dongguan Yaxu (AiT) Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

Report Revise Record

| Report Version | Issued Date | Notes |
|----------------|---------------|-----------------|
| V1.0 | July 07, 2025 | Initial Release |

Contents

| | | |
|-----|----------------------------------|----|
| 1 | GENERAL INFORMATION | 4 |
| 1.1 | ENVIRONMENTAL CONDITIONS | 4 |
| 1.2 | GENERAL DESCRIPTION OF EUT | 4 |
| 1.3 | TEST FACILITY | 6 |
| 1.4 | MEASUREMENT UNCERTAINTY | 7 |
| 2 | METHOD OF MEASUREMENT | 8 |
| 2.1 | APPLICABLE STANDARD | 8 |
| 2.2 | LIMIT | 8 |
| 2.3 | MPE CALCULATION METHOD | 9 |
| 2.4 | MANUFACTURING TOLERANCE | 9 |
| 2.5 | STANDALONE MPE RESULT | 11 |
| 2.6 | CONCLUSION | 11 |

1 GENERAL INFORMATION

1.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---------------------|---------|
| Normal Temperature: | 25°C |
| Relative Humidity: | 55 % |
| Air Pressure: | 101 kPa |

1.2 General Description of EUT

| | |
|------------------------|--|
| Product Name: | Wireless camera |
| Model/Type reference: | IPC03 |
| Serial Model: | N/A |
| Power Supply: | DC 5V from adapter |
| Adapter: | MODEL: CY-01050100UU INPUT: 100-240V~50/60Hz 0.3A MAX OUTPUT: 5.0V 1.0A 5.0W |
| Hardware version.: | N/A |
| Software version.: | N/A |
| Test sample(s) ID: | AiTDG-250618017-1 |
| BT: | |
| Operation frequency: | 2402MHz-2480MHz |
| Channel Number: | BLE:40 Channels |
| Channel separation: | BLE:2MHz |
| Modulation Technology: | GFSK, |
| Antenna Type: | Metal Antenna |
| Antenna gain: | 2.76dBi |
| 2.4G WIFI: | |
| Operation frequency: | 802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz |
| Channel Number: | 802.11b/802.11g/802.11n(HT20): 11 802.11n(HT40):7 |
| Channel separation: | 5MHz |
| Modulation Technology: | 802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(HT20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM) |
| Antenna Type: | Metal Antenna |
| Antenna gain: | 2.76dBi |
| 5G WIFI: | |
| Modulation: | IEEE 802.11a/n: OFDM(64QAM, 16QAM, QPSK, BPSK) |

| Operation frequency: | Band | Mode | Frequency Range(MHz) | Number of channels |
|--|----------------|--------------------|----------------------|--------------------|
| | U-NII Band I | IEEE 802.11a | 5180-5240 | 4 |
| | | IEEE 802.11n 20MHz | 5180-5240 | 4 |
| | | IEEE 802.11n 40MHz | 5190-5230 | 2 |
| | U-NII Band III | IEEE 802.11a | 5745-5825 | 5 |
| | | IEEE 802.11n 20MHz | 5745-5825 | 5 |
| | | IEEE 802.11n 40MHz | 5755-5795 | 2 |
| Antenna type: | Metal Antenna | | | |
| Antenna gain: | -0.49dBi | | | |
| Remark: The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. | | | | |

1.3 Test Facility

Test Laboratory:

Dongguan Yaxu (AiT) Technology Limited

No.22, Jinqianling 3rd Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2017 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on April 18, 2022

FCC-Registration No.: 703111 Designation Number: CN1313

Dongguan Yaxu (AiT) Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 6819A CAB identifier: CN0122

The 3m Semi-anechoic chamber of Dongguan Yaxu (AiT) Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6819A

A2LA-Lab Cert. No.: 6317.01

Dongguan Yaxu (AiT) Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Dongguan Yaxu (AiT) Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Yaxu (AiT) laboratory is reported:

| Test | Measurement Uncertainty | Notes |
|-------------------------------|----------------------------|-------|
| Power Line Conducted Emission | 150KHz~30MHz ± 1.20 dB | (1) |
| Radiated Emission | 9KHz~30Hz ± 3.10 dB | (1) |
| Radiated Emission | 9KHz~1GHz ± 3.75 dB | (1) |
| Radiated Emission | 1GHz~18GHz ± 3.88 dB | (1) |
| Radiated Emission | 18GHz-40GHz ± 3.88 dB | (1) |

The report uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

2 Method of measurement

2.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures

2.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0 – 30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30 – 300 | 61.4 | 0.163 | 1.0 | 6 |
| 300 – 1500 | / | / | f/300 | 6 |
| 1500 – 100,000 | / | / | 5 | 6 |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm ²) | Averaging Time (minute) |
|---|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3 – 3.0 | 614 | 1.63 | (100)* | 30 |
| 3.0 – 30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30 – 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 – 1500 | / | / | f/1500 | 30 |
| 1500 – 100,000 | / | / | 1.0 | 30 |

F=frequency in MHz

*=Plane-wave equivalent power density

2.3 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

2.4 Manufacturing Tolerance

BLE (Conducted)

| Frequency (MHz) | GFSK 1Mbps | | |
|----------------------|------------|------|------|
| | 2402 | 2440 | 2480 |
| Target (dBm) | 0.0 | 1.0 | 1.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

2.4GWIFI (Conducted)

| Frequency (MHz) | 11b(Peak) | | |
|----------------------|-----------|------|------|
| | 2412 | 2437 | 2462 |
| Target (dBm) | 16.0 | 16.0 | 16.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 11g(Peak) | | | |
| Frequency (MHz) | 2412 | 2437 | 2462 |
| | 16.0 | 16.0 | 16.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 11n(HT20) (Peak) | | | |
| Frequency (MHz) | 2412 | 2437 | 2462 |
| | 16.0 | 16.0 | 16.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| 11n(HT40) (Peak) | | | |
| Frequency (MHz) | 2422 | 2437 | 2452 |
| | 16.0 | 16.0 | 16.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |

5.2G WIFI (Conducted)

| Frequency (MHz) | IEEE 802.11a(AV) | | |
|----------------------|------------------|------|------|
| | 5180 | 5200 | 5240 |
| Target (dBm) | 15.0 | 15.0 | 16.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| IEEE 802.11n20(AV) | | | |
| Frequency (MHz) | 5180 | 5200 | 5240 |
| | 15.0 | 15.0 | 15.0 |
| Tolerance \pm (dB) | 1.0 | 1.0 | 1.0 |
| IEEE 802.11n40(AV) | | | |
| Frequency (MHz) | 5190 | 5230 | |
| | 15.0 | 15.0 | |
| Tolerance \pm (dB) | 1.0 | 1.0 | |

5.8G WIFI (Conducted)

| Frequency (MHz) | IEEE 802.11a(AV) | | |
|--------------------|--------------------|------|------|
| | 5745 | 5785 | 5825 |
| Target (dBm) | 15.0 | 15.0 | 14.0 |
| Tolerance ± (dB) | 1.0 | 1.0 | 1.0 |
| Frequency (MHz) | IEEE 802.11n20(AV) | | |
| | 5745 | 5785 | 5825 |
| Target (dBm) | 15.0 | 15.0 | 14.0 |
| Tolerance ± (dB) | 1.0 | 1.0 | 1.0 |
| Frequency (MHz) | IEEE 802.11n40(AV) | | |
| | 5755 | 5795 | |
| Target (dBm) | 14.0 | 14.0 | |
| Tolerance ± (dB) | 1.0 | 1.0 | |

2.5 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

| Modulation Type | Output power with tune_up | | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm ²) | MPE Limits (mW/cm ²) |
|-----------------|---------------------------|--------|--------------------|-----------------------|---------------------------|----------------------------------|
| | dBm | mW | | | | |
| BR_EDR | 2.0 | 1.585 | 2.76 | 1.888 | 0.00060 | 1.0000 |
| 2.4G WIFI | 17.0 | 50.119 | 2.76 | 1.888 | 0.01882 | 1.0000 |
| 5.2G WIFI | 17.0 | 50.119 | -0.49 | 0.893 | 0.00891 | 1.0000 |
| 5.8G WIFI | 16.0 | 39.811 | -0.49 | 0.893 | 0.00707 | 1.0000 |

Remark:

1. *Output power (Peak) including turn-up tolerance;*
2. *MPE evaluate distance is 20cm from user manual provide by manufacturer.*

2.6 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

*****End of Report*****