

# RF Test Report

For

**Applicant name:** BEIJING MENG FRIEND TECHNOLOGY LIMITED  
**Address:** Room A-2079, 2nd Floor, Building 3, Courtyard 30, Shixing Avenue, Shijingshan District, Beijing, China  
**EUT name:** ropet AI robot  
**Brand name:** N/A  
**Model number:** MY-RTPT01  
**Series model number:** N/A  
**FCC ID:** 2BQMFMY-RTPT01

## Issued By

**Company name:** BTF Testing Lab (Shenzhen) Co., Ltd.  
**Address:** 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China  
**Report number:** BTF241226R00503  
**Test standards:** 47 CFR Part 2 Subpart J Section 2.1091  
**Test conclusion:** Pass  
  
**Date of sample receipt:** 2024-12-26  
**Test date:** 2025-04-16 to 2025-05-20  
**Date of issue:** 2025-09-03

Prepared by:



Chris Liu /Project engineer

Approved by:



Ryan CJ /EMC manager

*Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.*

Revision History		
Version	Issue date	Revisions content
R_V0	2025-09-03	Original

## Table of Contents

<b>1 Introduction .....</b>	<b>4</b>
1.1 Laboratory Location .....	4
1.2 Laboratory Facility .....	4
1.3 Announcement .....	4
<b>2 Product Information .....</b>	<b>5</b>
2.1 Application Information .....	5
2.2 Manufacturer Information .....	5
2.3 Factory Information .....	5
2.4 General Description of Equipment under Test (EUT) .....	5
2.5 Technical Information .....	5
<b>3 RF Output Power .....</b>	<b>7</b>
<b>4 Applied Reference Documents .....</b>	<b>9</b>
<b>5 Device Category and RF Exposure Limit .....</b>	<b>9</b>
<b>6 RF Exposure Assessment .....</b>	<b>11</b>

# 1 Introduction

## 1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

## 1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1409**

BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 695374.

- **CNAS - Registration No.: CNAS L17568**

BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.

- **A2LA - Registration No.: 6660.01**

BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

## 1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.
- (7) All entrusted information in this report is provided by the client and has been confirmed through consultation with the client; The testing items for this report have been discussed and confirmed with the client, and our company is only responsible for the content reflected in the report.

## 2 Product Information

### 2.1 Application Information

Company name:	BEIJING MENG FRIEND TECHNOLOGY LIMITED
Address:	Room A-2079, 2nd Floor, Building 3, Courtyard 30, Shixing Avenue, Shijingshan District, Beijing, China

### 2.2 Manufacturer Information

Company name:	BEIJING MENG FRIEND TECHNOLOGY LIMITED
Address:	Room A-2079, 2nd Floor, Building 3, Courtyard 30, Shixing Avenue, Shijingshan District, Beijing, China

### 2.3 Factory Information

Company name:	Shenzhen Kim Dai Intelligence Innovation Technology Co., Ltd.
Address:	3rd Floor, A5-11, South Huanzhen Rd., Da Bo Industrial Zone, Bo Gang, Shajing Town, Bao An District, Shenzhen

### 2.4 General Description of Equipment under Test (EUT)

EUT name	ropet AI robot
Under test model name	MY-RTPT01
Series model name	N/A
Description of model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Rating:	Battery:3.6V 4400mAh 15.84Wh

### 2.5 Technical Information

Modulation Mode:	WLAN 2.4GHz	DSSS-DBPSK, DQPSK, CCK, OFDM-BPSK, QPSK, 16QAM, 64QAM
	WLAN 5GHz	OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM
Frequency Bands:	WLAN 2.4GHz:	2402MHz-2480MHz
	WLAN 5GHz BAND 1:	5150MHz ~ 5250MHz
	WLAN 5GHz BAND 2A:	5250MHz ~ 5350MHz
	WLAN 5GHz BAND 2C:	5470MHz ~ 5725MHz
	WLAN 5GHz BAND 3:	5725MHz ~ 5850MHz
Antenna type:	Internal Antenna	
Antenna Gain:	2.4G WIF: 3.08 dBi (declare by Applicant) 5G WIF BAND 1: 4.95 dBi (declare by Applicant) 5G WIF BAND 2A: 5.54 dBi (declare by Applicant) 5G WIF BAND 2C: 5.52 dBi (declare by Applicant) 5G WIF BAND 3: 5.52 dBi (declare by Applicant)	

Antenna transmit mode:	SISO (1TX, 1RX)
------------------------	-----------------

### 3 RF Output Power

Mode	Channel	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)
802.11b	CH1	2412	14.09
	CH7	2437	14.58
	CH13	2462	14.67
Maximum Tune-up (dBm)			15.00
802.11g	CH1	2412	12.78
	CH7	2437	11.33
	CH13	2462	12.84
Maximum Tune-up (dBm)			13.00
802.11n (HT20)	CH1	2412	11.45
	CH7	2437	10.13
	CH13	2462	11.47
Maximum Tune-up (dBm)			12.00
802.11n (HT40)	CH3	2412	10.72
	CH7	2437	10.30
	CH11	2462	11.29
Maximum Tune-up (dBm)			12.00

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)
			ANT1
802.11a	SISO	5180	10.57
		5200	10.90
		5240	11.32
		5260	10.29
		5300	9.72
		5320	10.00
		5500	8.64
		5580	9.47
		5700	10.73
		5745	12.28
		5785	11.47
		5825	11.73
		Maximum Tune-up (dBm)	
		5180	13.00
802.11n (HT20)	SISO	5200	11.61
		5240	11.34
		5260	11.18
		5300	9.77
		5320	9.87
		5500	10.73
		5580	9.51
		5700	10.87
		5745	11.14
		5785	13.19
		5825	12.16
		Maximum Tune-up (dBm)	
		5180	12.36
		5200	14.00

802.11n (HT40)	SISO	5190	11.30	
		5230	10.67	
		5270	11.11	
		5310	9.19	
		5510	10.10	
		5550	8.01	
		5670	11.07	
		5755	12.65	
		5795	13.68	
		Maximum Tune-up (dBm)	14.00	
802.11ac (VHT20)	SISO	5180	11.76	
		5200	11.37	
		5240	11.92	
		5260	10.20	
		5300	9.66	
		5320	9.73	
		5500	9.76	
		5580	11.57	
		5700	11.47	
		5745	12.33	
802.11ac (VHT40)	SISO	5785	12.39	
		5825	11.81	
		Maximum Tune-up (dBm)	13.00	
		5190	12.24	
		5230	11.41	
		5270	9.67	
		5310	10.07	
		5510	8.82	
		5550	8.37	
		5670	12.56	
Maximum Tune-up (dBm)		5755	12.42	
		5795	12.75	
Maximum Tune-up (dBm)		13.00		

**Note 1:** According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

## 4 Applied Reference Documents

Identity	Document Title
47 CFR Part 2(2.1091)	Radio Frequency Radiation Exposure Assessment: mobile devices
KDB 447498 D01v06	General RF Exposure Guidance

## 5 Device Category and RF Exposure Limit

Per user manual, Based on 47 CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:	<p>47 CFR 2.1091(b)</p> <p>For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location.</p> <p>Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.</p>
General Population/ Uncontrolled Exposure:	<p>The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.</p>
Test Standards:	<p>The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.</p> <p>Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.</p>

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b) Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6

1500–100,000	-	-	5	6	
(B) Limits for General Population/Uncontrolled Exposure					
0.3–1.34	614	1.63	*(100)	30	
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30	
30–300	27.5	0.073	0.2	30	
300–1500	-	-	f/1500	30	
1500–100,000	-	-	1.0	30	

f = frequency in MHz \* = Plane-wave equivalent power density

## 6 RF Exposure Assessment

### ➤ Standalone Transmission Assessment:

Bands	Frequency (MHz)	Tune-up Power(dBm)	Antenna Gain(dBi)	E.I.R.P. (mW)	Power Density (mW/cm <sup>2</sup> )	Limit for MPE (mW/cm <sup>2</sup> )
WLAN 2.4GHz	2462	15.00	3.08	64.27	0.013	1.0
WLAN 5GHz	5795	14.00	5.54	89.95	0.018	1.0

**Note:**

1. According to KDB 447498, MPE assessment is based on source-based time-averaged maximum conducted output power of the RF channel requiring assessment, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.
2. MPE calculate method

$$S = PG/4\pi R^2$$

Where:

S = Power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = Time-average maximum tune-up power (in appropriate units, e.g. dBm)

G = numeric gain of the antenna (in appropriate units, e.g. dBi)

R = Separation distance to the centre of radiation of the antenna (20cm)

### ➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

[www.btf-lab.com](http://www.btf-lab.com)

**--END OF REPORT--**