

# TEST REPORT

Report No.	CISRR25062529002
Project No.	CISR250625290
FCC ID	2BQMW-BLM-CK
Applicant	Guangzhou Geeklink Intelligent Technology Co., Ltd.
Address	Room 401, No. 26 Qinglan Street, Xiaoguwei Street, Panyu District, Guangzhou City, Guangdong Province, China
Manufacturer	Guangzhou Geeklink Intelligent Technology Co., Ltd.
Address	Room 401, No. 26 Qinglan Street, Xiaoguwei Street, Panyu District, Guangzhou City, Guangdong Province, China
Product Name	Smart Key Card Power Switch
Trade Mark	N/A
Model/Type reference	BLM-CK
Listed Model(s)	BLM-CK1、BLM-CK2、BLM-CK3、BLM-CH1、BLM-CH2、BLM-CH3、BLM-CL1、BLM-CL2、BLM-CL3、BLM-CGH1、BLM-CGH2、BLM-CGH3、BLM-CGL1、BLM-CGL2、BLM-CGL3
Standard	Part 15 Subpart C Section 15.225
Test date	July 17, 2025 to July 24, 2025
Issue date	July 25, 2025
<b>Test result</b>	<b>Complied</b>



Prepared by: Jimmy Huang



Approved by: Genry Long

*The test results relate only to the tested samples.*

*The test report should not be reproduced except in full without the written approval of Shenzhen Bangce Testing Technology Co., Ltd.*

## Contents

<b>1. REPORT VERSION .....</b>	<b>3</b>
<b>2. SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>3. SUMMARY .....</b>	<b>5</b>
3.1. Product Description .....	5
3.2. Radio Specification Description .....	5
3.3. Modification of EUT .....	6
3.4. Testing Site .....	6
3.5. Field Strength Calculation .....	6
3.6. DISTURBANCE Calculation .....	6
<b>4. TEST CONFIGURATION .....</b>	<b>7</b>
4.1. Test frequency list .....	7
4.2. Test mode .....	7
4.3. Support unit used in test configuration and system .....	7
4.4. Test sample information .....	7
4.5. Testing environmental condition .....	8
4.6. Statement of the measurement uncertainty .....	8
4.7. Equipment Used during the Test .....	9
<b>5. TEST CONDITIONS AND RESULTS .....</b>	<b>10</b>
5.1. Antenna Requirement .....	10
5.2. AC Conducted Emission .....	11
5.3. Field Strength of Fundamental Emissions .....	14
5.4. 20 dB Bandwidth .....	16
5.5. Frequency Stability .....	18
5.6. Radiated Spurious Emission .....	19
<b>6. TEST SETUP PHOTOS .....</b>	<b>24</b>
<b>7. EXTERNAL AND INTERNAL PHOTOS .....</b>	<b>26</b>
7.1 External photos .....	26
7.2 Internal photos .....	26

## 1. **REPORT VERSION**

Version No.	Issue date	Description
00	July 25, 2025	Original

## 2. **SUMMARY OF TEST RESULT**

Report clause	Test Item	Standard Requirement	Result
5.1	Antenna Requirement	15.203	PASS
5.2	AC Conducted Emission	15.207	N/A
5.3	Field Strength of Fundamental Emissions	15.225 (a) (b) (c)	PASS
5.4	20 dB Bandwidth	15.215	PASS
5.5	Frequency Stability	15.225 (e)	PASS
5.6	Radiated Emissions	15.225 (d)/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- \*1: No requirement on standard, only report these test data.
- N/A: Not Applicable.

### 3. SUMMARY

#### 3.1. Product Description

Main unit information:	
Product Name:	Smart Key Card Power Switch
Trade Mark:	N/A
Model No.:	BLM-CK
Listed Model(s):	BLM-CK1、BLM-CK2、BLM-CK3、BLM-CH1、BLM-CH2、BLM-CH3、BLM-CL1、BLM-CL2、BLM-CL3、BLM-CGH1、BLM-CGH2、BLM-CGH3、BLM-CGL1、BLM-CGL2、BLM-CGL3
Model difference:	The difference between different models is that in this application, due to different sales channels and different model names.
Power supply:	Input:100-240V~
Hardware version:	N/A
Software version:	N/A
Accessory unit (AU) information:	
AU-1	N/A

#### 3.2. Radio Specification Description

Technology:	NFC
Modulation:	ASK
Operation frequency:	13.56MHz
Channel number:	1
Antenna type:	PCB Antenna
Antenna gain:	N/A

### 3.3. Modification of EUT

No modifications are made to the EUT during all test items.

### 3.4. Testing Site

Laboratory Name	Shenzhen Bangce Testing Technology Co., Ltd.
Laboratory Location	101, building 10, Yunli Intelligent Park, Shutianpu community, Matian Street, Guangming District, Shenzhen, Guangdong, China
FCC registration number	736346

### 3.5. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS (\text{dBuV/m}) = RA (\text{dBuV}) + AF (\text{dB/m}) + CL (\text{dB}) - AG (\text{dB})$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

### 3.6. DISTURBANCE Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD (\text{dBuV}) = RA (\text{dBuV}) + PL (\text{dB}) + CL (\text{dB})$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

## 4. TEST CONFIGURATION

### 4.1. Test frequency list

Channel	Frequency (MHz)
1	13.56

### 4.2. Test mode

For RF test items:
The system was configured for testing in a continuous transmits condition and change test channels by software provided by applicant. Power setting Default.
Test Item
Conducted test item
Radiated test item
Remark:
<ul style="list-style-type: none"> <li>– The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.</li> </ul>

### 4.3. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Item	Equipment name	Trade Name	Model No.
1	--	--	--

### 4.4. Test sample information

Type	sample no.
Engineer sample	CISR250625290-S01
Normal sample	CISR250625290-S02

#### 4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

#### 4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	1.63dB
2	Frequency Stability	20Hz
3	20dB Bandwidth	0.002%
4	Radiated Spurious Emission	3.76dB for 30MHz-1GHz 3.80dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

#### 4.7. Equipment Used during the Test

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	SKET	9.3*6.3*6	N/A	2024.09.01	3Year
Spectrum analyzer	Agilent	N9020A	MY50530263	2025.01.08	1Year
Receiver	ROHDE&SCHWARZ	ESCI	100853	2025.01.08	1Year
Spectrum analyzer	R&S	FSV-40N	/	2025.01.08	1Year
Bilog Antenna	Schwarzbeck	VULB 9163	1463	2025.01.08	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2487	2025.01.08	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	2025.01.08	2Year
RF Cable	Tonscend	Cable 1	/	2025.01.08	1Year
RF Cable	Tonscend	Cable 2	/	2025.01.08	1Year
RF Cable	SKET	Cable 3	/	2025.01.08	1Year
Pre-amplifier	Tonscend	TAP9K3G32	AP21G806153	2025.01.08	1Year
Pre-amplifier	Tonscend	TAP01018050	AP22E806229	2025.01.08	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8127	/	2025.01.08	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	2025.01.08	1Year
Horn Antenna	SCHWARZBECK	BBHA9170	1130	2025.01.08	2 Year
Preamplifier	Tonscend	TAP18040048	AP21C806126	2025.01.08	1Year
variable-frequency power source	Pinhong	PH1110	/	2025.01.08	1Year
6dB Attenuator	SKET	DC-6G	/	N/A	N/A
Artificial power network	Schwarzbeck	NSLK8127	8127-01096	2025.01.08	1Year
EMI Test Receiver	Rohde&schwarz	ESCI7	100853	2025.01.08	1Year
8-wire Impedance Stabilization Network	Schwarzbeck	NTFM 8158	8158-00337	2025.01.08	1Year
Artificial power network	Schwarzbeck	ENV216	/	2025.01.08	1Year
Antenna tower	SKET	Bk-4AT-BS	AT2021040101-V1	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS


### 5.1. Antenna Requirement

Limit:

**FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test configuration:



Result:

**Passed**

Description

The antenna type is a PCB Antenna(N/A), Antenna structure please refer to the EUT internal photographs antenna photo.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen Bangce Testing Technology Co., Ltd. does not assume any responsibility.

## 5.2. AC Conducted Emission


Limit:

### FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

Test configuration:



Test procedure:

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.


Test mode:

Refer to the clause 4.3

Result:


**Passed**

## Mode1 / Line: Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	0.5420	24.49	10.38	34.87	46.00	-11.13	AVG
2	0.5580	34.24	10.38	44.62	56.00	-11.38	QP
3	0.9740	19.80	10.43	30.23	46.00	-15.77	AVG
4	0.9860	31.26	10.43	41.69	56.00	-14.31	QP
5	2.6099	29.62	10.87	40.49	56.00	-15.51	QP
6	2.6380	18.78	10.88	29.66	46.00	-16.34	AVG
7	4.7420	15.60	11.67	27.27	46.00	-18.73	AVG
8	4.8460	27.22	11.71	38.93	56.00	-17.07	QP
9	11.2060	21.83	14.24	36.07	60.00	-23.93	QP
10	13.2540	6.93	15.30	22.23	50.00	-27.77	AVG
11	25.2620	26.18	15.11	41.29	60.00	-18.71	QP
12	25.2620	10.08	15.11	25.19	50.00	-24.81	AVG

## Mode1 / Line: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2290	32.16	10.33	42.49	62.49	-20.00	QP
2	0.2290	21.73	10.33	32.06	52.49	-20.43	AVG
3	0.5140	32.63	10.38	43.01	56.00	-12.99	QP
4 *	0.5260	24.38	10.38	34.76	46.00	-11.24	AVG
5	1.1019	29.00	10.46	39.46	56.00	-16.54	QP
6	1.1019	18.73	10.46	29.19	46.00	-16.81	AVG
7	3.1619	18.93	11.05	29.98	46.00	-16.02	AVG
8	3.7100	28.69	11.27	39.96	56.00	-16.04	QP
9	8.0020	17.13	13.06	30.19	50.00	-19.81	AVG
10	8.3220	24.03	13.15	37.18	60.00	-22.82	QP
11	25.4660	28.94	15.31	44.25	60.00	-15.75	QP
12	25.7620	12.84	15.28	28.12	50.00	-21.88	AVG

### 5.3. Field Strength of Fundamental Emissions

Limit:

**FCC CFR Title 47 Part 15 Subpart C Section 15.225**


The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

Frequencies (MHz)	Field Strength (microvolts/meter)	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
13.553 ~ 13.567MHz	15848 at 30m	103.08 (QP)	124 (QP)

Mask Limit:

Frequency (MHz)	Limit (dB $\mu$ V/m)	Distance (m)
1.705-13.110	69.5	3
13.110-13.410	80.5	3
13.410-13.553	90.5	3
13.553-13.567	124.0	3
13.567-13.710	90.5	3
13.710-14.010	80.5	3
14.010-30.000	69.5	3

Test configuration:



Test procedure:

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For X axis / Y axis/ Z axis were tested.

Test mode:


Refer to the clause 4.3

Test data:

Refer to the Appendix B

Result:

**Passed**



\*Note: Factor= Antenna Factor + Cable Loss

Measured ( dB $\mu$ V/m ) = Reading + Factor+51.5, Margin= Measured - Limit

Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).


All emissions emit from non-NFC function of digital unintentional emissions. All NFC's spurious emissions are below 20dB of limits.

X axis / Y axis/ Z axis were tested, report only recorded the worst result of X axis.

## 5.4. 20 dB Bandwidth

Limit:

Test configuration:



Test procedure:


1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW  
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

Test mode:

Refer to the clause 4.3

Result:

**Passed**




## 5.5. Frequency Stability

Limit:

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a full charged battery.

Test configuration:



Test mode:

Refer to the clause 4.3

Test data:

Refer to the Appendix B

Result:

**Passed**

Voltage vs. Frequency Stability

Voltage(V)	Measurement Frequency (MHz)	Deviation (KHz)	Deviation (ppm)	Limit (ppm)
VL	13.56046	0.46	26.92	100
VN	13.56025	0.25	36.43	100
VH	13.56035	0.35	25.81	100

Temperature vs. Frequency Stability

Temperature (°C)	Measurement Frequency (MHz)	Deviation (KHz)	Deviation (ppm)	Limit (ppm)
-20	13.56035	0.35	15.81	100
-10	13.56029	0.29	24.39	100
0	13.56034	0.34	35.07	100
10	13.56033	0.33	32.34	100
20	13.56035	0.35	25.81	100
30	13.56034	0.33	25.07	100
40	13.56033	0.37	24.34	100
50	13.56026	0.26	15.17	100

## 5.6. Radiated Spurious Emission

Limit:

### FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Limit dBuV/m @3m = Limit dBuV/m @300m + 40\*log(300/3)

Limit dBuV/m @3m = Limit dBuV/m @30m +40\*log(30/3)


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

Test configuration:


9kHz~30MHz



30 MHz ~ 1 GHz



Above 1 GHz



Test procedure:

5. The EUT was setup and tested according to ANSI C63.10.
6. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
7. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
8. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
9. Set to the maximum power setting and enable the EUT transmit continuously.
10. Use the following spectrum analyzer settings
  - a) Span shall wide enough to fully capture the emission being measured;
  - b) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement  
For average measurement: use duty cycle correction factor method (DCCF)  
Averager level = Peak level + DCCF

Test mode:

Refer to the clause 4.3


Result:**Passed**

## Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

For 9 kHz ~ 30 MHz

0°




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0120	100.35	-22.08	78.27	126.02	-47.75	peak
2	0.1213	99.28	-22.42	76.86	105.93	-29.07	peak
3	0.6955	58.84	-21.75	37.09	70.76	-33.67	peak
4	1.3099	59.21	-21.32	37.89	65.25	-27.36	peak
5	4.7194	53.20	-21.61	31.59	60.10	-28.51	peak
6 *	18.8933	53.66	-22.48	31.18	49.54	-18.36	peak

Note: Only recorded the worst test result.

**For 30 MHz ~ 1000 MHz**


Have pre-scan all test channel, found CH00 which it was worst case, so only show the worst case's data on this report.

Mode1 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	41.4215	54.71	-30.36	24.35	48.50	-24.15	QP
2	114.5146	60.22	-31.42	28.80	53.00	-24.20	QP
3 *	229.2930	62.98	-29.06	33.92	55.90	-21.98	QP
4	301.4223	56.05	-27.05	29.00	55.90	-26.90	QP
5	459.1143	49.51	-23.10	26.41	55.90	-29.49	QP
6	793.3960	48.39	-16.61	31.78	55.90	-24.12	QP


## Mode1 / Polarization: Vertical




No.	Frequency (MHz)	Reading (dB <sub>uV</sub> )	Factor (dB/m)	Level (dB <sub>uV/m</sub> )	Limit (dB <sub>uV/m</sub> )	Margin (dB)	Detector
1 *	51.1210	57.69	-29.37	28.32	48.50	-20.18	QP
2	73.1025	59.33	-33.57	25.76	48.50	-22.74	QP
3	114.5146	59.47	-31.42	28.05	53.00	-24.95	QP
4	297.2240	53.02	-27.14	25.88	55.90	-30.02	QP
5	382.5878	51.29	-25.26	26.03	55.90	-29.87	QP
6	925.7562	39.59	-14.70	24.89	55.90	-31.01	QP

## 6. TEST SETUP PHOTOS


Conducted Emission at AC power line



Emissions in frequency bands (below 30MHz)



Emissions in frequency bands (30M-1GHz)



## **7. EXTERNAL AND INTERNAL PHOTOS**

### **7.1 External photos**

Refer to the report CISRR25062529001.

### **7.2 Internal photos**

Refer to the report CISRR25062529001.

-----End of the report-----