



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

## RF Exposure MPE

Report Reference No.....: CTA25070800105

FCC ID.....: 2BQTY-S1

Compiled by

( position+printed name+signature) :: File administrators Zoey Cao

Supervised by

( position+printed name+signature) :: Project Engineer Ace Chai

Approved by

( position+printed name+signature) :: RF Manager Eric Wang

Date of issue .....: Jul. 16, 2025

Testing Laboratory Name.....: Shenzhen CTA Testing Technology Co., Ltd.

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: SHENZHEN XINLINK TIMESTECHNOLOGY CO., LTD.

Address.....: F6 Block A, Xingzhan plaza, 446 Nan Huan Road, Shajing, Baoan, Shenzhen, China

Standard .....: 47CFR §1.1310

47CFR §2.1091

KDB447498 D01 General RF Exposure Guidance v06

**Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description .....: Mobile Surveillance Robot

Trade Mark .....: N/A

Manufacturer .....: SHENZHEN XINLINK TIMESTECHNOLOGY CO., LTD.

Model/Type reference .....: Magic S1

Listed Models .....: N/A

Rating .....: DC 3.7V From battery and DC 5.0V From external circuit

Result .....: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

## TEST REPORT

Equipment under Test : Mobile Surveillance Robot

Model /Type : Magic S1

Listed Models : N/A

**Applicant** : SHENZHEN XINLINK TIMESTECHNOLOGY CO., LTD.

**Address** : F6 Block A, Xingzhan plaza, 446 Nan Huan Road, Shajing, Baoan, Shenzhen, China

**Manufacturer** : SHENZHEN XINLINK TIMESTECHNOLOGY CO., LTD.

**Address** : F6 Block A, Xingzhan plaza, 446 Nan Huan Road, Shajing, Baoan, Shenzhen, China

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|     |                                                |    |
|-----|------------------------------------------------|----|
| 1   | TEST STANDARDS .....                           | 4  |
| 2   | SUMMARY .....                                  | 5  |
| 2.1 | General Remarks .....                          | 5  |
| 2.2 | Product Description .....                      | 5  |
| 2.3 | Special Accessories .....                      | 6  |
| 2.4 | Modifications .....                            | 6  |
| 3   | TEST ENVIRONMENT .....                         | 7  |
| 3.1 | Address of the test laboratory .....           | 7  |
| 3.2 | Test Facility .....                            | 7  |
| 3.3 | Statement of the measurement uncertainty ..... | 7  |
| 4   | Test limit .....                               | 8  |
| 4.1 | Requirement .....                              | 8  |
| 4.2 | MPE Calculation Method .....                   | 8  |
| 4.3 | Conducted Power Results .....                  | 8  |
| 4.4 | Manufacturing tolerance .....                  | 10 |
| 4.5 | Standalone MPE Result .....                    | 10 |
| 4.6 | Simultaneous Transmission for MPE Result ..... | 10 |
| 5   | Conclusion .....                               | 11 |

## 1 TEST STANDARDS

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Jul. 08, 2025 |
| Testing commenced on           | : | Jul. 08, 2025 |
| Testing concluded on           | : | Jul. 16, 2025 |

### 2.2 Product Description

|                            |                                                                                |                 |              |               |
|----------------------------|--------------------------------------------------------------------------------|-----------------|--------------|---------------|
| Product Name:              | Mobile Surveillance Robot                                                      |                 |              |               |
| Model/Type reference:      | Magic S1                                                                       |                 |              |               |
| Power supply:              | DC 3.7V From battery and DC 5.0V From external circuit                         |                 |              |               |
| Adapter information:       | Model: GDW-050200-U<br>Input: AC 100-240V 50/60Hz 0.5A<br>Output: DC 5V 2A     |                 |              |               |
| Charging base information: | Input: DC 5V 2A<br>Output: DC 5V 2A                                            |                 |              |               |
| Hardware version:          | V1.0                                                                           |                 |              |               |
| Software version:          | V1.0                                                                           |                 |              |               |
| Testing sample ID:         | CTA250708001-1# (Engineer sample)<br>CTA250708001-2# (Normal sample)           |                 |              |               |
| Bluetooth BLE              |                                                                                |                 |              |               |
| Supported type:            | Bluetooth low Energy                                                           |                 |              |               |
| Modulation:                | GFSK                                                                           |                 |              |               |
| Operation frequency:       | 2402MHz to 2480MHz                                                             |                 |              |               |
| Channel number:            | 40                                                                             |                 |              |               |
| Channel separation:        | 2 MHz                                                                          |                 |              |               |
| Antenna type:              | PIFA Antenna                                                                   |                 |              |               |
| Antenna gain:              | 3.15 dBi                                                                       |                 |              |               |
| 2.4GWIFI :                 |                                                                                |                 |              |               |
| Supported type:            | 802.11b/802.11g/802.11n(H20)/ 802.11n(H40)                                     |                 |              |               |
| Modulation:                | 802.11b: DSSS<br>802.11g/802.11n(H20)/ 802.11n(H40): OFDM                      |                 |              |               |
| Operation frequency:       | 802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz<br>802.11n(H40): 2422MHz~2452MHz |                 |              |               |
| Channel number:            | 802.11b/802.11g/802.11n(H20): 11<br>802.11n(H40):7                             |                 |              |               |
| Channel separation:        | 5MHz                                                                           |                 |              |               |
| Antenna type:              | PIFA Antenna                                                                   |                 |              |               |
| Antenna gain:              | 3.15 dBi                                                                       |                 |              |               |
| 5GWIFI                     |                                                                                |                 |              |               |
| Supported type:            | 20MHz system                                                                   | 40MHz system    | 80MHz system | 160MHz system |
|                            | 802.11a<br>802.11n                                                             | 802.11n         | N/A          | N/A           |
| Operation frequency:       | 5180MHz-5240MHz                                                                | 5190MHz-5230MHz | N/A          | N/A           |

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

|                     |                                                                                                                 |                                                        |     |     |
|---------------------|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|-----|-----|
|                     | 5260MHz-5320MHz<br>5500MHz-5700MHz<br>5745MHz-5825MHz                                                           | 5270MHz-5310MHz<br>5510MHz-56700MHz<br>5755MHz-5795MHz |     |     |
| Modulation:         | OFDM                                                                                                            | OFDM                                                   | N/A | N/A |
| Channel separation: | 20MHz                                                                                                           | 40MHz                                                  | N/A | N/A |
| Antenna type:       | PIFA Antenna                                                                                                    |                                                        |     |     |
| Antenna gain:       | 3.87 dBi for 5180-5240MHz<br>3.3 dBi for 5260-5320MHz<br>5.67 dBi for 5500-5700MHz<br>4.91 dBi for 5745-5825MHz |                                                        |     |     |

### 2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|-------------|--------------|-------|----------------------|-------------|-------------|
| /           | /            | /     | /                    | /           | /           |

### 2.4 Modifications

No modifications were implemented to meet testing criteria.



### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,  
Fuhai Street, Bao'an District, Shenzhen, China

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 517856 Designation Number: CN1318**

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6534.01**

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

| Test                                     | Range       | Measurement Uncertainty | Notes |
|------------------------------------------|-------------|-------------------------|-------|
| Radiated Emission                        | 9KHz~30MHz  | 3.02 dB                 | (1)   |
| Radiated Emission                        | 30~1000MHz  | 4.06 dB                 | (1)   |
| Radiated Emission                        | 1~18GHz     | 5.14 dB                 | (1)   |
| Radiated Emission                        | 18-40GHz    | 5.38 dB                 | (1)   |
| Conducted Disturbance                    | 0.15~30MHz  | 2.14 dB                 | (1)   |
| Output Peak power                        | 30MHz~18GHz | 0.55 dB                 | (1)   |
| Power spectral density                   | /           | 0.57 dB                 | (1)   |
| Spectrum bandwidth                       | /           | 1.1%                    | (1)   |
| Radiated spurious emission (30MHz-1GHz)  | 30~1000MHz  | 4.10 dB                 | (1)   |
| Radiated spurious emission (1GHz-18GHz)  | 1~18GHz     | 4.32 dB                 | (1)   |
| Radiated spurious emission (18GHz-40GHz) | 18-40GHz    | 5.54 dB                 | (1)   |
| Time                                     | /           | ± 2%                    | (1)   |

**Shenzhen CTA Testing Technology Co., Ltd.**

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

## 4 Test limit

### 4.1 Requirement

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz)                        | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                   | 614                          | 1.63                         | (100) *                             | 6                       |
| 3.0 – 30                                    | 1842/f                       | 4.89/f                       | (900/f <sup>2</sup> )*              | 6                       |
| 30 – 300                                    | 61.4                         | 0.163                        | 1.0                                 | 6                       |
| 300 – 1500                                  | /                            | /                            | f/300                               | 6                       |
| 1500 – 100,000                              | /                            | /                            | 5                                   | 6                       |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz)                        | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minute) |
|---------------------------------------------|------------------------------|------------------------------|-------------------------------------|-------------------------|
| Limits for Occupational/Controlled Exposure |                              |                              |                                     |                         |
| 0.3 – 3.0                                   | 614                          | 1.63                         | (100) *                             | 30                      |
| 3.0 – 30                                    | 824/f                        | 2.19/f                       | (180/f <sup>2</sup> )*              | 30                      |
| 30 – 300                                    | 27.5                         | 0.073                        | 0.2                                 | 30                      |
| 300 – 1500                                  | /                            | /                            | f/1500                              | 30                      |
| 1500 – 100,000                              | /                            | /                            | 1.0                                 | 30                      |

F=frequency in MHz

\*=Plane-wave equivalent power density

### 4.2 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 4.3 Conducted Power Results

| TestMode | Freq(MHz) | Conducted Peak Power[dBm] |
|----------|-----------|---------------------------|
| BLE_1M   | 2402      | -3.18                     |
|          | 2440      | -3.53                     |
|          | 2480      | -3.56                     |

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn



| Test Mode | Frequency[MHz] | Peak power [dBm] |
|-----------|----------------|------------------|
| 11B       | 2412           | 14.61            |
|           | 2437           | 13.3             |
|           | 2462           | 14.52            |
| 11G       | 2412           | 13.62            |
|           | 2437           | 13.44            |
|           | 2462           | 13.23            |
| 11N20SISO | 2412           | 13.4             |
|           | 2437           | 13.27            |
|           | 2462           | 12.91            |
| 11N40SISO | 2422           | 12.66            |
|           | 2437           | 13.2             |
|           | 2452           | 13.15            |

| Test Mode | Freq(MHz) | Conducted Result [dBm] |
|-----------|-----------|------------------------|
| 11A       | 5180      | 12.35                  |
|           | 5220      | 11.54                  |
|           | 5240      | 11.1                   |
|           | 5260      | 11.34                  |
|           | 5300      | 10.35                  |
|           | 5320      | 10.56                  |
|           | 5500      | 9.48                   |
|           | 5580      | 10.93                  |
|           | 5700      | 9.67                   |
|           | 5745      | 10.8                   |
|           | 5785      | 11.11                  |
|           | 5825      | 10.8                   |
| 11N20SISO | 5180      | 12.2                   |
|           | 5220      | 11.61                  |
|           | 5240      | 11.62                  |
|           | 5260      | 11.88                  |
|           | 5300      | 10.54                  |
|           | 5320      | 10.13                  |
|           | 5500      | 9.55                   |
|           | 5580      | 10.47                  |
|           | 5700      | 9.93                   |
|           | 5745      | 10.68                  |
|           | 5785      | 10.57                  |

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

|           |      |       |
|-----------|------|-------|
| 11N40SISO | 5825 | 10.92 |
|           | 5190 | 11.88 |
|           | 5230 | 11.16 |
|           | 5270 | 10.41 |
|           | 5310 | 10.32 |
|           | 5510 | 11.39 |
|           | 5550 | 11.35 |
|           | 5670 | 10.13 |
|           | 5755 | 9.97  |
|           | 5795 | 10.27 |

#### 4.4 Manufacturing tolerance

| Mode     | Max. Peak Conducted Output Power (dBm) | Max. tune-up |
|----------|----------------------------------------|--------------|
| BLE      | -3.18                                  | -3.0±1       |
| 2.4GWIFI | 14.61                                  | 14.0±1       |

| Mode    | Max. Average Conducted Output Power (dBm) | Max. tune-up |
|---------|-------------------------------------------|--------------|
| UNII-1  | 12.35                                     | 12.0±1       |
| UNII-2A | 11.88                                     | 12.0±1       |
| UNII-2C | 11.39                                     | 12.0±1       |
| UNII-3  | 11.11                                     | 12.0±1       |

#### 4.5 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r=20\text{cm}$ , as well as the gain of the used antenna is refer to section 2.2, the RF power density can be obtained.

| Modulation Type | Output power |         | Antenna Gain (dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) | MPE Limits (mW/cm <sup>2</sup> ) |
|-----------------|--------------|---------|--------------------|-----------------------|---------------------------|----------------------------------|
|                 | dBm          | mW      |                    |                       |                           |                                  |
| BLE             | -2.0         | 0.6310  | 3.15               | 2.0654                | 0.0003                    | 1.0000                           |
| 2.4GWIFI        | 15.0         | 31.6228 | 3.15               | 2.0654                | 0.0130                    | 1.0000                           |
| UNII-1          | 12.0         | 15.8489 | 3.87               | 2.4378                | 0.0077                    | 1.0000                           |
| UNII-2A         | 12.0         | 15.8489 | 3.3                | 2.1380                | 0.0067                    | 1.0000                           |
| UNII-2C         | 12.0         | 15.8489 | 5.67               | 3.6898                | 0.0116                    | 1.0000                           |
| UNII-3          | 12.0         | 15.8489 | 4.91               | 3.0974                | 0.0098                    | 1.0000                           |

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.
3. BT and WLAN can be active at the same time, but only with interleaving of packages switched on board level. That means that they cannot transmit at the same time.

#### 4.6 Simultaneous Transmission for MPE Result

N/A

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China  
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

## 5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device Threshold per KDB 447498 D01v06

\*\*\*\*\* End of Report \*\*\*\*\*