

Shenzhen HTT Technology Co., Ltd.

RF Exposure MPE

Compiled by

(position+printed name+signature) .: File administrators

Supervised by

(position+printed name+signature) .: Project Engineer

Approved by

(position+printed name+signature) .: RF Manager

Date of issue Jul. 21, 2025

Testing Laboratory Name...... Shenzhen HTT Technology Co.,Ltd.

1F, Building B, Huafeng International Robotics Industrial Park,
Address...... Hangcheng Road, Nanchang Community, Xixiang Street, Bao'an

District, Shenzhen, Guangdong, China

Applicant's name...... Guangdong Lingxiao Pump Industry Co., Ltd.

Address.....: 117 CHUNJIANG RD YANGCHUN, Guangdong 529600 China

47CFR §1.1310

Standard 47CFR §2.1091

KDB447498 D01 General RF Exposure Guidance v06

Shenzhen HTT Technology Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HTT Technology Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HTT Technology Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description Variable Speed Swimming Pool Pump

Manufacturer Guangdong Lingxiao Pump Industry Co., Ltd.

Trade Mark...... LX,LINGXIAO,Relaax, KEY LANDER

 Model/Type reference
 SFP220-VS

 Rating
 AC 110-230V

Result PASS

Report No.: HTT202507513F02 Page 2 of 8

TEST REPORT

Equipment under Test : Variable Speed Swimming Pool Pump

Model /Type : SFP220-VS

Listed Models : SHP130-VS,SWP390-VS, Relaax130-VS,SPH130-VS,

ILG8PP130-VS,LU-VS130,VSP13-Pro; Relaax220-VS, SPH220-VS,ILG8PP220-VS,LU-VS220,VSP22-Pro;

Relaax390-VS,SPH390-VS,ILG8PP-390-VS,LU-VS390,VSP39-Pro

Model difference : The PCB board, circuit, structure and internal of these models are the

same, Only model number is different for these model.

Applicant : Guangdong Lingxiao Pump Industry Co., Ltd.

Address : 117 CHUNJIANG RD YANGCHUN, Guangdong 529600 China

Manufacturer : Guangdong Lingxiao Pump Industry Co., Ltd.

Address : 117 CHUNJIANG RD YANGCHUN, Guangdong 529600 China

Test Result:	PASS

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	TEST STANDARDS 4	
<u>2</u>	SUMMARY5	
2.1	General Remarks	5
2.2	Product Description	5
2.3	Special Accessories	5
2.4	Modifications	5
<u>3</u>	TEST ENVIRONMENT6	
3.1	Address of the test laboratory	6
3.2	Test Facility	e
3.3	Statement of the measurement uncertainty	E
<u>4</u>	<u>TEST LIMIT 7</u>	
4.1	Requirement	7
4.2	MPE Calculation Method	7
4.3	Conducted Power Results	8
4.4	Manufacturing tolerance	8
4.5	Standalone MPE Result	8
4.6	Simultaneous Transmission for MPE Result	3
<u>5</u>	CONCLUSION8	

Report No.: HTT202507513F02 Page 4 of 8

1 TEST STANDARDS

The tests were performed according to following standards:

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

<u>FCC KDB 447498 D01 General RF Exposure Guidance v06:</u> Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

Report No.: HTT202507513F02 Page 5 of 8

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample		Jul. 10, 2025
Testing commenced on		Jul. 10, 2025
Testing concluded on	:	Jul. 21, 2025

2.2 Product Description

39-Pro

2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

Description	Manufacturer	Model	Technical Parameters	Certificate	Provided by
1	/	/	1	/	1

2.4 Modifications

No modifications were implemented to meet testing criteria.

Report No.: HTT202507513F02 Page 6 of 8

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen HTT Technology Co.,Ltd.

1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road, Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 779513 Designation Number: CN1319

Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6435.01

Shenzhen HTT Technology Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen HTT Technology Co.,Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen HTT Technology Co.,Ltd.:

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.12 dB	(1)
Radiated Emission	30~1000MHz	4.37 dB	(1)
Radiated Emission	1~18GHz	5.40 dB	(1)
Radiated Emission	18-40GHz	5.45 dB	(1)
Conducted Disturbance	0.15~30MHz	2.68 dB	(1)
Spectrum bandwidth	1	1.2%	(1)
Output Peak power	30MHz~18GHz	0.57dB	(1)
Time	1	±10%	(1)
Note (1): The measurement unce	ertainty is for coverage factor of k	=2 and a level of confidence of 9	95%.

Shenzhen HTT Technology Co.,Ltd.

Tel: 0755-23595200 Fax: 0755-23595201

¹F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road, Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

4 Test limit

4.1 Requirement

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Electric Field Strength(V/m)		Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
	Limits for Occ	cupational/Control	led Exposure	(minute)
0.3 - 3.0 3.0 - 30 30 - 300 300 - 1500 1500 - 100,000	614 1842/f 61.4 /	1.63 4.89/f 0.163 /	(100) * (900/f²)* 1.0 f/300 5	6 6 6 6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Limits for Maximum r emissible Exposure (Mr E)roncontrolled Exposure						
Frequency Electric Field Strength(V/m)		Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)		
	Limits for Occupational/Controlled Exposure					
0.3 - 3.0 3.0 - 30 30 - 300 300 - 1500 1500 - 100.000	614 824/f 27.5 /	1.63 2.19/f 0.073 /	(100) * (180/f ²)* 0.2 f/1500 1.0	30 30 30 30 30		

F=frequency in MHz

4.2 MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna

^{*=}Plane-wave equivalent power density

4.3 Conducted Power Results

Mode	TX	Frequency	Conducte	m Peak ed Output (dBm)
	Туре	(MHz)	ANT1	Limit
		2412	11.81	<=30
802.11b	SISO	2437	13.1	<=30
		2462	13.76	<=30
		2412	17.02	<=30
802.11g	SISO	2437	18.54	<=30
		2462	19.12	<=30
802.11n		2412	16.97	<=30
(HT20)	SISO	2437	18.6	<=30
		2462	19.01	<=30

4.4 Manufacturing tolerance

Mode Max. Peak Conducted Output Power (dBm)		Max. tune-up	
2.4GWIFI	19.12	20.0±1	

4.5 Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, r =20cm, as well as the gain of the used antenna is refer to section 2.2, the RF power density can be obtained.

	Outp	ut power	Antenna	Antenna	MPE	MPE
Modulation Type	dBm	mW	Gain	Gain	(mW/cm ²)	Limits
	ubili	IIIVV	(dBi)	(linear)	(IIIVV/CIII)	(mW/cm ²)
2.4GWIFI	21.0	125.8925	2.54	1.7947	0.0450	1.0000

Remark:

- 1. Output power (Peak) including turn-up tolerance;
- 2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

4.6 Simultaneous Transmission for MPE Result

N/A

5 <u>Conclusion</u>

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device Threshold per KDB 447498 D01v06