

RF TEST REPORT

Report Reference No...... : **MAX25090059P01-R01RF**

FCC ID..... : **2BR28-KJK230**

Compiled by
(position+printed name+signature)... : Engineer/ Cindy Zheng

Supervised by
(position+printed name+signature)... : Manager/Haley Wen

Approved by
(position+printed name+signature)... : RF Manager/ Vivian Jiang

Date of issue..... : September 18, 2025

Testing Laboratory Name..... : **MAXLAB Testing Co.,Ltd.**

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

Applicant's name..... : **Shenzhen Haiyida Electronic Commerce Co., Ltd.**

Address..... : Room 2712, COFCO Ziyun Building, Block 22, Lingzhiyuan Community, Xin'an Subdistrict, Bao'an District, Shenzhen, Guangdong Province, China

Test specification..... :

Standard..... : **FCC 1.1310**

MAXLAB Testing Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd.is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : Trail Camera

Trade Mark..... : N/A

Manufacturer..... : Shenzhen Haiyida Electronic Commerce Co., Ltd.

Model/Type reference..... : KJK230

Listed Models : PV330, HR18, DL10T2C, HC-T10, HC-T20, HC-T30

Modulation Type..... : GFSK, π /4DQPSK, 8-DPSK
CCK/ DSSS/ OFDM

Operation Frequency..... : From 2402MHz to 2480MHz
From 2412 - 2462MHz

Rating..... : DC 6V From Battery 2x(4X1.5AA)

Result..... : **PASS**

RF EXPOSURE EVALUATION METHOD

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.150GHz ~ 5.250GHz ☐ WLAN: 5.725GHz ~ 5.850GHz ☒ Others BT:2402-2480MHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	8.652dBm (0.00733W)
Antenna gain (Max)	BT:1.88dBi;Wifi:3.82 dBi
Evaluation applied	☐ MPE Evaluation ☒ SAR Evaluation

RF EXPOSURE EVALUATION METHOD

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation

Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

Operating Mode	Frequency	Measured Power	max. power	Antenna Gain	min. test separation distance	[$\sqrt{f}$ (GHz)]	Result	Limit
	(MHz)	(dBm)	(mW)	(dBi)	(mm)			
802.11b	2412	8.652	7.33	3.82	5	1.553	2.2773	3
	2437	8.456	7.01	3.82	5	1.561	2.1881	3
	2462	8.352	6.84	3.82	5	1.569	2.1472	3
802.11g	2412	6.526	4.49	3.82	5	1.553	1.3958	3
	2437	6.652	4.63	3.82	5	1.561	1.4443	3
	2462	6.452	4.42	3.82	5	1.569	1.3864	3
802.11n (HT20)	2412	5.412	3.48	3.82	5	1.553	1.0800	3
	2437	5.235	3.34	3.82	5	1.561	1.0422	3
	2462	5.123	3.25	3.82	5	1.569	1.0209	3
802.11n (HT40)	2422	2.652	1.84	3.82	5	1.556	0.5732	3
	2437	2.526	1.79	3.82	5	1.561	0.5585	3
	2452	2.341	1.71	3.82	5	1.566	0.5369	3
GFSK	2402	0.623	1.15	1.88	5	1.550	0.3578	3
	2441	0.691	1.17	1.88	5	1.562	0.3664	3
	2480	0.486	1.12	1.88	5	1.575	0.3523	3
$\pi/4$ DQPSK	2402	2.399	1.74	1.88	5	1.550	0.5385	3
	2441	2.588	1.81	1.88	5	1.562	0.5670	3
	2480	2.311	1.70	1.88	5	1.575	0.5362	3
8-DPSK	2402	2.473	1.77	1.88	5	1.550	0.5478	3
	2441	2.479	1.77	1.88	5	1.562	0.5530	3
	2480	2.170	1.65	1.88	5	1.575	0.5191	3

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f}(\text{GHz})]$ The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Bluetooth and WiFi 2.4G cannot be transmitted simultaneously.

Conclusion: No SAR is required.