

RF Exposure Evaluation

For

Shenzhen Touch Think Intelligence Co.,Ltd.

Android All-in-one Panel PC

Test Model: IPC101-A02-A02

Additional Model No.: Please Refer to Page 6

Prepared for : Shenzhen Touch Think Intelligence Co.,Ltd.
Building 4, XinJianXing Industrial Park, Yangguang second road, Xili

Address : Subdistrict, Nanshan District, Shenzhen City, Guangdong Province,
China

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address : No.44-1,Qianfeng North Road, Shiqi, Panyu District, Guangzhou,
Guangdong, China

Tel : (+86) 020-39166689

Fax : (+86) 020-39166619

Web : www.LCS-cert.com

Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 07, 2025

Number of tested samples : 2

Sample No. : C250801012-1, C250801012-2

Serial number : Prototype

Date of Test : August 07, 2025 ~ September 03, 2025

Date of Report : September 04, 2025

RF Exposure Evaluation	
Report Reference No.	LCSC08015015EF
Date of Issue	September 04, 2025
Testing Laboratory Name	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	No.44-1,Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Testing Location/ Procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's Name	Shenzhen Touch Think Intelligence Co.,Ltd.
Address	Building 4, XinJianXing Industrial Park, Yangguang second road, Xili Subdistrict, Nanshan District, Shenzhen City, Guangdong Province, China
Test Specification	
Standard	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-214 A/0
TRF Originator	Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
EUT Description	Android All-in-one Panel PC
Trade Mark	Shenzhen Touch Think Intelligence Co.,Ltd.
Test Model	IPC101-A02-A02
Ratings	Please Refer to Page 6
Result	PASS

Compiled by:

Lifeng Le.

Lifeng Le / File administrators

Supervised by:

Justin Zhu

Justin Zhu / Technique Director

Approved by:

Gavin Liang

Gavin Liang/ Manager

RF Exposure Evaluation

Test Report No. :	LCSC08015015EF	<u>September 04, 2025</u> Date of issue
--------------------------	-----------------------	--

EUT.....	: Android All-in-one Panel PC
Test Model.....	: IPC101-A02-A02
Applicant.....	: Shenzhen Touch Think Intelligence Co.,Ltd. Building 4, XinJianXing Industrial Park, Yangguang second road, Address..... : Xili Subdistrict, Nanshan District, Shenzhen City, Guangdong Province, China Telephone..... : / Fax..... : /
Manufacturer.....	: Shenzhen Touch Think Intelligence Co.,Ltd. Building 4, XinJianXing Industrial Park, Yangguang second road, Address..... : Xili Subdistrict, Nanshan District, Shenzhen City, Guangdong Province, China Telephone..... : / Fax..... : /
Factory.....	: Shenzhen Touch Think Intelligence Co.,Ltd. Building 4, XinJianXing Industrial Park, Yangguang second road, Address..... : Xili Subdistrict, Nanshan District, Shenzhen City, Guangdong Province, China Telephone..... : / Fax..... : /

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 04, 2025	Initial Issue	--

TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION.....	6
2. EVALUATION METHOD.....	7
3. LIMIT.....	7
4. MPE CALCULATION METHOD	8
5. ANTENNA INFORMATION.....	8
6. CONDUCTED POWER	9
7. MANUFACTURING TOLERANCE	11
8. MEASUREMENT RESULTS.....	14
9. CONCLUSION.....	16
10. DESCRIPTION OF TEST FACILITY.....	16
11. MEASUREMENT UNCERTAINTY.....	16

1. Product Information

EUT	: Android All-in-one Panel PC
Test Model	: IPC101-A02-A02
Additional Model No.	: IPC156-A02-01, TPCaaa-Axyz (aaa=000,070,080,097,101,102,103,104,116,120,121,133,150,156,170,173,185,190,191,215,220,238,240,270,320,420: customer code; A:Product series; x=D/T/1~99,representing the software version; y=0-9,representing the touch mode; z=0-9,representing the product color.The difference does not affect product EMC performance)
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Ratings	: Input: 12.0V $\Rightarrow$ 4.0A For AC Adapter: Input:100-240V~, 50/60Hz, 1.5A Max Output: 12.0V $\Rightarrow$ 4.0A, 48.0W
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: Ant1: External Antenna, 2.95dBi (max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 2.95dBi(Max.) Ant2: External Antenna, 2.95dBi(Max.)
WIFI(5.2G Band)	:
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz) 1 channels for 80MHz bandwidth(5210MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 1.29dBi(Max.) Ant2: External Antenna, 1.29dBi(Max.)
WIFI(5.8G Band)	:
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)

	IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant1: External Antenna, 2.02dBi(Max.) Ant2: External Antenna, 2.02dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3. 1 Refer Evaluation Method

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure				
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6
Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
External	External Antenna 1	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	Bluetooth / 2.4GWIFI: 2.95dBi 5.2GWIFI: 1.29dBi 5.8GWIFI: 2.02dBi	Bluetooth/WIFI Antenna
	External Antenna 2	2400MHz ~ 2500MHz 5000MHz ~ 6000MHz	2.4GWIFI: 2.95dBi 5.2GWIFI: 1.29dBi 5.8GWIFI: 2.02dBi	WIFI Antenna

6. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	0.58
	39	2441	0.14
	79	2480	-0.69
$\pi/4$ -DQPSK	0	2402	0.79
	39	2441	0.91
	79	2480	0.12
8-DPSK	0	2402	0.06
	39	2441	1.17
	79	2480	0.27

[BLE 1M]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-1.05
	19	2440	0.34
	39	2480	-0.73

[BLE 2M]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-1.18
	19	2440	0.2
	39	2480	-0.93

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Ant1 Max Conducted Power(dBm)	Ant2 Max Conducted Power(dBm)
11B	1	2412	15.07	13.93
	6	2437	15.35	14.49
	11	2462	15.45	14.46
11G	1	2412	14.49	13.37
	6	2437	14.99	13.69
	11	2462	15.06	13.69
11N20 SISO	1	2412	13.03	12.98
	6	2437	13.1	12.07
	11	2462	13.3	12.32
11N40 SISO	3	2422	12.49	11.62
	6	2437	12.31	11.31
	9	2452	12.26	11.39

[5.2G WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Ant1 Max Conducted Power(dBm)	Ant2 Max Conducted Power(dBm)
11A	36	5180	13.37	11.57
	40	5200	12.9	11.62
	48	5240	12.25	12.25
11N20 SISO	36	5180	11.63	10.72
	40	5200	11.46	10.61
	48	5240	11.62	9.64
11N40 SISO	38	5190	11.29	10.36
	46	5230	10.66	9.5
11AC20 SISO	36	5180	11.5	10.83
	40	5200	11.32	10.45
	48	5240	11.13	10.39
11AC40 SISO	38	5190	11.3	10.34
	46	5230	10.73	9.51
11AC80 SISO	42	5210	9.59	8.74

[5.8G WIFI Max Conducted Power]

Mode	Channel	Frequency (MHz)	Ant1 Max Conducted Power(dBm)	Ant2 Max Conducted Power(dBm)
11A	149	5745	13.04	11.07
	157	5785	12.38	11.27
	165	5825	12.45	11.37
11N20 SISO	149	5745	11.45	10.6
	157	5785	11.73	9.89
	165	5825	11.87	10.94
11N40 SISO	151	5755	10.23	9.13
	159	5795	10.4	9.37
11AC20 SISO	149	5745	11.45	10.58
	157	5785	11.72	10.81
	165	5825	12.3	10.99
11AC40 SISO	151	5755	10.32	9.96
	159	5795	10.51	9.3
11AC80 SISO	155	5775	9.57	9.16

7. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[BLE 1M]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-1.0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[BLE 2M]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-1.0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant1]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant2]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WIFI Ant1]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	11.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Average)			
Channel	Channel 42		
Target (dBm)	9.0		
Tolerance $\pm$ (dB)	1.0		

[5.2G WIFI Ant2]

11A(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	9.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	9.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80(Average)			
Channel	Channel 42		
Target (dBm)	8.0		
Tolerance $\pm$ (dB)	1.0		

[5.8G WIFI Ant1]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	

11AC80 (Average)	
Channel	Channel 155
Target (dBm)	9.0
Tolerance $\pm$ (dB)	1.0

[5.8G WIFI Ant2]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	9.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	9.0	9.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC20(Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11AC40(Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	9.0	9.0	
Tolerance $\pm$ (dB)	1.0	1.0	
11AC80 (Average)			
Channel	Channel 155		
Target (dBm)	9.0		
Tolerance $\pm$ (dB)	1.0		

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK	1.0	1.2589	2.95	1.9724	0.0005	1.0000
$\pi/4$ -DQPSK	1.0	1.2589	2.95	1.9724	0.0005	1.0000
8-DPSK	2.0	1.5849	2.95	1.9724	0.0006	1.0000

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BLE1M	1.0	1.2589	2.95	1.9724	0.0005	1.0000
BLE2M	1.0	1.2589	2.95	1.9724	0.0005	1.0000

[2.4G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	16.0	39.8107	2.95	1.9724	0.0156	1.0000
IEEE 802.11g	16.0	39.8107	2.95	1.9724	0.0156	1.0000
IEEE 802.11n HT20	14.0	25.1189	2.95	1.9724	0.0099	1.0000
IEEE 802.11n HT40	13.0	19.9526	2.95	1.9724	0.0078	1.0000

[2.4G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	15.0	31.6228	2.95	1.9724	0.0124	1.0000
IEEE 802.11g	14.0	25.1189	2.95	1.9724	0.0099	1.0000
IEEE 802.11n HT20	13.0	19.9526	2.95	1.9724	0.0078	1.0000
IEEE 802.11n HT40	12.0	15.8489	2.95	1.9724	0.0062	1.0000

[5.2G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	1.29	1.3459	0.0067	1.0000
IEEE 802.11n HT20	12.0	15.8489	1.29	1.3459	0.0042	1.0000
IEEE 802.11n HT40	12.0	15.8489	1.29	1.3459	0.0042	1.0000
IEEE 802.11ac VHT20	12.0	15.8489	1.29	1.3459	0.0042	1.0000
IEEE 802.11ac VHT40	12.0	15.8489	1.29	1.3459	0.0042	1.0000
IEEE 802.11ac VHT80	10.0	10.0000	1.29	1.3459	0.0027	1.0000

[5.2G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	13.0	19.9526	1.29	1.3459	0.0053	1.0000
IEEE 802.11n HT20	11.0	12.5893	1.29	1.3459	0.0034	1.0000
IEEE 802.11n HT40	11.0	12.5893	1.29	1.3459	0.0034	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	1.29	1.3459	0.0034	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	1.29	1.3459	0.0034	1.0000
IEEE 802.11ac VHT80	9.0	7.9433	1.29	1.3459	0.0021	1.0000

[5.8G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	14.0	25.1189	2.02	1.5922	0.0080	1.0000
IEEE 802.11n HT20	12.0	15.8489	2.02	1.5922	0.0050	1.0000
IEEE 802.11n HT40	11.0	12.5893	2.02	1.5922	0.0040	1.0000
IEEE 802.11ac VHT20	13.0	19.9526	2.02	1.5922	0.0063	1.0000
IEEE 802.11ac VHT40	11.0	12.5893	2.02	1.5922	0.0040	1.0000
IEEE 802.11ac VHT80	10.0	10.0000	2.02	1.5922	0.0032	1.0000

[5.8G WIFI Ant2]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11a	12.0	15.8489	2.02	1.5922	0.0050	1.0000
IEEE 802.11n HT20	11.0	12.5893	2.02	1.5922	0.0040	1.0000
IEEE 802.11n HT40	10.0	10.0000	2.02	1.5922	0.0032	1.0000
IEEE 802.11ac VHT20	11.0	12.5893	2.02	1.5922	0.0040	1.0000
IEEE 802.11ac VHT40	10.0	10.0000	2.02	1.5922	0.0032	1.0000
IEEE 802.11ac VHT80	10.0	10.0000	2.02	1.5922	0.0032	1.0000

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT&BLE&2.4G WLAN&5.2G WLAN&5.8G WLAN, another one 2.4G WLAN&5.2G WLAN&5.8G WLAN, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum \sum$ of MPE ratios ≤ 1.0

<the worst simultaneous transmission operations result-2.4GWIFI>

2.4GWIFI-Ant 1	2.4GWIFI-Ant 2	$\sum$ MPE ratios	Limit	Results
0.0099	0.0078	0.0177	1.0	Pass

<the worst simultaneous transmission operations result-5GWIFI>

5GWIFI-Ant 1	5GWIFI-Ant 2	$\sum$ MPE ratios	Limit	Results
0.0063	0.0040	0.0103	1.0	Pass

Remark:

1. Output power including tune-up tolerance;
2. BT/BLE/2.4G WIFI output power is burst peak power;
3. 5G WIFI output power is burst average power;
4. MPE evaluate distance is 20cm from user manual provide by manufacturer;
5. MPE values = $PG/4\pi R^2$
6. Both Bluetooth and WIFI cannot be transmitter simultaneously.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

11. Measurement Uncertainty

BT/BLE/2.4GWIFI/5.2GWIFI/5.8GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	: 1GHz-40GHz	± 0.57 dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----