

深圳市瑞通千业科技有限公司

Shenzhen Ruitong Qianyi Technology Co., Ltd.

客户/Ciient Golden World

名称/TYPE A11 Wireless Charging Transmitting Coil

产品型号

Model NO Two-in-one emission coil / 7.5 * 2 * 2800 GS

Product Number Part numbering systey

Customer part number Cient p/NO

Project Number

Enginrer NO

日期/Date October 6th, 2024

本公司工程部/For Enginer Departner Only	
修改内容/Rvised Cintent	认可日期/APProved Date

编制/Prepared

审核/Checked

认可/Approved

Wan Jimei

Wan Jimei

Liu Chengzhao

客户认可回签/Authorixed Signaturure Company Chop		
工程/ Enginrer	认可/QC APProved	认可日期/APProved

深圳市瑞通千业科技有限公司

Shenzhen Ruitong Qianyi Technology Co., Ltd.

一、线圈工艺/Winding Procese:

NO	Winding	Wire gauge	Number of turns	Winding direction	Note
1	N1	2UEW-B-0.08*24*2P	9TS	CCW	
2	N2	2UEW-B-0.08*24*1P	11T	CCW	

二. 电气性能/FEATURES:

1.测试条件 (Test conditions) : 25°C,65%RH@100KHz/1V

1.1 电感量 (Inductance)

1.12 L0A(Coil + Magnetic Plate)=6.3uH±10%

1.2 Q value=40MIN

1.3 Direct current resistance (DCR) : 60mΩ MAX

1.4 (Operating Temperature): -25°C~85°C

2.测试仪器(Test instrument): L:创达 1068+1310;DCR:502BC;SIZE:Callipers


3.Material List

NO	Project	Materials
1	WIRE	φ 0.08*24*2p 2UEW-
2	FERRITE	43.5*8*0.8 L-shaped double-slot ferrite hard magnetic back adhesive with holes
3	GLUE	Water-based white glue
4	SOLDER	HQ-996/JS-996
5	Tin	Kanji Tsubaki Pure Tin
6	High temperature adhesive	8MM High-temperature adhesive tape
7		7.5*2-2800GS
8		

三. 电路图/CIRCUIT DIAGRAM

Organization: MM

四. 外形图/OUTSIDE DIAGRA



Standard	A	B	C	D	E	F	G	H
STD	43.5 ± 0.5	40 ± 0.5	22 ± 2	20.5 ± 0.2	14 ± 0.3	60 ± 2	3 ± 1	0.8 ± 0.5

深圳市瑞通千业科技有限公司


Shenzhen Ruitong Qianyi Technology Co., Ltd.

Standard	I	Magnet						
STD	2.2±0.2	7.5*2.3						

Organization: MM

五. 包装/PACKAGE

5.1 包装图片 Packing pictures:



深圳市瑞通千业科技有限公司

Shenzhen Ruitong Qianyi Technology Co., Ltd.

5.2 包装数量及规格 Packing Quantity:

项目 Item	数量 Quantity	材料规格 Material
盒 Box	350 Pcs	345*330*50 mm
箱 Big Carton	1750 Pcs	360*340*280 mm

5.3 包装以现有包装盘为参照标准，以实际出货包装为准，如有特殊要求可定制。

The packaging shall be based on the exusting packing plate and the actual delivery package shall prevail .If there is any requirement,we can customize it.

六、贮存和使用条件 Storage and Use condition

6.1 贮存条件 Storage condition

6.1.1 建议贮存条件：温度 $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ，湿度 70% (Max.)

Recommended keeping conditions: $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, 70%RH (Max.)

6.1.2 贮存期限：自生产之日起六个月内

Storage life : Within the limits of six months from being produced.

6.2 使用条件 Use condition

使用条件限制：温度 $=-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ ，湿度 $\leq 90\%$

Use condition limit: $T=-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$, $\text{RH} \leq 90\%$.