

Testing Report

Customer Name: SHENZHEN VICTRONICS TECHNOLOGY CO.,
LTD

Product Name: GEL08-4 WIFI module

Sample Model: GEL08-4

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-2021*

Issue Date: 2025.7.25

Engineer:	Jeremy	Date:	2025.7.25
Auditor:	Eason	Date:	2025.7.25
Approver:	Aaron	Date:	2025.7.25



Version

Version No.	Date	Description	Formulate	Approval
A0	2025.07.25	For the first time, formulate	Jeremy	Eason

Contents


1.General Information	3
1.1 General information of testing institutions	3
1.2 Testing principle	3
1.3 Test equipment	4
1.4 Test environment	4
1.5 Statement	4
2.Sample Information	5
2.1 Client information	5
2.2 Description of EUT(S)	5
2.3 EUT appearance	6
2.4 EUT setup photo of free space OTA testing	6
3.Test Results	7
3.1 Test standard	7
3.2 Test uncertainty	7
3.3 Test data	7
3.3.1 Typical free space efficiency and gain	7
3.3.2 Typical free space radiation pattern	8
(The following is blank)	9

1.General Information

1.1 General information of testing institutions

Name	Shenzhen RFI-LAB Communication Technology Co., Ltd.
Address	
Tel	
E-mail	
Equipment	

1.2 Testing principle



1.3 Test equipment

Equipment	Model No.	Serial No.	Manufacturer	Calibration date	Next calibration date
OTA Test System	RayZone-5000	RFI-LAB-RF-D00	GTS	2024.3.15	2026.3.14
Network Analyzer	E5071C	RFI-LAB-RF-D01	KEYSIGHT	2024.5.13	2026.5.12

1.4 Test environment

Temperature	25.1°C
Humidity	58%RH
Pressure	100.13kPa

1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

2.Sample Information


2.1 Client information

Name	
Address	
Contacts	
Tel	
E-mail	
Manufacturer	

2.2 Description of EUT(S)


Product Name	GEL08-4 WIFI module
Sample Model	GEL08-4
Antenna Size	/
Serial No.	/
Test Item	Antenna gain; Efficiency; Radiation pattern
Frequency Range	2400-2500MHz
Received Date	2025.07.24
Test Date	2026.07.25
Remark	The length of the RF cable is 35 mm

2.3 EUT appearance



2.4 EUT setup photo of free space OTA testing

Front view



3. Test Results

3.1 Test standard

Name	Parameter	Method	Standard no.
Mobile communication antenna	Antenna gain	Generic specification for antennas used in the mobile communications	GB/T 9410-2008
	Radiation pattern		
Antenna	Radiation efficiency	IEEE Standard Test Procedures for Antennas	ANSI/IEEE Std 149-2021
	Gain and directivity		

3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of K=2 and the 95% confidence level to express the extended uncertainty.

Item	Uncertainty
Antenna gain	$\pm 0.72\text{dB}$
Radiation efficiency	$\pm 0.72\text{dB}$


3.3 Test data

3.3.1 Typical free space efficiency and gain


Frequency/MHz	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Peak Gain/dBi	-2.45	-2.39	-2.35	-2.21	-1.95	1.70	-1.36	-1.01	-0.72	-0.68	-0.76
Efficiency/%	17.94	18.41	18.77	19.39	20.76	22.21	24.02	26.00	27.79	27.86	27.65

3.3.2 Typical free space radiation pattern


(1) X-Z Plane:




(2) Y-Z Plane:



(3) X-Y Plane:



(4) Typical Free Space 3D Radiation Pattern at 2.45GHz:



End

(The following is blank)