



# RF Exposure Evaluation Report

**Application No.:** DNT2508040032R8390-10944  
**Applicant:** Guangzhoushi fanyuqu xinzaozhen shangpai maoyi shangxing (getigongshanghu)  
**Address of Applicant:** Room 101, No. 28, Xinguang Road, Xinzao Town, Panyu District, Guangzhou, Guangdong, China  
**EUT Description:** Wireless Microphone  
**Model No.:** SP4  
**Additional Model(s):** U3,U2,E2,E3,E4,E5,E6,E7,E9,SP1,SP2,SP3,SP5,SP6,SP7,SP9,SP11, TZ-2,TZ-3  
**FCC ID:** 2BR7A-SP4  
**Power supply:** Input DC 5V; DC 3.7V from rechargeable lithium-ion battery  
**Trade Mark:** /  
**Standards:** 47 CFR Part 2.1093  
FCC KDB 447498 D04 v01  
**Date of Receipt:** 2025/8/4  
**Date of Test:** 2025/8/5 to 2025/9/4  
**Date of Issue:** 2025/9/8  
**Test Result:** PASS

**Prepared By:** Wayne Lin (Testing Engineer)



**Reviewed By:** Pencils Chen (Project Engineer)

**Approved By:** Yiwei Chen (Manager)

Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

**Dongguan DN Testing Co., Ltd.**

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang'an Town, Dongguan City, Guangdong P.R.China

Web: [www.dn-testing.com](http://www.dn-testing.com)

Tel: +86-769-88087383

E-mail: [service@dn-testing.com](mailto:service@dn-testing.com)

**Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V2.0	/	Sep.8, 2025	Valid	Original Report



## Contents

<b>RF EXPOSURE EVALUATION REPORT .....</b>	<b>1</b>
<b>1 GENERAL INFORMATION .....</b>	<b>4</b>
1.1 TEST LOCATION .....	4
1.2 GENERAL DESCRIPTION OF EUT .....	4
1.3 TEST FACILITY .....	5
1.4 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) .....	5
<b>2 RF EXPOSURE EVALUATION .....</b>	<b>6</b>
2.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	6



## 1 General Information

### 1.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin

### 1.2 General Description of EUT

Manufacturer:	Guangzhoushi fanyuqu xinzaozhen shangpai maoyi shangxing (getigongshanghu)
Address of Manufacturer:	Room 101, No. 28, Xinguang Road, Xinzao Town, Panyu District, Guangzhou, Guangdong, China
EUT Description:	Wireless Microphone
Test Model No.:	SP4
Additional Model(s):	U3,U2,E2,E3,E4,E5,E6,E7,E9,SP1,SP2,SP3,SP5,SP6,SP7,SP9,SP11,TZ-2, TZ-3
Power Supply:	Input DC 5V; DC 3.7V from rechargeable lithium-ion battery
Chip Type:	AC7063M2
Serial number:	PR2508040032R8390
Trade Mark:	/
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz-2480MHz
Type of Modulation:	GFSK
Sample Type:	<input checked="" type="checkbox"/> Portable Device, <input type="checkbox"/> Module, <input type="checkbox"/> Mobile Device
Antenna Type:	<input type="checkbox"/> External, <input checked="" type="checkbox"/> Integrated
Antenna Ports	<input checked="" type="checkbox"/> Ant 1, <input type="checkbox"/> Ant 2, <input type="checkbox"/> Ant 3
Antenna Gain:	<input checked="" type="checkbox"/> Provided by applicant 1.7dBi
Remark:	<p>*Since the above data and/or information is provided by the applicant relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.</p> <p>*All models are just color and appearance differences, motherboard, PCB circuit board, chip, electronic components is all the same.</p>



## 1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**Lab A:**

- FCC, USA

Designation Number: CN1348

- A2LA (Certificate No. 7050.01)

DONGGUAN DN TESTING CO., LTD.

- Innovation, Science and Economic Development Canada

DONGGUAN DN TESTING CO., LTD. EMC Laboratory has been recognized by ISED as an accredited testing laboratory. CAB identifier is CN0149.

IC#: 30755.

## 1.4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	±0.41dB
2	RF power density, conducted	±1.96dB

No.	Item	Measurement Uncertainty
1	Conduction Emission	± 3.0dB (150kHz to 30MHz) ± 4.8dB (Below 1GHz)
2	Radiated Emission	± 4.8dB (1GHz to 6GHz) ± 4.5dB (6GHz to 18GHz) ± 5.02dB (Above 18GHz)



## 2 RF Exposure Evaluation

### 2.1 RF Exposure Compliance Requirement

#### 2.1.1 Limits

Human exposure to RF emissions from portable devices (47 CFR §2.1093), as defined by the FCC, must be evaluated with respect to the FCC-adopted limits for SAR. Evaluation of mobile devices, as defined by the FCC, may also be performed with respect to SAR limits, but in such cases it is usually simpler and more cost-effective to evaluate compliance with respect to field strength or power density limits. For certain devices that are designed to be used in both mobile and portable configurations similar to those described in 47 CFR §2.1091(d)(4), such as certain desktop phones and wireless modem modules, compliance for mobile configurations is also satisfied when the same device is evaluated for SAR compliance in portable configurations.

Refer to 47 CFR §2.1093:

A portable device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that the RF source's radiating structure(s) is/are within 20 centimeters of the body of the user.

Evaluation of compliance with the exposure limits in § 1.1310 of this chapter, and preparation of an EA if the limits are exceeded, is necessary for portable devices having single RF sources with more than an available maximum time-averaged power of 1 mW, more than the ERP listed in Table 1 to § 1.1307(b)(3)(i)(C), or more than the  $P_{th}$  in the following formula, whichever is greater. The following formula shall only be used in conjunction with portable devices not exempt by § 1.1307(b)(3)(i)(C) at distances from 0.5 centimeters to 20 centimeters and frequencies from 0.3 GHz to 6 GHz.



$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20\text{cm}}$  is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 300 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.



## 2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

## 2.1.3 EUT RF Exposure Evaluation

Mode	Fre (MHz)	Peak Level (dB <sup>μ</sup> V/m)	EIPR Power (dBm)	Target Power (dBm)	Max. E.R.P (dBm)	Max. Target power (mW)	SAR Test Exemption Limit (mW)	Distance (mm)
GFSK	2402	99.04	3.81	3±1	1.85	1.531	3	5
	2440	99.78	4.55	4±1	2.85	1.928	3	5
	2480	102.73	4.55	4±1	2.85	1.928	3	5

Note:

1. EIRP=E-104.8+20logD, D is test distance.

1. E.R.P=Conducted output Power+Antenna Gain -2.15.

2. SAR Test Exclusion Thresholds is 3mW for separation distance 5mm. Therefore, SAR test is not required.

---

The End Report