

FCC RF Exposure

EUT Description: Wireless Stereo Dynamic Headphones

Model No.: VJ033

FCC ID: 2BRCX-VJ033

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where:

Result = $P/D \cdot \sqrt{F}$

F = the RF channel transmit frequency in GHz

P = Maximum turn-up power in mw

D = Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (dBm/mW)	Min test separation distance (mm)	Result	Limit (mW/cm ²)	SAR Test Exclusion
2402	-2.90	-2±1(-1)	0.794	5	0.246	3.0	Pass

Note:

PK Output power = conducted power.

Conducted power see the test report HK2507163871-E, antenna gain = -0.58dBi

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.246 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results = $\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance = 5mm