

TEST REPORT

Report No.: 8332EU013009W2

Applicant: Shenzhen Ihome IoT Technology Co., LTD

Address: 1301-1302, West Building 6, Tian An CloudPark, NO.2018, Xuegang Road, Bantian SubDistrict, Long Gang District, ShenZhen Guangdong Province, China

Product Name: Smart Pet Feeder

Model No.: PF6 (refer to clause 2.4)

Trademark: N/A

FCC ID: 2BRGT-PF6

Test Standard(s): 47 CFR Part 15 Subpart C

Test Result: Pass

Date of Receipt: Jul. 30, 2025

Test Date: Jul. 30, 2025 – Aug. 20, 2025


Date of Issue: Sep. 04, 2025

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED



Prepared by:



Mikey Zhu/ Engineer

Reviewed and Approved by:



Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Sep. 04, 2025	Original	Valid



Table of Contents

1	COVER PAGE.....	1
2	GENERAL INFORMATION	5
2.1	APPLICANT INFORMATION.....	5
2.2	MANUFACTURER INFORMATION.....	5
2.3	FACTORY INFORMATION.....	5
2.4	GENERAL DESCRIPTION OF E.U.T.....	5
2.5	TECHNICAL INFORMATION OF E.U.T.....	6
3	TEST SUMMARY	8
3.1	TEST STANDARD	8
3.2	TEST VERDICT.....	8
3.3	TEST LABORATORY	8
4	TEST CONFIGURATION.....	9
4.1	TEST ENVIRONMENT	9
4.2	TEST EQUIPMENT	9
4.3	DESCRIPTION OF SUPPORT UNIT	10
4.4	TEST MODE	10
4.5	DESCRIPTION OF CALCULATION	10
4.6	MEASUREMENT UNCERTAINTY	11
4.7	DEVIATION FROM STANDARDS	11
4.8	ABNORMALITIES FROM STANDARD CONDITION	11
5	TEST ITEMS	12
5.1	ANTENNA REQUIREMENT.....	12
5.1.1	Test Requirement	12
5.1.2	Antenna Anti-Replacement Construction.....	12
5.1.3	Antenna Gain	12
5.2	CONDUCTED EMISSION AT AC POWER LINE	13
5.2.1	Test Requirement	13
5.2.2	Test Setup Diagram	13
5.2.3	Test Procedure	13
5.2.4	Test Data.....	13
5.3	DTS BANDWIDTH	16
5.3.1	Test Requirement	16
5.3.2	Test Setup Diagram	16
5.3.3	Test Procedure	16
5.3.4	Test Data.....	16
5.4	MAXIMUM CONDUCTED OUTPUT POWER	17
5.4.1	Test Requirement	17
5.4.2	Test Setup Diagram	17
5.4.3	Test Procedure	17
5.4.4	Test Data.....	17
5.5	POWER SPECTRAL DENSITY	18
5.5.1	Test Requirement	18
5.5.2	Test Setup Diagram	18
5.5.3	Test Procedure	18
5.5.4	Test Data.....	18
5.6	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS (CONDUCTED)	19
5.6.1	Test Requirement	19
5.6.2	Test Setup Diagram	19
5.6.3	Test Procedure	20
5.6.4	Test Data.....	20

5.7	BAND EDGE EMISSIONS (RESTRICTED FREQUENCY BANDS)	21
5.7.1	Test Requirement	21
5.7.2	Test Setup Diagram	22
5.7.3	Test Procedure	23
5.7.4	Test Data	23
5.8	RADIATED SPURIOUS EMISSIONS	28
5.8.1	Test Requirement	28
5.8.2	Test Setup Diagram	29
5.8.3	Test Procedure	30
5.8.4	Test Data	30
ANNEX A	TEST SETUP PHOTOS	36
ANNEX B	EXTERNAL PHOTOS	36
ANNEX C	INTERNAL PHOTOS	36
ANNEX E	TEST DATA	36



2 General Information

2.1 Applicant Information

Applicant	Shenzhen Ihome IoT Technology Co., LTD
Address	1301-1302,West Building6,Tian An CloudPark,NO.2018,Xuegang Road,Bantian SubDistrict,Long GangDistrict,ShenZhen Guangdong Province,China

2.2 Manufacturer Information

Manufacturer	Shenzhen Ihome IoT Technology Co., LTD
Address	1301-1302,West Building6,Tian An CloudPark,NO.2018,Xuegang Road,Bantian SubDistrict,Long GangDistrict,ShenZhen Guangdong Province,China

2.3 Factory Information

Factory	Shenzhen Ihome IoT Technology Co., LTD
Address	1301-1302,West Building6,Tian An CloudPark,NO.2018,Xuegang Road,Bantian SubDistrict,Long GangDistrict,ShenZhen Guangdong Province,China

2.4 General Description of E.U.T.

Product Name	Smart Pet Feeder
Model No. Under Test	PF6
List Model No.	PF6-B, PF6-W
Description of Model differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in appearance color and model name. (this information provided by the customer)
Rating(s)	Input: 5.0V $\overline{\text{---}}$ 1.0A (Adapter Input: 100-240V~, 50/60Hz, 0.3A MAX; Output: 5.0V $\overline{\text{---}}$ 1.0A 5.0W)
Adapter	Model No.: CY-01050100UU Input: 100-240V~, 50/60Hz, 0.3A MAX Output: 5.0V $\overline{\text{---}}$ 1.0A 5.0W Manufacturer: Bazhong Chuanyuan Technology Co., Ltd.
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Test Sample No.	-1/2(Normal Sample), -2/2(Engineering Sample)
Hardware Version	PF6-V1.0
Software Version	81.0.3.2
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BLE) WiFi 2.4G: 802.11b, 802.11g, 802.11n(HT20/40) WiFi 5G: 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40) U-NII-1/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Technology	WiFi 2.4G
Operation Mode	☒ b ☒ g ☒ n(HT20) ☒ n(HT40)
	☐ ac(VHT20) ☐ ac(VHT40) ☐ ax(HEW20) ☐ ax(HEW40)
Operating Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Number of Channels	802.11b/g/n(HT20): 11 Channels 802.11n(HT40): 7 Channels
Modulation Technology	DSSS, OFDM
Modulation Type	☒ 802.11b: DSSS (CCK, DQPSK, DBPSK) ☒ 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) ☒ 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) ☐ 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) ☐ 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	FPC Antenna
Antenna Gain(Peak)	3.66 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Modulation technology	Modulation Type	Transfer Rate (Mbps)(Single RF path)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n-20 MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM (802.11n-40 MHz)	BPSK	13.5/15
	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Conducted Emission at AC Power Line	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
DTS Bandwidth	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
Maximum Conducted Output Power	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
Emission in non-restricted frequency bands (Conducted)	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
Band Edge Emissions (Restricted frequency bands)	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.5 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices
3	KDB Publication 558074 D01v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

No.	Description	FCC Part No.	Verdict	Remark
1	Antenna Requirement	15.203	Pass	Note ¹
2	Conducted Emission at AC Power Line	15.207	Pass	--
3	DTS Bandwidth	15.247(a)(2)	Pass	--
4	Maximum Conducted Output Power	15.247(b)(3)	Pass	--
5	Power spectral density (PSD)	15.247(e)	Pass	--
6	Emission in non-restricted frequency bands (Conducted)	15.247(d)	Pass	--
7	Band Edge Emissions (Restricted frequency bands)	15.247(d)	Pass	--
8	Radiated Spurious Emission	15.247(d)	Pass	--

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: N/A" denotes test is not applicable in this test report.

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15°C to +35°C
Working Voltage of the EUT	NV (Normal Voltage)	120VAC, 60Hz for adapter

4.2 Test Equipment

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	EE-004	2025/01/08	2026/01/07
EMI Test Receiver	Rohde & Schwarz	ESCI	EE-005	2025/01/08	2026/01/07
Test Software	Farad	EZ-EMC	EE-014	N.C.R	N.C.R

Radiated Emission and RF Test					
Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2025/01/08	2026/01/07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2023/01/14	2026/01/13
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2023/01/12	2026/01/11
Pre-amplifier	Agilent	8447D	EE-009	2025/01/08	2026/01/07
Pre-amplifier	Agilent	8449B	EE-010	2025/01/08	2026/01/07
MXA Signal Analyzer	Agilent	N9020A	EE-011	2025/01/08	2026/01/07
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2025/01/08	2026/01/07
Test Software	Farad	EZ-EMC	EE-015	N.C.R	N.C.R
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2025/01/08	2026/01/07
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	N.C.R	N.C.R
Antenna Mast	TOP Precision	TPBAM-4	EE-306	N.C.R	N.C.R
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-402	2025/02/14	2026/02/13
Loop Antenna	TESEQ	HLA6121	EE-403	2025/02/14	2026/02/13
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2025/02/14	2026/02/13
DRG Horn Antenna	SCHWARZBECK	BBHA 9170	EE-410	2025/02/14	2026/02/13
Pre-amplifier	SKET	LNPA-1840-50	EE-411	2025/02/14	2026/02/13
Power Meter	Anritsu	ML2495A	EE-416	2025/02/14	2026/02/13
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2025/07/29	2026/07/28

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	Adapter	refer to clause 2.4	refer to clause 2.4	--

4.4 Test Mode

No.	Test Modes	Description
TM1	802.11b mode	Keep the EUT in 802.11b transmitting mode.
TM2	802.11g mode	Keep the EUT in 802.11g transmitting mode.
TM3	802.11n(HT20) mode	Keep the EUT in 802.11n(HT20) transmitting mode.
TM4	802.11n(HT40) mode	Keep the EUT in 802.11n(HT40) transmitting mode.

4.5 Description of Calculation

4.5.1. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS \text{ (dBuV/m)} = RA \text{ (dBuV)} + AF \text{ (dB/m)} + CL \text{ (dB)} - AG \text{ (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2. Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Test Item	Measurement Uncertainty
Conducted Emission	2.64 dB
Occupied Channel Bandwidth	70 kHz
RF output power, conducted	1.04 dB
Power Spectral Density, conducted	0.91 dB
Time of Occupancy (Dwell Time)	1.8 %
Unwanted Emissions, conducted	2.72 dB
Radiated Emission (9kHz- 30MHz)	Ur = 2.50 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.70 dB (Horizontal)
	Ur = 2.70 dB (Vertical)
Radiated Emission (1GHz- 18GHz)	Ur = 3.50 dB (Horizontal)
	Ur = 3.50 dB (Vertical)
Radiated Emission (18GHz- 40GHz)	Ur = 5.15 dB (Horizontal)
	Ur = 5.24 dB (Vertical)
Temperature	0.8°C
Humidity	4%

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Condition

None.

5 Test Items

5.1 Antenna requirement

5.1.1 Test Requirement

Test Requirement	According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.
------------------	---

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain


The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Conducted Emission at AC Power Line

5.2.1 Test Requirement

Test Requirement	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method	ANSI C63.10-2020 section 6.2		

5.2.2 Test Setup Diagram



5.2.3 Test Procedure

The EUT is put on the plane 0.8 m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipment. Both sides of AC line are investigated to find out the maximum conducted emission according to the test standard regulations during conducted emission measurement.

The bandwidth of the field strength meter (R&S Test Receiver ESCI) is set at 9kHz in 150kHz~30MHz.

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.


5.2.4 Test Data

PASS.

All modes have been tested and Pass. Only the worst case data was showed in the report, please to see the following pages.

Conducted Emission Test Data

Test Site: Shielded Room #1
Test Mode: TM1/ CH Middle
Comments: Live Line




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1590	38.72	9.96	48.68	65.52	-16.84	QP	P	
2	0.1590	19.16	9.96	29.12	55.52	-26.40	AVG	P	
3 *	0.4082	34.57	10.02	44.59	57.68	-13.09	QP	P	
4	0.4082	19.25	10.02	29.27	47.68	-18.41	AVG	P	
5	0.6473	25.24	10.04	35.28	56.00	-20.72	QP	P	
6	0.6473	13.44	10.04	23.48	46.00	-22.52	AVG	P	
7	2.1552	23.08	10.03	33.11	56.00	-22.89	QP	P	
8	2.1552	7.52	10.03	17.55	46.00	-28.45	AVG	P	
9	3.4906	19.70	10.05	29.75	56.00	-26.25	QP	P	
10	3.4906	4.06	10.05	14.11	46.00	-31.89	AVG	P	
11	7.1753	17.92	10.00	27.92	60.00	-32.08	QP	P	
12	7.1753	2.01	10.00	12.01	50.00	-37.99	AVG	P	

Note: Level = Reading + Factor

Margin = Level - Limit

Conducted Emission Test Data

Test Site: Shielded Room #1
Test Mode: TM1/ CH Middle
Comments: Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1544	39.85	9.98	49.83	65.76	-15.93	QP	P	
2	0.1544	26.19	9.98	36.17	55.76	-19.59	AVG	P	
3	0.4110	33.31	10.04	43.35	57.63	-14.28	QP	P	
4 *	0.4110	24.83	10.04	34.87	47.63	-12.76	AVG	P	
5	0.6313	26.84	10.06	36.90	56.00	-19.10	QP	P	
6	0.6313	14.77	10.06	24.83	46.00	-21.17	AVG	P	
7	1.4640	20.13	10.06	30.19	56.00	-25.81	QP	P	
8	1.4640	7.58	10.06	17.64	46.00	-28.36	AVG	P	
9	4.7625	15.75	10.05	25.80	56.00	-30.20	QP	P	
10	4.7625	5.16	10.05	15.21	46.00	-30.79	AVG	P	
11	8.8440	13.74	10.02	23.76	60.00	-36.24	QP	P	
12	8.8440	1.98	10.02	12.00	50.00	-38.00	AVG	P	


Note: Level = Reading + Factor Margin = Level - Limit

5.3 DTS Bandwidth

5.3.1 Test Requirement

Test Requirement	Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Limit	Section (a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method	ANSI C63.10-2020 section 11.8

5.3.2 Test Setup Diagram



5.3.3 Test Procedure

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Data

PASS.


Please refer to Annex E for details.

5.4 Maximum Conducted Output Power

5.4.1 Test Requirement

Test Requirement	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Limit	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method	ANSI C63.10-2020 section 11.9

5.4.2 Test Setup Diagram



5.4.3 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

5.4.4 Test Data

PASS.


Please refer to Annex E for details.

5.5 Power Spectral Density

5.5.1 Test Requirement

Test Requirement	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Limit	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method	ANSI C63.10-2020 section 11.10

5.5.2 Test Setup Diagram



5.5.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.
Set the span to 1.5 times the DTS bandwidth.
Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
Set the VBW $\geq 3 \text{ RBW}$.
Detector = peak.
Sweep time = auto couple.
Trace mode = max hold.
Allow trace to fully stabilize.
Use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.4 Test Data

PASS.


Please refer to Annex E for details.

5.6 Emissions in Non-restricted Frequency Bands (Conducted)

5.6.1 Test Requirement

Test Requirement	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Limit	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method	ANSI C63.10-2020 section 11.11

5.6.2 Test Setup Diagram



5.6.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.6.4 Test Data

PASS.

Please refer to Annex E for details.


5.7 Band edge Emissions (Restricted frequency bands)

5.7.1 Test Requirement

Test Requirement	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).																																																																							
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																					
	0.009-0.490	2400/F(kHz)	300																																																																					
	0.490-1.705	24000/F(kHz)	30																																																																					
	1.705-30.0	30	30																																																																					
	30-88	100 **	3																																																																					
	88-216	150 **	3																																																																					
	216-960	200 **	3																																																																					
	Above 960	500	3																																																																					
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.																																																																							
	Restricted frequency bands:																																																																							
Test Limit	<table><tr><th>MHz</th></tr><tr><td>0.090 - 0.110</td></tr><tr><td>0.495 - 0.505</td></tr><tr><td>2.1735 - 2.1905</td></tr><tr><td>3.020 - 3.026</td></tr><tr><td>4.125 - 4.128</td></tr><tr><td>4.17725 - 4.17775</td></tr><tr><td>4.20725 - 4.20775</td></tr><tr><td>5.677 - 5.683</td></tr><tr><td>6.215 - 6.218</td></tr><tr><td>6.26775 - 6.26825</td></tr><tr><td>6.31175 - 6.31225</td></tr><tr><td>8.291 - 8.294</td></tr><tr><td>8.362 - 8.366</td></tr><tr><td>8.37625 - 8.38675</td></tr><tr><td>8.41425 - 8.41475</td></tr><tr><td>12.29 - 12.293</td></tr><tr><td>12.51975 - 12.52025</td></tr><tr><td>12.57675 - 12.57725</td></tr><tr><td>13.36 - 13.41</td></tr><tr><td>16.42 - 16.423</td></tr><tr><td>16.69475 - 16.69525</td></tr><tr><td>16.80425 - 16.80475</td></tr><tr><td>25.5 - 25.67</td></tr><tr><td>37.5 - 38.25</td></tr><tr><td>73 - 74.6</td></tr><tr><td>74.8 - 75.2</td></tr><tr><td>108 - 138</td></tr></table>	MHz	0.090 - 0.110	0.495 - 0.505	2.1735 - 2.1905	3.020 - 3.026	4.125 - 4.128	4.17725 - 4.17775	4.20725 - 4.20775	5.677 - 5.683	6.215 - 6.218	6.26775 - 6.26825	6.31175 - 6.31225	8.291 - 8.294	8.362 - 8.366	8.37625 - 8.38675	8.41425 - 8.41475	12.29 - 12.293	12.51975 - 12.52025	12.57675 - 12.57725	13.36 - 13.41	16.42 - 16.423	16.69475 - 16.69525	16.80425 - 16.80475	25.5 - 25.67	37.5 - 38.25	73 - 74.6	74.8 - 75.2	108 - 138	<table><tr><th>MHz</th></tr><tr><td>149.9 - 150.05</td></tr><tr><td>156.52475 - 156.52525</td></tr><tr><td>156.7 - 156.9</td></tr><tr><td>162.0125 - 167.17</td></tr><tr><td>167.72 - 173.2</td></tr><tr><td>240 - 285</td></tr><tr><td>322 - 335.4</td></tr><tr><td>399.9 - 410</td></tr><tr><td>608 - 614</td></tr><tr><td>960 - 1427</td></tr><tr><td>1435 - 1626.5</td></tr><tr><td>1645.5 - 1646.5</td></tr><tr><td>1660 - 1710</td></tr><tr><td>1718.8 - 1722.2</td></tr><tr><td>2200 - 2300</td></tr><tr><td>2310 - 2390</td></tr><tr><td>2483.5 - 2500</td></tr><tr><td>2655 - 2900</td></tr><tr><td>3260 - 3267</td></tr><tr><td>3332 - 3339</td></tr><tr><td>3345.8 - 3358</td></tr><tr><td>3500 - 4400</td></tr><tr><td>4500 - 5150</td></tr><tr><td>5350 - 5460</td></tr><tr><td>7250 - 7750</td></tr><tr><td>8025 - 8500</td></tr><tr><td>--</td></tr></table>	MHz	149.9 - 150.05	156.52475 - 156.52525	156.7 - 156.9	162.0125 - 167.17	167.72 - 173.2	240 - 285	322 - 335.4	399.9 - 410	608 - 614	960 - 1427	1435 - 1626.5	1645.5 - 1646.5	1660 - 1710	1718.8 - 1722.2	2200 - 2300	2310 - 2390	2483.5 - 2500	2655 - 2900	3260 - 3267	3332 - 3339	3345.8 - 3358	3500 - 4400	4500 - 5150	5350 - 5460	7250 - 7750	8025 - 8500	--	<table><tr><th>GHz</th></tr><tr><td>9.0 - 9.2</td></tr><tr><td>9.3 - 9.5</td></tr><tr><td>10.6 - 12.7</td></tr><tr><td>13.25 - 13.4</td></tr><tr><td>14.47 - 14.5</td></tr><tr><td>15.35 - 16.2</td></tr><tr><td>17.7 - 21.4</td></tr><tr><td>22.01 - 23.12</td></tr><tr><td>23.6 - 24.0</td></tr><tr><td>31.2 - 31.8</td></tr><tr><td>36.43 - 36.5</td></tr><tr><td>Above 38.6</td></tr></table>	GHz	9.0 - 9.2	9.3 - 9.5	10.6 - 12.7	13.25 - 13.4	14.47 - 14.5	15.35 - 16.2	17.7 - 21.4	22.01 - 23.12	23.6 - 24.0	31.2 - 31.8	36.43 - 36.5	Above 38.6
	MHz																																																																							
	0.090 - 0.110																																																																							
	0.495 - 0.505																																																																							
	2.1735 - 2.1905																																																																							
	3.020 - 3.026																																																																							
	4.125 - 4.128																																																																							
	4.17725 - 4.17775																																																																							
	4.20725 - 4.20775																																																																							
	5.677 - 5.683																																																																							
	6.215 - 6.218																																																																							
	6.26775 - 6.26825																																																																							
	6.31175 - 6.31225																																																																							
	8.291 - 8.294																																																																							
	8.362 - 8.366																																																																							
	8.37625 - 8.38675																																																																							
	8.41425 - 8.41475																																																																							
	12.29 - 12.293																																																																							
	12.51975 - 12.52025																																																																							
	12.57675 - 12.57725																																																																							
	13.36 - 13.41																																																																							
	16.42 - 16.423																																																																							
	16.69475 - 16.69525																																																																							
	16.80425 - 16.80475																																																																							
	25.5 - 25.67																																																																							
	37.5 - 38.25																																																																							
	73 - 74.6																																																																							
	74.8 - 75.2																																																																							
108 - 138																																																																								
MHz																																																																								
149.9 - 150.05																																																																								
156.52475 - 156.52525																																																																								
156.7 - 156.9																																																																								
162.0125 - 167.17																																																																								
167.72 - 173.2																																																																								
240 - 285																																																																								
322 - 335.4																																																																								
399.9 - 410																																																																								
608 - 614																																																																								
960 - 1427																																																																								
1435 - 1626.5																																																																								
1645.5 - 1646.5																																																																								
1660 - 1710																																																																								
1718.8 - 1722.2																																																																								
2200 - 2300																																																																								
2310 - 2390																																																																								
2483.5 - 2500																																																																								
2655 - 2900																																																																								
3260 - 3267																																																																								
3332 - 3339																																																																								
3345.8 - 3358																																																																								
3500 - 4400																																																																								
4500 - 5150																																																																								
5350 - 5460																																																																								
7250 - 7750																																																																								
8025 - 8500																																																																								
--																																																																								
GHz																																																																								
9.0 - 9.2																																																																								
9.3 - 9.5																																																																								
10.6 - 12.7																																																																								
13.25 - 13.4																																																																								
14.47 - 14.5																																																																								
15.35 - 16.2																																																																								
17.7 - 21.4																																																																								
22.01 - 23.12																																																																								
23.6 - 24.0																																																																								
31.2 - 31.8																																																																								
36.43 - 36.5																																																																								
Above 38.6																																																																								
* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.																																																																								
Note: 1) Field Strength (dBµV/m) = 20*log[Field Strength (µV/m)]. 2) In the emission tables above, the tighter limit applies at the band edges. 3) For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using																																																																								

	instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit. 4) For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).
Test Method	ANSI C63.10-2020 section 11.12

5.7.2 Test Setup Diagram



5.7.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold.

5.7.4 Test Data

PASS.

Please refer to the following pages.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11b					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	45.11	-2.81	42.30	74.00	-31.70	PK	PASS
H	2390.00	47.72	-2.69	45.03	74.00	-28.97	PK	PASS
H	**2400.00	62.35	-2.68	59.67	74.00	-14.33	PK	PASS
V	2310.00	43.33	-2.81	40.52	74.00	-33.48	PK	PASS
V	2390.00	48.97	-2.69	46.28	74.00	-27.72	PK	PASS
V	**2400.00	63.44	-2.68	60.76	74.00	-13.24	PK	PASS
H	2310.00	32.47	-2.81	29.66	54.00	-24.34	AV	PASS
H	2390.00	38.33	-2.69	35.64	54.00	-18.36	AV	PASS
H	**2400.00	46.27	-2.68	43.59	54.00	-10.41	AV	PASS
V	2310.00	33.19	-2.81	30.38	54.00	-23.62	AV	PASS
V	2390.00	35.65	-2.69	32.96	54.00	-21.04	AV	PASS
V	**2400.00	49.21	-2.68	46.53	54.00	-7.47	AV	PASS

Test Mode: 802.11b					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	46.29	-2.56	43.73	74.00	-30.27	PK	PASS
H	2500.00	50.56	-2.54	48.02	74.00	-25.98	PK	PASS
V	**2483.50	48.27	-2.56	45.71	74.00	-28.29	PK	PASS
V	2500.00	49.71	-2.54	47.17	74.00	-26.83	PK	PASS
H	**2483.50	38.58	-2.56	36.02	54.00	-17.98	AV	PASS
H	2500.00	39.01	-2.54	36.47	54.00	-17.53	AV	PASS
V	**2483.50	37.00	-2.56	34.44	54.00	-19.56	AV	PASS
V	2500.00	40.82	-2.54	38.28	54.00	-15.72	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11g					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	44.26	-2.81	41.45	74.00	-32.55	PK	PASS
H	2390.00	46.00	-2.69	43.31	74.00	-30.69	PK	PASS
H	**2400.00	62.27	-2.68	59.59	74.00	-14.41	PK	PASS
V	2310.00	43.22	-2.81	40.41	74.00	-33.59	PK	PASS
V	2390.00	49.47	-2.69	46.78	74.00	-27.22	PK	PASS
V	**2400.00	63.63	-2.68	60.95	74.00	-13.05	PK	PASS
H	2310.00	34.75	-2.81	31.94	54.00	-22.06	AV	PASS
H	2390.00	34.88	-2.69	32.19	54.00	-21.81	AV	PASS
H	**2400.00	48.50	-2.68	45.82	54.00	-8.18	AV	PASS
V	2310.00	35.01	-2.81	32.20	54.00	-21.80	AV	PASS
V	2390.00	37.22	-2.69	34.53	54.00	-19.47	AV	PASS
V	**2400.00	46.61	-2.68	43.93	54.00	-10.07	AV	PASS

Test Mode: 802.11g					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.85	-2.56	45.29	74.00	-28.71	PK	PASS
H	2500.00	49.97	-2.54	47.43	74.00	-26.57	PK	PASS
V	**2483.50	46.86	-2.56	44.30	74.00	-29.70	PK	PASS
V	2500.00	52.46	-2.54	49.92	74.00	-24.08	PK	PASS
H	**2483.50	37.75	-2.56	35.19	54.00	-18.81	AV	PASS
H	2500.00	42.08	-2.54	39.54	54.00	-14.46	AV	PASS
V	**2483.50	38.43	-2.56	35.87	54.00	-18.13	AV	PASS
V	2500.00	42.07	-2.54	39.53	54.00	-14.47	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11n(HT20)					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	43.32	-2.81	40.51	74.00	-33.49	PK	PASS
H	2390.00	46.38	-2.69	43.69	74.00	-30.31	PK	PASS
H	**2400.00	63.74	-2.68	61.06	74.00	-12.94	PK	PASS
V	2310.00	44.26	-2.81	41.45	74.00	-32.55	PK	PASS
V	2390.00	47.87	-2.69	45.18	74.00	-28.82	PK	PASS
V	**2400.00	64.08	-2.68	61.40	74.00	-12.60	PK	PASS
H	2310.00	32.03	-2.81	29.22	54.00	-24.78	AV	PASS
H	2390.00	35.80	-2.69	33.11	54.00	-20.89	AV	PASS
H	**2400.00	48.67	-2.68	45.99	54.00	-8.01	AV	PASS
V	2310.00	32.95	-2.81	30.14	54.00	-23.86	AV	PASS
V	2390.00	35.86	-2.69	33.17	54.00	-20.83	AV	PASS
V	**2400.00	46.63	-2.68	43.95	54.00	-10.05	AV	PASS

Test Mode: 802.11n(HT20)					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.77	-2.56	45.21	74.00	-28.79	PK	PASS
H	2500.00	49.26	-2.54	46.72	74.00	-27.28	PK	PASS
V	**2483.50	46.89	-2.56	44.33	74.00	-29.67	PK	PASS
V	2500.00	49.25	-2.54	46.71	74.00	-27.29	PK	PASS
H	**2483.50	39.80	-2.56	37.24	54.00	-16.76	AV	PASS
H	2500.00	42.15	-2.54	39.61	54.00	-14.39	AV	PASS
V	**2483.50	36.77	-2.56	34.21	54.00	-19.79	AV	PASS
V	2500.00	40.85	-2.54	38.31	54.00	-15.69	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 802.11n(HT40)					CH Low: 2422 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	44.10	-2.81	41.29	74.00	-32.71	PK	PASS
H	2390.00	49.68	-2.69	46.99	74.00	-27.01	PK	PASS
H	**2400.00	64.67	-2.68	61.99	74.00	-12.01	PK	PASS
V	2310.00	42.74	-2.81	39.93	74.00	-34.07	PK	PASS
V	2390.00	47.36	-2.69	44.67	74.00	-29.33	PK	PASS
V	**2400.00	62.09	-2.68	59.41	74.00	-14.59	PK	PASS
H	2310.00	33.38	-2.81	30.57	54.00	-23.43	AV	PASS
H	2390.00	34.92	-2.69	32.23	54.00	-21.77	AV	PASS
H	**2400.00	49.04	-2.68	46.36	54.00	-7.64	AV	PASS
V	2310.00	34.74	-2.81	31.93	54.00	-22.07	AV	PASS
V	2390.00	34.72	-2.69	32.03	54.00	-21.97	AV	PASS
V	**2400.00	48.23	-2.68	45.55	54.00	-8.45	AV	PASS

Test Mode: 802.11n(HT40)					CH High: 2452 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.14	-2.56	44.58	74.00	-29.42	PK	PASS
H	2500.00	51.52	-2.54	48.98	74.00	-25.02	PK	PASS
V	**2483.50	49.04	-2.56	46.48	74.00	-27.52	PK	PASS
V	2500.00	50.23	-2.54	47.69	74.00	-26.31	PK	PASS
H	**2483.50	36.38	-2.56	33.82	54.00	-20.18	AV	PASS
H	2500.00	40.36	-2.54	37.82	54.00	-16.18	AV	PASS
V	**2483.50	38.73	-2.56	36.17	54.00	-17.83	AV	PASS
V	2500.00	40.86	-2.54	38.32	54.00	-15.68	AV	PASS

Remark:




1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

5.8 Radiated Spurious Emissions

5.8.1 Test Requirement

Test Requirement	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. Note: 1) Field Strength (dBµV/m) = 20*log[Field Strength (µV/m)]. 2) In the emission tables above, the tighter limit applies at the band edges. 3) For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit. 4) For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).		
Test Method	ANSI C63.10-2020 section 6.6.4		

5.8.2 Test Setup Diagram



5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power.

Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.8.4 Test Data

PASS.

Please to see the following pages.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

For test of 30MHz-1GHz, during the test, pre-scan all modes, only the worst case is recorded in the report.

For test of 1GHz-25GHz, during the test, pre-scan all test modes, and found the 802.11n(HT20) is worse case, the report only record this mode.

Radiated Emission Test Data (30-1000MHz)

Test Site:	966 Chamber #1	Polarization:	Horizontal
Distance:	3m	Test Mode:	TM1/ CH Middle




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	44.2752	31.25	-14.38	16.87	40.00	-23.13	QP	P	
2	125.0066	33.77	-17.21	16.56	43.50	-26.94	QP	P	
3	176.8878	36.99	-16.74	20.25	43.50	-23.25	QP	P	
4	260.1444	36.33	-13.06	23.27	46.00	-22.73	QP	P	
5 *	319.9370	35.56	-11.56	24.00	46.00	-22.00	QP	P	
6	467.2349	32.43	-8.90	23.53	46.00	-22.47	QP	P	

Note: Level = Reading + Factor
Margin = Level - Limit

Radiated Emission Test Data (30-1000MHz)

Test Site:	966 Chamber #1	Polarization:	Vertical
Distance:	3m	Test Mode:	TM1/ CH Middle



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	44.4308	43.38	-14.35	29.03	40.00	-10.97	QP	P	
2	144.3348	39.81	-18.35	21.46	43.50	-22.04	QP	P	
3	245.9509	34.76	-13.47	21.29	46.00	-24.71	QP	P	
4	407.5145	30.45	-9.80	20.65	46.00	-25.35	QP	P	
5	651.9417	31.96	-5.75	26.21	46.00	-19.79	QP	P	
6	922.5157	30.93	-1.73	29.20	46.00	-16.80	QP	P	

Note: Level = Reading + Factor
Margin = Level - Limit

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH Low: 2412 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4824.61	42.30	4.74	47.04	74.00	-26.97	PK	PASS
V	7236.36	33.10	9.84	42.94	74.00	-31.06	PK	PASS
V	9648.68	29.27	13.18	42.45	74.00	-31.56	PK	PASS
V	12060.04	*	*	*	74.00	*	PK	PASS
V	14472.26	*	*	*	74.00	*	PK	PASS
V	16884.20	*	*	*	74.00	*	PK	PASS
H	4824.34	41.97	4.74	46.71	74.00	-27.30	PK	PASS
H	7236.86	35.58	9.84	45.42	74.00	-28.59	PK	PASS
H	9648.76	30.45	13.18	43.63	74.00	-30.38	PK	PASS
H	12060.86	*	*	*	74.00	*	PK	PASS
H	14472.44	*	*	*	74.00	*	PK	PASS
H	16884.22	*	*	*	74.00	*	PK	PASS
V	4824.79	31.58	4.74	36.32	54.00	-17.68	AV	PASS
V	7236.43	22.28	9.84	32.12	54.00	-21.88	AV	PASS
V	9648.31	19.33	13.18	32.51	54.00	-21.49	AV	PASS
V	12060.98	*	*	*	54.00	*	AV	PASS
V	14472.26	*	*	*	54.00	*	AV	PASS
V	16884.29	*	*	*	54.00	*	AV	PASS
H	4824.40	30.16	4.74	34.90	54.00	-19.11	AV	PASS
H	7236.86	23.13	9.84	32.97	54.00	-21.04	AV	PASS
H	9648.76	19.12	13.18	32.30	54.00	-21.71	AV	PASS
H	12060.86	*	*	*	54.00	*	AV	PASS
H	14472.44	*	*	*	54.00	*	AV	PASS
H	16884.22	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH Middle: 2437 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4874.68	40.82	4.90	45.72	74.00	-28.28	PK	PASS
V	7311.89	33.07	9.83	42.90	74.00	-31.11	PK	PASS
V	9748.54	28.49	13.21	41.70	74.00	-32.31	PK	PASS
V	12185.12	*	*	*	74.00	*	PK	PASS
V	14622.82	*	*	*	74.00	*	PK	PASS
V	17059.10	*	*	*	74.00	*	PK	PASS
H	4874.03	41.09	4.90	45.99	74.00	-28.02	PK	PASS
H	7311.58	35.03	9.83	44.86	74.00	-29.15	PK	PASS
H	9748.84	30.46	13.21	43.67	74.00	-30.34	PK	PASS
H	12185.59	*	*	*	74.00	*	PK	PASS
H	14622.97	*	*	*	74.00	*	PK	PASS
H	17059.35	*	*	*	74.00	*	PK	PASS
V	4874.10	31.91	4.90	36.81	54.00	-17.20	AV	PASS
V	7311.95	23.46	9.83	33.29	54.00	-20.71	AV	PASS
V	9748.01	18.46	13.21	31.67	54.00	-22.33	AV	PASS
V	12185.91	*	*	*	54.00	*	AV	PASS
V	14622.05	*	*	*	54.00	*	AV	PASS
V	17059.12	*	*	*	54.00	*	AV	PASS
H	4874.03	30.53	4.90	35.43	54.00	-18.58	AV	PASS
H	7311.58	22.93	9.83	32.76	54.00	-21.25	AV	PASS
H	9748.84	19.74	13.21	32.95	54.00	-21.06	AV	PASS
H	12185.59	*	*	*	54.00	*	AV	PASS
H	14622.97	*	*	*	54.00	*	AV	PASS
H	17059.35	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: 802.11n(HT20)					CH High: 2462 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4924.99	42.34	5.05	47.39	74.00	-26.62	PK	PASS
V	7386.93	34.32	9.83	44.15	74.00	-29.86	PK	PASS
V	9848.80	29.37	13.24	42.61	74.00	-31.40	PK	PASS
V	12310.23	*	*	*	74.00	*	PK	PASS
V	14772.31	*	*	*	74.00	*	PK	PASS
V	17234.85	*	*	*	74.00	*	PK	PASS
H	4924.10	41.19	5.05	46.24	74.00	-27.76	PK	PASS
H	7386.80	34.92	9.83	44.75	74.00	-29.26	PK	PASS
H	9848.58	28.62	13.24	41.86	74.00	-32.15	PK	PASS
H	12310.04	*	*	*	74.00	*	PK	PASS
H	14772.21	*	*	*	74.00	*	PK	PASS
H	17234.12	*	*	*	74.00	*	PK	PASS
V	4924.74	31.79	5.05	36.84	54.00	-17.17	AV	PASS
V	7386.48	24.24	9.83	34.07	54.00	-19.93	AV	PASS
V	9848.98	19.89	13.24	33.13	54.00	-20.88	AV	PASS
V	12310.59	*	*	*	54.00	*	AV	PASS
V	14772.18	*	*	*	54.00	*	AV	PASS
V	17234.30	*	*	*	54.00	*	AV	PASS
H	4924.10	32.56	5.05	37.61	54.00	-16.39	AV	PASS
H	7386.80	23.06	9.83	32.89	54.00	-21.12	AV	PASS
H	9848.58	17.25	13.24	30.49	54.00	-23.52	AV	PASS
H	12310.04	*	*	*	54.00	*	AV	PASS
H	14772.21	*	*	*	54.00	*	AV	PASS
H	17234.12	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document “8332EU013009W-AA.PDF”

ANNEX B EXTERNAL PHOTOS


Please refer to the document “8332EU013009W-AB.PDF”

ANNEX C INTERNAL PHOTOS

Please refer to the document “8332EU013009W-AC.PDF”

ANNEX E TEST DATA

Please refer to the document “8332EU013009W-AE.PDF”



STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---