

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

BT:

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type: FPC Antenna

Antenna gain: 3.76dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	DH5	1.96	1.5±1	2.5	1.778	3.76	2.38	0.0008	1
2441		0.88	1.5±1	2.5	1.778	3.76	2.38	0.0008	1
2480		-1.01	-1±1	0	1.000	3.76	2.38	0.0005	1
2402	2DH5	5.09	7±1	8	6.310	3.76	2.38	0.0030	1
2441		2.82	7±1	8	6.310	3.76	2.38	0.0030	1
2480		1.45	7±1	8	6.310	3.76	2.38	0.0030	1
2402	3DH5	4.97	7±1	8	6.310	3.76	2.38	0.0030	1
2441		2.71	7±1	8	6.310	3.76	2.38	0.0030	1
2480		1.3	7±1	8	6.310	3.76	2.38	0.0030	1

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)
2402	BLE 1M	4.5	4±1	5	3.162	3.76	2.38	0.0015	1
2440		2.23	2±1	3	1.995	3.76	2.38	0.0009	1
2480		0.55	1±1	2	1.585	3.76	2.38	0.0007	1
2402	BLE 2M	4.38	4±1	5	3.162	3.76	2.38	0.0015	1
2440		2.11	2±1	3	1.995	3.76	2.38	0.0009	1
2480		0.47	1±1	2	1.585	3.76	2.38	0.0007	1

WIFI 2.4G/5G:

Operation Frequency: 2412MHz-2462MHz; 5180MHz-5240MHz; 5260MHz~5320MHz;
5500MHz~5700MHz; 5745MHz-5825MHz;

Antenna Type: FPC Antenna

Antenna gain:

WIFI ANT: 2400-2500MHz-- 3.76dBi;
5150-5850 MHz-- 4.9 dBi

R=20cm

Maximum Single sources

Band	Max Conducted	Antenna	Separation distance (cm)	Evaluation result	Power density Limits	Verdict
	(dBm)	Gain (dBi)		(mW/cm ²)	(mW/cm ²)	
Wi-Fi 2.4G	17.12	3.76	20	0.024362	1	PASS
Wi-Fi 5.2G	15.04	4.9	20	0.019621	1	PASS
Wi-Fi 5.3G	14.89	4.9	20	0.018955	1	PASS
Wi-Fi 5.6G	14.52	4.9	20	0.017407	1	PASS
Wi-Fi 5.8G	14.77	4.9	20	0.018438	1	PASS

NFC

Operation Frequency: ASK: 13.56MHz

Antenna Type: Induction coil

R=20cm

Transmit power:

Frequency (MHz)	EIRP power (dBuV/m)	EIRP power (dBm)
13.56	67.98	-27.22

$$\text{EIRP} = \text{E} - 104.8 + 20 \log(D)$$

Channel Freq. (MHz)	modulation	EIRP power	Tune-up power (dBm)	Max		Evaluation result	Power density Limits
		(dBm)		tune-up power			
				(dBm)	(dBm)	(mW)	(mW/cm2)
13.56	ASK	-27.22	-27±1	-26	0.003	0.0000005	0.98

Maximum multi-sources

Mode	Maximum Single sources Evaluation result	Maximum Single sources Power density Limits	Maximum multi-sources Evaluation result	Maximum multi-sources Power density Limits	Verdict
LTE Band 12	0.13858944	0.466	0.32	1	PASS
BT	0.003	1			
WIFI 5G	0.019621	1			
NFC	0.0000005	0.98			

Maximum multi-sources

Mode	Maximum Single sources Evaluation result	Maximum Single sources Power density Limits	Maximum multi-sources Evaluation result	Maximum multi-sources Power density Limits	Verdict
LTE Band 12	0.13858944	0.466	0.32	1	PASS
WIFI 2.4G	0.024362	1			
NFC	0.0000005	0.98			

Note:

1. NO simultaneous transmissions are possible for this device of Wi-Fi 2.4G + BT.
2. NO simultaneous transmissions are possible for this device of Wi-Fi 5G + Wi-Fi 2.4G.
3. LTE Band 12 results are from FCC ID: 2APJ4-SLM750VA.

Signature:

Date: 2025-08-05



NAME AND TITLE (Please print or type): Alex/Manager

COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China