



Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community,
Fenghuang Street, Guangming District, Shenzhen, China

RF Exposure evaluation

Report Reference No.....: GRCTR250702041-04

FCC ID.....: 2BRL9-PROGIC

Compiled by

(position+printed name+signature)..: Testing Engineer Jimmy Wang

Supervised by

(position+printed name+signature)..: Project Engineer Kelley Zhang

Approved by

(position+printed name+signature)..: Manager Sam Wang

Date of issue.....: Jul. 31, 2025

Testing Laboratory Name.....: Shenzhen GUOREN Certification Technology Service Co., Ltd.

Address.....: 101#, Building K & Building T, The Second Industrial Zone,
Jiazitang Community, Fenghuang Street, Guangming District,
Shenzhen, China

Applicant's name.....: Prodig Tecnologia e Comunicacao LTDA

Address.....: Rodovia Jose Carlos Daux, n 500 Edificio Techno Towers - Torre II,
1 andar Joao Paulo Cep 88030-000 Florianopolis SC Brasil

Test specification.....:

Standard.....: 47CFR §2.1091
KDB447498 D01 v06

Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Prodig Player 2

Trade Mark.....: /

Manufacturer.....: Prodig Tecnologia e Comunicacao LTDA

Model/Type reference.....: Prodig Player 2

Listed Models: /

Hardware Version: V1.0

Software Version.....: V1.0

Ratings.....: DC 5V From External Circuit

Result.....: PASS



TEST REPORT

Equipment under Test : Progic Player 2

Model /Type : Progic Player 2

Listed Models : /

Applicant : **Progic Tecnologia e Comunicacao LTDA**

Address : Rodovia Jose Carlos Daux, n 500 Edificio Techno Towers - Torre II, 1 andar Joao Paulo Cep 88030-000 Florianopolis SC Brasil

Manufacturer : **Progic Tecnologia e Comunicacao LTDA**

Address : Rodovia Jose Carlos Daux, n 500 Edificio Techno Towers - Torre II, 1 andar Joao Paulo Cep 88030-000 Florianopolis SC Brasil

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1. General Remarks	4
1.2. Product Description	4
1.3. Equipment Under Test	5
1.4. Short description of the Equipment under Test (EUT)	5
1.5. EUT configuration	5
1.6. Modifications	5
2. TEST ENVIRONMENT	6
2.1. Address of the test laboratory	6
2.2. Test Facility	6
2.3. Environmental conditions	6
2.4. Statement of the measurement uncertainty	6
3. METHOD OF MEASUREMENT	8
3.1. Applicable Standard	8
3.2. Limit	8
3.3. MPE Calculation Method	8
3.4. Antenna Information	9
3.5. Manufacturing Tolerance	9
4. EVALUATION RESULT	12
5. CONCLUSION	12

1. SUMMARY

1.1. General Remarks

Date of receipt of test sample	:	Jul. 08, 2025
Testing commenced on	:	Jul. 08, 2025
Testing concluded on	:	Jul. 31, 2025

1.2. Product Description

Product Name:	Progic Player 2			
Model/Type reference:	Progic Player 2			
Listed Models:	/			
Power supply:	DC 5V From External Circuit			
Adapter information:	M/N:GJ15WD-0500200UW Input:100-240V~ 50/60Hz 0.5A Output:5.0V== 2.0A 10.0W			
Testing sample ID:	GRCTR250702041-1# (Engineer sample), GRCTR250702041-2# (Normal sample)			
Bluetooth				
Supported type:	Bluetooth low Energy			
Modulation:	GFSK			
Operation frequency:	2402MHz to 2480MHz			
Channel number:	40			
Channel separation:	2 MHz			
Antenna type:	PCB antenna			
Antenna gain*(Supplied by the customer):	2.83 dBi			
WIFI 2.4G:				
Supported type:	802.11b/802.11g/802.11n(H20) /802.11n(H40)			
Modulation:	802.11b: DSSS 802.11g/802.11n(H20) /802.11n(H40): OFDM			
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz			
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40): 7			
Channel separation:	5MHz			
Antenna type:	External antenna(Ant 1)+Iron antenna(Ant 2)			
Antenna gain*(Supplied by the customer):	Ant 1: 2.83 dBi Ant 2: 2.83 dBi			
WIFI 5G				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n 802.11ac	802.11n 802.11ac	802.11ac	N/A
Operation frequency:	5180MHz-	5190MHz-	5210MHz	N/A

	5240MHz	5230MHz		
Modulation:	OFDM	OFDM	OFDM	N/A
Channel number:	9	4	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
Antenna type:	External antenna(Ant 1)+Iron antenna(Ant 2)			
Antenna gain*(Supplied by the customer):	Ant 1: 3.00 dBi Ant 2: 3.00 dBi			
Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.				

1.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☒ 24 V DC
		☐ Other (specified in blank below)	

/

1.4. Short description of the Equipment under Test (EUT)

This is a Prodig Player 2.

For more details, refer to the user's manual of the EUT.

1.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

☐ /	M/N: /
	Manufacturer: /

1.6. Modifications

No modifications were implemented to meet testing criteria.

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 920798 Designation Number: CN1304

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6202.01

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27264 CAB identifier: CN0115

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

CNAS-Lab Code: L15631

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

Test Items	Measurement Uncertainty	Notes
Max output power	0.54 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 v06: RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION
POLICIES FOR MOBILE AND PORTABLE DEVICES

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

3.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT	/	PCB ANT	2.83 dBi for 2400-2500MHz	
2.4G WIFI	/	External antenna(Ant 1)+Iron antenna(Ant 2)	Ant 1: 2.83 dBi for 2400-2500MHz Ant 2: 2.83 dBi for 2400-2500MHz	
5G WIFI	/	External antenna(Ant 1)+Iron antenna(Ant 2)	Ant 1: 3.00 dBi for 5180MHz-5240MHz Ant 2: 3.00 dBi for 5180MHz-5240MHz	

3.5. Manufacturing Tolerance

BT(Peak)			
GFSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	0.0	0.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
π /4QPSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	0.0	0.0	0.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	1.0	1.0	1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

For ANT1

2.4GWIFI(Peak)			
802.11b			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11g			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11n HT20			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11n HT40			
Channel	Channel 03	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5GHz WLAN U-NII 1

IEEE 802.11a (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

IEEE 802.11n HT40 (Average)			
Frequency(MHz)	5190		5230
Target (dBm)	12.0		12.0
Tolerance ± (dB)	1.0		1.0
IEEE 802.11ac VHT20 (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Frequency(MHz)	5190		5230
Target (dBm)	12.0		12.0
Tolerance ± (dB)	1.0		1.0
IEEE 802.11ac VHT80 (Average)			
Frequency(MHz)	5210		
Target (dBm)	12.0		
Tolerance ± (dB)	1.0		

For ANT2

2.4GWIFI(Peak)			
802.11b			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11g			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11n HT20			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11n HT40			
Channel	Channel 03	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5GHz WLAN U-NII 1			
IEEE 802.11a (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	12.0	12.0	12.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	13.0	13.0	13.0
Tolerance ± (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Frequency(MHz)	5190		5230
Target (dBm)	12.0		12.0
Tolerance ± (dB)	1.0		1.0
IEEE 802.11ac VHT20 (Average)			

Frequency(MHz)	5180	5200	5240
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Frequency(MHz)	5190	5230	
Target (dBm)	12.0	12.0	
Tolerance $\pm$ (dB)	1.0	1.0	
IEEE 802.11ac VHT80 (Average)			
Frequency(MHz)	5210		
Target (dBm)	12.0		
Tolerance $\pm$ (dB)	1.0		

For MIMO:

2.4GWIFI

802.11n HT20			
Channel	Channel 01	Channel 6	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
802.11n HT40			
Channel	Channel 03	Channel 6	Channel 9
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5GHz WLAN U-NII 1

IEEE 802.11n HT20 (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Average)			
Frequency(MHz)	5190	5230	
Target (dBm)	16.0	16.0	
Tolerance $\pm$ (dB)	1.0	1.0	
IEEE 802.11ac VHT20 (Average)			
Frequency(MHz)	5180	5200	5240
Target (dBm)	16.0	16.0	16.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ac VHT40 (Average)			
Frequency(MHz)	5190	5230	
Target (dBm)	16.0	16.0	
Tolerance $\pm$ (dB)	1.0	1.0	
IEEE 802.11ac VHT80 (Average)			
Frequency(MHz)	5210		
Target (dBm)	16.0		
Tolerance $\pm$ (dB)	1.0		

4. Evaluation Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BLE	2.0	1.5849	2.83	1.9187	0.0006	1.0000
2.4G WIFI ANT 1	15.0	31.6228	2.83	1.9187	0.0121	1.0000
2.4G WIFI ANT 2	15.0	31.6228	2.83	1.9187	0.0121	1.0000
5G WIFI ANT 1	14.0	25.1189	3.00	1.9953	0.0100	1.0000
5G WIFI ANT 2	14.0	25.1189	3.00	1.9953	0.0100	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

Simultaneous Evaluation

BT MPE (mW/cm ²)	2.4GWIFI ANT 1 MPE (mW/cm ²)	2.4GWIFI ANT 2 MPE (mW/cm ²)	MPE	MPE Limits
0.0006	0.0121	0.0121	0.0248	1.0000

5. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....**End of Report**.....