



TEST REPORT

Reference No...... : WTF25F07194112W001
FCC ID : 2BRMV-P230
Applicant..... : AQUAGEM TECHNOLOGY LIMITED
Address..... : FLAT/RM H 19/FMAXGRAND PLAZA3 TAI YAU STREETSAN
POKONG KLHONG KONG
Manufacturer : Aquagem Manufacturing Limited
Address..... : NO.15, 101, 16, 401, 501, No.193, Jinlong Road, Dalong Street,
Panyu District, Guangzhou
Product Name..... : Surfing SwimJet
Model No...... : Refer to section 3.2
Test specification..... : FCC CFR47 Part 15 Subpart C (Section 15.247)
Date of Receipt sample : 2025-07-23
Date of Test..... : 2025-07-23 to 2025-07-28
Date of Issue..... : 2025-08-29
Test Report Form No. : WEW-15247A-01B
Test Result..... **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Foshan) Co., Ltd.

Address: 1/F., Building 19, Sunlink Machinery City, Xingye 4 Road,
Guanglong Industrial Park, Chihua Neighborhood Committee, Chencun,
Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398

Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Tested by:

Jess Chen

Jess Chen

Approved by:

Danny Zhou

Danny Zhou



1 Revision History

Test Report No.	Date of Issue	Description	Status
WTF25F07194112W001	2025-08-29	Original	Valid

WALTEK



2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T.....	4
3.2 MODEL LIST.....	4
3.3 TECHNICAL CHARACTERISTICS OF EUT.....	5
3.4 STANDARDS APPLICABLE FOR TESTING.....	5
3.5 TEST FACILITY.....	6
3.6 SUBCONTRACTED.....	6
3.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
3.8 DISCLAIMER.....	6
4 EUT SETUP AND TEST MODE.....	7
5 EQUIPMENT USED DURING TEST.....	8
5.1 EQUIPMENT LIST.....	9
5.2 TEST SOFTWARE.....	9
5.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	9
5.4 MEASUREMENT UNCERTAINTY.....	9
6 SUMMARY OF TEST RESULT.....	10
6.1 ANTENNA REQUIREMENT.....	11
6.2 RADIATED SPURIOUS EMISSIONS.....	12
6.3 POWER SPECTRAL DENSITY.....	22
6.4 DTS BANDWIDTH.....	27
6.5 RF OUTPUT POWER.....	32
6.6 OUT OF BAND EMISSIONS.....	38
6.7 CONDUCTED EMISSIONS.....	52
7 PHOTOGRAPHS TEST SETUP.....	56
7.1 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP.....	56
7.2 PHOTOGRAPHS – CONDUCTED EMISSION TEST SETUP.....	57
8 PHOTOGRAPHS – EUT CONSTRUCTIONAL DETAILS.....	58



3 General Information

3.1 General Description of E.U.T

Product Name : Surfing SwimJet

Model No. : Refer to section 3.2

Model Description : All models have same electric circuit, PCB, WiFi module and Bluetooth module, the difference among them are the model name, flow parameters and external water pump.

Series “iGarden SwimJet P Series” and “InverJet” are identical except the brand.

Series “InverJet”, “InverJet H” and “InverJet V” are identical except the external water pump.

Therefore the full tests were performed on model P230.

Rating : AC 100-120V, 60Hz

Battery Capacity : ---

Power Adapter : ---

3.2 Model List

Series	Model No.	Power (W)	Other Difference
iGarden SwimJet P Series	P450	400	Identical except rating parameters.
	P720	600	
	P900	900	
	P1100	1200	
InverJet	SJ100, P100	400	Identical except mode name or rating parameters.
	SJ160, P160	600	
	SJ200, P200	900	
	SJ230, P230	1250	
	SJ240, P240	1250	
InverJet H	SJH100, H100	400	Identical except mode name or rating parameters.
	SJH160, H160	600	
	SJH200, H200	900	
	SJH240, H240	1250	
InverJet V	SJV100, V100	400	Identical except mode name or rating parameters.
	SJV160, V160	600	
	SJV200, V200	900	
	SJV240, V240	1250	



3.3 Technical Characteristics of EUT

Support Standards	: 802.11b, 802.11g, 802.11n
Frequency Range	: 2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40)
RF Output Power	: 16.35dBm (Conducted)
Modulation	: 802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM (BPSK/QPSK/16QAM/64QAM)
Quantity of Channels	: 11 for 802.11b/g/n(HT20); 8 for 802.11n(HT40)
Channel Separation	: 5MHz
Type of Antenna	: FPC Antenna
Antenna Gain	: -2.97dBi

3.4 Standards Applicable for Testing

The tests were performed according to following standards:

FCC Rules Part 15.247	Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
558074 D01 15.247 Meas Guidance v05r02	Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The FCC Rules
662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band
ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices



3.5 Test Facility

The test facility has a test site registered with the following organizations:

- **ISED – Registration No.: 21895**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Innovation, Science and Economic Development Canada (ISED). The acceptance letter from the ISED is maintained in our files. Registration ISED number: 21895.

- **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106.

- **FCC – Designation No.: CN5034**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No. CN5034.

- **NVLAP – Lab Code: 600191-0**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

3.6 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

3.7 Abnormalities from Standard Conditions

None.

3.8 Disclaimer

The antenna gain information is provided by the customer. The laboratory is not responsible for the accuracy of the antenna gain information.



4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List

Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz, High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz, High:2452MHz

Test Conditions

Temperature:	22~25°C
Relative Humidity:	50~55%
Atmospheric pressure:	101.8kPa



5 Equipment Used during Test

☐ Conducted Emissions 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESR3	102423	2025-01-06	2026-01-05
2.	LISN	R&S	ENV216	101343	2025-01-06	2026-01-05
3.	Cable	HUBER+SUHNER	CBL2-NN-6M	223NN624	2025-01-06	2026-01-05
4.	Switch	CD	RSU-A4	RSUA4008	2025-01-06	2026-01-05

☒ Conducted Emissions 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESCI	101178	2025-01-06	2026-01-05
2.	LISN	R&S	ENV216	101215	2025-01-07	2026-01-06
3.	Cable	LMR195UF-BMNM-5.00M	Times Microwave Systems	---	2025-01-08	2026-01-07
4.	Switch	ESE	RSU/M2	---	2025-01-06	2026-01-05

☐ Conducted Emissions 3#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	EMI Test Receiver	R&S	ESR3	102842	2025-01-06	2026-01-05
2.	LISN	R&S	ENV216	101542	2025-01-06	2026-01-05
3.	Cable	YIHENG	LMR195UF-NMNM-2.5	---	2025-01-06	2026-01-05
4.	Manual RF Switch	YIHENG	SW-2	RSU0402	2025-01-06	2026-01-05

☒ Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	3m Semi-anechoic Chamber	CHANGCHUANG	9m×6m×6m	-	2024-01-05	2027-01-04
2.	EMI Test Receiver	R&S	ESR7	102454	2025-01-06	2026-01-05
3.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2025-01-06	2026-01-05
4.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	2025-01-06	2026-01-05
5.	Trilog Broadband Antenna	SCHWARZBECK	VULB9162	9162-117	2025-01-12	2026-01-11
6.	Coaxial Cable (below 1GHz)	Times Microwave Systems	RG223-NMNM-10M	-	2025-01-07	2026-01-06
7.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	01561	2025-01-13	2026-01-12
9.	Coaxial Cable (above 1GHz)	Times-Microwave	CBL5-NN	-	2025-01-06	2026-01-05
10.	Broadband Preamplifier (Above 1GHz)	Lunar E M	LNA1G18-40	20160501002	2025-01-06	2026-01-05



☒ RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Cal Due Date
1.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2025-01-06	2026-01-05
2.	EXG Analog Signal Generator	Agilent	N5181A	MY48180720	2025-01-06	2026-01-05
3.	RF Control Unit	CHANGCHUANG	JS0806-2	-	2025-01-08	2026-01-07

5.1 Equipment List

☐: Not Used

☒: Used

5.2 Test Software

Description	Manufacturer	Model	Version
EMI Test Software (Conducted Emission 1#)	FARATRONIC	EZ-EMC	EMEC-3A1
EMI Test Software (Conducted Emission 2#)	FARATRONIC	EZ-CON	FARAD-3A1.1+
EMI Test Software (Conducted Emission 3#)	FARATRONIC	EZ-EMC	EMC-CON 3A1.1+
EMI Test Software (Radiated Emission)	FARATRONIC	EZ-EMC	RA-03A1-2
RF Conducted Test Software	TONSCEND	JS1120-2	V2.6

5.3 Special Accessories and Auxiliary Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.
1.	/	/	/	/

5.4 Measurement Uncertainty

Parameter	Uncertainty
RF Output Power	±2.2dB
Occupied Bandwidth	±1.5%
Conducted Emission	±2.6dB
Transmitter Spurious Emission	±3.8dB (for 25MHz-1GHz)
	±5.0dB (for 1GHz-18GHz)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



6 Summary of Test Result

Test Items	FCC Rules	Result
Antenna Requirement	§15.203; §15.247(b)(4)(i)	Compliant
Restricted Band of Operation	§15.205	Compliant
Conducted Emissions	§15.207(a)	Compliant
Radiated Spurious Emissions	§15.209(a)	Compliant
Power Spectral Density	§15.247(e)	Compliant
DTS Bandwidth	§ 15.247(a)(2)	Compliant
RF Output Power	§15.247(b)(3)	Compliant
Band edge (Out of Band Emissions)	§15.247(d)	Compliant

Remark:

Pass Test item meets the requirement

Fail Test item does not meet the requirement

N/A Test case does not apply to the test object

WALTEK




6.1 Antenna Requirement

6.1.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

6.1.2 Evaluation Information

The EUT has an External monopole sub-antenna, the gain is -2.97dBi, fulfil the requirement of this section.





6.2 Radiated Spurious Emissions

6.2.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

6.2.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

The test setup for emission measurement below 30MHz.






The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.





6.2.3 Spectrum Analyzer Setup

9KHz-30MHz

RBW=10kHz

VBW=30kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak

30MHz-1GHz

RBW=120kHz

VBW=300kHz

Sweep time=Auto

Trace=Max hold

Detector function=peak, QP

Above 1GHz

RBW=1MHz

VBW=3MHz(Peak), 10MHz(AV)

Sweep time=Auto

Trace=Max hold

Detector function=peak, AV

6.2.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Corr. Factor}$$

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$



6.2.5 Test Results

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.


Test Frequency: Below 1GHz

Test Mode: 802.11b (worst case)

Test Channel Low Channel

Polarization Vertical

Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	45.5029	-1.08	14.07	12.99	40.00	-27.01	peak	
2	51.9522	-0.11	14.36	14.25	40.00	-25.75	peak	
3	301.7396	0.93	15.80	16.73	46.00	-29.27	peak	
4	374.7540	0.26	17.96	18.22	46.00	-27.78	peak	
5	587.8735	0.69	22.46	23.15	46.00	-22.85	peak	
6	923.1629	1.54	27.33	28.87	46.00	-17.13	peak	



Test Channel Low Channel

Polarization Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	45.6307	-1.11	14.06	12.95	40.00	-27.05	peak	
2	52.8155	-1.98	14.33	12.35	40.00	-27.65	peak	
3	224.8344	-0.21	14.39	14.18	46.00	-31.82	peak	
4	380.7143	-0.25	17.97	17.72	46.00	-28.28	peak	
5	576.6443	0.11	22.82	22.93	46.00	-23.07	peak	
6	996.1502	0.80	27.90	28.70	54.00	-25.30	peak	



Test Channel Middle Channel

Polarization


Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	53.6367	0.81	14.30	15.11	40.00	-24.89	peak	
2	104.0971	0.19	12.95	13.14	43.50	-30.36	peak	
3	285.4768	0.44	15.35	15.79	46.00	-30.21	peak	
4	420.7278	0.84	18.54	19.38	46.00	-26.62	peak	
5	565.4313	1.75	22.60	24.35	46.00	-21.65	peak	
6	959.4669	2.37	27.65	30.02	46.00	-15.98	peak	



Test Channel Middle Channel Polarization Horizontal




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	47.6252	-0.72	14.36	13.64	40.00	-26.36	peak	
2	108.9522	-0.39	12.80	12.41	43.50	-31.09	peak	
3	246.2962	0.74	14.51	15.25	46.00	-30.75	peak	
4	428.1694	0.77	18.79	19.56	46.00	-26.44	peak	
5	520.3406	-0.15	20.86	20.71	46.00	-25.29	peak	
6	826.6234	0.00	26.26	26.26	46.00	-19.74	peak	



Test Channel High Channel

Polarization Vertical




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	57.2918	-0.40	14.37	13.97	40.00	-26.03	peak	
2	92.8523	0.93	11.05	11.98	43.50	-31.52	peak	
3	293.3927	0.67	15.63	16.30	46.00	-29.70	peak	
4	439.2711	0.57	19.24	19.81	46.00	-26.19	peak	
5	706.2044	2.20	24.09	26.29	46.00	-19.71	peak	
6	916.0687	2.47	27.05	29.52	46.00	-16.48	peak	



Test Channel High Channel

Polarization Horizontal



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	43.9042	-0.79	14.19	13.40	40.00	-26.60	peak	
2	52.2079	-0.36	14.36	14.00	40.00	-26.00	peak	
3	320.8357	0.31	15.80	16.11	46.00	-29.89	peak	
4	476.8349	-0.09	19.99	19.90	46.00	-26.10	peak	
5	699.0594	0.34	24.25	24.59	46.00	-21.41	peak	
6	973.3608	1.46	27.71	29.17	54.00	-24.83	peak	

**Test Frequency: Above 1GHz****Test Mode: 802.11b (worst case)**

Frequency (MHz)	Reading (dBμV/m)	Detector	Polar (H/V)	Corrected Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel							
4824	42.18	PK	H	-3.59	38.59	74	-35.41
4824	32.28	AV	H	-3.59	28.69	54	-25.31
7236	45.07	PK	H	3.07	48.14	74	-25.86
7236	36.46	AV	H	3.07	39.53	54	-14.47
4824	40.26	PK	V	-3.46	36.8	74	-37.2
4824	31.69	AV	V	-3.46	28.23	54	-25.77
7236	45.44	PK	V	2.97	48.41	74	-25.59
7236	36.97	AV	V	2.97	39.94	54	-14.06
Middle Channel							
4874	42.8	PK	H	-3.41	39.39	74	-34.61
4874	32.41	AV	H	-3.41	29	54	-25.00
7311	44.92	PK	H	3.23	48.15	74	-25.85
7311	35.71	AV	H	3.23	38.94	54	-15.06
4874	40.88	PK	V	-3.26	37.62	74	-36.38
4874	31.37	AV	V	-3.26	28.11	54	-25.89
7311	44.62	PK	V	3.13	47.75	74	-26.25
7311	35.72	AV	V	3.13	38.85	54	-15.15
High Channel							
4924	42.12	PK	H	-3.24	38.88	74	-35.12
4924	32.28	AV	H	-3.24	29.04	54	-24.96
7386	45.6	PK	H	3.38	48.98	74	-25.02
7386	36.54	AV	H	3.38	39.92	54	-14.08
4924	41.75	PK	V	-3.06	38.69	74	-35.31
4924	32.81	AV	V	-3.06	29.75	54	-24.25
7386	46.95	PK	V	3.28	50.23	74	-23.77
7386	36.57	AV	V	3.28	39.85	54	-14.15

Note: Testing is carried out with frequency range 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



6.3 Power Spectral Density

6.3.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).


6.3.3 Test Result

Test Mode	Test Channel(MHz)	Test Result (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-14.644	8
	2437	-14.518	8
	2462	-14.446	8
802.11g	2412	-15.272	8
	2437	-16.779	8
	2462	-14.710	8
802.11n (HT20)	2412	-15.003	8
	2437	-17.277	8
	2462	-16.258	8
802.11n (HT40)	2422	-17.476	8
	2437	-18.040	8
	2452	-17.312	8




Test plots:


802.11b_Low Channel



802.11b_Middle Channel




802.11b_High Channel







802.11g_Low Channel



802.11g_Middle Channel




802.11g_High Channel







802.11n(HT20)_Low Channel



802.11n(HT20)_Middle Channel




802.11n(HT20)_High Channel







802.11n(HT40)_Low Channel



802.11n(HT40)_Middle Channel



802.11n(HT40)_High Channel





6.4 DTS Bandwidth

6.4.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.4.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


6.4.3 Test Result

Test Mode	Test Channel (MHz)	Test Result (MHz)	Limit (kHz)
802.11b	2412	9.360	≥ 500
	2437	8.840	≥ 500
	2462	9.200	≥ 500
802.11g	2412	16.800	≥ 500
	2437	16.480	≥ 500
	2462	16.520	≥ 500
802.11n (HT20)	2412	17.000	≥ 500
	2437	17.080	≥ 500
	2462	17.080	≥ 500
802.11n (HT40)	2422	35.600	≥ 500
	2437	35.600	≥ 500
	2452	35.600	≥ 500




Test plots:

802.11b_Low Channel



802.11b_Middle Channel




802.11b_High Channel







802.11g_Low Channel



802.11g_Middle Channel




802.11g_High Channel







802.11n(HT20)_Low Channel



802.11n(HT20)_Middle Channel




802.11n(HT20)_High Channel







802.11n(HT40) Low Channel



802.11n(HT40) Middle Channel



802.11n(HT40) High Channel





6.5 RF Output Power

6.5.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.5.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2020 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing $\geq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.



6.5.3 Test Result


Modulation	Test Channel (MHz)	Reading (dBm)	Output Power (mW)	Limit (mW)
802.11b	2412	16.28	42.46	1000
	2437	16.07	40.46	1000
	2462	16.35	43.15	1000
802.11g	2412	14.93	31.12	1000
	2437	12.56	18.03	1000
	2462	14.72	29.65	1000
802.11n (HT20)	2412	14.14	25.94	1000
	2437	12.09	16.18	1000
	2462	13.25	21.13	1000
802.11n (HT40)	2422	13.11	20.46	1000
	2437	13.02	20.04	1000
	2452	13.23	21.04	1000

WALTEK




Test plots:


802.11b_Low Channel









802.11b_Middle Channel






802.11b_High Channel



**802.11g_Low Channel****802.11g_Middle Channel****802.11g_High Channel**

**802.11n(HT20)_Low Channel****802.11n(HT20)_Middle Channel****802.11n(HT20)_High Channel**

**802.11n(HT40)_Low Channel****802.11n(HT40)_Middle Channel****802.11n(HT40)_High Channel**



6.6 Out of Band Emissions

6.6.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

6.6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge,

as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz

for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emissions must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205.



Note that the method of measurement KDB publication number: 913591 may be used for the radiated band edge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1.




6.6.3 Test Result

Radiated Test

802.11b


Test Channel Low Channel

Polarization Horizontal (worst case)





Test Channel High Channel Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	57.45	32.54	89.99	74.00	15.99	peak	
2	2483.500	10.47	32.63	43.10	74.00	-30.90	peak	
3	2483.500	-11.39	32.63	21.24	54.00	-32.76	AVG	
4	2500.000	11.87	32.70	44.57	74.00	-29.43	peak	
5	2500.000	-11.32	32.70	21.38	54.00	-32.62	AVG	

**802.11g****Test Channel**

Low Channel

Polarization

Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	11.16	31.90	43.06	74.00	-30.94	peak	
2	2310.000	-12.26	31.90	19.64	54.00	-34.36	AVG	
3	2390.000	15.95	32.24	48.19	74.00	-25.81	peak	
4	2390.000	-9.63	32.24	22.61	54.00	-31.39	AVG	
5	2400.000	18.73	32.28	51.01	74.00	-22.99	peak	
6	2400.000	-4.38	32.28	27.90	54.00	-26.10	AVG	
7	2412.000	54.03	32.33	86.36	74.00	12.36	peak	



Test Channel High Channel

Polarization

Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	52.39	32.54	84.93	74.00	10.93	peak	
2	2483.500	16.14	32.63	48.77	74.00	-25.23	peak	
3	2483.500	-8.87	32.63	23.76	54.00	-30.24	AVG	
4	2500.000	10.67	32.70	43.37	74.00	-30.63	peak	
5	2500.000	-11.36	32.70	21.34	54.00	-32.66	AVG	



802.11n(HT20)

Test Channel Low Channel

Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	9.54	31.90	41.44	74.00	-32.56	peak	
2	2310.000	-12.26	31.90	19.64	54.00	-34.36	AVG	
3	2390.000	14.17	32.24	46.41	74.00	-27.59	peak	
4	2390.000	-10.13	32.24	22.11	54.00	-31.89	AVG	
5	2400.000	19.50	32.28	51.78	74.00	-22.22	peak	
6	2400.000	-4.97	32.28	27.31	54.00	-26.69	AVG	
7	2412.000	54.18	32.33	86.51	74.00	12.51	peak	



Test Channel High Channel

Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2462.000	52.54	32.54	85.08	74.00	11.08	peak	
2	2483.500	15.64	32.63	48.27	74.00	-25.73	peak	
3	2483.500	-9.01	32.63	23.62	54.00	-30.38	AVG	
4	2500.000	12.13	32.70	44.83	74.00	-29.17	peak	
5	2500.000	-11.31	32.70	21.39	54.00	-32.61	AVG	



802.11n(HT40)

Test Channel Low Channel

Polarization Horizontal (worst case)




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2310.000	9.69	31.90	41.59	74.00	-32.41	peak	
2	2310.000	-12.26	31.90	19.64	54.00	-34.36	AVG	
3	2390.000	13.34	32.24	45.58	74.00	-28.42	peak	
4	2390.000	-9.71	32.24	22.53	54.00	-31.47	AVG	
5	2400.000	20.31	32.28	52.59	74.00	-21.41	peak	
6	2400.000	-5.01	32.28	27.27	54.00	-26.73	AVG	
7	2422.000	46.66	32.38	79.04	74.00	5.04	peak	



Test Channel High Channel

Polarization Horizontal (worst case)



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2452.000	46.30	32.50	78.80	74.00	4.80	peak	
2	2483.500	16.50	32.63	49.13	74.00	-24.87	peak	
3	2483.500	-8.05	32.63	24.58	54.00	-29.42	AVG	
4	2500.000	12.25	32.70	44.95	74.00	-29.05	peak	
5	2500.000	-10.50	32.70	22.20	54.00	-31.80	AVG	




Conducted Test


Test Mode	Channel (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
802.11b	2412	7.71	-42.64	<=-22.29	Pass
	2462	7.71	-47.21	<=-22.29	Pass
802.11g	2412	3.90	-36.53	<=-26.10	Pass
	2462	3.51	-41.72	<=-26.49	Pass
802.11n (HT20)	2412	3.56	-36.17	<=-26.44	Pass
	2462	2.19	-45.87	<=-27.82	Pass
802.11n (HT40)	2422	-0.92	-38.63	<=-30.92	Pass
	2452	-0.83	-42.65	<=-30.83	Pass

Test Plots:

802.11b_Low Channel




802.11b_High Channel






802.11g_Low Channel




802.11g_High Channel






802.11n (HT20)_Low Channel




802.11n (HT20)_High Channel






802.11n (HT40)_Low Channel



802.11n (HT40)_High Channel





6.7 Conducted Emissions


6.7.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

6.7.2 Basic Test Setup Block Diagram



6.7.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal



6.7.4 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.7.5 Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF(Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Measurement} = \text{Reading Level} + \text{Correct Factor}$$

$$\text{Correct Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Measurement} - \text{Limit}$$

WALTEK



6.7.6 Test Result

Test Mode Communication mode(AC 120V/60Hz) **Polarity** Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.3480	33.37	9.70	43.07	59.01	-15.94	QP	
2		0.3480	28.60	9.70	38.30	49.01	-10.71	AVG	
3		0.5280	31.63	9.71	41.34	56.00	-14.66	QP	
4	*	0.5280	27.94	9.71	37.65	46.00	-8.35	AVG	
5		0.6765	29.20	9.71	38.91	56.00	-17.09	QP	
6		0.6765	25.72	9.71	35.43	46.00	-10.57	AVG	
7		1.1310	28.22	9.73	37.95	56.00	-18.05	QP	
8		1.1310	23.63	9.73	33.36	46.00	-12.64	AVG	
9		1.9140	26.55	9.76	36.31	56.00	-19.69	QP	
10		1.9140	20.73	9.76	30.49	46.00	-15.51	AVG	
11		21.2415	20.70	10.22	30.92	60.00	-29.08	QP	
12		21.2415	14.78	10.22	25.00	50.00	-25.00	AVG	

**Test Mode**

Communication mode(AC 120V/60Hz)

Polarity

Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.3480	33.19	9.70	42.89	59.01	-16.12	QP	
2		0.3480	28.47	9.70	38.17	49.01	-10.84	AVG	
3		0.5280	31.21	9.71	40.92	56.00	-15.08	QP	
4	*	0.5280	28.32	9.71	38.03	46.00	-7.97	AVG	
5		0.7845	30.52	9.71	40.23	56.00	-15.77	QP	
6		0.7845	27.12	9.71	36.83	46.00	-9.17	AVG	
7		1.2210	29.44	9.74	39.18	56.00	-16.82	QP	
8		1.2210	24.17	9.74	33.91	46.00	-12.09	AVG	
9		4.9605	21.36	9.86	31.22	56.00	-24.78	QP	
10		4.9605	15.91	9.86	25.77	46.00	-20.23	AVG	
11		21.0210	21.99	10.22	32.21	60.00	-27.79	QP	
12		21.0210	16.25	10.22	26.47	50.00	-23.53	AVG	




7 Photographs Test Setup

7.1 Photographs - Radiated Emission Test Setup

30MHz-1GHz



Above 1GHz





7.2 Photographs – Conducted Emission Test Setup



WALTEK



8 Photographs – EUT Constructional Details

Please refer to “ANNEX” (Reference No. WTF25F07194112W).

=====End of Report=====

WALTEK