

FCC TEST REPORT

For
Zhuhai Xuanqi Trading Co., LTD
Nightstands

Test Model: ELQ551

Additional Model No.: Please Refer to Page 6

Prepared for : Zhuhai Xuanqi Trading Co., LTD
Address : 103, Building 4, Haiyun Garden, Haiyiwanpan, Tangjiawan Town
 : Zhuhai Guangdong China

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou,
 : Guangdong, China

Tel : (+86) 020-39166689
Fax : (+86) 020-39166619
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 19, 2025
Number of tested samples : 2
Sample No. : A250818064-1, A250818064-2
Serial number : Prototype
Date of Test : August 19, 2025 ~ August 26, 2025
Date of Report : August 27, 2025

FCC TEST REPORT
FCC CFR 47 PART 15C

Report Reference No. : LCSC08125010ED

Date Of Issue : August 27, 2025

Testing Laboratory Name : Guangzhou LCS Compliance Testing Laboratory Ltd.

Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Testing Location/ Procedure : Full application of Harmonised standards Partial application of Harmonised standards Other standard testing method

Applicant's Name : Zhuhai Xuanqi Trading Co., LTD

Address : 103, Building 4, Haiyun Garden, Haiyewanpan, Tangjiawan Town Zhuhai Guangdong China

Test Specification

Standard : FCC CFR 47 PART 15C

Test Report Form No. : TRF-4-E-168 A/0

TRF Originator : Guangzhou LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : Nightstands

Trade Mark : N/A

Test Model : ELQ551

Power Supply : Please Refer to Page 6


Result : PASS

Compiled by:



Lifeng Le/ Administrator

Supervised by:



Justin Zhu/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC TEST REPORT

| | |
|---|---|
| Test Report No. : LCSC08125010ED | <u>August 27, 2025</u> Date of issue |
|---|---|

| |
|--|
| Test Model..... : ELQ551 |
| EUT..... : Nightstands |
| Applicant..... : Zhuhai Xuanqi Trading Co., LTD Address..... : 103, Building 4, Haiyun Garden, Haiyewanpan, Tangjiawan Town Zhuhai Guangdong China Telephone..... : / Fax..... : / |
| Manufacturer..... : Zhuhai Xuanqi Trading Co., LTD Address..... : 103, Building 4, Haiyun Garden, Haiyewanpan, Tangjiawan Town Zhuhai Guangdong China Telephone..... : / Fax..... : / |
| Factory..... : Zhuhai Xuanqi Trading Co., LTD Address..... : 103, Building 4, Haiyun Garden, Haiyewanpan, Tangjiawan Town Zhuhai Guangdong China Telephone..... : / Fax..... : / |

| | |
|--------------------|-------------|
| Test Result | PASS |
|--------------------|-------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

| Report Version | Issue Date | Revision Content | Revised By |
|----------------|-----------------|------------------|------------|
| 000 | August 27, 2025 | Initial Issue | -- |
| | | | |
| | | | |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. GENERAL INFORMATION..... | 6 |
| 1.1 Description of Device (EUT)..... | 6 |
| 1.2 Support equipment List | 7 |
| 1.3 External I/O Cable | 7 |
| 1.4 Description of Test Facility | 7 |
| 1.5 Statement of the Measurement Uncertainty | 8 |
| 1.6 Measurement Uncertainty | 8 |
| 1.7 Description of Test Modes..... | 8 |
| 2. TEST METHODOLOGY | 9 |
| 2.1 EUT Configuration | 9 |
| 2.2 EUT Exercise..... | 9 |
| 2.3 General Test Procedures..... | 9 |
| 2.3.1 Conducted Emissions | 9 |
| 2.3.2 Radiated Emissions | 9 |
| 2.4. Test Sample..... | 9 |
| 3. SYSTEM TEST CONFIGURATION..... | 10 |
| 3.1 Justification | 10 |
| 3.2 EUT Exercise Software..... | 10 |
| 3.3 Special Accessories | 10 |
| 3.4 Block Diagram/Schematics | 10 |
| 3.5 Equipment Modifications..... | 10 |
| 3.6 Test Setup..... | 10 |
| 4. SUMMARY OF TEST EQUIPMENT..... | 11 |
| 5. SUMMARY OF TEST RESULT..... | 12 |
| 6. POWER LINE CONDUCTED MEASUREMENT | 13 |
| 7. RADIATED EMISSION MEASUREMENT..... | 16 |
| 7.1. Block Diagram of Test Setup | 16 |
| 7.2. Radiated Emission Limit | 17 |
| 7.3. EUT Configuration on Measurement | 17 |
| 7.4. Field Strength Calculation | 18 |
| 7.5. Operating Condition of EUT | 18 |
| 7.6. Measuring Setting..... | 18 |
| 7.7. Test Procedure..... | 18 |
| 7.8. Test Results..... | 19 |
| 8. 20 DB BANDWIDTH MEASUREMENT | 23 |
| 8.1. Block Diagram of Test Setup | 23 |
| 8.2. Test Procedure..... | 23 |
| 8.3. Test Results..... | 24 |
| 9. PHOTOGRAPHS OF TEST SETUP..... | 25 |
| 10. EXTERNAL PHOTOGRAPHS OF THE EUT | 25 |
| 11. INTERNAL PHOTOGRAPHS OF THE EUT..... | 25 |

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

| | |
|----------------------|---|
| EUT | : Nightstands |
| Test Model | : ELQ551 |
| Additional Model No. | : ELQ502, ELQ503, ELQ504, ELQ545, ELQ529, ELQ531 |
| Model Declaration | : PCB board, structure and internal of these model(s) are the same, So no additional models were tested |
| Ratings | : Input: 12V==2A For AC Adapter: Input:100-240V~, 50/60Hz Output: 12V==2A |
| Hardware Version | : YY SZ-ZCW-USBLE-V12 |
| Software Version | : / |
| Bluetooth | : |
| Frequency Range | : 2402MHz~2480MHz |
| Channel Number | : 79 channels for Bluetooth V6.0 (DSS) 40 channels for Bluetooth V6.0 (DTS) |
| Channel Spacing | : 1MHz for Bluetooth V6.0 (DSS) 2MHz for Bluetooth V6.0 (DTS) |
| Modulation Type | : GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V6.0 (DSS) GFSK for Bluetooth V6.0 (DTS) |
| Bluetooth Version | : V6.0 |
| Antenna Description | : PCB Antenna, -2.9dBi (max.) |
| Wireless Charging | : |
| Operating Frequency | : 110.1-205.0KHz |
| Modulation Type | : ASK |
| Antenna Type | : Coil Antenna |

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

1.2 Support equipment List

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|------------------|----------|---------------|-------------|
| --- | AC/DC ADAPTOR | XH-1220W | -- | FCC |

1.3 External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| Power Port | 1 | N/A |
| Type-C Port | 1 | N/A |
| USB Port | 1 | N/A |

1.4 Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10:2013 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6 Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty | 9KHz~30MHz | 3.10dB | (1) |
| | 30MHz~200MHz | 2.96dB | (1) |
| | 200MHz~1000MHz | 3.10dB | (1) |
| | 1GHz~26.5GHz | 3.80dB | (1) |
| | 26.5GHz~40GHz | 3.90dB | (1) |
| Conduction Uncertainty | 150kHz~30MHz | 1.63dB | (1) |
| Power disturbance | 30MHz~300MHz | 1.60dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

Charging and communication mode

Modulation Type: CW (ASK)

| Test Modes | | |
|------------|---|--------|
| Mode 1 | AC/DC Adapter(5V/1A)+EUT (Battery Status: <1%) | Record |
| Mode 2 | AC/DC Adapter(5V/1A)+EUT (Battery Status: <50%) | Record |
| Mode 3 | AC/DC Adapter(5V/1A)+EUT (Battery Status: 100%) | Record |

Note: All test modes were pre-tested for ac and dc mode, but we only recorded the worst case in this report for ac mode.

For AC conducted emission, pre-test at both AC 120V/60Hz and AC 240V/50Hz, recorded worst case;

For AC conducted emission, pre-test at both AC charge from power adapter modes, recorded worst case.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR PART 15C 15.207.

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT was operated in the normal operating mode and a continuous transmits mode for other tests.

According to its specifications, the EUT must comply with the requirements of the Section 15.207 under the FCC Rules Part 15 Subpart C.

2.3 General Test Procedures

2.3.1 Conducted Emissions

The EUT is directly placed on the ground. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turntable, which is directly placed on the ground. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

2.4. Test Sample

The application provides 2 samples to meet requirement;

| Sample Number | Description |
|------------------------|---------------------------------------|
| Sample 1(A250818064-1) | Engineer sample – continuous transmit |
| Sample 2(A250818064-2) | Normal sample – Intermittent transmit |

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a normal condition.

3.2 EUT Exercise Software

N/A.

3.3 Special Accessories

| No. | Equipment | Manufacturer | Model No. | Serial No. | Length | shielded/ unshielded | Notes |
|-----|-----------|--------------|-----------|------------|--------|-------------------------|-------|
| / | / | / | / | / | / | / | / |

3.4 Block Diagram/Schematics

Please refer to the related document.

3.5 Equipment Modifications

Guangzhou LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6 Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST EQUIPMENT

| Item | Equipment | Manufacturer | Model No. | Equipment No. | Cal Date | Due Date |
|------|--------------------------|-----------------|--------------------------|---------------|------------|------------|
| 1 | Power Meter | Keysight | E4417A | GLCS-E-279 | 2025-04-10 | 2026-04-09 |
| 2 | Power Sensor | Keysight | E9304A | GLCS-E-280 | 2025-04-10 | 2026-04-09 |
| 3 | Power Sensor | Keysight | E9304A | GLCS-E-281 | 2025-04-10 | 2026-04-09 |
| 4 | Test Software | MWRFtest | TS 8310 | N/A | N/A | N/A |
| 5 | MXA Signal Analyzer | Agilent | N9020A | GLCS-E-346 | 2025-07-15 | 2026-07-14 |
| 6 | DC Power Supply | Manson | HCS-3604 | GLCS-E-126 | 2025-04-10 | 2026-04-09 |
| 7 | EMI Test Software | Farad | EZ-EMC(Ver.F A-03A2 RE+) | GLCS-E-012 | N/A | N/A |
| 8 | Semi Anechoic Chamber#1 | Maorui | 966 | GLCS-E-001 | 2024-04-21 | 2027-04-20 |
| 9 | Positioning Controller | Max-Full | MF-7802 | GLCS-E-015 | N/A | N/A |
| 10 | Active Loop Antenna | TESEQ | HLA 6121 | GLCS-E-155 | 2025-07-27 | 2026-07-26 |
| 11 | By-log Antenna | SCHWARZBECK | VULB9163 | GLCS-E-352 | 2025-07-15 | 2026-07-14 |
| 12 | Horn Antenna | SCHWARZBECK | BBHA 9120D | GLCS-E-060 | 2025-07-19 | 2026-07-18 |
| 13 | Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | GLCS-E-347 | 2025-07-15 | 2026-07-14 |
| 14 | Broadband Preamplifier | SCHWARZBECK | BBV9719 | GLCS-E-348 | 2025-07-15 | 2026-07-14 |
| 15 | EMI Test Receiver | R&S | ESR 7 | GLCS-E-192 | 2025-04-10 | 2026-04-09 |
| 16 | RS SPECTRUM ANALYZER | R&S | FSP40 | GLCS-E-349 | 2025-07-15 | 2026-07-14 |
| 17 | Low-frequency amplifier | Sonoma | 310N | GLCS-E-036 | 2025-04-10 | 2026-04-09 |
| 18 | High-frequency amplifier | SKET | LNPA_30M06 G-40 | GLCS-E-286 | 2025-04-11 | 2026-04-10 |
| 19 | 6dB Attenuator | / | 100W/6dB | GLCS-E-350 | 2025-07-15 | 2026-07-14 |
| 20 | 3dB Attenuator | / | 2N-3dB | GLCS-E-351 | 2025-07-15 | 2026-07-14 |
| 21 | EMI Test Receiver | ROHDE & SCHWARZ | ESR7 | GLCS-E-158 | 2025-04-10 | 2026-04-09 |
| 22 | Artificial Mains Network | ROHDE & SCHWARZ | ESH2-Z5 | GLCS-E-011 | 2025-04-10 | 2026-04-09 |
| 23 | EMI Test Software | Farad | EZ-EMC(Ver.F A-03A2 RE+) | GLCS-E-017 | N/A | N/A |
| 24 | Antenna Mast | Maorui | BK-4AT-BS | GLCS-E-249 | N/A | N/A |
| 25 | Pulse Limiter | SCHWARZBECK | VTSD 9561-F | GLCS-E-052 | 2025-04-10 | 2026-04-09 |

5. SUMMARY OF TEST RESULT


| FCC Rules | Description of Test | Test Sample | Result |
|------------|-----------------------------|-------------|-----------|
| §15.207(a) | AC Conducted Emissions | Sample 1 | Compliant |
| §15.209 | Radiated Spurious Emissions | Sample 1 | Compliant |
| §15.215 | 20 dB Bandwidth | Sample 1 | Compliant |

Remark: The measurement uncertainty is not included in the test result.

N/A – Not Applicable!!!

6. POWER LINE CONDUCTED MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. Standard Applicable

According to §15.207: For all the consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

6.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS (\text{dBuV/m}) = RA (\text{dBuV}) + AF (\text{dB/m}) + CL (\text{dB}) - AG (\text{dB})$$

| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

6.4 Test Results


PASS

The test data please refer to following page.

| | | | |
|---------------|----------|----------------|----------|
| Temperature | 24.8°C | Humidity | 53.7% |
| Test Engineer | Jone.Lee | Configurations | Transmit |


AC Power Line Conducted Emission (Power input to adapter @ AC 120V/60Hz (Worst Case))

Line



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Margin | Detector | Comment |
|-----|-----|--------|---------|---------|----------|-------|--------|----------|---------|
| | | | Level | Factor | ment | | | | |
| | | MHz | dBuV | dB | dBuV | dB | | | |
| 1 | | 0.194 | 33.58 | 19.67 | 53.25 | 63.86 | -10.61 | QP | |
| 2 | | 0.194 | 15.16 | 19.67 | 34.83 | 53.86 | -19.03 | AVG | |
| 3 | * | 0.263 | 33.68 | 19.75 | 53.43 | 61.34 | -7.91 | QP | |
| 4 | | 0.263 | 12.19 | 19.75 | 31.94 | 51.34 | -19.40 | AVG | |
| 5 | | 0.348 | 29.06 | 19.91 | 48.97 | 59.01 | -10.04 | QP | |
| 6 | | 0.348 | 0.28 | 19.91 | 20.19 | 49.01 | -28.82 | AVG | |
| 7 | | 1.675 | 26.43 | 19.01 | 45.44 | 56.00 | -10.56 | QP | |
| 8 | | 1.675 | 2.29 | 19.01 | 21.30 | 46.00 | -24.70 | AVG | |
| 9 | | 8.597 | 27.44 | 19.64 | 47.08 | 60.00 | -12.92 | QP | |
| 10 | | 8.597 | 15.63 | 19.64 | 35.27 | 50.00 | -14.73 | AVG | |
| 11 | | 18.488 | 29.93 | 19.33 | 49.26 | 60.00 | -10.74 | QP | |
| 12 | | 18.488 | 15.76 | 19.33 | 35.09 | 50.00 | -14.91 | AVG | |

Neutral



| No. Mk. | Freq. MHz | Reading Level | Correct Factor | Measure- ment | Limit | Margin | Detector | Comment |
|---------|--------------|------------------|-------------------|------------------|-------|--------|----------|---------|
| | | dBuV | dB | dBuV | dB | | | |
| 1 | 0.208 | 32.53 | 19.78 | 52.31 | 63.28 | -10.97 | QP | |
| 2 | 0.208 | 19.33 | 19.78 | 39.11 | 53.28 | -14.17 | AVG | |
| 3 | 0.348 | 28.66 | 19.81 | 48.47 | 59.01 | -10.54 | QP | |
| 4 | 0.348 | 0.88 | 19.81 | 20.69 | 49.01 | -28.32 | AVG | |
| 5 * | 0.897 | 30.40 | 18.94 | 49.34 | 56.00 | -6.66 | QP | |
| 6 | 0.897 | 9.18 | 18.94 | 28.12 | 46.00 | -17.88 | AVG | |
| 7 | 2.220 | 28.34 | 19.11 | 47.45 | 56.00 | -8.55 | QP | |
| 8 | 2.220 | 9.51 | 19.11 | 28.62 | 46.00 | -17.38 | AVG | |
| 9 | 8.597 | 26.76 | 19.82 | 46.58 | 60.00 | -13.42 | QP | |
| 10 | 8.597 | 14.95 | 19.82 | 34.77 | 50.00 | -15.23 | AVG | |
| 11 | 18.488 | 30.50 | 19.26 | 49.76 | 60.00 | -10.24 | QP | |
| 12 | 18.488 | 16.33 | 19.26 | 35.59 | 50.00 | -14.41 | AVG | |


***Note: Pre-scan all modes and recorded the worst case results in this report.

Margin=Reading level + Correct - Limit;

Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limitter

7. RADIATED EMISSION MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293. | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | \2\ |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

7.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{FS (dBuV/m)} = \text{RA (dBuV)} + \text{AF (dB/m)} + \text{CL (dB)} - \text{AG (dB)}$$

| | |
|---------------------------|--|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude | AG = Amplifier Gain |
| AF = Antenna Factor | |

7.5. Operating Condition of EUT

- (1) Setup the EUT as shown in Section 7.1.

7.6. Measuring Setting

The following table is the setting of spectrum analyzer and receiver.

| Receiver Parameter | Setting |
|------------------------|---------------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP/Average |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP/Average |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 100kHz for QP |

7.7. Test Procedure

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premereasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premereasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

7.8. Test Results

PASS.

Both AC and DC modes were tested, only AC mode was recorded


Only report the worst test data (Mode 1) in test report;

The test data please refer to following page:

| | | | |
|---------------|----------|----------------|----------|
| Temperature | 23.6°C | Humidity | 52.2% |
| Test Engineer | Jone.Lee | Configurations | Transmit |

0.009 MHz – 30 MHz

0 degree




| No. Mk. | Freq. | Reading | Correct | Measure- | Limit | Margin | Detector | Comment |
|---------|---------|---------|---------|----------|--------|--------|----------|---------|
| | | Level | Factor | ment | | | | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 0.1360 | 77.37 | -10.39 | 66.98 | 104.87 | -37.89 | QP | |
| 2 | 0.4072 | 51.10 | -10.32 | 40.78 | 95.40 | -54.62 | QP | |
| 3 | 0.5410 | 42.08 | -10.28 | 31.80 | 72.94 | -41.14 | QP | |
| 4 * | 1.0691 | 53.86 | -10.05 | 43.81 | 67.02 | -23.21 | QP | |
| 5 | 4.8357 | 44.78 | -9.90 | 34.88 | 69.54 | -34.66 | QP | |
| 6 | 16.7287 | 42.45 | -9.31 | 33.14 | 69.54 | -36.40 | QP | |


Remark: 1). Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.

2). Margin=Reading level + Factor- Limit

| | | | |
|---------------|----------|----------------|----------|
| Temperature | 23.8°C | Humidity | 52.1% |
| Test Engineer | Jone.Lee | Configurations | Transmit |

Below 1GHz*Horizontal*


| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Margin | Detector | Comment |
|-----|-----|----------|---------|---------|----------|--------|--------|----------|---------|
| | | | Level | Factor | ment | | | | |
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | | 38.6160 | 38.27 | -17.11 | 21.16 | 40.00 | -18.84 | QP | |
| 2 | | 74.9191 | 51.95 | -19.51 | 32.44 | 40.00 | -7.56 | QP | |
| 3 | | 119.0177 | 44.46 | -18.96 | 25.50 | 43.50 | -18.00 | QP | |
| 4 | * | 190.4050 | 56.03 | -19.69 | 36.34 | 43.50 | -7.16 | QP | |
| 5 | | 425.0280 | 35.05 | -13.30 | 21.75 | 46.00 | -24.25 | QP | |
| 6 | | 768.7481 | 34.47 | -9.39 | 25.08 | 46.00 | -20.92 | QP | |



- 1). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Margin=Reading level + Factor- Limit.
Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor

8. 20 DB BANDWIDTH MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. Test Procedure

Use the following spectrum analyzer settings:

Span = 500 Hz

RBW = 10Hz

VBW = 30Hz

Sweep = auto

Detector function = peak

Trace = max hold


The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

8.3. Test Results

| Test Result Of 20dB Bandwidth Measurement | | | |
|---|----------------------|----------------------|---------------|
| Test Mode | Test Frequency (MHz) | 20dB Bandwidth (kHz) | Limit (kHz) |
| TM1 | 0.136 | 0.027 | Non-Specified |

Result: Pass

Please refer to the following page for test plot.



9. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

10. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

11. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----