

RF TEST REPORT

For

Shenzhen Enhōt E-Commerce Co., Ltd

Product Name: Foldable sex machine remote control

Test Model(s): ENHOT-08

Report Reference No. : DACE250614001RL001

FCC ID : 2BRO3ENHOT-08

Applicant's Name : Shenzhen Enhōt E-Commerce Co., Ltd

Address : No. 318 WanshengBaihuo, WanzhongCheng, XinNiu Community, Minzhi Street, Longhua District, ShenZhen City, Guangdong province, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15.231

Date of Receipt : June 14, 2025

Date of Test : June 14, 2025 to /

Date of Issue : June 26, 2025

Result : Init

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	Shenzhen Enhot E-Commerce Co., Ltd
Address	:	No. 318 WanshengBaihuo, WanzhongCheng, XinNiu Community, Minzhi Street, Longhua District, ShenZhen City, Guangdong province, China
Product Name	:	Foldable sex machine remote control
Test Model(s)	:	ENHOT-08
Series Model(s)	:	SR5002,SR5003,SR5XXX, Series(XXX=001-100)ENHOT-02,ENHOT-03,ENHOT-04,ENHOT-XXX,(XXX=02-100)
Test Specification Standard(s)	:	47 CFR Part 15.231

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Keren Huang

Keren Huang / Test Engineer

June 26, 2025

Supervised by:

Ben Tang

Ben Tang / Project Engineer

June 26, 2025

Approved by:

Tom Chen

Tom Chen / Manager

June 26, 2025

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE250614001RL001	June 26, 2025

CONTENTS

1 TEST SUMMARY	5
1.1 TEST STANDARDS	5
1.2 SUMMARY OF TEST RESULT	5
2 GENERAL INFORMATION	6
2.1 CLIENT INFORMATION	6
2.2 DESCRIPTION OF DEVICE (EUT)	6
2.3 DESCRIPTION OF TEST MODES	6
2.4 DESCRIPTION OF SUPPORT UNITS	6
2.5 EQUIPMENTS USED DURING THE TEST	7
2.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
2.7 IDENTIFICATION OF TESTING LABORATORY	8
2.8 ANNOUNCEMENT	8
3 EVALUATION RESULTS (EVALUATION)	9
3.1 ANTENNA REQUIREMENT	9
3.1.1 Conclusion:	9
4 RADIO SPECTRUM MATTER TEST RESULTS (RF)	10
4.1 20dB BANDWIDTH	10
4.1.1 E.U.T. Operation:	11
4.1.2 Test Setup Diagram:	11
4.1.3 Test Data:	11
4.2 DWELL TIME	12
4.2.1 E.U.T. Operation:	12
4.2.2 Test Setup Diagram:	12
4.2.3 Test Data:	13
4.3 DUTY CYCLE	14
4.3.1 E.U.T. Operation:	14
4.3.2 Test Setup Diagram:	15
4.3.3 Test Data:	15
4.3.4 Test Data:	15
4.4 RADIATED EMISSION	18
4.4.1 E.U.T. Operation:	19
4.4.2 Test Setup Diagram:	19
4.4.3 Test Data:	20
5 TEST SETUP PHOTOS	23
6 PHOTOS OF THE EUT	24

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.231: Periodic operation in the band 40.66-40.70 MHz and above 70 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.231		47 CFR 15.203	Pass
20dB Bandwidth	47 CFR Part 15.231	ANSI C63.10-2013, section 6.9.2	47 CFR 15.231(c)	Pass
Dwell Time	47 CFR Part 15.231	ANSI C63.10-2013, Section 7.4	47 CFR 15.231(a)(1) & (a)(2)	Pass
Duty Cycle	47 CFR Part 15.231	ANSI C63.10-2013, Section 7.5	47 CFR 15.231(b) & (e)	Pass
Radiated Emission (below 1GHz)	47 CFR Part 15.231	ANSI C63.10-2013, Section 6.5&6.6	47 CFR 15.231	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Shenzhen Enhot E-Commerce Co., Ltd
Address : No. 318 WanshengBaihuo, WanzhongCheng, XinNiu Community, Minzhi Street, Longhua District, ShenZhen City, Guangdong province, China

Manufacturer : Shenzhen Enhot E-Commerce co., ltd. Dongguan Branch
Address : Room No.702, No. 6 Changxing Road, Chang'antang, Dongkeng Town, Dongguan City, Guangdong province, China

2.2 Description of Device (EUT)

Product Name:	Foldable sex machine remote control
Model/Type reference:	ENHOT-08
Series Model:	SR5002,SR5003,SR5XXX, Series(XXX=001-100)ENHOT-02,ENHOT-03,ENHOT-04,ENHOT-XXX,(XXX=02-100)
Model Difference:	The product has many models, only the model name is different, and the other parts such as the circuit principle, pcb and electrical structure are the same.
Trade Mark:	N/A
Power Supply:	DC3.0
Operation Frequency:	433.92MHz
Number of Channels:	1
Modulation Type:	ASK
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Hardware Version:	V1.0
Software Version:	V1.0

2.3 Description of Test Modes

No	Title	Description
TM1	Transmitting	433.92MHz

2.4 Description of Support Units

The EUT was tested as an independent device.

2.5 Equipments Used During The Test

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(shenzhen) Co.,Ltd.	RTS-01	V1.0.0	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2025-04-18	2026-05-10
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Vector Signal Generator	Keysight	N5181A	MY50143455	2024-12-06	2025-12-05
Signal Generator	Keysight	N5182A	MY48180415	2024-12-06	2025-12-05
Spectrum Analyzer	Keysight	N9020A	MY53420323	2024-12-06	2025-12-05

Field Strength of The Fundamental Signal

Radiated Emission (below 1GHz)

Radiated Emission (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2025-04-28	2026-04-27
Cable(LF)#2	Schwarzbeck	/	/	2024-12-19	2025-12-18
Cable(LF)#1	Schwarzbeck	/	/	2024-12-19	2025-12-18
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2025-04-25	2026-04-24
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2025-04-25	2026-04-24
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2025-04-29	2026-04-28
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2025-04-29	2026-04-28
Wideband radio communication tester	R&S	CMW500	113410	2025-04-25	2026-04-24
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2025-04-18	2026-04-17
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2025-04-18	2026-04-17
Horn Antenna	Sunol Sciences	DRH-118	A091114	2025-04-21	2026-04-20
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Occupied Bandwidth	±3.63%
Duty cycle	±3.1%
Radiated Emission (Below 1GHz)	±5.79dB
Radiated Emission (Above 1GHz)	±5.46dB

Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
Designation Number:	CN1342
Test Firm Registration No.:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client. When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

3.1.1 Conclusion:



4 Radio Spectrum Matter Test Results (RF)


4.1 20dB Bandwidth

Test Requirement:	47 CFR 15.231(c)
Test Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Method:	ANSI C63.10-2013, section 6.9.2
Procedure:	<ul style="list-style-type: none">a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.d) Steps a) through c) might require iteration to adjust within the specified tolerances.e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.f) Set detection mode to peak and trace mode to max hold.g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.1.1 E.U.T. Operation:

Operating Environment:				
Temperature:	23.3 °C	Humidity:	46 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1			
Final test mode:	TM1			

4.1.2 Test Setup Diagram:



4.1.3 Test Data:

Condition	Antenna	Frequency (MHz)	20dB BW(kHz)	limit(MHz)	Result
NVNT	ANT1	433.92	55.5	1.0848	Pass




4.2 Dwell Time

Test Requirement:	47 CFR 15.231(a)(1) & (a)(2)
Test Limit:	(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released. (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
Test Method:	ANSI C63.10-2013, Section 7.4
Procedure:	For evaluation of periodic operation characteristics, the following procedure may be used: a) Trigger the spectrum analyzer sweep on the RF waveform of the unlicensed wireless device. b) Set the spectrum analyzer sweep time greater than the specified time for periodic operation. c) Manually activate and deactivate the unlicensed wireless device and confirm that it ceases transmission within the specified time of deactivation. d) Document the test results. e) Verify and document that periodic transmissions at regular predetermined intervals do not exist, except where regulatory requirements allow polling or supervision transmissions, including data, to determine system integrity. Compliance is addressed by an attestation supported by the equipment theory of operation.

4.2.1 E.U.T. Operation:

Operating Environment:				
Temperature:	23.3 °C	Humidity:	46 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1			
Final test mode:	TM1			

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Condition	Antenna	Frequency (MHz)	Dwell time(s)	limit(s)	Result
NVNT	ANT1	433.92	0.19s	5s	Pass




4.3 Duty Cycle

Test Requirement:	47 CFR 15.231(b) & (e)
Test Limit:	No limit, only for Report Use.
Test Method:	ANSI C63.10-2013, Section 7.5
Procedure:	<p>a) Adjust and configure any EUT switches, controls, or input data streams to ensure that the EUT is transmitting or encoded to obtain the "worst-case" pulse ON time.</p> <p>b) Couple the final radio frequency output signal to the input of a spectrum analyzer. This may be performed by a radiated, direct connection (i.e., conducted) or by a "near-field" coupling method. The signal received shall be of sufficient level to trigger adequately the spectrum analyzer sweep display.</p> <p>NOTE—If the bandwidth of the pulse is greater than the RBW of the spectrum analyzer, then a similar measurement may be performed using a wideband digital storage oscilloscope (DSO).</p> <p>c) Adjust the center frequency of the spectrum analyzer to the center of the RF signal.</p> <p>d) Set the spectrum analyzer for ZERO SPAN.</p> <p>e) Adjust the SWEEP TIME to obtain at least a 100 ms period of time on the horizontal display axis of the spectrum analyzer.</p> <p>f) If the pulse train is periodic (i.e., consists of a series of pulses that repeat in a characteristic pattern over a constant time period), and the period (T) is less than or equal to 100 ms, then:</p> <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture at least one period of the pulse train, including any blanking intervals. 2) Determine the total maximum pulse "ON time" (t_{ON}) over one period of the pulse train. An example of a periodic pulse train and the associated period is shown in Figure 14. If the pulse train contains pulses of different widths, then t_{ON} is determined by summing the duration of all of the pulses within the pulse train [i.e., $t_{ON} = \sum(t_1 + t_2 + \dots + t_n)$]. 3) The duty cycle is then determined by dividing the total maximum "ON time" by the period of the pulse train (t_{ON}/T). <p>g) If the pulse train is nonperiodic or is periodic with a period that exceeds 100 ms, or as an alternative to step f), then:</p> <ol style="list-style-type: none"> 1) Set the TRIGGER on the spectrum analyzer to capture the greatest amount of pulse "ON time" over 100 ms. 2) Find the 100 ms period that contains the maximum "on time"; this may require summing the duration of multiple pulses as described in step f2). 3) Determine the duty cycle by dividing the total maximum "ON time" by 100 ms ($t_{ON}/100$ ms).

4.3.1 E.U.T. Operation:

Operating Environment:				
Temperature:	23.3 °C	Humidity:	46 %	Atmospheric Pressure: 101 kPa
Pretest mode:	TM1			
Final test mode:	TM1			

4.3.2 Test Setup Diagram:




4.3.3 Test Data:


4.3.4 Test Data:

Frequency (MHz)	Type of Pulse	Width of Pulse (ms)	Quantity of Pulse	Transmission Time (ms)	Total Time (Ton) (ms)
433.92	Pulse 1 (widest)	1.08	11	11.88	17.08
	Pulse 2 (Wide)	0.4	13	5.2	

Frequency (MHz)	Test Period (Tp)	Total Time (Ton)	Duty Cycle	Duty Cycle Factor
	ms	ms	%	dB
433.92	17.08	45.44	37.5	-8.50

Remark: Duty Cycle Factor=20*log(Duty Cycle)







4.4 Radiated Emission

Test Requirement:	47 CFR 15.231		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Test Method:	ANSI C63.10-2013, Section 6.5&6.6		
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <ol style="list-style-type: none"> 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest 		

point could be found when testing, so only the above harmonics had been displayed.

4. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


5. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.


4.4.1 E.U.T. Operation:

Operating Environment:

Temperature:	23.3 °C	Humidity:	50.9 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.4.2 Test Setup Diagram:





4.4.3 Test Data:

TM1 / Polarization: Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)
1	434.0650	76.40	-4.33	N/A	72.07	100.8	-28.73	Peak	100
2	434.0650	N/A	N/A	-8.50	63.57	80.8	-17.23	AV	100
3	869.1302	39.11	3.01	N/A	42.12	80.8	-38.68	Peak	100
4	869.1302	N/A	N/A	-8.50	33.62	60.8	-27.18	AV	100

above 1GHz

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1520.000	42.99	-6.35	36.64	74.00	-37.36	peak			P	
2	1570.000	30.58	-6.15	24.43	54.00	-29.57	AVG			P	
3	2295.000	41.66	-3.48	38.18	74.00	-35.82	peak			P	
4	2340.000	29.55	-3.34	26.21	54.00	-27.79	AVG			P	
5	3000.000	41.55	-1.67	39.88	74.00	-34.12	peak			P	
6	3005.000	30.08	-1.65	28.43	54.00	-25.57	AVG			P	
7	3660.000	29.64	0.82	30.46	54.00	-23.54	AVG			P	
8	3710.000	42.82	0.95	43.77	74.00	-30.23	peak			P	
9	4840.000	27.53	3.87	31.40	54.00	-22.60	AVG			P	
10	4870.000	38.44	3.98	42.42	74.00	-31.58	peak			P	
11 *	5755.000	26.33	6.30	32.63	54.00	-21.37	AVG			P	
12	5775.000	37.98	6.33	44.31	74.00	-29.69	peak			P	

TM1 / Polarization: Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Dutycycle Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)
1	434.0650	74.71	-4.58	N/A	70.13	100.8	-30.67	Peak	100
2	434.0650	N/A	N/A	-8.50	61.63	80.8	-19.17	AV	100
3	869.1302	44.94	2.89	N/A	47.83	80.8	-32.97	Peak	100
4	869.1302	N/A	N/A	-8.50	39.33	60.8	-21.47	AV	100

above 1GHz


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1530.000	42.51	-6.29	36.22	74.00	-37.78	peak			P	
2	1535.000	30.69	-6.28	24.41	54.00	-29.59	AVG			P	
3	2085.000	41.33	-4.17	37.16	74.00	-36.84	peak			P	
4	2130.000	29.88	-4.03	25.85	54.00	-28.15	AVG			P	
5	3005.000	29.98	-1.65	28.33	54.00	-25.67	AVG			P	
6	3010.000	41.73	-1.63	40.10	74.00	-33.90	peak			P	
7	3660.000	29.68	0.82	30.50	54.00	-23.50	AVG			P	
8	3690.000	41.06	0.89	41.95	74.00	-32.05	peak			P	
9	4430.000	28.30	2.53	30.83	54.00	-23.17	AVG			P	
10	4435.000	39.60	2.54	42.14	74.00	-31.86	peak			P	
11 *	5260.000	27.04	5.15	32.19	54.00	-21.81	AVG			P	
12	5270.000	39.05	5.17	44.22	74.00	-29.78	peak			P	

5 TEST SETUP PHOTOS

Radiated Emission (below 1GHz)**Radiated Emission (above 1GHz)**

6 PHOTOS OF THE EUT


External








Internal





***** End of Report *****