

TEST REPORT

Product Name : Bubble Tea Machine T04
Brand Name : N/A
Model : CT04B-CNS
Series Model : See page 6
FCC ID : 2BROO-CT04B
Applicant : **SHENZHEN YINLI TECHNOLOGY Co., LTD**
Address : 2802, Building 1, Huide Building, North Station Community, Minzhi Street, Longhua District, Shenzhen, China
Manufacturer : **Shenzhen Laiyin Intelligent Equipment Co., Ltd**
Address : 3/F, Plant 1, South of Choushi Road, Tangtou Community, Shiyuan Street, Bao'an District, Shenzhen, China
FCC CFR Title 47 Part 2, Part 22H, Part 24E, Part 27
Standard(s) : ANSI C63.26:2015
KDB 971168 D01
Date of Receipt : June 12, 2025
Date of Test : June 13, 2025~ July 09, 2025
Issued Date : July 10, 2025

Issued By: **Guangdong Asia Hongke Test Technology Limited**
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street,
Bao'an District, Shenzhen, Guangdong, China
Tel.: +86 0755-230967639 Fax.: +86 0755-230967639

Reviewed by:

Leon Yi

Leon.yi

Approved by:

Sean She

Sean She



Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



Report Revise Record

Report Version	Issued Date	Notes
M1	July 10, 2025	Initial Release

Contents

1	TEST SUMMARY.....	4
1.1	TEST STANDARDS	4
1.2	TEST SUMMARY	4
1.3	TEST FACILITY	7
1.4	MEASUREMENT UNCERTAINTY	7
2	GENERAL INFORMATION	8
2.1	ENVIRONMENTAL CONDITIONS.....	8
2.2	GENERAL DESCRIPTION OF EUT	8
2.3	DESCRIPTION OF TEST MODES AND TEST FREQUENCY	9
2.4	TEST SETUP AND CONDITIONS	12
2.4.1	<i>Conducted Measurement Test Setup.....</i>	<i>12</i>
2.4.2	<i>Radiated Measurement Test Setup.....</i>	<i>12</i>
2.5	EQUIPMENT LIST FOR THE TEST.....	13
3	TEST CONDITIONS AND RESULTS.....	14
3.1	OUTPUT POWER	14
3.2	PEAK-TO-AVERAGE RATIO	15
3.3	OCCUPIED BANDWIDTH.....	16
3.4	BAND EDGE COMPLIANCE	17
3.5	SPURIOUS EMISSION.....	18
3.6	FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS	29
4	TEST SETUP PHOTOGRAPHS OF EUT	30
5	PHOTOS OF EUT.....	31

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

[FCC Part 22](#): PRIVATE LAND MOBILE RADIO SERVICES.

[FCC Part 24](#): PUBLIC MOBILE SERVICES

[Part 27](#): MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

[FCC Part 2](#): FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

[ANSI C63.26:2015](#): American National Standard of procedures for compliance testing of transmitters used in licensed radio services.

[ANSI C63.10-2013](#) Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

[KDB971168 D01:v03r01](#) MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS


1.2 Test Summary


Band5

Test Item	FCC Rule No.	Requirements	Verdict (Note1)
Effective(Isotropic) Radiated Power Output Data	Part 2.1046, 22.913(a)	ERP $\leq$ 3W	Pass
Peak-Average Ratio	--	Limits13 dB	Pass
Bandwidth	Part 2.1049	OBW:No limit. EBW:No limit.	Pass
Band Edges Compliance	Part 2.1051, 22.917(a)	$\leq$ -13 dBm/1%*EBW,in1MHz bands immediately outside and adjacent to the frequency block.	Pass
Spurious Emission at Antenna Terminals	Part 2.1051, 22.917(a)	$\leq$ -13 dBm/1MHz,from9 kHz to 10 th harmonics but out sideauthorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	Part 2.1051, 22.917(a)	$\leq$ -13 dBm/1MHz.	Pass
Frequency Stability	Part 2.1055, 22.355	$\leq$ $\pm$ 2.5ppm.	Pass

Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Band 38/41

Test Item	FCC Rule No.	Requirements	Verdict (Note1)
Effective (Isotropic) Radiated Power Output Data	Part 2.1046 27.50(h)	EIRP $\leq$ 2 W	Pass
Peak-Average Ratio	Part 27.50(a)	Limit $\leq$ 13 dB	Pass
Bandwidth	Part 2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	Part 2.1051, 27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.	Pass
Spurious Emission at Antenna Terminals	Part 2.1051, 27.53(m)		Pass

Field Strength of Spurious Radiation	Part 2.1053, 27.53(m)		Pass
Frequency Stability	Part 2.1055, 27.54	Within authorized bands of operation/frequency block.	Pass
Note1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".			

1.3 Test Facility

Test Laboratory:

Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC —Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Guangdong Asia Hongke Test Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Asia Hongke laboratory is reported:

Test	Measurement Uncertainty	Notes
Power Line Conducted Emission	9KHz~30MHz ± 1.20 dB	(1)
Radiated Emission	9KHz~30MHz ± 3.10 dB	(1)
Radiated Emission	30MHz ~1GHz ± 3.75 dB	(1)
Radiated Emission	1GHz~18GHz ± 3.88 dB	(1)
Radiated Emission	18GHz-40GHz ± 3.88 dB	(1)
RF power, conducted	30MHz~6GHz ± 0.16 dB	(1)
RF power density, conducted	± 0.24 dB	(1)
Spurious emissions, conducted	± 0.21 dB	(1)
Temperature	$\pm 1^{\circ}\text{C}$	(1)
Humidity	$\pm 3\%$	(1)
DC and low frequency voltages	$\pm 1.5\%$	(1)
Time	$\pm 2\%$	(1)
Duty cycle	$\pm 2\%$	(1)

The report uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty Multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%

2 GENERAL INFORMATION

2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2 General Description of EUT

Product Name:	Bubble Tea Machine T04
Model/Type reference:	CT04B-CNS
Serial Model:	CT04B-GLS, CT04B-EUS, CT04B-NAS, CT04B-SES, CT04B-USS, CT04B-UKS, CT04B-THS, CT04B-VNS, CT04B-SGS, CT04B-IDS, CT04B-MYS, CT04B-PHS, CT04B-AUS, CT04B-DES, CT04B-FRS, CT04B-ATS, CT04B-ITS, CT04B-DKS, CT04W-CNS, CT04W-GLS, CT04W-EUS, CT04W-NAS, CT04W-USS, CT04W-UKS, CT04W-THS, CT04W-VNS, CT04W-SGS, CT04W-IDS, CT04W-MYS, CT04W-PHS, CT04W-AUS, CT04W-DES, CT04W-FRS, CT04W-ATS, CT04W-ITS, CT04W-DKS, , CT04B-CNH, CT04B-GLH, CT04B-EUH, CT04B-NAH, CT04B-USH, CT04B-UKH, CT04B-THH, CT04B-VNH, CT04B-SGH, CT04B-IDH, CT04B-MYH, CT04B-PHH, CT04B-AUH, CT04B-DEH, CT04B-FRH, CT04B-ATH, CT04B-ITH, CT04B-DKH, CT05B-CNS, CT05B-GLS, CT05B-EUS, CT05B-NAS, CT05B-USS, CT05B-UKS, CT05B-THS, CT05B-VNS CT05B-SGS, CT05B-IDS, CT05B-MYS, CT05B-PHS, CT05B-AUS, CT05B-DES, CT05B-FRS, CT05B-ATS, CT05B-ITS, CT05B-DKS, CT05B-CNH, CT06B-CNS, CT06B-CNH, CT07B-CNS, CT07B-CNH, CT05W-CNS, CT05W-CNH, CT06W-CNS, CT06W-CNH, CT07W-CNS, CT07W-CNH
Model difference:	All models are same as the samples except model name, all the models are electrical identical same mechanical structure and design.
Power Rating:	AC100-220V 50Hz/60Hz 15A
Hardware Version:	B1V01
Software Version:	V2.3
Sample(s) Status:	AiTSZ-250612014-1(Normal sample) AiTSZ-250612014-2(Engineer sample)
LTE:	
Operation Band:	FDD-LTE: Band 5 TDD-LTE: Band 38/41
Support Bandwidth:	Band 5: ☒ 1.4MHz, ☒ 3MHz, ☒ 5MHz, ☒ 10MHz Band 38: ☒ 5MHz, ☒ 10MHz, ☒ 15MHz, ☒ 20MHz Band 41: ☒ 5MHz, ☒ 10MHz, ☒ 15MHz, ☒ 20MHz
Frequency Range:	Band 5:uplink 824MHz to 849MHz; downlink 869MHz to 894MHz Band 38:uplink 2570MHz to 2620MHz;downlink 2570MHz to 2620MHz Band 41:uplink 2555MHz to 2655MHz; downlink 2555MHz to 2655MHz
UE category	Cat. 1
Power Class:	Power Class 3
Modulation Type:	QPSK, 16QAM
Antenna type:	External Antenna
Antenna gain:	LTE band 5:0.39dBi, LTE band 38/41:2.82dBi
Remark: The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.	

2.3 Description of Test Modes and Test Frequency

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

Test Frequency:

Band 5

Test Frequency ID	Bandwidth [MHz]	NUL	Frequency of Uplink [MHz]	NDL	Frequency of Downlink [MHz]
Low Range	1.4	20407	824.7	2407	869.7
	3	20415	825.5	2415	870.5
	5	20425	826.5	2425	871.5
	10	20450	829	2450	874
Mid Range	1.4/3/5/10	20525	836.5	2525	881.5
High Range	1.4	20643	848.3	2643	893.3
	3	20635	847.5	2635	892.5
	5	20625	846.5	2625	891.5
	10	20700	835	2700	880

Band 38


Test Frequency ID	Bandwidth [MHz]	NUL	Frequency (UL and DL) [MHz]
Low Range	5	37775	2572.5
	10	37800	2575
	15	37825	2577.5
	20	37850	2580
Mid Range	5/10/15/20	38000	2595
High Range	5	38225	2617.5
	10	38200	2615
	15	38175	2612.5
	20	38150	2610

Band 41

Test Frequency ID	Bandwidth [MHz]	NUL	Frequency (UL and DL) [MHz]
Low Range	5	40265	2557.5
	10	40290	2560
	15	40315	2562.5
	20	40340	2565
Mid Range	5/10/15/20	40740	2605
High Range	5	41215	2652.5
	10	41190	2650
	15	41165	2647.5
	20	41140	2645


2.4 Test Setup and Conditions

2.4.1 Conducted Measurement Test Setup




2.4.2 Radiated Measurement Test Setup

Step 1: Pre-test



Step 2: Substitution method to verify the maximum ERP/EIRP



2.5 Equipment List for the Test

RF Conducted measurement						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
☒ 1	Spectrum Analyzer	Agilent	N9020A	MY53421570	2024.09.25	2025.09.24
☐ 2	Power Sensor	Agilent	8481A	MY41097697	2024.09.25	2025.09.24
☐ 3	Vector Signal Generator	Agilent	N5182A	MY50143009	2024.09.25	2025.09.24
☐ 4	Analog signal generator	Agilent	E8257	MY51554256	2024.09.25	2025.09.24
☒ 5	Const Temp. & Humidity Chamber	Eastlab	YH-HW-408L	23051109	2024.09.24	2025.09.23
☒ 6	Wideband Radio communication tester	R&S	CMW500	1201.0002K50	2024.09.24	2025.09.23
☒ 7	DC power supply	ZHAOXIN	RXN-305D-2	28070002559	2024.09.24	2025.09.23
☒ 8	RF Test box	TST	TSTPASS	21033016	2024.09.25	2025.09.24
☒ 9	RF Software	TST	TSTPASS	Version 2.0	N/A	N/A

Radiation Emission measurement						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
☒ 1	EMI Measuring Receiver	R&S	ESR	101160	2024.09.25	2025.09.24
☒ 2	Low Noise Pre Amplifier	SCHWARZBECK	BBV 9745	00282	2024.09.25	2025.09.24
☒ 3	Low Noise Pre Amplifier	CESHENG	CSKJLNA231016A	CSKJLNA231016A	2024.09.25	2025.09.24
☒ 4	Spectrum Analyzer	R&S	FSV40	101470	2024.09.23	2025.09.22
☒ 5	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9168	01434	2024.08.29	2027.08.28
☒ 6	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9168	01435	2024.08.29	2027.08.28
☒ 7	Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	452	2024.08.29	2027.08.28
☒ 8	Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	453	2024.08.29	2027.08.28
☒ 9	Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA9170367	2024.08.28	2027.08.27
☒ 10	Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA9170368	2024.08.28	2027.08.27
☒ 11	Wideband Radio communication tester	R&S	CMW500	1201.0002K50	2024.09.24	2025.09.23
☒ 12	6dB Attenuator	JFW	50FPE-006	4360846-949-1	2024.09.24	2025.09.23
☒ 13	RE Software	EZ	EZ-EMC_RE	Ver.AIT-03A	N/A	N/A

Note: ☐ is not applicable in this Test Report. ☒ is applicable in this Test Report.

3 TEST CONDITIONS AND RESULTS

3.1 Output Power

MEASUREMENT SETUP

Test set up as section 2.4.1& 2.4.2.

TEST PROCEDURE

The EUT was setup according to ANSI C63.26:2015

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

Determining ERP and/or EIRP from conducted RF output power measurements according to ANSI C63.26 2015 Section 5.2.5.5.

In many cases, RF output power limits are specified in terms of the ERP or the EIRP. Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are defined as the product of the power supplied to the antenna and its gain (relative to a dipole antenna in the case of ERP, and relative to an isotropic antenna in the case of EIRP); however, when working in decibels (i.e., logarithmic scale), the ERP and EIRP represent the sum of the transmit antenna gain (in dBd or dBi, respectively) and the conducted RF output power (expressed in dB relative to watts or milliwatts).

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation (1) as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = \text{EIRP} - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

For devices utilizing multiple antennas, see 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between ERP and EIRP:

- $\text{ERP} = \text{EIRP} - 2.15$, where ERP and EIRP are expressed in consistent units.
- $\text{EIRP} = \text{ERP} + 2.15$, where ERP and EIRP are expressed in consistent units.

TEST RESULTS

Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

3.2 Peak-to-Average Ratio

MEASUREMENT SETUP

Test set up as section 2.4.1.

TEST PROCEDURE

CCDF Procedure for PAPR :

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - for continuous transmissions, set to 1 ms,
 - or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

3.3 Occupied Bandwidth

MEASUREMENT SETUP

Test set up as section 2.4.1.

TEST PROCEDURE

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99%occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

TEST RESULTS

Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

3.4 Band Edge compliance

MEASUREMENT SETUP

Test set up as section 2.4.1.

TEST PROCEDURE

1. Set the spectrum analyzer center frequency to the block, band, or channel edge frequency.
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = Average
8. Sweep time = > (number of points in sweep) $\times$ (symbol period)
9. Sweep = Single

Or

1. Set the spectrum analyzer center frequency to the block, band, or channel edge frequency.
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = Maxhold
8. Sweep time = Auto
9. Sweep = Single

TEST RESULTS

Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

3.5 Spurious Emission

MEASUREMENT SETUP

Test set up as section 2.4.1& 2.4.2.

TEST PROCEDURE

The EUT was setup according to ANSI C63.26:2015

Conducted Spurious Measurement:

Test Settings

1. RBW = 1KHz (for 9K-150KHz), 10KHz (for 150KHz-10MHz), 100KHz (for 10MHz-30MHz), 1MHz (for above 1GHz)
2. VBW $\geq 3 * RBW$
3. Detector = RMS
4. Trace Mode = Trace average
5. Sweep time $> (\text{number of points in sweep}) \times (\text{symbol period})$
6. Number of points in sweep $\geq 2 \times \text{Span} / RBW$
7. Sweep = Single

Or

1. RBW = 1KHz (for 9K-150KHz), 10KHz (for 150KHz-10MHz), 100KHz (for 10MHz-30MHz), 1MHz (for above 1GHz)
2. VBW $\geq 3 * RBW$
3. Detector = Peak
4. Trace Mode = Maxhold
5. Sweep time = Auto
6. Number of points in sweep $\geq 2 \times \text{Span} / RBW$
7. Sweep = Single

Radiated Spurious Measurement:

1. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
3. The output of the test antenna shall be connected to the measuring receiver.
4. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum

signal level is detected by the measuring receiver.

7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a substitution antenna.
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
16. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
17. The frequency range need checked up to 10th harmonic.

Final measurement calculation as below:

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

TEST RESULTS

Conducted Measurement result:

Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

Radiated Measurement:

LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1649.90	-43.47	9.31	3.02	-37.18	-13.00	-24.18	H
2474.40	-46.01	10.4	3.96	-39.57	-13.00	-26.57	H
3299.60	-51.93	11.08	4.74	-45.59	-13.00	-32.59	H
1649.90	-42.47	9.31	3.02	-36.18	-13.00	-23.18	V
2474.40	-44.98	10.4	3.96	-38.54	-13.00	-25.54	V
3299.60	-51.55	11.08	4.74	-45.21	-13.00	-32.21	V
LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1672.70	-43.70	9.48	3.06	-37.28	-13.00	-24.28	H
2509.85	-49.13	10.41	4	-42.72	-13.00	-29.72	H
3345.30	-53.41	11.24	4.81	-46.98	-13.00	-33.98	H
1672.70	-43.25	9.48	3.06	-36.83	-13.00	-23.83	V
2509.85	-48.46	10.41	4	-42.05	-13.00	-29.05	V
3345.30	-52.30	11.24	4.81	-45.87	-13.00	-32.87	V
LTE Band 5 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
1697.00	-44.79	9.65	3.11	-38.25	-13.00	-25.25	H
2545.65	-45.27	10.41	4.04	-38.90	-13.00	-25.90	H
3394.40	-51.87	11.41	4.88	-45.34	-13.00	-32.34	H
1697.00	-44.01	9.65	3.11	-37.47	-13.00	-24.47	V
2545.65	-45.15	10.41	4.04	-38.78	-13.00	-25.78	V
3394.40	-51.75	11.41	4.88	-45.22	-13.00	-32.22	V

LTE Band 38 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5144.85	-42.13	11.43	5.74	-36.44	-25.00	-11.44	H
7718.50	-45.73	11.38	7.71	-42.06	-25.00	-17.06	H
10290.00	-47.10	11.65	9.16	-44.61	-25.00	-19.61	H
5144.85	-41.20	11.43	5.74	-35.51	-25.00	-10.51	V
7718.50	-45.53	11.38	7.71	-41.86	-25.00	-16.86	V
10290.00	-45.90	11.65	9.16	-43.41	-25.00	-18.41	V
LTE Band 38 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5190.25	-44.85	11.53	5.86	-39.18	-25.00	-14.18	H
7785.70	-42.89	11.30	7.71	-39.30	-25.00	-14.30	H
10379.25	-46.46	11.69	9.23	-44.00	-25.00	-19.00	H
5190.25	-44.25	11.53	5.86	-38.58	-25.00	-13.58	V
7785.70	-42.86	11.30	7.71	-39.27	-25.00	-14.27	V
10379.25	-46.04	11.69	9.23	-43.58	-25.00	-18.58	V
LTE Band 38 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5235.40	-42.10	11.65	5.91	-36.36	-25.00	-11.36	H
7852.40	-46.39	11.26	7.74	-42.87	-25.00	-17.87	H
10469.55	-50.09	11.74	9.29	-47.64	-25.00	-22.64	H
5235.40	-42.03	11.65	5.91	-36.29	-25.00	-11.29	V
7852.40	-45.96	11.26	7.74	-42.44	-25.00	-17.44	V
10469.55	-49.32	11.74	9.29	-46.87	-25.00	-21.87	V

LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5115.60	-42.21	11.37	5.67	-36.51	-25.00	-11.51	H
7673.55	-43.07	11.42	7.70	-39.35	-25.00	-14.35	H
10229.95	-47.55	11.61	9.25	-45.19	-25.00	-20.19	H
5115.60	-41.53	11.37	5.67	-35.83	-25.00	-10.83	V
7673.55	-42.38	11.42	7.70	-38.66	-25.00	-13.66	V
10229.95	-46.93	11.61	9.25	-44.57	-25.00	-19.57	V
LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5209.35	-44.25	11.58	5.89	-38.56	-25.00	-13.56	H
7815.00	-45.19	11.28	7.72	-41.63	-25.00	-16.63	H
10420.60	-50.19	11.72	9.27	-47.74	-25.00	-22.74	H
5209.35	-43.46	11.58	5.89	-37.77	-25.00	-12.77	V
7815.00	-44.87	11.28	7.72	-41.31	-25.00	-16.31	V
10420.60	-50.09	11.72	9.27	-47.64	-25.00	-22.64	V
LTE Band 41 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea (dBm)	Limit (dBm)	Margin (dBm)	Polarity
5305.55	-40.86	11.84	5.96	-34.98	-25.00	-9.98	H
7958.30	-42.98	11.26	7.78	-39.50	-25.00	-14.50	H
10610.10	-49.82	11.67	9.44	-47.59	-25.00	-22.59	H
5305.55	-40.11	11.84	5.96	-34.23	-25.00	-9.23	V
7958.30	-42.18	11.26	7.78	-38.70	-25.00	-13.70	V
10610.10	-48.65	11.67	9.44	-46.42	-25.00	-21.42	V

Remark:

1. PMea = S G.Lev + Ant - Loss
2. Margin = PMea – Limit
3. Other emission levels are attenuated 20dB below the limit and not recorded in report.

3.6 Frequency Stability under Temperature & Voltage Variations

TEST CONFIGURATION

Test set up as section 2.4.1.

TEST PROCEDURE

The EUT was setup according to ANSI C63.26:2015

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS



Passed

☒ **Pass** ☐ **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for LTE.

4 Test Setup Photographs of EUT




5 Photos of EUT




External photos










Internal photos









***** End of Report *****