

# FCC TEST REPORT

**FCC ID: 2BRUS-YK01**

**Report No.** : SSP25080058-1E

**Applicant** : Shenzhen Aifeisi Technology Co., Ltd

**Product Name** : Remote control

**Model Name** : Yk01

**Test Standard** : FCC Part 15.249

**Date of Issue** : 2025-08-30

**Shenzhen CCUT Quality Technology Co., Ltd.**

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China; (Tel.:+86-755-23406590 website: [www.ccuttest.com](http://www.ccuttest.com))

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

**Test Report Basic Information**

**Applicant**.....: Shenzhen Aifeisi Technology Co., Ltd  
36001 Huaide Yinshan Building, beside National Highway 107, Fuwei  
Address of Applicant.....: Community, Fuyong Street, Bao'an District, Shenzhen, China

**Manufacturer**.....: Shenzhen Aifeisi Technology Co., Ltd  
36001 Huaide Yinshan Building, beside National Highway 107, Fuwei  
Address of Manufacturer.....: Community, Fuyong Street, Bao'an District, Shenzhen, China

**Product Name**.....: Remote control

**Brand Name**.....: -

**Main Model**.....: Yk01

**Series Models**.....: -

FCC Part 15 Subpart C

ANSI C63.4-2014

**Test Standard**.....: ANSI C63.10-2013

**Date of Test** .....: 2025-08-20 to 2025-08-27

**Test Result**.....: PASS

**Tested By** .....: Tate Chen (Tate Chen)

**Reviewed By**.....: Lorrix Luo (Lorrix Luo)

**Authorized Signatory**.....: Lahm Peng (Lahm Peng)



Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

**CONTENTS**

<b>1. General Information.....</b>	<b>5</b>
1.1 Product Information .....	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments .....	8
1.6 Measurement Uncertainty .....	9
<b>2. Summary of Test Results.....</b>	<b>10</b>
<b>3. Antenna Requirement.....</b>	<b>11</b>
3.1 Standard and Limit.....	11
3.2 Test Result.....	11
<b>4. Radiated Emissions .....</b>	<b>12</b>
4.1 Standard and Limit.....	12
4.2 Test Procedure.....	12
4.3 Test Data and Results .....	14
<b>5. Band-edge Emissions .....</b>	<b>18</b>
5.1 Standard and Limit.....	18
5.2 Test Procedure.....	18
5.3 Test Data and Results .....	18
<b>6. Occupied Bandwidth .....</b>	<b>20</b>
6.1 Standard and Limit.....	20
6.2 Test Procedure.....	20
6.3 Test Data and Results .....	20

**Revision History**

Revision	Issue Date	Description	Revised By
V1.0	2025-08-30	Initial Release	Lahm Peng

## 1. General Information

### 1.1 Product Information

Product Name:	Remote control
Trade Name:	-
Test Model:	Yk01
Series Models:	-
Rated Voltage:	DC 3V
Power Adapter:	-
Battery:	DC 3V by CR2032 Battery
Test Sample No:	SSP25080058-1
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	2.4GHz RF
Operating Frequency:	2402MH
Max. Field Strength:	90.31dBuV/m
Quantity of Channel:	1
Modulation:	GFSK
Antenna Gain:	0dBi
Type of Antenna:	Integral Antenna
Type of Device:	<input checked="" type="checkbox"/> Portable Device <input type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

## 1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Transmitting	2402MHz	
-	-	-	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2402	-	-	-	-	-	-
-	-	-	-	-	-	-	-

### 1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

### 1.4 Test Facilities

Laboratory Name:	<b>Shenzhen CCUT Quality Technology Co., Ltd.</b> 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6983.01
FCC Registration No.:	583813
FCC Designation No.:	CN1373
ISED Registration No.:	CN0164

## 1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
<b>Conducted Emissions</b>					
AMN	ROHDE&SCHWARZ	ENV216	101097	2025-07-15	2026-07-14
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2025-07-15	2026-07-14
Test Cable	N/A	Cable 5	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
<b>Radiated Emissions</b>					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2025-07-15	2026-07-14
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2025-07-15	2026-07-14
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2025-07-15	2026-07-14
Amplifier	SCHWARZBECK	BBV 9743B	00251	2025-07-15	2026-07-14
Amplifier	HUABO	YXL0518-2.5-45	--	2025-07-15	2026-07-14
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2025-07-15	2026-07-14
Loop Antenna	DAZE	ZN30900C	21104	2025-07-12	2026-07-11
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2025-07-12	2026-07-11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2025-07-12	2026-07-11
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2025-07-12	2026-07-11
Attenuator	QUANJUDA	6dB	220731	2025-07-15	2026-07-14
Test Cable	N/A	Cable 1	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 2	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 3	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 4	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 8	N/A	2025-07-15	2026-07-14
Test Cable	N/A	Cable 9	N/A	2025-07-15	2026-07-14
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
<b>Conducted RF Testing</b>					
RF Test System	MWRFTest	MW100-RFCB	220418SQS-37	2025-07-16	2026-07-15
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2025-07-16	2026-07-15
RF Test Software	MWRFTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThlnkPad E15 Gen 3	SPPOZ22485	N/A	N/A

## 1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %

## 2. Summary of Test Results

---

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.207	Conducted Emissions	N/A
FCC Part 15.209, 15.249(a)&(d)	Radiated Emissions	Passed
FCC Part 15.249(d)	Band-edge Emissions	Passed
FCC Part 15.215(c)	Occupied Bandwidth	Passed

Passed: The EUT complies with the essential requirements in the standard  
Failed: The EUT does not comply with the essential requirements in the standard  
N/A: Not applicable

---

### **3. Antenna Requirement**

---

#### **3.1 Standard and Limit**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Test Result**

This product has an Integral antenna, fulfill the requirement of this section.

## 4. Radiated Emissions

### 4.1 Standard and Limit

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of emission (MHz)	Radiated emissions (3m)
	Quasi-peak (dBuV/m)
30-88	40
88-216	43.5
216-960	46
Above 960	54


Note: The more stringent limit applies at transition frequencies.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


*Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.*

### 4.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz

a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.

b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.

c) Use the following spectrum analyzer settings:  
Span = wide enough to fully capture the emission being measured  
RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{ GHz}$ , 10kHz for  $f < 30\text{MHz}$   
VBW  $\geq$  RBW, Sweep = auto  
Detector function = peak  
Trace = max hold

d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.

f) For the actual test configuration, please refer to the related item - EUT test photos.


#### 4.3 Test Data and Results

Based on the tested data, the EUT complied with the FCC Part 15.249 standard limit for a wireless device, and the tested data as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

## Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	48.6719	27.32	-8.36	18.96	40.00	-21.04	QP	100	303	P	
2	61.5618	26.28	-10.22	16.06	40.00	-23.94	QP	100	95	P	
3	152.6641	26.46	-7.77	18.69	43.50	-24.81	QP	100	11	P	
4	332.5187	26.30	-7.17	19.13	46.00	-26.87	QP	100	105	P	
5	593.0497	26.48	-1.77	24.71	46.00	-21.29	QP	100	229	P	
6 *	760.7036	28.46	1.01	29.47	46.00	-16.53	QP	100	229	P	

## Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM1

Test Antenna Polarization: Vertical

Remark:



Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
GFSK(2402MHz)							
2402	111.2	-20.89	90.31	114	-23.69	H	PK
2402	88.53	-20.89	67.64	94	-26.36	H	AV
4804	77.98	-14.72	63.26	74	-10.74	H	PK
4804	60.27	-14.72	45.55	54	-8.45	H	AV
7206	64.9	-8.41	56.49	74	-17.51	H	PK
7206	46.02	-8.41	37.61	54	-16.39	H	AV
2402	107.69	-20.7	86.99	114	-27.01	V	PK
2402	88.17	-20.7	67.47	94	-26.53	V	AV
4804	78.27	-14.72	63.55	74	-10.45	V	PK
4804	60.18	-14.72	45.46	54	-8.54	V	AV
7206	62.96	-8.41	54.55	74	-19.45	V	PK
7206	48.52	-8.41	40.11	54	-13.89	V	AV

*Note 1: This EUT was tested in 3 orthogonal positions with the X-axis being the worst and the worst case position data was reported.*

*Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.*

*Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.*


## 5. Band-edge Emissions

### 5.1 Standard and Limit

According to §15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### 5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



As the radiated emissions testing, set the Transmitting Channel, observed the outside band of 2310MHz to 2400MHz, than mark the higher-level emission for comparing with the FCC rules.

### 5.3 Test Data and Results

Based on the tested data, the EUT complied with the FCC Part 15.249 standard limit, and the tested data as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
2402MHz	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
GFSK(2402MHz)							
2310	67.12	-21.34	45.78	74	-28.22	H	PK
2310	50.02	-21.34	28.68	54	-25.32	H	AV
2390	69.93	-20.96	48.97	74	-25.03	H	PK
2390	52.58	-20.96	31.62	54	-22.38	H	AV
2400	72.97	-20.91	52.06	74	-21.94	H	PK
2400	56.02	-20.91	35.11	54	-18.89	H	AV
2310	68.32	-21.34	46.98	74	-27.02	V	PK
2310	49.76	-21.34	28.42	54	-25.58	V	AV
2390	64.32	-20.96	43.36	74	-30.64	V	PK
2390	51.76	-20.96	30.8	54	-23.2	V	AV
2400	74.75	-20.91	53.84	74	-20.16	V	PK
2400	55.46	-20.91	34.55	54	-19.45	V	AV

Remark: Level = Reading + Factor, Margin = Level - Limit

## 6. Occupied Bandwidth

### 6.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 6.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.


- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set  $RBW = 1\% \sim 5\%$  of 99% bandwidth,  $VBW \geq [3 \times RBW]$ , Sweep = Auto.
- 4) Set a reference level on the measuring instrument equal to the highest peak value.
- 5) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- 6) Repeat the above procedures until all frequencies measured were complete.

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.



### 6.3 Test Data and Results

Test Frequency	20dB Bandwidth (MHz)	99% Bandwidth (MHz)
2402MHz	5.828	5.655



\*\*\*\*\* END OF REPORT \*\*\*\*\*