



Test Report

Report No.: RKEYS250814718

Date: Aug.31, 2025

Page 1 of 6

RF EXPOSURE EVALUATION REPORT

for

Product: Wireless Presenter

Model: P10

FCC ID:2BRWQ-P10

Report No.: RKEYS250814718

Issued for

Shenzhen Wumusen Technology Co., Ltd.

**4th Floor, No. 68, Yangtai Mountain Road, Guantian Community, Shiyan Street, Bao'an ,
ShenzhenCity,China**

Issued by

Guangdong KEYS Testing Technology Co., Ltd.

Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China

Guangdong KEYS Testing Technology Co., Ltd.

Address: Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China
Tel: +86-0769-22221088 <http://www.keys-lab.com> E-mail: info@keys-lab.com

This report is only responsible for the test results of the samples submitted for inspection, and is not responsible for the source of the samples submitted for inspection.
This report shall not be altered, increased or deleted. Without written approval of KEYS, this test report shall not be copied except in full and published as advertisement.

CONTENTS

	PAGE
1. TEST CERTIFICATION	3
2. GENERAL INFORMATION	4
2.1 GENERAL DESCRIPTION OF E.U.T.	4
3. RF EXPOSURE EVALUATION	5

1. TEST CERTIFICATION

Product: Wireless Presenter

Trade mark: /

FCC ID: 2BRWQ-P10

Model: P10

Model List(s): /

Applicant : Shenzhen Wumusen Technology Co., Ltd.

Address: 4th Floor, No. 68, Yangtai Mountain Road, Guantian Community, Shiyan Street, Bao'an, Shenzhen City, China

Manufacturer: Shenzhen Wumusen Technology Co., Ltd.

Address: 4th Floor, No. 68, Yangtai Mountain Road, Guantian Community, Shiyan Street, Bao'an , Shenzhen City, China

Applicable Standards: CFR 47, FCC Part 2.1093

The above equipment has been tested by Guangdong KEYS Testing Technology Co., Ltd. and found compliance with the requirements in the technical standards mentioned above. The test results presented in this report only relate to the product/system tested. The other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.



Prepared by:

Evan Fang / Engineer



Approved by:

Bruce Zhang / Manager

2. GENERAL INFORMATION

2.1. General Description of E.U.T.

Product Name	:	Wireless Presenter
Model Name	:	P10
Specification	:	2.4GHz
Operating frequency	:	2411-2476MHz
Number of Channel	:	3
Antenna installation	:	PCB antenna
Antenna Gain	:	0.17dBi
Type of Modulation	:	GFSK

3. RF EXPOSURE EVALUATION

3.1. Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1

Standalone Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²⁸ The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc.²⁹

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation³¹

The result is rounded to one decimal place for comparison

The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

3.2. Tune-up Result

Frequency (MHz)	Max Field strength(dBuV/m))	EIRP (dBm)	Maximum Tune up Power (dBm)
2411	93.7	-1.56	-1 $\pm$ 1
Note: $E = \text{EIRP} - 20 \log D + 104.8$ E =electric field strength in dBuV/m EIRP =equivalent isotropic radiated power in dBm D =specified measurement distance in meters(3m)			

3.3. Evaluation Result

Mode	Frequency (GHz)	Maximum Tune up Power (dBm)	Maximum Tune up Power (mW)	Antenna Distance (mm)	Result calculation	SAR Test Exclusion Threshold (Limit)	Result
2.4G	2.411	0	1	5	0.3105	3	PASS

3.4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01V06

****End of Report****