



RF EXPOSURE EVALUATION

FCC ID: 2BRXS-H02PRO

Product Name	:	Handy2.0
Model Name	:	H02_Pro
Serial Model	:	H02
Difference Description	:	The battery capacities differ between the two models: the H02_PRO is 3200mAh, while the H02 is 2000mAh.
Specification	:	BT BLE 802.11b/g/n HT20/HT40
Operating frequency	:	2402-2480MHz(BLE) 2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11 n(HT40)
Numbers of Channel	:	40 channels(BLE) 11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11n(HT40)
Smart System	:	802.11 b/g/n20/n40
Antenna Type	:	FPC Antenna
Antenna Gain	:	-0.89 dBi
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Power Supply	:	Input:DC 20V Lithium-ion battery Model:ZN 18650-4S1P Rated:14.8V 3200mAh 47.36Wh
Hardware Version	:	N/A
Software Version	:	ESP32-WROVER-IE-N8RB



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g SAR extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is $\leq 50\text{mm}$ and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is $<5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2480	1.75	1.75 ± 1	1.883649	5	0.593275	3	BLE
2412	7.92	7.92 ± 1	7.798301	5	2.422248	3	2.4G WiFi

Remark:There is no simultaneous transmission of WiFi and BT.

Conclusion:No stand-alone SAR required for BT and 2.4G WiFi.

Signature

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu

Manager

Date: 2025-09-19