



RF TEST REPORT

Product Name: LED wireless sensor

Model Name: 2BRY7-96686DS,
2BRY7-96686DS-XX ("XX" stands for "BK, TG, SG, WT, GR")

FCC ID: 2BRY7-96686DS

Issued For : LUMILAND INDUSTRIES LIMITED

Room 1401C Tower 2, Phase 1 of Excellence City, No. 128
Zhongkang Rd, Futian District, Shenzhen, 518049, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT25H148SA01

Sample Received Date: Aug.19, 2025

Date of Test: Aug.19, 2025 - Aug.29, 2025

Date of Issue: Aug.29, 2025

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: LUMILAND INDUSTRIES LIMITED

Address: Room 1401C Tower 2, Phase 1 of Excellence City, No. 128
Zhongkang Rd, Futian District, Shenzhen, 518049, China

Manufacturer: HUIZHOU GD LIGHTING TECHNOLOGY CO.,LTD

Address: 8-12F, Workshop 6, Xinghe Zhongkai Artificial Intelligence
Industrial Park, No.333, Zhongkai 6th Road, Chenjiang
Subdistrict, Zhongkai High-tech Zone, Huizhou, Guangdong,
China

Product Name: LED wireless sensor

Trademark: **LUMILAND**

Model Name: 2BRY7-96686DS

Series Model: 2BRY7-96686DS-XX ("XX" stands for "BK, TG, SG, WT, GR")

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2 . FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 CLASSIFICATION	7
2.4 TEST RESULT	8



Revision History

Rev.	Issue Date	Revisions
00	Aug.29, 2025	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	LED wireless sensor	
Trademark:	LUMILAND	
Test Model Name:	2BRY7-96686DS	
Series Model:	2BRY7-96686DS-XX ("XX" stands for "BK, TG, SG, WT, GR")	
Model Difference:	Only the model and color are different	
Frequency Bands:	SRD	2409 MHz
Battery:	DC 3V By battery	
Hardware Version:	N/A	
Software Version:	N/A	

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
0.3-3.0	614	1.63	*(100)
3.0-30	1842/f	4.89/f	*(900/f ²)
30-300	61.4	0.163	1.0
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
0.3-1.34	614	1.63	*(100)
1.34-30	824/f	2.19/f	*(180/f ²)
30-300	27.5	0.073	0.2
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

* = Plane-wave equivalent power density.

Friis Formula

Friis Transmission Formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.4 TEST RESULT

dBuV/m	dBm
95.24	0.04

dBm=dBuV/m-95.2

Turn up Result

Mode	Turn up Power
2.4G-GFSK	0±1dBm

The MPE result of worst mode:

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Max Turn up Power (mW)	Estimated SAR	Limit	Ratio	Result
GFSK	2409	1.00	1.26	0.391	3	0.130	Pass

Note:

1. The Maximum Power Density is less than the limit, complies with the exemption requirements.

※※※※ END OF THE REPORT ※※※※