

TEST REPORT

Product Name : Mouse with Tail-Assortment
Model Number : FBWM1300AST1, FBWM1300-COW,
FCC ID : FBWM1300-PIG, FBWM1300-WHL
2BRYN-RCV

Prepared for : Guangdong Heminway Electronics Co.,Ltd
Address : Building W2, Tianan Shenchuang Valley West District,
Feng Gang, DONG GUAN, CHINA

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2508260132W00502R
Date of sample receipt : Aug 26, 2025
Date(s) of Tests : Aug 26, 2025 to Sep 15, 2025
Date of issue : Sep 16, 2025

Table of Contents

1. TEST RESULT CERTIFICATION.....	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Guangdong Heminway Electronics Co.,Ltd
 Address : Building W2, Tianan Shenchuang Valley West District, Feng Gang, DONG GUAN, CHINA
 Manufacturer : Guangdong Heminway Electronics Co.,Ltd
 Address : Building W2, Tianan Shenchuang Valley West District, Feng Gang, DONG GUAN, CHINA
 Factory : Guangdong Heminway Electronics Co.,Ltd
 Address : Building W2, Tianan Shenchuang Valley West District, Feng Gang, DONG GUAN, CHINA
 EUT : Mouse with Tail-Assortment
 Model Name : FBWM1300AST1, FBWM1300-COW, FBWM1300-PIG, FBWM1300-WHL
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Aug 26, 2025 to Sep 15, 2025

Prepared by : Una Yu
Una Yu /Editor

Reviewer : Joe Xia
Joe Xia/Supervisor

Approve & Authorized Signer : Lisa Wang
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2508260132W00502R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Mouse with Tail-Assortment
Model Number:	FBWM1300AST1, FBWM1300-COW, FBWM1300-PIG, FBWM1300-WHL (Note: These models are the same, except for the model numbers and colors;FBWM1300AST1 was selected for full test.)
Sample:	1#
Modulation:	GFSK
Operating Frequency Range(s) :	2402-2479MHz
Number of Channels:	16 channels
Transmit Power Max:	-1.94 dBm(0.000640W)
Antenna Gain:	3.55 dBi
Power supply:	DC 5V from USB
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 3.55 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	EIRP (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	Calculation threshold(1-g SAR)
2402	GFSK	-1.94	1.61	1±1	2	0.4913	3
2446	GFSK	-2.27	1.28	1±1	2	0.4957	3
2479	GFSK	-3.42	0.13	0±1	1	0.3964	3

According to KDB 447498 D01 V06, no stand-alone required for 2.4G SRD antenna, and no simultaneous SAR measurement is required.

*** End of Report ***