

## Letter of declaration KDB680106 requirement

### Federal Communications Commission

Equipment Authorization Division, Application Processing Branch  
7435 Oakland Mills Road  
**Columbia, MD 21048**

**Date: 2025-9-3**

**FCC ID: 2BRZJ-SYJ-A011C**

**Model Number: SYJ-A011C**

To Whom It May Concern,


We, <Shenzhen SYJ Gift Co., Ltd>, hereby declare that our product (as above) meet item 5.2 of KDB 680106v03r01 as follow:

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 111kHz - 205kHz
The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.	Yes	The maximum output power of the primary coil is 15W.
A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)	Yes	Client device is placed directly in contact with the transmitter.
Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover §2.1093-Portable exposure conditions).	Yes	EUT is a mobile device
The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Yes	Fulfil requirements

For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested	Yes	EUT has only one coil
--	-----	-----------------------

Please do not hesitate to contact us for further explanations or comments.

Sincerely,



2025-9-3

---

Signature

Date

Printed Name of Signee: Yingyu Zhang

Company: Shenzhen SYJ Gift Co., Ltd

Address: A Entrance, 4th Floor, Block B, Xuexiang Yuandong Industrial Park, Bantian, Longgang District, Shenzhen city, Guangdong Province, China

Phone: 13172459540

Email: ying@sykusb.com