

FCC RF Exposure

EUT Description: Screen Mirroring Display

Model No.: TP10

FCC ID: 2BSAZ-TP10

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[[max power of channel, including tune - up tolerance, mW]/(min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result= $P/D \cdot \sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

	Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power (dBm/mW)	Min test separation distance (mm)	Result	Limit	SAR Test Exclusion
EDR	2440	1.69	1 ± 1	2/1.585	5	0.495	3.0	Pass
2.4G WiFi	2422	4.95	4 ± 1	5/3.162	5	0.984	3.0	Pass
5.2G WiFi	5190	2.58	2 ± 1	3/1.995	5	0.909	3.0	Pass

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2508154600-1E/2E/3E**, BT antenna gain=2.25dBi, 2.4GWiFi antenna gain=1.63dBi, 5.2GWiFi antenna gain=1.76dBi.

BT and 2.4GWiFi Simultaneous evaluation:

$0.495 / 3 + 0.984 / 3 = 0.493 < 1$, SAR testing is not required

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold meets the requirements, SAR testing is not required.

Note: Exclusion Thresholds Results= $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm