



Test report No:
NIE: 61299RRF003

Partial Test report

USA FCC Part 15.247,15.407, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices.

Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Unlicensed National Information Infrastructure (U-NII) Devices:

General technical requirements.

Radiated emission limits; general requirements.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs)

and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	Automotive Infotainment System
(*) Trademark	BMW
(*) Model and /or type reference	MGU_F APN
Other identification of the product	HW version: HW 3.1 SW version: 19w20.5-1-16 FCC ID: A269ZUA160 IC: 700B-UA160
(*) Features	BT, WiFi, USB2/3
Applicant	ALPSALPINE INC. 20-1 YOSHIMA INDUSTRIAL PARK, IWAKI, FUKUSHIMA 970-1192, JAPAN
Test method requested, standard	USA FCC Part 15.407 (10-1-18) Edition: Unlicensed National Information Infrastructure (U-NII) Devices. General technical requirements. Band U-NII-3 (5725 MHz – 5850 MHz). USA FCC Part 15.247 (10-1-18) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-18) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (April 2018). -Transmitter out of band radiated emissions with simultaneous transmissions. Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. Guidance for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE

Approved by (name / position & signature)	Jose Carlos Luque RF Lab. Supervisor
Date of issue	2020-01-07
Report template No	FDT08_22 (*) "Data provided by the client"

Index

Competences and guarantees4

General conditions.....4

Uncertainty.....4

Data provided by the client4

Usage of samples4

Test sample description.....5

Identification of the client8

Testing period and place8

Document history.....8

Environmental conditions8

Remarks and comments.....9

Testing verdicts.....10

Summary10

Appendix A: Test results.....11

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of MGU_F APN is a device for entertainment and communication inside the car, this includes playing music from several external sources or internal flash-memory, connecting mobile devices (e.g. Apple Car Play) and a navigation system.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
61299/058	Automotive Infotainment System	MGU_F APN	ALB314K0672984	2019/07/24
61299/043	CAN Box	--	J0035319	2019/07/16
61299/046	Display	--	--	2019/07/16
61299/061	Ethernet Board	--	--	2019/07/24
61299/064	Ethernet-USB Adapter	EU-4306	EU430693MA00744	2019/07/24
61299/065	Harness	--	--	2019/07/24
61299/111	Antenna	--	--	2019/08/30
61299/112	Antenna			2019/08/30

Sample S/01 has undergone the following test(s): The RADIATED tests indicated in Appendix A for the mode bluetooth basic rate, 802.11 b and 802.11 a20 U-NII-1.

- Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
61299/057	Automotive Infotainment System	MGU_F APN	ALB314K0673026	2019/07/24
61299/046	Display	--	--	2019/07/16
61299/059	CAN Box	--	80008147	2019/07/24
61299/061	Ethernet Board	--	--	2019/07/24
61299/064	Ethernet-USB Adapter	EU-4306	EU430693MA00744	2019/07/24
61299/065	Harness	--	--	2019/07/24
61299/111	Antenna			2019/08/30
61299/112	Antenna			2019/08/30

Sample S/02 has undergone the following test(s): The RADIATED tests indicated in Appendix A for the mode bluetooth basic rate, 802.11 b and 802.11 a20 U-NII-3.

Test sample description

Ports..... :	Port name and description	Cable					
		Specified length [m]	Attached during test	Shielded			
	BT		☒	☐			
	WLAN		☒	☐			
	USB2		☒	☐			
	USB3		☒	☐			
	APIX		☒	☐			
	OABR		☒	☐			
Supplementary information to the ports..... :	N/A						
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☒	DC: 12Vdc.					
Rated Power	12V						
Clock frequencies.....	Not provided data						
Other parameters	FCC ID: A269ZUA160 IC: 700B-UA160						
Software version	19w20.5-1-16						
Hardware version	HW 3.1						
Dimensions in cm (L x W x D).....	Not provided data						
Mounting position	☒	Table top equipment					
	☒	Other: Vehicular environment equipment					
Modules/parts..... :	Module/parts of test item		Type		Manufacturer		
	BT				WNC		
	WiFi				WNC		
Accessories (not part of the test item)	Description		Type		Manufacturer		
	Can Box				Harman		
	Display				Visteon		
	OABR-converter				Harman		
	Description		File name		Issue date		

Documents as provided by the applicant	Testing manual for BT and WLAN	I&k-MGU_Testing Manual (Radio_WLAN-BT)_v11_2018-01-18	18.1.2018
	-		
	-		

Identification of the client

ALPINE ELECTRONICS GMBH
Ohmstrasse 4, 85716 Unterschleißheim, Germany

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2019-09-10
Date (finish)	2019-12-12

Document history

Report number	Date	Description
61299RRF003	2020-01-07	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

The tests have been performed by the technical personnel: Ignacio Cabra, Cristina Calle.

Used instrumentation:

Radiated Measurements:

	Last Calibration	Due Calibration
1. Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2. EMI Test Receiver ROHDE AND SCHWARZ ESR7	2018/10	2020/10
3. BiconicalLog antenna ETS LINDGREN 3142E	2017/09	2020/09
4. RF Pre-amplifier 40 dB, 10 MHz-6 GHz BONN ELEKTRONIK BLNA 0160-01N	2019/02	2020/08
5. Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40	2018/02	2020/02
6. RF Pre-amplifier, 30 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-3A	2019/04	2020/04
7. Broadband Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2018/01	2021/01
8. RF Pre-amplifier 30 dB, 18 GHz-40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
9. Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2018/07	2021/07
10. DC Power Supply Keysight Technologies U8002A	---	---
12. Biconical/Log Antenna 30 MHz - 6 GHz ETS LINDGREN 3142E	2017/04	2020/04
13. DC Power Supply, 30V, 5A KEYSIGHT TECHNOLOGIES U8002A	N.A.	N.A.
14. Multimeter FLUKE 179	2019/06	2020/06
15. Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
16. Shielded Room ETS LINDGREN S101	N.A.	N.A.
17. Multi-device Controller EMCO 2090	N.A.	N.A.
18. Multi-device Controller FRANKONIA FC-06	N.A.	N.A.
19. Low Pass Filter DC - 1 GHz WAINWRIGHT INSTRUMENTS WLK1000-6SS	2018/06	2020/06
20. EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2018/10	2020/10
21. Pre-Amplifier G>40dB 10MHz-6GHz, BONN ELEKTRONIK, BLNA 0160-01N	2019/02	2020/02
22. Spectrum Analyzer ROHDE AND SCHWARZ FSW50	2018/02	2020/02
23. RF Pre-amplifier, 40 dB ,1-18 GHz BONN ELEKTRONIK BLMA 0118-1M	2019/04	2020/04
24. Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M	2018/02	2020/02
25. Broadband Horn Antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2018/07	2021/07

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

FCC PART 15 PARAGRAPH / RSS-247		
Requirement – Test case	Verdict	Remark
FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.2.2, 6.2.3.2 & 6.2.4.2: - Emission limitations radiated (Transmitter)	P	(1)
<u>Supplementary information and remarks:</u> (1) Only co-location radiated spurious emission test was requested.		

Appendix A: Test results.

INDEX

TEST CONDITIONS13

FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.2.2, 6.2.3.2 & 6.2.4.2 Emission
limitations radiated (Transmitter)18

TEST CONDITIONS

POWER SUPPLY (V):

V nominal: 12 Vdc.
Type of Power Supply: External power supply (Car Battery).

ANTENNA:

Bluetooth EDR and 802.11 bgn20 1x1:

Type of Antenna: External antenna.
Maximum Declared Antenna Gain: -6.2 dBi (Antenna gain plus antenna cable loss).

802.11 a20 / n2040 / ac2040 / ac80 1x1:

Type of Antenna: External antenna.
Maximum Declared Antenna Gain: -5.4 dBi (antenna gain plus antenna cable loss).

RADIOS AND CHANNELS TESTED:

	Bluetooth EDR (FHSS)	
Mode:	Basic Rate (GFSK - DH5)	
Channel Spacing:	1 MHz	
Frequency Range:	2402 MHz to 2480 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	39	2441

	WLAN (IEEE 802.11 bgn20 1x1) / Digital Transmission System (DTS)	
Mode:	802.11 b: 1, 2, 5.5 & 11 Mbps (SISO)	
Channel Spacing:	20 MHz	
Frequency Range:	2412 MHz to 2472 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	6	2437

	WLAN (IEEE 802.11 anac) / U-NII-1	
Mode:	802.11 a20: 6, 9, 12, 18, 24, 36, 48 & 54 Mbps (SISO)	
Frequency Range:	5150 MHz to 5250 MHz	
Channel Spacing:	20 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	Middle: 40	5200

	WLAN (IEEE 802.11 anac) / U-NII-3	
Mode:	802.11 a20: 6, 9, 12, 18, 24, 36, 48 & 54 Mbps (SISO)	
Frequency Range:	5725 MHz to 5850 MHz	
Channel Spacing:	20 MHz	
Transmit Channels	Channel	Channel Frequency (MHz)
	Middle: 157	5785

The test set-up was made in accordance to the general provisions of FCC DTS Measurement 558074 D01 DTS Meas Guidance v05r2 dated April 2, 2019 and FCC Unlicensed National Information Infrastructure (U-NII) Devices 789033 D02 General U-NII Test Procedures New Rules v02r01 dated Dec 14, 2017.

The EUT was tested in the following operating mode:

- Continuous transmission with a modulated carrier at maximum power in all required channels selecting the supported data rates/modulations types.

During transmitter test the EUT was being controlled by the SW tool to operate in a continuous transmit mode on the test channel as required and in each of the different modulation modes.

The following configurations were selected based on preliminary testing that identified those corresponding to the worst cases:

Transmission modes selected with each radio:

* Bluetooth Basic Rate: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in Basic Rate mode because its power is higher than EDR mode.

* 2.4 GHz WLAN: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 802.11 b / 1Mbps / SISO mode configuration as this mode was found to transmit higher EIRP than all the other 2.4 GHz WLAN modes.

* 5 GHz U-NII-1 WLAN: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in U-NII-1 802.11a 20 / 6Mbps / SISO mode configuration as this mode was found to transmit higher EIRP than all the other 5 GHz WLAN modes.

* 5 GHz U-NII-3 WLAN: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in U-NII-3 802.11a 20 / 6Mbps / SISO mode configuration as this mode was found to transmit higher EIRP than all the other 5 GHz WLAN modes.

Simultaneous transmission modes selected:

* **Bluetooth Basic Rate, 2.4 GHz WLAN and 5 GHz U-NII-1 WLAN co-location**, with the EUT configured to simultaneously transmit three signals at maximum output power, Bluetooth Basic Rate in DH5 mode, 2.4GHz WLAN (Wi-Fi) in 802.11b / 1 Mbps / SISO and 5GHz WLAN (Wi-Fi) in 802.11a20 / 6 Mbps / SISO.

* **Bluetooth Basic Rate, 2.4 GHz WLAN and 5 GHz U-NII-3 WLAN co-location**, with the EUT configured to simultaneously transmit three signals at maximum output power, Bluetooth Basic Rate in DH5 mode, 2.4GHz WLAN (Wi-Fi) in 802.11b / 1 Mbps / SISO and 5GHz WLAN (Wi-Fi) in 802.11a20 / 6 Mbps / SISO.


RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m. The EUT was placed at a height of 80 cm above the reference ground plane in the center of the chamber turntable to perform the measurements below 1GHz and The EUT was placed at a height of 1.5 meters above the test chamber floor in the center of the chamber turntable to perform the measurements above 1GHz. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

The final measured value, for the given emission, in the tables below incorporates the calibrated antenna factor, preamplifier gain (if used) and cable losses.


Radiated measurements setup $9 \text{ kHz} < f < 30 \text{ MHz}$:




Radiated measurements setup $30 \text{ MHz} < f < 1 \text{ GHz}$:



Radiated measurements setup $f > 1 \text{ GHz}$ up to 18 GHz:



Radiated measurements setup $f > 18$ GHz up to 40 GHz:



FCC 15.209 (a), 15.247 (d), 15.407 (b) / RSS-Gen 8.9, RSS-247 5.5, 6.2.1.2, 6.2.4.2 Emission limitations radiated (Transmitter)

SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), appearing outside of the band 13.110 MHz - 14.010 MHz band must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	29.54	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 40000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-40 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Test performed on the following worst cases in all relevant tests channels:

- **Mode Bluetooth BR, 802.11 b, 802.11 a20 U-NII-1.**

Bluetooth EDR:	GFSK (2441 MHz).
802.11 b:	20MHz, 1Mbps, SISO, Port 2 (2437 MHz).
802.11 a20:	20MHz, 6Mbps, SISO, Port 1 (5200 MHz).

Frequency range 30 MHz - 1 GHz

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

No spurious frequencies detected at less than 20 dB below the limit.


Frequency range 1 - 40 GHz

Spurious frequencies detected at less than 20 dB below the limit:


Spurious frequency (GHz)	Emission Level (dBμV/m)	Polarization	Detector	Measurement Uncertainty (dB)
1.39701	49.21	H	Peak	<±3.04
1.7999	44.16	H	Peak	<±3.04
10.0010	45.87	V	Peak	<±4.88
10.39288	54.26	V	Peak	<±4.88

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz




FREQUENCY RANGE 1 – 6.5 GHz




The peaks above the limit are the Bluetooth EDR, Wi-Fi 2.4 GHz and Wi-Fi 5 GHz carrier frequencies.


FREQUENCY RANGE 6.5 - 17 GHz



FREQUENCY RANGE 17 - 26 GHz



FREQUENCY RANGE 26 - 40 GHz



- **Mode Bluetooth BR, 802.11 b, 802.11 a20 U-NII-3.**

Bluetooth EDR:	GFSK (2441 MHz).
802.11 b:	20MHz, 1Mbps, SISO, Port 2 (2437 MHz).
802.11 a20:	20MHz, 6Mbps, SISO, Port 1 (5785 MHz).

Frequency range 30 MHz - 1 GHz

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

Spurious frequencies detected at less than 20 dB below the limit:

Spurious frequency (MHz)	Emission Level (dBμV/m)	Polarization	Detector	Measurement Uncertainty (dB)
86.697	21.9	V	Quasi peak	<± 2.07
375.013	26.7	V	Quasi peak	<± 2.07
542.209	28.8	V	Quasi peak	<± 2.07
750.015	29.7	H	Quasi peak	<± 2.07


Frequency range 1 - 40 GHz

Spurious frequencies detected at less than 20 dB below the limit:


Spurious frequency (GHz)	Emission Level (dBμV/m)	Polarization	Detector	Measurement Uncertainty (dB)
1.39858	43.73	H	Peak	<±3.04
1.50042	45.18	V	Peak	<±3.04
5.63799	53.87	V	Peak	<±4.88
11.57083	60.87	V	Peak	<±4.88
	50.81		Average	<±4.88

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz




FREQUENCY RANGE 1 – 5.65 GHz




The peaks above the limit are the Bluetooth EDR and Wi-Fi 2.4 GHz carrier frequencies.

FREQUENCY RANGE 5.65 – 5.68 GHz




FREQUENCY RANGE 5.68 – 5.898 GHz




The peak above the limit is the Wi-Fi 5 GHz carrier frequency.


FREQUENCY RANGE 5.898 – 5.925 GHz



FREQUENCY RANGE 5.925 - 7 GHz



FREQUENCY RANGE 7 - 17 GHz



FREQUENCY RANGE 17 - 40 GHz

