

Certis Technology International Pte Ltd.

Access Control Reader

Model: MP-8000

November 21, 2011
Report No.: 11021322-FCC
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

Deon Dai Test Engineer	Alex Liu Technical Manager

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.





Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless , Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC, (RCB 208)	RF , Telecom
HongKong	OFTA (US002)	RF , Telecom



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 3 of 34
www.siemic.com.cn

This page has been left blank intentionally.



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 4 of 34
www.siemic.com.cn

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
	ANNEX A. TEST INSTRUMENT & METHOD	18
	ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	22
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	28
	ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	32
	ANNEX E. SIEMIC ACCREDITATION CERTIFICATES.....	33



1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Certis Technology International Pte Ltd., Access Control Reader , and model: MP-8000 against the current Stipulated Standards. The Access Control Reader has demonstrated compliance with the FCC Part 15.207;15.209: 2011.

EUT Information

EUT : Access Control Reader
Description
Model No : MP-8000 (Note)
Serial No : N/A
Input Power : Voltage:10-15V, Current:160mA(max)
Classification
Per Stipulated : FCC Part 15.207; 15.209:2011
Test Standard

Note: Series model RP-8000, RPK-8000, OPK-8000, ME-8000, REK-8000, RE-8000, ME-3000, REK-3000, RE-3000, MP-3000, RPK-3000, RP-3000, only look different other identical.



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 6 of 34
www.siemic.com.cn

2 TECHNICAL DETAILS

Purpose	Compliance testing of Access Control Reader with stipulated standard
Applicant / Client	Certis Technology International Pte Ltd. Certis CISCO Centre 20, Jalan Afifi, Singapore 409179
Manufacturer	Certis Technology International Pte Ltd. Certis CISCO Centre 20, Jalan Afifi, Singapore 409179
Laboratory performing the tests	SIEMIC Nanjing (China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: info@siemic.com
Test report reference number	11021322-FCC
Date EUT received	October 21, 2011
Standard applied	FCC Part 15.207;15.209: 2011
Dates of test (from – to)	November 13 to November 18, 2011
No of Units :	#1
Equipment Category :	DXX
Trade Name :	Certis
Model :	MP-8000
RF Operating Frequency (ies) :	125kHz(RFID)
Number of Channels :	1
FCC ID :	X3A-SMARFID



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 7 of 34
www.siemic.com.cn

3 MODIFICATION

NONE



4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Class B Emission Product

Test Results Summary

Test Standard	Description	Pass/Fail
FCC Part 15 :2011		
15.203	Antenna Requirement	Pass
15.207(a)	Conducted Emissions Voltage	Pass
15.209	Radiated Emissions	Pass
15.209	Fundamental & Radiated Spurious Emission	Pass
2.1049	Occupied Bandwidth	Pass



5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The antenna is permanently attached to the device.

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 10 of 34
www.siemic.com.cn

5.2 Conducted Emissions Voltage

Requirement(s): 47 CFR §15.207

Requirement:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Procedures:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ± 3.5 dB.
4. Environmental Conditions Temperature 21°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
5. Test date : N/A
Tested By : Deon Dai

Not applicable (No power adapter included)



5.3 Radiated Emission <30MHz(9KHz – 30MHz, H-Field)

Requirement(s): 47 CFR § 15.209

Procedures: For <30MHz, Radiated emissions were measured according to ANSIC63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the centre of the loop. The measuring bandwidth was set to 10KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT.)

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude=Raw Amplitude(dBuV/m)+ACF(dB)+Cable Loss(dB)-Distance Correction Factor

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors are reported. All other emissions were relatively insignificant.
2. A “-ve” margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.
4. Environmental Conditions Temperature 21°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
5. Test date : 14 November, 2011
Tested By : Deon Dai

The result: Pass

**SIEMIC, INC.**


Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 12 of 34
www.siemic.com.cn

Loop Antenna Positioned at 90 degree

Frequency	Measure	Reading	Factor	Correct	Limit@3m	Margin
(MHz)	(Avg/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
21.84	Peak	18.27	13.87	32.14	49.08	-16.94

**Note:**

- (1) Emissions from 9KHz to 1MHz is very low under transmit mode so test data is not presented in this report.
- (2) Emissions from 9KHz to 30MHz is very low under receiver mode so test data is not presented in this report.



5.4 Radiated Emissions >30MHz(30MHz-1GHz,E-Field)

Requirement(s): 47 CFR § 15.209

Procedures: For >30MHz, Radiated emissions were measured according to ANSIC63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The Log periodic antenna was positioned 1 meter above the ground from the centre of the antenna. The measuring bandwidth was set to 120KHz. (Note: During testing the receive antenna was raise from 1-4meters to maximize the emission from the EUT.)

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude=Raw Amplitude(dBuV/m)+ACF(dB)+Cable Loss(dB)-Distance Correction Factor

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors are reported. All other emissions were relatively insignificant.
2. A “-ve” margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, is +/-6dB.
4. Environmental Conditions Temperature 21°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
5. Test date : November 14, 2011
Tested By : Deon Dai

The result: Pass



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011


Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 14 of 34
www.siemic.com.cn

Test mode:

Normal working

30MHz to 1GHz Radiated Emission Test Results
Horizontal

Peak Detector 
Quasi Peak Limit 



Test Data

Frequency (MHz)	Peak (dBuV/m)	Azimuth	Polarity(H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
905.18	39.88	270.60	V	300.00	-15.17	46.00	-6.12
900.33	39.85	260.00	V	300.00	-15.13	46.00	-6.15
945.20	35.81	278.10	V	100.00	-15.50	46.00	-10.19
914.15	34.88	206.00	V	200.00	-15.23	46.00	-11.12
939.01	34.70	208.90	V	200.00	-15.58	46.00	-11.30
44.91	28.10	260.50	V	100.00	-33.99	40.00	-11.90

**SIEMIC, INC.**

Accessing global markets


Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 15 of 34
www.siemic.com.cn

Test mode:**Normal working**

30MHz to 1GHz Radiated Emission Test Results
Horizontal

Peak Detector 
Quasi Peak Limit 

**Test Data**

Frequency (MHz)	Peak (dBuV/m)	Azimuth	Polarity(H/V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
908.46	38.33	306.90	H	400.00	-14.83	46.00	-7.67
943.25	34.96	216.20	H	300.00	-15.11	46.00	-11.04
197.57	32.12	219.70	H	200.00	-30.32	43.50	-11.38
938.89	34.14	248.30	H	300.00	-15.19	46.00	-11.86
958.53	34.03	153.30	H	100.00	-14.67	46.00	-11.97
592.84	34.02	104.10	H	200.00	-23.33	46.00	-11.98



5.5 Fundamental Field Strength Test Result

Test Requirement:

125KHz – The fundamental field strength should not exceed general spurious emission requirement.

Dipole Antenna at 90 degree

Frequency	Measure	Reading	Factor	Correct	Limit@3m	Margin
(MHz)	(Avg/QP)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
0.125	Peak	12.74	64.76	77.50	105.67	-28.17

5.6 Occupied Bandwidth


Requirement(s): None

Procedures: Occupied Bandwidth was measured according to 47 CFR § 2.1049. Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz.

Frequency (kHz)	99% bandwidth (kHz)
125.85	3.307

Test Result: Pass

Plots: 125 KHz





Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 18 of 34
www.siemic.com.cn

Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Manufacturer	Model	CAL Due Date
Spectrum Analyzer	HP	8563 E	2012.01.10
EMI Receiver	Rohde & Schwarz	ESPI 3	2012.05.25
Antenna (30MHz~2GHz)	Sunol Sciences	JB1	2012.10.04
Horn Antenna (1~18GHz)	A-INFOMW	JXTXLB-10180	2012.06.24
Horn Antenna (1~18GHz)	ETS-Lindgren	3115	2012.10.03
Pre-Amplifier(0.01 ~ 1.3GHz)	HP	8447F	2012.05.25
Pre-Amplifier(0.1 ~ 18GHz)	MITEQ	AMF-7D-00101800-30- 10P	2012.05.25
Horn Antenna (18~40GHz)	Com Power	AH-840	2012.05.21
Microwave Pre-Amp (18~40GHz)	Com Power	PA-840	2012.05.21
RF POWER METER	BOONTON	4231A	2012.04.23
POWER SENSOR	BOONTON	51011-EMC	2012.04.23



Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz

limit = $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$
(Calibrated for system losses)

Therefore, Q-P margin = $47.96 - 40.00 = 7.96$

i.e. **7.96 dB below limit**



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 20 of 34
www.siemic.com.cn

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.





Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor} \text{ or}$$
$$\text{Set RBW} = 1\text{MHz}, \text{VBW} = 10\text{Hz}.$$

Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209-2011


Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 22 of 34
www.siemic.com.cn

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph: EUT External Photo



Front View of EUT




Rear View of EUT



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 23 of 34
www.siemic.com.cn



Bottom View of EUT



Top View of EUT



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 24 of 34
www.siemic.com.cn



Left View of EUT



Right View of EUT




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 25 of 34
www.siemic.com.cn

Annex B.ii. Photograph: EUT Internal Photo



Rear View of Main PCB Board



Front View of Main PCB Board




SIEMIC, INC.

Accessing global markets


Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209-2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 26 of 34
www.siemic.com.cn

Annex B.iii. Photograph: Test Setup Photo



Front View of Radiated Emission Test Setup below 30MHz



Rear View of Radiated Emission Test Setup below 30MHz




SIEMIC, INC.


Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 27 of 34
www.siemic.com.cn



Front View of Radiated Emission Test Setup above 30MHz



Rear View of Radiated Emission Test Setup above 30MHz



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 28 of 34
www.siemic.com.cn

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
N/A	N/A	N/A



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 29 of 34
www.siemic.com.cn

Block Configuration Diagram for Conducted Emissions

N/A




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 30 of 34
www.siemic.com.cn

Block Configuration Diagram for Radiated Emissions





SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 31 of 34
www.siemic.com.cn

Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was continuously transmitting to stimulate the worst case.



Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207;15.209- 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 32 of 34
www.siemic.com.cn

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 33 of 34
www.siemic.com.cn

Annex E. SIEMIC ACCREDITATION CERTIFICATES

SIEMIC ACCREDITATION DETAILS: FCC Listing, Registration NO:986914

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

April 19, 2011

Registration Number: 986914

SIEMIC Nanjing (China) Laboratories
2-1 Longcang Avenue,
Yuhua Economic and Technology Development Park,
Nanjing, 210039
China

Attention: Leslie Bai,

Re: Measurement facility located at 2-1 Longcang Avenue, Nanjing, China
Anechoic chamber (3 meters) and 3&10 meter OATS
Date of Renewal: April 19, 2011

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish
Industry Analyst




SIEMIC, INC.

Accessing global markets

Title: RF Test Report for Access Control Reader
Model: MP-8000
To: FCC Part 15.207/15.209: 2011

Serial#: 11021322-FCC
Issue Date: November 21, 2011
Page: 34 of 34
www.siemic.com.cn

SIEMIC ACCREDITATION DETAILS: Industry of Canada Registration No. 4842



January 25, 2011

OUR FILE: 46405-4842
Submission No: 145222

Siemic Nanjing (China) Laboratories
2-1 Longcang Avenue
Yuhua Economic & Technology Dev. Park, Nanjing
China

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (Site# 4842B-2). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: 4842B

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed three years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Dalwinder Gill
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
Email: dalwinder.gill@ic.gc.ca
Tel. No. (613) 998-8363
Fax. No. (613) 990-4752