

RF EXPOSURE REPORT



Report No.: 15070621-FCC-H

Applicant	Shenzhen Creative Industry Co., Ltd.	
Product Name	Video Baby Monitor	
Model No.	IPC100	
Serial No.	N/A	
Test Standard	FCC 2.1091:2014	
Test Date	September 03 to October 14, 2015	
Issue Date	October 14, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Winnie Zhang	David Huang	
Winnie Zhang Test Engineer	Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070621-FCC-H
Page	3 of 9

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
6.1 APPLICABLE STANDARD.....	7
6.2 TEST RESULT	8

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070621-FCC-H	NONE	Original	October 14, 2015

2. Customer information

Applicant Name	Shenzhen Creative Industry Co., Ltd.
Applicant Add	2/F, Block 3, Nanyou Tian'an Industry Town, Guangd, Shenzhen, China,518054
Manufacturer	MC Devices Co., Ltd.
Manufacturer Add	Suite 516 BLD 4, National Software Base, Ke ji zhong 2 Road, Shenzhen Hi-Tech Park, Shenzhen, 518.57, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

4. Equipment under Test (EUT) Information

Description of EUT: Video Baby Monitor

Main Model: IPC100

Serial Model: N/A

Equipment Category : PCB

Antenna Gain: WIFI: 3dBi
 433MHz Receiver: 0dBi

Adapter:

Input Power: Model :PS10E050K2000UU
 Input :100-240Vac, 50/60Hz, 0.35A
 Output :5.0Vdc, 2000mA

Trade Name : N/A

FCC ID: A49IPC100

Type of Modulation: 802.11b/g/n: DSSS, OFDM

RF Operating Frequency (ies): WIFI:802.11b/g/n(20M): 2412-2462 MHz
 WIFI:802.11n(40M): 2422-2452 MHz
 Receiver: 433MHz

Number of Channels: WIFI :802.11b/g/n(20M): 11CH
 WIFI :802.11n(40M): 7CH
 Receiver: 1CH

5. FCC §2.1091 - Maximum Permissible exposure (MPE)

6.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

6.2 Test Result

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	802.11b	Low	2412	13.39	13.5±1
		Mid	2437	14.05	13.5±1
		High	2462	14.17	13.5±1
	802.11g	Low	2412	12.98	13.5±1
		Mid	2437	12.90	13.5±1
		High	2462	13.54	13.5±1
	802.11n (20M)	Low	2412	12.54	12±1
		Mid	2437	13.43	13.5±1
		High	2462	13.63	13.5±1
	802.11n (40M)	Low	2422	11.95	12±1
		Mid	2437	12.04	12±1
		High	2452	12.32	12±1

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum output power at antenna input terminal: 14.5(dBm)

Maximum output power at antenna input terminal: 28.18(mW)

Test Report	15070621-FCC-H
Page	9 of 9

Prediction distance: >20 (cm)

Predication frequency: 2462 (MHz) High frequency

Antenna Gain (typical): 3 (dBi)

The worst case is power density at predication frequency at 20 cm: 0.01(mW/cm²)

MPE limit for general population exposure at prediction frequency: 1.0 (mW/cm²)

0.01(mW/cm²) < 1.0 (mW/cm²)

Result: Pass