



RF TEST REPORT

Report No.: SET2020-05313

Product Name: Fingertip Oximeter

FCC ID: A49PC-60FW

Model No. : PC-60FW

Applicant: Shenzhen Creative Industry Co., Ltd.

Address: Floor 5, BLD 9, Baiwangxin High-Tech Industrial Park, Songbai Road, Xili Street, Nanshan District, 518110 Shenzhen, P. R. China.

Dates of Testing: 05/10/2020 —05/27/2020

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 36 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name : Fingertip Oximeter

Brand Name : N/A

Trade Name : N/A

Applicant : Shenzhen Creative Industry Co., Ltd.

Applicant Address : Floor 5, BLD 9, Baiwangxin High-Tech Industrial Park,
Songbai Road, Xili Street, Nanshan District, 518110
Shenzhen, P. R. China.

Manufacturer : Shenzhen Creative Industry Co., Ltd.

Manufacturer Address : Floor 5, BLD 9, Baiwangxin High-Tech Industrial Park,
Songbai Road, Xili Street, Nanshan District, 518110
Shenzhen, P. R. China.

Test Standards : 47 CFR Part 15 Subpart C: Radio Frequency Devices
ANSI C63.10-2013 : American National Standard for
Testing Unlicensed Wireless Devices
KDB558074 D01 DTS Meas Guidance v05r02

Test Result : PASS

Tested by : *Vincent*
2020.07.20

Vincent, Test Engineer

Reviewed by : *Chris You*
2020.07.20

Chris You, Senior Engineer

Approved by : *Shuangwen Zhang*
2020.07.20

Shuangwen Zhang, Manager

TABLE OF CONTENTS

RF TEST REPORT	1
1. GENERAL INFORMATION	4
1.1. EUT Description	4
1.2. Test Standards and Results.....	5
1.3. Table for Supporting Units.....	6
1.4. Facilities and Accreditations	7
2. 47 CFR PART 15C REQUIREMENTS.....	8
2.1. Antenna requirement.....	8
2.2. Peak Output Power.....	9
2.3. 6dB Bandwidth	10
2.4. Conducted Band Edges and Spurious Emissions.....	11
2.5. Power spectral density (PSD)	13
2.6. Radiated Band Edge and Spurious Emission.....	15
3. LIST OF MEASURING EQUIPMENT	23
4. UNCERTAINTY OF EVALUATION	24
APPENDIX A	25

Change History		
Issue	Date	Reason for change
1.0	2020.07.20	First edition

1. General Information

1.1. EUT Description

EUT Type	Fingertip Oximeter	
Frequency Range	Bluetooth LE 5.2	2402MHz~2480MHz
Channel Number	Bluetooth LE 5.2	40
Bit Rate of Transmitter	Bluetooth LE 5.2	1/2Mbps
Modulation Type	Bluetooth LE 5.2	GFSK
Antenna Type	PCB	
Antenna Gain	-1dBi	

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

1.2. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC Certification:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	Description	Result
1	15.203	Antenna Requirement	PASS
2	15.247(b)	Peak Output Power	PASS
3	15.247(a)	Bandwidth	PASS
4	15.247(d)	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	Power spectral density (PSD)	PASS
6	15.207	Conducted Emission	N/A
7	15.209 15.205 15.247(d)	Radiated Band Edges and Spurious Emission	PASS

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2013.

These RF tests were performed according to the method of measurements prescribed in KDB 558074D01 v05r02.

40 channels are provided for Bluetooth LE

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464

12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

	Test Items	Modulation	Channel
Bluetooth LE	Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Conducted and Spurious Emission Radiated and Spurious Emission	GFSK (1M/2M)	0/20/39
	Band Edge	GFSK (1M/2M)	0/39

1.3. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Notebook	DELL	PP11L	DELL	H5914A03	FCC DOC

1.4. Facilities and Accreditations

1.4.1. Facilities

CNAS-Lab Code: L1659

CCIC-SET is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

FCC-Registration No.: CN5031

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. DesignationNumber: CN5031, valid time is until December 31, 2020.

ISED Registration: 11185A-1

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Dec. 31, 2020.

NVLAP Lab Code: 201008-0

CCIC-SET is a third party testing organization accredited by NVLAP according to ISO/IEC 17025. The accreditation certificate number is 201008-0.

1.4.2. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	30% -60%
Atmospheric Pressure (kPa):	86KPa-106KPa

2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Antenna Category: Internal antenna

An Internal antenna was soldered to the antenna port of EUT via an adaptor cable, can't be removed.

Antenna General Information:

No.	EUT	Ant. Type	Ant. Gain
1	Fingertip Oximeter	PCB	-1dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Peak Output Power


2.2.1. Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10:2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings: Span ≥ 3 RBW;
RBW $\geq$ DTS bandwidth; VBW ≥ 3 RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Measure the conducted output power and record the results in the test report.

2.2.5. Test Result

Please refer to Appendix A for detail

2.3. 6dB Bandwidth


2.3.1. Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows ANSI C63.10:2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

2.3.5. Test Results of 6dB Bandwidth

Please refer to Appendix A for detail

2.4. Conducted Band Edges and Spurious Emissions


2.4.1. Limit of Conducted Band Edges and Spurious Emissions

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedure

1. The testing follows ANSI C63.10:2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

2.4.5. Test Results of Conducted Band Edges

Please refer to Appendix A for detail

2.5. Power spectral density (PSD)


2.5.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of ANSI C63.10:2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.

Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

6. Measure and record the results in the test report.

7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

2.5.5. Test Results of Power spectral density

Please refer to Appendix A for detail

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Note: Wireless charger configuration was evaluated.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 KHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on a turntable 0.8m below 1GHz and 1.5m above 1GHz above ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported.
Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case (Data Rate 1Mbps) emissions are reported only.

2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9KHz to 30MHz


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1000 MHz



Plot A: 30MHz to 1GHz, Antenna Horizontal

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Corr. Factor (dB/m)	Antenna height (cm)	Limit (dB μ V/m)	Margin	Antenna	Verdict
30.000000	28.30	120.000	17.9	100.0	40.0	11.7	Horizontal	Pass
31.030000	26.75	120.000	17.9	100.0	40.0	13.25	Horizontal	Pass
136.350000	23.66	120.000	13.7	100.0	43.5	19.84	Horizontal	Pass
168.570000	23.34	120.000	10.5	100.0	43.5	20.16	Horizontal	Pass
685.250000	36.77	120.000	11.6	100.0	46.0	9.23	Horizontal	Pass
908.330000	38.32	120.000	13.1	100.0	46.0	7.68	Horizontal	Pass



Plot B: 30MHz to 1GHz, Antenna Vertical

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Corr. Factor (dBμV/m)	Antenna height (cm)	Limit (dB μ V/m)	Margin	Antenna	Verdict
30.000000	28.08	120.000	17.9	100.0	40.0	11.92	Vertical	Pass
31.050000	26.17	120.000	17.9	100.0	40.0	13.83	Vertical	Pass
136.220000	23.44	120.000	10.2	100.0	43.5	20.06	Vertical	Pass
168.740000	23.27	120.000	13.7	100.0	43.5	20.23	Vertical	Pass
685.250000	36.85	120.000	15.8	100.0	46.0	9.15	Vertical	Pass
911.250000	38.25	120.000	17.5	100.0	46.0	7.75	Vertical	Pass

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. Margin value = Limit value - Emission Level
4. The other emission levels were very low against the limit.

For 1GHz to 25GHz
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (0CH_2402MHz)

No.	Fre. (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390	50.32	PK	74.00	-23.68	1.6	290	49.02	5.2	28.60	32.5	1.3
2	2390	39.93	AV	54.00	-14.07	1.6	290	38.63	5.2	28.60	32.5	1.3
3	4804	51.44	PK	74.00	-22.56	1.6	290	45.04	7.4	30.40	31.4	6.4
4	4804	40.77	AV	54.00	-13.23	1.6	290	34.37	7.4	30.40	31.4	6.4
5	7206	51.98	PK	74.00	-22.02	1.6	290	42.68	9.9	31.50	32.1	9.3
6	7206	41.50	AV	54.00	-12.5	1.6	290	32.2	9.9	31.50	32.1	9.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (0CH_2402MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390	48.65	PK	74.00	-25.35	1.5	300	47.35	5.2	28.60	32.5	1.3
2	2390	38.54	AV	54.00	-15.46	1.5	300	37.24	5.2	28.60	32.5	1.3
3	4804	50.98	PK	74.00	-23.02	1.5	300	44.58	7.4	30.40	31.4	6.4
4	4804	40.90	AV	54.00	-13.1	1.5	300	34.5	7.4	30.40	31.4	6.4
5	7206	51.11	PK	74.00	-22.89	1.5	300	41.81	9.9	31.50	32.1	9.3
6	7206	40.79	AV	54.00	-13.21	1.5	300	31.49	9.9	31.50	32.1	9.3

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (19CH_2440MHz)

No.	Fre. (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4880	49.65	PK	74	-24.35	1.6	290	42.55	6.7	31.2	31.5	6.4
2	4880	39.29	AV	54	-14.71	1.6	290	32.18	6.7	31.2	31.5	6.4
3	7320	52.36	PK	74	-21.64	1.6	290	45.94	6.7	31.2	31.5	6.4
4	7320	42.25	AV	54	-11.75	1.6	300	35.75	6.7	31.2	31.5	6.4

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (19CH_2440MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4880	49.65	PK	74	-24.35	1.5	300	44.77	6.7	31.2	31.5	6.4
2	4880	39.43	AV	54	-14.57	1.5	300	34.53	6.7	31.2	31.5	6.4
3	7320	51.25	PK	74	-22.75	1.5	300	45.97	6.7	31.2	31.5	6.4
4	7320	41.16	AV	54	-12.84	1.5	300	35.68	6.7	31.2	31.5	6.4

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (39CH_2480MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.5	50.36	PK	74	-23.64	1.6	290	46.45	5.7	29.5	31.8	3.4
2	2483.5	39.06	AV	54	-14.94	1.6	290	36.23	5.7	29.5	31.8	3.4
3	4960	51.25	PK	74	-22.75	1.6	290	45.92	7	30.05	31.5	5.55
4	4960	41.01	AV	54	-12.99	1.6	290	35.74	7	30.05	31.5	5.55
5	7440	51.89	PK	74	-22.11	1.6	290	37.44	16	31.2	32	15.2
6	7440	41.54	AV	54	-12.46	1.6	290	27.19	16	31.2	32	15.2

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (39CH_2480MHz)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.5	49.98	PK	74	-24.02	1.5	300	45.25	5.7	29.5	31.8	3.4
2	2483.5	37.92	AV	54	-16.08	1.5	300	35.1	5.7	29.5	31.8	3.4
3	4960	52.32	PK	74	-21.68	1.5	300	45.89	7	30.05	31.5	5.55
4	4960	40.62	AV	54	-13.38	1.5	300	35.07	7	30.05	31.5	5.55
5	7440	52.84	PK	74	-21.16	1.5	300	38.42	16	31.2	32	15.2
6	7440	42.47	AV	54	-11.53	1.5	300	28.07	16	31.2	32	15.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
- Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level - Limit value

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI TEST RECEIVER	R&S	ESIB7	A0501375	2019.07.30	2020.07.29
2	Power Meter	R&S	NRP-Z31	102872	2020.05.18	2021.05.17
3	TURNTABLE	ETS	2088	2149	N/A	N/A
4	ANTENNA MAST	ETS	2075	2346	N/A	N/A
5	EMI TEST Software	R&S	ESK1	N/A	N/A	N/A
6	Horn antenna (18GHz~26.5GHz)	AR	AT4002A	305753	2017.11.10	2020.11.09
7	Amplifier	MILMEGA	80RF1000-250	A140901925	2017.10.09	2020.10.08
8	JS amplifier	AR	25S1G4AM1	A0304248	2017.10.09	2020.10.08
9	High pass filter	Compliance Direction systems	BSU-6	34202	2019.11.10	2020.11.09
13	Horn Antenna	AR	AT4002A	305753	2017.07.12	2020.07.11
14	Horn Antenna	AR	AT4510	325306	2018.07.14	2020.07.13
15	ULTRA-BROADBAND ANTENNA	R&S	HL562	A0304224	2017.07.14	2020.07.13
16	Passive Loop Antenna	R&S	HFH2-Z2	100047	2019.04.26	2022.04.25
17	Temperature chamber	welissom Inc.	SU-642	A150802409	2019.07.18	2020.07.17
18	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2019.06.05	2020.06.04
19	Power Supply	R&S	NGMO1	101037	2019.08.03	2020.08.02
20	EMI TEST RECEIVER	KEYSIGHT	ESCI	A0902601	2019.07.02	2020.07.01
21	LISN	ROHDE&SCHWARZ	ENV216	A140701847	2019.11.21	2020.11.20

4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150KHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	2.8dB
---	-------

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz~18GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%($U=2U_c(y)$)	5.1dB
---	-------


Appendix A

Peak Output Power Test Result and Data


Data Rate	Test Frequency	Power(dBm)	Limit(dBm)	Result
1Mbps	2402	-9.212	30	Pass
	2440	-8.772		Pass
	2480	-7.119		Pass
2Mbps	2402	-9.238	30	Pass
	2440	-8.826		Pass
	2480	-7.140		Pass

Data Rate 1Mbps


Output Power: 2402MHz



Output Power: 2440MHz




Output Power: 2480MHz




Data Rate 2Mbps


Output Power: 2402MHz



Output Power: 2440MHz



Output Power: 2480MHz




Power Spectral Density Test Result and Data


Data Rate	Test Frequency	PSD(dBm/3KHz)	Limit(dBm/3KHz)	Result
1Mbps	2402	-24.856	8	Pass
	2440	-24.467		Pass
	2480	-22.696		Pass
2Mbps	2402	-27.273	8	Pass
	2440	-26.869		Pass
	2480	-25.154		Pass

Data Rate 1Mbps


Power spectral density: 2402MHz



Power spectral density: 2440MHz




Power spectral density: 2480MHz




Data Rate 2Mbps


Power spectral density: 2402MHz



Power spectral density: 2440MHz



Power spectral density: 2480MHz



6dB BandWidth Test Result and Data

Data Rate	Test Frequency	6dBOccupy Bandwidth(Khz)	Min Limit(kHz)	Result
1Mbps	2402	710.023	500	Pass
	2440	713.739		Pass
	2480	718.635		Pass
2Mbps	2402	1134.333	500	Pass
	2440	1145.931		Pass
	2480	1141.651		Pass

Data Rate 1Mbps

6dB Bandwidth: 2402MHz



6dB Bandwidth: 2440MHz



6dB Bandwidth: 2480MHz



Data Rate 2Mbps

6dB Bandwidth: 2402MHz



6dB Bandwidth: 2440MHz








6dB Bandwidth: 2480MHz




Conducted Band Edges and Spurious Emissions Test Result and Data

Data Rate 1Mbps


,Plot ,1Transmitter Spurious Emission
: 2402,Reference Level

,Plot ,1Transmitter Spurious Emission
: 2440,Reference Level

,Plot ,1Transmitter Spurious Emission
: 2480,Reference Level

,Plot ,2Conducted Emission: 2402
,Band Edge

,Plot ,2Conducted Emission: 2440
,Band Edge

,Plot ,2Conducted Emission: 2480
,Band Edge



,Plot ,3Transmitter Spurious Emission
: 2402,30MHz~2310MHz




,Plot ,3Transmitter Spurious Emission
: 2440,30MHz~2310MHz




,Plot ,3Transmitter Spurious Emission
: 2480,30MHz~2310MHz




,Plot ,4Transmitter Spurious Emission
: 2402,2500MHz~10000MHz



,Plot ,4Transmitter Spurious Emission
: 2440,2500MHz~10000MHz




,Plot ,4Transmitter Spurious Emission
: 2480,2500MHz~10000MHz




,Plot ,5Transmitter Spurious Emission
: 2402,10000MHz~25000MHz



,Plot ,5Transmitter Spurious Emission
: 2440,10000MHz~25000MHz








,Plot ,5Transmitter Spurious Emission
: 2480,10000MHz~25000MHz







,Plot ,1Transmitter Spurious Emission
: 2402,Reference Level




,Plot ,3Transmitter Spurious Emission
: 2402,30MHz~2310MHz




,Plot ,3Transmitter Spurious Emission
: 2440,30MHz~2310MHz




,Plot ,3Transmitter Spurious Emission
: 2480,30MHz~2310MHz




,Plot ,4Transmitter Spurious Emission
: 2402,2500MHz~10000MHz




,Plot ,4Transmitter Spurious Emission
: 2440,2500MHz~10000MHz




,Plot ,4Transmitter Spurious Emission
: 2480,2500MHz~10000MHz




,Plot ,5Transmitter Spurious Emission
: 2402,10000MHz~25000MHz



,Plot ,5Transmitter Spurious Emission
: 2440,10000MHz~25000MHz



,Plot ,5Transmitter Spurious Emission
: 2480,10000MHz~25000MHz



** END OF REPORT **