

Transmitter Emission above 1GHz

Worse case mode:		GFSK(1Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390	53.81	-9.2	44.61	74	-29.39	Peak	H
2400	54.97	-9.39	45.58	74	-28.42	Peak	H
4804	53.12	-4.33	48.79	74	-25.21	Peak	H
7206	51.08	1.01	52.09	74	-21.91	Peak	H
2390	54.14	-9.2	44.94	74	-29.06	Peak	V
2400	52.65	-9.39	43.26	74	-30.74	Peak	V
4804	53.77	-4.33	49.44	74	-24.56	Peak	V
7206	50.51	1.01	51.52	74	-22.48	Peak	V

Worse case mode:		GFSK(1Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4880	51.77	-4.11	47.66	74	-26.34	peak	H
7320	50.83	1.51	52.34	74	-21.66	peak	H
4880	53.17	-4.11	49.06	74	-24.94	peak	V
7320	50.98	1.51	52.49	74	-21.51	peak	V

Worse case mode:		GFSK(1Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.5	55.20	-9.29	45.91	74	-28.09	Peak	H
4960	53.16	-4.04	49.12	74	-24.88	Peak	H
7440	50.07	1.57	51.64	74	-22.36	Peak	H
2483.5	55.82	-9.29	46.53	74	-27.47	Peak	V
4960	51.29	-4.04	47.25	74	-26.75	Peak	V
7440	49.10	1.57	50.67	74	-23.33	Peak	V

Worse case mode:		GFSK(2Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390	55.51	-9.2	46.31	74	-27.69	Peak	H
2400	55.27	-9.39	45.88	74	-28.12	Peak	H
4804	51.30	-4.33	46.97	74	-27.03	Peak	H
7206	49.63	1.01	50.64	74	-23.36	Peak	H
2390	53.07	-9.2	43.87	74	-30.13	Peak	V
2400	50.90	-9.39	41.51	74	-32.49	Peak	V
4804	53.07	-4.33	48.74	74	-25.26	Peak	V
7206	48.68	1.01	49.69	74	-24.31	Peak	V

Worse case mode:		GFSK(2Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4880	53.21	-4.11	49.10	74	-24.90	peak	H
7320	50.62	1.51	52.13	74	-21.87	peak	H
4880	54.03	-4.11	49.92	74	-24.08	peak	V
7320	48.88	1.51	50.39	74	-23.61	peak	V

Worse case mode:		GFSK(2Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.5	56.89	-9.29	47.60	74	-26.40	Peak	H
4960	52.68	-4.04	48.64	74	-25.36	Peak	H
7440	51.15	1.57	52.72	74	-21.28	Peak	H
2483.5	57.19	-9.29	47.90	74	-26.10	Peak	V
4960	50.05	-4.04	46.01	74	-27.99	Peak	V
7440	48.67	1.57	50.24	74	-23.76	Peak	V


Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission


9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emissions Test Setup



7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for CQASZ20230701332E-01.

*** END OF REPORT ***