




# RF Exposure Evaluation Report

**Equipment** : Dual band WiFi Router  
**Brand Name** : Google  
**Model No.** : AC-1304  
**FCC ID** : A4RAC-1304  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : Google Inc.  
1600 Amphitheater Parkway, Mountain View, CA  
94043  
**Manufacturer** : Wistron NeWeb Corporation  
20 Park Ave. II, Hsinchu Science Park, Hsinchu 308,  
Taiwan

The product sample received on Sep. 14, 2016 and completely tested on Mar. 22, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Cliff Chang  
SPORTON INTERNATIONAL INC.





## **TABLE OF CONTENTS**

|          |                                             |          |
|----------|---------------------------------------------|----------|
| <b>1</b> | <b>GENERAL DESCRIPTION .....</b>            | <b>4</b> |
| 1.1      | EUT General Information .....               | 4        |
| 1.2      | Table for Multiple source Listing .....     | 4        |
| 1.3      | Testing Location .....                      | 4        |
| <b>2</b> | <b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>   | <b>5</b> |
| 2.1      | Limit of Maximum Permissible Exposure ..... | 5        |
| 2.2      | MPE Calculation Method .....                | 5        |
| 2.3      | Calculated Result and Limit.....            | 6        |

### **PHOTOGRAPHS OF EUT V01**

## REVISION HISTORY

[illegible]

# 1 General Description

## 1.1 EUT General Information

| RF General Information |                        |                           |                                                                                                                                      |
|------------------------|------------------------|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode        | Frequency Range (MHz)  | Operating Frequency (MHz) | Modulation Type                                                                                                                      |
| 2.4GHz WLAN            | 2400-2483.5            | 2412-2462                 | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |
| 5GHz WLAN              | 5150-5250<br>5725-5850 | 5180-5240<br>5745-5825    | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)                                      |
| Bluetooth              | 2400-2483.5            | 2402-2480                 | BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK)<br>LE: DSSS (GFSK)                                                                    |

## 1.2 Table for Multiple source Listing

The EUT has three types, which are identical to each other in all aspects except for the following table:

| EUT   | PHY           | U2                      |
|-------|---------------|-------------------------|
| EUT 1 | Main source   | Second source (samsung) |
| EUT 2 | Second source | Second source (samsung) |
| EUT 3 | Main source   | Main source (toshiba)   |

The PHY and U2 detail information as below:

| Source            | Model Name                    |
|-------------------|-------------------------------|
| PHY Main source   | QCA8072                       |
| PHY Second source | QCA8075                       |
| U2 main source    | Toshiba EMMC, THGBMDG5D1LBAIT |
| U2 second source  | Samsung EMMC, KLM4G1FEPD-B031 |

## 1.3 Testing Location

| Testing Location                    |        |                                                                                                                               |
|-------------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/>            | HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.<br>TEL : 886-3-327-3456 FAX : 886-3-327-0973   |
| <input checked="" type="checkbox"/> | JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.<br>TEL : 886-3-656-9065 FAX : 886-3-656-9085 |

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6                                                                |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500              |                                   |                                   | F/300                                    | 6                                                                |
| 1500-100,000          |                                   |                                   | 5                                        | 6                                                                |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30                                                               |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                 | 30                                                               |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30                                                               |
| 300-1500              |                                   |                                   | F/1500                                   | 30                                                               |
| 1500-100,000          |                                   |                                   | 1.0                                      | 30                                                               |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

| Mode     | DG<br>(dBi) | Power<br>(dBm) | EIRP<br>(dBm) | EIRP<br>(W) | Distance<br>(cm) | S<br>(mW/cm <sup>2</sup> ) | S Limit<br>(mW/cm <sup>2</sup> ) | Ratio<br>(S/Limit) |
|----------|-------------|----------------|---------------|-------------|------------------|----------------------------|----------------------------------|--------------------|
| 2.4G;G1D | 3.53        | 28.17          | 31.89         | 1.54525     | 20               | 0.30757                    | 1                                | 0.30757            |
| 5.2G;D1D | 7.57        | 25.59          | 33.16         | 2.07014     | 20               | 0.41205                    | 1                                | 0.41205            |
| BT 4.0   | 5.46        | 10.27          | 15.73         | 0.03741     | 20               | 0.00744                    | 1                                | 0.00744            |
|          |             |                |               |             |                  |                            | Sum Ratio                        | 0.72706            |
|          |             |                |               |             |                  |                            | Ratio Limit                      | 1                  |