

FCC Test Report

Report No.: RF180920C21-1

FCC ID: A4RG020E

Model Name: G020E

Received Date: Sep. 21, 2018

Test Date: Oct. 08 ~ Nov. 14, 2018

Issued Date: Dec. 17, 2018

Applicant: Google LLC

Address: 1600 Amphitheatre Parkway, Mountain View, CA 94043, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location (1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

Test Location (2): No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

FCC Registration / Designation Number (1): 788550 / TW0003

FCC Registration / Designation Number (2): 198487 / TW2021



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	11
3.3 Duty Cycle of Test Signal	13
3.4 Description of Support Units	14
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures	17
4.1.4 Deviation from Test Standard	17
4.1.5 Test Setup	18
4.1.6 EUT Operating Conditions	19
4.1.7 Test Results for Fundamental and Harmonic above 1GHz	20
4.1.8 Test Results for Bandedge above 1GHz	104
4.1.9 Test Results for below 1GHz	188
4.2 Conducted Emission Measurement	190
4.2.1 Limits of Conducted Emission Measurement	190
4.2.2 Test Instruments	190
4.2.3 Test Procedures	191
4.2.4 Deviation from Test Standard	191
4.2.5 Test Setup	191
4.2.6 EUT Operating Conditions	191
4.2.7 Test Results	192
4.3 Transmit Power Measurement	194
4.3.1 Limits of Transmit Power Measurement	194
4.3.2 Test Setup	194
4.3.3 Test Instruments	194
4.3.4 Test Procedure	195
4.3.5 Deviation from Test Standard	195
4.3.6 EUT Operating Conditions	195
4.3.7 Test Result	196
4.4 Occupied Bandwidth Measurement	209
4.4.1 Test Setup	209
4.4.2 Test Instruments	209
4.4.3 Test Procedure	209
4.4.4 Test Result	210
4.5 Peak Power Spectral Density Measurement	213
4.5.1 Limits of Peak Power Spectral Density Measurement	213
4.5.2 Test Setup	213
4.5.3 Test Instruments	213
4.5.4 Test Procedures	214
4.5.5 Deviation from Test Standard	214
4.5.6 EUT Operating Conditions	214
4.5.7 Test Results	215

4.6	Frequency Stability.....	222
4.6.1	Limits of Frequency Stability Measurement	222
4.6.2	Test Setup.....	222
4.6.3	Test Instruments	222
4.6.4	Test Procedure	222
4.6.5	Deviation from Test Standard	223
4.6.6	EUT Operating Condition	223
4.6.7	Test Results	223
4.7	6dB Bandwidth Measurement.....	224
4.7.1	Limits of 6dB Bandwidth Measurement.....	224
4.7.2	Test Setup.....	224
4.7.3	Test Instruments	224
4.7.4	Test Procedure	224
4.7.5	Deviation from Test Standard	224
4.7.6	EUT Operating Condition	224
4.7.7	Test Results	225
4.8	Automatically Discontinue Transmission.....	227
4.8.1	Limit of Automatically Discontinue Transmission	227
4.8.2	Test Instruments	227
4.8.3	Test Result.....	227
5	Pictures of Test Arrangements.....	228
	Appendix – Information on the Testing Laboratories	229

Release Control Record

Issue No.	Description	Date Issued
RF180920C21-1	Original release	Dec. 17, 2018

1 Certificate of Conformity

Product: Smartphone

Model Name: G020E

Sample Status: Identical Prototype

Applicant: Google LLC

Test Date: Oct. 08 ~ Nov. 14, 2018

Standards: 47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Dec. 17, 2018
Celine Chou / Senior Specialist

Approved by : Bruce Chen , **Date:** Dec. 17, 2018
Bruce Chen / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
FCC Clause	Test Item	Result	Remarks
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -12.76dB at 0.50242MHz.
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -1.54dB at 5149.88MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	-	Reference only.
15.407(a)(1/2/3)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6dB bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.407(c)	Automatically Discontinue Transmission	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.94 dB
Radiated Emissions	9kHz ~ 30MHz	2.38 dB
	30MHz ~ 1GHz	5.54 dB
	Above 1GHz	5.48 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Smartphone
Model Name	G020E
Sample Status	Identical Prototype
Power Supply Rating	3.85Vdc (Battery) 5Vdc or 9Vdc (Adapter) 5Vdc (Host equipment)
Modulation Type	256QAM, 64QAM, 16QAM, QPSK, BPSK
Modulation Technology	OFDM
Transfer Rate	802.11a: 54/48/36/24/18/12/9/6Mbps 802.11n/ac: up to 300Mbps 802.11ac: up to 867Mbps
Operating Frequency	5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5720MHz, 5745 ~ 5825MHz
Number of Channel	5180 ~ 5240MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 4 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1 5260 ~ 5320MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 4 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1 5500 ~ 5720MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 12 802.11n (HT40), 802.11ac (VHT40): 6 802.11ac (VHT80): 3 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 5 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1
Output Power	5180 ~ 5240MHz: 108.678mW 5260 ~ 5320MHz: 107.787mW 5500 ~ 5720MHz: 110.037mW 5745 ~ 5825MHz: 109.915mW
Antenna Type	Refer to Note as below
Antenna Connector	Refer to Note as below
Accessory Device	Refer to Note as below
Cable Supplied	Refer to Note as below

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Modulation Mode	TX Function
802.11a	1TX(SISO)/2TX(MIMO)
802.11n (HT20)	1TX(SISO)/2TX(MIMO)
802.11n (HT40)	1TX(SISO)/2TX(MIMO)
802.11ac (VHT20)	1TX(SISO)/2TX(MIMO)
802.11ac (VHT40)	1TX(SISO)/2TX(MIMO)
802.11ac (VHT80)	1TX(SISO)/2TX(MIMO)

* The modulation and bandwidth are similar for 802.11n mode for 20MHz/40MHz and 802.11ac mode for 20MHz/40MHz, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

* SISO mode and MIMO mode are presented in power output test item. For other test items, MIMO mode is the worst case for final tests after pretesting.

2. There're 2 configurations for the EUT listed as below.

- Main Sample: EUT + Battery 1
- 2nd Sample: EUT + Battery 2

After pre-tested with the EUT, only the worst configuration (main sample) was chosen for the final test.

3. The EUT accessories list refers to EUT Photo.pdf.

4. The following antennas were provided to the EUT.

No.	Type	Connector	Gain (dBi)			
			5.15-5.25 GHz	5.25-5.35 GHz	5.47-5.725 GHz	5.725-5.85 GHz
0	PIFA	NA	-2.2	-2.7	-3.4	-3.0
1	PIFA	NA	-0.2	-0.5	-1.7	-2.8

5. The worst configuration power mode is presented in the report as below. Please refer to SAR test report for more detail test mode.

Maximum Tune-up Power Mode				
Band		TX Antenna	WWAN Function	Body-Worn/Hotspot
WLAN	5G Band 1	Ant 0+1	WWAN-Off	Body-Worn/Hotspot
	5G Band 2	Ant 0+1	WWAN-Off	Body-Worn/Hotspot
	5G Band 3	Ant 0+1	WWAN-Off	Body-Worn/Hotspot
	5G Band 4	Ant 0+1	WWAN-Off	Body-Worn/Hotspot

3.2 Description of Test Modes

For 5180 ~ 5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
42	5210MHz

For 5260 ~ 5320MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
54	5270 MHz	62	5310 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
58	5290MHz

For 5500 ~ 5720MHz:

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
100	5500 MHz	124	5620 MHz
104	5520 MHz	128	5640 MHz
108	5540 MHz	132	5660 MHz
112	5560 MHz	136	5680 MHz
116	5580 MHz	140	5700 MHz
120	5600 MHz	144	5720 MHz

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
102	5510 MHz	126	5630 MHz
110	5550 MHz	134	5670 MHz
118	5590 MHz	142	5710 MHz

3 channels are provided for 802.11ac (VHT80):

Channel	Frequency	Channel	Frequency
106	5530 MHz	122	5610 MHz
138	5690 MHz		

For 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
155	5775MHz

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
	802.11ac (VHT20)		36 to 48	36, 40, 48	OFDM	6.5
	802.11ac (VHT40)		38 to 46	38, 46	OFDM	13.5
	802.11ac (VHT80)		42	42	OFDM	29.3
-	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
	802.11ac (VHT20)		52 to 64	52, 60, 64	OFDM	6.5
	802.11ac (VHT40)		54 to 62	54, 62	OFDM	13.5
	802.11ac (VHT80)		58	58	OFDM	29.3
-	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
	802.11ac (VHT20)		100 to 144	100, 116, 140, 144	OFDM	6.5
	802.11ac (VHT40)		102 to 142	102, 110, 134, 142	OFDM	13.5
	802.11ac (VHT80)		106 to 138	106, 122, 138	OFDM	29.3
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
	802.11ac (VHT20)		149 to 165	149, 157, 165	OFDM	6.5
	802.11ac (VHT40)		151 to 159	151, 159	OFDM	13.5
	802.11ac (VHT80)		155	155	OFDM	29.3

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36	OFDM	6.0
-	802.11a	5260-5320	52 to 64		OFDM	6.0
-	802.11a	5500-5720	100 to 140		OFDM	6.0
-	802.11a	5745-5825	149 to 165		OFDM	6.0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36	OFDM	6.0
-	802.11a	5260-5320	52 to 64		OFDM	6.0
-	802.11a	5500-5720	100 to 140		OFDM	6.0
-	802.11a	5745-5825	149 to 165		OFDM	6.0

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
	802.11ac (VHT20)		36 to 48	36, 40, 48	OFDM	6.5
	802.11ac (VHT40)		38 to 46	38, 46	OFDM	13.5
	802.11ac (VHT80)		42	42	OFDM	29.3
-	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
	802.11ac (VHT20)		52 to 64	52, 60, 64	OFDM	6.5
	802.11ac (VHT40)		54 to 62	54, 62	OFDM	13.5
	802.11ac (VHT80)		58	58	OFDM	29.3
-	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
	802.11ac (VHT20)		100 to 144	100, 116, 140, 144	OFDM	6.5
	802.11ac (VHT40)		102 to 142	102, 110, 134, 142	OFDM	13.5
	802.11ac (VHT80)		106 to 138	106, 122, 138	OFDM	29.3
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
	802.11ac (VHT20)		149 to 165	149, 157, 165	OFDM	6.5
	802.11ac (VHT40)		151 to 159	151, 159	OFDM	13.5
	802.11ac (VHT80)		155	155	OFDM	29.3

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE _≥ 1G	26 deg. C, 77% RH	120Vac, 60Hz	Dalen Dai
RE _{<} 1G	23 deg. C, 68% RH	120Vac, 60Hz	Dalen Dai
PLC	25 deg. C, 68% RH	120Vac, 60Hz	Jones Chang
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Chris Lin

3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98%, duty factor is required.

802.11a: Duty cycle = $2.020/2.065 = 0.978$, Duty factor = $10 * \log(1/0.978) = 0.10$

802.11ac (VHT20): Duty cycle = $1.880/1.940 = 0.969$, Duty factor = $10 * \log(1/0.969) = 0.14$

802.11ac (VHT40): Duty cycle = $0.922/0.963 = 0.957$, Duty factor = $10 * \log(1/0.957) = 0.19$


802.11ac (VHT80): Duty cycle = $0.455/0.493 = 0.923$, Duty factor = $10 * \log(1/0.923) = 0.35$



3.4 Description of Support Units

The EUT has been tested as an independent unit.

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To			Limit	
789033 D02 General UNII Test Procedure New Rules v02r01			Field Strength at 3m	
			PK: 74 (dBµV/m)	AV: 54 (dBµV/m)
Frequency Band	Applicable To		EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)		PK: -27 (dBm/MHz)	PK: 68.2(dBµV/m)
5250~5350 MHz	15.407(b)(2)			
5470~5725 MHz	15.407(b)(3)			
5725~5850 MHz	☒	15.407(b)(4)(i)	PK: -27 (dBm/MHz) ^{*1} PK: 10 (dBm/MHz) ^{*2} PK: 15.6 (dBm/MHz) ^{*3} PK: 27 (dBm/MHz) ^{*4}	PK: 68.2(dBµV/m) ^{*1} PK: 105.2 (dBµV/m) ^{*2} PK: 110.8(dBµV/m) ^{*3} PK: 122.2 (dBµV/m) ^{*4}
	☐	15.407(b)(4)(ii)	Emission limits in section 15.247(d)	
^{*1} beyond 75 MHz or more above of the band edge.			^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.	
^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.			^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
HP Preamplifier	8447D	2432A03504	Feb. 21, 2018	Feb. 20, 2019
HP Preamplifier	8449B	3008A01201	Feb. 22, 2018	Feb. 21, 2019
MITEQ Preamplifier	AMF-6F-260400-33-8P	892164	Feb. 21, 2018	Feb. 20, 2019
Agilent TEST RECEIVER	N9038A	MY51210129	Feb. 06, 2018	Feb. 05, 2019
Schwarzbeck Antenna	VULB 9168	139	Dec. 29, 2017	Dec. 28, 2018
Schwarzbeck Antenna	VHBA 9123	480	May 19, 2017	May 18, 2019
Schwarzbeck Horn Antenna	BBHA-9170	212	Dec. 29, 2017	Dec. 28, 2018
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Mar. 29, 2018	Mar. 28, 2019
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V7.6.15.9.5	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF102	Cable-CH6-01	Aug. 13, 2018	Aug. 12, 2019
SUHNER RF cable With 3/4dB PAD	SF102	Cable-CH8-3.6m	Aug. 13, 2018	Aug. 12, 2019
KEYSIGHT MIMO Powermeasurement Test set	U2021XA	U2021XA-001	Jun. 04, 2018	Jun. 03, 2019
KEYSIGHT Spectrum Analyzer	N9030A	MY54490260	Aug. 03, 2018	Aug. 02, 2019
Loop Antenna EMCI	LPA600	270	Aug. 11, 2017	Aug. 10, 2019
EMCO Horn Antenna	3115	00028257	Mar. 29, 2018	Mar. 28, 2019
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 27, 2018	Sep. 26, 2019
Anritsu Power Sensor	MA2411B	0738404	Apr. 26, 2018	Apr. 25, 2019
Anritsu Power Meter	ML2495A	0842014	Apr. 26, 2018	Apr. 25, 2019

Note: 1. The calibration interval of the above test instruments is 12 months (24 months for Loop Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 3. The test was performed in Lin Kou Chamber No. 6.
 4. The Industry Canada Reference No. 7450E-6.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Test Mode	DutyCycle (%)	RBW (PK)	VBW (PK)	RBW (AV)	VBW (AV)
802.11a	97.8	1MHz	3MHz	1MHz	1kHz
802.11ac (VHT20)	96.9	1MHz	3MHz	1MHz	1kHz
802.11ac (VHT40)	95.7	1MHz	3MHz	1MHz	3kHz
802.11ac (VHT80)	92.3	1MHz	3MHz	1MHz	3kHz

4.1.6 EUT Operating Conditions

- Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results for Fundamental and Harmonic above 1GHz




802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5180.00	109.63 PK			1.00 H	336	104.58	5.05
2	*5180.00	99.71 AV			1.00 H	336	94.66	5.05
3	#10360.00	54.16 PK	68.20	-14.04	2.35 H	231	38.42	15.74
4	18000.00	60.65 PK	74.00	-13.35	1.41 H	285	38.17	22.48
5	18000.00	50.30 AV	54.00	-3.70	1.41 H	285	27.82	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5180.00	106.55 PK			1.00 V	0	101.50	5.05
2	*5180.00	96.86 AV			1.00 V	0	91.81	5.05
3	#10360.00	53.25 PK	68.20	-14.95	1.21 V	307	37.51	15.74
4	18000.00	59.49 PK	74.00	-14.51	2.38 V	177	37.01	22.48
5	18000.00	50.54 AV	54.00	-3.46	2.38 V	177	28.06	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5200.00	109.04 PK			1.00 H	334	104.14	4.90
2	*5200.00	98.97 AV			1.00 H	334	94.07	4.90
3	#10400.00	54.34 PK	68.20	-13.86	2.60 H	217	38.29	16.05
4	17983.00	58.32 PK	74.00	-15.68	1.35 H	279	36.28	22.04
5	17983.00	50.22 AV	54.00	-3.78	1.35 H	279	28.18	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5200.00	106.11 PK			1.03 V	5	101.21	4.90
2	*5200.00	96.28 AV			1.03 V	5	91.38	4.90
3	#10400.00	53.47 PK	68.20	-14.73	1.30 V	294	37.42	16.05
4	17898.00	58.97 PK	74.00	-15.03	2.33 V	180	39.07	19.90
5	17898.00	50.18 AV	54.00	-3.82	2.33 V	180	30.28	19.90

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	108.96 PK			1.02 H	337	104.31	4.65
2	*5240.00	99.50 AV			1.02 H	337	94.85	4.65
3	#10480.00	55.31 PK	68.20	-12.89	2.51 H	228	38.65	16.66
4	17983.00	59.27 PK	74.00	-14.73	1.45 H	283	37.23	22.04
5	17983.00	50.63 AV	54.00	-3.37	1.45 H	283	28.59	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	105.31 PK			1.01 V	1	100.66	4.65
2	*5240.00	96.40 AV			1.01 V	1	91.75	4.65
3	#10480.00	54.20 PK	68.20	-14.00	1.25 V	298	37.54	16.66
4	18000.00	59.60 PK	74.00	-14.40	2.39 V	174	37.12	22.48
5	18000.00	50.41 AV	54.00	-3.59	2.39 V	174	27.93	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5260.00	109.51 PK			1.00 H	333	104.99	4.52
2	*5260.00	99.60 AV			1.00 H	333	95.08	4.52
3	#10520.00	55.34 PK	68.20	-12.86	2.41 H	225	38.49	16.85
4	17983.00	59.06 PK	74.00	-14.94	1.50 H	277	37.02	22.04
5	17983.00	50.19 AV	54.00	-3.81	1.50 H	277	28.15	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5260.00	105.21 PK			1.02 V	6	100.69	4.52
2	*5260.00	94.66 AV			1.02 V	6	90.14	4.52
3	#10520.00	54.46 PK	68.20	-13.74	1.31 V	290	37.61	16.85
4	18000.00	58.89 PK	74.00	-15.11	2.42 V	185	36.41	22.48
5	18000.00	50.32 AV	54.00	-3.68	2.42 V	185	27.84	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	108.69 PK			1.03 H	337	104.37	4.32
2	*5300.00	98.74 AV			1.03 H	337	94.42	4.32
3	10600.00	55.26 PK	74.00	-18.74	2.50 H	221	38.29	16.97
4	10600.00	45.11 AV	54.00	-8.89	2.50 H	221	28.14	16.97
5	18000.00	59.10 PK	74.00	-14.90	1.54 H	281	36.62	22.48
6	18000.00	50.04 AV	54.00	-3.96	1.54 H	281	27.56	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	104.16 PK			1.05 V	3	99.84	4.32
2	*5300.00	94.23 AV			1.05 V	3	89.91	4.32
3	10600.00	54.43 PK	74.00	-19.57	1.24 V	297	37.46	16.97
4	10600.00	44.36 AV	54.00	-9.64	1.24 V	297	27.39	16.97
5	17983.00	59.00 PK	74.00	-15.00	2.38 V	179	36.96	22.04
6	17983.00	50.23 AV	54.00	-3.77	2.38 V	179	28.19	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	108.63 PK			1.00 H	331	104.25	4.38
2	*5320.00	98.96 AV			1.00 H	331	94.58	4.38
3	10640.00	55.06 PK	74.00	-18.94	2.37 H	217	38.40	16.66
4	10640.00	43.88 AV	54.00	-10.12	2.37 H	217	27.22	16.66
5	17983.00	58.58 PK	74.00	-15.42	1.46 H	273	36.54	22.04
6	17983.00	50.26 AV	54.00	-3.74	1.46 H	273	28.22	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	103.62 PK			1.01 V	2	99.24	4.38
2	*5320.00	93.91 AV			1.01 V	2	89.53	4.38
3	10640.00	54.09 PK	74.00	-19.91	1.20 V	288	37.43	16.66
4	10640.00	43.91 AV	54.00	-10.09	1.20 V	288	27.25	16.66
5	17966.00	58.60 PK	74.00	-15.40	2.47 V	188	37.00	21.60
6	17966.00	50.46 AV	54.00	-3.54	2.47 V	188	28.86	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5500.00	106.75 PK			1.57 H	336	102.28	4.47
2	*5500.00	97.48 AV			1.57 H	336	93.01	4.47
3	11000.00	55.37 PK	74.00	-18.63	2.15 H	204	38.95	16.42
4	11000.00	44.05 AV	54.00	-9.95	2.15 H	204	27.63	16.42
5	17932.00	58.57 PK	74.00	-15.43	1.42 H	288	37.83	20.74
6	17932.00	50.29 AV	54.00	-3.71	1.42 H	288	29.55	20.74

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5500.00	105.34 PK			1.60 V	355	100.87	4.47
2	*5500.00	96.54 AV			1.60 V	355	92.07	4.47
3	11000.00	54.04 PK	74.00	-19.96	1.33 V	286	37.62	16.42
4	11000.00	43.65 AV	54.00	-10.35	1.33 V	286	27.23	16.42
5	18000.00	59.61 PK	74.00	-14.39	2.40 V	184	37.13	22.48
6	18000.00	50.23 AV	54.00	-3.77	2.40 V	184	27.75	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5580.00	107.50 PK			1.59 H	313	102.67	4.83
2	*5580.00	98.77 AV			1.59 H	313	93.94	4.83
3	11160.00	55.86 PK	74.00	-18.14	2.08 H	213	38.82	17.04
4	11160.00	44.59 AV	54.00	-9.41	2.08 H	213	27.55	17.04
5	18000.00	59.04 PK	74.00	-14.96	1.52 H	276	36.56	22.48
6	18000.00	50.01 AV	54.00	-3.99	1.52 H	276	27.53	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5580.00	105.20 PK			1.53 V	358	100.37	4.83
2	*5580.00	96.65 AV			1.53 V	358	91.82	4.83
3	11160.00	54.57 PK	74.00	-19.43	1.28 V	291	37.53	17.04
4	11160.00	44.18 AV	54.00	-9.82	1.28 V	291	27.14	17.04
5	18000.00	59.65 PK	74.00	-14.35	2.37 V	169	37.17	22.48
6	18000.00	50.23 AV	54.00	-3.77	2.37 V	169	27.75	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	107.87 PK			1.50 H	348	102.58	5.29
2	*5700.00	97.67 AV			1.50 H	348	92.38	5.29
3	11400.00	55.76 PK	74.00	-18.24	2.20 H	206	38.92	16.84
4	11400.00	44.68 AV	54.00	-9.32	2.20 H	206	27.84	16.84
5	17983.00	59.13 PK	74.00	-14.87	1.56 H	273	37.09	22.04
6	17983.00	50.28 AV	54.00	-3.72	1.56 H	273	28.24	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	103.98 PK			1.58 V	344	98.69	5.29
2	*5700.00	94.49 AV			1.58 V	344	89.20	5.29
3	11400.00	55.38 PK	74.00	-18.62	1.21 V	295	38.54	16.84
4	11400.00	44.20 AV	54.00	-9.80	1.21 V	295	27.36	16.84
5	18000.00	58.75 PK	74.00	-15.25	2.33 V	185	36.27	22.48
6	18000.00	50.52 AV	54.00	-3.48	2.33 V	185	28.04	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * " : Fundamental frequency





CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5720.00	108.18 PK			1.02 H	334	102.74	5.44
2	*5720.00	98.42 AV			1.02 H	334	92.98	5.44
3	11440.00	55.50 PK	74.00	-18.50	2.03 H	217	38.47	17.03
4	11440.00	44.78 AV	54.00	-9.22	2.03 H	217	27.75	17.03
5	17983.00	59.16 PK	74.00	-14.84	1.66 H	279	37.12	22.04
6	17983.00	49.73 AV	54.00	-4.27	1.66 H	279	27.69	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5720.00	104.46 PK			1.05 V	1	99.02	5.44
2	*5720.00	94.78 AV			1.05 V	1	89.34	5.44
3	11440.00	54.61 PK	74.00	-19.39	1.26 V	293	37.58	17.03
4	11440.00	44.17 AV	54.00	-9.83	1.26 V	293	27.14	17.03
5	18000.00	60.45 PK	74.00	-13.55	2.57 V	173	37.97	22.48
6	18000.00	50.08 AV	54.00	-3.92	2.57 V	173	27.60	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	105.46 PK			1.03 H	333	99.85	5.61
2	*5745.00	95.28 AV			1.03 H	333	89.67	5.61
3	11490.00	56.18 PK	74.00	-17.82	2.08 H	229	38.92	17.26
4	11490.00	45.90 AV	54.00	-8.10	2.08 H	229	28.64	17.26
5	17949.00	60.61 PK	74.00	-13.39	1.56 H	317	39.43	21.18
6	17949.00	50.81 AV	54.00	-3.19	1.56 H	317	29.63	21.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	103.72 PK			1.00 V	6	98.11	5.61
2	*5745.00	93.61 AV			1.00 V	6	88.00	5.61
3	11490.00	55.08 PK	74.00	-18.92	1.38 V	296	37.82	17.26
4	11490.00	44.62 AV	54.00	-9.38	1.38 V	296	27.36	17.26
5	18000.00	60.14 PK	74.00	-13.86	2.39 V	162	37.66	22.48
6	18000.00	50.48 AV	54.00	-3.52	2.39 V	162	28.00	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	106.19 PK			1.00 H	331	100.29	5.90
2	*5785.00	97.84 AV			1.00 H	331	91.94	5.90
3	11570.00	56.17 PK	74.00	-17.83	2.11 H	217	38.81	17.36
4	11570.00	45.91 AV	54.00	-8.09	2.11 H	217	28.55	17.36
5	17983.00	59.68 PK	74.00	-14.32	1.63 H	294	37.64	22.04
6	17983.00	50.26 AV	54.00	-3.74	1.63 H	294	28.22	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	103.98 PK			1.02 V	4	98.08	5.90
2	*5785.00	96.76 AV			1.02 V	4	90.86	5.90
3	11570.00	55.05 PK	74.00	-18.95	1.24 V	303	37.69	17.36
4	11570.00	44.90 AV	54.00	-9.10	1.24 V	303	27.54	17.36
5	17983.00	59.56 PK	74.00	-14.44	2.55 V	146	37.52	22.04
6	17983.00	50.43 AV	54.00	-3.57	2.55 V	146	28.39	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	106.03 PK			1.01 H	332	99.92	6.11
2	*5825.00	96.27 AV			1.01 H	332	90.16	6.11
3	11650.00	56.07 PK	74.00	-17.93	2.03 H	231	38.92	17.15
4	11650.00	45.78 AV	54.00	-8.22	2.03 H	231	28.63	17.15
5	18000.00	60.82 PK	74.00	-13.18	1.59 H	303	38.34	22.48
6	18000.00	50.53 AV	54.00	-3.47	1.59 H	303	28.05	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	104.05 PK			1.04 V	3	97.94	6.11
2	*5825.00	94.18 AV			1.04 V	3	88.07	6.11
3	11650.00	55.03 PK	74.00	-18.97	1.30 V	287	37.88	17.15
4	11650.00	44.49 AV	54.00	-9.51	1.30 V	287	27.34	17.15
5	17966.00	59.39 PK	74.00	-14.61	2.48 V	137	37.79	21.60
6	17966.00	50.61 AV	54.00	-3.39	2.48 V	137	29.01	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





802.11ac (VHT20)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5180.00	109.20 PK			1.00 H	338	104.15	5.05
2	*5180.00	98.92 AV			1.00 H	338	93.87	5.05
3	#10360.00	54.41 PK	68.20	-13.79	2.55 H	224	38.67	15.74
4	18000.00	58.92 PK	74.00	-15.08	1.42 H	277	36.44	22.48
5	18000.00	50.53 AV	54.00	-3.47	1.42 H	277	28.05	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5180.00	106.46 PK			1.02 V	4	101.41	5.05
2	*5180.00	96.07 AV			1.02 V	4	91.02	5.05
3	#10360.00	53.23 PK	68.20	-14.97	1.18 V	287	37.49	15.74
4	17983.00	59.65 PK	74.00	-14.35	2.36 V	171	37.61	22.04
5	17983.00	50.37 AV	54.00	-3.63	2.36 V	171	28.33	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5200.00	108.97 PK			1.03 H	335	104.07	4.90
2	*5200.00	98.86 AV			1.03 H	335	93.96	4.90
3	#10400.00	54.32 PK	68.20	-13.88	2.62 H	216	38.27	16.05
4	17983.00	59.31 PK	74.00	-14.69	1.38 H	274	37.27	22.04
5	17983.00	50.65 AV	54.00	-3.35	1.38 H	274	28.61	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5200.00	105.85 PK			1.01 V	2	100.95	4.90
2	*5200.00	95.74 AV			1.01 V	2	90.84	4.90
3	#10400.00	53.26 PK	68.20	-14.94	1.28 V	294	37.21	16.05
4	18000.00	61.06 PK	74.00	-12.94	2.40 V	181	38.58	22.48
5	18000.00	50.80 AV	54.00	-3.20	2.40 V	181	28.32	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	108.77 PK			1.00 H	336	104.12	4.65
2	*5240.00	99.63 AV			1.00 H	336	94.98	4.65
3	#10480.00	55.18 PK	68.20	-13.02	2.58 H	223	38.52	16.66
4	17966.00	58.87 PK	74.00	-15.13	1.47 H	282	37.27	21.60
5	17966.00	50.13 AV	54.00	-3.87	1.47 H	282	28.53	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	105.17 PK			1.00 V	0	100.52	4.65
2	*5240.00	95.08 AV			1.00 V	0	90.43	4.65
3	#10480.00	54.26 PK	68.20	-13.94	1.30 V	304	37.60	16.66
4	17983.00	59.77 PK	74.00	-14.23	2.43 V	175	37.73	22.04
5	17983.00	49.93 AV	54.00	-4.07	2.43 V	175	27.89	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5260.00	108.89 PK			1.04 H	330	104.37	4.52
2	*5260.00	98.78 AV			1.04 H	330	94.26	4.52
3	#10520.00	55.51 PK	68.20	-12.69	2.27 H	218	38.66	16.85
4	18000.00	59.03 PK	74.00	-14.97	1.52 H	276	36.55	22.48
5	18000.00	50.25 AV	54.00	-3.75	1.52 H	276	27.77	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5260.00	104.40 PK			1.00 V	3	99.88	4.52
2	*5260.00	94.55 AV			1.00 V	3	90.03	4.52
3	#10520.00	54.55 PK	68.20	-13.65	1.18 V	296	37.70	16.85
4	17966.00	60.99 PK	74.00	-13.01	2.44 V	180	39.39	21.60
5	17966.00	50.34 AV	54.00	-3.66	2.44 V	180	28.74	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band





CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	108.45 PK			1.01 H	332	104.13	4.32
2	*5300.00	98.40 AV			1.01 H	332	94.08	4.32
3	10600.00	55.36 PK	74.00	-18.64	2.19 H	230	38.39	16.97
4	10600.00	45.13 AV	54.00	-8.87	2.19 H	230	28.16	16.97
5	17983.00	59.93 PK	74.00	-14.07	1.48 H	270	37.89	22.04
6	17983.00	50.14 AV	54.00	-3.86	1.48 H	270	28.10	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5300.00	103.99 PK			1.02 V	359	99.67	4.32
2	*5300.00	94.25 AV			1.02 V	359	89.93	4.32
3	10600.00	54.58 PK	74.00	-19.42	1.22 V	294	37.61	16.97
4	10600.00	44.21 AV	54.00	-9.79	1.22 V	294	27.24	16.97
5	17949.00	58.96 PK	74.00	-15.04	2.39 V	174	37.78	21.18
6	17949.00	50.15 AV	54.00	-3.85	2.39 V	174	28.97	21.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	108.65 PK			1.00 H	333	104.27	4.38
2	*5320.00	98.50 AV			1.00 H	333	94.12	4.38
3	10640.00	55.20 PK	74.00	-18.80	2.17 H	233	38.54	16.66
4	10640.00	44.92 AV	54.00	-9.08	2.17 H	333	28.26	16.66
5	18000.00	59.06 PK	74.00	-14.94	1.37 H	266	36.58	22.48
6	18000.00	49.94 AV	54.00	-4.06	1.37 H	266	27.46	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	103.76 PK			1.01 V	11	99.38	4.38
2	*5320.00	93.90 AV			1.01 V	11	89.52	4.38
3	10640.00	54.18 PK	74.00	-19.82	1.17 V	284	37.52	16.66
4	10640.00	43.99 AV	54.00	-10.01	1.17 V	274	27.33	16.66
5	17983.00	59.32 PK	74.00	-14.68	2.46 V	183	37.28	22.04
6	17983.00	50.16 AV	54.00	-3.84	2.46 V	183	28.12	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5500.00	106.16 PK			1.50 H	335	101.69	4.47
2	*5500.00	96.51 AV			1.50 H	335	92.04	4.47
3	11000.00	55.09 PK	74.00	-18.91	2.23 H	194	38.67	16.42
4	11000.00	44.16 AV	54.00	-9.84	2.23 H	194	27.74	16.42
5	18000.00	58.38 PK	74.00	-15.62	1.49 H	280	35.90	22.48
6	18000.00	50.16 AV	54.00	-3.84	1.49 H	280	27.68	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5500.00	103.98 PK			1.02 V	344	99.51	4.47
2	*5500.00	95.15 AV			1.02 V	344	90.68	4.47
3	11000.00	54.12 PK	74.00	-19.88	1.25 V	290	37.70	16.42
4	11000.00	43.75 AV	54.00	-10.25	1.25 V	290	27.33	16.42
5	17949.00	58.74 PK	74.00	-15.26	2.40 V	177	37.56	21.18
6	17949.00	50.27 AV	54.00	-3.73	2.40 V	177	29.09	21.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5580.00	107.00 PK			1.00 H	331	102.17	4.83
2	*5580.00	97.13 AV			1.00 H	331	92.30	4.83
3	11160.00	55.45 PK	74.00	-18.55	2.27 H	198	38.41	17.04
4	11160.00	44.84 AV	54.00	-9.16	2.27 H	198	27.80	17.04
5	18000.00	59.76 PK	74.00	-14.24	1.51 H	274	37.28	22.48
6	18000.00	50.27 AV	54.00	-3.73	1.51 H	274	27.79	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5580.00	104.04 PK			1.06 V	347	99.21	4.83
2	*5580.00	94.50 AV			1.06 V	347	89.67	4.83
3	11160.00	54.57 PK	74.00	-19.43	1.18 V	285	37.53	17.04
4	11160.00	44.30 AV	54.00	-9.70	1.18 V	285	27.26	17.04
5	17983.00	58.33 PK	74.00	-15.67	2.36 V	182	36.29	22.04
6	17983.00	50.40 AV	54.00	-3.60	2.36 V	182	28.36	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	107.34 PK			1.48 H	346	102.05	5.29
2	*5700.00	97.66 AV			1.48 H	346	92.37	5.29
3	11400.00	55.34 PK	74.00	-18.66	2.27 H	208	38.50	16.84
4	11400.00	44.43 AV	54.00	-9.57	2.27 H	208	27.59	16.84
5	17983.00	58.85 PK	74.00	-15.15	1.41 H	265	36.81	22.04
6	17983.00	49.79 AV	54.00	-4.21	1.41 H	265	27.75	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	104.52 PK			1.46 V	330	99.23	5.29
2	*5700.00	94.83 AV			1.46 V	330	89.54	5.29
3	11400.00	54.45 PK	74.00	-19.55	1.19 V	285	37.61	16.84
4	11400.00	44.13 AV	54.00	-9.87	1.19 V	285	27.29	16.84
5	18000.00	59.67 PK	74.00	-14.33	2.36 V	184	37.19	22.48
6	18000.00	50.17 AV	54.00	-3.83	2.36 V	184	27.69	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5720.00	107.50 PK			1.00 H	339	102.06	5.44
2	*5720.00	97.75 AV			1.00 H	339	92.31	5.44
3	11440.00	55.27 PK	74.00	-18.73	2.09 H	238	38.24	17.03
4	11440.00	44.66 AV	54.00	-9.34	2.09 H	238	27.63	17.03
5	17966.00	57.91 PK	74.00	-16.09	1.52 H	271	36.31	21.60
6	17966.00	50.48 AV	54.00	-3.52	1.52 H	271	28.88	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5720.00	103.85 PK			1.03 V	2	98.41	5.44
2	*5720.00	94.19 AV			1.03 V	2	88.75	5.44
3	11440.00	55.41 PK	74.00	-18.59	1.23 V	297	38.38	17.03
4	11440.00	44.24 AV	54.00	-9.76	1.23 V	297	27.21	17.03
5	18000.00	59.18 PK	74.00	-14.82	2.63 V	185	36.70	22.48
6	18000.00	50.30 AV	54.00	-3.70	2.63 V	185	27.82	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	104.72 PK			1.00 H	336	99.11	5.61
2	*5745.00	94.93 AV			1.00 H	336	89.32	5.61
3	11490.00	56.03 PK	74.00	-17.97	1.96 H	237	38.77	17.26
4	11490.00	45.81 AV	54.00	-8.19	1.96 H	237	28.55	17.26
5	17983.00	59.65 PK	74.00	-14.35	1.61 H	310	37.61	22.04
6	17983.00	50.58 AV	54.00	-3.42	1.61 H	310	28.54	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5745.00	102.53 PK			1.07 V	2	96.92	5.61
2	*5745.00	92.70 AV			1.07 V	2	87.09	5.61
3	11490.00	54.95 PK	74.00	-19.05	1.26 V	315	37.69	17.26
4	11490.00	44.77 AV	54.00	-9.23	1.26 V	315	27.51	17.26
5	17966.00	59.59 PK	74.00	-14.41	2.50 V	141	37.99	21.60
6	17966.00	50.37 AV	54.00	-3.63	2.50 V	141	28.77	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	105.28 PK			1.01 H	332	99.38	5.90
2	*5785.00	95.33 AV			1.01 H	332	89.43	5.90
3	11570.00	56.11 PK	74.00	-17.89	1.88 H	227	38.75	17.36
4	11570.00	45.74 AV	54.00	-8.26	1.88 H	227	28.38	17.36
5	17983.00	58.32 PK	74.00	-15.68	1.54 H	305	36.28	22.04
6	17983.00	50.29 AV	54.00	-3.71	1.54 H	305	28.25	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5785.00	101.63 PK			1.04 V	5	95.73	5.90
2	*5785.00	91.78 AV			1.04 V	5	85.88	5.90
3	11570.00	54.88 PK	74.00	-19.12	1.22 V	293	37.52	17.36
4	11570.00	44.86 AV	54.00	-9.14	1.22 V	293	27.50	17.36
5	17966.00	59.06 PK	74.00	-14.94	2.46 V	149	37.46	21.60
6	17966.00	50.32 AV	54.00	-3.68	2.46 V	149	28.72	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	106.21 PK			1.00 H	333	100.10	6.11
2	*5825.00	96.38 AV			1.00 H	333	90.27	6.11
3	11650.00	56.07 PK	74.00	-17.93	2.05 H	234	38.92	17.15
4	11650.00	45.78 AV	54.00	-8.22	2.05 H	234	28.63	17.15
5	17966.00	59.63 PK	74.00	-14.37	1.57 H	299	38.03	21.60
6	17966.00	50.34 AV	54.00	-3.66	1.57 H	299	28.74	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5825.00	102.74 PK			1.02 V	1	96.63	6.11
2	*5825.00	92.88 AV			1.02 V	1	86.77	6.11
3	11650.00	54.96 PK	74.00	-19.04	1.29 V	287	37.81	17.15
4	11650.00	44.72 AV	54.00	-9.28	1.29 V	287	27.57	17.15
5	18000.00	60.26 PK	74.00	-13.74	2.61 V	138	37.78	22.48
6	18000.00	49.98 AV	54.00	-4.02	2.61 V	138	27.50	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





802.11ac (VHT40)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5190.00	106.02 PK			1.04 H	339	101.04	4.98
2	*5190.00	105.61 AV			1.04 H	339	100.63	4.98
3	#10380.00	54.14 PK	68.20	-14.06	2.53 H	216	38.25	15.89
4	18000.00	59.57 PK	74.00	-14.43	1.53 H	274	37.09	22.48
5	18000.00	50.31 AV	54.00	-3.69	1.53 H	274	27.83	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5190.00	102.66 PK			1.01 V	2	97.68	4.98
2	*5190.00	91.89 AV			1.01 V	2	86.91	4.98
3	#10380.00	53.03 PK	68.20	-15.17	1.20 V	293	37.14	15.89
4	18000.00	58.62 PK	74.00	-15.38	2.51 V	179	36.14	22.48
5	18000.00	50.41 AV	54.00	-3.59	2.51 V	179	27.93	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	106.44 PK			1.00 H	336	101.73	4.71
2	*5230.00	96.76 AV			1.00 H	336	92.05	4.71
3	#10460.00	55.01 PK	68.20	-13.19	2.61 H	211	38.49	16.52
4	17983.00	59.80 PK	74.00	-14.20	1.56 H	279	37.76	22.04
5	17983.00	50.17 AV	54.00	-3.83	1.56 H	279	28.13	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	103.00 PK			1.00 V	0	98.29	4.71
2	*5230.00	92.55 AV			1.00 V	0	87.84	4.71
3	#10460.00	54.04 PK	68.20	-14.16	1.14 V	288	37.52	16.52
4	17983.00	59.78 PK	74.00	-14.22	1.39 V	267	37.74	22.04
5	17983.00	50.35 AV	54.00	-3.65	1.39 V	267	28.31	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	105.96 PK			1.06 H	333	101.49	4.47
2	*5270.00	96.43 AV			1.06 H	333	91.96	4.47
3	#10540.00	55.35 PK	68.20	-12.85	2.34 H	213	38.47	16.88
4	18000.00	59.32 PK	74.00	-14.68	1.58 H	274	36.84	22.48
5	18000.00	50.14 AV	54.00	-3.86	1.58 H	274	27.66	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band





CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	103.41 PK			1.00 V	13	98.94	4.47
2	*5270.00	93.53 AV			1.00 V	13	89.06	4.47
3	#10540.00	54.55 PK	68.20	-13.65	1.21 V	294	37.67	16.88
4	18000.00	58.77 PK	74.00	-15.23	2.42 V	176	36.29	22.48
5	18000.00	50.32 AV	54.00	-3.68	2.42 V	176	27.84	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	105.22 PK			1.03 H	331	100.86	4.36
2	*5310.00	95.50 AV			1.03 H	331	91.14	4.36
3	10620.00	55.28 PK	74.00	-18.72	2.46 H	225	38.46	16.82
4	10620.00	44.90 AV	54.00	-9.10	2.46 H	225	28.08	16.82
5	18000.00	60.35 PK	74.00	-13.65	1.53 H	277	37.87	22.48
6	18000.00	50.15 AV	54.00	-3.85	1.53 H	277	27.67	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	105.22 PK			1.03 H	331	100.86	4.36
2	*5310.00	95.50 AV			1.03 H	331	91.14	4.36
3	10620.00	55.28 PK	74.00	-18.72	2.46 H	225	38.46	16.82
4	10620.00	44.90 AV	54.00	-9.10	2.46 H	225	28.08	16.82
5	18000.00	60.35 PK	74.00	-13.65	1.53 H	277	37.87	22.48
6	18000.00	50.15 AV	54.00	-3.85	1.53 H	277	27.67	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 102	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5510.00	105.32 PK			1.00 H	335	100.81	4.51
2	*5510.00	96.45 AV			1.00 H	335	91.94	4.51
3	11020.00	54.92 PK	74.00	-19.08	2.02 H	228	38.39	16.53
4	11020.00	44.34 AV	54.00	-9.66	2.02 H	228	27.81	16.53
5	18000.00	59.81 PK	74.00	-14.19	1.52 H	273	37.33	22.48
6	18000.00	50.45 AV	54.00	-3.55	1.52 H	273	27.97	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 102	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5510.00	101.07 PK			1.07 V	2	96.56	4.51
2	*5510.00	92.54 AV			1.07 V	2	88.03	4.51
3	11020.00	54.18 PK	74.00	-19.82	1.35 V	301	37.65	16.53
4	11020.00	43.73 AV	54.00	-10.27	1.35 V	301	27.20	16.53
5	17983.00	59.23 PK	74.00	-14.77	2.44 V	166	37.19	22.04
6	17983.00	49.88 AV	54.00	-4.12	2.44 V	166	27.84	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 110	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5550.00	105.79 PK			1.00 H	338	101.09	4.70
2	*5550.00	97.23 AV			1.00 H	338	92.53	4.70
3	11100.00	55.46 PK	74.00	-18.54	1.96 H	223	38.53	16.93
4	11100.00	44.87 AV	54.00	-9.13	1.96 H	223	27.94	16.93
5	18000.00	59.19 PK	74.00	-14.81	1.37 H	264	36.71	22.48
6	18000.00	50.60 AV	54.00	-3.40	1.37 H	264	28.12	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 110	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5550.00	103.37 PK			1.03 V	3	98.67	4.70
2	*5550.00	93.82 AV			1.03 V	3	89.12	4.70
3	11100.00	54.64 PK	74.00	-19.36	1.41 V	294	37.71	16.93
4	11100.00	44.09 AV	54.00	-9.91	1.41 V	294	27.16	16.93
5	17983.00	59.00 PK	74.00	-15.00	2.51 V	170	36.96	22.04
6	17983.00	50.00 AV	54.00	-4.00	2.51 V	170	27.96	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 134	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5670.00	104.98 PK			1.01 H	336	99.84	5.14
2	*5670.00	95.30 AV			1.01 H	336	90.16	5.14
3	11340.00	55.00 PK	74.00	-19.00	1.89 H	230	38.27	16.73
4	11340.00	44.49 AV	54.00	-9.51	1.89 H	230	27.76	16.73
5	18000.00	60.06 PK	74.00	-13.94	1.43 H	272	37.58	22.48
6	18000.00	50.13 AV	54.00	-3.87	1.43 H	272	27.65	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 134	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5670.00	102.16 PK			1.02 V	4	97.02	5.14
2	*5670.00	93.38 AV			1.02 V	4	88.24	5.14
3	11340.00	54.39 PK	74.00	-19.61	1.10 V	311	37.66	16.73
4	11340.00	44.01 AV	54.00	-9.99	1.10 V	311	27.28	16.73
5	17966.00	59.32 PK	74.00	-14.68	2.41 V	159	37.72	21.60
6	17966.00	50.06 AV	54.00	-3.94	2.41 V	159	28.46	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 142	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5710.00	104.77 PK			1.00 H	335	99.41	5.36
2	*5710.00	95.21 AV			1.00 H	335	89.85	5.36
3	11420.00	55.30 PK	74.00	-18.70	1.99 H	205	38.36	16.94
4	11420.00	44.63 AV	54.00	-9.37	1.99 H	205	27.69	16.94
5	17949.00	58.86 PK	74.00	-15.14	1.46 H	277	37.68	21.18
6	17949.00	49.94 AV	54.00	-4.06	1.46 H	277	28.76	21.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 142	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5710.00	102.49 PK			1.04 V	6	97.13	5.36
2	*5710.00	92.82 AV			1.04 V	6	87.46	5.36
3	11420.00	54.57 PK	74.00	-19.43	1.30 V	302	37.63	16.94
4	11420.00	44.14 AV	54.00	-9.86	1.30 V	302	27.20	16.94
5	18000.00	59.94 PK	74.00	-14.06	2.59 V	178	37.46	22.48
6	18000.00	50.33 AV	54.00	-3.67	2.59 V	178	27.85	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	105.31 PK			1.00 H	333	99.64	5.67
2	*5755.00	95.42 AV			1.00 H	333	89.75	5.67
3	11510.00	55.91 PK	74.00	-18.09	1.88 H	225	38.60	17.31
4	11510.00	45.69 AV	54.00	-8.31	1.88 H	225	28.38	17.31
5	17983.00	59.52 PK	74.00	-14.48	1.51 H	293	37.48	22.04
6	17983.00	50.52 AV	54.00	-3.48	1.51 H	293	28.48	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5755.00	102.87 PK			1.03 V	1	97.20	5.67
2	*5755.00	92.53 AV			1.03 V	1	86.86	5.67
3	11510.00	54.82 PK	74.00	-19.18	1.20 V	294	37.51	17.31
4	11510.00	44.63 AV	54.00	-9.37	1.20 V	294	27.32	17.31
5	17983.00	59.42 PK	74.00	-14.58	2.54 V	155	37.38	22.04
6	17983.00	50.23 AV	54.00	-3.77	2.54 V	155	28.19	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	105.27 PK			1.02 H	332	99.30	5.97
2	*5795.00	95.38 AV			1.02 H	332	89.41	5.97
3	11590.00	55.73 PK	74.00	-18.27	1.95 H	217	38.36	17.37
4	11590.00	45.62 AV	54.00	-8.38	1.95 H	217	28.25	17.37
5	18000.00	59.51 PK	74.00	-14.49	1.43 H	297	37.03	22.48
6	18000.00	50.74 AV	54.00	-3.26	1.43 H	297	28.26	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5795.00	102.36 PK			1.05 V	0	96.39	5.97
2	*5795.00	92.48 AV			1.05 V	0	86.51	5.97
3	11590.00	54.73 PK	74.00	-19.27	1.26 V	284	37.36	17.37
4	11590.00	44.81 AV	54.00	-9.19	1.26 V	284	27.44	17.37
5	18000.00	60.41 PK	74.00	-13.59	2.52 V	160	37.93	22.48
6	18000.00	50.21 AV	54.00	-3.79	2.52 V	160	27.73	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency





802.11ac (VHT80)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5210.00	101.57 PK			1.03 H	334	96.74	4.83
2	*5210.00	91.71 AV			1.03 H	334	86.88	4.83
3	#10420.00	54.28 PK	68.20	-13.92	2.59 H	227	38.07	16.21
4	18000.00	58.48 PK	74.00	-15.52	1.42 H	268	36.00	22.48
5	18000.00	50.36 AV	54.00	-3.64	1.42 H	268	27.88	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5210.00	98.10 PK			1.01 V	0	93.27	4.83
2	*5210.00	88.34 AV			1.01 V	0	83.51	4.83
3	#10420.00	53.37 PK	68.20	-14.83	1.15 V	297	37.16	16.21
4	18000.00	58.62 PK	74.00	-15.38	1.44 V	273	36.14	22.48
5	18000.00	50.06 AV	54.00	-3.94	1.44 V	273	27.58	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 58	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5290.00	101.95 PK			1.05 H	335	97.58	4.37
2	*5290.00	93.01 AV			1.05 H	335	88.64	4.37
3	#10580.00	55.43 PK	68.20	-12.77	2.27 H	206	38.49	16.94
4	18000.00	59.31 PK	74.00	-14.69	1.49 H	281	36.83	22.48
5	18000.00	50.28 AV	54.00	-3.72	1.49 H	281	27.80	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band






CHANNEL	TX Channel 58	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5290.00	97.78 PK			1.01 V	15	93.41	4.37
2	*5290.00	88.87 AV			1.01 V	15	84.50	4.37
3	#10580.00	54.60 PK	68.20	-13.60	1.14 V	293	37.66	16.94
4	17966.00	58.46 PK	74.00	-15.54	2.45 V	179	36.86	21.60
5	17966.00	50.15 AV	54.00	-3.85	2.45 V	179	28.55	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency
6. " # ": The radiated frequency is out of the restricted band




CHANNEL	TX Channel 106	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5530.00	100.15 PK			1.00 H	339	95.53	4.62
2	*5530.00	89.30 AV			1.00 H	339	84.68	4.62
3	11060.00	54.86 PK	74.00	-19.14	1.88 H	227	38.14	16.72
4	11060.00	44.37 AV	54.00	-9.63	1.88 H	227	27.65	16.72
5	17983.00	59.89 PK	74.00	-14.11	1.48 H	269	37.85	22.04
6	17983.00	50.23 AV	54.00	-3.77	1.48 H	269	28.19	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 106	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5530.00	96.59 PK			1.03 V	0	91.97	4.62
2	*5530.00	85.96 AV			1.03 V	0	81.34	4.62
3	11060.00	54.01 PK	74.00	-19.99	1.32 V	295	37.29	16.72
4	11060.00	43.66 AV	54.00	-10.34	1.32 V	295	26.94	16.72
5	18000.00	58.39 PK	74.00	-15.61	2.50 V	167	35.91	22.48
6	18000.00	50.28 AV	54.00	-3.72	2.50 V	167	27.80	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 122	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5610.00	101.90 PK			1.02 H	337	96.97	4.93
2	*5610.00	91.18 AV			1.02 H	337	86.25	4.93
3	11220.00	55.57 PK	74.00	-18.43	2.01 H	235	38.54	17.03
4	11220.00	45.22 AV	54.00	-8.78	2.01 H	235	28.19	17.03
5	18000.00	61.23 PK	74.00	-12.77	1.56 H	258	38.75	22.48
6	18000.00	50.54 AV	54.00	-3.46	1.56 H	258	28.06	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 122	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5610.00	100.62 PK			1.00 V	1	95.69	4.93
2	*5610.00	90.33 AV			1.00 V	1	85.40	4.93
3	11220.00	54.70 PK	74.00	-19.30	1.28 V	302	37.67	17.03
4	11220.00	44.28 AV	54.00	-9.72	1.28 V	302	27.25	17.03
5	17966.00	60.37 PK	74.00	-13.63	2.49 V	178	38.77	21.60
6	17966.00	50.25 AV	54.00	-3.75	2.49 V	178	28.65	21.60

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 138	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5690.00	103.87 PK			1.01 H	338	98.63	5.24
2	*5690.00	93.83 AV			1.01 H	338	88.59	5.24
3	11380.00	55.21 PK	74.00	-18.79	2.03 H	210	38.41	16.80
4	11380.00	44.51 AV	54.00	-9.49	2.03 H	210	27.71	16.80
5	17983.00	59.50 PK	74.00	-14.50	1.54 H	263	37.46	22.04
6	17983.00	50.46 AV	54.00	-3.54	1.54 H	263	28.42	22.04

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 138	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5690.00	101.16 PK			1.00 V	0	95.92	5.24
2	*5690.00	91.12 AV			1.00 V	0	85.88	5.24
3	11380.00	54.41 PK	74.00	-19.59	1.22 V	298	37.61	16.80
4	11380.00	44.05 AV	54.00	-9.95	1.22 V	298	27.25	16.80
5	18000.00	58.71 PK	74.00	-15.29	2.61 V	184	36.23	22.48
6	18000.00	50.26 AV	54.00	-3.74	2.61 V	184	27.78	22.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency






CHANNEL	TX Channel 155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5775.00	101.56 PK			1.01 H	336	95.73	5.83
2	*5775.00	91.68 AV			1.01 H	336	85.85	5.83
3	11550.00	55.79 PK	74.00	-18.21	2.03 H	230	38.45	17.34
4	11550.00	45.64 AV	54.00	-8.36	2.03 H	230	28.30	17.34
5	17915.00	58.71 PK	74.00	-15.29	1.63 H	301	38.41	20.30
6	17915.00	50.56 AV	54.00	-3.44	1.63 H	301	30.26	20.30

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency




CHANNEL	TX Channel 155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5775.00	98.92 PK			1.00 V	0	93.09	5.83
2	*5775.00	88.98 AV			1.00 V	0	83.15	5.83
3	11550.00	54.88 PK	74.00	-19.12	1.30 V	291	37.54	17.34
4	11550.00	44.96 AV	54.00	-9.04	1.30 V	291	27.62	17.34
5	17949.00	59.25 PK	74.00	-14.75	2.49 V	164	38.07	21.18
6	17949.00	50.55 AV	54.00	-3.45	2.49 V	164	29.37	21.18

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency



4.1.8 Test Results for Bandedge above 1GHz


802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5149.99	61.56 PK	74.00	-12.44	1.00 H	336	56.29	5.27
AV.1	5149.99	48.43 AV	54.00	-5.57	1.00 H	336	43.16	5.27

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5149.99	59.03 PK	74.00	-14.97	1.00 V	0	53.76	5.27
AV.1	5149.99	47.22 AV	54.00	-6.78	1.00 V	0	41.95	5.27

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5095.20	55.31 PK	74.00	-18.69	1.00 H	334	49.90	5.41
PK.2	5456.16	53.81 PK	74.00	-20.19	1.00 H	334	49.13	4.68
AV.1	5100.00	45.26 AV	54.00	-8.74	1.00 H	334	39.82	5.44
AV.2	5449.44	43.69 AV	54.00	-10.31	1.00 H	334	38.98	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5026.08	55.94 PK	74.00	-18.06	1.03 V	5	50.99	4.95
PK.2	5404.32	54.27 PK	74.00	-19.73	1.03 V	5	49.56	4.71
AV.1	5109.60	45.56 AV	54.00	-8.44	1.03 V	5	40.15	5.41
AV.2	5436.01	43.89 AV	54.00	-10.11	1.03 V	5	39.19	4.70

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5100.00	55.46 PK	74.00	-18.54	1.02 H	337	50.02	5.44
PK.2	5364.96	54.21 PK	74.00	-19.79	1.02 H	337	49.65	4.56
AV.1	5100.00	45.28 AV	54.00	-8.72	1.02 H	337	39.84	5.44
AV.2	5449.44	43.69 AV	54.00	-10.31	1.02 H	337	38.98	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5101.92	56.48 PK	74.00	-17.52	1.01 V	1	51.05	5.43
PK.2	5413.92	54.86 PK	74.00	-19.14	1.01 V	1	50.14	4.72
AV.1	5076.00	45.37 AV	54.00	-8.63	1.01 V	1	40.07	5.30
AV.2	5408.16	43.80 AV	54.00	-10.20	1.01 V	1	39.09	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5099.04	55.79 PK	74.00	-18.21	1.00 H	333	50.36	5.43
AV.1	5120.16	45.34 AV	54.00	-8.66	1.00 H	333	39.97	5.37

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5136.48	56.15 PK	74.00	-17.85	1.02 V	6	50.83	5.32
AV.1	5108.64	45.46 AV	54.00	-8.54	1.02 V	6	40.05	5.41

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5097.12	54.86 PK	74.00	-19.14	1.03 H	337	49.44	5.42
PK.2	5368.80	53.91 PK	74.00	-20.09	1.03 H	337	49.33	4.58
AV.1	5112.48	45.40 AV	54.00	-8.60	1.03 H	337	40.01	5.39
AV.2	5422.56	43.99 AV	54.00	-10.01	1.03 H	337	39.28	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5141.28	56.08 PK	74.00	-17.92	1.05 V	3	50.78	5.30
PK.2	5440.80	54.59 PK	74.00	-19.41	1.05 V	3	49.88	4.71
AV.1	5095.20	45.29 AV	54.00	-8.71	1.05 V	3	39.88	5.41
AV.2	5415.84	43.81 AV	54.00	-10.19	1.05 V	3	39.09	4.72

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5361.12	53.95 PK	74.00	-20.05	1.00 H	331	49.41	4.54
AV.1	5351.52	44.43 AV	54.00	-9.57	1.00 H	331	39.92	4.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5430.24	55.35 PK	74.00	-18.65	1.01 V	2	50.64	4.71
AV.1	5451.36	43.87 AV	54.00	-10.13	1.01 V	2	39.18	4.69

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.99	56.64 PK	74.00	-17.36	1.57 H	336	51.99	4.65
PK.2	#5469.99	61.94 PK	68.20	-6.26	1.57 H	336	57.33	4.61
AV.1	5459.73	44.84 AV	54.00	-9.16	1.57 H	336	40.19	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.25	54.54 PK	74.00	-19.46	1.60 V	355	49.89	4.65
PK.2	#5469.23	56.24 PK	68.20	-11.96	1.60 V	355	51.62	4.62
AV.1	5459.73	43.89 AV	54.00	-10.11	1.60 V	355	39.24	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.25	53.83 PK	74.00	-20.17	1.59 H	313	49.18	4.65
PK.2	#5466.85	54.07 PK	68.20	-14.13	1.59 H	313	49.44	4.63
AV.1	5454.98	43.39 AV	54.00	-10.61	1.59 H	313	38.71	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5427.90	53.62 PK	74.00	-20.38	1.53 V	358	48.91	4.71
PK.2	#5462.10	53.96 PK	68.20	-14.24	1.53 V	358	49.32	4.64
AV.1	5448.32	43.43 AV	54.00	-10.57	1.53 V	358	38.72	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5725.25	63.21 PK	68.20	-4.99	1.50 H	348	57.74	5.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5725.73	63.19 PK	68.20	-5.01	1.58 V	344	57.72	5.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5428.00	53.54 PK	74.00	-20.46	1.02 H	334	48.83	4.71
PK.2	#5870.20	55.65 PK	68.20	-12.55	1.02 H	334	49.41	6.24
AV.1	5443.60	43.50 AV	54.00	-10.50	1.02 H	334	38.79	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5431.00	53.56 PK	74.00	-20.44	1.05 V	1	48.85	4.71
PK.2	#5925.40	55.44 PK	68.20	-12.76	1.05 V	1	49.17	6.27
AV.1	5445.40	43.46 AV	54.00	-10.54	1.05 V	1	38.75	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5638.35	55.34 PK	68.20	-12.86	1.03 H	333	50.33	5.01
PK.2	#5939.02	56.44 PK	68.20	-11.76	1.03 H	333	50.18	6.26

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5649.27	55.42 PK	68.20	-12.78	1.00 V	6	50.39	5.03
PK.2	#5983.68	56.40 PK	68.20	-11.80	1.00 V	6	50.06	6.34

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5643.57	55.36 PK	68.20	-12.84	1.00 H	331	50.33	5.03
PK.2	#6003.62	56.75 PK	68.20	-11.45	1.00 H	331	50.36	6.39

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5603.20	54.98 PK	68.20	-13.22	1.02 V	4	50.06	4.92
PK.2	#5982.25	55.39 PK	68.20	-12.81	1.02 V	4	49.04	6.35

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5616.02	54.95 PK	68.20	-13.25	1.01 H	332	49.99	4.96
PK.2	#5939.50	55.96 PK	68.20	-12.24	1.01 H	332	49.71	6.25

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5627.43	55.48 PK	68.20	-12.72	1.04 V	3	50.50	4.98
PK.2	#6009.80	56.08 PK	68.20	-12.12	1.04 V	3	49.68	6.40

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




802.11ac (VHT20)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5149.92	60.18 PK	74.00	-13.82	1.00 H	338	54.91	5.27
AV.1	5149.92	49.12 AV	54.00	-4.88	1.00 H	338	43.85	5.27

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5148.00	58.44 PK	74.00	-15.56	1.02 V	4	53.16	5.28
AV.1	5148.00	47.59 AV	54.00	-6.41	1.02 V	4	42.31	5.28

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5111.52	55.26 PK	74.00	-18.74	1.03 H	335	49.86	5.40
PK.2	5449.44	54.83 PK	74.00	-19.17	1.03 H	335	50.12	4.71
AV.1	5148.00	45.54 AV	54.00	-8.46	1.03 H	335	40.26	5.28
AV.2	5430.26	44.05 AV	54.00	-9.95	1.03 H	335	39.34	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5078.88	55.56 PK	74.00	-18.44	1.01 V	2	50.24	5.32
PK.2	5435.04	53.81 PK	74.00	-20.19	1.01 V	2	49.11	4.70
AV.1	5145.12	45.66 AV	54.00	-8.34	1.01 V	2	40.37	5.29
AV.2	5425.44	43.83 AV	54.00	-10.17	1.01 V	2	39.11	4.72

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5107.68	54.09 PK	74.00	-19.91	1.00 H	336	48.67	5.42
PK.2	5436.96	54.67 PK	74.00	-19.33	1.00 H	336	49.97	4.70
AV.1	5121.12	43.71 AV	54.00	-10.29	1.00 H	336	38.35	5.36
AV.2	5446.56	42.17 AV	54.00	-11.83	1.00 H	336	37.46	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5057.76	55.58 PK	74.00	-18.42	1.00 V	0	50.38	5.20
PK.2	5448.48	54.89 PK	74.00	-19.11	1.00 V	0	50.18	4.71
AV.1	5111.52	45.51 AV	54.00	-8.49	1.00 V	0	40.11	5.40
AV.2	5436.00	44.02 AV	54.00	-9.98	1.00 V	0	39.32	4.70

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5148.00	55.67 PK	74.00	-18.33	1.04 H	330	50.39	5.28
AV.1	5092.32	45.51 AV	54.00	-8.49	1.04 H	330	40.12	5.39

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5113.44	56.19 PK	74.00	-17.81	1.00 V	3	50.80	5.39
AV.1	5101.92	45.69 AV	54.00	-8.31	1.00 V	3	40.26	5.43

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5070.24	56.64 PK	74.00	-17.36	1.01 H	332	51.37	5.27
PK.2	5432.16	54.50 PK	74.00	-19.50	1.01 H	332	49.79	4.71
AV.1	5095.20	45.55 AV	54.00	-8.45	1.01 H	332	40.14	5.41
AV.2	5429.28	43.97 AV	54.00	-10.03	1.01 H	332	39.26	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5035.68	56.64 PK	74.00	-17.36	1.02 V	359	51.60	5.04
PK.2	5442.72	53.96 PK	74.00	-20.04	1.02 V	359	49.25	4.71
AV.1	5132.64	45.28 AV	54.00	-8.72	1.02 V	359	39.94	5.34
AV.2	5445.60	44.01 AV	54.00	-9.99	1.02 V	359	39.30	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5350.56	56.06 PK	74.00	-17.94	1.00 H	333	51.56	4.50
AV.1	5351.52	45.57 AV	54.00	-8.43	1.00 H	333	41.06	4.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5457.12	54.85 PK	74.00	-19.15	1.01 V	11	50.18	4.67
AV.1	5351.52	44.17 AV	54.00	-9.83	1.01 V	11	39.66	4.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.25	55.21 PK	74.00	-18.79	1.50 H	335	50.56	4.65
PK.2	#5467.32	60.34 PK	68.20	-7.86	1.50 H	335	55.72	4.62
AV.1	5459.25	44.96 AV	54.00	-9.04	1.50 H	335	40.31	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 100	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.73	53.53 PK	74.00	-20.47	1.02 V	344	48.88	4.65
PK.2	#5464.48	56.90 PK	68.20	-11.30	1.02 V	344	52.26	4.64
AV.1	5459.25	44.20 AV	54.00	-9.80	1.02 V	344	39.55	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5453.55	53.38 PK	74.00	-20.62	1.00 H	331	48.69	4.69
PK.2	#5464.48	52.97 PK	68.20	-15.23	1.00 H	331	48.33	4.64
AV.1	5459.25	43.31 AV	54.00	-10.69	1.00 H	331	38.66	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 116	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5437.40	54.95 PK	74.00	-19.05	1.06 V	347	50.25	4.70
PK.2	#5463.52	53.45 PK	68.20	-14.75	1.06 V	347	48.80	4.65
AV.1	5454.02	43.55 AV	54.00	-10.45	1.06 V	347	38.87	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5725.01	66.61 PK	68.20	-1.59	1.48 H	346	61.14	5.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 140	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5725.25	62.88 PK	68.20	-5.32	1.46 V	330	57.41	5.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5444.80	53.95 PK	74.00	-20.05	1.00 H	339	49.24	4.71
PK.2	#5889.40	55.94 PK	68.20	-12.26	1.00 H	339	49.66	6.28
AV.1	5455.00	43.39 AV	54.00	-10.61	1.00 H	339	38.71	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 144	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5385.40	53.83 PK	74.00	-20.17	1.03 V	2	49.17	4.66
PK.2	#5892.40	56.03 PK	68.20	-12.17	1.03 V	2	49.75	6.28
AV.1	5442.40	43.42 AV	54.00	-10.58	1.03 V	2	38.71	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5612.70	55.31 PK	68.20	-12.89	1.00 H	336	50.36	4.95
PK.2	#6015.50	56.03 PK	68.20	-12.17	1.00 H	336	49.63	6.40

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5592.27	55.16 PK	68.20	-13.04	1.07 V	2	50.29	4.87
PK.2	#5932.85	56.44 PK	68.20	-11.76	1.07 V	2	50.18	6.26

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5589.90	55.08 PK	68.20	-13.12	1.01 H	332	50.21	4.87
PK.2	#5945.68	55.84 PK	68.20	-12.36	1.01 H	332	49.58	6.26

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5649.75	54.87 PK	68.20	-13.33	1.04 V	5	49.84	5.03
PK.2	#5973.23	56.66 PK	68.20	-11.54	1.04 V	5	50.34	6.32

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5613.65	55.49 PK	68.20	-12.71	1.00 H	333	50.54	4.95
PK.2	#5977.02	55.95 PK	68.20	-12.25	1.00 H	333	49.62	6.33

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 165	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5621.25	55.46 PK	68.20	-12.74	1.02 V	1	50.50	4.96
PK.2	#5948.05	55.81 PK	68.20	-12.39	1.02 V	1	49.55	6.26

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




802.11ac (VHT40)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5149.92	63.13 PK	74.00	-10.87	1.04 H	339	57.86	5.27
AV.1	5149.88	52.46 AV	54.00	-1.54	1.04 H	339	47.19	5.27

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5149.92	65.22 PK	74.00	-8.78	1.01 V	2	59.95	5.27
AV.1	5149.92	51.45 AV	54.00	-2.55	1.01 V	2	46.18	5.27

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5120.16	55.67 PK	74.00	-18.33	1.00 H	336	50.30	5.37
PK.2	5427.36	54.22 PK	74.00	-19.78	1.00 H	336	49.51	4.71
AV.1	5149.92	45.73 AV	54.00	-8.27	1.00 H	336	40.46	5.27
AV.2	5407.20	43.81 AV	54.00	-10.19	1.00 H	336	39.10	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5092.32	56.34 PK	74.00	-17.66	1.00 V	0	50.95	5.39
PK.2	5428.32	54.79 PK	74.00	-19.21	1.00 V	0	50.08	4.71
AV.1	5094.24	45.39 AV	54.00	-8.61	1.00 V	0	39.99	5.40
AV.2	5437.92	43.89 AV	54.00	-10.11	1.00 V	0	39.18	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5089.44	56.31 PK	74.00	-17.69	1.06 H	333	50.94	5.37
AV.1	5105.76	45.35 AV	54.00	-8.65	1.06 H	333	39.93	5.42

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5144.16	55.71 PK	74.00	-18.29	1.00 V	13	50.42	5.29
AV.1	5093.28	45.43 AV	54.00	-8.57	1.00 V	13	40.03	5.40

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5351.52	61.50 PK	74.00	-12.50	1.03 H	331	56.99	4.51
AV.1	5350.18	52.36 AV	54.00	-1.64	1.03 H	331	47.86	4.50

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5351.52	56.79 PK	74.00	-17.21	1.04 V	12	52.28	4.51
AV.1	5351.52	47.02 AV	54.00	-6.98	1.04 V	12	42.51	4.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 102	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.25	58.75 PK	74.00	-15.25	1.00 H	335	54.10	4.65
PK.2	#5469.99	62.88 PK	68.20	-5.32	1.00 H	335	58.27	4.61
AV.1	5459.73	48.47 AV	54.00	-5.53	1.00 H	335	43.82	4.65
AV.1	5457.91	46.3 AV	54.0	-7.7	1.06 H	351	43.6	2.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 102	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5459.25	56.45 PK	74.00	-17.55	1.07 V	2	51.80	4.65
PK.2	#5469.70	60.79 PK	68.20	-7.41	1.07 V	2	56.17	4.62
AV.1	5456.40	45.93 AV	54.00	-8.07	1.07 V	2	41.25	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 110	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5453.07	53.59 PK	74.00	-20.41	1.00 H	338	48.90	4.69
PK.2	#5469.99	53.89 PK	68.20	-14.31	1.00 H	338	49.28	4.61
AV.1	5454.02	43.76 AV	54.00	-10.24	1.00 H	338	39.08	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 110	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5447.37	54.30 PK	74.00	-19.70	1.03 V	3	49.59	4.71
PK.2	#5469.23	54.17 PK	68.20	-14.03	1.03 V	3	49.55	4.62
AV.1	5452.12	43.74 AV	54.00	-10.26	1.03 V	3	39.05	4.69

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 134	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5725.73	60.59 PK	68.20	-7.61	1.01 H	336	55.12	5.47

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 134	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5726.68	57.80 PK	68.20	-10.40	1.02 V	4	52.32	5.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 142	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5448.40	53.43 PK	74.00	-20.57	1.00 H	335	48.72	4.71
PK.2	#5876.20	55.66 PK	68.20	-12.54	1.00 H	335	49.40	6.26
AV.1	5449.00	43.53 AV	54.00	-10.47	1.00 H	335	38.82	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 142	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5447.80	53.80 PK	74.00	-20.20	1.04 V	6	49.09	4.71
PK.2	#5879.20	55.46 PK	68.20	-12.74	1.04 V	6	49.19	6.27
AV.1	5455.00	43.42 AV	54.00	-10.58	1.04 V	6	38.74	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5622.68	56.19 PK	68.20	-12.01	1.00 H	333	51.22	4.97
PK.2	#6023.57	56.84 PK	68.20	-11.36	1.00 H	333	50.46	6.38

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5647.37	56.07 PK	68.20	-12.13	1.03 V	1	51.04	5.03
PK.2	#6022.62	56.69 PK	68.20	-11.51	1.03 V	1	50.30	6.39

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5580.40	55.34 PK	68.20	-12.86	1.02 H	332	50.51	4.83
PK.2	#5990.80	56.18 PK	68.20	-12.02	1.02 H	332	49.80	6.38

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 159	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5602.25	54.90 PK	68.20	-13.30	1.05 V	0	49.98	4.92
PK.2	#6010.27	56.16 PK	68.20	-12.04	1.05 V	0	49.77	6.39

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




802.11ac (VHT80)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5146.08	64.89 PK	74.00	-9.11	1.03 H	334	59.61	5.28
PK.2	5447.52	54.69 PK	74.00	-19.31	1.03 H	334	49.98	4.71
AV.1	5139.36	52.45 AV	54.00	-1.55	1.03 H	334	47.14	5.31
AV.2	5442.72	42.10 AV	54.00	-11.90	1.03 H	334	37.39	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5146.08	63.25 PK	74.00	-10.75	1.01 V	0	57.97	5.28
PK.2	5429.28	54.00 PK	74.00	-20.00	1.01 V	0	49.29	4.71
AV.1	5149.92	51.29 AV	54.00	-2.71	1.01 V	0	46.02	5.27
AV.2	5422.56	43.99 AV	54.00	-10.01	1.01 V	0	39.28	4.71

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 58	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5103.84	56.07 PK	74.00	-17.93	1.05 H	335	50.64	5.43
PK.2	5355.36	64.41 PK	74.00	-9.59	1.05 H	335	59.89	4.52
AV.1	5105.76	42.95 AV	54.00	-11.05	1.05 H	335	37.53	5.42
AV.2	5356.32	52.37 AV	54.00	-1.63	1.05 H	335	47.85	4.52

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 58	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	4500MHz ~ 5460MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5083.68	55.52 PK	74.00	-18.48	1.01 V	15	50.17	5.35
PK.2	5355.36	59.68 PK	74.00	-14.32	1.01 V	15	55.16	4.52
AV.1	5108.64	45.25 AV	54.00	-8.75	1.01 V	15	39.84	5.41
AV.2	5353.44	49.01 AV	54.00	-4.99	1.01 V	15	44.50	4.51

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 106	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5458.77	65.15 PK	74.00	-8.85	1.00 H	339	60.49	4.66
PK.2	#5466.37	66.22 PK	68.20	-1.98	1.00 H	339	61.59	4.63
AV.1	5457.82	52.45 AV	54.00	-1.55	1.00 H	339	47.79	4.66

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 106	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5454.50	61.91 PK	74.00	-12.09	1.03 V	0	57.23	4.68
PK.2	#5466.37	62.55 PK	68.20	-5.65	1.03 V	0	57.92	4.63
AV.1	5454.50	51.05 AV	54.00	-2.95	1.03 V	0	46.37	4.68

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 122	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5727.62	55.91 PK	68.20	-12.29	1.02 H	337	50.43	5.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 122	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5850MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5727.62	55.86 PK	68.20	-12.34	1.00 V	1	50.38	5.48

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 138	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5454.40	53.90 PK	74.00	-20.10	1.01 H	338	49.22	4.68
PK.2	#5932.60	55.54 PK	68.20	-12.66	1.01 H	338	49.28	6.26
AV.1	5458.00	43.36 AV	54.00	-10.64	1.01 H	338	38.70	4.66

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 138	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5350MHz ~ 5950MHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	5435.20	54.13 PK	74.00	-19.87	1.00 V	0	49.43	4.70
PK.2	#5900.80	56.19 PK	68.20	-12.01	1.00 V	0	49.90	6.29
AV.1	5459.80	43.38 AV	54.00	-10.62	1.00 V	0	38.73	4.65

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5600.82	56.49 PK	68.20	-11.71	1.01 H	336	51.58	4.91
PK.2	#6006.48	56.91 PK	68.20	-11.29	1.01 H	336	50.51	6.40

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.




CHANNEL	TX Channel 155	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	5550MHz ~ 6025MHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
PK.1	#5645.00	55.41 PK	68.20	-12.79	1.00 V	0	50.39	5.02
PK.2	#5996.02	55.93 PK	68.20	-12.27	1.00 V	0	49.55	6.38

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit
4. Margin value = Emission Level – Limit value
5. " # ": The radiated frequency is out of the restricted band.



4.1.9 Test Results for below 1GHz


802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	53.81	26.93 PK	40.00	-13.07	1.55 H	312	34.09	-7.16
2	117.78	23.25 PK	43.50	-20.25	2.03 H	312	32.91	-9.66
3	367.07	23.23 PK	46.00	-22.77	1.74 H	339	27.16	-3.93
4	479.64	26.52 PK	46.00	-19.48	1.58 H	334	28.07	-1.55
5	624.42	30.05 PK	46.00	-15.95	1.71 H	12	28.58	1.47
6	820.11	32.87 PK	46.00	-13.13	2.17 H	339	28.25	4.62

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report
6. The PK detector measurement value is much smaller than the limit QP value, so the pass is determined




CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	40.57	20.55 PK	40.00	-19.45	1.64 V	322	28.22	-7.67
2	143.15	19.56 PK	43.50	-23.94	1.30 V	360	26.92	-7.36
3	431.87	25.58 PK	46.00	-20.42	1.92 V	275	27.91	-2.33
4	563.16	27.92 PK	46.00	-18.08	1.52 V	332	28.07	-0.15
5	697.60	30.75 PK	46.00	-15.25	1.73 V	255	28.38	2.37
6	856.25	32.78 PK	46.00	-13.22	2.17 V	187	27.72	5.06

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report
6. The PK detector measurement value is much smaller than the limit QP value, so the pass is determined



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Sep. 03, 2018	Sep. 02, 2019
RF signal cable Woken	5D-FB	Cable-cond1-01	Sep. 05, 2018	Sep. 04, 2019
LISN ROHDE & SCHWARZ (EUT)	ENV216	101826	Feb. 26, 2018	Feb. 25, 2019
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 19, 2018	Aug. 18, 2019
Software ADT	BV ADT_Conc_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results

Worst-case data:


802.11a

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.19305	9.72	32.78	14.92	42.50	24.64	63.90	53.90	-21.40	-29.26
2	0.33377	9.74	26.20	4.44	35.94	14.18	59.36	49.36	-23.42	-35.18
3	0.51754	9.74	26.77	10.09	36.51	19.83	56.00	46.00	-19.49	-26.17
4	0.58792	9.73	26.08	8.50	35.81	18.23	56.00	46.00	-20.19	-27.77
5	0.92418	9.69	26.11	12.09	35.80	21.78	56.00	46.00	-20.20	-24.22
6	22.05773	9.95	19.39	4.38	29.34	14.33	60.00	50.00	-30.66	-35.67

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18508	9.73	33.62	16.59	43.35	26.32	64.25	54.25	-20.90	-27.93
2	0.25557	9.74	29.65	12.01	39.39	21.75	61.57	51.57	-22.18	-29.82
3	0.40586	9.75	29.87	15.30	39.62	25.05	57.73	47.73	-18.11	-22.68
4	0.50242	9.74	33.50	16.89	43.24	26.63	56.00	46.00	-12.76	-19.37
5	1.05069	9.72	31.05	16.71	40.77	26.43	56.00	46.00	-15.23	-19.57
6	17.15850	10.04	17.31	9.48	27.35	19.52	60.00	50.00	-32.65	-30.48

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Transmit Power Measurement

4.3.1 Limits of Transmit Power Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
		Fixed point-to-point Access Point	1 Watt (30 dBm)
		Indoor Access Point	1 Watt (30 dBm)
	✓	Mobile and Portable client device	250mW (24 dBm)
U-NII-2A		✓	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C		✓	250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3		✓	1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;


Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.3.2 Test Setup

For Power Output



For 26dB Bandwidth



4.3.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
USB Wideband Power Meter KEYSIGHT	U2021XA	MY55050005/MY55190004/MY55190007/MY55210005	Jul. 17, 2018	Jul. 16, 2019
SPECTRUM ANALYZER R&S	FSP40	100041	Dec 12, 2017	Dec 11, 2018

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.4 Test Procedure

For Average Power Measurement

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to average. Duty factor is not added to measured value.

For 26dB Bandwidth

- a. Set RBW = approximately 1% of the emission bandwidth.
- b. Set the VBW > RBW.
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

Power Output:

Ant. 0 (SISO)

802.11a

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
36	5180	54.325	17.35	24.00	Pass
40	5200	53.088	17.25	24.00	Pass
48	5240	53.456	17.28	24.00	Pass
52	5260	51.761	17.14	24.00	Pass
60	5300	52.481	17.20	24.00	Pass
64	5320	52.602	17.21	24.00	Pass
100	5500	53.951	17.32	24.00	Pass
116	5580	51.286	17.10	24.00	Pass
140	5700	52.000	17.16	24.00	Pass
144	5720 (For U-NII-2C)	31.696	15.01	23.31	Pass
144	5720 (For U-NII-3)	5.984	7.77	30.00	Pass
149	5745	53.088	17.25	30.00	Pass
157	5785	51.404	17.11	30.00	Pass
165	5825	53.456	17.28	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(24.36) = 24.86 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.26) = 24.84 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(24.02) = 24.80 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(24.88) = 24.95 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(25.08) = 24.99 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(24.50) = 24.89 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5707.96) = 23.31 < 24\text{dBm}$

802.11ac (VHT20)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
36	5180	54.828	17.39	24.00	Pass
40	5200	53.580	17.29	24.00	Pass
48	5240	53.951	17.32	24.00	Pass
52	5260	52.845	17.23	24.00	Pass
60	5300	53.333	17.27	24.00	Pass
64	5320	52.481	17.20	24.00	Pass
100	5500	55.208	17.42	24.00	Pass
116	5580	52.119	17.17	24.00	Pass
140	5700	54.075	17.33	24.00	Pass
144	5720 (For U-NII-2C)	29.785	14.74	23.60	Pass
144	5720 (For U-NII-3)	8.110	9.09	30.00	Pass
149	5745	54.450	17.36	30.00	Pass
157	5785	52.360	17.19	30.00	Pass
165	5825	54.325	17.35	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(25.19) = 25.01 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.86) = 24.95 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.59) = 25.08 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(25.52) = 25.06 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(26.51) = 25.23 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(26.48) = 25.22 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5706.79) = 23.60 < 24\text{dBm}$

802.11ac (VHT40)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
38	5190	54.702	17.38	24.00	Pass
46	5230	52.602	17.21	24.00	Pass
54	5270	53.951	17.32	24.00	Pass
62	5310	53.333	17.27	24.00	Pass
102	5510	52.119	17.17	24.00	Pass
110	5550	52.966	17.24	24.00	Pass
134	5670	53.703	17.30	24.00	Pass
142	5710 (For U-NII-2C)	23.227	13.66	24.00	Pass
142	5710 (For U-NII-3)	1.690	2.28	30.00	Pass
151	5755	53.211	17.26	30.00	Pass
159	5795	53.703	17.30	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(42.21) = 27.25 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(42.46) = 27.27 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(42.25) = 27.25 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(5725.00 - 5688.90) = 26.57 > 24\text{dBm}$

802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
42	5210	53.703	17.30	24.00	Pass
58	5290	52.360	17.19	24.00	Pass
106	5530	53.703	17.30	24.00	Pass
122	5610	53.088	17.25	24.00	Pass
138	5690 (For U-NII-2C)	20.845	13.19	24.00	Pass
138	5690 (For U-NII-3)	0.822	-0.85	30.00	Pass
155	5775	53.333	17.27	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(83.95) = 30.24 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(84.30) = 30.25 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(98.89) = 30.95 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(5725.00 - 5647.91) = 29.87 > 24\text{dBm}$

Ant. 1 (SISO)

802.11a

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
36	5180	52.240	17.18	24.00	Pass
40	5200	52.000	17.16	24.00	Pass
48	5240	51.880	17.15	24.00	Pass
52	5260	50.933	17.07	24.00	Pass
60	5300	51.286	17.10	24.00	Pass
64	5320	53.211	17.26	24.00	Pass
100	5500	53.211	17.26	24.00	Pass
116	5580	52.602	17.21	24.00	Pass
140	5700	54.200	17.34	24.00	Pass
144	5720 (For U-NII-2C)	33.343	15.23	23.36	Pass
144	5720 (For U-NII-3)	6.412	8.07	30.00	Pass
149	5745	53.703	17.30	30.00	Pass
157	5785	52.723	17.22	30.00	Pass
165	5825	53.827	17.31	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(24.29) = 24.85 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.06) = 24.81 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.34) = 25.03 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(25.94) = 25.13 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(26.31) = 25.20 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(25.50) = 25.06 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5707.76) = 23.36 < 24\text{dBm}$

802.11ac (VHT20)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
36	5180	52.240	17.18	24.00	Pass
40	5200	52.845	17.23	24.00	Pass
48	5240	52.240	17.18	24.00	Pass
52	5260	52.240	17.18	24.00	Pass
60	5300	51.404	17.11	24.00	Pass
64	5320	54.450	17.36	24.00	Pass
100	5500	53.827	17.31	24.00	Pass
116	5580	52.119	17.17	24.00	Pass
140	5700	55.335	17.43	24.00	Pass
144	5720 (For U-NII-2C)	28.249	14.51	23.57	Pass
144	5720 (For U-NII-3)	4.864	6.87	30.00	Pass
149	5745	54.200	17.34	30.00	Pass
157	5785	53.456	17.28	30.00	Pass
165	5825	54.200	17.34	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(25.85) = 25.12 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(25.96) = 25.14 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.97) = 25.14 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(26.92) = 25.30 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(28.98) = 25.62 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(27.91) = 25.45 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5706.90) = 23.57 < 24\text{dBm}$

802.11ac (VHT40)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
38	5190	51.404	17.11	24.00	Pass
46	5230	51.642	17.13	24.00	Pass
54	5270	51.642	17.13	24.00	Pass
62	5310	52.000	17.16	24.00	Pass
102	5510	52.602	17.21	24.00	Pass
110	5550	51.286	17.10	24.00	Pass
134	5670	52.602	17.21	24.00	Pass
142	5710 (For U-NII-2C)	34.198	15.34	24.00	Pass
142	5710 (For U-NII-3)	2.046	3.11	30.00	Pass
151	5755	53.456	17.28	30.00	Pass
159	5795	51.050	17.08	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(42.38) = 27.27 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(50.27) = 28.01 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(57.67) = 28.60 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(62.83) = 28.98 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(5725.00 - 5685.39) = 26.97 > 24\text{dBm}$

802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (mW)	Maximum Conducted Power (dBm)	Power Limit (dBm)	Pass / Fail
42	5210	51.286	17.10	24.00	Pass
58	5290	52.000	17.16	24.00	Pass
106	5530	51.286	17.10	24.00	Pass
122	5610	51.168	17.09	24.00	Pass
138	5690 (For U-NII-2C)	24.660	13.92	24.00	Pass
138	5690 (For U-NII-3)	0.957	-0.19	30.00	Pass
155	5775	54.576	17.37	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

1. $11\text{dBm} + 10\log(83.79) = 30.23 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(99.22) = 30.96 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(112.51) = 31.51 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(5725.00 - 5635.27) = 30.53 > 24\text{dBm}$

Ant. 0 + 1 (MIMO)

802.11a

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	17.42	17.23	108.053	20.34	24.00	Pass
40	5200	17.27	17.22	106.056	20.26	24.00	Pass
48	5240	17.33	17.22	106.798	20.29	24.00	Pass
52	5260	17.22	17.16	104.723	20.20	24.00	Pass
60	5300	17.29	17.17	105.699	20.24	24.00	Pass
64	5320	17.24	17.35	107.291	20.31	24.00	Pass
100	5500	17.41	17.29	108.661	20.36	24.00	Pass
116	5580	17.17	17.23	104.964	20.21	24.00	Pass
140	5700	17.25	17.41	108.169	20.34	24.00	Pass
144	5720 (For U-NII-2C)	15.01	15.23	66.488	18.23	23.31	Pass
144	5720 (For U-NII-3)	7.77	8.07	12.672	11.03	30.00	Pass
149	5745	17.27	17.33	107.408	20.31	30.00	Pass
157	5785	17.20	17.29	106.061	20.26	30.00	Pass
165	5825	17.30	17.34	107.903	20.33	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11\text{dBm} + 10\log(24.36) = 24.86 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.26) = 24.84 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(24.02) = 24.80 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(24.88) = 24.95 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(25.08) = 24.99 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(24.50) = 24.89 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5707.96) = 23.31 < 24\text{dBm}$

Chain 1

1. $11\text{dBm} + 10\log(24.29) = 24.85 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.06) = 24.81 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.34) = 25.03 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(25.94) = 25.13 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(26.31) = 25.20 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(25.50) = 25.06 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5707.76) = 23.36 < 24\text{dBm}$

802.11ac (VHT20)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	17.45	17.25	108.678	20.36	24.00	Pass
40	5200	17.32	17.26	107.162	20.30	24.00	Pass
48	5240	17.38	17.24	107.668	20.32	24.00	Pass
52	5260	17.27	17.25	106.421	20.27	24.00	Pass
60	5300	17.34	17.21	106.802	20.29	24.00	Pass
64	5320	17.26	17.37	107.787	20.33	24.00	Pass
100	5500	17.43	17.38	110.037	20.42	24.00	Pass
116	5580	17.27	17.26	106.544	20.28	24.00	Pass
140	5700	17.34	17.45	109.790	20.41	24.00	Pass
144	5720 (For U-NII-2C)	14.74	14.51	59.886	17.77	23.57	Pass
144	5720 (For U-NII-3)	9.09	6.87	13.388	11.27	30.00	Pass
149	5745	17.37	17.37	109.152	20.38	30.00	Pass
157	5785	17.45	17.35	109.915	20.41	30.00	Pass
165	5825	17.38	17.38	109.404	20.39	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11\text{dBm} + 10\log(25.19) = 25.01 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(24.86) = 24.95 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.59) = 25.08 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(25.52) = 25.06 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(26.51) = 25.23 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(26.48) = 25.22 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5706.79) = 23.60 < 24\text{dBm}$

Chain 1

1. $11\text{dBm} + 10\log(25.85) = 25.12 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(25.96) = 25.14 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(25.97) = 25.14 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(26.92) = 25.30 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(28.98) = 25.62 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(27.91) = 25.45 > 24\text{dBm}$
7. $11\text{dBm} + 10\log(5725.00 - 5706.90) = 23.57 < 24\text{dBm}$

802.11ac (VHT40)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	17.44	17.17	107.582	20.32	24.00	Pass
46	5230	17.28	17.20	105.937	20.25	24.00	Pass
54	5270	17.41	17.17	107.200	20.30	24.00	Pass
62	5310	17.32	17.22	106.674	20.28	24.00	Pass
102	5510	17.20	17.23	105.326	20.23	24.00	Pass
110	5550	17.26	17.17	105.330	20.23	24.00	Pass
134	5670	17.37	17.30	108.279	20.35	24.00	Pass
142	5710 (For U-NII-2C)	13.66	15.34	59.979	17.78	24.00	Pass
142	5710 (For U-NII-3)	2.28	3.11	3.902	5.91	30.00	Pass
151	5755	17.29	17.31	107.407	20.31	30.00	Pass
159	5795	17.35	17.14	106.086	20.26	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11\text{dBm} + 10\log(42.07) = 27.23 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(42.21) = 27.25 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(42.27) = 27.26 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(42.46) = 27.27 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(42.25) = 27.25 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(5725.00 - 5688.90) = 26.57 > 24\text{dBm}$

Chain 1

1. $11\text{dBm} + 10\log(42.29) = 27.26 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(42.38) = 27.27 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(50.27) = 28.01 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(57.67) = 28.60 > 24\text{dBm}$
5. $11\text{dBm} + 10\log(62.83) = 28.98 > 24\text{dBm}$
6. $11\text{dBm} + 10\log(5725.00 - 5685.39) = 26.97 > 24\text{dBm}$

802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	17.35	17.15	106.205	20.26	24.00	Pass
58	5290	17.27	17.22	106.056	20.26	24.00	Pass
106	5530	17.39	17.16	106.828	20.29	24.00	Pass
122	5610	17.29	17.17	105.699	20.24	24.00	Pass
138	5690 (For U-NII-2C)	13.19	13.92	49.305	16.93	24.00	Pass
138	5690 (For U-NII-3)	-0.85	-0.19	1.928	2.85	30.00	Pass
155	5775	17.36	17.39	109.278	20.39	30.00	Pass

Note:

For U-NII-2A, U-NII-2C Band:

Chain 0

1. $11\text{dBm} + 10\log(83.95) = 30.24 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(84.30) = 30.25 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(98.89) = 30.95 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(5725.00 - 5647.91) = 29.87 > 24\text{dBm}$

Chain 1

1. $11\text{dBm} + 10\log(83.79) = 30.23 > 24\text{dBm}$
2. $11\text{dBm} + 10\log(99.22) = 30.96 > 24\text{dBm}$
3. $11\text{dBm} + 10\log(112.51) = 31.51 > 24\text{dBm}$
4. $11\text{dBm} + 10\log(5725.00 - 5635.27) = 30.53 > 24\text{dBm}$

26dB Bandwidth:

802.11a

Chan.	Freq. (MHz)	26dBc Bandwidth (MHz)	
		Chain 0	Chain 1
52	5260	24.36	24.29
60	5300	24.26	24.06
64	5320	24.02	25.34
100	5500	24.88	25.94
116	5580	25.08	26.31
140	5700	24.50	25.50
144	5720 (For U-NII-2C)	17.04	17.24
144	5720 (For U-NII-3)	7.29	7.60

802.11ac (VHT20)

Chan.	Freq. (MHz)	26dBc Bandwidth (MHz)	
		Chain 0	Chain 1
52	5260	25.19	25.85
60	5300	24.86	25.96
64	5320	25.59	25.97
100	5500	25.52	26.92
116	5580	26.51	28.98
140	5700	26.48	27.91
144	5720 (For U-NII-2C)	18.21	18.10
144	5720 (For U-NII-3)	7.98	8.88


802.11ac (VHT40)

Chan.	Freq. (MHz)	26dBc Bandwidth (MHz)	
		Chain 0	Chain 1
54	5270	42.07	42.29
62	5310	42.21	42.38
102	5510	42.27	50.27
110	5550	42.46	57.67
134	5670	42.25	62.83
142	5710 (For U-NII-2C)	36.10	39.61
142	5710 (For U-NII-3)	5.95	20.00

802.11ac (VHT80)

Chan.	Freq. (MHz)	26dBc Bandwidth (MHz)	
		Chain 0	Chain 1
58	5290	83.95	83.79
106	5530	84.30	99.22
122	5610	98.89	112.51
138	5690 (For U-NII-2C)	77.09	89.73
138	5690 (For U-NII-3)	6.70	21.32

Spectrum Plot of Worst Value



EUT Maximum Conducted Power

802.11a

Frequency Band (MHz)	Max. Power	
	Output Power (mW)	Output Power (dBm)
5250~5350	107.291	20.31
5470~5725	108.661	20.36

802.11ac (VHT20)

Frequency Band (MHz)	Max. Power	
	Output Power (mW)	Output Power (dBm)
5250~5350	107.787	20.33
5470~5725	110.037	20.42

802.11ac (VHT40)


Frequency Band (MHz)	Max. Power	
	Output Power (mW)	Output Power (dBm)
5250~5350	107.200	20.30
5470~5725	108.279	20.35

802.11ac (VHT80)

Frequency Band (MHz)	Max. Power	
	Output Power (mW)	Output Power (dBm)
5250~5350	106.056	20.26
5470~5725	106.828	20.29

4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.4.4 Test Result

802.11a

Chan.	Freq. (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	16.80	16.80
40	5200	16.80	16.80
48	5240	16.80	16.80
52	5260	16.80	16.80
60	5300	16.92	16.80
64	5320	16.92	16.80
100	5500	16.92	16.92
116	5580	16.92	17.04
140	5700	16.92	16.92
144	5720 (For U-NII-2C)	13.28	13.40
144	5720 (For U-NII-3)	3.16	3.28
149	5745	16.92	17.04
157	5785	16.92	17.04
165	5825	16.86	16.92

802.11ac (VHT20)


Chan.	Freq. (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	18.00	18.00
40	5200	18.00	18.00
48	5240	18.00	18.00
52	5260	18.00	18.00
60	5300	18.00	18.00
64	5320	18.00	18.00
100	5500	18.12	18.00
116	5580	18.12	18.12
140	5700	18.24	18.12
144	5720 (For U-NII-2C)	14.00	14.00
144	5720 (For U-NII-3)	3.76	3.88
149	5745	18.00	18.12
157	5785	18.12	18.12
165	5825	18.00	18.00

802.11ac (VHT40)

Chan.	Freq. (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
38	5190	36.48	36.48
46	5230	36.48	36.48
54	5270	36.60	36.48
62	5310	36.48	36.48
102	5510	36.60	36.72
110	5550	36.72	36.84
134	5670	36.60	36.72
142	5710 (For U-NII-2C)	33.36	33.36
142	5710 (For U-NII-3)	3.24	3.48
151	5755	36.48	36.84
159	5795	36.48	36.96

802.11ac (VHT80)

Chan.	Freq. (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
42	5210	75.84	75.84
58	5290	75.84	75.84
106	5530	75.60	75.84
122	5610	75.60	76.08
138	5690 (For U-NII-2C)	72.92	72.92
138	5690 (For U-NII-3)	2.92	2.92
155	5775	75.84	76.08




4.5 Peak Power Spectral Density Measurement

4.5.1 Limits of Peak Power Spectral Density Measurement

Operation Band	EUT Category		Limit
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
		Indoor Access Point	
	√	Mobile and Portable client device	11dBm/ MHz
U-NII-2A	√		11dBm/ MHz
U-NII-2C	√		11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

4.5.2 Test Setup



4.5.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
SPECTRUM ANALYZER R&S	FSP40	100041	Dec 12, 2017	Dec 11, 2018

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.4 Test Procedures

For U-NII-1, U-NII-2A and U-NII-2C band:

Using method SA-2

- a. Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b. Set RBW = 1MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- c. Set Channel power measure = 1MHz
- d. Sweep time = auto, trigger set to "free run".
- e. Trace average at least 100 traces in power averaging mode.
- f. Record the max value and add 10 log (1/duty cycle)

For U-NII-3 band:

- a. Set span to encompass the entire emission bandwidth (EBW) of the signal.
- b. Set RBW = 300 kHz, Set VBW $\geq$ 1 MHz, Detector = RMS
- c. Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
- d. Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500 \text{ kHz} / 300 \text{ kHz})$
- e. Sweep time = auto, trigger set to "free run".
- f. Trace average at least 100 traces in power averaging mode.
- g. Record the max value and add 10 log (1/duty cycle)

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

Same as 4.3.6.

4.5.7 Test Results

For U-NII-1, U-NII-2A and U-NII-2C band:

802.11a

Chan.	Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
36	5180	4.15	4.26	0.10	7.32	11.00	Pass
40	5200	4.46	4.39	0.10	7.54	11.00	Pass
48	5240	4.41	4.43	0.10	7.53	11.00	Pass
52	5260	4.31	4.39	0.10	7.46	11.00	Pass
60	5300	4.39	4.38	0.10	7.50	11.00	Pass
64	5320	4.46	4.45	0.10	7.57	11.00	Pass
100	5500	5.05	5.24	0.10	8.26	11.00	Pass
116	5580	5.50	5.57	0.10	8.65	11.00	Pass
140	5700	5.16	5.13	0.10	8.26	11.00	Pass
144	5720	4.67	4.65	0.10	7.77	11.00	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- U-NII-1 Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.87\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2A Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.48\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2C Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.50\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT20)

Chan.	Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
36	5180	4.05	4.47	0.14	7.42	11.00	Pass
40	5200	4.13	4.54	0.14	7.49	11.00	Pass
48	5240	4.23	4.20	0.14	7.37	11.00	Pass
52	5260	4.28	4.04	0.14	7.31	11.00	Pass
60	5300	4.23	4.18	0.14	7.36	11.00	Pass
64	5320	4.23	4.22	0.14	7.38	11.00	Pass
100	5500	4.39	4.40	0.14	7.55	11.00	Pass
116	5580	5.00	4.63	0.14	7.97	11.00	Pass
140	5700	4.17	4.32	0.14	7.40	11.00	Pass
144	5720	4.81	4.39	0.14	7.76	11.00	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- U-NII-1 Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.87\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
 U-NII-2A Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.48\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
 U-NII-2C Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.50\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT40)

Chan.	Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
38	5190	0.74	0.57	0.19	3.86	11.00	Pass
46	5230	1.19	0.08	0.19	3.87	11.00	Pass
54	5270	0.99	0.24	0.19	3.83	11.00	Pass
62	5310	1.42	0.71	0.19	4.28	11.00	Pass
102	5510	1.47	0.79	0.19	4.34	11.00	Pass
110	5550	1.36	1.28	0.19	4.52	11.00	Pass
134	5670	1.37	0.91	0.19	4.35	11.00	Pass
142	5710	1.28	1.02	0.19	4.35	11.00	Pass

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- U-NII-1 Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.87\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2A Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.48\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2C Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.50\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT80)


Chan.	Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD with Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
42	5210	-2.68	-3.13	0.35	0.46	11.00	Pass
58	5290	-2.55	-2.90	0.35	0.64	11.00	Pass
106	5530	-1.31	-1.10	0.35	2.16	11.00	Pass
122	5610	-1.56	-1.04	0.35	2.07	11.00	Pass
138	5690	-2.12	-1.38	0.35	1.63	11.00	Pass

Note:


- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- U-NII-1 Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.87\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2A Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 1.48\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
U-NII-2C Band: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.50\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
- Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a / Chain 1 / CH 116




802.11ac (VHT20) / Chain 0 / CH 116



802.11ac (VHT40) / Chain 0 / CH 102



802.11ac (VHT80) / Chain 1 / 122



For U-NII-3 band:

802.11a

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	144	5720	-5.44	-3.22	3.01	0.10	-0.11	30.00	Pass
	149	5745	-2.76	-0.54	3.01	0.10	2.57	30.00	Pass
	157	5785	-2.30	-0.08	3.01	0.10	3.03	30.00	Pass
	165	5825	-2.61	-0.39	3.01	0.10	2.72	30.00	Pass
1	144	5720	-5.42	-3.20	3.01	0.10	-0.09	30.00	Pass
	149	5745	-2.66	-0.44	3.01	0.10	2.67	30.00	Pass
	157	5785	-2.84	-0.62	3.01	0.10	2.49	30.00	Pass
	165	5825	-3.46	-1.24	3.01	0.10	1.87	30.00	Pass

Note:

1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.11\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT20)

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	144	5720	-5.19	-2.97	3.01	0.14	0.18	30.00	Pass
	149	5745	-2.97	-0.75	3.01	0.14	2.40	30.00	Pass
	157	5785	-2.71	-0.49	3.01	0.14	2.66	30.00	Pass
	165	5825	-2.56	-0.34	3.01	0.14	2.81	30.00	Pass
1	144	5720	-5.68	-3.46	3.01	0.14	-0.31	30.00	Pass
	149	5745	-3.49	-1.27	3.01	0.14	1.88	30.00	Pass
	157	5785	-3.26	-1.04	3.01	0.14	2.11	30.00	Pass
	165	5825	-3.37	-1.15	3.01	0.14	2.00	30.00	Pass

Note:

1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.11\text{dBi} < 6\text{dBi}$, so the power density limit no need to reduce.
2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT40)

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	142	5710	-9.21	-6.99	3.01	0.19	-3.79	30.00	Pass
	151	5755	-7.15	-4.93	3.01	0.19	-1.73	30.00	Pass
	159	5795	-6.35	-4.13	3.01	0.19	-0.93	30.00	Pass
1	142	5710	-9.55	-7.33	3.01	0.19	-4.13	30.00	Pass
	151	5755	-7.42	-5.20	3.01	0.19	-2.00	30.00	Pass
	159	5795	-7.43	-5.21	3.01	0.19	-2.01	30.00	Pass

Note:

1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.11 \text{dBi} < 6 \text{dBi}$, so the power density limit no need to reduce.
2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ac (VHT80)


TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=2) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	138	5690	-12.95	-10.73	3.01	0.35	-7.37	30.00	Pass
	155	5775	-9.20	-6.98	3.01	0.35	-3.62	30.00	Pass
1	138	5690	-12.34	-10.12	3.01	0.35	-6.76	30.00	Pass
	155	5775	-9.90	-7.68	3.01	0.35	-4.32	30.00	Pass

Note:


1. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 0.11 \text{dBi} < 6 \text{dBi}$, so the power density limit no need to reduce.
2. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a




802.11ac (VHT20)



802.11ac (VHT40)



802.11ac (VHT80)




4.6 Frequency Stability

4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

4.6.2 Test Setup



4.6.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jun. 11, 2018	Jun. 10, 2019
WIT Standard Temperature And Humidity Chamber	TH-4S-C	W981030	Jun. 04, 2018	Jun. 03, 2019
Digital Multimeter Fluke	87-III	70360742	Jun. 29, 2018	Jun. 28, 2019
DC Power Supply Topward	6603D	700637	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

Frequency Stability Versus Temp.									
Operating Frequency: 5180MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result
55	3.85	5179.9799	Pass	5179.9821	Pass	5179.9806	Pass	5179.9788	Pass
50	3.85	5180.0137	Pass	5180.0164	Pass	5180.0133	Pass	5180.0131	Pass
40	3.85	5180.012	Pass	5180.0134	Pass	5180.0164	Pass	5180.0127	Pass
30	3.85	5180.0149	Pass	5180.0177	Pass	5180.0148	Pass	5180.0143	Pass
20	3.85	5179.9992	Pass	5179.9977	Pass	5179.9999	Pass	5179.999	Pass
10	3.85	5180.0021	Pass	5180.0007	Pass	5180.0015	Pass	5179.9988	Pass
0	3.85	5180.0149	Pass	5180.0159	Pass	5180.017	Pass	5180.0177	Pass
-10	3.85	5180.0016	Pass	5180.0021	Pass	5180.0045	Pass	5180.0036	Pass


Frequency Stability Versus Voltage									
Operating Frequency: 5180MHz									
Temp. (°C)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result	Measured Frequency (MHz)	Result
20	4.4	5180.0146	Pass	5180.0179	Pass	5180.0146	Pass	5180.0135	Pass
	3.85	5180.0149	Pass	5180.0177	Pass	5180.0148	Pass	5180.0143	Pass
	3.6	5180.0151	Pass	5180.0185	Pass	5180.0138	Pass	5180.0145	Pass

4.7 6dB Bandwidth Measurement

4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

802.11a

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
144 (For U-NII-3)	5720	2.58	2.90	0.5	Pass
149	5745	15.39	15.72	0.5	Pass
157	5785	15.21	16.09	0.5	Pass
165	5825	15.80	15.22	0.5	Pass

802.11ac (VHT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
144 (For U-NII-3)	5720	3.12	2.57	0.5	Pass
149	5745	16.01	15.99	0.5	Pass
157	5785	15.19	16.54	0.5	Pass
165	5825	16.53	16.04	0.5	Pass

802.11ac (VHT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
142 (For U-NII-3)	5710	2.67	2.67	0.5	Pass
151	5755	35.53	35.34	0.5	Pass
159	5795	35.58	35.40	0.5	Pass

802.11ac (VHT80)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
138 (For U-NII-3)	5690	2.69	2.66	0.5	Pass
155	5775	75.37	75.35	0.5	Pass

Spectrum Plot of Worst Value


802.11a




802.11ac (VHT20)



802.11ac (VHT40)



802.11ac (VHT80)



Note:

For CH144 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

For CH142 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

For CH138 (UNII-3 Band): The 6dB bandwidth above 5725MHz = Marker 1 + Delta 2 - 5725MHz

4.8 Automatically Discontinue Transmission

4.8.1 Limit of Automatically Discontinue Transmission

FCC 15.407(c) states: The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

Data transmission is always initiated by software, which is then pass down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets (ACKs, CTS, PSpoll, etc...) are initiated by the MAC. There are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets are being transmitted.

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Result

While the EUT is not transmitting any information, the EUT does automatically discontinue transmission and become standby mode for power saving. The EUT does detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---