




FCC CO-LOCATION RADIO TEST REPORT

FCC ID : A4RG1KAW
Equipment : Wireless Device
Model Name : G1KAW
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Mar. 10, 2025 and testing was performed from Mar. 14, 2025 to Mar. 28, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Connection Diagram of Test System.....	7
2.3 Support Unit used in test configuration and system	7
2.4 EUT Operation Test Setup	8
3 Test Result	9
3.1 Unwanted Emissions Measurement	9
3.2 Antenna Requirements	14
4 List of Measuring Equipment.....	15
5 Measurement Uncertainty	16
Appendix A. Radiated Spurious Emission Test Data	
Appendix B. Duty Cycle Plots	
Appendix C. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4D1914I	01	Initial issue of report	Apr. 10, 2025
FR4D1914I	02	Revise Antenna Gain and Section 2 This report is an updated version, replacing the report issued on Apr. 10, 2025.	Apr. 15, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(d) 15.407(b)	Unwanted Emissions	Pass	-
3.2	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Dara Chiu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs LTE/NTN, Bluetooth, BLE, BLE ASK, BLE GFSK, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, UWB, 60GHz, and GNSS.
Antenna Type WWAN: <Ant. 1> : PIFA Antenna <Ant. 2> : PIFA Antenna UWB: PIFA Antenna Bluetooth: PIFA Antenna WLAN: PIFA Antenna

EUT Information List	
S/N	Performed Test Item
51161WRBNL31R4	Radiated Spurious Emission

Antenna information		
LTE Band 7	Peak Gain (dBi)	-7.5
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	-5.4
5470 MHz ~ 5725 MHz	Peak Gain (dBi)	0.1
6489.6 MHz	Peak Gain (dBi)	-0.5

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH23-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.


2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Y plane with Adapter as worst plane.

2.1 Carrier Frequency and Channel

The detailed test modes are shown in Appendix A.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	N/A	N/A	N/A	N/A



2.4 EUT Operation Test Setup

The RF test items, utility "CMD Version 10.0.22631.5039" were installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.1.1 Limit of Unwanted Emissions

<For 2402 MHz ~ 2480 MHz>

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

<For 5150 MHz ~ 5250 MHz>

For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(2) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

- The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
- The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.


4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.1.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.1.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.1.7 Duty Cycle

Please refer to Appendix B.

3.1.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix A.



3.2 Antenna Requirements

3.2.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.2.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

(3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug 29, 2024	Mar. 14, 2025~ Mar. 28, 2025	Aug 28, 2025	Radiation (03CH23-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	62028 & 003	30MHz~1GHz	Nov. 27, 2024	Mar. 14, 2025~ Mar. 28, 2025	Nov. 26, 2025	Radiation (03CH23-HY)
Amplifier	SONOMA	310N	421582	9kHz~1GHz	Jul. 14, 2024	Mar. 14, 2025~ Mar. 28, 2025	Jul. 13, 2025	Radiation (03CH23-HY)
Amplifier	EMEC	EM01G18GA	060878	N/A	Sep. 27, 2024	Mar. 14, 2025~ Mar. 28, 2025	Sep. 26, 2025	Radiation (03CH23-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C05A18E N	1GHz~18GHz	Jun. 20, 2024	Mar. 14, 2025~ Mar. 28, 2025	Jun. 19, 2025	Radiation (03CH23-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz~40GHz	Jun. 24, 2024	Mar. 14, 2025~ Mar. 28, 2025	Jun. 23, 2025	Radiation (03CH23-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Sep. 02, 2024	Mar. 14, 2025~ Mar. 28, 2025	Sep. 01, 2025	Radiation (03CH23-HY)
Signal Analyzer	Keysight	N9010B	MY62170337	N/A	Aug. 21, 2024	Mar. 14, 2025~ Mar. 28, 2025	Aug. 20, 2025	Radiation (03CH23-HY)
Hygrometer	TECPEL	DTM-303B	TP211542	N/A	Oct. 21, 2024	Mar. 14, 2025~ Mar. 28, 2025	Oct. 20, 2025	Radiation (03CH23-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Mar. 14, 2025~ Mar. 28, 2025	N/A	Radiation (03CH23-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 14, 2025~ Mar. 28, 2025	N/A	Radiation (03CH23-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 14, 2025~ Mar. 28, 2025	N/A	Radiation (03CH23-HY)
Software	Audix	E3 6.09824_2019122	RK-002348	N/A	N/A	Mar. 14, 2025~ Mar. 28, 2025	N/A	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Mar. 14, 2025~ Mar. 28, 2025	Mar. 04, 2026	Radiation (03CH23-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804395/2	N/A	Nov. 26, 2024	Mar. 14, 2025~ Mar. 28, 2025	Nov. 25, 2025	Radiation (03CH23-HY)
RF Cable	EMC	EMC101Y	231115/231119/231122	N/A	Nov. 26, 2024	Mar. 14, 2025~ Mar. 28, 2025	Nov. 25, 2025	Radiation (03CH23-HY)



5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.60 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.40 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.80 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.70 dB
---	---------

Appendix A. Radiated Spurious Emission Test Data

Test Engineer :	Leo Li, Karl Hou, and Lucifer Jiang	Temperature :	21.7 ~ 22.5°C
		Relative Humidity :	51 ~ 57%

Note symbol

-L	Low channel location
-R	High channel location





A1. Radiated Spurious Emission Test Modes

Mode	Antenna	Mode	Remark
Mode 1	1	Bluetooth LE GFSK 2Mbps Ch38	-
	1	LTE Band 7 (BW20M 1RB0 QPSK Ch21100)	-
Mode 2	1	11ax HE20 Full RU Ch11	-
	1	LTE Band 7 (BW20M 1RB0 QPSK Ch21100)	-
	1	UWB Ch05 (BPRF10 SP3 STS1 0)	-
Mode 3	1	Bluetooth LE GFSK 2Mbps Ch38	-
	1	11a Ch100	-
	1	LTE Band 7 (BW20M 1RB0 QPSK Ch21100)	-



A2. Summary of each worse mode

Mode	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	2498.74	46.68	54.00	-7.32	H	Avg.	Pass	-
2	33.88	32.58	40.00	-7.42	V	Peak	Pass	-
3	5469.4	65.79	54.00	-2.41	V	Peak	Pass	-







Mode	1																																																																																	
	Band Edge - L																																																																																	
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																	
ANT	1																																																																																	
Pol.	Horizontal						Fundamental																																																																											
Peak																																																																																		
	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto						Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto																																																																											
Avg																																																																																		
	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto						Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto																																																																											
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2382.15</td><td>50.47</td><td>74.00</td><td>-23.53</td><td>37.95</td><td>26.90</td><td>7.20</td><td>31.96</td><td>10.38</td><td>119</td><td>116</td><td>Peak</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2382.15	50.47	74.00	-23.53	37.95	26.90	7.20	31.96	10.38	119	116	Peak																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																								
1	2382.15	50.47	74.00	-23.53	37.95	26.90	7.20	31.96	10.38	119	116	Peak																																																																						
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>94.83</td><td>-----</td><td>-----</td><td>82.27</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>119</td><td>116</td><td>Peak</td></tr><tr><td>2</td><td>2526.00</td><td>88.77</td><td>-----</td><td>-----</td><td>76.13</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>119</td><td>116</td><td>Peak</td></tr><tr><td>3</td><td>2648.00</td><td>60.80</td><td>-----</td><td>-----</td><td>47.46</td><td>27.40</td><td>7.57</td><td>32.04</td><td>10.41</td><td>119</td><td>116</td><td>Peak</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	94.83	-----	-----	82.27	26.90	7.28	32.00	10.38	119	116	Peak	2	2526.00	88.77	-----	-----	76.13	26.90	7.39	32.04	10.39	119	116	Peak	3	2648.00	60.80	-----	-----	47.46	27.40	7.57	32.04	10.41	119	116	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																								
1	2440.00	94.83	-----	-----	82.27	26.90	7.28	32.00	10.38	119	116	Peak																																																																						
2	2526.00	88.77	-----	-----	76.13	26.90	7.39	32.04	10.39	119	116	Peak																																																																						
3	2648.00	60.80	-----	-----	47.46	27.40	7.57	32.04	10.41	119	116	Peak																																																																						
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2328.46</td><td>46.13</td><td>54.00</td><td>-7.87</td><td>33.26</td><td>27.30</td><td>7.12</td><td>31.92</td><td>10.37</td><td>119</td><td>116</td><td>Average</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2328.46	46.13	54.00	-7.87	33.26	27.30	7.12	31.92	10.37	119	116	Average																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																								
1	2328.46	46.13	54.00	-7.87	33.26	27.30	7.12	31.92	10.37	119	116	Average																																																																						
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>93.40</td><td>-----</td><td>-----</td><td>80.84</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>119</td><td>116</td><td>Average</td></tr><tr><td>2</td><td>2526.00</td><td>86.95</td><td>-----</td><td>-----</td><td>74.31</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>119</td><td>116</td><td>Average</td></tr><tr><td>3</td><td>2648.00</td><td>55.22</td><td>-----</td><td>-----</td><td>41.88</td><td>27.40</td><td>7.57</td><td>32.04</td><td>10.41</td><td>119</td><td>116</td><td>Average</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	93.40	-----	-----	80.84	26.90	7.28	32.00	10.38	119	116	Average	2	2526.00	86.95	-----	-----	74.31	26.90	7.39	32.04	10.39	119	116	Average	3	2648.00	55.22	-----	-----	41.88	27.40	7.57	32.04	10.41	119	116	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																								
1	2440.00	93.40	-----	-----	80.84	26.90	7.28	32.00	10.38	119	116	Average																																																																						
2	2526.00	86.95	-----	-----	74.31	26.90	7.39	32.04	10.39	119	116	Average																																																																						
3	2648.00	55.22	-----	-----	41.88	27.40	7.57	32.04	10.41	119	116	Average																																																																						





Mode	1																																								
	Band Edge - R																																								
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																								
ANT	1																																								
Pol.	Horizontal	Fundamental																																							
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2489.74</td><td>50.73</td><td>74.00</td><td>-23.27</td><td>38.13</td><td>26.90</td><td>7.35</td><td>32.03</td><td>10.38</td><td>119</td><td>116</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2489.74	50.73	74.00	-23.27	38.13	26.90	7.35	32.03	10.38	119	116	Peak	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1	2489.74	50.73	74.00	-23.27	38.13	26.90	7.35	32.03	10.38	119	116	Peak																													
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2498.74</td><td>46.68</td><td>54.00</td><td>-7.32</td><td>34.08</td><td>26.90</td><td>7.36</td><td>32.04</td><td>10.38</td><td>119</td><td>116</td><td>Average</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2498.74	46.68	54.00	-7.32	34.08	26.90	7.36	32.04	10.38	119	116	Average	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1	2498.74	46.68	54.00	-7.32	34.08	26.90	7.36	32.04	10.38	119	116	Average																													





Mode	1																																																																																																																										
	Band Edge - L																																																																																																																										
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																																										
ANT	1																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																				
Peak																																																																																																																											
	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto						Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto																																																																																																																				
<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2376.56</td><td>50.82</td><td>74.00</td><td>-23.18</td><td>38.21</td><td>27.00</td><td>7.19</td><td>31.96</td><td>10.38</td><td>151</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2376.56	50.82	74.00	-23.18	38.21	27.00	7.19	31.96	10.38	151	Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>96.38</td><td>-----</td><td>-----</td><td>83.82</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>100</td><td>151</td><td>Peak</td></tr><tr><td>2</td><td>2526.00</td><td>90.95</td><td>-----</td><td>-----</td><td>78.31</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>100</td><td>151</td><td>Peak</td></tr><tr><td>3</td><td>2658.00</td><td>57.78</td><td>-----</td><td>-----</td><td>44.52</td><td>27.30</td><td>7.59</td><td>32.04</td><td>10.41</td><td>100</td><td>151</td><td>Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	96.38	-----	-----	83.82	26.90	7.28	32.00	10.38	100	151	Peak	2	2526.00	90.95	-----	-----	78.31	26.90	7.39	32.04	10.39	100	151	Peak	3	2658.00	57.78	-----	-----	44.52	27.30	7.59	32.04	10.41	100	151	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																	
1	2376.56	50.82	74.00	-23.18	38.21	27.00	7.19	31.96	10.38	151	Peak																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																	
1	2440.00	96.38	-----	-----	83.82	26.90	7.28	32.00	10.38	100	151	Peak																																																																																																															
2	2526.00	90.95	-----	-----	78.31	26.90	7.39	32.04	10.39	100	151	Peak																																																																																																															
3	2658.00	57.78	-----	-----	44.52	27.30	7.59	32.04	10.41	100	151	Peak																																																																																																															
Avg																																																																																																																											
	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto						Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto																																																																																																																				
<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2372.92</td><td>46.04</td><td>54.00</td><td>-7.96</td><td>33.32</td><td>27.11</td><td>7.19</td><td>31.95</td><td>10.37</td><td>151</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2372.92	46.04	54.00	-7.96	33.32	27.11	7.19	31.95	10.37	151	Average	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>94.76</td><td>-----</td><td>-----</td><td>82.20</td><td>26.90</td><td>7.28</td><td>32.00</td><td>10.38</td><td>100</td><td>151</td><td>Average</td></tr><tr><td>2</td><td>2526.00</td><td>89.13</td><td>-----</td><td>-----</td><td>76.49</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>100</td><td>151</td><td>Average</td></tr><tr><td>3</td><td>2658.00</td><td>52.81</td><td>-----</td><td>-----</td><td>39.53</td><td>27.32</td><td>7.59</td><td>32.04</td><td>10.41</td><td>100</td><td>151</td><td>Average</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	94.76	-----	-----	82.20	26.90	7.28	32.00	10.38	100	151	Average	2	2526.00	89.13	-----	-----	76.49	26.90	7.39	32.04	10.39	100	151	Average	3	2658.00	52.81	-----	-----	39.53	27.32	7.59	32.04	10.41	100	151	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																	
1	2372.92	46.04	54.00	-7.96	33.32	27.11	7.19	31.95	10.37	151	Average																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																	
1	2440.00	94.76	-----	-----	82.20	26.90	7.28	32.00	10.38	100	151	Average																																																																																																															
2	2526.00	89.13	-----	-----	76.49	26.90	7.39	32.04	10.39	100	151	Average																																																																																																															
3	2658.00	52.81	-----	-----	39.53	27.32	7.59	32.04	10.41	100	151	Average																																																																																																															





Mode	1																																																						
	Band Edge - R																																																						
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																						
ANT	1																																																						
Pol.	Vertical												Fundamental																																										
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2496.82</td><td>50.35</td><td>74.00</td><td>-23.65</td><td>37.75</td><td>26.90</td><td>7.36</td><td>32.04</td><td>10.38</td><td></td><td>100</td><td>151</td><td>Peak</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2496.82	50.35	74.00	-23.65	37.75	26.90	7.36	32.04	10.38		100	151	Peak	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	2496.82	50.35	74.00	-23.65	37.75	26.90	7.36	32.04	10.38		100	151	Peak																																										
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2496.52</td><td>45.52</td><td>54.00</td><td>-8.48</td><td>32.92</td><td>26.90</td><td>7.36</td><td>32.04</td><td>10.38</td><td></td><td>100</td><td>151</td><td>Average</td></tr></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2496.52	45.52	54.00	-8.48	32.92	26.90	7.36	32.04	10.38		100	151	Average	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	2496.52	45.52	54.00	-8.48	32.92	26.90	7.36	32.04	10.38		100	151	Average																																										





Mode	1																																																																																	
	Harmonic																																																																																	
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																	
ANT	1																																																																																	
Pol.	Horizontal						Vertical																																																																											
Peak Avg																																																																																		
	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL						Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL																																																																											
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>45.57</td><td>74.00</td><td>-28.43</td><td>34.36</td><td>32.66</td><td>10.25</td><td>33.17</td><td>1.47</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7320.00</td><td>49.94</td><td>74.00</td><td>-24.06</td><td>34.06</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7320.00</td><td>42.14</td><td>54.00</td><td>-11.86</td><td>26.26</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.01</td><td>--</td><td>--</td><td>Average</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	45.57	74.00	-28.43	34.36	32.66	10.25	33.17	1.47	--	--	Peak	2	7320.00	49.94	74.00	-24.06	34.06	37.36	12.49	35.98	2.01	--	--	Peak	3	7320.00	42.14	54.00	-11.86	26.26	37.36	12.49	35.98	2.01	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																								
1	4880.00	45.57	74.00	-28.43	34.36	32.66	10.25	33.17	1.47	--	--	Peak																																																																						
2	7320.00	49.94	74.00	-24.06	34.06	37.36	12.49	35.98	2.01	--	--	Peak																																																																						
3	7320.00	42.14	54.00	-11.86	26.26	37.36	12.49	35.98	2.01	--	--	Average																																																																						





Mode	1	
	Harmonic	
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL







Mode	1																																																																			
	SHF																																																																			
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																			
ANT	1																																																																			
Pol.	Horizontal	Vertical																																																																		
Peak	 Site : 03CH23-HY Condition: PEAK_74 1m SHF_1224_240624 HORIZONTAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 18528.00</td><td>41.84</td><td>74.00</td><td>-32.16</td><td>58.20</td><td>30.00</td><td>20.05</td><td>64.87</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 18528.00	41.84	74.00	-32.16	58.20	30.00	20.05	64.87	-9.54	--	-- Peak	 Site : 03CH23-HY Condition: PEAK_74 1m SHF_1224_240624 VERTICAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 24600.00</td><td>43.19</td><td>74.00</td><td>-30.81</td><td>51.77</td><td>39.40</td><td>23.46</td><td>61.90</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 24600.00	43.19	74.00	-30.81	51.77	39.40	23.46	61.90	-9.54	--	-- Peak
	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																									
1 18528.00	41.84	74.00	-32.16	58.20	30.00	20.05	64.87	-9.54	--	-- Peak																																																										
Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																										
1 24600.00	43.19	74.00	-30.81	51.77	39.40	23.46	61.90	-9.54	--	-- Peak																																																										







Mode	1											
	LF											
	Bluetooth LE GFSK 2Mbps Ch38 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)											
ANT	1											
Pol.	Horizontal						Vertical					
QP/ Peak												
	Site : 03CH23-HY Condition: QP 3m CBL6111D_62028 & 003_241127 HORIZONTAL											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	33.88	22.31	40.00	-17.69	31.73	22.68	0.69	32.82	0.03	--	--	Peak
2	95.96	29.00	43.50	-14.50	44.95	15.52	1.22	32.69	0.00	--	--	Peak
3	215.27	34.97	43.50	-8.53	50.89	14.91	1.88	32.78	0.07	--	--	Peak
4	410.24	31.94	46.00	-14.06	39.88	22.12	2.65	32.82	0.11	--	--	Peak
5	743.92	32.52	46.00	-13.48	33.38	28.14	3.69	32.81	0.12	--	--	Peak
6	870.99	32.87	46.00	-13.13	31.87	29.22	3.88	32.23	0.13	--	--	Peak
												
	Site : 03CH23-HY Condition: QP 3m CBL6111D_62028 & 003_241127 VERTICAL											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	33.88	32.06	40.00	-7.14	42.28	22.68	0.69	32.82	0.03	--	--	Peak
2	93.05	30.12	43.50	-13.38	46.44	15.16	1.20	32.70	0.02	--	--	Peak
3	184.23	26.84	43.50	-16.66	42.86	14.91	1.74	32.75	0.08	--	--	Peak
4	293.84	25.72	46.00	-20.28	37.05	19.25	2.22	32.86	0.06	--	--	Peak
5	567.38	27.54	46.00	-18.46	30.99	26.26	3.19	33.06	0.16	--	--	Peak
6	739.07	30.69	46.00	-15.31	31.70	28.00	3.68	32.81	0.12	--	--	Peak





		2																																																																																																																										
Mode	Band Edge																																																																																																																											
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)																																																																																																																											
ANT	1																																																																																																																											
Pol.	Horizontal						Fundamental																																																																																																																					
Peak																																																																																																																												
	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.10</td><td>64.21</td><td>74.00</td><td>-9.79</td><td>51.67</td><td>26.85</td><td>7.34</td><td>32.03</td><td>10.38</td><td>217</td><td>155</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.10	64.21	74.00	-9.79	51.67	26.85	7.34	32.03	10.38	217	155	Peak	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>102.19</td><td>-----</td><td>-----</td><td>89.63</td><td>26.88</td><td>7.31</td><td>32.01</td><td>10.38</td><td>217</td><td>155</td><td>Peak</td></tr><tr><td>2</td><td>2526.00</td><td>93.15</td><td>-----</td><td>-----</td><td>80.51</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>217</td><td>155</td><td>Peak</td></tr><tr><td>3</td><td>2654.00</td><td>59.89</td><td>-----</td><td>-----</td><td>46.58</td><td>27.36</td><td>7.58</td><td>32.04</td><td>10.41</td><td>217</td><td>155</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	102.19	-----	-----	89.63	26.88	7.31	32.01	10.38	217	155	Peak	2	2526.00	93.15	-----	-----	80.51	26.90	7.39	32.04	10.39	217	155	Peak	3	2654.00	59.89	-----	-----	46.58	27.36	7.58	32.04	10.41	217	155
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2485.10	64.21	74.00	-9.79	51.67	26.85	7.34	32.03	10.38	217	155	Peak																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2462.00	102.19	-----	-----	89.63	26.88	7.31	32.01	10.38	217	155	Peak																																																																																																																
2	2526.00	93.15	-----	-----	80.51	26.90	7.39	32.04	10.39	217	155	Peak																																																																																																																
3	2654.00	59.89	-----	-----	46.58	27.36	7.58	32.04	10.41	217	155	Peak																																																																																																																
Avg																																																																																																																												
	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.81</td><td>46.50</td><td>54.00</td><td>-7.50</td><td>33.97</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>217</td><td>155</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.81	46.50	54.00	-7.50	33.97	26.84	7.34	32.03	10.38	217	155	Average	Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>92.39</td><td>-----</td><td>-----</td><td>79.81</td><td>26.90</td><td>7.31</td><td>32.01</td><td>10.38</td><td>217</td><td>155</td><td>Average</td></tr><tr><td>2</td><td>2526.00</td><td>87.61</td><td>-----</td><td>-----</td><td>74.97</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>217</td><td>155</td><td>Average</td></tr><tr><td>3</td><td>2648.00</td><td>50.74</td><td>-----</td><td>-----</td><td>37.40</td><td>27.40</td><td>7.57</td><td>32.04</td><td>10.41</td><td>217</td><td>155</td><td>Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	92.39	-----	-----	79.81	26.90	7.31	32.01	10.38	217	155	Average	2	2526.00	87.61	-----	-----	74.97	26.90	7.39	32.04	10.39	217	155	Average	3	2648.00	50.74	-----	-----	37.40	27.40	7.57	32.04	10.41	217	155
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2483.81	46.50	54.00	-7.50	33.97	26.84	7.34	32.03	10.38	217	155	Average																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2462.00	92.39	-----	-----	79.81	26.90	7.31	32.01	10.38	217	155	Average																																																																																																																
2	2526.00	87.61	-----	-----	74.97	26.90	7.39	32.04	10.39	217	155	Average																																																																																																																
3	2648.00	50.74	-----	-----	37.40	27.40	7.57	32.04	10.41	217	155	Average																																																																																																																





		2																																																																														
Mode	Band Edge																																																																															
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)																																																																															
ANT	1																																																																															
Pol.	Vertical																																																																															
Peak																																																																																
	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2485.52</td><td>60.42</td><td>74.00</td><td>-13.58</td><td>47.87</td><td>26.86</td><td>7.34</td><td>32.03</td><td>10.38</td><td>155</td><td>150</td><td>Peak</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.52	60.42	74.00	-13.58	47.87	26.86	7.34	32.03	10.38	155	150	Peak																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																						
1	2485.52	60.42	74.00	-13.58	47.87	26.86	7.34	32.03	10.38	155	150	Peak																																																																				
Fundamental																																																																																
	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>100.74</td><td>-----</td><td>-----</td><td>88.14</td><td>26.92</td><td>7.31</td><td>32.01</td><td>10.38</td><td>155</td><td>150</td><td>Peak</td></tr><tr><td>2</td><td>2526.00</td><td>87.11</td><td>-----</td><td>-----</td><td>74.47</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>155</td><td>150</td><td>Peak</td></tr><tr><td>3</td><td>2658.00</td><td>60.30</td><td>-----</td><td>-----</td><td>47.02</td><td>27.32</td><td>7.59</td><td>32.04</td><td>10.41</td><td>155</td><td>150</td><td>Peak</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	100.74	-----	-----	88.14	26.92	7.31	32.01	10.38	155	150	Peak	2	2526.00	87.11	-----	-----	74.47	26.90	7.39	32.04	10.39	155	150	Peak	3	2658.00	60.30	-----	-----	47.02	27.32	7.59	32.04	10.41	155	150
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																						
1	2462.00	100.74	-----	-----	88.14	26.92	7.31	32.01	10.38	155	150	Peak																																																																				
2	2526.00	87.11	-----	-----	74.47	26.90	7.39	32.04	10.39	155	150	Peak																																																																				
3	2658.00	60.30	-----	-----	47.02	27.32	7.59	32.04	10.41	155	150	Peak																																																																				
Avg																																																																																
	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.66</td><td>43.97</td><td>54.00</td><td>-10.03</td><td>31.44</td><td>26.84</td><td>7.34</td><td>32.03</td><td>10.38</td><td>155</td><td>150</td><td>Average</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.66	43.97	54.00	-10.03	31.44	26.84	7.34	32.03	10.38	155	150	Average																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																						
1	2483.66	43.97	54.00	-10.03	31.44	26.84	7.34	32.03	10.38	155	150	Average																																																																				
Fundamental																																																																																
	Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>89.44</td><td>-----</td><td>-----</td><td>76.86</td><td>26.90</td><td>7.31</td><td>32.01</td><td>10.38</td><td>155</td><td>150</td><td>Average</td></tr><tr><td>2</td><td>2526.00</td><td>82.21</td><td>-----</td><td>-----</td><td>69.57</td><td>26.90</td><td>7.39</td><td>32.04</td><td>10.39</td><td>155</td><td>150</td><td>Average</td></tr><tr><td>3</td><td>2660.00</td><td>50.61</td><td>-----</td><td>-----</td><td>37.35</td><td>27.30</td><td>7.59</td><td>32.04</td><td>10.41</td><td>155</td><td>150</td><td>Average</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	89.44	-----	-----	76.86	26.90	7.31	32.01	10.38	155	150	Average	2	2526.00	82.21	-----	-----	69.57	26.90	7.39	32.04	10.39	155	150	Average	3	2660.00	50.61	-----	-----	37.35	27.30	7.59	32.04	10.41	155	150
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																						
1	2462.00	89.44	-----	-----	76.86	26.90	7.31	32.01	10.38	155	150	Average																																																																				
2	2526.00	82.21	-----	-----	69.57	26.90	7.39	32.04	10.39	155	150	Average																																																																				
3	2660.00	50.61	-----	-----	37.35	27.30	7.59	32.04	10.41	155	150	Average																																																																				





Mode	2																																																																																																																																																																																				
	Harmonic																																																																																																																																																																																				
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)																																																																																																																																																																																				
ANT	1																																																																																																																																																																																				
Pol.	Horizontal						Vertical																																																																																																																																																																														
Peak Avg																																																																																																																																																																																					
	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL						Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL																																																																																																																																																																														
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4924.00</td><td>46.02</td><td>74.00</td><td>-27.98</td><td>34.57</td><td>32.75</td><td>10.32</td><td>33.18</td><td>1.56</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>6500.00</td><td>67.48</td><td>-----</td><td>-----</td><td>52.93</td><td>35.57</td><td>11.79</td><td>34.75</td><td>1.94</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7386.00</td><td>49.47</td><td>74.00</td><td>-24.53</td><td>33.77</td><td>37.23</td><td>12.52</td><td>36.03</td><td>1.98</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7386.00</td><td>39.36</td><td>54.00</td><td>-14.64</td><td>23.66</td><td>37.23</td><td>12.52</td><td>36.03</td><td>1.98</td><td>--</td><td>Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4924.00	46.02	74.00	-27.98	34.57	32.75	10.32	33.18	1.56	--	Peak	2	6500.00	67.48	-----	-----	52.93	35.57	11.79	34.75	1.94	--	Peak	3	7386.00	49.47	74.00	-24.53	33.77	37.23	12.52	36.03	1.98	--	Peak	4	7386.00	39.36	54.00	-14.64	23.66	37.23	12.52	36.03	1.98	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4924.00</td><td>45.68</td><td>74.00</td><td>-28.32</td><td>34.23</td><td>32.75</td><td>10.32</td><td>33.18</td><td>1.56</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>6500.00</td><td>64.74</td><td>-----</td><td>-----</td><td>50.51</td><td>35.24</td><td>11.74</td><td>34.70</td><td>1.95</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7386.00</td><td>49.32</td><td>74.00</td><td>-24.68</td><td>33.62</td><td>37.23</td><td>12.52</td><td>36.03</td><td>1.98</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7386.00</td><td>39.22</td><td>54.00</td><td>-14.78</td><td>23.52</td><td>37.23</td><td>12.52</td><td>36.03</td><td>1.98</td><td>--</td><td>Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4924.00	45.68	74.00	-28.32	34.23	32.75	10.32	33.18	1.56	--	Peak	2	6500.00	64.74	-----	-----	50.51	35.24	11.74	34.70	1.95	--	Peak	3	7386.00	49.32	74.00	-24.68	33.62	37.23	12.52	36.03	1.98	--	Peak	4	7386.00	39.22	54.00	-14.78	23.52	37.23	12.52	36.03	1.98	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																											
1	4924.00	46.02	74.00	-27.98	34.57	32.75	10.32	33.18	1.56	--	Peak																																																																																																																																																																										
2	6500.00	67.48	-----	-----	52.93	35.57	11.79	34.75	1.94	--	Peak																																																																																																																																																																										
3	7386.00	49.47	74.00	-24.53	33.77	37.23	12.52	36.03	1.98	--	Peak																																																																																																																																																																										
4	7386.00	39.36	54.00	-14.64	23.66	37.23	12.52	36.03	1.98	--	Average																																																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																											
1	4924.00	45.68	74.00	-28.32	34.23	32.75	10.32	33.18	1.56	--	Peak																																																																																																																																																																										
2	6500.00	64.74	-----	-----	50.51	35.24	11.74	34.70	1.95	--	Peak																																																																																																																																																																										
3	7386.00	49.32	74.00	-24.68	33.62	37.23	12.52	36.03	1.98	--	Peak																																																																																																																																																																										
4	7386.00	39.22	54.00	-14.78	23.52	37.23	12.52	36.03	1.98	--	Average																																																																																																																																																																										





Mode	2	
	Harmonic	
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL







Mode	2																																																																																																															
	SHF																																																																																																															
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)																																																																																																															
ANT	1																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 1m SHF_1224_240624 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>39610.12</td><td>48.45</td><td>74.00</td><td>-25.55</td><td>44.65</td><td>45.48</td><td>31.05</td><td>63.19</td><td>-9.54</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>39610.12</td><td>38.71</td><td>54.00</td><td>-15.29</td><td>34.91</td><td>45.48</td><td>31.05</td><td>63.19</td><td>-9.54</td><td>--</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	39610.12	48.45	74.00	-25.55	44.65	45.48	31.05	63.19	-9.54	--	PEAK	2	39610.12	38.71	54.00	-15.29	34.91	45.48	31.05	63.19	-9.54	--	Average	 Site : 03CH23-HY Condition: PEAK(UNII) 1m SHF_1224_240624 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>39601.86</td><td>49.25</td><td>74.00</td><td>-24.75</td><td>45.32</td><td>45.58</td><td>31.05</td><td>63.16</td><td>-9.54</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>39601.86</td><td>39.00</td><td>54.00</td><td>-15.00</td><td>35.07</td><td>45.58</td><td>31.05</td><td>63.16</td><td>-9.54</td><td>--</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	39601.86	49.25	74.00	-24.75	45.32	45.58	31.05	63.16	-9.54	--	PEAK	2	39601.86	39.00	54.00	-15.00	35.07	45.58	31.05	63.16	-9.54	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	39610.12	48.45	74.00	-25.55	44.65	45.48	31.05	63.19	-9.54	--	PEAK																																																																																																					
2	39610.12	38.71	54.00	-15.29	34.91	45.48	31.05	63.19	-9.54	--	Average																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	39601.86	49.25	74.00	-24.75	45.32	45.58	31.05	63.16	-9.54	--	PEAK																																																																																																					
2	39601.86	39.00	54.00	-15.00	35.07	45.58	31.05	63.16	-9.54	--	Average																																																																																																					



Mode	2											
	LF											
	11ax HE20 Full RU Ch11 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100) + UWB Ch05(BPRF10 SP3 STS1 0)											
ANT	1											
Pol.	Horizontal						Vertical					
QP/ Peak												
	Site : 03CH23-HY Condition: QP 3m CBL6111D_62028 & 003_241127 HORIZONTAL						Site : 03CH23-HY Condition: QP 3m CBL6111D_62028 & 003_241127 VERTICAL					
	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		
	MHz	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	33.88	24.66	40.00	-15.34	34.08	22.68	0.69	32.82	0.03	--	-- Peak	
2	98.87	26.77	43.50	-16.73	42.30	15.88	1.26	32.68	0.01	--	-- Peak	
3	183.26	28.38	43.50	-15.12	44.38	14.93	1.73	32.75	0.09	--	-- Peak	
4	216.24	32.65	46.00	-13.35	48.58	14.90	1.88	32.78	0.07	--	-- Peak	
5	410.24	26.90	46.00	-19.10	34.84	22.12	2.65	32.82	0.11	--	-- Peak	
6	894.27	31.67	46.00	-14.33	30.37	29.24	4.00	32.05	0.11	--	-- Peak	
	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		
	MHz	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	33.88	32.58	40.00	-7.42	42.00	22.68	0.69	32.82	0.03	--	-- Peak	
2	93.05	28.52	43.50	-14.98	44.84	15.16	1.20	32.70	0.02	--	-- Peak	
3	184.23	25.55	43.50	-17.95	41.57	14.91	1.74	32.75	0.08	--	-- Peak	
4	215.27	24.72	43.50	-18.78	40.64	14.91	1.88	32.78	0.07	--	-- Peak	
5	564.47	27.56	46.00	-18.44	30.95	26.33	3.18	33.06	0.16	--	-- Peak	
6	910.76	31.99	46.00	-14.01	30.33	29.36	4.08	31.90	0.12	--	-- Peak	







		3																																																																																																																							
Mode	Band Edge - L																																																																																																																								
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak																																																																																																																									
	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2377.47</td><td>43.68</td><td>74.00</td><td>-30.32</td><td>38.33</td><td>26.98</td><td>7.19</td><td>31.96</td><td>3.14</td><td>300 198 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos				Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg	1	2377.47	43.68	74.00	-30.32	38.33	26.98	7.19	31.96	3.14	300 198 Peak	Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>86.35</td><td>-----</td><td>-----</td><td>81.02</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>300 198 Peak</td></tr><tr><td>2</td><td>2530.00</td><td>82.93</td><td>-----</td><td>-----</td><td>77.51</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>300 198 Peak</td></tr><tr><td>3</td><td>2655.00</td><td>49.85</td><td>-----</td><td>-----</td><td>43.77</td><td>27.35</td><td>7.58</td><td>32.04</td><td>3.19</td><td>300 198 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos				Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg	1	2440.00	86.35	-----	-----	81.02	26.90	7.28	32.00	3.15	300 198 Peak	2	2530.00	82.93	-----	-----	77.51	26.90	7.40	32.04	3.16	300 198 Peak	3	2655.00	49.85	-----	-----	43.77	27.35	7.58	32.04	3.19
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg																																																																																																															
1	2377.47	43.68	74.00	-30.32	38.33	26.98	7.19	31.96	3.14	300 198 Peak																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg																																																																																																															
1	2440.00	86.35	-----	-----	81.02	26.90	7.28	32.00	3.15	300 198 Peak																																																																																																															
2	2530.00	82.93	-----	-----	77.51	26.90	7.40	32.04	3.16	300 198 Peak																																																																																																															
3	2655.00	49.85	-----	-----	43.77	27.35	7.58	32.04	3.19	300 198 Peak																																																																																																															
Avg																																																																																																																									
	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2351.21</td><td>38.83</td><td>54.00</td><td>-15.17</td><td>33.38</td><td>27.11</td><td>7.15</td><td>31.94</td><td>3.13</td><td>300 198 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos				Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg	1	2351.21	38.83	54.00	-15.17	33.38	27.11	7.15	31.94	3.13	300 198 Average	Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2440.00</td><td>84.49</td><td>-----</td><td>-----</td><td>79.16</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>300 198 Average</td></tr><tr><td>2</td><td>2530.00</td><td>81.34</td><td>-----</td><td>-----</td><td>75.92</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>300 198 Average</td></tr><tr><td>3</td><td>2655.00</td><td>44.00</td><td>-----</td><td>-----</td><td>37.97</td><td>27.38</td><td>7.58</td><td>32.04</td><td>3.19</td><td>300 198 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos				Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg	1	2440.00	84.49	-----	-----	79.16	26.90	7.28	32.00	3.15	300 198 Average	2	2530.00	81.34	-----	-----	75.92	26.90	7.40	32.04	3.16	300 198 Average	3	2655.00	44.00	-----	-----	37.97	27.38	7.58	32.04	3.19
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg																																																																																																															
1	2351.21	38.83	54.00	-15.17	33.38	27.11	7.15	31.94	3.13	300 198 Average																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	deg																																																																																																															
1	2440.00	84.49	-----	-----	79.16	26.90	7.28	32.00	3.15	300 198 Average																																																																																																															
2	2530.00	81.34	-----	-----	75.92	26.90	7.40	32.04	3.16	300 198 Average																																																																																																															
3	2655.00	44.00	-----	-----	37.97	27.38	7.58	32.04	3.19	300 198 Average																																																																																																															



Mode	3																																											
	Band Edge - R																																											
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																											
ANT	1																																											
Pol.	Horizontal	Fundamental																																										
Peak	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2489.62</td><td>43.44</td><td>74.00</td><td>-30.56</td><td>38.06</td><td>26.90</td><td>7.35</td><td>32.03</td><td>3.16</td><td>300</td><td>198 Peak</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 2489.62	43.44	74.00	-30.56	38.06	26.90	7.35	32.03	3.16	300	198 Peak	Blank
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																		
1 2489.62	43.44	74.00	-30.56	38.06	26.90	7.35	32.03	3.16	300	198 Peak																																		
Avg	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2496.70</td><td>38.02</td><td>54.00</td><td>-15.18</td><td>33.44</td><td>26.90</td><td>7.36</td><td>32.04</td><td>3.16</td><td>300</td><td>198 Average</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 2496.70	38.02	54.00	-15.18	33.44	26.90	7.36	32.04	3.16	300	198 Average	Blank
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																		
1 2496.70	38.02	54.00	-15.18	33.44	26.90	7.36	32.04	3.16	300	198 Average																																		







	3																																																																																																																									
Mode	Band Edge - L																																																																																																																									
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																																									
ANT	1																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																			
Peak	 Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2314.68</td><td>43.92</td><td>74.00</td><td>-30.08</td><td>38.38</td><td>27.25</td><td>7.09</td><td>31.91</td><td>3.11</td><td>122 145 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2314.68	43.92	74.00	-30.08	38.38	27.25	7.09	31.91	3.11	122 145 Peak	 Site : 03CH23-HY Condition: PEAK_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>88.06</td><td>-----</td><td>82.73</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>122</td><td>145 Peak</td></tr><tr><td>2</td><td>2530.00</td><td>83.07</td><td>-----</td><td>77.65</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>122</td><td>145 Peak</td></tr><tr><td>3</td><td>2655.00</td><td>50.01</td><td>-----</td><td>43.90</td><td>27.38</td><td>7.58</td><td>32.04</td><td>3.19</td><td>122</td><td>145 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2440.00	88.06	-----	82.73	26.90	7.28	32.00	3.15	122	145 Peak	2	2530.00	83.07	-----	77.65	26.90	7.40	32.04	3.16	122	145 Peak	3	2655.00	50.01	-----	43.90	27.38	7.58	32.04	3.19	122	145 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																
1	2314.68	43.92	74.00	-30.08	38.38	27.25	7.09	31.91	3.11	122 145 Peak																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																
1	2440.00	88.06	-----	82.73	26.90	7.28	32.00	3.15	122	145 Peak																																																																																																																
2	2530.00	83.07	-----	77.65	26.90	7.40	32.04	3.16	122	145 Peak																																																																																																																
3	2655.00	50.01	-----	43.90	27.38	7.58	32.04	3.19	122	145 Peak																																																																																																																
Avg	 Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2375.13</td><td>39.08</td><td>54.00</td><td>-14.92</td><td>33.66</td><td>27.05</td><td>7.19</td><td>31.96</td><td>3.14</td><td>122 145 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2375.13	39.08	54.00	-14.92	33.66	27.05	7.19	31.96	3.14	122 145 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL : RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector: PEAK Mode : 2 Setting : 7F <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2"></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>dB</th><th>deg</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>86.38</td><td>-----</td><td>81.05</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>122</td><td>145 Average</td></tr><tr><td>2</td><td>2530.00</td><td>81.13</td><td>-----</td><td>75.71</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>122</td><td>145 Average</td></tr><tr><td>3</td><td>2655.00</td><td>44.42</td><td>-----</td><td>38.34</td><td>27.34</td><td>7.59</td><td>32.04</td><td>3.19</td><td>122</td><td>145 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2440.00	86.38	-----	81.05	26.90	7.28	32.00	3.15	122	145 Average	2	2530.00	81.13	-----	75.71	26.90	7.40	32.04	3.16	122	145 Average	3	2655.00	44.42	-----	38.34	27.34	7.59	32.04	3.19	122	145 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																
1	2375.13	39.08	54.00	-14.92	33.66	27.05	7.19	31.96	3.14	122 145 Average																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	dB	deg																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																
1	2440.00	86.38	-----	81.05	26.90	7.28	32.00	3.15	122	145 Average																																																																																																																
2	2530.00	81.13	-----	75.71	26.90	7.40	32.04	3.16	122	145 Average																																																																																																																
3	2655.00	44.42	-----	38.34	27.34	7.59	32.04	3.19	122	145 Average																																																																																																																



Mode	3																																								
	Band Edge - R																																								
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																								
ANT	1																																								
Pol.	Vertical	Fundamental																																							
Peak	Site : 03CH23-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C05A18EN_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 2 Setting : 7F <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2485.18</td><td>43.36</td><td>74.00</td><td>-30.64</td><td>38.04</td><td>26.85</td><td>7.34</td><td>32.03</td><td>3.16</td><td>122</td><td>145</td><td>Peak</td><td></td></tr></table>	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2485.18	43.36	74.00	-30.64	38.04	26.85	7.34	32.03	3.16	122	145	Peak		Blank
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																													
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1 2485.18	43.36	74.00	-30.64	38.04	26.85	7.34	32.03	3.16	122	145	Peak																														
Avg	Site : 03CH23-HY Condition: AVG_BE_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL RBW:1000.000kHz VBW:39.000kHz SMT:Auto Detector : PEAK Mode : 2 Setting : 7F <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2488.78</td><td>38.72</td><td>54.00</td><td>-15.28</td><td>33.35</td><td>26.09</td><td>7.35</td><td>32.03</td><td>3.16</td><td>122</td><td>145</td><td>Average</td><td></td></tr></table>	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2488.78	38.72	54.00	-15.28	33.35	26.09	7.35	32.03	3.16	122	145	Average		Blank
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																													
MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																														
1 2488.78	38.72	54.00	-15.28	33.35	26.09	7.35	32.03	3.16	122	145	Average																														



		3																																																																																																												
Mode	Band Edge																																																																																																													
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																													
ANT	1																																																																																																													
Pol.	Horizontal	Fundamental																																																																																																												
Peak	 Site : 03CH23-HY Condition: PEAK_BE(UNII) B3 3m DRH18-E LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 1 Setting : 65 <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5458.45</td><td>62.33</td><td>74.00</td><td>-11.67</td><td>49.21</td><td>32.73</td><td>10.91</td><td>34.34</td><td>3.82 100 192 Peak</td></tr><tr><td>2 5468.00</td><td>65.64</td><td>68.20</td><td>-2.56</td><td>52.47</td><td>32.78</td><td>10.93</td><td>34.36</td><td>3.82 100 192 Peak</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5458.45	62.33	74.00	-11.67	49.21	32.73	10.91	34.34	3.82 100 192 Peak	2 5468.00	65.64	68.20	-2.56	52.47	32.78	10.93	34.36	3.82 100 192 Peak	 Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2440.00</td><td>90.86</td><td>-----</td><td>85.53</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>100 192 Peak</td></tr><tr><td>2 2530.00</td><td>89.37</td><td>-----</td><td>83.95</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>100 192 Peak</td></tr><tr><td>3 2656.00</td><td>58.17</td><td>-----</td><td>52.09</td><td>27.34</td><td>7.59</td><td>32.04</td><td>3.19</td><td>100 192 Peak</td></tr><tr><td>4 5500.00</td><td>105.45</td><td>-----</td><td>92.18</td><td>32.88</td><td>10.97</td><td>34.42</td><td>3.84</td><td>100 192 Peak</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2440.00	90.86	-----	85.53	26.90	7.28	32.00	3.15	100 192 Peak	2 2530.00	89.37	-----	83.95	26.90	7.40	32.04	3.16	100 192 Peak	3 2656.00	58.17	-----	52.09	27.34	7.59	32.04	3.19	100 192 Peak	4 5500.00	105.45	-----	92.18	32.88	10.97	34.42	3.84	100 192 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																					
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																							
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1 5458.45	62.33	74.00	-11.67	49.21	32.73	10.91	34.34	3.82 100 192 Peak																																																																																																						
2 5468.00	65.64	68.20	-2.56	52.47	32.78	10.93	34.36	3.82 100 192 Peak																																																																																																						
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																							
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1 2440.00	90.86	-----	85.53	26.90	7.28	32.00	3.15	100 192 Peak																																																																																																						
2 2530.00	89.37	-----	83.95	26.90	7.40	32.04	3.16	100 192 Peak																																																																																																						
3 2656.00	58.17	-----	52.09	27.34	7.59	32.04	3.19	100 192 Peak																																																																																																						
4 5500.00	105.45	-----	92.18	32.88	10.97	34.42	3.84	100 192 Peak																																																																																																						
Avg	 Site : 03CH23-HY Condition: AVG_BE(UNII) B3 3m DRH18-E LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto Detector : PEAK Mode : 1 Setting : 65 <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5459.00</td><td>50.03</td><td>54.00</td><td>-3.97</td><td>36.90</td><td>32.74</td><td>10.91</td><td>34.34</td><td>3.82 100 192 Average</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5459.00	50.03	54.00	-3.97	36.90	32.74	10.91	34.34	3.82 100 192 Average	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E LE2C05A18EN_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2440.00</td><td>82.50</td><td>-----</td><td>77.17</td><td>26.90</td><td>7.28</td><td>32.00</td><td>3.15</td><td>100 192 Average</td></tr><tr><td>2 2530.00</td><td>84.56</td><td>-----</td><td>79.14</td><td>26.90</td><td>7.40</td><td>32.04</td><td>3.16</td><td>100 192 Average</td></tr><tr><td>3 2656.00</td><td>51.53</td><td>-----</td><td>45.45</td><td>27.34</td><td>7.59</td><td>32.04</td><td>3.19</td><td>100 192 Average</td></tr><tr><td>4 5500.00</td><td>90.00</td><td>-----</td><td>84.77</td><td>32.91</td><td>11.00</td><td>34.44</td><td>3.84</td><td>100 192 Average</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2440.00	82.50	-----	77.17	26.90	7.28	32.00	3.15	100 192 Average	2 2530.00	84.56	-----	79.14	26.90	7.40	32.04	3.16	100 192 Average	3 2656.00	51.53	-----	45.45	27.34	7.59	32.04	3.19	100 192 Average	4 5500.00	90.00	-----	84.77	32.91	11.00	34.44	3.84	100 192 Average									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																					
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																							
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1 5459.00	50.03	54.00	-3.97	36.90	32.74	10.91	34.34	3.82 100 192 Average																																																																																																						
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																							
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1 2440.00	82.50	-----	77.17	26.90	7.28	32.00	3.15	100 192 Average																																																																																																						
2 2530.00	84.56	-----	79.14	26.90	7.40	32.04	3.16	100 192 Average																																																																																																						
3 2656.00	51.53	-----	45.45	27.34	7.59	32.04	3.19	100 192 Average																																																																																																						
4 5500.00	90.00	-----	84.77	32.91	11.00	34.44	3.84	100 192 Average																																																																																																						

Mode

3

Band Edge

Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)

ANT

1

Pol.

Vertical

Fundamental

Peak

Level (dBuV/m)

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

5350

5380

5410

5440

5470

5500

Frequency (MHz)

Site : 03CH23-HY

Condition: PEAK_BE(UNII)_B3 3m DRH18-E_LE2C05A18EN_240620 VERTICAL

: RBW:1000.000kHz VBW:3000.000kHz SMT:Auto

Detector : PEAK

Mode : 1

Setting : 65

	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg
1 5459.00	62.34	74.00	-11.66	49.21	32.74	10.91	34.34	3.82	100 119 Peak
2 5469.40	65.79	68.20	-2.41	52.62	32.78	10.93	34.36	3.82	100 119 Peak

Level (dBuV/m)

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

1000

2200

3400

4600

5800

7000

Frequency (MHz)

Site : 03CH23-HY

Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_240620 VERTICAL

: RBW:1000.000kHz VBW:3000.000kHz SMT:Auto

	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg
1 2440.00	89.29	-----	-----	83.96	26.90	7.28	32.00	3.15	100 119 Peak
2 2530.00	95.62	-----	-----	90.20	26.90	7.40	32.04	3.16	100 119 Peak
3 2650.00	52.66	-----	-----	46.54	27.40	7.57	32.04	3.19	100 119 Peak
4 5500.00	105.91	-----	-----	92.60	32.91	11.00	34.44	3.84	100 119 Peak

Avg

Level (dBuV/m)

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

5350

5380

5410

5440

5470

5500

Frequency (MHz)

Site : 03CH23-HY

Condition: AVG_BE(UNII)_B3 3m DRH18-E_LE2C05A18EN_240620 VERTICAL

: RBW:1000.000kHz VBW:0.750kHz SMT:Auto

Detector : PEAK

Mode : 1

Setting : 65

	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg
1 5459.00	50.23	54.00	-3.77	37.10	32.74	10.91	34.34	3.82	100 119 Average

Level (dBuV/m)

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

1000

2200

3400

4600

5800

7000

Frequency (MHz)



Site : 03CH23-HY

Condition: AVG 54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL



: RBW:1000.000kHz VBW:0.750kHz SMT:Auto

	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor	Factor	Factor	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg
1 2440.00	80.97	-----	-----	75.64	26.90	7.28	32.00	3.15	100 119 Average
2 2530.00	92.72	-----	-----	87.30	26.90	7.40	32.04	3.16	100 119 Average
3 2650.00	46.22	-----	-----	40.14	27.34	7.59	32.04	3.19	100 119 Average
4 5500.00	98.30	-----	-----	85.02	32.90	10.90	34.44	3.84	100 119 Average





		3																																																																																																																																																																																												
Mode	Harmonic																																																																																																																																																																																													
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																																																																																																													
ANT	1																																																																																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																																																																																							
Peak Avg																																																																																																																																																																																														
	Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL Mode : 1 Setting : <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 4800.00</td><td>45.11</td><td>74.00</td><td>-28.89</td><td>33.90</td><td>32.66</td><td>10.25</td><td>33.17</td><td>1.47</td><td>-- -- Peak</td></tr><tr><td>2 7320.00</td><td>49.60</td><td>74.00</td><td>-24.40</td><td>33.41</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.32</td><td>-- -- Peak</td></tr><tr><td>3 7320.00</td><td>44.21</td><td>54.00</td><td>-9.79</td><td>28.02</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.32</td><td>-- -- Average</td></tr><tr><td>4 11000.00</td><td>49.27</td><td>74.00</td><td>-24.73</td><td>33.70</td><td>37.80</td><td>15.37</td><td>39.84</td><td>2.24</td><td>-- -- Peak</td></tr><tr><td>5 11000.00</td><td>40.62</td><td>54.00</td><td>-13.38</td><td>25.05</td><td>37.80</td><td>15.37</td><td>39.84</td><td>2.24</td><td>-- -- Average</td></tr><tr><td>6 16500.00</td><td>54.51</td><td>68.20</td><td>-13.69</td><td>38.00</td><td>40.80</td><td>18.84</td><td>45.85</td><td>2.72</td><td>-- -- Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 4800.00	45.11	74.00	-28.89	33.90	32.66	10.25	33.17	1.47	-- -- Peak	2 7320.00	49.60	74.00	-24.40	33.41	37.36	12.49	35.98	2.32	-- -- Peak	3 7320.00	44.21	54.00	-9.79	28.02	37.36	12.49	35.98	2.32	-- -- Average	4 11000.00	49.27	74.00	-24.73	33.70	37.80	15.37	39.84	2.24	-- -- Peak	5 11000.00	40.62	54.00	-13.38	25.05	37.80	15.37	39.84	2.24	-- -- Average	6 16500.00	54.51	68.20	-13.69	38.00	40.80	18.84	45.85	2.72	-- -- Peak	Site : 03CH23-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C05A18EN_240620 VERTICAL Mode : 1 Setting : <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 4800.00</td><td>44.25</td><td>74.00</td><td>-29.75</td><td>33.04</td><td>32.66</td><td>10.25</td><td>33.17</td><td>1.47</td><td>-- -- Peak</td></tr><tr><td>2 7320.00</td><td>49.05</td><td>74.00</td><td>-24.95</td><td>32.86</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.32</td><td>-- -- Peak</td></tr><tr><td>3 7320.00</td><td>44.17</td><td>54.00</td><td>-9.83</td><td>27.98</td><td>37.36</td><td>12.49</td><td>35.98</td><td>2.32</td><td>-- -- Average</td></tr><tr><td>4 11000.00</td><td>50.46</td><td>74.00</td><td>-23.54</td><td>34.89</td><td>37.80</td><td>15.37</td><td>39.84</td><td>2.24</td><td>-- -- Peak</td></tr><tr><td>5 11000.00</td><td>40.65</td><td>54.00</td><td>-13.35</td><td>25.08</td><td>37.80</td><td>15.37</td><td>39.84</td><td>2.24</td><td>-- -- Average</td></tr><tr><td>6 16500.00</td><td>53.52</td><td>68.20</td><td>-14.68</td><td>37.01</td><td>40.80</td><td>18.84</td><td>45.85</td><td>2.72</td><td>-- -- Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 4800.00	44.25	74.00	-29.75	33.04	32.66	10.25	33.17	1.47	-- -- Peak	2 7320.00	49.05	74.00	-24.95	32.86	37.36	12.49	35.98	2.32	-- -- Peak	3 7320.00	44.17	54.00	-9.83	27.98	37.36	12.49	35.98	2.32	-- -- Average	4 11000.00	50.46	74.00	-23.54	34.89	37.80	15.37	39.84	2.24	-- -- Peak	5 11000.00	40.65	54.00	-13.35	25.08	37.80	15.37	39.84	2.24	-- -- Average	6 16500.00	53.52	68.20	-14.68	37.01	40.80	18.84	45.85	2.72
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																					
1 4800.00	45.11	74.00	-28.89	33.90	32.66	10.25	33.17	1.47	-- -- Peak																																																																																																																																																																																					
2 7320.00	49.60	74.00	-24.40	33.41	37.36	12.49	35.98	2.32	-- -- Peak																																																																																																																																																																																					
3 7320.00	44.21	54.00	-9.79	28.02	37.36	12.49	35.98	2.32	-- -- Average																																																																																																																																																																																					
4 11000.00	49.27	74.00	-24.73	33.70	37.80	15.37	39.84	2.24	-- -- Peak																																																																																																																																																																																					
5 11000.00	40.62	54.00	-13.38	25.05	37.80	15.37	39.84	2.24	-- -- Average																																																																																																																																																																																					
6 16500.00	54.51	68.20	-13.69	38.00	40.80	18.84	45.85	2.72	-- -- Peak																																																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																					
1 4800.00	44.25	74.00	-29.75	33.04	32.66	10.25	33.17	1.47	-- -- Peak																																																																																																																																																																																					
2 7320.00	49.05	74.00	-24.95	32.86	37.36	12.49	35.98	2.32	-- -- Peak																																																																																																																																																																																					
3 7320.00	44.17	54.00	-9.83	27.98	37.36	12.49	35.98	2.32	-- -- Average																																																																																																																																																																																					
4 11000.00	50.46	74.00	-23.54	34.89	37.80	15.37	39.84	2.24	-- -- Peak																																																																																																																																																																																					
5 11000.00	40.65	54.00	-13.35	25.08	37.80	15.37	39.84	2.24	-- -- Average																																																																																																																																																																																					
6 16500.00	53.52	68.20	-14.68	37.01	40.80	18.84	45.85	2.72	-- -- Peak																																																																																																																																																																																					





Mode	3	
	Harmonic	
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 HORIZONTAL Mode : 1 Setting :	 Site : 03CH23-HY Condition: AVG_54 3m DRH18-E_LE2C05A18EN_240620 VERTICAL Mode : 1 Setting :



Mode	3																																																																																																					
	SHF																																																																																																					
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																					
ANT	1																																																																																																					
Pol.	Horizontal	Vertical																																																																																																				
Peak	 Site : 03CH23-HY Condition: PEAK(UNI) 1m SHF_1224_240624 HORIZONTAL Mode : 3 Setting : <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 39633.56</td><td>48.38</td><td>74.00</td><td>-25.62</td><td>44.92</td><td>45.20</td><td>31.05</td><td>63.25</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 39633.56</td><td>38.44</td><td>54.00</td><td>-15.56</td><td>34.98</td><td>45.20</td><td>31.05</td><td>63.25</td><td>-9.54</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 39633.56	48.38	74.00	-25.62	44.92	45.20	31.05	63.25	-9.54	-- -- PEAK	2 39633.56	38.44	54.00	-15.56	34.98	45.20	31.05	63.25	-9.54	-- -- Average	 Site : 03CH23-HY Condition: PEAK(UNI) 1m SHF_1224_240624 VERTICAL Mode : 3 Setting : <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 39381.22</td><td>48.63</td><td>74.00</td><td>-25.37</td><td>44.63</td><td>45.26</td><td>31.04</td><td>62.76</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 39381.22</td><td>38.84</td><td>54.00</td><td>-15.16</td><td>34.84</td><td>45.26</td><td>31.04</td><td>62.76</td><td>-9.54</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 39381.22	48.63	74.00	-25.37	44.63	45.26	31.04	62.76	-9.54	-- -- PEAK	2 39381.22	38.84	54.00	-15.16	34.84	45.26	31.04	62.76	-9.54	-- -- Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																													
1 39633.56	48.38	74.00	-25.62	44.92	45.20	31.05	63.25	-9.54	-- -- PEAK																																																																																													
2 39633.56	38.44	54.00	-15.56	34.98	45.20	31.05	63.25	-9.54	-- -- Average																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																													
1 39381.22	48.63	74.00	-25.37	44.63	45.26	31.04	62.76	-9.54	-- -- PEAK																																																																																													
2 39381.22	38.84	54.00	-15.16	34.84	45.26	31.04	62.76	-9.54	-- -- Average																																																																																													





Mode	3																																																																																																																																																																																	
	LF																																																																																																																																																																																	
	Bluetooth LE GFSK 2Mbps Ch38 + 11a Ch100 + LTE Band 7 (BW20M 1RB0 QPSK Ch21100)																																																																																																																																																																																	
ANT	1																																																																																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																																																																																
QP/ Peak	 Site : 03CH23-HY Condition: QP 3m CBL61110_62028 & 003_241127 HORIZONTAL Mode : 3 Setting : <table><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>23.31</td><td>40.00</td><td>-16.69</td><td>32.73</td><td>22.68</td><td>0.69</td><td>32.82</td><td>0.03</td><td>-- -- Peak</td></tr><tr><td>2</td><td>95.96</td><td>28.00</td><td>43.50</td><td>-15.50</td><td>43.95</td><td>15.52</td><td>1.22</td><td>32.69</td><td>0.00</td><td>-- -- Peak</td></tr><tr><td>3</td><td>215.27</td><td>33.97</td><td>43.50</td><td>-9.53</td><td>49.09</td><td>14.91</td><td>1.88</td><td>32.78</td><td>0.07</td><td>-- -- Peak</td></tr><tr><td>4</td><td>408.30</td><td>32.69</td><td>46.00</td><td>-13.31</td><td>40.70</td><td>22.06</td><td>2.64</td><td>32.82</td><td>0.11</td><td>-- -- Peak</td></tr><tr><td>5</td><td>751.68</td><td>32.68</td><td>46.00</td><td>-13.32</td><td>33.52</td><td>28.14</td><td>3.71</td><td>32.80</td><td>0.11</td><td>-- -- Peak</td></tr><tr><td>6</td><td>851.59</td><td>33.54</td><td>46.00</td><td>-12.46</td><td>32.86</td><td>29.12</td><td>3.79</td><td>32.38</td><td>0.15</td><td>-- -- Peak</td></tr></table>		Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	33.88	23.31	40.00	-16.69	32.73	22.68	0.69	32.82	0.03	-- -- Peak	2	95.96	28.00	43.50	-15.50	43.95	15.52	1.22	32.69	0.00	-- -- Peak	3	215.27	33.97	43.50	-9.53	49.09	14.91	1.88	32.78	0.07	-- -- Peak	4	408.30	32.69	46.00	-13.31	40.70	22.06	2.64	32.82	0.11	-- -- Peak	5	751.68	32.68	46.00	-13.32	33.52	28.14	3.71	32.80	0.11	-- -- Peak	6	851.59	33.54	46.00	-12.46	32.86	29.12	3.79	32.38	0.15	-- -- Peak	 Site : 03CH23-HY Condition: QP 3m CBL61110_62028 & 003_241127 VERTICAL Mode : 3 Setting : <table><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>31.86</td><td>40.00</td><td>-8.14</td><td>41.28</td><td>22.68</td><td>0.69</td><td>32.82</td><td>0.03</td><td>-- -- Peak</td></tr><tr><td>2</td><td>95.96</td><td>28.45</td><td>43.50</td><td>-15.05</td><td>44.48</td><td>15.52</td><td>1.22</td><td>32.69</td><td>0.00</td><td>-- -- Peak</td></tr><tr><td>3</td><td>184.23</td><td>26.84</td><td>43.50</td><td>-16.66</td><td>42.86</td><td>14.91</td><td>1.74</td><td>32.75</td><td>0.08</td><td>-- -- Peak</td></tr><tr><td>4</td><td>268.86</td><td>25.61</td><td>46.00</td><td>-20.39</td><td>36.15</td><td>20.13</td><td>2.08</td><td>32.83</td><td>0.08</td><td>-- -- Peak</td></tr><tr><td>5</td><td>641.10</td><td>28.71</td><td>46.00</td><td>-17.29</td><td>31.57</td><td>26.60</td><td>3.44</td><td>32.98</td><td>0.08</td><td>-- -- Peak</td></tr><tr><td>6</td><td>958.53</td><td>33.16</td><td>46.00</td><td>-12.84</td><td>29.35</td><td>30.87</td><td>4.27</td><td>31.51</td><td>0.18</td><td>-- -- Peak</td></tr></table>		Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	33.88	31.86	40.00	-8.14	41.28	22.68	0.69	32.82	0.03	-- -- Peak	2	95.96	28.45	43.50	-15.05	44.48	15.52	1.22	32.69	0.00	-- -- Peak	3	184.23	26.84	43.50	-16.66	42.86	14.91	1.74	32.75	0.08	-- -- Peak	4	268.86	25.61	46.00	-20.39	36.15	20.13	2.08	32.83	0.08	-- -- Peak	5	641.10	28.71	46.00	-17.29	31.57	26.60	3.44	32.98	0.08	-- -- Peak	6	958.53	33.16	46.00	-12.84	29.35	30.87	4.27	31.51	0.18	-- -- Peak
		Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																								
1	33.88	23.31	40.00	-16.69	32.73	22.68	0.69	32.82	0.03	-- -- Peak																																																																																																																																																																								
2	95.96	28.00	43.50	-15.50	43.95	15.52	1.22	32.69	0.00	-- -- Peak																																																																																																																																																																								
3	215.27	33.97	43.50	-9.53	49.09	14.91	1.88	32.78	0.07	-- -- Peak																																																																																																																																																																								
4	408.30	32.69	46.00	-13.31	40.70	22.06	2.64	32.82	0.11	-- -- Peak																																																																																																																																																																								
5	751.68	32.68	46.00	-13.32	33.52	28.14	3.71	32.80	0.11	-- -- Peak																																																																																																																																																																								
6	851.59	33.54	46.00	-12.46	32.86	29.12	3.79	32.38	0.15	-- -- Peak																																																																																																																																																																								
	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																								
1	33.88	31.86	40.00	-8.14	41.28	22.68	0.69	32.82	0.03	-- -- Peak																																																																																																																																																																								
2	95.96	28.45	43.50	-15.05	44.48	15.52	1.22	32.69	0.00	-- -- Peak																																																																																																																																																																								
3	184.23	26.84	43.50	-16.66	42.86	14.91	1.74	32.75	0.08	-- -- Peak																																																																																																																																																																								
4	268.86	25.61	46.00	-20.39	36.15	20.13	2.08	32.83	0.08	-- -- Peak																																																																																																																																																																								
5	641.10	28.71	46.00	-17.29	31.57	26.60	3.44	32.98	0.08	-- -- Peak																																																																																																																																																																								
6	958.53	33.16	46.00	-12.84	29.35	30.87	4.27	31.51	0.18	-- -- Peak																																																																																																																																																																								



Appendix B. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	Bluetooth - LE GFSK for 2Mbps	10.71	27	37.04	39KHz
1	2.4GHz 802.11ax HE20 Full RU	87.58	1044	0.96	1kHz
1	5GHz 802.11a	90.38	1428	0.70	750Hz



—THE END—