



FCC RADIO TEST REPORT

FCC ID : A4RG1MNW
Equipment : Phone
Model Name : G1MNW
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Feb. 06, 2023 and testing was performed from Mar. 17, 2023 to Jun. 08, 2023. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	10
1.4 Testing Location	10
1.5 Applicable Standards.....	10
2 Test Configuration of Equipment Under Test	11
2.1 Carrier Frequency and Channel	11
2.2 Test Mode	14
2.3 Connection Diagram of Test System.....	17
2.4 Support Unit used in test configuration and system	18
2.5 EUT Operation Test Setup	18
2.6 Measurement Results Explanation Example.....	18
3 Test Result	19
3.1 26dB & 99% Occupied Bandwidth Measurement	19
3.2 Fundamental Maximum EIRP Measurement	23
3.3 Fundamental Power Spectral Density Measurement	24
3.4 In-Band Emissions (Channel Mask)	31
3.5 Contention Based Protocol	122
3.6 Unwanted Emissions Measurement	145
3.7 AC Conducted Emission Measurement.....	149
3.8 Antenna Requirements	151
4 List of Measuring Equipment	152
5 Measurement Uncertainty	154
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.407(a)(10)	26dB Emission Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)(8)	Fundamental Maximum EIRP	Pass	-
3.3	15.407(a)(8)	Fundamental Power Spectral Density	Pass	-
3.4	15.407(b)(6)	In-Band Emissions (Channel Mask)	Pass	-
3.5	15.407(d)(6)	Contention Based Protocol	Pass	-
3.6	15.407(b)	Unwanted Emissions	Pass	2.66 dB under the limit at 5913.96 MHz
3.7	15.207	AC Conducted Emission	Pass	12.31 dB under the limit at 1.58 MHz
3.8	15.203 15.407(a)	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Clio Lo



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	G1MNW
FCC ID	A4RG1MNW
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/NFC/GNSS/ UWB/WPT WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 WLAN 11be EHT20/EHT40/EHT80/EHT160 Bluetooth BR/EDR/LE/HR

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
S/N	Performed Test Item
33141FDJG000Z1	Conducted Measurement
33141FDJG0003F	Radiated Spurious Emission
31101FDJG0003F	Conducted Emission
35121FDJG0000B	Contention Based Protocol



1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz
Maximum Output Power	MIMO <Ant. 3+4> <5925 MHz ~ 6425 MHz> 802.11a: 12.51 dBm / 0.0178 W 802.11ax HE20: 12.82 dBm / 0.0191 W 802.11ax HE40: 15.61 dBm / 0.0364 W 802.11ax HE80: 18.41 dBm / 0.0693 W 802.11ax HE160: 21.41 dBm / 0.1384 W 802.11be EHT20: 12.97 dBm / 0.0198 W 802.11be EHT40: 15.96 dBm / 0.0394 W 802.11be EHT 80: 18.82 dBm / 0.0762 W 802.11be EHT 160: 21.61 dBm / 0.1449 W <6425 MHz ~ 6525 MHz> 802.11a: 12.54 dBm / 0.0179 W 802.11ax HE20: 12.89 dBm / 0.0195 W 802.11ax HE40: 15.75 dBm / 0.0376 W 802.11ax HE80: 18.59 dBm / 0.0723 W 802.11ax HE160: 21.64 dBm / 0.1459 W 802.11be EHT20: 13.14 dBm / 0.0206 W 802.11be EHT40: 15.94 dBm / 0.0393 W 802.11be EHT80: 18.89 dBm / 0.0774 W 802.11be EHT160: 21.78 dBm / 0.1507 W <6525 MHz ~ 6875 MHz> 802.11a: 13.24 dBm / 0.0211 W 802.11ax HE20: 13.34 dBm / 0.0216 W 802.11ax HE40: 16.48 dBm / 0.0445 W 802.11ax HE80: 19.38 dBm / 0.0867 W 802.11ax HE160: 22.18 dBm / 0.1652 W 802.11be EHT20: 13.39 dBm / 0.0218 W 802.11be EHT40: 16.63 dBm / 0.0460 W 802.11be EHT80: 19.58 dBm / 0.0908 W 802.11be EHT160: 22.23 dBm / 0.1671 W <6875 MHz ~ 7125 MHz> 802.11a: 14.03dBm / 0.0253 W 802.11ax HE20: 14.08 dBm / 0.0256 W 802.11ax HE40: 16.78 dBm / 0.0476 W 802.11ax HE80: 19.48 dBm / 0.0887 W 802.11ax HE160: 22.29 dBm / 0.1694 W 802.11be EHT20: 14.13 dBm / 0.0259 W 802.11be EHT40: 17.08 dBm / 0.0511 W 802.11be EHT80: 19.63 dBm / 0.0918 W 802.11be EHT160: 22.39 dBm / 0.1734 W



Product Specification is subject to this standard	
99% Occupied Bandwidth	MIMO <Ant. 3> 802.11a: 17.38 MHz 802.11be EHT20: 19.23 MHz 802.11be EHT40: 37.96 MHz 802.11be EHT80: 77.44 MHz 802.11be EHT160: 157.76 MHz MIMO <Ant. 4> 802.11a: 17.13 MHz 802.11be EHT20: 19.23 MHz 802.11be EHT40: 37.96 MHz 802.11be EHT80: 77.32 MHz 802.11be EHT160: 157.76 MHz
Antenna Type	<5925 MHz ~ 6425 MHz> <Ant. 3> : PIFA Antenna <Ant. 4> : IFA Antenna <6425 MHz ~ 6525 MHz> <Ant. 3> : PIFA Antenna <Ant. 4> : IFA Antenna <6525 MHz ~ 6875 MHz> <Ant. 3> : PIFA Antenna <Ant. 4> : IFA Antenna <6875 MHz ~ 7125 MHz> <Ant. 3> : PIFA Antenna <Ant. 4> : IFA Antenna
Antenna Gain	<5925 MHz ~ 6425 MHz> <Ant. 3> : -3.9 dBi <Ant. 4> : -5.4 dBi <6425 MHz ~ 6525 MHz> <Ant. 3> : -3.7 dBi <Ant. 4> : -5.8 dBi <6525 MHz ~ 6875 MHz> <Ant. 3> : -4.7 dBi <Ant. 4> : -5.9 dBi <6875 MHz ~ 7125 MHz> <Ant. 3> : -6.7 dBi <Ant. 4> : -4.4 dBi



Product Specification is subject to this standard			
Type of Modulation	802.11a : OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ax : OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM) 802.11be : OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM/ 4096QAM)		
Antenna Function Description	802.11a/ax/be MIMO	Ant. 3 V	Ant. 4 V

Remark:

1. MIMO Ant. 3+4 Directional Gain is a calculated result from MIMO Ant. 3 and MIMO Ant. 4. The formula used in calculation is documented in section 1.2.1.
2. Power of MIMO Ant. 3 + Ant. 4 is a calculated result from sum of the power MIMO Ant. 3 and MIMO Ant. 4.
3. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
4. The CBP antenna gain is considering the minimum gain from closed mode as worse case.



1.2.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F(2)f(ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$Directional\ Gain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ dBi

Where $G1, G2, \dots, GN$ denote single antenna gain.

The directional gain “DG” is calculated as following table.

	Ant 3 (dBi)	Ant 4 (dBi)	DG	DG
			for	for
			Power (dBi)	PSD (dBi)
5925 MHz ~ 6425 MHz	-3.90	-5.40	-3.90	-1.61
6425 MHz ~ 6525 MHz	-3.70	-5.80	-3.70	-1.68
6525 MHz ~ 6875 MHz	-4.70	-5.90	-4.70	-2.27
6875 MHz ~ 7125 MHz	-6.70	-4.40	-4.40	-2.46

Calculation example:

If a device has two antenna, $G_{ANT1} = -3.9$ dBi; $G_{ANT2} = -5.4$ dBi

Directional gain of power measurement = $\max(-3.9, -5.4) + 0 = -3.9$ dBi

Directional gain of PSD derived from formula which is

$$10 \cdot \log \{ \{ [10^{(-3.9 \text{ dBi} / 20)} + 10^{(-5.4 \text{ dBi} / 20)}]^2 \} / 2 \} = -1.61 \text{ dBi}$$



1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sportun International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sportun Site No. CO05-HY, DF02-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sportun International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sportun Site No. TH05-HY, 03CH22-HY (TAF Code: 3786)
Remark	The Conducted and Unwanted Emissions test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 987594 D02 U-NII 6 GHz EMC Measurement v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, , the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

BW 20M	Channel	1	5	9	13	17	21	25	29				
	Freq. (MHz)	5955	5975	5995	6015	6035	6055	6075	6095				
BW 40M	Channel	3		11		19		27					
	Freq. (MHz)	5965		6005		6045		6085					
BW 80M	Channel	7				23							
	Freq. (MHz)	5985				6065							
BW 160M	Channel	15											
	Freq. (MHz)	6025											

BW 20M	Channel	33	37	41	45	49	53	57	61				
	Freq. (MHz)	6115	6135	6155	6175	6195	6215	6235	6255				
BW 40M	Channel	35		43		51		59					
	Freq. (MHz)	6125		6165		6205		6245					
BW 80M	Channel	39				55							
	Freq. (MHz)	6145				6225							
BW 160M	Channel	47											
	Freq. (MHz)	6185											



BW 20M	Channel	65	69	73	77	81	85	89	93				
	Freq. (MHz)	6275	6295	6315	6335	6355	6375	6395	6415				
BW 40M	Channel	67		75		83		91					
	Freq. (MHz)	6285		6325		6365		6405					
BW 80M	Channel	71			87								
	Freq. (MHz)	6305			6385								
BW 160M	Channel	79											
	Freq. (MHz)	6345											

BW 20M	Channel	97	101	105	109	113	117	121	125				
	Freq. (MHz)	6435	6455	6475	6495	6515	6535	6555	6575				
BW 40M	Channel	99		107		115		123					
	Freq. (MHz)	6445		6485		6525		6565					
BW 80M	Channel	103			119								
	Freq. (MHz)	6465			6545								
BW 160M	Channel	111											
	Freq. (MHz)	6505											

BW 20M	Channel	129	133	137	141	145	149	153	157				
	Freq. (MHz)	6595	6615	6635	6655	6675	6695	6715	6735				
BW 40M	Channel	131		139		147		155					
	Freq. (MHz)	6605		6645		6685		6725					
BW 80M	Channel	135			151								
	Freq. (MHz)	6625			6705								
BW 160M	Channel	143											
	Freq. (MHz)	6665											

BW 20M	Channel	161	165	169	173	177	181	185	189				
	Freq. (MHz)	6755	6775	6795	6815	6835	6855	6875	6895				
BW 40M	Channel	163		171		179		187					
	Freq. (MHz)	6765		6805		6845		6885					
BW 80M	Channel	167			183								
	Freq. (MHz)	6785			6865								
BW 160M	Channel	175											
	Freq. (MHz)	6825											



BW 20M	Channel	193	197	201	205	209	213	217	221
	Freq. (MHz)	6915	6935	6955	6975	6995	7015	7035	7055
BW 40M	Channel	195		203		211		219	
	Freq. (MHz)	6925		6965		7005		7045	
BW 80M	Channel	199		215		215		219	
	Freq. (MHz)	6945		7025		7025		7045	
BW 160M	Channel	207		215		219		221	
	Freq. (MHz)	6985		7045		7095		7115	
BW 20M	Channel	225		229		231		233	
	Freq. (MHz)	7075		7095		7115		7135	
BW 40M	Channel	227		231		233		235	
	Freq. (MHz)	7085		7105		7125		7145	



2.2 Test Mode

This device supports WiFi 802.11be 20MHz bandwidth for 2.4GHz and 160MHz bandwidth for both 5GHz and 6GHz.

This device supports 26/52/106/242/484/996 single tone RU modes for 802.11ax/be modes and the 242/484/996-tone RU modes are covered by 20/40/80MHz channels.

This device supports MRU 52T+26T/106T+26T (small RU) and punctured modes (large RU) for 802.11be mode.

The PSD of partial RU/MRU modes are reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2018 and Oct. 2022 for WiFi 7 device.

The 802.11ax/be modes are investigated among full RU, single RU and MRU modes for emission spot check and the 11ax modes are covered by 11be modes.

The PSD and power of partial RU and MRU are less than full RU configurations so the full RU is chosen as main test configuration.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is chosen as main test configuration..

The power for 802.11n, 802.11ac and 802.11ax mode is smaller than 802.11be mode, so all other conducted and radiated test is covered by 802.11be mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11ax HE20 (Covered by EHT20)	MCS0
802.11ax HE40 (Covered by EHT40)	MCS0
802.11ax HE80 (Covered by EHT80)	MCS0
802.11ax HE160 (Covered by EHT160)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0
802.11be EHT160	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.



Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + WLAN (6GHz) Link + Bluetooth Link + USB Cable 1 (Charging from AC Adapter 2)
Remark: 1. For Radiated Test Cases, the tests were performed with AC Adapter 1 and USB Cable 1. 2. During the preliminary test, both charging modes (Adapter mode and WPT mode) were verified. It is determined that the adaptor mode is the worst case for official test.	

Based on ANSI C63.10 clause 5.6.2.2, b) spurious emissions,

Measure the mode with the highest output power and the mode with highest output power spectral density for each modulation family.

		5.6.2.2 (b) Spurious Emissions
UNII-5	20MHz	Covered by 160MHz
	40MHz	Covered by 160MHz
	80MHz	Covered by 160MHz
	160MHz	Test
UNII-6	20MHz	Covered by 160MHz
	40MHz	Covered by 160MHz
	80MHz	Covered by 160MHz
	160MHz	Test
UNII-7	20MHz	Covered by 160MHz
	40MHz	Covered by 160MHz
	80MHz	Covered by 160MHz
	160MHz	Test
UNII-8	20MHz	Covered by 160MHz
	40MHz	Covered by 160MHz
	80MHz	Covered by 160MHz
	160MHz	Test



Ch. #		UNII-5 (5925-6425 MHz)	UNII-6 (6425-6525 MHz)	UNII-7 (6525-6875 MHz)	UNII-8 (6875-7125 MHz)
		802.11be EHT20	802.11be EHT20	802.11be EHT20	802.11be EHT20
L	Low	001	-	-	-
M	Middle	-	-	-	-
H	High	-	-	-	229
Straddle		-	-	-	-

Ch. #		UNII-5 (5925-6425 MHz)	UNII-6 (6425-6525 MHz)	UNII-7 (6525-6875 MHz)	UNII-8 (6875-7125 MHz)
		802.11be EHT40	802.11be EHT40	802.11be EHT40	802.11be EHT40
L	Low	003	-	-	-
M	Middle	-	-	-	-
H	High	-	-	-	227
Straddle		-	-	-	-


Ch. #		UNII-5 (5925-6425 MHz)	UNII-6 (6425-6525 MHz)	UNII-7 (6525-6875 MHz)	UNII-8 (6875-7125 MHz)
		802.11be EHT80	802.11be EHT80	802.11be EHT80	802.11be EHT80
L	Low	007		-	-
M	Middle	-	-	-	-
H	High	-		-	215
Straddle		-	-	-	-

Ch. #		UNII-5 (5925-6425 MHz)	UNII-6 (6425-6525 MHz)	UNII-7 (6525-6875 MHz)	UNII-8 (6875-7125 MHz)
		802.11be EHT160	802.11be EHT160	802.11be EHT160	802.11be EHT160
L	Low	015			
M	Middle	047	-	143	207
H	High	079			
Straddle		-	111	175	-


Remark: Based on ANSI C63.10 clause 5.6.2.2, b) Spurious emissions, measure the mode with the highest output power and the mode with highest output power spectral density for each modulation family.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Wireless Earphone	Google	G1007/G1008	A4RG1007/ A4RG1008	N/A	N/A
3.	WLAN AP	NETGEAR64	RAXE500	N/A	N/A	Unshielded, 1.8m
4.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “CMD v.10.0.18362.1256” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Limit of 26dB & 99% Occupied Bandwidth

<FCC 14-30 CFR 15.407>

(a)(10) The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
8. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.




MIMO <Ant. 3+4>

<802.11a>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


<802.11be EHT20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11be EHT40>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


<802.11be EHT80>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11be EHT160>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Fundamental Maximum EIRP Measurement

3.2.1 Limit of Fundamental Maximum EIRP

<FCC 14-30 CFR 15.407>

(a)(8) For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Fundamental Maximum EIRP

Please refer to Appendix A.



3.3 Fundamental Power Spectral Density Measurement

3.3.1 Limit of Fundamental Power Spectral Density

<FCC 14-30 CFR 15.407>

(a)(8) For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW \geq 3 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.


1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points; the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.



3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



<802.11a>

Maximum Power Density Plot (dBm/MHz)

**Note:**

1. EIRP Power Density (dBm/MHz) = Measured value + Duty Factor + Directional Gain
2. The test plot is showing a bin by bin combined result mathematically adds two traces.

Power Density Plot Trace 1 (Ant 3)




Power Density Plot Trace 2 (Ant 4)






<802.11be EHT20 Full RU>

Maximum Power Density Plot (dBm/MHz)


**Note:**

1. EIRP Power Density (dBm/MHz) = Measured value + Duty Factor + Directional Gain
2. The test plot is showing a bin by bin combined result mathematically adds two traces.

Power Density Plot Trace 1 (Ant 3)




Power Density Plot Trace 2 (Ant 4)






<802.11be EHT40 Full RU>

Maximum Power Density Plot (dBm/MHz)

**Note:**

1. EIRP Power Density (dBm/MHz) = Measured value + Duty Factor + Directional Gain
2. The test plot is showing a bin by bin combined result mathematically adds two traces.

Power Density Plot Trace 1 (Ant 3)




Power Density Plot Trace 2 (Ant 4)






<802.11be EHT80 Full RU>

Maximum Power Density Plot (dBm/MHz)


**Note:**

1. EIRP Power Density (dBm/MHz) = Measured value + Duty Factor + Directional Gain
2. The test plot is showing a bin by bin combined result mathematically adds two traces.

Power Density Plot Trace 1 (Ant 3)




Power Density Plot Trace 2 (Ant 4)






<802.11be EHT160 Full RU>

Maximum Power Density Plot (dBm/MHz)


**Note:**

1. EIRP Power Density (dBm/MHz) = Measured value + Duty Factor + Directional Gain
2. The test plot is showing a bin by bin combined result mathematically adds two traces.

Power Density Plot Trace 1 (Ant 3)



Power Density Plot Trace 2 (Ant 4)





3.4 In-Band Emissions (Channel Mask)

3.4.1 Limit of Unwanted Emissions

<FCC 14-30 CFR 15.407>

(a)(6) For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

The testing follows FCC KDB 987594 D02 U-NII 6GHz EMC Measurement v01.

Section J) In-Band Emissions.

1. Take nominal bandwidth as reference channel bandwidth provided that 26 dB emission bandwidth is always larger than nominal bandwidth
2. Measure the power spectral density (which will be used for emissions mask reference) using the following procedure:
 - a) Set the span to encompass the entire 26 dB EBW of the signal.
 - b) Set RBW = same RBW used for 26 dB EBW measurement.
 - c) Set VBW $\geq 3 \times$ RBW
 - d) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$.
 - e) Sweep time = auto.
 - f) Detector = RMS (i.e., power averaging)
 - g) Trace average at least 100 traces in power averaging (rms) mode.
 - h) Use the peak search function on the instrument to find the peak of the spectrum.
3. Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
 - a. Suppressed by 20 dB at 1 MHz outside of the channel edge.
 - b. Suppressed by 28 dB at one channel bandwidth from the channel center.
 - c. Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
4. Adjust the span to encompass the entire mask as necessary.
5. Clear trace.
6. Trace average at least 100 traces in power averaging (rms) mode.
7. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

3.4.4 Test Setup






3.4.5 Test Result

MIMO <Ant. 3+4(3)>


EUT Mode : 802.11a

Plot on Channel 5955 MHz




Date: 6.MAY.2023 04:00:39

Plot on Channel 6195 MHz




Date: 6.MAY.2023 04:09:08

Plot on Channel 6415 MHz



Date: 6.MAY.2023 06:50:18


Plot on Channel 6435 MHz



Date: 6.MAY.2023 04:31:00




Plot on Channel 6475 MHz




Date: 6.MAY.2023 04:37:58

Plot on Channel 6515 MHz




Date: 6.MAY.2023 04:53:34

Plot on Channel 6535 MHz



Date: 6.MAY.2023 05:02:57


Plot on Channel 6695 MHz



Date: 6.MAY.2023 05:14:02




Plot on Channel 6855 MHz




Date: 6.MAY.2023 05:24:36

Plot on Channel 6875 MHz




Date: 6.MAY.2023 05:52:48

Plot on Channel 6995 MHz



Date: 6.MAY.2023 06:13:30

Plot on Channel 7095 MHz




Date: 6.MAY.2023 06:46:09




EUT Mode : 802.11be EHT20 Full RU

Plot on Channel 5955 MHz




Date: 6.MAY.2023 07:13:15

Plot on Channel 6195 MHz




Date: 6.MAY.2023 07:20:30

Plot on Channel 6415 MHz



Date: 6.MAY.2023 07:28:54


Plot on Channel 6435 MHz



Date: 6.MAY.2023 08:08:01




Plot on Channel 6475 MHz




Date: 6.MAY.2023 08:15:08

Plot on Channel 6515 MHz




Date: 9.MAY.2023 07:27:41

Plot on Channel 6535 MHz



Date: 9.MAY.2023 07:38:18


Plot on Channel 6695 MHz



Date: 9.MAY.2023 07:48:36




Plot on Channel 6855 MHz




Date: 9.MAY.2023 07:59:40

Plot on Channel 6875 MHz




Date: 9.MAY.2023 08:06:35

Plot on Channel 6995 MHz



Date: 9.MAY.2023 08:16:59

Plot on Channel 7095 MHz




Date: 9.MAY.2023 23:32:46



EUT Mode


802.11be EHT20 26RU0

Plot on Channel 5955 MHz




Date: 30.MAY.2023 00:42:36

Plot on Channel 6435 MHz



Date: 30.MAY.2023 01:16:12

Plot on Channel 6535 MHz




Date: 30.MAY.2023 20:00:23



EUT Mode


802.11be EHT20 26RU4

Plot on Channel 6195 MHz




Date: 30.MAY.2023 00:55:07

Plot on Channel 6475 MHz




Date: 30.MAY.2023 21:07:41

Plot on Channel 6695 MHz



Date: 30.MAY.2023 20:03:53

Plot on Channel 6995 MHz




Date: 30.MAY.2023 20:20:22



EUT Mode


802.11be EHT20 26RU8

Plot on Channel 6415 MHz




Date: 30.MAY.2023 01:04:28

Plot on Channel 6515 MHz




Date: 30.MAY.2023 19:45:42

Plot on Channel 6855 MHz



Date: 30.MAY.2023 20:08:08


Plot on Channel 6875 MHz



Date: 30.MAY.2023 20:16:48



Plot on Channel 7095 MHz




Date: 30.MAY.2023 20:26:35



EUT Mode


802.11be EHT20 52RU37

Plot on Channel 5955 MHz




Date: 30.MAY.2023 00:47:17

Plot on Channel 6435 MHz



Date: 30.MAY.2023 01:21:32

Plot on Channel 6535 MHz




Date: 30.MAY.2023 21:18:48



EUT Mode


802.11be EHT20 52RU38

Plot on Channel 6195 MHz




Date: 30.MAY.2023 01:45:09

Plot on Channel 6475 MHz




Date: 30.MAY.2023 21:12:02

Plot on Channel 6695 MHz



Date: 30.MAY.2023 21:35:39

Plot on Channel 6995 MHz




Date: 30.MAY.2023 21:48:00



EUT Mode


802.11be EHT20 52RU40

Plot on Channel 6415 MHz




Date: 30.MAY.2023 01:08:06

Plot on Channel 6515 MHz




Date: 30.MAY.2023 21:15:36

Plot on Channel 6855 MHz



Date: 30.MAY.2023 21:38:16


Plot on Channel 6875 MHz



Date: 30.MAY.2023 21:41:41



Plot on Channel 7095 MHz




Date: 30.MAY.2023 22:03:59



EUT Mode


802.11be EHT20 106RU53

Plot on Channel 5955 MHz




Date: 30.MAY.2023 00:50:29

Plot on Channel 6195 MHz




Date: 30.MAY.2023 01:01:08

Plot on Channel 6435 MHz



Date: 30.MAY.2023 01:30:01


Plot on Channel 6475 MHz



Date: 30.MAY.2023 22:27:01




Plot on Channel 6535 MHz




Date: 30.MAY.2023 22:35:07

Plot on Channel 6695 MHz



Date: 30.MAY.2023 22:38:26

Plot on Channel 6995 MHz




Date: 30.MAY.2023 22:55:44



EUT Mode


802.11be EHT20 106RU54

Plot on Channel 6415 MHz




Date: 30.MAY.2023 01:11:56

Plot on Channel 6515 MHz




Date: 30.MAY.2023 22:29:58

Plot on Channel 6855 MHz



Date: 30.MAY.2023 22:44:37


Plot on Channel 6875 MHz



Date: 30.MAY.2023 22:50:27



Plot on Channel 7095 MHz






EUT Mode


802.11be EHT20 MRU 106T+26T82

Plot on Channel 5955 MHz




Date: 8.JUN.2023 12:17:31

Plot on Channel 6435 MHz



Date: 8.JUN.2023 16:14:52

Plot on Channel 6535 MHz



Date: 8.JUN.2023 18:11:54