



FCC RADIO TEST REPORT

FCC ID : A4RG4QUR
Equipment : Phone
Model Name : G4QUR
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Dec. 12, 2024 and testing was performed from Dec. 20, 2024 to Mar. 21, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement	12
3.3 Dwell Time Measurement.....	13
3.4 20dB and 99% Bandwidth Measurement	14
3.5 Output Power Measurement.....	15
3.6 Conducted Band Edges Measurement.....	16
3.7 Conducted Spurious Emission Measurement	17
3.8 Radiated Band Edges and Spurious Emission Measurement	18
3.9 AC Conducted Emission Measurement.....	22
3.10 Antenna Requirements.....	24
4 List of Measuring Equipment	25
5 Measurement Uncertainty	27
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4N0917K	01	Initial issue of report	Mar. 27, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Pass	-
3.5	15.247(b)(1) 15.247(b)(4)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.9	15.207	AC Conducted Emission	Pass	-
3.10	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Clio Lo

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN , Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx.
Antenna Type Bluetooth: <Ant. 3> : IFA Antenna <Ant. 4> : ILA Antenna

EUT Information List	
S/N	Performed Test Item
4B251FDCH0002V	RF Conducted Measurement
4B201FDCH0000X	Radiated Spurious Emission
51091FDCH0006V	Conducted Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant.3: 1.9 Ant.4: 1.9

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH13-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2404-2478 MHz	2	2404	32	2434	59	2461
	3	2405	33	2435	60	2462
	4	2406	34	2436	61	2463
	5	2407	35	2437	62	2464
	6	2408	36	2438	63	2465
	7	2409	37	2439	64	2466
	8	2410	38	2440	65	2467
	9	2411	39	2441	66	2468
	10	2412	40	2442	67	2469
	11	2413	41	2443	68	2470
	12	2414	42	2444	69	2471
	13	2415	43	2445	70	2472
	14	2416	44	2446	71	2473
	15	2417	45	2447	72	2474
	16	2418	46	2448	73	2475
	17	2419	47	2449	74	2476
	18	2420	48	2450	75	2477
	19	2421	49	2451	76	2478
	20	2422	50	2452	-	-
	21	2423	51	2453	-	-
	22	2424	52	2454	-	-
	26	2428	53	2455	-	-
	27	2429	54	2456	-	-
	28	2430	55	2457	-	-
	29	2431	56	2458	-	-
	30	2432	57	2459	-	-
	31	2433	58	2460	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz) radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z plane with Adapter as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases		
Test Item	Data Rate / Modulation	
Conducted Test Cases	Bluetooth LE 1Mbps CS ASK	Bluetooth LE 2Mbps CS ASK
	Mode 1: CH02_2404 MHz	Mode 4: CH02_2404 MHz
	Mode 2: CH38_2440 MHz	Mode 5: CH38_2440 MHz
	Mode 3: CH76_2478 MHz	Mode 6: CH76_2478 MHz
AC Conducted Emission	Mode 1 : BLE CS Channel 19 TX + USB Cable 2 (Charging from Adapter)	
Remark: 1. For Radiated Test Cases, the worst mode data rate 2Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 2Mbps, and no other significantly frequencies found in conducted spurious emission. 2. For Radiated Test Cases, the tests were performed with USB Cable 2. 3. During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test. 4. The detailed Radiated test modes are shown in Appendix C.		

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth-LE CS Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BT DUT Control GUI v.03-04-24” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW within 1-5% of the 99% bandwidth; VBW $\geq$ 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.
If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. The average power is compensated with duty factor.
6. Record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.8.3 Test Procedures


1. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT is arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW $\geq$ 10Hz; Sweep = auto; Detector function = peak; Trace = max hold for average
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
8. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Duty Cycle

Please refer to Appendix D.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.9.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.10.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	Dec. 28, 2024~ Mar. 07, 2025	Aug. 28, 2025	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9k~30M	Apr. 22, 2024	Dec. 28, 2024~ Mar. 07, 2025	Apr. 21, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX6-7268- 9200-26500-40 CD	SN2	9GHz High Pass Filter	May 22, 2024	Dec. 28, 2024~ Mar. 07, 2025	May 21, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN5	6.75GHz High Pass Filter	Mar. 08, 2024	Dec. 28, 2024~ Mar. 06, 2025	Mar. 07, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN5	6.75GHz High Pass Filter	Mar. 07, 2025	Mar. 07, 2025	Mar. 06, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN12	1.53GHz Low Pass Filter	Sep. 11, 2024	Dec. 28, 2024~ Mar. 07, 2025	Sep. 10, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX12-2700 -3000-18000-6 0SS	SN3	3GHz High Pass Filter	Jul. 09, 2024	Dec. 28, 2024~ Mar. 07, 2025	Jul. 08, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WRCQV14-60 25-6425-7125- 7525-60SS	SN2	N/A	Jan. 05, 2024	Dec. 28, 2024~ Jan. 02, 2025	Jan. 04, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WRCQV14-60 25-6425-7125- 7525-60SS	SN2	N/A	Jan. 03, 2025	Jan. 03, 2025~ Mar. 07, 2025	Jan. 02, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WRCQV14-54 25-5825-6525- 6925-60SS	SN1	N/A	Jan. 05, 2024	Dec. 28, 2024~ Jan. 02, 2025	Jan. 04, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WRCQV14-54 25-5825-6525- 6925-60SS	SN1	N/A	Jan. 03, 2025	Jan. 03, 2025~ Mar. 07, 2025	Jan. 02, 2026	Radiation (03CH13-HY)
Amplifier	SONOMA	310N	187282	9kHz~1GHz	Dec. 12, 2024	Dec. 28, 2024~ Mar. 07, 2025	Dec. 11, 2025	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	40103 & 07	30MHz~1GHz	Apr. 12, 2024	Dec. 28, 2024~ Mar. 07, 2025	Apr. 11, 2025	Radiation (03CH13-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	Sep. 09, 2024	Dec. 28, 2024~ Mar. 07, 2025	Sep. 08, 2025	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Aug. 15, 2024	Dec. 28, 2024~ Mar. 07, 2025	Aug. 14, 2025	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP215159	N/A	Sep. 10, 2024	Dec. 28, 2024~ Mar. 07, 2025	Sep. 09, 2025	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 15, 2024	Dec. 28, 2024~ Mar. 07, 2025	May 14, 2025	Radiation (03CH13-HY)
Preamplifier	EM Electronics	EM01G18G	060803	1GHz-18GHz	Jan. 09, 2024	Dec. 28, 2024~ Jan. 07, 2025	Jan. 08, 2025	Radiation (03CH13-HY)
Preamplifier	EM Electronics	EM01G18G	060803	1GHz-18GHz	Jan. 08, 2025	Jan. 08, 2025~ Mar. 07, 2025	Jan. 07, 2026	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Jan. 18, 2024	Dec. 28, 2024~ Jan. 05, 2025	Jan. 17, 2025	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010B	MY62170337	10Hz~44GHz	Aug. 21, 2024	Jan. 06, 2025~ Jan. 10, 2025	Aug. 20, 2025	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Jan. 11, 2025	Jan. 11, 2025~ Mar. 07, 2025	Jan. 10, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30MHz~18GHz	Feb. 07, 2024	Dec. 28, 2024~ Feb. 05, 2025	Feb. 06, 2025	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30MHz~18GHz	Feb. 06, 2025	Feb. 06, 2025~ Mar. 07, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804616/2	30MHz~40GHz	Jul. 18, 2024	Dec. 28, 2024~ Feb. 05, 2025	Jul. 17, 2025	Radiation (03CH13-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804616/2	30MHz~40GHz	Feb. 06, 2025	Feb. 06, 2025~ Mar. 07, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30MHz~18GHz	Feb. 07, 2024	Dec. 28, 2024~ Feb. 05, 2025	Feb. 06, 2025	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30MHz~18GHz	Feb. 06, 2025	Feb. 06, 2025~ Mar. 07, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 28, 2024~ Mar. 07, 2025	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Dec. 28, 2024~ Mar. 07, 2025	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Dec. 28, 2024~ Mar. 07, 2025	N/A	Radiation (03CH13-HY)
Software	Audix	N/A	RK-001124	N/A	N/A	Dec. 28, 2024~ Mar. 07, 2025	N/A	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Dec. 28, 2024~ Mar. 07, 2025	May 26, 2025	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1224	18GHz~40GHz	Jun. 24, 2024	Dec. 28, 2024~ Mar. 07, 2025	Jun. 23, 2025	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Dec. 20, 2024~ Mar. 14, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 37 (NO:167)	10MHz~6GHz	Nov. 21, 2024	Dec. 20, 2024~ Mar. 14, 2025	Nov. 20, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	Dec. 20, 2024~ Mar. 14, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Dec. 20, 2024~ Mar. 14, 2025	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24121 1	N/A	Conducted Other Test Item	N/A	Dec. 20, 2024~ Mar. 14, 2025	N/A	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 19, 2025~ Mar. 21, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 19, 2025~ Mar. 21, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBE CK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 23, 2024	Mar. 19, 2025~ Mar. 21, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Mar. 19, 2025~ Mar. 21, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Lisn	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 12, 2024	Mar. 19, 2025~ Mar. 21, 2025	Dec. 11, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Mar. 19, 2025~ Mar. 21, 2025	Sep. 22, 2025	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2024/12/20~2025/3/14	Relative Humidity:	51~54	%

<Ant. 3>

TEST RESULTS DATA									
20dB and 99% Occupied Bandwidth and Hopping Channel Separation									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20dB BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
ASK	1Mbps	1	2	2404	0.507	0.507	0.999	0.3379	Pass
	1Mbps	1	38	2440	0.517	0.516	1.007	0.3449	Pass
	1Mbps	1	76	2478	0.523	0.521	1.012	0.3487	Pass
ASK	2Mbps	1	2	2404	0.992	0.987	1.012	0.6616	Pass
	2Mbps	1	38	2440	0.996	0.992	0.994	0.6642	Pass
	2Mbps	1	76	2478	1.023	1.017	1.003	0.6817	Pass

TEST RESULTS DATA						
Dwell Time						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
ASK	72	1762	0.044	0.078	0.4	Pass

TEST RESULTS DATA					
Peak Power Table					
DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
ASK 1Mbps	2	1	19.96	20.97	Pass
	38	1	19.94	20.97	Pass
	76	1	19.57	20.97	Pass
ASK 2Mbps	2	1	19.51	20.97	Pass
	38	1	19.50	20.97	Pass
	76	1	19.75	20.97	Pass

TEST RESULTS DATA				
Average Power Table				
(Reporting Only)				
DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
ASK 1Mbps	2	1	18.99	8.01
	38	1	18.94	8.01
	76	1	18.69	8.01
ASK 2Mbps	2	1	18.55	7.97
	38	1	18.66	7.97
	76	1	18.91	7.97

TEST RESULTS DATA			
Number of Hopping Frequency			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
72	15	> 15	Pass

<Ant. 4>

TEST RESULTS DATA**20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20dB BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
ASK	1Mbps	1	2	2404	0.508	0.508	1.012	0.3384	Pass
	1Mbps	1	38	2440	0.517	0.517	0.981	0.3449	Pass
	1Mbps	1	76	2478	0.523	0.522	0.986	0.3488	Pass
ASK	2Mbps	1	2	2404	0.988	0.982	0.994	0.6586	Pass
	2Mbps	1	38	2440	0.997	0.992	1.016	0.6648	Pass
	2Mbps	1	76	2478	1.021	1.014	0.999	0.6807	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
ASK	72	1817	0.045	0.082	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
ASK 1Mbps	2	1	19.65	20.97	Pass
	38	1	19.96	20.97	Pass
	76	1	19.97	20.97	Pass
ASK 2Mbps	2	1	19.56	20.97	Pass
	38	1	19.78	20.97	Pass
	76	1	19.77	20.97	Pass

TEST RESULTS DATA**Average Power Table
(Reporting Only)**

DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
ASK 1Mbps	2	1	18.79	8.04
	38	1	18.92	8.04
	76	1	18.97	8.04
ASK 2Mbps	2	1	18.56	7.91
	38	1	18.84	7.91
	76	1	18.86	7.91

TEST RESULTS DATA**Number of Hopping Frequency**


Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
72	15	> 15	Pass




<Ant.3>

Number of Hopping Frequency

<1Mbps>



<2Mbps>







Hopping Channel Separation

<1Mbps>


Channel Separation Plot on Channel 02 - 03



Channel Separation Plot on Channel 38 - 39




Channel Separation Plot on Channel 75 - 76






<2Mbps>


Channel Separation Plot on Channel 02 - 03




Channel Separation Plot on Channel 38 - 39



Channel Separation Plot on Channel 75 - 76



Dwell Time



Remark:

1. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

$$= 1762 \times 0.044333 \text{ ms} = 0.078 \text{ sec}$$

2. The observation Occupancy time is hopping channel 72 channels x 400ms = 28.8sec using sweep point 30,000. This shows that 1ms per on-time contains 1 hop.

The total hops is finally counted via computer analysis.







20dB Bandwidth

<1Mbps>


20 dB Bandwidth Plot in Channel 02






20 dB Bandwidth Plot in Channel 38



20 dB Bandwidth Plot in Channel 76









99% Occupied Bandwidth

<1Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38




99% Occupied Bandwidth on Channel 76




<2Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38




99% Occupied Bandwidth on Channel 76






Band Edges

<1Mbps>





<2Mbps>





Hopping Mode Low Band Edge Plot







Conducted Spurious Emission

<1Mbps>


CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz




CSE Plot on High Ch between 1GHz ~ 26.5GHz




<2Mbps>




CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz



CSE Plot on High Ch between 1GHz ~ 26.5GHz







<Ant.4>

Number of Hopping Frequency

<1Mbps>



<2Mbps>







Hopping Channel Separation

<1Mbps>


Channel Separation Plot on Channel 02 - 03



Channel Separation Plot on Channel 38 - 39




Channel Separation Plot on Channel 75 - 76






<2Mbps>


Channel Separation Plot on Channel 02 - 03




Channel Separation Plot on Channel 38 - 39



Channel Separation Plot on Channel 75 - 76



Dwell Time




Remark:

1. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

$$= 1817 \times 0.045 \text{ ms} = 0.082 \text{ sec}$$

2. The observation Occupancy time is hopping channel 72 channels x 400ms = 28.8sec using sweep point 30,000. This shows that 1ms per on-time contains 1 hop.

The total hops is finally counted via computer analysis.







20dB Bandwidth

<1Mbps>


20 dB Bandwidth Plot in Channel 02






20 dB Bandwidth Plot in Channel 38



20 dB Bandwidth Plot in Channel 76









99% Occupied Bandwidth

<1Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38




99% Occupied Bandwidth on Channel 76






<2Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38



99% Occupied Bandwidth on Channel 76







Band Edges

<1Mbps>

Low Band Edge Plot on Channel 02




High Band Edge Plot on Channel 76




<2Mbps>

Low Band Edge Plot on Channel 02




High Band Edge Plot on Channel 76






Hopping Mode Band Edges

<1Mbps>



<2Mbps>







Conducted Spurious Emission

<1Mbps>


CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz




CSE Plot on High Ch between 1GHz ~ 26.5GHz




<2Mbps>




CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz



CSE Plot on High Ch between 1GHz ~ 26.5GHz





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	16.1~22.7℃
		Relative Humidity :	45.9~48.9%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N0917
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	21.95	55.75	33.80	L1	OFF	19.8
0.154500	47.24	---	65.75	18.51	L1	OFF	19.8
0.168000	---	34.48	55.06	20.58	L1	OFF	19.8
0.168000	51.40	---	65.06	13.66	L1	OFF	19.8
0.186000	---	30.29	54.21	23.92	L1	OFF	19.8
0.186000	48.88	---	64.21	15.33	L1	OFF	19.8
0.217500	---	13.07	52.91	39.84	L1	OFF	19.8
0.217500	39.77	---	62.91	23.14	L1	OFF	19.8
0.683250	---	20.89	46.00	25.11	L1	OFF	19.8
0.683250	42.16	---	56.00	13.84	L1	OFF	19.8
5.820000	---	21.65	50.00	28.35	L1	OFF	20.0
5.820000	27.11	---	60.00	32.89	L1	OFF	20.0
22.292250	---	26.75	50.00	23.25	L1	OFF	20.7
22.292250	32.14	---	60.00	27.86	L1	OFF	20.7

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N0917
Mode 1
120Vac/60Hz
Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	23.47	55.63	32.16	N	OFF	19.8
0.156750	47.58	---	65.63	18.05	N	OFF	19.8
0.170835	---	36.97	54.92	17.95	N	OFF	19.8
0.170835	51.95	---	64.92	12.97	N	OFF	19.8
0.185955	---	31.94	54.22	22.28	N	OFF	19.8
0.185955	49.31	---	64.22	14.91	N	OFF	19.8
0.208500	---	13.42	53.27	39.85	N	OFF	19.8
0.208500	40.60	---	63.27	22.67	N	OFF	19.8
0.258000	---	26.12	51.50	25.38	N	OFF	19.8
0.258000	37.55	---	61.50	23.95	N	OFF	19.8
0.684375	---	17.28	46.00	28.72	N	OFF	19.8
0.684375	37.99	---	56.00	18.01	N	OFF	19.8
22.217955	---	23.00	50.00	27.00	N	OFF	20.8
22.217955	28.41	---	60.00	31.59	N	OFF	20.8



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Rain Lee, Jacky Hong and White Hou	Temperature :	20~26℃
		Relative Humidity :	40~65%

Note symbol

-L	Low channel location
-R	High channel location

**C1. Radiated Spurious Emission Test Modes**

<Ant. 3>

<1Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 33	2400-2483.5	3	Bluetooth-LE_ASK	02	2404	1Mbps	-	-
Mode 34	2400-2483.5	3	Bluetooth-LE_ASK	38	2440	1Mbps	-	-
Mode 35	2400-2483.5	3	Bluetooth-LE_ASK	76	2478	1Mbps	-	-
Mode 39	2400-2483.5	3	Bluetooth-LE_ASK	76	2478	1Mbps	-	LF
Mode 40	2400-2483.5	3	Bluetooth-LE_ASK	76	2478	1Mbps	-	SHF

<2Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 36	2400-2483.5	3	Bluetooth-LE_ASK	02	2404	2Mbps	-	-
Mode 37	2400-2483.5	3	Bluetooth-LE_ASK	38	2440	2Mbps	-	-
Mode 38	2400-2483.5	3	Bluetooth-LE_ASK	76	2478	2Mbps	-	-

<Ant. 4>

<1Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 41	2400-2483.5	4	Bluetooth-LE_ASK	02	2404	1Mbps	-	-
Mode 42	2400-2483.5	4	Bluetooth-LE_ASK	38	2440	1Mbps	-	-
Mode 43	2400-2483.5	4	Bluetooth-LE_ASK	76	2478	1Mbps	-	-
Mode 47	2400-2483.5	4	Bluetooth-LE_ASK	76	2478	1Mbps	-	LF
Mode 48	2400-2483.5	4	Bluetooth-LE_ASK	76	2478	1Mbps	-	SHF

<2Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 44	2400-2483.5	4	Bluetooth-LE_ASK	02	2404	2Mbps	-	-
Mode 45	2400-2483.5	4	Bluetooth-LE_ASK	38	2440	2Mbps	-	-
Mode 46	2400-2483.5	4	Bluetooth-LE_ASK	76	2478	2Mbps	-	-

**C2. Summary of each worse mode**

<Ant. 3>

<1Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
33	Bluetooth-LE_ASK	02	2389.52	57.13	74.00	-16.87	H	Peak	Pass	-	Band Edge
28	Bluetooth-LE_ASK	02	4808.00	39.81	74.00	-34.19	H	Peak	Pass	-	Harmonic
34	Bluetooth-LE_ASK	38	2491.12	52.64	74.00	-21.36	H	Peak	Pass	-	Band Edge
29	Bluetooth-LE_ASK	38	7320.00	46.00	74.00	-28.00	V	Peak	Pass	-	Harmonic
35	Bluetooth-LE_ASK	76	2483.57	66.33	74.00	-7.67	H	Peak	Pass	-	Band Edge
30	Bluetooth-LE_ASK	76	7434.00	45.19	74.00	-28.81	V	Peak	Pass	-	Harmonic
39	LF	76	48.56	32.49	40.00	-7.51	V	QP	Pass	-	LF
40	SHF	76	24664.00	41.10	74.00	-32.90	H	Peak	Pass	-	SHF

<2Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
36	Bluetooth-LE_ASK	02	2389.71	56.12	74.00	-17.88	V	Peak	Pass	-	Band Edge
31	Bluetooth-LE_ASK	02	4808.00	40.30	74.00	-33.70	V	Peak	Pass	-	Harmonic
37	Bluetooth-LE_ASK	38	2485.00	53.40	74.00	-20.60	V	Peak	Pass	-	Band Edge
32	Bluetooth-LE_ASK	38	7320.00	46.05	74.00	-27.95	H	Peak	Pass	-	Harmonic
38	Bluetooth-LE_ASK	76	2483.52	67.87	74.00	-6.13	V	Peak	Pass	-	Band Edge
33	Bluetooth-LE_ASK	76	7434.00	45.75	74.00	-28.25	H	Peak	Pass	-	Harmonic



<Ant. 4>

<1Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
41	Bluetooth-LE_ASK	02	2389.61	56.21	74.00	-17.79	H	Peak	Pass	-	Band Edge
34	Bluetooth-LE_ASK	02	4808.00	40.04	74.00	-33.96	V	Peak	Pass	-	Harmonic
42	Bluetooth-LE_ASK	38	2484.58	52.52	74.00	-21.48	H	Peak	Pass	-	Band Edge
35	Bluetooth-LE_ASK	38	7320.00	47.76	74.00	-26.24	V	Peak	Pass	-	Harmonic
43	Bluetooth-LE_ASK	76	2483.57	64.53	74.00	-9.47	H	Peak	Pass	-	Band Edge
36	Bluetooth-LE_ASK	76	7434.00	48.14	74.00	-25.86	V	Peak	Pass	-	Harmonic
47	LF	76	62.01	30.83	40.00	-9.17	H	Peak	Pass	-	LF
48	SHF	76	24752.00	41.02	74.00	-32.98	V	Peak	Pass	-	SHF



<2Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
44	Bluetooth-LE_ASK	02	2389.99	55.67	74.00	-18.33	H	Peak	Pass	-	Band Edge
37	Bluetooth-LE_ASK	02	4808.00	39.59	74.00	-34.41	H	Peak	Pass	-	Harmonic
45	Bluetooth-LE_ASK	38	2497.84	52.91	74.00	-21.09	H	Peak	Pass	-	Band Edge
38	Bluetooth-LE_ASK	38	7320.00	48.11	74.00	-25.89	V	Peak	Pass	-	Harmonic
46	Bluetooth-LE_ASK	76	2483.72	64.71	74.00	-9.29	H	Peak	Pass	-	Band Edge
39	Bluetooth-LE_ASK	76	7434.00	48.57	74.00	-25.43	V	Peak	Pass	-	Harmonic



<Ant. 3>



<1Mbps>

Mode	33																																																																																																																												
	Band Edge																																																																																																																												
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																												
ANT	3																																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																																						
Peak																																																																																																																													
	Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.52</td><td>57.13</td><td>74.00</td><td>-16.87</td><td>49.93</td><td>27.50</td><td>6.74</td><td>36.97</td><td>9.93</td><td>121</td><td>18</td><td>PEAK</td></tr><tr><td>2</td><td>2389.52</td><td>1.21</td><td>54.00</td><td>-52.79</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>121</td><td>18</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.52	57.13	74.00	-16.87	49.93	27.50	6.74	36.97	9.93	121	18	PEAK	2	2389.52	1.21	54.00	-52.79	--	--	--	--	--	121	18	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2404.00</td><td>115.81</td><td>-----</td><td>-----</td><td>100.49</td><td>27.60</td><td>6.76</td><td>36.97</td><td>9.93</td><td>121</td><td>18</td><td>PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>59.89</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>121</td><td>18</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	115.81	-----	-----	100.49	27.60	6.76	36.97	9.93	121	18	PEAK	2	2404.00	59.89	-----	-----	--	--	--	--	--	121	18
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2389.52	57.13	74.00	-16.87	49.93	27.50	6.74	36.97	9.93	121	18	PEAK																																																																																																																	
2	2389.52	1.21	54.00	-52.79	--	--	--	--	--	121	18	AVERAGE																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2404.00	115.81	-----	-----	100.49	27.60	6.76	36.97	9.93	121	18	PEAK																																																																																																																	
2	2404.00	59.89	-----	-----	--	--	--	--	--	121	18	AVERAGE																																																																																																																	



Mode	33																																																																																																																													
	Band Edge																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																													
ANT	3																																																																																																																													
Pol.	Vertical						Fundamental																																																																																																																							
Peak	Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2387.81</td><td>55.34</td><td>74.00</td><td>-18.66</td><td>48.17</td><td>27.48</td><td>6.73</td><td>36.97</td><td>9.93</td><td>400</td><td>111</td><td>PEAK</td></tr><tr><td>2</td><td>2387.81</td><td>-0.58</td><td>54.00</td><td>-54.58</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>400</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.81	55.34	74.00	-18.66	48.17	27.48	6.73	36.97	9.93	400	111	PEAK	2	2387.81	-0.58	54.00	-54.58	--	--	--	--	--	400	111	AVERAGE	Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2404.00</td><td>113.71</td><td>-----</td><td>-----</td><td>106.39</td><td>27.60</td><td>6.76</td><td>36.97</td><td>9.93</td><td>400</td><td>111</td><td>PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>57.79</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>400</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	113.71	-----	-----	106.39	27.60	6.76	36.97	9.93	400	111	PEAK	2	2404.00	57.79	-----	-----	--	--	--	--	--	400	111	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2387.81	55.34	74.00	-18.66	48.17	27.48	6.73	36.97	9.93	400	111	PEAK																																																																																																																		
2	2387.81	-0.58	54.00	-54.58	--	--	--	--	--	400	111	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2404.00	113.71	-----	-----	106.39	27.60	6.76	36.97	9.93	400	111	PEAK																																																																																																																		
2	2404.00	57.79	-----	-----	--	--	--	--	--	400	111	AVERAGE																																																																																																																		



Mode	33																																																																																																																																																		
	Harmonic																																																																																																																																																		
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																																																		
ANT	3																																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																																												
Peak Avg																																																																																																																																																			
	Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL						Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL																																																																																																																																												
<table><tr><th></th><th></th><th colspan="3">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4808.00</td><td>39.81</td><td>74.00</td><td>-34.19</td><td>54.74</td><td>32.43</td><td>9.37</td><td>57.43</td><td>0.70</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4808.00</td><td>-15.81</td><td>54.00</td><td>-69.81</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>														Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4808.00	39.81	74.00	-34.19	54.74	32.43	9.37	57.43	0.70	--	--	Peak	2	4808.00	-15.81	54.00	-69.81	--	--	--	--	--	--	--	AVERAGE	<table><tr><th></th><th></th><th colspan="3">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4808.00</td><td>39.74</td><td>74.00</td><td>-34.26</td><td>54.67</td><td>32.43</td><td>9.37</td><td>57.43</td><td>0.70</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-16.18</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>								Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4808.00	39.74	74.00	-34.26	54.67	32.43	9.37	57.43	0.70	--	--	PEAK	2	4808.00	-16.18	-----	-----	--	--	--	--	--	--	--	AVERAGE
		Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																								
1	4808.00	39.81	74.00	-34.19	54.74	32.43	9.37	57.43	0.70	--	--	Peak																																																																																																																																							
2	4808.00	-15.81	54.00	-69.81	--	--	--	--	--	--	--	AVERAGE																																																																																																																																							
		Limit			Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																								
1	4808.00	39.74	74.00	-34.26	54.67	32.43	9.37	57.43	0.70	--	--	PEAK																																																																																																																																							
2	4808.00	-16.18	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																																							

Remark: The unwanted signal 4808.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).




Mode	33	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL



Mode	34																																																																																																															
	Band Edge - L																																																																																																															
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																															
ANT	3																																																																																																															
Pol.	Horizontal	Fundamental																																																																																																														
Peak	Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>51.73</td><td>74.00</td><td>-22.27</td><td>44.53</td><td>27.50</td><td>6.74</td><td>36.97</td><td>9.93</td><td>300</td><td>22 PEAK</td></tr><tr><td>2</td><td>2389.95</td><td>-4.19</td><td>54.00</td><td>-58.19</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>300</td><td>22 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	51.73	74.00	-22.27	44.53	27.50	6.74	36.97	9.93	300	22 PEAK	2	2389.95	-4.19	54.00	-58.19	--	--	--	--	--	300	22 AVERAGE	Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>116.03</td><td>-----</td><td>-----</td><td>100.66</td><td>27.60</td><td>6.81</td><td>36.97</td><td>9.93</td><td>300</td><td>22 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>60.11</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>300</td><td>22 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	116.03	-----	-----	100.66	27.60	6.81	36.97	9.93	300	22 PEAK	2	2440.00	60.11	-----	-----	--	--	--	--	--	300	22 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	2389.95	51.73	74.00	-22.27	44.53	27.50	6.74	36.97	9.93	300	22 PEAK																																																																																																					
2	2389.95	-4.19	54.00	-58.19	--	--	--	--	--	300	22 AVERAGE																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	2440.00	116.03	-----	-----	100.66	27.60	6.81	36.97	9.93	300	22 PEAK																																																																																																					
2	2440.00	60.11	-----	-----	--	--	--	--	--	300	22 AVERAGE																																																																																																					




Mode	34																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																							
ANT	3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2491.12</td><td>52.64</td><td>74.00</td><td>-21.36</td><td>44.99</td><td>27.81</td><td>6.88</td><td>36.97</td><td>9.93</td><td>300</td><td>22</td><td>PEAK</td></tr><tr><td>2</td><td>2491.12</td><td>-3.28</td><td>54.00</td><td>-57.28</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>300</td><td>22</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2491.12	52.64	74.00	-21.36	44.99	27.81	6.88	36.97	9.93	300	22	PEAK	2	2491.12	-3.28	54.00	-57.28	--	--	--	--	--	300	22	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	2491.12	52.64	74.00	-21.36	44.99	27.81	6.88	36.97	9.93	300	22	PEAK																																												
2	2491.12	-3.28	54.00	-57.28	--	--	--	--	--	300	22	AVERAGE																																												





Mode	34																																																																																																																													
	Band Edge - L																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																													
ANT	3																																																																																																																													
Pol.	Vertical						Fundamental																																																																																																																							
Peak	Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2387.09</td><td>52.08</td><td>74.00</td><td>-21.92</td><td>44.92</td><td>27.47</td><td>6.73</td><td>36.97</td><td>9.93</td><td>391</td><td>111</td><td>PEAK</td></tr><tr><td>2</td><td>2387.09</td><td>-3.84</td><td>54.00</td><td>-57.84</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>391</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.09	52.08	74.00	-21.92	44.92	27.47	6.73	36.97	9.93	391	111	PEAK	2	2387.09	-3.84	54.00	-57.84	--	--	--	--	--	391	111	AVERAGE	Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>114.77</td><td>-----</td><td>-----</td><td>107.40</td><td>27.60</td><td>6.81</td><td>36.97</td><td>9.93</td><td>391</td><td>111</td><td>PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>58.85</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>391</td><td>111</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	114.77	-----	-----	107.40	27.60	6.81	36.97	9.93	391	111	PEAK	2	2440.00	58.85	-----	-----	--	--	--	--	--	391	111	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2387.09	52.08	74.00	-21.92	44.92	27.47	6.73	36.97	9.93	391	111	PEAK																																																																																																																		
2	2387.09	-3.84	54.00	-57.84	--	--	--	--	--	391	111	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2440.00	114.77	-----	-----	107.40	27.60	6.81	36.97	9.93	391	111	PEAK																																																																																																																		
2	2440.00	58.85	-----	-----	--	--	--	--	--	391	111	AVERAGE																																																																																																																		







Mode	34																																																					
	Band Edge - R																																																					
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																					
ANT	3																																																					
Pol.	Vertical	Fundamental																																																				
Peak	 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2496.76</td><td>52.10</td><td>74.00</td><td>-21.90</td><td>44.38</td><td>27.87</td><td>6.89</td><td>36.97</td><td>9.93</td><td>391</td><td>111</td><td>PEAK</td></tr><tr><td>2</td><td>2496.76</td><td>-3.82</td><td>54.00</td><td>-57.82</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>391</td><td>111</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2496.76	52.10	74.00	-21.90	44.38	27.87	6.89	36.97	9.93	391	111	PEAK	2	2496.76	-3.82	54.00	-57.82	--	--	--	--	--	391	111	AVERAGE	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	2496.76	52.10	74.00	-21.90	44.38	27.87	6.89	36.97	9.93	391	111	PEAK																																										
2	2496.76	-3.82	54.00	-57.82	--	--	--	--	--	391	111	AVERAGE																																										





		34																																																																																																																																																																												
Mode	Harmonic																																																																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																																																																													
ANT	3																																																																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																																																																							
Peak Avg																																																																																																																																																																														
	Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL						Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL																																																																																																																																																																							
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>40.72</td><td>74.00</td><td>-33.28</td><td>54.75</td><td>32.72</td><td>9.81</td><td>57.27</td><td>0.71</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>-15.20</td><td>54.00</td><td>-69.20</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7320.00</td><td>45.68</td><td>74.00</td><td>-28.32</td><td>52.57</td><td>37.00</td><td>12.76</td><td>57.39</td><td>0.66</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>-10.24</td><td>54.00</td><td>-64.24</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	40.72	74.00	-33.28	54.75	32.72	9.81	57.27	0.71	--	PEAK	2	4880.00	-15.20	54.00	-69.20	--	--	--	--	--	--	AVERAGE	3	7320.00	45.68	74.00	-28.32	52.57	37.00	12.76	57.39	0.66	--	PEAK	4	7320.00	-10.24	54.00	-64.24	--	--	--	--	--	--	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>40.43</td><td>74.00</td><td>-33.57</td><td>54.46</td><td>32.72</td><td>9.81</td><td>57.27</td><td>0.71</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>-15.49</td><td>54.00</td><td>-69.49</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7320.00</td><td>46.00</td><td>74.00</td><td>-28.00</td><td>52.09</td><td>37.00</td><td>12.76</td><td>57.39</td><td>0.66</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>-9.92</td><td>54.00</td><td>-63.92</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	40.43	74.00	-33.57	54.46	32.72	9.81	57.27	0.71	--	PEAK	2	4880.00	-15.49	54.00	-69.49	--	--	--	--	--	--	AVERAGE	3	7320.00	46.00	74.00	-28.00	52.09	37.00	12.76	57.39	0.66	--	PEAK	4	7320.00	-9.92	54.00	-63.92	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																				
1	4880.00	40.72	74.00	-33.28	54.75	32.72	9.81	57.27	0.71	--	PEAK																																																																																																																																																																			
2	4880.00	-15.20	54.00	-69.20	--	--	--	--	--	--	AVERAGE																																																																																																																																																																			
3	7320.00	45.68	74.00	-28.32	52.57	37.00	12.76	57.39	0.66	--	PEAK																																																																																																																																																																			
4	7320.00	-10.24	54.00	-64.24	--	--	--	--	--	--	AVERAGE																																																																																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																				
1	4880.00	40.43	74.00	-33.57	54.46	32.72	9.81	57.27	0.71	--	PEAK																																																																																																																																																																			
2	4880.00	-15.49	54.00	-69.49	--	--	--	--	--	--	AVERAGE																																																																																																																																																																			
3	7320.00	46.00	74.00	-28.00	52.09	37.00	12.76	57.39	0.66	--	PEAK																																																																																																																																																																			
4	7320.00	-9.92	54.00	-63.92	--	--	--	--	--	--	AVERAGE																																																																																																																																																																			



Mode	34	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL





Mode	35																																																																																																																									
	Band Edge																																																																																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																									
ANT	3																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																			
Peak	 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.57</td><td>66.33</td><td>74.00</td><td>-7.67</td><td>58.70</td><td>27.00</td><td>6.87</td><td>36.97</td><td>9.93</td><td>300</td><td>43 PEAK</td></tr><tr><td>2</td><td>2483.57</td><td>10.41</td><td>54.00</td><td>-43.59</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>300</td><td>43 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.57	66.33	74.00	-7.67	58.70	27.00	6.87	36.97	9.93	300	43 PEAK	2	2483.57	10.41	54.00	-43.59	--	--	--	--	--	300	43 AVERAGE	 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>117.00</td><td>-----</td><td>-----</td><td>109.48</td><td>27.78</td><td>6.86</td><td>36.97</td><td>9.93</td><td>300</td><td>43 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>61.16</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>300</td><td>43 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	117.00	-----	-----	109.48	27.78	6.86	36.97	9.93	300	43 PEAK	2	2478.00	61.16	-----	-----	--	--	--	--	--	300	43 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2483.57	66.33	74.00	-7.67	58.70	27.00	6.87	36.97	9.93	300	43 PEAK																																																																																																															
2	2483.57	10.41	54.00	-43.59	--	--	--	--	--	300	43 AVERAGE																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2478.00	117.00	-----	-----	109.48	27.78	6.86	36.97	9.93	300	43 PEAK																																																																																																															
2	2478.00	61.16	-----	-----	--	--	--	--	--	300	43 AVERAGE																																																																																																															







Mode	35																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Vertical	Fundamental																																																																																																				
Peak	Level (dBuV/m) Frequency (MHz) PEAK_BE_74 Site : 03CH13-HY Condition: PEAK_BE_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2483.54</td><td>65.09</td><td>74.00</td><td>-8.91</td><td>57.46</td><td>27.00</td><td>6.87</td><td>36.97</td><td>9.93 329 113 PEAK</td></tr><tr><td>2</td><td>2483.54</td><td>9.17</td><td>54.00</td><td>-44.83</td><td>--</td><td>--</td><td>--</td><td>--</td><td>329 113 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2483.54	65.09	74.00	-8.91	57.46	27.00	6.87	36.97	9.93 329 113 PEAK	2	2483.54	9.17	54.00	-44.83	--	--	--	--	329 113 AVERAGE	Level (dBuV/m) Frequency (MHz) PEAK_74 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2478.00</td><td>115.16</td><td>-----</td><td>-----</td><td>107.56</td><td>27.78</td><td>6.86</td><td>36.97</td><td>9.93 329 113 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>59.24</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>329 113 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2478.00	115.16	-----	-----	107.56	27.78	6.86	36.97	9.93 329 113 PEAK	2	2478.00	59.24	-----	-----	--	--	--	--	329 113 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2483.54	65.09	74.00	-8.91	57.46	27.00	6.87	36.97	9.93 329 113 PEAK																																																																																													
2	2483.54	9.17	54.00	-44.83	--	--	--	--	329 113 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2478.00	115.16	-----	-----	107.56	27.78	6.86	36.97	9.93 329 113 PEAK																																																																																													
2	2478.00	59.24	-----	-----	--	--	--	--	329 113 AVERAGE																																																																																													





Mode	35																																																																																																																																																															
	Harmonic																																																																																																																																																															
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																																																															
ANT	3																																																																																																																																																															
Pol.	Horizontal	Vertical																																																																																																																																																														
Peak Avg	 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>41.67</td><td>74.00</td><td>-32.33</td><td>54.66</td><td>33.12</td><td>10.27</td><td>57.10</td><td>0.72</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>-14.25</td><td>54.00</td><td>-68.25</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7434.00</td><td>45.15</td><td>74.00</td><td>-28.85</td><td>52.72</td><td>36.53</td><td>12.84</td><td>57.61</td><td>0.67</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7434.00</td><td>-10.77</td><td>54.00</td><td>-64.77</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	41.67	74.00	-32.33	54.66	33.12	10.27	57.10	0.72	--	PEAK	2	4956.00	-14.25	54.00	-68.25	--	--	--	--	--	--	AVERAGE	3	7434.00	45.15	74.00	-28.85	52.72	36.53	12.84	57.61	0.67	--	PEAK	4	7434.00	-10.77	54.00	-64.77	--	--	--	--	--	--	AVERAGE	 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91200_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>42.35</td><td>74.00</td><td>-31.65</td><td>55.34</td><td>33.12</td><td>10.27</td><td>57.10</td><td>0.72</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>-13.57</td><td>54.00</td><td>-67.57</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7434.00</td><td>45.19</td><td>74.00</td><td>-28.81</td><td>52.76</td><td>36.53</td><td>12.84</td><td>57.61</td><td>0.67</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7434.00</td><td>-10.73</td><td>54.00</td><td>-64.73</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	42.35	74.00	-31.65	55.34	33.12	10.27	57.10	0.72	--	PEAK	2	4956.00	-13.57	54.00	-67.57	--	--	--	--	--	--	AVERAGE	3	7434.00	45.19	74.00	-28.81	52.76	36.53	12.84	57.61	0.67	--	PEAK	4	7434.00	-10.73	54.00	-64.73	--	--	--	--	--	--	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																						
1	4956.00	41.67	74.00	-32.33	54.66	33.12	10.27	57.10	0.72	--	PEAK																																																																																																																																																					
2	4956.00	-14.25	54.00	-68.25	--	--	--	--	--	--	AVERAGE																																																																																																																																																					
3	7434.00	45.15	74.00	-28.85	52.72	36.53	12.84	57.61	0.67	--	PEAK																																																																																																																																																					
4	7434.00	-10.77	54.00	-64.77	--	--	--	--	--	--	AVERAGE																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																						
1	4956.00	42.35	74.00	-31.65	55.34	33.12	10.27	57.10	0.72	--	PEAK																																																																																																																																																					
2	4956.00	-13.57	54.00	-67.57	--	--	--	--	--	--	AVERAGE																																																																																																																																																					
3	7434.00	45.19	74.00	-28.81	52.76	36.53	12.84	57.61	0.67	--	PEAK																																																																																																																																																					
4	7434.00	-10.73	54.00	-64.73	--	--	--	--	--	--	AVERAGE																																																																																																																																																					



Mode	35	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL
	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 HORIZONTAL	 Site : 03CH13-HY Condition: AVG_54 3m HORN_91200_1326 VERTICAL



Mode	39																																																																																																																																																																																																																																			
	LF																																																																																																																																																																																																																																			
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																																																																																																																																			
ANT	3																																																																																																																																																																																																																																			
Pol.	Horizontal						Vertical																																																																																																																																																																																																																													
QP/ Peak	 Site : 03CH13-HY Condition: QP 3m BILOG_40103 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>64.92</td><td>29.34</td><td>40.00</td><td>-10.66</td><td>47.99</td><td>12.00</td><td>1.18</td><td>31.91</td><td>0.08</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>203.63</td><td>35.04</td><td>43.50</td><td>-8.46</td><td>49.68</td><td>15.07</td><td>2.04</td><td>31.81</td><td>0.06</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>262.80</td><td>34.22</td><td>46.00</td><td>-11.78</td><td>43.51</td><td>20.00</td><td>2.33</td><td>31.74</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>273.47</td><td>31.17</td><td>46.00</td><td>-14.83</td><td>41.58</td><td>18.06</td><td>2.37</td><td>31.76</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>749.74</td><td>31.90</td><td>46.00</td><td>-14.10</td><td>31.23</td><td>28.30</td><td>3.84</td><td>31.61</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>943.74</td><td>36.24</td><td>46.00</td><td>-9.76</td><td>31.71</td><td>30.75</td><td>4.31</td><td>30.73</td><td>0.20</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	64.92	29.34	40.00	-10.66	47.99	12.00	1.18	31.91	0.08	--	Peak	2	203.63	35.04	43.50	-8.46	49.68	15.07	2.04	31.81	0.06	--	Peak	3	262.80	34.22	46.00	-11.78	43.51	20.00	2.33	31.74	0.12	--	Peak	4	273.47	31.17	46.00	-14.83	41.58	18.06	2.37	31.76	0.12	--	Peak	5	749.74	31.90	46.00	-14.10	31.23	28.30	3.84	31.61	0.14	--	Peak	6	943.74	36.24	46.00	-9.76	31.71	30.75	4.31	30.73	0.20	--	Peak	 Site : 03CH13-HY Condition: QP 3m BILOG_40103 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>48.56</td><td>32.49</td><td>40.00</td><td>-7.51</td><td>48.31</td><td>15.02</td><td>1.02</td><td>31.98</td><td>0.12</td><td>100</td><td>145 QP</td></tr><tr><td>2</td><td>187.14</td><td>33.18</td><td>43.50</td><td>-10.32</td><td>48.17</td><td>14.80</td><td>1.96</td><td>31.84</td><td>0.09</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>267.65</td><td>27.62</td><td>46.00</td><td>-18.38</td><td>37.43</td><td>19.47</td><td>2.35</td><td>31.75</td><td>0.12</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>276.38</td><td>29.44</td><td>46.00</td><td>-16.56</td><td>39.92</td><td>18.77</td><td>2.39</td><td>31.77</td><td>0.13</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>754.59</td><td>32.96</td><td>46.00</td><td>-13.04</td><td>32.28</td><td>28.30</td><td>3.85</td><td>31.61</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>948.59</td><td>36.80</td><td>46.00</td><td>-9.20</td><td>32.03</td><td>30.94</td><td>4.32</td><td>30.69</td><td>0.20</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	48.56	32.49	40.00	-7.51	48.31	15.02	1.02	31.98	0.12	100	145 QP	2	187.14	33.18	43.50	-10.32	48.17	14.80	1.96	31.84	0.09	--	Peak	3	267.65	27.62	46.00	-18.38	37.43	19.47	2.35	31.75	0.12	--	Peak	4	276.38	29.44	46.00	-16.56	39.92	18.77	2.39	31.77	0.13	--	Peak	5	754.59	32.96	46.00	-13.04	32.28	28.30	3.85	31.61	0.14	--	Peak	6	948.59	36.80	46.00	-9.20	32.03	30.94	4.32	30.69	0.20	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																										
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																											
1	64.92	29.34	40.00	-10.66	47.99	12.00	1.18	31.91	0.08	--	Peak																																																																																																																																																																																																																									
2	203.63	35.04	43.50	-8.46	49.68	15.07	2.04	31.81	0.06	--	Peak																																																																																																																																																																																																																									
3	262.80	34.22	46.00	-11.78	43.51	20.00	2.33	31.74	0.12	--	Peak																																																																																																																																																																																																																									
4	273.47	31.17	46.00	-14.83	41.58	18.06	2.37	31.76	0.12	--	Peak																																																																																																																																																																																																																									
5	749.74	31.90	46.00	-14.10	31.23	28.30	3.84	31.61	0.14	--	Peak																																																																																																																																																																																																																									
6	943.74	36.24	46.00	-9.76	31.71	30.75	4.31	30.73	0.20	--	Peak																																																																																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																																											
1	48.56	32.49	40.00	-7.51	48.31	15.02	1.02	31.98	0.12	100	145 QP																																																																																																																																																																																																																									
2	187.14	33.18	43.50	-10.32	48.17	14.80	1.96	31.84	0.09	--	Peak																																																																																																																																																																																																																									
3	267.65	27.62	46.00	-18.38	37.43	19.47	2.35	31.75	0.12	--	Peak																																																																																																																																																																																																																									
4	276.38	29.44	46.00	-16.56	39.92	18.77	2.39	31.77	0.13	--	Peak																																																																																																																																																																																																																									
5	754.59	32.96	46.00	-13.04	32.28	28.30	3.85	31.61	0.14	--	Peak																																																																																																																																																																																																																									
6	948.59	36.80	46.00	-9.20	32.03	30.94	4.32	30.69	0.20	--	Peak																																																																																																																																																																																																																									



Mode	40																																																																																											
	SHF																																																																																											
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																											
ANT	3																																																																																											
Pol.	Horizontal						Vertical																																																																																					
Peak	Site : 03CH13-HY Condition: PEAK_74 1m SHF_1224 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 24664.00</td><td>41.10</td><td>74.00</td><td>-32.90</td><td>57.61</td><td>39.30</td><td>7.13</td><td>53.40</td><td>-9.54</td><td>-- -- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 24664.00	41.10	74.00	-32.90	57.61	39.30	7.13	53.40	-9.54	-- -- Peak	Site : 03CH13-HY Condition: PEAK_74 1m SHF_1224 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 24720.00</td><td>40.65</td><td>74.00</td><td>-33.35</td><td>57.09</td><td>39.34</td><td>7.13</td><td>53.37</td><td>-9.54</td><td>-- -- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 24720.00	40.65	74.00	-33.35	57.09	39.34	7.13	53.37	-9.54	-- -- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																			
1 24664.00	41.10	74.00	-32.90	57.61	39.30	7.13	53.40	-9.54	-- -- Peak																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																			
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																			
1 24720.00	40.65	74.00	-33.35	57.09	39.34	7.13	53.37	-9.54	-- -- Peak																																																																																			