



FCC RADIO TEST REPORT

FCC ID : A4RGB7N6
Equipment : Phone
Model Name : GB7N6, GR1YH
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jun. 03, 2021 and testing was started from Jun. 11, 2021 and completed on Jul. 06, 2021. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	20
3.3 Power Spectral Density Measurement	21
3.4 Conducted Band Edges and Spurious Emission Measurement	30
3.5 Radiated Band Edges and Spurious Emission Measurement	41
3.6 AC Conducted Emission Measurement.....	45
3.7 Antenna Requirements.....	47
4 List of Measuring Equipment	48
5 Uncertainty of Evaluation.....	50
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	Under limit 5.00 dB at 17985.000 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 20.56 dB at 12.679 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: William Chen

Report Producer: Cindy Liu



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	GB7N6, GR1YH
FCC ID	A4RGB7N6
EUT supports Radios application	GSM/EGPRS/WCDM/HSPA/LTE/5G NR/NFC/ GNSS/WPC/WPT WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
S/N	Performed Test Item
15201FDF60001C	RF Conducted Measurement
15171FDF600099	Radiated Spurious Emission
15141FDF600064	Conducted Emission

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<Ant. 4> Bluetooth – LE (1Mbps): 19.85 dBm / 0.0966 W Bluetooth – LE (2Mbps): 19.95 dBm / 0.0989 W <Ant. 3> Bluetooth – LE (1Mbps): 19.95 dBm / 0.0989 W Bluetooth – LE (2Mbps): 19.95 dBm / 0.0989 W
99% Occupied Bandwidth	<Ant. 4> Bluetooth – LE (1Mbps): 1.037MHz Bluetooth – LE (2Mbps): 2.050MHz. <Ant. 3> Bluetooth – LE (1Mbps): 1.037MHz Bluetooth – LE (2Mbps): 2.054MHz
Antenna Type / Gain	<Ant. 4>: ILA Antenna with gain -1.1 dBi <Ant. 3>: IFA Antenna with gain -1.4 dBi
Type of Modulation	Bluetooth LE : GFSK

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.



1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH11-HY, CO07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find X plane as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + USB Cable 2 (Charging from AC Adapter 2)

Remark:


1. For Radiated Test Cases, the tests were performed with Adapter 2 and USB Cable 2.
2. During the preliminary test, both charging modes (Adapter mode and WPC Charging mode) were verified. It is determined that the adaptor mode is the worst case for official test.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth-LE Tx Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Google	G1013	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	Dell	Latitude E3480	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m

2.5 EUT Operation Test Setup

The RF test items, utility “adb command V_1.0.36” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}.$$

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<Ant. 4>

<1Mbps>






<2Mbps>






<Ant. 3>

<1Mbps>





<2Mbps>






3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<Ant. 4>


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<2Mbps>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<Ant. 3>


<1Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<2Mbps>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT was connected to the power meter by RF cable and attenuator.
3. The path loss was compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<Ant. 4>

<1Mbps>






<2Mbps>






<Ant. 3>

<1Mbps>





<2Mbps>






3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<Ant. 4>

<1Mbps>






<2Mbps>






<Ant. 3>

<1Mbps>





<2Mbps>



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup







3.4.5 Test Result of Conducted Band Edges Plots

<Ant. 4>

<1Mbps>




<2Mbps>






<Ant. 3>

<1Mbps>



<2Mbps>







3.4.6 Test Result of Conducted Spurious Emission Plots

<Ant. 4>


<1Mbps>








<2Mbps>









<Ant. 3>


<1Mbps>








<2Mbps>







3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1 GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and be reported.
7. For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and be reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Nov. 03, 2020	Jun. 11, 2021~Jul. 06, 2021	Nov. 02, 2021	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00991	18GHz~40GHz	May 12, 2021	Jun. 11, 2021~Jul. 06, 2021	May 11, 2022	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 11, 2020	Jun. 11, 2021~Jul. 06, 2021	Oct. 10, 2021	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 04, 2021	Jun. 11, 2021~Jul. 06, 2021	Jan. 03, 2022	Radiation (03CH11-HY)
Preamplifier	EMEC	EM1G18G	060812	1GHz~18GHz	Oct. 27, 2020	Jun. 11, 2021~Jul. 06, 2021	Oct. 26, 2021	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 12, 2020	Jun. 11, 2021~Jul. 06, 2021	Nov. 11, 2021	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 22, 2021	Jul. 05, 2021~Jul. 06, 2021	Jun. 21, 2022	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 02, 2020	Jun. 11, 2021~Jul. 06, 2021	Dec. 01, 2021	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 23, 2020	Jun. 11, 2021~Jul. 06, 2021	Oct. 22, 2021	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MX E)	MY54130085	20MHz~8.4GHz	Nov. 02, 2020	Jun. 11, 2021~Jul. 06, 2021	Nov. 01, 2021	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1~4m	N/A	Jun. 11, 2021~Jul. 06, 2021	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jun. 11, 2021~Jul. 06, 2021	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Jun. 11, 2021~Jul. 06, 2021	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 11, 2021	Jun. 11, 2021~Jul. 06, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 11, 2021	Jun. 11, 2021~Jul. 06, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 11, 2021	Jun. 11, 2021~Jul. 06, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 11, 2021	Jun. 11, 2021~Jul. 06, 2021	Mar. 10, 2022	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60SS	SN3	3GHz High Pass Filter	Sep. 14, 2020	Jun. 11, 2021~Jul. 06, 2021	Sep. 13, 2021	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-4 OSS	SN1	1.53GHz Low Pass Filter	Sep. 14, 2020	Jun. 11, 2021~Jul. 06, 2021	Sep. 13, 2021	Radiation (03CH11-HY)
Hygrometer	TECPTEL	DTM-303B	TP140325	N/A	Nov. 18, 2020	Jun. 11, 2021~Jul. 06, 2021	Nov. 17, 2021	Radiation (03CH11-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F3170400 33	N/A	N/A	Jun. 29, 2021	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 29, 2021	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 02, 2020	Jun. 29, 2021	Nov. 01, 2021	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 17, 2021	Jun. 29, 2021	Mar. 16, 2022	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Feb. 01, 2021	Jun. 29, 2021	Jan. 31, 2022	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 11, 2020	Jun. 29, 2021	Sep. 10, 2021	Conduction (CO07-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 03, 2021	Jun. 28, 2021~ Jun. 29, 2021	Mar. 02, 2022	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054S NO12	10MHz~6GHz	Dec. 16, 2020	Jun. 28, 2021~ Jun. 29, 2021	Dec. 15, 2021	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jan. 21, 2021	Jun. 28, 2021~ Jun. 29, 2021	Jan. 20, 2022	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2021	Jun. 28, 2021~ Jun. 29, 2021	Mar. 16, 2022	Conducted (TH05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	2.2 dB
-------------------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	4.7 dB
-------------------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	5.2 dB
-------------------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$)	5.1 dB
-------------------------------------------------------------------------------	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Richard Qiu	Temperature:	24~25.1	°C
Test Date:	2021/6/28~2021/6/29	Relative Humidity:	54.9~58.7	%

<Ant. 4>

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.035	0.704	0.50	Pass
BLE	1Mbps	1	19	2440	1.037	0.714	0.50	Pass
BLE	1Mbps	1	39	2480	1.035	0.714	0.50	Pass

TEST RESULTS DATA Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	19.75	30.00	-1.10	18.65	36.00	Pass
BLE	1Mbps	1	19	2440	19.85	30.00	-1.10	18.75	36.00	Pass
BLE	1Mbps	1	39	2480	19.45	30.00	-1.10	18.35	36.00	Pass

TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	19.01	4.27	-1.10	8.00	Pass
BLE	1Mbps	1	19	2440	19.21	4.50	-1.10	8.00	Pass
BLE	1Mbps	1	39	2480	18.77	4.09	-1.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.050	1.184	0.50	Pass
BLE	2Mbps	1	19	2440	2.050	1.228	0.50	Pass
BLE	2Mbps	1	39	2480	2.050	1.240	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	19.65	30.00	-1.10	18.55	36.00	Pass
BLE	2Mbps	1	19	2440	19.95	30.00	-1.10	18.85	36.00	Pass
BLE	2Mbps	1	39	2480	19.55	30.00	-1.10	18.45	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	18.76	0.50	-1.10	8.00	Pass
BLE	2Mbps	1	19	2440	19.14	0.87	-1.10	8.00	Pass
BLE	2Mbps	1	39	2480	18.70	0.50	-1.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 3>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.035	0.712	0.50	Pass
BLE	1Mbps	1	19	2440	1.037	0.714	0.50	Pass
BLE	1Mbps	1	39	2480	1.037	0.716	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	19.95	30.00	-1.40	18.55	36.00	Pass
BLE	1Mbps	1	19	2440	19.95	30.00	-1.40	18.55	36.00	Pass
BLE	1Mbps	1	39	2480	19.15	30.00	-1.40	17.75	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	19.14	4.43	-1.40	8.00	Pass
BLE	1Mbps	1	19	2440	19.53	4.89	-1.40	8.00	Pass
BLE	1Mbps	1	39	2480	18.31	3.67	-1.40	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.050	1.188	0.50	Pass
BLE	2Mbps	1	19	2440	2.054	1.239	0.50	Pass
BLE	2Mbps	1	39	2480	2.054	1.240	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	19.95	30.00	-1.40	18.55	36.00	Pass
BLE	2Mbps	1	19	2440	19.75	30.00	-1.40	18.35	36.00	Pass
BLE	2Mbps	1	39	2480	19.15	30.00	-1.40	17.75	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	19.05	0.81	-1.40	8.00	Pass
BLE	2Mbps	1	19	2440	18.77	0.56	-1.40	8.00	Pass
BLE	2Mbps	1	39	2480	18.24	0.04	-1.40	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Howard Huang	Temperature :	23~26°C
		Relative Humidity :	40~50%

EUT Information

Report NO : 0D2942-05
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.151620	---	26.99	55.91	28.92	L1	OFF	20.0
0.151620	42.19	---	65.91	23.72	L1	OFF	20.0
0.334680	---	14.57	49.33	34.76	L1	OFF	20.0
0.334680	19.41	---	59.33	39.92	L1	OFF	20.0
2.780340	---	23.71	46.00	22.29	L1	OFF	20.1
2.780340	28.50	---	56.00	27.50	L1	OFF	20.1
8.764530	---	23.23	50.00	26.77	L1	OFF	20.1
8.764530	27.60	---	60.00	32.40	L1	OFF	20.1
12.679350	---	29.44	50.00	20.56	L1	OFF	20.2
12.679350	32.92	---	60.00	27.08	L1	OFF	20.2
20.043240	---	24.48	50.00	25.52	L1	OFF	20.2
20.043240	29.13	---	60.00	30.87	L1	OFF	20.2

EUT Information

Report NO : 0D2942-05
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	23.55	55.63	32.08	N	OFF	20.0
0.156750	38.12	---	65.63	27.51	N	OFF	20.0
0.481380	---	20.78	46.32	25.54	N	OFF	20.0
0.481380	24.26	---	56.32	32.06	N	OFF	20.0
2.890500	---	23.46	46.00	22.54	N	OFF	20.1
2.890500	26.92	---	56.00	29.08	N	OFF	20.1
8.902860	---	23.31	50.00	26.69	N	OFF	20.1
8.902860	28.04	---	60.00	31.96	N	OFF	20.1
12.687000	---	26.12	50.00	23.88	N	OFF	20.2
12.687000	31.15	---	60.00	28.85	N	OFF	20.2
19.783050	---	28.20	50.00	21.80	N	OFF	20.3
19.783050	32.97	---	60.00	27.03	N	OFF	20.3



Appendix C. Radiated Spurious Emission

Test Engineer :	Harvey Guo, Fu Chen and Troye Hsieh	Temperature :	18.1~24.5°C
		Relative Humidity :	56.5~69.9%

<Ant. 4>

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak	Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2329.53	53.26	-20.74	74	42.1	27.64	17.01	33.49	121	301	P	H	
		2357.88	43.32	-10.68	54	32.18	27.58	17.03	33.47	121	301	A	H	
	*	2402	110.82	-	-	99.7	27.5	17.07	33.45	121	301	P	H	
	*	2402	110.24	-	-	99.12	27.5	17.07	33.45	121	301	A	H	
														H
		2373.525	53.22	-20.78	74	42.08	27.55	17.05	33.46	316	127	P	V	
		2353.68	43.36	-10.64	54	32.21	27.59	17.03	33.47	316	127	A	V	
	*	2402	103.97	-	-	92.85	27.5	17.07	33.45	316	127	P	V	
	*	2402	103.42	-	-	92.3	27.5	17.07	33.45	316	127	A	V	
BLE CH 19 2440MHz		2378.32	53.61	-20.39	74	42.48	27.54	17.05	33.46	110	298	P	H	
		2378.64	43.33	-10.67	54	32.2	27.54	17.05	33.46	110	298	A	H	
	*	2440	111.19	-	-	99.99	27.5	17.13	33.43	110	298	P	H	
	*	2440	110.44	-	-	99.24	27.5	17.13	33.43	110	298	A	H	
		2498.16	52.64	-21.36	74	41.42	27.4	17.22	33.4	110	298	P	H	
		2487.6	43.33	-10.67	54	32.11	27.42	17.21	33.41	110	298	A	H	
		2364.24	52.89	-21.11	74	41.75	27.57	17.04	33.47	344	126	P	V	
		2381.68	43.24	-10.76	54	32.11	27.54	17.05	33.46	344	126	A	V	
	*	2440	105.47	-	-	94.27	27.5	17.13	33.43	344	126	P	V	
	*	2440	104.89	-	-	93.69	27.5	17.13	33.43	344	126	A	V	
		2486.24	52.5	-21.5	74	41.28	27.43	17.2	33.41	344	126	P	V	
		2494.08	43.31	-10.69	54	32.08	27.41	17.22	33.4	344	126	A	V	



BLE CH 39 2480MHz	*	2480	110.35	-	-	99.13	27.44	17.19	33.41	100	296	P	H
	*	2480	109.73	-	-	98.51	27.44	17.19	33.41	100	296	A	H
		2495	53.38	-20.62	74	42.15	27.41	17.22	33.4	100	296	P	H
		2483.64	43.97	-10.03	54	32.75	27.43	17.2	33.41	100	296	A	H
													H
													H
	*	2480	104.67	-	-	93.45	27.44	17.19	33.41	334	128	P	V
	*	2480	103.99	-	-	92.77	27.44	17.19	33.41	334	128	A	V
		2493.92	52.64	-21.36	74	41.41	27.41	17.22	33.4	334	128	P	V
		2489.72	43.52	-10.48	54	32.3	27.42	17.21	33.41	334	128	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.49	-36.51	74	61.48	31	11.18	66.17	100	0	P	H
		17955	56.67	-17.33	74	51.48	46.5	23.86	65.17	100	0	P	H
		17955	48.16	-5.84	54	42.97	46.5	23.86	65.17	100	0	A	H
													H
		4804	37.42	-36.58	74	61.41	31	11.18	66.17	100	0	P	V
		17955	56.25	-17.75	74	51.06	46.5	23.86	65.17	100	0	P	V
		17955	48.33	-5.67	54	43.14	46.5	23.86	65.17	100	0	A	V
													V
BLE CH 19 2440MHz		4880	38.15	-35.85	74	61.39	31.54	11.34	66.12	100	0	P	H
		7320	42.13	-31.87	74	58	36.4	13.45	65.72	100	0	P	H
		17955	56.73	-17.27	74	51.54	46.5	23.86	65.17	100	0	P	H
		17955	48.03	-5.97	54	42.84	46.5	23.86	65.17	100	0	A	H
		4880	39.18	-34.82	74	62.42	31.54	11.34	66.12	100	0	P	V
		7320	40.69	-33.31	74	56.56	36.4	13.45	65.72	100	0	P	V
		17985	58.73	-15.27	74	52.86	47.1	23.89	65.12	100	0	P	V
		17985	49	-5	54	43.13	47.1	23.89	65.12	100	0	A	V
BLE CH 39 2480MHz		4960	38.29	-35.71	74	61.78	31.06	11.51	66.06	100	0	P	H
		7440	41.53	-32.47	74	57.02	36.56	13.74	65.79	100	0	P	H
		17985	58.7	-15.3	74	52.83	47.1	23.89	65.12	100	0	P	H
		17985	48.82	-5.18	54	42.95	47.1	23.89	65.12	100	0	A	H
		4960	38.41	-35.59	74	61.9	31.06	11.51	66.06	100	0	P	V
		7440	41.44	-32.56	74	56.93	36.56	13.74	65.79	100	0	P	V
		17985	57.65	-16.35	74	51.78	47.1	23.89	65.12	100	0	P	V
		17985	49	-5	54	43.13	47.1	23.89	65.12	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2314.515	52.61	-21.39	74	41.44	27.67	16.99	33.49	121	295	P	H
		2375.835	42.57	-11.43	54	31.43	27.55	17.05	33.46	121	295	A	H
	*	2402	111.32	-	-	100.2	27.5	17.07	33.45	121	295	P	H
	*	2402	109.73	-	-	98.61	27.5	17.07	33.45	121	295	A	H
													H
													H
		2386.65	52.49	-21.51	74	41.36	27.53	17.06	33.46	351	114	P	V
		2365.86	42.75	-11.25	54	31.61	27.57	17.04	33.47	351	114	A	V
	*	2402	104.66	-	-	93.54	27.5	17.07	33.45	351	114	P	V
	*	2402	102.44	-	-	91.32	27.5	17.07	33.45	351	114	A	V
													V
													V
BLE CH 19 2440MHz		2325.36	52.76	-21.24	74	41.6	27.65	17	33.49	110	298	P	H
		2382.64	42.56	-11.44	54	31.44	27.53	17.05	33.46	110	298	A	H
	*	2440	111.18	-	-	99.98	27.5	17.13	33.43	110	298	P	H
	*	2440	109.55	-	-	98.35	27.5	17.13	33.43	110	298	A	H
		2497.44	53.2	-20.8	74	41.97	27.41	17.22	33.4	110	298	P	H
		2489.68	42.63	-11.37	54	31.41	27.42	17.21	33.41	110	298	A	H
		2347.92	52.98	-21.02	74	41.84	27.6	17.02	33.48	337	116	P	V
		2380.72	42.6	-11.4	54	31.47	27.54	17.05	33.46	337	116	A	V
	*	2440	106.09	-	-	94.89	27.5	17.13	33.43	337	116	P	V
	*	2440	104.48	-	-	93.28	27.5	17.13	33.43	337	116	A	V
		2488.08	52.63	-21.37	74	41.41	27.42	17.21	33.41	337	116	P	V
		2486.32	42.66	-11.34	54	31.44	27.43	17.2	33.41	337	116	A	V



BLE CH 39 2480MHz	*	2480	110.69	-	-	99.47	27.44	17.19	33.41	100	296	P	H
	*	2480	109.03	-	-	97.81	27.44	17.19	33.41	100	296	A	H
		2485.2	52.8	-21.2	74	41.58	27.43	17.2	33.41	100	296	P	H
		2483.5	44.22	-9.78	54	33	27.43	17.2	33.41	100	296	A	H
													H
													H
	*	2480	105.25	-	-	94.03	27.44	17.19	33.41	370	116	P	V
	*	2480	101.42	-	-	90.2	27.44	17.19	33.41	370	116	A	V
		2496.45	52.33	-21.67	74	41.1	27.41	17.22	33.4	370	116	P	V
		2483.5	43.18	-10.82	54	31.96	27.43	17.2	33.41	370	116	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	38.98	-35.02	74	62.97	31	11.18	66.17	100	0	P	H
		17955	58.26	-15.74	74	53.07	46.5	23.86	65.17	100	0	P	H
		17955	47.97	-6.03	54	42.78	46.5	23.86	65.17	100	0	A	H
													H
		4804	37.21	-36.79	74	61.2	31	11.18	66.17	100	0	P	V
		17955	57.87	-16.13	74	52.68	46.5	23.86	65.17	100	0	P	V
		17955	48.31	-5.69	54	43.12	46.5	23.86	65.17	100	0	A	V
													V
BLE CH 19 2440MHz		4880	38.36	-35.64	74	61.6	31.54	11.34	66.12	100	0	P	H
		7320	40.69	-33.31	74	56.56	36.4	13.45	65.72	100	0	P	H
		17970	58.71	-15.29	74	53.19	46.8	23.87	65.15	100	0	P	H
		17970	48.49	-5.51	54	42.97	46.8	23.87	65.15	100	0	A	H
		4880	38.81	-35.19	74	62.05	31.54	11.34	66.12	100	0	P	V
		7320	41.51	-32.49	74	57.38	36.4	13.45	65.72	100	0	P	V
		17955	57.58	-16.42	74	52.39	46.5	23.86	65.17	100	0	P	V
		17955	48.36	-5.64	54	43.17	46.5	23.86	65.17	100	0	A	V
BLE CH 39 2480MHz		4960	38.13	-35.87	74	61.62	31.06	11.51	66.06	100	0	P	H
		7440	40.92	-33.08	74	56.41	36.56	13.74	65.79	100	0	P	H
		17970	57.7	-16.3	74	52.18	46.8	23.87	65.15	100	0	P	H
		17970	48.41	-5.59	54	42.89	46.8	23.87	65.15	100	0	A	H
		4960	38.3	-35.7	74	61.79	31.06	11.51	66.06	100	0	P	V
		7440	41.39	-32.61	74	56.88	36.56	13.74	65.79	100	0	P	V
		17970	58.27	-15.73	74	52.75	46.8	23.87	65.15	100	0	P	V
		17970	48.65	-5.35	54	43.13	46.8	23.87	65.15	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
2.4GHz BLE SHF	24846	35.97	-38.03	74	52.75	39.22	-2.81	53.19	150	0	P	H		
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Emission below 1GHz

2.4GHz BLE (LF)



<Ant. 3>

<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2385.6	53.4	-20.6	74	42.27	27.53	17.06	33.46	100	238	P	H
		2385.18	43.73	-10.27	54	32.6	27.53	17.06	33.46	100	238	A	H
	*	2402	112.67	-	-	101.55	27.5	17.07	33.45	100	238	P	H
	*	2402	111.99	-	-	100.87	27.5	17.07	33.45	100	238	A	H
													H
													H
		2348.955	53.12	-20.88	74	41.98	27.6	17.02	33.48	318	106	P	V
		2342.025	43.6	-10.4	54	32.44	27.62	17.02	33.48	318	106	A	V
	*	2402	107.99	-	-	96.87	27.5	17.07	33.45	318	106	P	V
	*	2402	107.4	-	-	96.28	27.5	17.07	33.45	318	106	A	V
BLE CH 19 2440MHz		2381.04	53.81	-20.19	74	42.68	27.54	17.05	33.46	109	243	P	H
		2384.24	43.77	-10.23	54	32.64	27.53	17.06	33.46	109	243	A	H
	*	2440	112.78	-	-	101.58	27.5	17.13	33.43	109	243	P	H
	*	2440	112.24	-	-	101.04	27.5	17.13	33.43	109	243	A	H
		2492.88	53.04	-20.96	74	41.82	27.41	17.21	33.4	109	243	P	H
		2497.52	43.81	-10.19	54	32.59	27.4	17.22	33.4	109	243	A	H
		2324.24	53.39	-20.61	74	42.23	27.65	17	33.49	307	143	P	V
		2350.16	43.63	-10.37	54	32.47	27.6	17.03	33.47	307	143	A	V
	*	2440	105.66	-	-	94.46	27.5	17.13	33.43	307	143	P	V
	*	2440	105.01	-	-	93.81	27.5	17.13	33.43	307	143	A	V
		2497.2	53.64	-20.36	74	42.41	27.41	17.22	33.4	307	143	P	V
		2489.28	43.71	-10.29	54	32.49	27.42	17.21	33.41	307	143	A	V



BLE CH 39 2480MHz	*	2480	111.79	-	-	100.57	27.44	17.19	33.41	100	244	P	H
	*	2480	110.75	-	-	99.53	27.44	17.19	33.41	100	244	A	H
		2484.44	53.9	-20.1	74	42.68	27.43	17.2	33.41	100	244	P	H
		2483.52	44.41	-9.59	54	33.19	27.43	17.2	33.41	100	244	A	H
													H
													H
	*	2480	106.31	-	-	95.09	27.44	17.19	33.41	300	142	P	V
	*	2480	103.98	-	-	92.76	27.44	17.19	33.41	300	142	A	V
		2483.92	53.56	-20.44	74	42.34	27.43	17.2	33.41	300	142	P	V
		2486.84	43.75	-10.25	54	32.53	27.43	17.2	33.41	300	142	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.52	-36.48	74	61.51	31	11.18	66.17	100	0	P	H
		17955	56.28	-17.72	74	51.09	46.5	23.86	65.17	100	0	P	H
		17955	48.12	-5.88	54	42.93	46.5	23.86	65.17	100	0	A	H
													H
		4804	38.41	-35.59	74	62.4	31	11.18	66.17	100	0	P	V
		17955	56.8	-17.2	74	51.61	46.5	23.86	65.17	100	0	P	V
		17955	48.08	-5.92	54	42.89	46.5	23.86	65.17	100	0	A	V
													V
BLE CH 19 2440MHz		4880	37.95	-36.05	74	61.19	31.54	11.34	66.12	100	0	P	H
		7320	41	-33	74	56.87	36.4	13.45	65.72	100	0	P	H
		17955	56.82	-17.18	74	51.63	46.5	23.86	65.17	100	0	P	H
		17955	48.12	-5.88	54	42.93	46.5	23.86	65.17	100	0	A	H
		4880	38.7	-35.3	74	61.94	31.54	11.34	66.12	100	0	P	V
		7320	40.7	-33.3	74	56.57	36.4	13.45	65.72	100	0	P	V
		17955	57.5	-16.5	74	52.31	46.5	23.86	65.17	100	0	P	V
		17955	48.4	-5.6	54	43.21	46.5	23.86	65.17	100	0	A	V
BLE CH 39 2480MHz		4960	38.62	-35.38	74	62.11	31.06	11.51	66.06	100	0	P	H
		7440	41.66	-32.34	74	57.15	36.56	13.74	65.79	100	0	P	H
		17955	57.13	-16.87	74	51.94	46.5	23.86	65.17	100	0	P	H
		17955	47.08	-6.92	54	41.89	46.5	23.86	65.17	100	0	A	H
		4960	38.46	-35.54	74	61.95	31.06	11.51	66.06	100	0	P	V
		7440	41.67	-32.33	74	57.16	36.56	13.74	65.79	100	0	P	V
		17955	56.81	-17.19	74	51.62	46.5	23.86	65.17	100	0	P	V
		17955	48.33	-5.67	54	43.14	46.5	23.86	65.17	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2320.815	54.1	-19.9	74	42.93	27.66	17	33.49	100	244	P	H
		2372.79	43.23	-10.77	54	32.09	27.55	17.05	33.46	100	244	A	H
	*	2402	112.94	-	-	101.82	27.5	17.07	33.45	100	244	P	H
	*	2402	111.35	-	-	100.23	27.5	17.07	33.45	100	244	A	H
													H
													H
		2378.145	53.1	-20.9	74	41.97	27.54	17.05	33.46	276	89	P	V
		2348.535	42.98	-11.02	54	31.84	27.6	17.02	33.48	276	89	A	V
	*	2402	108.56	-	-	97.44	27.5	17.07	33.45	276	89	P	V
	*	2402	104.85	-	-	93.73	27.5	17.07	33.45	276	89	A	V
													V
													V
BLE CH 19 2440MHz		2333.68	53.16	-20.84	74	42	27.63	17.01	33.48	108	243	P	H
		2341.84	42.98	-11.02	54	31.82	27.62	17.02	33.48	108	243	A	H
	*	2440	112.96	-	-	101.76	27.5	17.13	33.43	108	243	P	H
	*	2440	111.38	-	-	100.18	27.5	17.13	33.43	108	243	A	H
		2487.28	53.25	-20.75	74	42.02	27.43	17.21	33.41	108	243	P	H
		2487.28	43.03	-10.97	54	31.8	27.43	17.21	33.41	108	243	A	H
		2372.4	52.83	-21.17	74	41.68	27.56	17.05	33.46	308	140	P	V
		2382.64	42.95	-11.05	54	31.83	27.53	17.05	33.46	308	140	A	V
	*	2440	105.56	-	-	94.36	27.5	17.13	33.43	308	140	P	V
	*	2440	103.96	-	-	92.76	27.5	17.13	33.43	308	140	A	V
		2484.88	52.98	-21.02	74	41.76	27.43	17.2	33.41	308	140	P	V
		2487.84	43.19	-10.81	54	31.97	27.42	17.21	33.41	308	140	A	V



BLE CH 39 2480MHz	*	2480	112.84	-	-	101.62	27.44	17.19	33.41	100	246	P	H
	*	2480	110.03	-	-	98.81	27.44	17.19	33.41	100	246	A	H
		2484.1	53.91	-20.09	74	42.69	27.43	17.2	33.41	100	246	P	H
		2483.5	45.72	-8.28	54	34.5	27.43	17.2	33.41	100	246	A	H
													H
													H
	*	2480	107.3	-	-	96.08	27.44	17.19	33.41	297	140	P	V
	*	2480	104.07	-	-	92.85	27.44	17.19	33.41	297	140	A	V
		2492	52.63	-21.37	74	41.4	27.42	17.21	33.4	297	140	P	V
		2483.5	43.56	-10.44	54	32.34	27.43	17.2	33.41	297	140	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dB μ V/m)	Over Limit (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	37.73	-36.27	74	61.72	31	11.18	66.17	100	0	P	H
		17970	57.47	-16.53	74	51.95	46.8	23.87	65.15	100	0	P	H
		17970	48.45	-5.55	54	42.93	46.8	23.87	65.15	100	0	A	H
													H
		4804	37.89	-36.11	74	61.88	31	11.18	66.17	100	0	P	V
		17970	58.85	-15.15	74	53.33	46.8	23.87	65.15	100	0	P	V
		17970	48.73	-5.27	54	43.21	46.8	23.87	65.15	100	0	A	V
													V
BLE CH 19 2440MHz		4880	38.26	-35.74	74	61.5	31.54	11.34	66.12	100	0	P	H
		7320	41.17	-32.83	74	57.04	36.4	13.45	65.72	100	0	P	H
		17970	57.81	-16.19	74	52.29	46.8	23.87	65.15	100	0	P	H
		17970	48.5	-5.5	54	42.98	46.8	23.87	65.15	100	0	A	H
		4880	38.74	-35.26	74	61.98	31.54	11.34	66.12	100	0	P	V
		7320	41.39	-32.61	74	57.26	36.4	13.45	65.72	100	0	P	V
		17985	57.92	-16.08	74	52.05	47.1	23.89	65.12	100	0	P	V
		17985	49	-5	54	43.13	47.1	23.89	65.12	100	0	A	V
BLE CH 39 2480MHz		4960	38.31	-35.69	74	61.8	31.06	11.51	66.06	100	0	P	H
		7440	40.77	-33.23	74	56.26	36.56	13.74	65.79	100	0	P	H
		17985	58.96	-15.04	74	53.09	47.1	23.89	65.12	100	0	P	H
		17985	48.75	-5.25	54	42.88	47.1	23.89	65.12	100	0	A	H
		4960	37.96	-36.04	74	61.45	31.06	11.51	66.06	100	0	P	V
		7440	41.24	-32.76	74	56.73	36.56	13.74	65.79	100	0	P	V
		17970	57.75	-16.25	74	52.23	46.8	23.87	65.15	100	0	P	V
		17970	48.67	-5.33	54	43.15	46.8	23.87	65.15	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
2.4GHz BLE SHF	24755	36.44	-37.56	74	53.4	39.11	-2.82	53.25	150	0		H		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



Emission below 1GHz

2.4GHz BLE (LF)

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
			Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
		(MHz)	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A) (H/V)	
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dB μ V/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) - Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dB μ V) - 35.86 (dB)

= 55.45 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 55.45(dB μ V/m) - 74(dB μ V/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dB μ V/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dB μ V) - 35.86 (dB)

= 43.54 (dB μ V/m)

2. Over Limit(dB)

= Level(dB μ V/m) - Limit Line(dB μ V/m)

= 43.54(dB μ V/m) - 54(dB μ V/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".