



FCC Part 1 Subpart I  
FCC Part 2 Subpart J

**RF EXPOSURE REPORT**

**FOR**

**Tv Box, 10/100 Ethernet, MoCA 1.1/2.0, WiFi AP, HDMI 1.4 w/ HDCP**

**MODEL NUMBER: GFHD200**

**FCC ID: A4RGFHD200**

**REPORT NUMBER: 14U17737-6 Revision B**

**ISSUE DATE: June 11, 2014**

*Prepared for*  
**GOOGLE**  
**1600 AMPHITHEATRE PARKWAY**  
**MOUNTAIN VIEW**  
**CA, 94043, US**

*Prepared by*  
**UL VERIFICATION SERVICES INC.**  
**47173 BENICIA STREET**  
**FREMONT, CA 94538, U.S.A.**  
**TEL: (510) 771-1000**  
**FAX: (510) 661-0888**

**NVLAP**<sup>®</sup>

NVLAP LAB CODE 200065-0

Revision History

| Rev. | Issue Date | Revisions   | Revised By |
|------|------------|---|------------|
| --   | 5/27/14    | Initial Issue   | F. de Anda |
| A    | 6/10/14    | Update- reference to operation description doc for manufactures max. output power | F. de Anda |
| B    | 6/11/14    | Updated average power numbers   | F. de Anda |

## TABLE OF CONTENTS

|  |    |
|--|----|
| 1. ATTESTATION OF TEST RESULTS .....     | 4  |
| 2. TEST METHODOLOGY .....                | 5  |
| 3. REFERENCES .....                      | 5  |
| 4. FACILITIES AND ACCREDITATION .....    | 5  |
| 5. MAXIMUM PERMISSIBLE RF EXPOSURE ..... | 6  |
| 5.1. FCC RULES .....                     | 6  |
| 5.2. EQUATIONS.....                      | 7  |
| 5.3. LIMITS AND IC EXEMPTION .....       | 9  |
| 6. RF EXPOSURE RESULTS.....              | 10 |

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** GOOGLE  
1600 AMPHITHEATRE PARKWAY  
MOUNTAIN VIEW, CA, 94043 US

**EUT DESCRIPTION:** Tv Box, 10/100 Ethernet, MoCA 1.1/2.0, WiFi AP,  
HDMI 1.4 w/ HDCP

**MODEL:** GFHD200

**SERIAL NUMBER:** GTAFSJ1419D0016


**DATE TESTED:** May 7, 2014 to May 16, 2014

| APPLICABLE STANDARDS                    |              |
|---|--------------|
| STANDARD                                | TEST RESULTS |
| FCC PART 1 SUBPART I & PART 2 SUBPART J | Pass         |

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For  
UL Verification Services Inc. By:



---

FRANCISCO DE ANDA  
PROJECT LEAD  
UL Verification Services Inc.

Calculated By:



---

JOE VANG  
EMC ENGINEER  
UL Verification Services Inc.

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01.

## 3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. Document 14U17737-2, 14U17737-4 and 14U17737-5 for operation in the 2.4 GHz band and UL Verification Services Inc. Document 14U17737-3 for operation in the 5 GHz bands.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Antenna gain data is excerpted from product documentation provided by the applicant.

## 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

## 5. MAXIMUM PERMISSIBLE RF EXPOSURE

### 5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz)                                   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures        |                               |                               |                                     |                          |
| 0.3–3.0 .....   | 614                           | 1.63                          | *(100)                              | 6                        |
| 3.0–30 .....  | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | 6                        |
| 30–300 .....  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300–1500 .....  | .....                         | .....                         | f/300                               | 6                        |
| 1500–100,000 .....                                      | .....                         | .....                         | 5                                   | 6                        |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
| 0.3–1.34 .....  | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30 .....   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 30–300 .....          | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500 .....        | .....                         | .....                         | f/1500                              | 30                       |
| 1500–100,000 .....    | .....                         | .....                         | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## 5.2. EQUATIONS

### POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

Distance is given by:

$$D = \sqrt{(\text{EIRP} / (4 * \pi * S))}$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

**MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

Total EIRP = (EIRP1) + (EIRP2) + ... + (EIRPn)

where

EIRPx = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

**MIMO AND COLOCATED TRANSMITTERS**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as (Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

### 5.3. LIMITS AND IC EXEMPTION

#### VARIABLE LIMITS

For mobile radio equipment operating in the cellular phone band, the lowest power density limit is calculated using the lowest frequency:

824 MHz / 1500 = 0.55 mW/cm<sup>2</sup> (FCC)  
824 MHz / 150 = 5.5 W/m<sup>2</sup> (IC).

#### FIXED LIMITS

For operation in the PCS band, the 2.4 GHz band and the 5 GHz bands:

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup>  
From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m<sup>2</sup>

## 6. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

### Individual Transmitter Analysis

| Band                    | (GHz)      | 2.4   | 2.4         | 2.4   | 2.4         | 5.2   | 5.2   | 5.8   | 5.8   |
|-------------------------|------------|-------|-------------|-------|-------------|-------|-------|-------|-------|
| Mode                    |            | BLE   | BT          | WLAN  | WLAN        | WLAN  | WLAN  | WLAN  | WLAN  |
| Transmitter             | Chain      | 1     | 1           | 0     | 1           | 0     | 1     | 0     | 1     |
| Separation Distance     | (cm)       | 20    | 20          | 20    | 20          | 20    | 20    | 20    | 20    |
| Max. Ave. Output Power  | (dBm)      | 5.50  | 5.50        | 16.00 | 16.00       | 11.00 | 11.00 | 12.00 | 12.00 |
| Antenna Gain            | (dBi)      | 3.00  | 3.00        | 2.80  | 3.00        | 3.00  | 5.00  | 5.00  | 4.0   |
| Duty Cycle              | (%)        | 60.70 | 76.77       | 100   | 100         | 100   | 100   | 100   | 100   |
| Source Based EIRP       | (mW)       | 4.30  | 5.43        | 75.86 | 79.43       | 25.12 | 39.81 | 50.12 | 39.81 |
| FCC Power Density       | (mW/cm ^2) | 0.001 | 0.001       | 0.015 | 0.016       | 0.005 | 0.008 | 0.010 | 0.01  |
| FCC Power Density Limit | (mW/cm ^2) | 1     | 1           | 1     | 1           | 1     | 1     | 1     | 1     |
| IC Power Density        | (W/m ^2)   | 0.009 | 0.011       | 0.151 | 0.158       | 0.050 | 0.079 | 0.100 | 0.079 |
| IC Power Density Limit  | (W/m ^2)   | 10    | 10          | 10    | 10          | 10    | 10    | 10    | 10    |
| Fraction of Limit       | (%)        | 0.09  | <b>0.11</b> | 1.51  | <b>1.58</b> | 0.50  | 0.79  | 1.00  | 0.79  |

The device operates above 1.5 GHz with a maximum EIRP less than or equal to 5 Watts as a mobile device with a minimum separation distance of 20 cm, therefore it is exempt from routine RF Exposure Evaluation under RSS-102.

To determine the worst case WLAN mode relative to the power density limits for rf exposure:

- The fraction of the limit for BT 2.4 GHz 1x mode is **0.11 %**
- The fraction of the limit for WLAN 2.4 GHz 1x mode is **1.58 %**

Worst case fraction is **1.69%**.

Multiple chain or colocated transmitters

| Band  | (GHz)     | 2.4   | 2.4   | 2.4    | 5.2    | 5.8    |
|---|-----------|-------|-------|--------|--------|--------|
| Mode  |           | BLE   | BT    | WLAN   | WLAN   | WLAN   |
| Transmitter                                 | Chain     | 1     | 1     | 0+1    | 0+1    | 0+1    |
| Separation Distance                         | (cm)      | 20    | 20    | 20     | 20     | 20     |
| Max. Ave. Output Power                      | (dBm)     | 5.50  | 5.50  | 19.01  | 14.01  | 15.01  |
| Antenna Gain                                | (dBi)     | 3.00  | 3.00  | 3.00   | 7.50   | 5.20   |
| Duty Cycle                                  | (%)       | 60.70 | 76.77 | 100    | 100    | 100    |
| Source Based EIRP                           | (mW)      | 4.30  | 5.43  | 158.85 | 141.58 | 104.95 |
| FCC Power Density                           | (mW/cm^2) | 0.001 | 0.001 | 0.032  | 0.028  | 0.021  |
| FCC Power Density Limit                     | (mW/cm^2) | 1     | 1     | 1      | 1      | 1      |
| IC Power Density                            | (W/m^2)   | 0.009 | 0.011 | 0.316  | 0.282  | 0.209  |
| IC Power Density Limit                      | (W/m^2)   | 10    | 10    | 10     | 10     | 10     |
| Fraction of Limit                           | (%)       | 0.09  | 0.11  | 3.16   | 2.82   | 2.09   |
| Sum of Fractions (%) of active transmitters | 3.3       |       |       |        |        |        |

Collocated transmitters that can operate simultaneously are BT + 2.4G, BLE + 2.4G, BT + 5.2G, BLE + 5.2G, BT + 5.8G or BLE + 5.8G. The worst case are BT+2.4WLAN. The total contribution of the power density for each transmitter, as a fraction of the rf exposure limit for each transmitter, is 0.11% + 3.16% = 3.3%. As the sum of the fractions is less than or equal to one (less than or equal to 100%) the device complies with the rf exposure limits for fixed use.

See Operational Description for manufacturer's maximum output power settings. The manufacturer configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.

**END OF REPORT**