



FCC RADIO TEST REPORT

FCC ID : A4RGLBW0
Equipment : Phone
Model Name : GLBW0
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Nov. 27, 2024 and testing was performed from Dec. 17, 2024 to Mar. 21, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement	12
3.3 Dwell Time Measurement.....	13
3.4 20dB and 99% Bandwidth Measurement	14
3.5 Output Power Measurement.....	15
3.6 Conducted Band Edges Measurement.....	16
3.7 Conducted Spurious Emission Measurement	17
3.8 Radiated Band Edges and Spurious Emission Measurement	18
3.9 AC Conducted Emission Measurement.....	22
3.10 Antenna Requirements.....	24
4 List of Measuring Equipment	25
5 Measurement Uncertainty	27
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4N0919K	01	Initial issue of report	Apr. 17, 2025
FR4N0919K	02	Revise List of Measuring Equipment and Appendix A This report is an updated version, replacing the report issued on Apr. 17, 2025.	Apr. 25, 2025
FR4N0919K	03	Revise Appendix A This report is an updated version, replacing the report issued on Apr. 25, 2025.	May 02, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Pass	-
3.5	15.247(b)(1) 15.247(b)(4)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.9	15.207	AC Conducted Emission	Pass	-
3.10	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Clio Lo

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Wi-Fi 802.11ax, NFC, WPC Rx and GNSS Rx.
Antenna Type Bluetooth: <Ant. 3> : IFA Antenna <Ant. 4> : ILA Antenna

EUT Information List	
S/N	Performed Test Item
4B121FDCR000BE	RF Conducted Measurement
4C271FDCR000WM	Radiated Spurious Emission
4B121FDCR0006U	Conducted Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant.3: 0.7 Ant.4: -1.0

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2404-2478 MHz	2	2404	32	2434	59	2461
	3	2405	33	2435	60	2462
	4	2406	34	2436	61	2463
	5	2407	35	2437	62	2464
	6	2408	36	2438	63	2465
	7	2409	37	2439	64	2466
	8	2410	38	2440	65	2467
	9	2411	39	2441	66	2468
	10	2412	40	2442	67	2469
	11	2413	41	2443	68	2470
	12	2414	42	2444	69	2471
	13	2415	43	2445	70	2472
	14	2416	44	2446	71	2473
	15	2417	45	2447	72	2474
	16	2418	46	2448	73	2475
	17	2419	47	2449	74	2476
	18	2420	48	2450	75	2477
	19	2421	49	2451	76	2478
	20	2422	50	2452	-	-
	21	2423	51	2453	-	-
	22	2424	52	2454	-	-
	26	2428	53	2455	-	-
	27	2429	54	2456	-	-
	28	2430	55	2457	-	-
	29	2431	56	2458	-	-
	30	2432	57	2459	-	-
	31	2433	58	2460	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz) radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find X plane with Adapter as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases		
Test Item	Data Rate / Modulation	
Conducted Test Cases	Bluetooth LE 1Mbps CS ASK	Bluetooth LE 2Mbps CS ASK
	Mode 1: CH02_2404 MHz	Mode 4: CH02_2404 MHz
	Mode 2: CH38_2440 MHz	Mode 5: CH38_2440 MHz
	Mode 3: CH76_2478 MHz	Mode 6: CH76_2478 MHz
AC Conducted Emission	Mode 1 : BLE CS Channel 19 TX + USB Cable 2 (Charging from Adapter)	
Remark: 1. For Radiated Test Cases, the worst mode data rate 2Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 2Mbps, and no other significantly frequencies found in conducted spurious emission. 2. For Radiated Test Cases, the tests were performed with USB Cable 2. 3. During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test. 4. The detailed Radiated test modes are shown in Appendix C.		

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth-LE CS Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "BT DUT Control GUI.exe (v.03-11-24)" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW within 1-5% of the 99% bandwidth; VBW $\geq$ 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.
If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. The average power is compensated with duty factor.
6. Record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.8.3 Test Procedures


1. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT is arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW $\geq$ 10Hz; Sweep = auto; Detector function = peak; Trace = max hold for average
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
8. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Duty Cycle

Please refer to Appendix D.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.9.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.10.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	Dec. 24, 2024~ Mar. 13, 2025	Aug. 28, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ	CBL 6111D&00802 N1D01N-06	55606 & 08	30MHz~1GHz	Nov. 27, 2024	Dec. 24, 2024~ Mar. 13, 2025	Nov. 26, 2025	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 14, 2024	Dec. 24, 2024~ Mar. 13, 2025	Jul. 13, 2025	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18E N	1GHz~18GHz	Jul. 11, 2024	Dec. 24, 2024~ Mar. 13, 2025	Jul. 10, 2025	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1225	18GHz~40GHz	Jun. 24, 2024	Dec. 24, 2024~ Mar. 13, 2025	Jun. 23, 2025	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 27, 2024	Dec. 24, 2024~ Mar. 13, 2025	Sep. 26, 2025	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060873	18-40GHz	Sep. 02, 2024	Dec. 24, 2024~ Mar. 13, 2025	Sep. 01, 2025	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 24, 2024	Dec. 24, 2024~ Mar. 13, 2025	Sep. 23, 2025	Radiation (03CH22-HY)
MXE EMI Receive	AGILENT	N9038A	MY53290053	20Hz~26.5GHz	Sep. 09, 2024	Dec. 24, 2024~ Mar. 13, 2025	Sep. 08, 2025	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Dec. 24, 2024	Dec. 24, 2024~ Mar. 13, 2025	Dec. 23, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 24, 2024~ Mar. 13, 2025	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Dec. 24, 2024~ Mar. 13, 2025	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Dec. 24, 2024~ Mar. 13, 2025	N/A	Radiation (03CH22-HY)
Software	Audix	E3	RK-002347	N/A	N/A	Dec. 24, 2024~ Mar. 13, 2025	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	Dec. 24, 2024~ Mar. 04, 2025	Mar. 05, 2025	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Mar. 05, 2025~ Mar. 13, 2025	Mar. 04, 2026	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,804 611/2,804615/ 2	N/A	Oct. 23, 2024	Dec. 24, 2024~ Mar. 13, 2025	Oct. 22, 2025	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Dec. 17, 2024~ Mar. 14, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	1036004	N/A	Jul. 04, 2024	Dec. 17, 2024~ Mar. 14, 2025	Jul. 03, 2025	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GH z	Jul. 04, 2024	Dec. 17, 2024~ Mar. 14, 2025	Jul. 03, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	Dec. 17, 2024~ Mar. 14, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Dec. 17, 2024~ Mar. 14, 2025	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24121 1	N/A	Conducted Other Test Item	N/A	Dec. 17, 2024~ Mar. 14, 2025	N/A	Conducted (TH05-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 19, 2025~ Mar. 21, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 19, 2025~ Mar. 21, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Mar. 19, 2025~ Mar. 21, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Mar. 19, 2025~ Mar. 21, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Lisn	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 12, 2024	Mar. 19, 2025~ Mar. 21, 2025	Dec. 11, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Mar. 19, 2025~ Mar. 21, 2025	Sep. 22, 2025	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Mina Liu	Temperature:	21~25	°C
Test Date:	2024/12/17~2025/3/14	Relative Humidity:	51~54	%

<Ant. 3>

TEST RESULTS DATA									
20dB and 99% Occupied Bandwidth and Hopping Channel Separation									
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20dB BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
ASK	1Mbps	1	2	2404	0.514	0.514	0.994	0.3425	Pass
	1Mbps	1	38	2440	0.522	0.523	1.007	0.3481	Pass
	1Mbps	1	76	2478	0.527	0.528	0.994	0.3513	Pass
ASK	2Mbps	1	2	2404	1.003	0.996	0.986	0.6689	Pass
	2Mbps	1	38	2440	1.018	1.008	1.003	0.6790	Pass
	2Mbps	1	76	2478	1.035	1.027	1.007	0.6900	Pass

TEST RESULTS DATA						
Dwell Time						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
ASK	72	1809	0.045	0.081	0.4	Pass

TEST RESULTS DATA					
Peak Power Table					
DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
ASK 1Mbps	2	1	19.17	20.97	Pass
	38	1	19.29	20.97	Pass
	76	1	19.21	20.97	Pass
ASK 2Mbps	2	1	19.35	20.97	Pass
	38	1	19.53	20.97	Pass
	76	1	19.19	20.97	Pass

TEST RESULTS DATA				
Average Power Table				
(Reporting Only)				
DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
ASK 1Mbps	2	1	18.88	8.01
	38	1	18.92	8.01
	76	1	18.84	8.01
ASK 2Mbps	2	1	18.89	7.91
	38	1	18.94	7.91
	76	1	18.91	7.91

TEST RESULTS DATA			
Number of Hopping Frequency			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
72	15	> 15	Pass

<Ant. 4>

TEST RESULTS DATA**20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20dB BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
ASK	1Mbps	1	2	2404	0.514	0.513	0.990	0.3427	Pass
	1Mbps	1	38	2440	0.523	0.524	0.999	0.3484	Pass
	1Mbps	1	76	2478	0.527	0.529	0.999	0.3515	Pass
ASK	2Mbps	1	2	2404	1.005	0.997	1.007	0.6701	Pass
	2Mbps	1	38	2440	1.021	1.008	0.994	0.6805	Pass
	2Mbps	1	76	2478	1.034	1.028	0.994	0.6892	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
ASK	72	1772	0.045	0.079	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
ASK 1Mbps	2	1	18.76	20.97	Pass
	38	1	18.97	20.97	Pass
	76	1	18.78	20.97	Pass
ASK 2Mbps	2	1	18.70	20.97	Pass
	38	1	18.95	20.97	Pass
	76	1	18.62	20.97	Pass

TEST RESULTS DATA**Average Power Table
(Reporting Only)**

DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
ASK 1Mbps	2	1	18.65	8.08
	38	1	18.73	8.08
	76	1	18.60	8.08
ASK 2Mbps	2	1	18.54	7.94
	38	1	18.70	7.94
	76	1	18.55	7.94

TEST RESULTS DATA**Number of Hopping Frequency**


Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
72	15	> 15	Pass




<Ant.3>

Number of Hopping Frequency

<1Mbps>



<2Mbps>







Hopping Channel Separation

<1Mbps>


Channel Separation Plot on Channel 02 - 03



Channel Separation Plot on Channel 38 - 39




Channel Separation Plot on Channel 75 - 76






<2Mbps>


Channel Separation Plot on Channel 02 - 03




Channel Separation Plot on Channel 38 - 39



Channel Separation Plot on Channel 75 - 76



Dwell Time




Remark:

1. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

$$= 1809 \times 0.045 \text{ ms} = 0.081 \text{ sec}$$

2. The observation Occupancy time is hopping channel 72 channels x 400ms = 28.8sec using sweep point 30,000. This shows that 1ms per on-time contains 1 hop.

The total hops is finally counted via computer analysis.







20dB Bandwidth

<1Mbps>


20 dB Bandwidth Plot in Channel 02



20 dB Bandwidth Plot in Channel 38




20 dB Bandwidth Plot in Channel 76






<2Mbps>


20 dB Bandwidth Plot in Channel 02



20 dB Bandwidth Plot in Channel 38



20 dB Bandwidth Plot in Channel 76







99% Occupied Bandwidth

<1Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38




99% Occupied Bandwidth on Channel 76






<2Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38



99% Occupied Bandwidth on Channel 76







Band Edges

<1Mbps>

Low Band Edge Plot on Channel 02




High Band Edge Plot on Channel 76




<2Mbps>

Low Band Edge Plot on Channel 02




High Band Edge Plot on Channel 76






Hopping Mode Band Edges

<1Mbps>



<2Mbps>







Conducted Spurious Emission

<1Mbps>


CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz




CSE Plot on High Ch between 1GHz ~ 26.5GHz




<2Mbps>




CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz



CSE Plot on High Ch between 1GHz ~ 26.5GHz







<Ant.4>

Number of Hopping Frequency

<1Mbps>



<2Mbps>







Hopping Channel Separation

<1Mbps>


Channel Separation Plot on Channel 02 - 03



Channel Separation Plot on Channel 38 - 39




Channel Separation Plot on Channel 75 - 76






<2Mbps>


Channel Separation Plot on Channel 02 - 03




Channel Separation Plot on Channel 38 - 39



Channel Separation Plot on Channel 75 - 76



Dwell Time




Remark:

1. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

$$= 1772 \times 0.044667 \text{ ms} = 0.079 \text{ sec}$$



2. The observation Occupancy time is hopping channel 72 channels x 400ms = 28.8sec using sweep point 30,000. This shows that 1ms per on-time contains 1 hop.




The total hops is finally counted via computer analysis.








20 dB Bandwidth Plot in Channel 38





**99% Occupied Bandwidth**


<1Mbps>

99% Occupied Bandwidth on Channel 02**99% Occupied Bandwidth on Channel 38****99% Occupied Bandwidth on Channel 76**




<2Mbps>


99% Occupied Bandwidth on Channel 02



99% Occupied Bandwidth on Channel 38




99% Occupied Bandwidth on Channel 76






Band Edges

<1Mbps>




<2Mbps>





Hopping Mode Low Band Edge Plot







Conducted Spurious Emission

<1Mbps>


CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz




CSE Plot on High Ch between 1GHz ~ 26.5GHz






<2Mbps>


CSE Plot on Low Ch between 30MHz ~ 1 GHz




CSE Plot on Low Ch between 1GHz ~ 26.5GHz




CSE Plot on Mid. Ch between 30MHz ~ 1 GHz




CSE Plot on Mid. Ch between 1GHz ~ 26.5GHz



CSE Plot on High Ch between 30MHz ~ 1 GHz



CSE Plot on High Ch between 1GHz ~ 26.5GHz





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	16.1~22.7℃
		Relative Humidity :	45.9~48.9%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N0919
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	22.45	55.88	33.43	L1	OFF	19.8
0.152250	48.30	---	65.88	17.58	L1	OFF	19.8
0.168000	---	34.68	55.06	20.38	L1	OFF	19.8
0.168000	51.64	---	65.06	13.42	L1	OFF	19.8
0.181500	---	34.79	54.42	19.63	L1	OFF	19.8
0.181500	50.60	---	64.42	13.82	L1	OFF	19.8
0.217500	---	13.21	52.91	39.70	L1	OFF	19.8
0.217500	39.88	---	62.91	23.03	L1	OFF	19.8
0.273750	---	24.53	51.00	26.47	L1	OFF	19.8
0.273750	36.60	---	61.00	24.40	L1	OFF	19.8
0.683250	---	21.99	46.00	24.01	L1	OFF	19.8
0.683250	41.74	---	56.00	14.26	L1	OFF	19.8
22.152750	---	26.91	50.00	23.09	L1	OFF	20.7
22.152750	32.30	---	60.00	27.70	L1	OFF	20.7

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N0919
Mode 1
120Vac/60Hz
Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.151114	---	21.95	55.94	33.99	N	OFF	19.8
0.151114	47.65	---	65.94	18.29	N	OFF	19.8
0.167910	---	36.08	55.06	18.98	N	OFF	19.8
0.167910	52.04	---	65.06	13.02	N	OFF	19.8
0.172500	---	38.84	54.84	16.00	N	OFF	19.8
0.172500	52.11	---	64.84	12.73	N	OFF	19.8
0.208500	---	13.62	53.27	39.65	N	OFF	19.8
0.208500	40.47	---	63.27	22.80	N	OFF	19.8
0.263085	---	27.52	51.33	23.81	N	OFF	19.8
0.263085	38.14	---	61.33	23.19	N	OFF	19.8
0.683565	---	21.97	46.00	24.03	N	OFF	19.8
0.683565	42.90	---	56.00	13.10	N	OFF	19.8
22.542225	---	23.95	50.00	26.05	N	OFF	20.8
22.542225	29.32	---	60.00	30.68	N	OFF	20.8



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Bill Chang, York Huang and Ken Kuo	Temperature :	18.8~22.5℃
		Relative Humidity :	57.7~63.3%

Note symbol

-L	Low channel location
-R	High channel location

**C1. Radiated Spurious Emission Test Modes**

<Ant. 3>

<1Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 37	2400-2483.5	3	Bluetooth-LE ASK	02	2404	1Mbps	-	-
Mode 38	2400-2483.5	3	Bluetooth-LE ASK	38	2440	1Mbps	-	-
Mode 39	2400-2483.5	3	Bluetooth-LE ASK	76	2478	1Mbps	-	-
Mode 43	2400-2483.5	3	Bluetooth-LE ASK	76	2478	1Mbps	-	LF
Mode 44	2400-2483.5	3	Bluetooth-LE ASK	76	2478	1Mbps	-	SHF

<2Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 40	2400-2483.5	3	Bluetooth-LE ASK	02	2404	2Mbps	-	-
Mode 41	2400-2483.5	3	Bluetooth-LE ASK	38	2440	2Mbps	-	-
Mode 42	2400-2483.5	3	Bluetooth-LE ASK	76	2478	2Mbps	-	-

<Ant. 4>

<1Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 45	2400-2483.5	4	Bluetooth-LE ASK	02	2404	1Mbps	-	-
Mode 46	2400-2483.5	4	Bluetooth-LE ASK	38	2440	1Mbps	-	-
Mode 47	2400-2483.5	4	Bluetooth-LE ASK	76	2478	1Mbps	-	-
Mode 51	2400-2483.5	4	Bluetooth-LE ASK	38	2440	1Mbps	-	LF
Mode 52	2400-2483.5	4	Bluetooth-LE ASK	38	2440	1Mbps	-	SHF

<2Mbps>

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 48	2400-2483.5	4	Bluetooth-LE ASK	02	2404	2Mbps	-	-
Mode 49	2400-2483.5	4	Bluetooth-LE ASK	38	2440	2Mbps	-	-
Mode 50	2400-2483.5	4	Bluetooth-LE ASK	76	2478	2Mbps	-	-

**C2. Summary of each worse mode**

<Ant. 3>

<1Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
37	Bluetooth-LE ASK	02	2328.03	50.80	74.00	-23.20	V	Peak	Pass	-	Band Edge
37	Bluetooth-LE ASK	02	4808.00	45.42	74.00	-28.58	V	Peak	Pass	-	Harmonic
38	Bluetooth-LE ASK	38	2368.89	51.32	74.00	-22.68	V	Peak	Pass	-	Band Edge
38	Bluetooth-LE ASK	38	7320.00	49.55	74.00	-24.45	V	Peak	Pass	-	Harmonic
39	Bluetooth-LE ASK	76	2483.70	52.12	74.00	-21.88	H	Peak	Pass	-	Band Edge
39	Bluetooth-LE ASK	76	7434.00	48.39	74.00	-25.61	V	Peak	Pass	-	Harmonic
43	LF	76	33.88	30.68	40.00	-9.32	V	QP	Pass	-	LF
44	SHF	76	24720.00	42.38	74.00	-31.62	V	Peak	Pass	-	SHF

<2Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
40	Bluetooth-LE ASK	02	2388.60	50.56	74.00	-23.44	H	Peak	Pass	-	Band Edge
40	Bluetooth-LE ASK	02	4808.00	45.15	74.00	-28.85	H	Peak	Pass	-	Harmonic
41	Bluetooth-LE ASK	38	2384.10	50.94	74.00	-23.06	V	Peak	Pass	-	Band Edge
41	Bluetooth-LE ASK	38	7320.00	49.12	74.00	-24.88	V	Peak	Pass	-	Harmonic
42	Bluetooth-LE ASK	76	2484.83	51.74	74.00	-22.26	H	Peak	Pass	-	Band Edge
42	Bluetooth-LE ASK	76	7434.00	48.69	74.00	-25.31	V	Peak	Pass	-	Harmonic

**<Ant. 4>****<1Mbps>**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
45	Bluetooth-LE ASK	02	2340.28	50.87	74.00	-23.13	H	Peak	Pass	-	Band Edge
45	Bluetooth-LE ASK	02	4808.00	45.86	74.00	-28.14	H	Peak	Pass	-	Harmonic
46	Bluetooth-LE ASK	38	2346.79	50.97	74.00	-23.03	H	Peak	Pass	-	Band Edge
46	Bluetooth-LE ASK	38	7320.00	58.03	74.00	-15.97	V	Peak	Pass	-	Harmonic
47	Bluetooth-LE ASK	76	2488.29	51.38	74.00	-22.62	H	Peak	Pass	-	Band Edge
47	Bluetooth-LE ASK	76	7434.00	53.77	74.00	-20.23	V	Peak	Pass	-	Harmonic
51	LF	38	40.67	31.51	40.00	-8.49	V	QP	Pass	-	LF
52	SHF	38	24996.24	40.93	74.00	-33.07	V	Peak	Pass	-	SHF



<2Mbps>

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
48	Bluetooth-LE ASK	02	2368.31	50.98	74.00	-23.02	V	Peak	Pass	-	Band Edge
48	Bluetooth-LE ASK	02	4808.00	44.73	74.00	-29.27	H	Peak	Pass	-	Harmonic
49	Bluetooth-LE ASK	38	2322.61	50.76	74.00	-23.24	V	Peak	Pass	-	Band Edge
49	Bluetooth-LE ASK	38	7320.00	57.33	74.00	-16.67	V	Peak	Pass	-	Harmonic
50	Bluetooth-LE ASK	76	2483.87	51.45	74.00	-22.55	V	Peak	Pass	-	Band Edge
50	Bluetooth-LE ASK	76	7434.00	54.22	74.00	-19.78	V	Peak	Pass	-	Harmonic



<Ant. 3>



<1Mbps>

	37																																																											
Mode	Band Edge																																																											
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																											
ANT	3																																																											
Pol.	Horizontal					Fundamental																																																						
Peak																																																												
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																											
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2368.00</td><td>50.73</td><td>74.00</td><td>-23.27</td><td>37.68</td><td>27.00</td><td>8.59</td><td>32.57</td><td>10.03 144 212 PEAK</td></tr><tr><td>2</td><td>2368.00</td><td>-5.19</td><td>54.00</td><td>-59.19</td><td>--</td><td>--</td><td>--</td><td>--</td><td>144 212 AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2368.00	50.73	74.00	-23.27	37.68	27.00	8.59	32.57	10.03 144 212 PEAK	2	2368.00	-5.19	54.00	-59.19	--	--	--	--	144 212 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																				
1	2368.00	50.73	74.00	-23.27	37.68	27.00	8.59	32.57	10.03 144 212 PEAK																																																			
2	2368.00	-5.19	54.00	-59.19	--	--	--	--	144 212 AVERAGE																																																			
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																											
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2404.00</td><td>114.46</td><td>-----</td><td>-----</td><td>101.53</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03 144 212 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>58.54</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>144 212 AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2404.00	114.46	-----	-----	101.53	26.84	8.66	32.60	10.03 144 212 PEAK	2	2404.00	58.54	-----	-----	--	--	--	--	144 212 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																				
1	2404.00	114.46	-----	-----	101.53	26.84	8.66	32.60	10.03 144 212 PEAK																																																			
2	2404.00	58.54	-----	-----	--	--	--	--	144 212 AVERAGE																																																			





Mode	37																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Vertical	Fundamental																																																																																																				
Peak	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2328.03</td><td>50.00</td><td>74.00</td><td>-23.20</td><td>37.00</td><td>27.00</td><td>8.52</td><td>32.55</td><td>10.03 395 296 PEAK</td></tr><tr><td>2</td><td>2328.03</td><td>-5.12</td><td>54.00</td><td>-59.12</td><td>--</td><td>--</td><td>--</td><td>--</td><td>395 296 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2328.03	50.00	74.00	-23.20	37.00	27.00	8.52	32.55	10.03 395 296 PEAK	2	2328.03	-5.12	54.00	-59.12	--	--	--	--	395 296 AVERAGE	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2404.00</td><td>112.32</td><td>-----</td><td>-----</td><td>99.39</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03 395 296 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>56.40</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>395 296 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2404.00	112.32	-----	-----	99.39	26.84	8.66	32.60	10.03 395 296 PEAK	2	2404.00	56.40	-----	-----	--	--	--	--	395 296 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2328.03	50.00	74.00	-23.20	37.00	27.00	8.52	32.55	10.03 395 296 PEAK																																																																																													
2	2328.03	-5.12	54.00	-59.12	--	--	--	--	395 296 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2404.00	112.32	-----	-----	99.39	26.84	8.66	32.60	10.03 395 296 PEAK																																																																																													
2	2404.00	56.40	-----	-----	--	--	--	--	395 296 AVERAGE																																																																																													



Mode	37																																																																					
	Harmonic																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																					
ANT	3																																																																					
Pol.	Horizontal						Vertical																																																															
Peak Avg																																																																						
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL																																																															
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4808.00</td><td>45.11</td><td>74.00</td><td>-28.89</td><td>33.47</td><td>32.40</td><td>12.43</td><td>33.67</td><td>0.48</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-10.81</td><td>54.00</td><td>-64.81</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>															Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4808.00	45.11	74.00	-28.89	33.47	32.40	12.43	33.67	0.48	--	--	PEAK	2	4808.00	-10.81	54.00	-64.81	--	--	--	--	--	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																												
1	4808.00	45.11	74.00	-28.89	33.47	32.40	12.43	33.67	0.48	--	--	PEAK																																																										
2	4808.00	-10.81	54.00	-64.81	--	--	--	--	--	--	--	Average																																																										




Mode	37	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m)  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	Level (dBuV/m)  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL



Mode	38																																																																																																															
	Band Edge - L																																																																																																															
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																																															
ANT	3																																																																																																															
Pol.	Horizontal						Fundamental																																																																																																									
Peak	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2320.01</td><td>50.99</td><td>74.00</td><td>-23.01</td><td>38.00</td><td>27.00</td><td>8.50</td><td>32.54</td><td>10.03 123 261 PEAK</td></tr><tr><td>2</td><td>2320.01</td><td>-4.93</td><td>54.00</td><td>-58.93</td><td>--</td><td>--</td><td>--</td><td>--</td><td>123 261 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2320.01	50.99	74.00	-23.01	38.00	27.00	8.50	32.54	10.03 123 261 PEAK	2	2320.01	-4.93	54.00	-58.93	--	--	--	--	123 261 AVERAGE	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2440.00</td><td>114.54</td><td>-----</td><td>-----</td><td>101.71</td><td>26.70</td><td>8.72</td><td>32.62</td><td>10.03 123 261 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>58.62</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>123 261 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2440.00	114.54	-----	-----	101.71	26.70	8.72	32.62	10.03 123 261 PEAK	2	2440.00	58.62	-----	-----	--	--	--	--	123 261 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																								
1	2320.01	50.99	74.00	-23.01	38.00	27.00	8.50	32.54	10.03 123 261 PEAK																																																																																																							
2	2320.01	-4.93	54.00	-58.93	--	--	--	--	123 261 AVERAGE																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																								
1	2440.00	114.54	-----	-----	101.71	26.70	8.72	32.62	10.03 123 261 PEAK																																																																																																							
2	2440.00	58.62	-----	-----	--	--	--	--	123 261 AVERAGE																																																																																																							




Mode	38																																																					
	Band Edge - R																																																					
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																					
ANT	3																																																					
Pol.	Horizontal	Fundamental																																																				
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2489.00</td><td>50.62</td><td>74.00</td><td>-23.38</td><td>37.73</td><td>26.70</td><td>8.81</td><td>32.65</td><td>10.03</td><td>123</td><td>261</td><td>PEAK</td></tr><tr><td>2</td><td>2489.00</td><td>-5.30</td><td>54.00</td><td>-59.30</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>123</td><td>261</td><td>AVERAGE</td></tr></table>		Freq	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2489.00	50.62	74.00	-23.38	37.73	26.70	8.81	32.65	10.03	123	261	PEAK	2	2489.00	-5.30	54.00	-59.30	--	--	--	--	--	123	261	AVERAGE	Blank
	Freq	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	2489.00	50.62	74.00	-23.38	37.73	26.70	8.81	32.65	10.03	123	261	PEAK																																										
2	2489.00	-5.30	54.00	-59.30	--	--	--	--	--	123	261	AVERAGE																																										





Mode	38																																																																																																					
	Band Edge - L																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Vertical	Fundamental																																																																																																				
Peak	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2368.09</td><td>51.32</td><td>74.00</td><td>-22.68</td><td>38.27</td><td>27.00</td><td>8.59</td><td>32.57</td><td>10.03 379 292 PEAK</td></tr><tr><td>2</td><td>2368.09</td><td>-4.60</td><td>54.00</td><td>-58.60</td><td>--</td><td>--</td><td>--</td><td>--</td><td>379 292 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2368.09	51.32	74.00	-22.68	38.27	27.00	8.59	32.57	10.03 379 292 PEAK	2	2368.09	-4.60	54.00	-58.60	--	--	--	--	379 292 AVERAGE	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2440.00</td><td>111.42</td><td>-----</td><td>-----</td><td>98.59</td><td>26.70</td><td>8.72</td><td>32.62</td><td>10.03 379 292 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>55.50</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>379 292 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2440.00	111.42	-----	-----	98.59	26.70	8.72	32.62	10.03 379 292 PEAK	2	2440.00	55.50	-----	-----	--	--	--	--	379 292 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2368.09	51.32	74.00	-22.68	38.27	27.00	8.59	32.57	10.03 379 292 PEAK																																																																																													
2	2368.09	-4.60	54.00	-58.60	--	--	--	--	379 292 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2440.00	111.42	-----	-----	98.59	26.70	8.72	32.62	10.03 379 292 PEAK																																																																																													
2	2440.00	55.50	-----	-----	--	--	--	--	379 292 AVERAGE																																																																																													





Mode	38																																																																			
	Band Edge - R																																																																			
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																			
ANT	3																																																																			
Pol.	Vertical						Fundamental																																																													
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2483.74</td><td>50.69</td><td>74.00</td><td>-23.31</td><td>37.81</td><td>26.70</td><td>8.80</td><td>32.65</td><td>10.03</td><td>379</td><td>292</td><td>PEAK</td></tr><tr><td>2</td><td>2483.74</td><td>-5.23</td><td>54.00</td><td>-59.23</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>379</td><td>292</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2483.74	50.69	74.00	-23.31	37.81	26.70	8.80	32.65	10.03	379	292	PEAK	2	2483.74	-5.23	54.00	-59.23	--	--	--	--	--	379	292	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																												
1	2483.74	50.69	74.00	-23.31	37.81	26.70	8.80	32.65	10.03	379	292	PEAK																																																								
2	2483.74	-5.23	54.00	-59.23	--	--	--	--	--	379	292	AVERAGE																																																								





Mode	38																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																									
ANT	3																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg																																																																																										
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>45.11</td><td>74.00</td><td>-28.89</td><td>33.33</td><td>32.46</td><td>12.49</td><td>33.67</td><td>0.50</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>-10.81</td><td>54.00</td><td>-64.81</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>48.86</td><td>74.00</td><td>-25.14</td><td>32.42</td><td>37.20</td><td>15.41</td><td>36.61</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>-7.06</td><td>54.00</td><td>-61.06</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	45.11	74.00	-28.89	33.33	32.46	12.49	33.67	0.50	--	PEAK	2	4880.00	-10.81	54.00	-64.81	--	--	--	--	--	--	Average	3	7320.00	48.86	74.00	-25.14	32.42	37.20	15.41	36.61	0.44	--	PEAK	4	7320.00	-7.06	54.00	-61.06	--	--	--	--	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4880.00	45.11	74.00	-28.89	33.33	32.46	12.49	33.67	0.50	--	PEAK																																																																															
2	4880.00	-10.81	54.00	-64.81	--	--	--	--	--	--	Average																																																																															
3	7320.00	48.86	74.00	-25.14	32.42	37.20	15.41	36.61	0.44	--	PEAK																																																																															
4	7320.00	-7.06	54.00	-61.06	--	--	--	--	--	--	Average																																																																															



Mode	38	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL





Mode	39																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Horizontal	Fundamental																																																																																																				
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2483.70</td><td>52.12</td><td>74.00</td><td>-21.88</td><td>39.24</td><td>26.70</td><td>8.00</td><td>32.65</td><td>10.03 191 214 PEAK</td></tr><tr><td>2</td><td>2483.70</td><td>-3.00</td><td>54.00</td><td>-57.00</td><td>--</td><td>--</td><td>--</td><td>--</td><td>191 214 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2483.70	52.12	74.00	-21.88	39.24	26.70	8.00	32.65	10.03 191 214 PEAK	2	2483.70	-3.00	54.00	-57.00	--	--	--	--	191 214 AVERAGE	 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2478.00</td><td>113.53</td><td>-----</td><td>-----</td><td>100.68</td><td>26.68</td><td>8.79</td><td>32.65</td><td>10.03 191 214 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>57.61</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>191 214 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2478.00	113.53	-----	-----	100.68	26.68	8.79	32.65	10.03 191 214 PEAK	2	2478.00	57.61	-----	-----	--	--	--	--	191 214 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2483.70	52.12	74.00	-21.88	39.24	26.70	8.00	32.65	10.03 191 214 PEAK																																																																																													
2	2483.70	-3.00	54.00	-57.00	--	--	--	--	191 214 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2478.00	113.53	-----	-----	100.68	26.68	8.79	32.65	10.03 191 214 PEAK																																																																																													
2	2478.00	57.61	-----	-----	--	--	--	--	191 214 AVERAGE																																																																																													



Mode	39																																																																																																													
	Band Edge																																																																																																													
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																																													
ANT	3																																																																																																													
Pol.	Vertical					Fundamental																																																																																																								
Peak	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2487.23</td><td>50.85</td><td>74.00</td><td>-23.15</td><td>37.96</td><td>26.70</td><td>8.81</td><td>32.65</td><td>10.03 400 305 PEAK</td></tr><tr><td>2</td><td>2487.23</td><td>-5.07</td><td>54.00</td><td>-59.07</td><td>--</td><td>--</td><td>--</td><td>--</td><td>400 305 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2487.23	50.85	74.00	-23.15	37.96	26.70	8.81	32.65	10.03 400 305 PEAK	2	2487.23	-5.07	54.00	-59.07	--	--	--	--	400 305 AVERAGE	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2478.00</td><td>100.81</td><td>-----</td><td>-----</td><td>95.96</td><td>26.68</td><td>8.79</td><td>32.65</td><td>10.03 400 305 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>52.89</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>400 305 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2478.00	100.81	-----	-----	95.96	26.68	8.79	32.65	10.03 400 305 PEAK	2	2478.00	52.89	-----	-----	--	--	--	--	400 305 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																						
1	2487.23	50.85	74.00	-23.15	37.96	26.70	8.81	32.65	10.03 400 305 PEAK																																																																																																					
2	2487.23	-5.07	54.00	-59.07	--	--	--	--	400 305 AVERAGE																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																						
1	2478.00	100.81	-----	-----	95.96	26.68	8.79	32.65	10.03 400 305 PEAK																																																																																																					
2	2478.00	52.89	-----	-----	--	--	--	--	400 305 AVERAGE																																																																																																					





Mode	39												
	Harmonic												
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz												
ANT	3												
Pol.	Horizontal						Vertical						
Peak Avg													
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL						
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB		Level	Factor	Loss	Factor	Factor			
1	4956.00	45.21	74.00	-28.79		33.09	32.70	12.56	33.67	0.53	--	--	PEAK
2	4956.00	-10.71	54.00	-64.71		--	--	--	--	--	--	--	Average
3	7434.00	48.19	74.00	-25.81		31.68	37.24	15.54	36.78	0.51	--	--	PEAK
4	7434.00	-7.73	54.00	-61.73		--	--	--	--	--	--	--	Average
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB		Level	Factor	Loss	Factor	Factor			
1	4956.00	45.23	74.00	-28.77		33.11	32.70	12.56	33.67	0.53	--	--	PEAK
2	4956.00	-10.69	54.00	-64.69		--	--	--	--	--	--	--	Average
3	7434.00	48.39	74.00	-25.61		31.88	37.24	15.54	36.78	0.51	--	--	PEAK
4	7434.00	-7.53	54.00	-61.53		--	--	--	--	--	--	--	Average



Mode	39	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL





Mode	43																																																																																																																
	LF																																																																																																																
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																																																
ANT	3																																																																																																																
Pol.	Horizontal						Vertical																																																																																																										
QPI Peak																																																																																																																	
	Site : 03CH20-HY Condition: QP 3m Bilog_55606 & 08_241127 HORIZONTAL																																																																																																																
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>32.91</td><td>24.08</td><td>40.00</td><td>-15.92</td><td>35.38</td><td>23.21</td><td>1.01</td><td>35.75</td><td>0.23</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>200.72</td><td>32.55</td><td>43.50</td><td>-10.95</td><td>50.25</td><td>15.09</td><td>2.52</td><td>35.51</td><td>0.20</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>272.50</td><td>35.73</td><td>46.00</td><td>-10.27</td><td>49.05</td><td>18.91</td><td>2.93</td><td>35.35</td><td>0.19</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>400.30</td><td>30.37</td><td>46.00</td><td>-15.63</td><td>39.50</td><td>22.12</td><td>3.58</td><td>34.98</td><td>0.15</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>751.68</td><td>31.48</td><td>46.00</td><td>-14.52</td><td>32.26</td><td>28.11</td><td>4.85</td><td>33.88</td><td>0.14</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>959.26</td><td>34.77</td><td>46.00</td><td>-11.23</td><td>31.28</td><td>31.07</td><td>5.45</td><td>33.12</td><td>0.09</td><td>--</td><td>Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	32.91	24.08	40.00	-15.92	35.38	23.21	1.01	35.75	0.23	--	Peak	2	200.72	32.55	43.50	-10.95	50.25	15.09	2.52	35.51	0.20	--	Peak	3	272.50	35.73	46.00	-10.27	49.05	18.91	2.93	35.35	0.19	--	Peak	4	400.30	30.37	46.00	-15.63	39.50	22.12	3.58	34.98	0.15	--	Peak	5	751.68	31.48	46.00	-14.52	32.26	28.11	4.85	33.88	0.14	--	Peak	6	959.26	34.77	46.00	-11.23	31.28	31.07	5.45	33.12	0.09	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1	32.91	24.08	40.00	-15.92	35.38	23.21	1.01	35.75	0.23	--	Peak																																																																																																						
2	200.72	32.55	43.50	-10.95	50.25	15.09	2.52	35.51	0.20	--	Peak																																																																																																						
3	272.50	35.73	46.00	-10.27	49.05	18.91	2.93	35.35	0.19	--	Peak																																																																																																						
4	400.30	30.37	46.00	-15.63	39.50	22.12	3.58	34.98	0.15	--	Peak																																																																																																						
5	751.68	31.48	46.00	-14.52	32.26	28.11	4.85	33.88	0.14	--	Peak																																																																																																						
6	959.26	34.77	46.00	-11.23	31.28	31.07	5.45	33.12	0.09	--	Peak																																																																																																						
Site : 03CH20-HY Condition: QP 3m Bilog_55606 & 08_241127 VERTICAL																																																																																																																	
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>30.68</td><td>40.00</td><td>-9.32</td><td>42.46</td><td>22.74</td><td>1.02</td><td>35.75</td><td>0.21</td><td>101</td><td>358 QP</td></tr><tr><td>2</td><td>42.61</td><td>28.46</td><td>40.00</td><td>-11.54</td><td>44.77</td><td>18.05</td><td>1.16</td><td>35.75</td><td>0.23</td><td>105</td><td>96 QP</td></tr><tr><td>3</td><td>53.28</td><td>29.16</td><td>40.00</td><td>-10.84</td><td>50.16</td><td>13.20</td><td>1.29</td><td>35.73</td><td>0.24</td><td>104</td><td>358 QP</td></tr><tr><td>4</td><td>83.35</td><td>29.71</td><td>40.00</td><td>-10.29</td><td>49.77</td><td>13.00</td><td>1.63</td><td>35.70</td><td>0.21</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>200.72</td><td>28.65</td><td>43.50</td><td>-14.85</td><td>46.35</td><td>15.09</td><td>2.52</td><td>35.51</td><td>0.20</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>409.27</td><td>30.96</td><td>46.00</td><td>-15.04</td><td>40.07</td><td>22.14</td><td>3.58</td><td>34.98</td><td>0.15</td><td>--</td><td>Peak</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	33.88	30.68	40.00	-9.32	42.46	22.74	1.02	35.75	0.21	101	358 QP	2	42.61	28.46	40.00	-11.54	44.77	18.05	1.16	35.75	0.23	105	96 QP	3	53.28	29.16	40.00	-10.84	50.16	13.20	1.29	35.73	0.24	104	358 QP	4	83.35	29.71	40.00	-10.29	49.77	13.00	1.63	35.70	0.21	--	Peak	5	200.72	28.65	43.50	-14.85	46.35	15.09	2.52	35.51	0.20	--	Peak	6	409.27	30.96	46.00	-15.04	40.07	22.14	3.58	34.98	0.15	--	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1	33.88	30.68	40.00	-9.32	42.46	22.74	1.02	35.75	0.21	101	358 QP																																																																																																						
2	42.61	28.46	40.00	-11.54	44.77	18.05	1.16	35.75	0.23	105	96 QP																																																																																																						
3	53.28	29.16	40.00	-10.84	50.16	13.20	1.29	35.73	0.24	104	358 QP																																																																																																						
4	83.35	29.71	40.00	-10.29	49.77	13.00	1.63	35.70	0.21	--	Peak																																																																																																						
5	200.72	28.65	43.50	-14.85	46.35	15.09	2.52	35.51	0.20	--	Peak																																																																																																						
6	409.27	30.96	46.00	-15.04	40.07	22.14	3.58	34.98	0.15	--	Peak																																																																																																						





Mode	44																																																																																															
	SHF																																																																																															
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																															
ANT	3																																																																																															
Pol.	Horizontal								Vertical																																																																																							
Peak	Site : 03CH22-HY Condition: PEAK_74 1m SHF_1225_240624 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 23082.00</td><td>41.54</td><td>74.00 -32.46</td><td>44.67</td><td>38.86</td><td>28.25</td><td>60.70</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 23082.00	41.54	74.00 -32.46	44.67	38.86	28.25	60.70	-9.54	--	-- Peak	Site : 03CH22-HY Condition: PEAK_74 1m SHF_1225_240624 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 24720.00</td><td>42.38</td><td>74.00 -31.62</td><td>43.57</td><td>39.30</td><td>29.37</td><td>60.32</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 24720.00	42.38	74.00 -31.62	43.57	39.30	29.37	60.32	-9.54	--	-- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1 23082.00	41.54	74.00 -32.46	44.67	38.86	28.25	60.70	-9.54	--	-- Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1 24720.00	42.38	74.00 -31.62	43.57	39.30	29.37	60.32	-9.54	--	-- Peak																																																																																							





<2Mbps>

Mode	40																																																																																																																												
	Band Edge																																																																																																																												
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																																												
ANT	3																																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																																						
Peak																																																																																																																													
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2388.60</td><td>50.56</td><td>74.00</td><td>-23.44</td><td>37.78</td><td>26.71</td><td>8.63</td><td>32.59</td><td>10.03</td><td>100</td><td>259</td><td>PEAK</td></tr><tr><td>2</td><td>2388.60</td><td>-5.36</td><td>54.00</td><td>-59.36</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>100</td><td>259</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.60	50.56	74.00	-23.44	37.78	26.71	8.63	32.59	10.03	100	259	PEAK	2	2388.60	-5.36	54.00	-59.36	--	--	--	--	--	100	259	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2404.00</td><td>116.36</td><td>-----</td><td>-----</td><td>103.43</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03</td><td>100</td><td>259</td><td>PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>60.44</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>100</td><td>259</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	116.36	-----	-----	103.43	26.84	8.66	32.60	10.03	100	259	PEAK	2	2404.00	60.44	-----	-----	--	--	--	--	--	100	259
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2388.60	50.56	74.00	-23.44	37.78	26.71	8.63	32.59	10.03	100	259	PEAK																																																																																																																	
2	2388.60	-5.36	54.00	-59.36	--	--	--	--	--	100	259	AVERAGE																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2404.00	116.36	-----	-----	103.43	26.84	8.66	32.60	10.03	100	259	PEAK																																																																																																																	
2	2404.00	60.44	-----	-----	--	--	--	--	--	100	259	AVERAGE																																																																																																																	



Mode	40																																																																																																													
	Band Edge																																																																																																													
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																													
ANT	3																																																																																																													
Pol.	Vertical					Fundamental																																																																																																								
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2363.31</td><td>50.19</td><td>74.00</td><td>-23.81</td><td>37.15</td><td>27.00</td><td>8.58</td><td>32.57</td><td>10.03 394 294 PEAK</td></tr><tr><td>2</td><td>2363.31</td><td>-5.73</td><td>54.00</td><td>-59.73</td><td>--</td><td>--</td><td>--</td><td>--</td><td>394 294 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2363.31	50.19	74.00	-23.81	37.15	27.00	8.58	32.57	10.03 394 294 PEAK	2	2363.31	-5.73	54.00	-59.73	--	--	--	--	394 294 AVERAGE	 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2404.00</td><td>112.65</td><td>-----</td><td>-----</td><td>99.72</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03 394 294 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>56.73</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>394 294 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2404.00	112.65	-----	-----	99.72	26.84	8.66	32.60	10.03 394 294 PEAK	2	2404.00	56.73	-----	-----	--	--	--	--	394 294 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																						
1	2363.31	50.19	74.00	-23.81	37.15	27.00	8.58	32.57	10.03 394 294 PEAK																																																																																																					
2	2363.31	-5.73	54.00	-59.73	--	--	--	--	394 294 AVERAGE																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																																						
1	2404.00	112.65	-----	-----	99.72	26.84	8.66	32.60	10.03 394 294 PEAK																																																																																																					
2	2404.00	56.73	-----	-----	--	--	--	--	394 294 AVERAGE																																																																																																					



Mode	40																																																																																																																																			
	Harmonic																																																																																																																																			
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																																																			
ANT	3																																																																																																																																			
Pol.	Horizontal						Vertical																																																																																																																													
Peak Avg																																																																																																																																				
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL																																																																																																																													
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4808.00</td><td>45.15</td><td>74.00</td><td>-28.85</td><td>33.51</td><td>32.40</td><td>12.43</td><td>33.67</td><td>0.48</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-10.77</td><td>54.00</td><td>-64.77</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4808.00	45.15	74.00	-28.85	33.51	32.40	12.43	33.67	0.48	--	--	PEAK	2	4808.00	-10.77	54.00	-64.77	--	--	--	--	--	--	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4808.00</td><td>44.64</td><td>74.00</td><td>-29.36</td><td>33.00</td><td>32.40</td><td>12.43</td><td>33.67</td><td>0.48</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-11.28</td><td>54.00</td><td>-65.28</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4808.00	44.64	74.00	-29.36	33.00	32.40	12.43	33.67	0.48	--	--	PEAK	2	4808.00	-11.28	54.00	-65.28	--	--	--	--	--	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	4808.00	45.15	74.00	-28.85	33.51	32.40	12.43	33.67	0.48	--	--	PEAK																																																																																																																								
2	4808.00	-10.77	54.00	-64.77	--	--	--	--	--	--	--	Average																																																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	4808.00	44.64	74.00	-29.36	33.00	32.40	12.43	33.67	0.48	--	--	PEAK																																																																																																																								
2	4808.00	-11.28	54.00	-65.28	--	--	--	--	--	--	--	Average																																																																																																																								




Mode	40	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL





Mode	41																																																																																																					
	Band Edge - L																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Horizontal	Fundamental																																																																																																				
Peak	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2352.12</td><td>50.46</td><td>74.00</td><td>-23.54</td><td>37.51</td><td>26.92</td><td>8.56</td><td>32.56</td><td>10.03 143 260 PEAK</td></tr><tr><td>2</td><td>2352.12</td><td>-5.46</td><td>54.00</td><td>-59.46</td><td>--</td><td>--</td><td>--</td><td>--</td><td>143 260 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2352.12	50.46	74.00	-23.54	37.51	26.92	8.56	32.56	10.03 143 260 PEAK	2	2352.12	-5.46	54.00	-59.46	--	--	--	--	143 260 AVERAGE	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2440.00</td><td>115.18</td><td>-----</td><td>-----</td><td>102.35</td><td>26.70</td><td>8.72</td><td>32.62</td><td>10.03 143 260 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>59.26</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>143 260 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2440.00	115.18	-----	-----	102.35	26.70	8.72	32.62	10.03 143 260 PEAK	2	2440.00	59.26	-----	-----	--	--	--	--	143 260 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2352.12	50.46	74.00	-23.54	37.51	26.92	8.56	32.56	10.03 143 260 PEAK																																																																																													
2	2352.12	-5.46	54.00	-59.46	--	--	--	--	143 260 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2440.00	115.18	-----	-----	102.35	26.70	8.72	32.62	10.03 143 260 PEAK																																																																																													
2	2440.00	59.26	-----	-----	--	--	--	--	143 260 AVERAGE																																																																																													




Mode	41																																																									
	Band Edge - R																																																									
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																									
ANT	3																																																									
Pol.	Horizontal	Fundamental																																																								
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.60</td><td>50.72</td><td>74.00</td><td>-23.28</td><td></td><td>37.84</td><td>26.70</td><td>8.80</td><td>32.65</td><td>10.03</td><td>143</td><td>260</td><td>PEAK</td></tr><tr><td>2</td><td>2483.60</td><td>-5.20</td><td>54.00</td><td>-59.20</td><td></td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>143</td><td>260</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.60	50.72	74.00	-23.28		37.84	26.70	8.80	32.65	10.03	143	260	PEAK	2	2483.60	-5.20	54.00	-59.20		--	--	--	--	--	143	260	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	2483.60	50.72	74.00	-23.28		37.84	26.70	8.80	32.65	10.03	143	260	PEAK																																													
2	2483.60	-5.20	54.00	-59.20		--	--	--	--	--	143	260	AVERAGE																																													





Mode	41																																																																																																					
	Band Edge - L																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Vertical	Fundamental																																																																																																				
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2384.10</td><td>50.94</td><td>74.00</td><td>-23.06</td><td>38.11</td><td>26.76</td><td>8.62</td><td>32.58</td><td>10.03 301 PEAK</td></tr><tr><td>2</td><td>2384.10</td><td>-4.98</td><td>54.00</td><td>-58.98</td><td>--</td><td>--</td><td>--</td><td>--</td><td>301 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2384.10	50.94	74.00	-23.06	38.11	26.76	8.62	32.58	10.03 301 PEAK	2	2384.10	-4.98	54.00	-58.98	--	--	--	--	301 AVERAGE	 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2440.00</td><td>111.78</td><td>-----</td><td>-----</td><td>98.95</td><td>26.70</td><td>8.72</td><td>32.62</td><td>10.03 301 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>55.86</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>301 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2440.00	111.78	-----	-----	98.95	26.70	8.72	32.62	10.03 301 PEAK	2	2440.00	55.86	-----	-----	--	--	--	--	301 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2384.10	50.94	74.00	-23.06	38.11	26.76	8.62	32.58	10.03 301 PEAK																																																																																													
2	2384.10	-4.98	54.00	-58.98	--	--	--	--	301 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2440.00	111.78	-----	-----	98.95	26.70	8.72	32.62	10.03 301 PEAK																																																																																													
2	2440.00	55.86	-----	-----	--	--	--	--	301 AVERAGE																																																																																													



Mode	41																																																										
	Band Edge - R																																																										
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																										
ANT	3																																																										
Pol.	Vertical	Fundamental																																																									
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.64</td><td>50.15</td><td>74.00</td><td>-23.85</td><td>37.26</td><td>26.70</td><td>8.81</td><td>32.65</td><td>10.03</td><td>301</td><td>301</td><td>PEAK</td></tr><tr><td>2</td><td>2487.64</td><td>-5.77</td><td>54.00</td><td>-59.77</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>301</td><td>301</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2487.64	50.15	74.00	-23.85	37.26	26.70	8.81	32.65	10.03	301	301	PEAK	2	2487.64	-5.77	54.00	-59.77	--	--	--	--	--	301	301	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	2487.64	50.15	74.00	-23.85	37.26	26.70	8.81	32.65	10.03	301	301	PEAK																																															
2	2487.64	-5.77	54.00	-59.77	--	--	--	--	--	301	301	AVERAGE																																															





Mode	41																																																																																																																																																																																
	Harmonic																																																																																																																																																																																
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz																																																																																																																																																																																
ANT	3																																																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																																																										
Peak Avg																																																																																																																																																																																	
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4880.00</td><td>44.80</td><td>74.00</td><td>-29.20</td><td>33.02</td><td>32.46</td><td>12.49</td><td>33.67</td><td>0.50</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>-11.12</td><td>54.00</td><td>-65.12</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>48.62</td><td>74.00</td><td>-25.38</td><td>32.18</td><td>37.20</td><td>15.41</td><td>36.61</td><td>0.44</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7320.00</td><td>-7.30</td><td>54.00</td><td>-61.30</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	44.80	74.00	-29.20	33.02	32.46	12.49	33.67	0.50	--	--	Peak	2	4880.00	-11.12	54.00	-65.12	--	--	--	--	--	--	--	Average	3	7320.00	48.62	74.00	-25.38	32.18	37.20	15.41	36.61	0.44	--	--	Peak	4	7320.00	-7.30	54.00	-61.30	--	--	--	--	--	--	--	Average	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4880.00</td><td>44.69</td><td>74.00</td><td>-29.31</td><td>32.91</td><td>32.46</td><td>12.49</td><td>33.67</td><td>0.50</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>4880.00</td><td>-11.23</td><td>54.00</td><td>-65.23</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>49.12</td><td>74.00</td><td>-24.88</td><td>32.68</td><td>37.20</td><td>15.41</td><td>36.61</td><td>0.44</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>7320.00</td><td>-6.80</td><td>54.00</td><td>-60.80</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	44.69	74.00	-29.31	32.91	32.46	12.49	33.67	0.50	--	--	Peak	2	4880.00	-11.23	54.00	-65.23	--	--	--	--	--	--	--	Average	3	7320.00	49.12	74.00	-24.88	32.68	37.20	15.41	36.61	0.44	--	--	Peak	4	7320.00	-6.80	54.00	-60.80	--	--	--	--	--	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	4880.00	44.80	74.00	-29.20	33.02	32.46	12.49	33.67	0.50	--	--	Peak																																																																																																																																																																					
2	4880.00	-11.12	54.00	-65.12	--	--	--	--	--	--	--	Average																																																																																																																																																																					
3	7320.00	48.62	74.00	-25.38	32.18	37.20	15.41	36.61	0.44	--	--	Peak																																																																																																																																																																					
4	7320.00	-7.30	54.00	-61.30	--	--	--	--	--	--	--	Average																																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	4880.00	44.69	74.00	-29.31	32.91	32.46	12.49	33.67	0.50	--	--	Peak																																																																																																																																																																					
2	4880.00	-11.23	54.00	-65.23	--	--	--	--	--	--	--	Average																																																																																																																																																																					
3	7320.00	49.12	74.00	-24.88	32.68	37.20	15.41	36.61	0.44	--	--	Peak																																																																																																																																																																					
4	7320.00	-6.80	54.00	-60.80	--	--	--	--	--	--	--	Average																																																																																																																																																																					





Mode	41	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL





Mode	42																																																																																																																											
	Band Edge																																																																																																																											
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																																																											
ANT	3																																																																																																																											
Pol.	Horizontal						Fundamental																																																																																																																					
Peak																																																																																																																												
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																					
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.83</td><td>51.74</td><td>74.00</td><td>-22.26</td><td>38.85</td><td>26.70</td><td>8.81</td><td>32.65</td><td>10.03</td><td>112</td><td>263</td><td>PEAK</td></tr><tr><td>2</td><td>2484.83</td><td>-4.18</td><td>54.00</td><td>-58.18</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>112</td><td>263</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg	1	2484.83	51.74	74.00	-22.26	38.85	26.70	8.81	32.65	10.03	112	263	PEAK	2	2484.83	-4.18	54.00	-58.18	--	--	--	--	--	112	263	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>114.74</td><td>-----</td><td>-----</td><td>101.89</td><td>26.68</td><td>8.79</td><td>32.65</td><td>10.03</td><td>112</td><td>263</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>58.82</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>112</td><td>263</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	114.74	-----	-----	101.89	26.68	8.79	32.65	10.03	112	263	PEAK	2	2478.00	58.82	-----	-----	--	--	--	--	--	112	263
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg																																																																																																																			
1	2484.83	51.74	74.00	-22.26	38.85	26.70	8.81	32.65	10.03	112	263	PEAK																																																																																																																
2	2484.83	-4.18	54.00	-58.18	--	--	--	--	--	112	263	AVERAGE																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2478.00	114.74	-----	-----	101.89	26.68	8.79	32.65	10.03	112	263	PEAK																																																																																																																
2	2478.00	58.82	-----	-----	--	--	--	--	--	112	263	AVERAGE																																																																																																																





Mode	42																																																																																																													
	Band Edge																																																																																																													
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																																													
ANT	3																																																																																																													
Pol.	Vertical					Fundamental																																																																																																								
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.35</td><td>51.26</td><td>74.00</td><td>-22.74</td><td>38.37</td><td>26.70</td><td>8.81</td><td>32.65</td><td>10.03 375 300 PEAK</td></tr><tr><td>2</td><td>2404.35</td><td>-4.66</td><td>54.00</td><td>-58.66</td><td>--</td><td>--</td><td>--</td><td>--</td><td>375 300 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg	1	2484.35	51.26	74.00	-22.74	38.37	26.70	8.81	32.65	10.03 375 300 PEAK	2	2404.35	-4.66	54.00	-58.66	--	--	--	--	375 300 AVERAGE	 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>2478.00</td><td>111.35</td><td>-----</td><td>-----</td><td>98.50</td><td>26.68</td><td>8.79</td><td>32.65</td><td>10.03 375 300 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>55.43</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>375 300 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	1	2478.00	111.35	-----	-----	98.50	26.68	8.79	32.65	10.03 375 300 PEAK	2	2478.00	55.43	-----	-----	--	--	--	--	375 300 AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg																																																																																																					
1	2484.35	51.26	74.00	-22.74	38.37	26.70	8.81	32.65	10.03 375 300 PEAK																																																																																																					
2	2404.35	-4.66	54.00	-58.66	--	--	--	--	375 300 AVERAGE																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm																																																																																																					
1	2478.00	111.35	-----	-----	98.50	26.68	8.79	32.65	10.03 375 300 PEAK																																																																																																					
2	2478.00	55.43	-----	-----	--	--	--	--	375 300 AVERAGE																																																																																																					



Mode	42																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz																																																																																									
ANT	3																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg																																																																																										
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>46.24</td><td>74.00</td><td>-27.76</td><td>34.12</td><td>32.70</td><td>12.56</td><td>33.67</td><td>0.53</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>-9.68</td><td>54.00</td><td>-63.68</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>7434.00</td><td>48.14</td><td>74.00</td><td>-25.86</td><td>31.63</td><td>37.24</td><td>15.54</td><td>36.78</td><td>0.51</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7434.00</td><td>-7.78</td><td>54.00</td><td>-61.78</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>Average</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	46.24	74.00	-27.76	34.12	32.70	12.56	33.67	0.53	--	PEAK	2	4956.00	-9.68	54.00	-63.68	--	--	--	--	--	--	Average	3	7434.00	48.14	74.00	-25.86	31.63	37.24	15.54	36.78	0.51	--	PEAK	4	7434.00	-7.78	54.00	-61.78	--	--	--	--	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4956.00	46.24	74.00	-27.76	34.12	32.70	12.56	33.67	0.53	--	PEAK																																																																															
2	4956.00	-9.68	54.00	-63.68	--	--	--	--	--	--	Average																																																																															
3	7434.00	48.14	74.00	-25.86	31.63	37.24	15.54	36.78	0.51	--	PEAK																																																																															
4	7434.00	-7.78	54.00	-61.78	--	--	--	--	--	--	Average																																																																															





Mode	42	
	Harmonic	
	2400-2483.5_Bluetooth-LE ASK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL	 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_240711 VERTICAL





<Ant. 4>

<1Mbps>

	45																																																																																																																							
Mode	Band Edge																																																																																																																							
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																																							
ANT	4																																																																																																																							
Pol.	Horizontal						Fundamental																																																																																																																	
Peak																																																																																																																								
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																	
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2340.28</td><td>50.87</td><td>74.00</td><td>-23.13</td><td>37.95</td><td>26.90</td><td>8.54</td><td>32.55</td><td>10.03</td><td>147</td><td>19 PEAK</td></tr><tr><td>2</td><td>2340.28</td><td>-5.05</td><td>54.00</td><td>-59.05</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>147</td><td>19 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2340.28	50.87	74.00	-23.13	37.95	26.90	8.54	32.55	10.03	147	19 PEAK	2	2340.28	-5.05	54.00	-59.05	--	--	--	--	--	147	19 AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2404.00</td><td>111.37</td><td>-----</td><td>-----</td><td>98.44</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03</td><td>147</td><td>19 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>55.45</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>147</td><td>19 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	111.37	-----	-----	98.44	26.84	8.66	32.60	10.03	147	19 PEAK	2	2404.00	55.45	-----	-----	--	--	--	--	--	147
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	2340.28	50.87	74.00	-23.13	37.95	26.90	8.54	32.55	10.03	147	19 PEAK																																																																																																													
2	2340.28	-5.05	54.00	-59.05	--	--	--	--	--	147	19 AVERAGE																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	2404.00	111.37	-----	-----	98.44	26.84	8.66	32.60	10.03	147	19 PEAK																																																																																																													
2	2404.00	55.45	-----	-----	--	--	--	--	--	147	19 AVERAGE																																																																																																													



Mode	45																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth-LE ASK_CH02_2404MHz																																																																																																					
ANT	4																																																																																																					
Pol.	Vertical	Fundamental																																																																																																				
Peak	 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2330.38</td><td>50.75</td><td>74.00</td><td>-23.25</td><td>37.75</td><td>27.00</td><td>8.52</td><td>32.55</td><td>10.03 394 264 PEAK</td></tr><tr><td>2</td><td>2330.38</td><td>-5.17</td><td>54.00</td><td>-59.17</td><td>--</td><td>--</td><td>--</td><td>--</td><td>394 264 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2330.38	50.75	74.00	-23.25	37.75	27.00	8.52	32.55	10.03 394 264 PEAK	2	2330.38	-5.17	54.00	-59.17	--	--	--	--	394 264 AVERAGE	 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>2404.00</td><td>107.42</td><td>-----</td><td>-----</td><td>94.49</td><td>26.84</td><td>8.66</td><td>32.60</td><td>10.03 394 264 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>51.50</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>394 264 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	2404.00	107.42	-----	-----	94.49	26.84	8.66	32.60	10.03 394 264 PEAK	2	2404.00	51.50	-----	-----	--	--	--	--	394 264 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2330.38	50.75	74.00	-23.25	37.75	27.00	8.52	32.55	10.03 394 264 PEAK																																																																																													
2	2330.38	-5.17	54.00	-59.17	--	--	--	--	394 264 AVERAGE																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																														
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																														
1	2404.00	107.42	-----	-----	94.49	26.84	8.66	32.60	10.03 394 264 PEAK																																																																																													
2	2404.00	51.50	-----	-----	--	--	--	--	394 264 AVERAGE																																																																																													