



FCC RADIO TEST REPORT

FCC ID : A4RGTF7P
Equipment : Phone
Model Name : GTF7P, G3Y12
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 21, 2024 and testing was performed from May 28, 2024 to Aug. 22, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 Test Result.....	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	16
3.6 AC Conducted Emission Measurement.....	20
3.7 Antenna Requirements.....	22
4 List of Measuring Equipment	23
5 Measurement Uncertainty	25
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Spot Check Evaluation on GTF7P, G3Y12	
Appendix F. Setup Photographs	



History of this test report



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	4.11 dB under the limit at 2483.56 MHz
3.6	15.207	AC Conducted Emission	Pass	13.04 dB under the limit at 0.17 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. ECR inquiry for data referencing from A4RGXQ96 has been approved by FCC. The ECR inquiry and the associated document are submitted in the confidential exhibit.
2. A4RGTF7P is different from FCC ID: A4RGXQ96 (Reference model), in the following:
 - The only difference between A4RGXQ96 and A4RGTF7P are the WWAN support bands, which is controlled by software.
3. All the test results are referenced from A4RGXQ96 (Sporton Test Report FR451606B), and spot check results to justify data referencing is presented in the Appendix E.
4. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
5. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

1. The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.
2. The GTF7P and G3Y12 are 100% identical in Hardware / Software to each other, and only have different model names for marketing segmentation.

Reviewed by: William Chen**Report Producer: Michelle Chen**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs GSM/WCDMA/LTE/5G NR, Bluetooth, BLE, BLE channel sounding, Wi-Fi 802.11ax, NFC, WPC Rx and GNSS.	
Antenna Type Bluetooth: <Ant.3>: IFA Antenna <Ant.4>: IFA Antenna	

EUT Information List	
S/N	Performed Test Item
44291JEBF05085	RF Conducted Measurement
46181JEBF10909	Radiated Spurious Emission
44291JEBF05116	Conducted Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant.3: 0.8 Ant.4: -4.4

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.



1.3 Testing Location

Test Site	Sportun International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sportun Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sportun International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sportun Site No. TH05-HY, 03CH16-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-



2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z plane with Adapter as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	<Ant. 3>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH01_2404 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH38_2478 MHz_2Mbps
	<Ant. 4>
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH01_2404 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH38_2478 MHz_2Mbps




Summary table of Test Cases	
Test Item	Data Rate / Modulation
Radiated Test Cases	<p><Ant. 3></p> <p>Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps</p> <p>Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps</p> <p>Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps</p> <p>Mode 4: Bluetooth Tx CH01_2404 MHz_2Mbps</p> <p>Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps</p> <p>Mode 6: Bluetooth Tx CH38_2478 MHz_2Mbps</p> <p><Ant. 4></p> <p>Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps</p> <p>Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps</p> <p>Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps</p> <p>Mode 4: Bluetooth Tx CH01_2404 MHz_2Mbps</p> <p>Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps</p> <p>Mode 6: Bluetooth Tx CH38_2478 MHz_2Mbps</p>
AC Conducted Emission	Mode 1: LTE Band 13 Idle + WLAN (2.4GHz) Link + Bluetooth Idle + USB Cable 1 (Charging from AC Adapter) + Battery < 50% + Google Meet (Front Camera)

Remark:


1. For Radiated Test Cases, the tests were performed with USB Cable 2.
2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.
3. During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Bluetooth -LE Tx Mode>





2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	ASUS	GT-AXE11000	FCC DoC	N/A	Unshielded,1.8m
3.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Wireless Earphone	Google	G1007/G1008	A4RG1007/ A4RG1008	N/A	N/A
5.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded,1.8m
6.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BT DUT Ver 03-04-24” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}.$$

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.



3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

- b) Unique (non-standard) antenna connector.
- (3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 12, 2023	Jun. 06, 2024~Aug. 17, 2024	Sep. 11, 2024	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N-06	47020 & 06	30MHz to 1GHz	Oct. 07, 2023	Jun. 06, 2024~Aug. 17, 2024	Oct. 06, 2024	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Mar. 28, 2024	Jun. 06, 2024~Aug. 17, 2024	Mar. 27, 2025	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00993	18GHz-40GHz	Nov. 24, 2023	Jun. 06, 2024~Aug. 17, 2024	Nov. 23, 2024	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Dec. 04, 2023	Jun. 06, 2024~Aug. 17, 2024	Dec. 03, 2024	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1GHz	Jul. 03, 2023	Jun. 06, 2024~Jul. 01, 2024	Jul. 02, 2024	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1GHz	Jul. 02, 2024	Jul. 02, 2024~Aug. 17, 2024	Jul. 01, 2025	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 07, 2023	Jun. 06, 2024~Aug. 17, 2024	Dec. 06, 2024	Radiation (03CH16-HY)
Preamplifier	EMEC	EM1G18G	060812	1GHz~18GHz	Dec. 25, 2023	Jun. 06, 2024~Aug. 17, 2024	Dec. 24, 2024	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060872	18GHz~40GHz	Sep. 06, 2023	Jun. 06, 2024~Aug. 17, 2024	Sep. 05, 2024	Radiation (03CH16-HY)
Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN17	1.53GHz Low Pass Filter	Jan. 15, 2024	Jun. 06, 2024~Aug. 17, 2024	Jan. 14, 2025	Radiation (03CH16-HY)
Filter	Wainwright	WFKX12-2700-3000-18000-60ST	SN3	3GHz High Pass Filter	Jun. 29, 2023	Jun. 06, 2024~Jun. 27, 2024	Jun. 28, 2024	Radiation (03CH16-HY)
Filter	Wainwright	WFKX12-2700-3000-18000-60ST	SN3	3GHz High Pass Filter	Jun. 28, 2024	Jun. 28, 2024~Aug. 17, 2024	Jun. 27, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	Jun. 06, 2024~Aug. 17, 2024	Mar. 05, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102/SUCOFLEX 104	EC-A5-300-5 757,805935/4 ,802434/4	30MHz~18GHz	Aug. 08, 2023	Jun. 06, 2024~Aug. 06, 2024	Aug. 07, 2024	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102/SUCOFLEX 104	EC-A5-300-5 757,805935/4 ,802434/4	30MHz~18GHz	Aug. 07, 2024	Aug. 07, 2024~Aug. 17, 2024	Aug. 06, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804012/2	18G~40GHz	Jan. 02, 2024	Jun. 06, 2024~Aug. 17, 2024	Jan. 01, 2025	Radiation (03CH16-HY)
Software	Audix	E3 230621 V9	RK-002393	N/A	N/A	Jun. 06, 2024~Aug. 17, 2024	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Jun. 06, 2024~Aug. 17, 2024	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jun. 06, 2024~Aug. 17, 2024	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jun. 06, 2024~Aug. 17, 2024	N/A	Radiation (03CH16-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 07, 2024	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 06, 2023	Aug. 07, 2024	Dec. 05, 2024	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 26, 2023	Aug. 07, 2024	Oct. 25, 2024	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 22, 2023	Aug. 07, 2024	Nov. 21, 2024	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Aug. 07, 2024	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 30, 2024	Aug. 07, 2024	Jul. 29, 2025	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 28, 2023	Aug. 07, 2024	Dec. 27, 2024	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	May 28, 2024~Aug. 22, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17100015SNO35 (NO:109)	10MHz~6GHz	Jan. 15, 2024	May 28, 2024~Aug. 22, 2024	Jan. 14, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2023	May 28, 2024~Aug. 21, 2024	Aug. 22, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101564	10Hz~40GHz	Sep. 12, 2023	Aug. 22, 2024	Sep. 11, 2024	Conducted (TH05-HY)
Switch Box & RF Cable	E-Instrument	ETF-1405-0	EC1900067	N/A	Jul. 10, 2023	May 28, 2024~Jul. 04, 2024	Jul. 09, 2024	Conducted (TH05-HY)
Switch Box & RF Cable	E-Instrument	ETF-1405-0	EC1900067	N/A	Jul. 05, 2024	Jul. 05, 2024~Aug. 22, 2024	Jul. 04, 2025	Conducted (TH05-HY)
Software	Sportun	BTWIFI_Final_version1.0	N/A	N/A	N/A	May 28, 2024~Aug. 22, 2024	N/A	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	3.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	4.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{C(y)}$)	5.50 dB
---	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Hank Hsu				Temperature:	21~25		°C
Test Date:	2024/05/28~2024/08/22				Relative Humidity:	51~54		%

<Ant. 3>

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	00	2402	1.037	0.716	0.50	Pass
BLE	1Mbps	1	19	2440	1.037	0.720	0.50	Pass
BLE	1Mbps	1	39	2480	1.037	0.719	0.50	Pass
BLE	2Mbps	1	01	2404	2.074	1.245	0.50	Pass
BLE	2Mbps	1	19	2440	2.074	1.243	0.50	Pass
BLE	2Mbps	1	38	2478	2.070	1.241	0.50	Pass

TEST RESULTS DATA Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	00	2402	18.12	30.00	0.80	18.92	36.00	Pass
BLE	1Mbps	1	19	2440	18.02	30.00	0.80	18.82	36.00	Pass
BLE	1Mbps	1	39	2480	19.32	30.00	0.80	20.12	36.00	Pass
BLE	2Mbps	1	01	2404	18.22	30.00	0.80	19.02	36.00	Pass
BLE	2Mbps	1	19	2440	18.22	30.00	0.80	19.02	36.00	Pass
BLE	2Mbps	1	38	2478	19.52	30.00	0.80	20.32	36.00	Pass

TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	00	2402	17.57	2.90	0.80	8.00	Pass
BLE	1Mbps	1	19	2440	17.51	2.84	0.80	8.00	Pass
BLE	1Mbps	1	39	2480	18.77	4.12	0.80	8.00	Pass
BLE	2Mbps	1	01	2404	16.10	-1.97	0.80	8.00	Pass
BLE	2Mbps	1	19	2440	17.49	-0.70	0.80	8.00	Pass
BLE	2Mbps	1	38	2478	17.27	-0.86	0.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 4>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	00	2402	1.037	0.715	0.50	Pass
BLE	1Mbps	1	19	2440	1.037	0.717	0.50	Pass
BLE	1Mbps	1	39	2480	1.037	0.712	0.50	Pass
BLE	2Mbps	1	01	2404	2.070	1.238	0.50	Pass
BLE	2Mbps	1	19	2440	2.070	1.241	0.50	Pass
BLE	2Mbps	1	38	2478	2.070	1.242	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	00	2402	19.40	30.00	-4.40	15.00	36.00	Pass
BLE	1Mbps	1	19	2440	19.90	30.00	-4.40	15.50	36.00	Pass
BLE	1Mbps	1	39	2480	19.00	30.00	-4.40	14.60	36.00	Pass
BLE	2Mbps	1	01	2404	19.60	30.00	-4.40	15.20	36.00	Pass
BLE	2Mbps	1	19	2440	20.20	30.00	-4.40	15.80	36.00	Pass
BLE	2Mbps	1	38	2478	19.20	30.00	-4.40	14.80	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	00	2402	18.76	4.03	-4.40	8.00	Pass
BLE	1Mbps	1	19	2440	19.28	4.59	-4.40	8.00	Pass
BLE	1Mbps	1	39	2480	18.41	3.74	-4.40	8.00	Pass
BLE	2Mbps	1	01	2404	17.73	-0.44	-4.40	8.00	Pass
BLE	2Mbps	1	19	2440	19.20	1.02	-4.40	8.00	Pass
BLE	2Mbps	1	38	2478	17.18	-0.98	-4.40	8.00	Pass


Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



<Ant.3>


6dB Bandwidth

<1Mbps>








<2Mbps>




**99% Occupied Bandwidth**

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**




<2Mbps>




**Power Spectral Density (dBm/3kHz)**

<1Mbps>







<2Mbps>




**Band Edge and Conducted Spurious Emission**

<1Mbps>












<2Mbps>










<Ant.4>


6dB Bandwidth

<1Mbps>








<2Mbps>




**99% Occupied Bandwidth**

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**




<2Mbps>




**Power Spectral Density (dBm/3kHz)**

<1Mbps>







<2Mbps>




**Band Edge and Conducted Spurious Emission**

<1Mbps>












<2Mbps>










Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	45~55%

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.62	55.88	27.26	L1	OFF	19.8
0.152250	33.80	---	65.88	32.08	L1	OFF	19.8
0.168000	---	37.53	55.06	17.53	L1	OFF	19.8
0.168000	52.02	---	65.06	13.04	L1	OFF	19.8
0.177000	---	36.95	54.63	17.68	L1	OFF	19.8
0.177000	50.40	---	64.63	14.23	L1	OFF	19.8
0.190500	---	25.20	54.02	28.82	L1	OFF	19.8
0.190500	31.74	---	64.02	32.28	L1	OFF	19.8
0.228750	---	24.29	52.50	28.21	L1	OFF	19.8
0.228750	28.90	---	62.50	33.60	L1	OFF	19.8
0.798000	---	24.18	46.00	21.82	L1	OFF	19.8
0.798000	26.55	---	56.00	29.45	L1	OFF	19.8
7.471500	---	26.27	50.00	23.73	L1	OFF	20.1
7.471500	27.76	---	60.00	32.24	L1	OFF	20.1

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.81	55.88	26.07	N	OFF	19.8
0.152250	47.86	---	65.88	18.02	N	OFF	19.8
0.170250	---	35.01	54.95	19.94	N	OFF	19.8
0.170250	50.30	---	64.95	14.65	N	OFF	19.8
0.179250	---	36.45	54.52	18.07	N	OFF	19.8
0.179250	49.53	---	64.52	14.99	N	OFF	19.8
0.226500	---	24.44	52.58	28.14	N	OFF	19.8
0.226500	31.34	---	62.58	31.24	N	OFF	19.8
1.734000	---	24.70	46.00	21.30	N	OFF	19.9
1.734000	26.92	---	56.00	29.08	N	OFF	19.9
9.289500	---	26.55	50.00	23.45	N	OFF	20.3
9.289500	28.31	---	60.00	31.69	N	OFF	20.3



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Bill Chang, Gary Guo and Steven Wu	Relative Humidity :	54.2~56.1%
		Temperature :	18.2~20.2°C

Note symbol

-L	Low channel location
-R	High channel location



C1-1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 13	2400-2483.5	3	Bluetooth-LE_GFSK	00	2402	1Mbps	-	-
Mode 14	2400-2483.5	3	Bluetooth-LE_GFSK	19	2440	1Mbps	-	-
Mode 15	2400-2483.5	3	Bluetooth-LE_GFSK	39	2480	1Mbps	-	-
Mode 29	2400-2483.5	3	Bluetooth-LE_GFSK	39	2480	1Mbps	-	LF
Mode 30	2400-2483.5	3	Bluetooth-LE_GFSK	39	2480	1Mbps	-	SHF









C1-2. Summary of each worse mode


Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
13	Bluetooth-LE_GFSK	00	2387.74	46.68	54.00	-7.32	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	00	4804.00	38.98	74.00	-35.02	H	Peak	Pass	-	Harmonic
14	Bluetooth-LE_GFSK	19	2494.84	47.51	54.00	-6.49	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	19	7320.00	45.36	74.00	-28.64	H	Peak	Pass	-	Harmonic
15	Bluetooth-LE_GFSK	39	2483.66	49.26	54.00	-4.74	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	39	7440.00	44.59	74.00	-29.41	V	Peak	Pass	-	Harmonic
29	LF	39	42.61	32.30	40.00	-7.70	V	QP	Pass	-	LF
30	SHF	39	24958.54	38.85	74.00	-35.15	H	Peak	Pass	-	SHF







Mode	13																																																													
	Band Edge																																																													
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																													
ANT	3																																																													
Pol.	Horizontal																																																													
Peak	<p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2373.02</td><td>56.48</td><td>74.00</td><td>-17.52</td><td>41.62</td><td>27.20</td><td>7.66</td><td>29.92</td><td>9.92</td><td>314 305 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2373.02	56.48	74.00	-17.52	41.62	27.20	7.66	29.92	9.92	314 305 PEAK	<p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2402.00</td><td>107.91</td><td>-----</td><td>-----</td><td>92.79</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>314 305 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2402.00	107.91	-----	-----	92.79	27.40	7.71	29.91	9.92	314 305 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2373.02	56.48	74.00	-17.52	41.62	27.20	7.66	29.92	9.92	314 305 PEAK																																																					
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2402.00	107.91	-----	-----	92.79	27.40	7.71	29.91	9.92	314 305 PEAK																																																					
<p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2374.58</td><td>46.67</td><td>54.00</td><td>-7.33</td><td>31.88</td><td>27.20</td><td>7.67</td><td>29.92</td><td>9.92</td><td>314 305 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2374.58	46.67	54.00	-7.33	31.88	27.20	7.67	29.92	9.92	314 305 AVERAGE	<p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2402.00</td><td>107.24</td><td>-----</td><td>-----</td><td>92.12</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>314 305 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2402.00	107.24	-----	-----	92.12	27.40	7.71	29.91	9.92	314 305 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2374.58	46.67	54.00	-7.33	31.88	27.20	7.67	29.92	9.92	314 305 AVERAGE																																																					
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2402.00	107.24	-----	-----	92.12	27.40	7.71	29.91	9.92	314 305 AVERAGE																																																					
Avg																																																														







Mode	13																																																															
	Band Edge																																																															
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz																																																															
ANT	3																																																															
Pol.	Vertical																																																															
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2310.55</td> <td>56.85</td> <td>74.00</td> <td>-17.15</td> <td>42.22</td> <td>27.10</td> <td>7.55</td> <td>29.94</td> <td>9.92</td> <td>300 211 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2310.55	56.85	74.00	-17.15	42.22	27.10	7.55	29.94	9.92	300 211 PEAK	 <p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>93.24</td> <td>-----</td> <td>-----</td> <td>78.12</td> <td>27.40</td> <td>7.71</td> <td>29.91</td> <td>9.92</td> <td>300 211 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2402.00	93.24	-----	-----	78.12	27.40	7.71	29.91	9.92	300 211 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2310.55	56.85	74.00	-17.15	42.22	27.10	7.55	29.94	9.92	300 211 PEAK																																																						
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2402.00	93.24	-----	-----	78.12	27.40	7.71	29.91	9.92	300 211 PEAK																																																						
 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2387.74</td> <td>46.68</td> <td>54.00</td> <td>-7.32</td> <td>31.70</td> <td>27.28</td> <td>7.69</td> <td>29.91</td> <td>9.92</td> <td>300 211 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2387.74	46.68	54.00	-7.32	31.70	27.28	7.69	29.91	9.92	300 211 AVERAGE	 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>92.59</td> <td>-----</td> <td>-----</td> <td>77.47</td> <td>27.40</td> <td>7.71</td> <td>29.91</td> <td>9.92</td> <td>300 211 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2402.00	92.59	-----	-----	77.47	27.40	7.71	29.91	9.92	300 211 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2387.74	46.68	54.00	-7.32	31.70	27.28	7.69	29.91	9.92	300 211 AVERAGE																																																						
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2402.00	92.59	-----	-----	77.47	27.40	7.71	29.91	9.92	300 211 AVERAGE																																																						
Avg	 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2387.74</td> <td>46.68</td> <td>54.00</td> <td>-7.32</td> <td>31.70</td> <td>27.28</td> <td>7.69</td> <td>29.91</td> <td>9.92</td> <td>300 211 AVERAGE</td> </tr> </tbody> </table>		Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2387.74	46.68	54.00	-7.32	31.70	27.28	7.69	29.91	9.92	300 211 AVERAGE																															
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2387.74	46.68	54.00	-7.32	31.70	27.28	7.69	29.91	9.92	300 211 AVERAGE																																																						
 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2402.00</td> <td>92.59</td> <td>-----</td> <td>-----</td> <td>77.47</td> <td>27.40</td> <td>7.71</td> <td>29.91</td> <td>9.92</td> <td>300 211 AVERAGE</td> </tr> </tbody> </table>		Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1	2402.00	92.59	-----	-----	77.47	27.40	7.71	29.91	9.92	300 211 AVERAGE																																
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																							
1	2402.00	92.59	-----	-----	77.47	27.40	7.71	29.91	9.92	300 211 AVERAGE																																																						







Mode	13	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL







Mode	14																																																													
	Band Edge - L																																																													
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																													
ANT	3																																																													
Pol.	Horizontal																																																													
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2341.98</td><td>56.17</td><td>74.00</td><td>-17.83</td><td>41.47</td><td>27.10</td><td>7.61</td><td>29.93</td><td>9.92</td><td>305 311 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2341.98	56.17	74.00	-17.83	41.47	27.10	7.61	29.93	9.92	305 311 PEAK	 <p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2440.00</td><td>110.79</td><td>-----</td><td>-----</td><td>95.49</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>305 311 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2440.00	110.79	-----	-----	95.49	27.60	7.68	29.90	9.92	305 311 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2341.98	56.17	74.00	-17.83	41.47	27.10	7.61	29.93	9.92	305 311 PEAK																																																					
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2440.00	110.79	-----	-----	95.49	27.60	7.68	29.90	9.92	305 311 PEAK																																																					
 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2386.31</td><td>46.79</td><td>54.00</td><td>-7.21</td><td>31.83</td><td>27.26</td><td>7.69</td><td>29.91</td><td>9.92</td><td>305 311 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2386.31	46.79	54.00	-7.21	31.83	27.26	7.69	29.91	9.92	305 311 AVERAGE	 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1 2440.00</td><td>110.09</td><td>-----</td><td>-----</td><td>94.79</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>305 311 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg	1 2440.00	110.09	-----	-----	94.79	27.60	7.68	29.90	9.92	305 311 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2386.31	46.79	54.00	-7.21	31.83	27.26	7.69	29.91	9.92	305 311 AVERAGE																																																					
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB	cm	deg																																																					
1 2440.00	110.09	-----	-----	94.79	27.60	7.68	29.90	9.92	305 311 AVERAGE																																																					






Mode	14																															
	Band Edge - R																															
	2400-2483.5_Bluetooth-LE_GFSK _CH19_2440MHz																															
ANT	3																															
Pol.	Horizontal																															
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>2486.98</td><td>57.87</td><td>74.00</td><td>-16.93</td><td>41.69</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>305 311 PEAK</td></tr></tbody></table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB		2486.98	57.87	74.00	-16.93	41.69	27.70	7.64	29.88	9.92	305 311 PEAK	Blank
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																								
2486.98	57.87	74.00	-16.93	41.69	27.70	7.64	29.88	9.92	305 311 PEAK																							
Avg	 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>2494.84</td><td>47.51</td><td>54.00</td><td>-6.49</td><td>32.14</td><td>27.70</td><td>7.63</td><td>29.88</td><td>9.92</td><td>305 311 AVERAGE</td></tr></tbody></table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB		2494.84	47.51	54.00	-6.49	32.14	27.70	7.63	29.88	9.92	305 311 AVERAGE	Blank
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																								
2494.84	47.51	54.00	-6.49	32.14	27.70	7.63	29.88	9.92	305 311 AVERAGE																							









Mode	14																																																																	
	Band Edge - L																																																																	
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																	
ANT	3																																																																	
Pol.	Vertical	Fundamental																																																																
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2367.33</td><td>56.81</td><td>74.00</td><td>-17.19</td><td>41.96</td><td>27.20</td><td>7.65</td><td>29.92</td><td>9.92</td><td>100</td><td>254 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2367.33	56.81	74.00	-17.19	41.96	27.20	7.65	29.92	9.92	100	254 PEAK	 <p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2440.00</td><td>110.06</td><td>-----</td><td>-----</td><td>94.76</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>100</td><td>254 PEAK</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	110.06	-----	-----	94.76	27.60	7.68	29.90	9.92	100	254 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																									
1	2367.33	56.81	74.00	-17.19	41.96	27.20	7.65	29.92	9.92	100	254 PEAK																																																							
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																									
1	2440.00	110.06	-----	-----	94.76	27.60	7.68	29.90	9.92	100	254 PEAK																																																							
 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2384.49</td><td>46.69</td><td>54.00</td><td>-7.31</td><td>31.76</td><td>27.24</td><td>7.68</td><td>29.91</td><td>9.92</td><td>100</td><td>254 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2384.49	46.69	54.00	-7.31	31.76	27.24	7.68	29.91	9.92	100	254 AVERAGE	 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2440.00</td><td>109.39</td><td>-----</td><td>-----</td><td>94.09</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>100</td><td>254 AVERAGE</td></tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	109.39	-----	-----	94.09	27.60	7.68	29.90	9.92	100	254 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																									
1	2384.49	46.69	54.00	-7.31	31.76	27.24	7.68	29.91	9.92	100	254 AVERAGE																																																							
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																									
1	2440.00	109.39	-----	-----	94.09	27.60	7.68	29.90	9.92	100	254 AVERAGE																																																							







Mode	14																															
	Band Edge - R																															
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																															
ANT	3																															
Pol.	Vertical	Fundamental																														
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>2494.96</td><td>57.37</td><td>74.00</td><td>-16.63</td><td>42.00</td><td>27.70</td><td>7.63</td><td>29.88</td><td>9.92</td><td>100 254 PEAK</td></tr></tbody></table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB		2494.96	57.37	74.00	-16.63	42.00	27.70	7.63	29.88	9.92	100 254 PEAK	Blank
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																								
2494.96	57.37	74.00	-16.63	42.00	27.70	7.63	29.88	9.92	100 254 PEAK																							
Avg	 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>2485.12</td><td>47.22</td><td>54.00</td><td>-6.78</td><td>31.84</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>100 254 AVERAGE</td></tr></tbody></table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB		2485.12	47.22	54.00	-6.78	31.84	27.70	7.64	29.88	9.92	100 254 AVERAGE	Blank
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																								
2485.12	47.22	54.00	-6.78	31.84	27.70	7.64	29.88	9.92	100 254 AVERAGE																							









Mode	14	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz	
ANT	3	
Pol.	Horizontal Vertical	
14.47G		
~14.5G		
Avg	Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL	
17.7G		
~18G		
Avg	Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL	



Mode	15																																																																																																					
	Band Edge																																																																																																					
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Horizontal																																																																																																					
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Factor</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> </tr> <tr> <td>1</td> <td>2483.70</td> <td>58.39</td> <td>74.00</td> <td>-15.61</td> <td>43.01</td> <td>27.70</td> <td>7.64</td> <td>29.88</td> <td>9.92</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>140</td> <td>217 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.70	58.39	74.00	-15.61	43.01	27.70	7.64	29.88	9.92									140	217 PEAK	 <p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Factor</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> </tr> <tr> <td>1</td> <td>2480.00</td> <td>116.37</td> <td>-----</td> <td>-----</td> <td>100.99</td> <td>27.70</td> <td>7.65</td> <td>29.89</td> <td>9.92</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>140</td> <td>217 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	116.37	-----	-----	100.99	27.70	7.65	29.89	9.92									140	217 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2483.70	58.39	74.00	-15.61	43.01	27.70	7.64	29.88	9.92																																																																																													
								140	217 PEAK																																																																																													
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2480.00	116.37	-----	-----	100.99	27.70	7.65	29.89	9.92																																																																																													
								140	217 PEAK																																																																																													
 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Factor</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> </tr> <tr> <td>1</td> <td>2483.66</td> <td>49.26</td> <td>54.00</td> <td>-4.74</td> <td>33.88</td> <td>27.70</td> <td>7.64</td> <td>29.88</td> <td>9.92</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>140</td> <td>217 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.66	49.26	54.00	-4.74	33.88	27.70	7.64	29.88	9.92									140	217 AVERAGE	 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level Factor</th> <th>Loss Factor</th> <th>Factor</th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dBuV</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> </tr> <tr> <td>1</td> <td>2480.00</td> <td>115.72</td> <td>-----</td> <td>-----</td> <td>100.34</td> <td>27.70</td> <td>7.65</td> <td>29.89</td> <td>9.92</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>140</td> <td>217 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	115.72	-----	-----	100.34	27.70	7.65	29.89	9.92									140	217 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2483.66	49.26	54.00	-4.74	33.88	27.70	7.64	29.88	9.92																																																																																													
								140	217 AVERAGE																																																																																													
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																													
1	2480.00	115.72	-----	-----	100.34	27.70	7.65	29.89	9.92																																																																																													
								140	217 AVERAGE																																																																																													



Mode	15																																																																																	
	Band Edge																																																																																	
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																	
ANT	3																																																																																	
Pol.	Vertical																																																																																	
Peak	 <p>Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Factor</th> <th>Factor</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> <td></td> </tr> <tr> <td>1</td> <td>2483.54</td> <td>58.96</td> <td>74.00</td> <td>-15.04</td> <td>43.58</td> <td>27.70</td> <td>7.64</td> <td>29.88</td> <td>9.92 100 300 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg		1	2483.54	58.96	74.00	-15.04	43.58	27.70	7.64	29.88	9.92 100 300 PEAK	 <p>Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_248328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Factor</th> <th>Factor</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> <td></td> </tr> <tr> <td>1</td> <td>2480.00</td> <td>117.17</td> <td>-----</td> <td>-----</td> <td>101.79</td> <td>27.70</td> <td>7.65</td> <td>29.89</td> <td>9.92 100 300 PEAK</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg		1	2480.00	117.17	-----	-----	101.79	27.70	7.65	29.89	9.92 100 300 PEAK
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																										
1	2483.54	58.96	74.00	-15.04	43.58	27.70	7.64	29.88	9.92 100 300 PEAK																																																																									
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																										
1	2480.00	117.17	-----	-----	101.79	27.70	7.65	29.89	9.92 100 300 PEAK																																																																									
 <p>Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Factor</th> <th>Factor</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> <td></td> </tr> <tr> <td>1</td> <td>2483.52</td> <td>49.06</td> <td>54.00</td> <td>-4.94</td> <td>33.68</td> <td>27.70</td> <td>7.64</td> <td>29.88</td> <td>9.92 100 300 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg		1	2483.52	49.06	54.00	-4.94	33.68	27.70	7.64	29.88	9.92 100 300 AVERAGE	 <p>Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Limit</th> <th>Read</th> <th>Ant</th> <th>Cable</th> <th>Preamp</th> <th>Aux</th> <th>APos</th> <th>TPos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Line Margin</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th>Factor</th> <th>Factor</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>MHz</td> <td>dBuV/m</td> <td>dBuV/m</td> <td>dB</td> <td>dB/m</td> <td>dB</td> <td>dB</td> <td>cm</td> <td>deg</td> <td></td> </tr> <tr> <td>1</td> <td>2480.00</td> <td>116.55</td> <td>-----</td> <td>-----</td> <td>101.17</td> <td>27.70</td> <td>7.65</td> <td>29.89</td> <td>9.92 100 300 AVERAGE</td> </tr> </tbody> </table>	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg		1	2480.00	116.55	-----	-----	101.17	27.70	7.65	29.89	9.92 100 300 AVERAGE	
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																										
1	2483.52	49.06	54.00	-4.94	33.68	27.70	7.64	29.88	9.92 100 300 AVERAGE																																																																									
Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																										
1	2480.00	116.55	-----	-----	101.17	27.70	7.65	29.89	9.92 100 300 AVERAGE																																																																									
TEL: 886-3-327-0868	Page Number	: C1-15 of 19																																																																																
FAX: 886-3-327-0855																																																																																		

