



FCC RADIO TEST REPORT

FCC ID : A4RGU0NP
Equipment : Phone
Model Name : GU0NP, GM66V
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Feb. 27, 2025 and testing was performed from Mar. 06, 2025 to Apr.30, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	13
3 Test Result	14
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	14
3.2 Maximum E.I.R.P Output Power Measurement	15
3.3 Power Spectral Density Measurement	16
3.4 Unwanted Emissions Measurement.....	18
3.5 AC Conducted Emission Measurement.....	23
3.6 Antenna Requirements.....	25
4 List of Measuring Equipment.....	26
5 Measurement Uncertainty	28
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR4N0920F	01	Initial issue of report	May 22, 2025
FR4N0920F	02	Fixed the test plots, added the note for section 1.1.1 and Added the test procedure for peak measurements above 1GHz This report is an updated version, replacing the report issued on May 22, 2025	May 22, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.407(e)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum E.I.R.P Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	-
3.5	15.207	AC Conducted Emission	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

1. The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.
2. The GU0NP and GM66V are 100% identical in Hardware / Software to each other, and only have different model names for marketing segmentation. The test sample are all model GU0NP.

Reviewed by: William Chen

Report Producer: Josie Hsu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx.		
Antenna Type WLAN: <Ant. 4>: ILA Antenna <Ant. 3>: IFA Antenna		
EUT Information List		
S/N	Performed Test Item	
52171FDCG0005B	RF Conducted Measurement	
52181FDCG0008P	Radiated Spurious Emission	
52181FDCG0008P	Conducted Emission	
Antenna information (Open Mode)		
5850 MHz ~ 5895 MHz	Peak Gain (dBi)	Ant. 4: -1.12
		Ant. 3: -4.60
Antenna information (Close Mode)		
5850 MHz ~ 5895 MHz	Peak Gain (dBi)	Ant. 4: -7.04
		Ant. 3: -5.25

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.1.1 Antenna Directional Gain

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

UNII-4			DG	DG
			for	for
	Ant 4	Ant 3	Power	PSD
	(dBi)	(dBi)	(dBi)	(dBi)
	-1.12	-4.60	-1.12	0.32

Calculation example:

If a device has two antenna, $G_{ANT4} = -1.12$ dBi; $G_{ANT3} = -4.60$ dBi

Directional gain of power measurement = $\max(-1.12, -4.60) + 0 = -1.12$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(-1.12 \text{ dBi} / 20)} + 10^{(-4.60 \text{ dBi} / 20)} \right]^2 / 2 \right\}$$

$$= 0.32 \text{ dBi}$$

Note: The antenna gain is from both open mode and close mode with highest number.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH15-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB 291074 D02 EMC Measurement v01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT (Open and Close) and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z plane with Adapter (Open Mode) for MIMO<Ant. 4+3> as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Bandwidth	Channel	Frequency (MHz)	Note
5850-5895 MHz (U-NII-4)	20 MHz	169	5845	Straddle
		173	5865	
		177	5885	
	40 MHz	167	5835	Straddle
		175	5875	
	80 MHz	171	5855	Straddle
	160 MHz	163	5815	Straddle

Note: The channel noted with "straddle" spans 5.725-5.850 GHz and 5.850-5.895 GHz.



2.2 Test Mode

This device supports WiFi 802.11be 20MHz bandwidth for 2.4GHz and 160MHz bandwidth for both 5GHz and 6GHz.

This device supports 26/52/106/242/484/996 single tone RU modes for 802.11ax/be modes and the 242/484/996-tone RU modes are covered by 20/40/80MHz channels.

This device supports both CDD and SDM modes and SDM is covered by CDD for NII-4.

This device supports MRU 52T+26T/106T+26T (small RU) and punctured modes 484+242-tone, 996+484+242-tone, and 996+484-tone (large RU) for 802.11be mode.

The PSD of partial RU/MRU modes are reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax/be modes are investigated among full RU, single RU and MRU modes for emission spot check and the 11ax modes are covered by 11be modes.

The PSD and power of partial RU and MRU are less than full RU configurations so the full RU is chosen as main test configuration.

The power for 802.11n, 802.11ac and 802.11ax mode is smaller than 802.11be mode, so all other conducted and radiated test is covered by 802.11be mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by EHT20)	MCS0
802.11n HT40 (Covered by EHT40)	MCS0
802.11ac VHT20 (Covered by EHT20)	MCS0
802.11ac VHT40 (Covered by EHT40)	MCS0
802.11ac VHT80 (Covered by EHT80)	MCS0
802.11ac VHT160 (Covered by EHT160)	MCS0
802.11ax HE20 (Covered by EHT20)	MCS0
802.11ax HE40 (Covered by EHT40)	MCS0
802.11ax HE80 (Covered by EHT80)	MCS0
802.11ax HE160 (Covered by EHT160)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0
802.11be EHT160	MCS0

Index of MRU and puncture mode mapping

Small MRU

MRU	26T	52T	106T
52T+26T	70	72	
	71		
106T+26T	82		
			83

Large MRU

484+242-tone MRU			
2	1	4	3
80MHz puncture 20			
8	4	2	1

996+484+242-tone MRU							
2	1	4	3	6	5	8	7
160MHz puncture 20							
128	64	32	16	8	4	2	1


996+484-tone MRU			
2	1	4	3
160MHz puncture 40			
192	48	12	3


Note: The RF waveform is identical for large MRU and puncture modes.

Test Cases	
AC Conducted Emission	Mode 1 : WLAN (5GHz) 11a Tx+ USB Cable 1 (Charging from AC Adapter)
Remark: 1. For Radiated Test Cases, the tests were performed with USB Cable 1. 2. The detailed Radiated test modes are shown in Appendix C. 3. During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test. 4. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power	

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>

2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “WLAN_DUT_Control_GUI_10-15-24” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

The testing follows FCC KDB 291074 D02 EMC Measurement v01 Section 2.11 Minimum Emission bandwidth

1. Set RBW = 100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold
5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum E.I.R.P Output Power Measurement

3.2.1 Limit of Maximum E.I.R.P Output Power

For client devices operating under the control of an indoor access point in the 5.850-5.895 GHz band, the maximum power spectral density must not exceed 14 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm. Client devices operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands must not exceed an e.i.r.p. of 30 dBm.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

1. For client devices operating under the control of an indoor access point in the 5.850-5.895 GHz band, the maximum power spectral density must not exceed 14 dBm e.i.r.p. in any 1-megahertz band.
2. For client devices operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands shall meet both 15.407(a)(3)(i) 30dBm/500kHz and 15.407(a)(3)(iii) 14dBm/MHz limit, where the stringent limit 14dBm/MHz is applied.
3. For an indoor access point operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands shall meet both 15.407(a)(3)(ii) 36dBm limit, where the stringent limit 20dBm/MHz is applied.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points; the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

- (2) For transmitters operating solely in the 5.850-5.895 GHz band or operating on a channel that spans across 5.725-5.895 GHz:

15.407(b)(5)(ii), all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of -5 dBm/MHz and shall decrease linearly to an e.i.r.p. of -27 dBm/MHz at or above 5.925 GHz.

All emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

- (3) KDB789033 D02 v02r01 G)2)c)

Use guidance in KDB Publication 789033 for all measurements. Unwanted emissions outside of restricted bands are measured with an RMS detector. In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.

Unwanted band-edge emissions may be measured using the integration method as described in KDB Publication 789033 3. d) (ii). Emissions below 5725 MHz should be measured using peak-detection while emission above 5895 MHz should be measured using average.

Frequency(GHz)	EIRP (dBm)	Field Strength @3m distance (dBuV/m)	Note
Below 5.65	-27dBm/MHz	68.2	Peak
5.7	10dBm/MHz	105.2	Peak
5.72	15.6dBm/MHz	110.8	Peak
5.725	27dBm/MHz	122.2	Peak
5.895	-5dBm/MHz	90.2	Average
5.895	15dBm/MHz	110.2	Peak
Above 5.925	-27dBm/MHz	68.2	Average
Above 5.925	-7dBm/MHz	88.2	Peak

Note: Field strength at 3 m distance is converted to EIRP as the following equation:

$$\text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} - 95.2$$

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
 Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT was placed at distance 3 meter from measurement antenna which was mounted on the top of a variable height antenna tower.
4. The measurement antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0 degree to 360 degree to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0 degree to 360 degree to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Results of Radiated Spurious Emissions (above 18 GHz)

For frequency above 18GHz, the pre-scanned result is 20dB lower than the limit line is not reported.

3.4.7 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.8 Duty Cycle

Please refer to Appendix D.

3.4.9 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

(3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	Mar. 14, 2025~ Apr. 22, 2025	Aug. 28, 2025	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N- 06	41912 & 05	30MHz~1GHz	Mar. 01, 2024	Mar. 14, 2025~ Apr. 22, 2025	Feb. 28, 2025	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-02294	1GHz~18GHz	Jun. 20, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jun. 19, 2025	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1224	18GHz~40GHz	Jun. 24, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jun. 23, 2025	Radiation (03CH15-HY)
Amplifier	EMEC	EM1G18G	060837	1GHz~18GHz	Feb. 13, 2025	Mar. 14, 2025~ Apr. 22, 2025	Feb. 12, 2026	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 14, 2025	Mar. 14, 2025~ Apr. 22, 2025	Feb. 13, 2026	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Mar. 14, 2025~ Apr. 22, 2025	May 26, 2025	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44Gz	Jul. 11, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jul. 10, 2025	Radiation (03CH15-HY)
EMI Receiver	Keysight	N9038A(MXE)	MY54130085	20MHz~8.4GHz	Oct. 16, 2024	Mar. 14, 2025~ Apr. 22, 2025	Oct. 15, 2025	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 14, 2025~ Apr. 22, 2025	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 14, 2025~ Apr. 22, 2025	N/A	Radiation (03CH15-HY)
Software	Audix	E3_V9_230621	RK-002394	N/A	N/A	Mar. 14, 2025~ Apr. 22, 2025	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104, 102E	MY582185/4, 519228/2,803 950/2	N/A	Jun. 11, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jun. 10, 2025	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40G	Dec. 31, 2024	Mar. 14, 2025~ Apr. 22, 2025	Dec. 30, 2025	Radiation (03CH15-HY)
Filter	Wainwright	WHKX8-5872.5- 6750-18000- 40ST	SN6	6.75GHz High Pass Filter	Jun. 05, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jun. 04, 2025	Radiation (03CH15-HY)
Filter	wright	WLJ4-1000- 1530-6000- 40ST	SN4	1.53GHz Low Pass Filter	Jun. 05, 2024	Mar. 14, 2025~ Apr. 22, 2025	Jun. 04, 2025	Radiation (03CH15-HY)
Hygrometer	TECEPEL	DTM-302	SN4	N/A	Aug. 29, 2024	Mar. 14, 2025~ Apr. 22, 2025	Aug. 28, 2025	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Mar.06, 2025~ Apr.18, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Mar.06, 2025~ Apr.18, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	Mar.06, 2025~ Apr.18, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	Burgeon	ETF-058	EC1300484 (BOX3)	N/A	May 20, 2024	Mar.06, 2025~ Apr.18, 2025	May 19, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_v ersion_240513	N/A	Conducted Other Test Item	N/A	Mar.06, 2025~ Apr.18, 2025	N/A	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Apr. 30, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 30, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Apr. 30, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Apr. 30, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Apr. 30, 2025	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Apr. 30, 2025	Sep. 22, 2025	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Benny Ku/Junyu Jhou	Temperature:	21~25	°C
Test Date:	2025/3/6~2025/4/18	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

UNII-4 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 4	Ant 3	Ant 4	Ant 3	Ant 4	Ant 3		
11a	6Mbps	2	169	5845	27.49	18.01	41.28	32.35	16.08	16.32	0.5	Pass
11a	6Mbps	2	173	5865	26.50	17.64	41.82	30.66	15.89	16.33	0.5	Pass
11a	6Mbps	2	177	5885	29.16	18.34	43.96	32.72	16.07	16.35	0.5	Pass

TEST RESULTS DATA
Average Power Table

UNII-4 MIMO										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			DG (dBi)	E.I.R.P Power (dBm)	E.I.R.P Limit (dBm)
					Ant 4	Ant 3	SUM			
11a	6Mbps	2	169	5845	20.05	20.96	23.54	-1.12	22.42	30
11a	6Mbps	2	173	5865	19.87	20.68	23.30	-1.12	22.18	30
11a	6Mbps	2	177	5885	19.95	20.77	23.39	-1.12	22.27	30
HT20	MCS0	2	169	5845	19.77	20.63	23.23	-1.12	22.11	30
HT20	MCS0	2	173	5865	19.76	20.62	23.22	-1.12	22.10	30
HT20	MCS0	2	177	5885	19.96	20.72	23.37	-1.12	22.25	30
HT40	MCS0	2	167	5835	19.29	19.84	22.58	-1.12	21.46	30
HT40	MCS0	2	175	5875	19.51	19.89	22.71	-1.12	21.59	30
VHT20	MCS0	2	169	5845	19.77	20.63	23.23	-1.12	22.11	30
VHT20	MCS0	2	173	5865	19.76	20.62	23.22	-1.12	22.10	30
VHT20	MCS0	2	177	5885	19.96	20.72	23.37	-1.12	22.25	30
VHT40	MCS0	2	167	5835	19.29	19.84	22.58	-1.12	21.46	30
VHT40	MCS0	2	175	5875	19.51	19.89	22.71	-1.12	21.59	30
VHT80	MCS0	2	171	5855	19.31	19.63	22.48	-1.12	21.36	30
VHT160	MCS0	2	163	5815	17.27	17.42	20.36	-1.12	19.24	30

TEST RESULTS DATA
Power Spectral Density

UNII-4 MIMO													
Mod.	Data Rate	N _{Tx}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			DG (dBi)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Pass /Fail
					Ant 1	Ant 2	Ant 4	Ant 3	SUM				
11a	6Mbps	2	169	5845	0.02	0.02			12.16	0.32	12.48	14.00	Pass
11a	6Mbps	2	173	5865	0.02	0.02			11.97	0.32	12.30	14.00	Pass
11a	6Mbps	2	177	5885	0.02	0.02			12.30	0.32	12.62	14.00	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

TEST RESULTS DATA
Average Power Table

UNII-4 MIMO											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			DG (dBi)	E.I.R.P Power (dBm)	E.I.R.P Limit (dBm)
						Ant 4	Ant 3	SUM			
HE20	MCS0	2	169	5845	Full	19.77	20.63	23.23	-1.12	22.11	30
HE20	MCS0	2	173	5865	Full	19.76	20.62	23.22	-1.12	22.10	30
HE20	MCS0	2	177	5885	Full	19.96	20.72	23.37	-1.12	22.25	30
HE40	MCS0	2	167	5835	Full	19.29	19.84	22.58	-1.12	21.46	30
HE40	MCS0	2	175	5875	Full	19.51	19.89	22.71	-1.12	21.59	30
HE80	MCS0	2	171	5855	Full	19.31	19.63	22.48	-1.12	21.36	30
HE160	MCS0	2	163	5815	Full	17.27	17.42	20.36	-1.12	19.24	30

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

UNII-4 MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 4	Ant 3	Ant 4	Ant 3	Ant 4	Ant 3		
EHT20	MCS0	2	169	5845	Full	27.09	19.29	44.29	30.03	18.52	18.85	0.5	Pass
EHT20	MCS0	2	173	5865	Full	26.00	19.35	42.63	33.52	18.27	18.80	0.5	Pass
EHT20	MCS0	2	177	5885	Full	29.49	19.43	46.38	34.04	18.41	18.74	0.5	Pass
EHT40	MCS0	2	167	5835	Full	43.09	38.27	82.86	49.57	37.67	37.40	0.5	Pass
EHT40	MCS0	2	175	5875	Full	46.21	38.34	83.78	61.90	37.56	36.77	0.5	Pass
EHT80	MCS0	2	171	5855	Full	78.09	77.22	153.63	87.42	76.21	76.62	0.5	Pass
EHT160	MCS0	2	163	5815	Full	158.22	157.42	322.94	268.66	157.63	156.03	0.5	Pass

TEST RESULTS DATA
Average Power Table

UNII-4 MIMO											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			DG (dBi)	E.I.R.P Power (dBm)	E.I.R.P Limit (dBm)
						Ant 4	Ant 3	SUM			
EHT20	MCS0	2	169	5845	Full	19.87	20.73	23.33	-1.12	22.21	30
EHT20	MCS0	2	169	5845	26/0	11.50	11.45	14.49	-1.12	13.37	30
EHT20	MCS0	2	169	5845	52/37	14.27	14.19	17.24	-1.12	16.12	30
EHT20	MCS0	2	169	5845	106/53	17.66	17.31	20.50	-1.12	19.38	30
EHT20	MCS0	2	169	5845	52T+26T/70	16.52	16.32	19.43	-1.12	18.31	30
EHT20	MCS0	2	169	5845	106T+26T/82	18.52	18.69	21.62	-1.12	20.50	30
EHT20	MCS0	2	173	5865	Full	19.86	20.72	23.32	-1.12	22.20	30
EHT20	MCS0	2	173	5865	26/4	12.47	12.17	15.33	-1.12	14.21	30
EHT20	MCS0	2	173	5865	52/38	14.65	14.31	17.49	-1.12	16.37	30
EHT20	MCS0	2	173	5865	106/53	17.77	17.25	20.53	-1.12	19.41	30
EHT20	MCS0	2	173	5865	52T+26T/71	16.58	15.95	19.29	-1.12	18.17	30
EHT20	MCS0	2	173	5865	106T+26T/83	18.73	18.16	21.46	-1.12	20.34	30
EHT20	MCS0	2	177	5885	Full	20.06	20.82	23.47	-1.12	22.35	30
EHT20	MCS0	2	177	5885	26/8	11.18	10.91	14.06	-1.12	12.94	30
EHT20	MCS0	2	177	5885	52/40	14.63	14.17	17.42	-1.12	16.30	30
EHT20	MCS0	2	177	5885	106/54	17.84	17.28	20.58	-1.12	19.46	30
EHT20	MCS0	2	177	5885	52T+26T/72	16.62	15.95	19.31	-1.12	18.19	30
EHT20	MCS0	2	177	5885	106T+26T/83	18.70	18.27	21.50	-1.12	20.38	30
EHT40	MCS0	2	167	5835	Full	19.39	19.94	22.68	-1.12	21.56	30
EHT40	MCS0	2	175	5875	Full	19.61	19.99	22.81	-1.12	21.69	30
EHT80	MCS0	2	171	5855	Full	19.41	19.73	22.58	-1.12	21.46	30
EHT80	MCS0	2	171	5855	Punctured 20/1	18.57	18.05	21.33	-1.12	20.21	30
EHT160	MCS0	2	163	5815	Full	17.37	17.52	20.46	-1.12	19.34	30
EHT160	MCS0	2	163	5815	Punctured 40/3	16.79	16.40	19.61	-1.12	18.49	30
EHT160	MCS0	2	163	5815	Punctured 20/1	17.35	16.98	20.18	-1.12	19.06	30

TEST RESULTS DATA
Power Spectral Density


UNII-4 MIMO														
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			DG (dBi)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Pass /Fail
						Ant 1	Ant 2	Ant 4	Ant 3	SUM				
EHT20	MCS0	2	169	5845	Full	0.03	0.03			11.45	0.32	11.78	14.00	Pass
EHT20	MCS0	2	169	5845	26/0	0.10	0.10			11.32	0.32	11.64	14.00	Pass
EHT20	MCS0	2	169	5845	52/37	0.11	0.11			11.21	0.32	11.53	14.00	Pass
EHT20	MCS0	2	169	5845	106/53	0.12	0.12			11.15	0.32	11.48	14.00	Pass
EHT20	MCS0	2	169	5845	52T+26T/70	0.04	0.04			11.24	0.32	11.56	14.00	Pass
EHT20	MCS0	2	169	5845	106T+26T/82	0.09	0.08			11.26	0.32	11.58	14.00	Pass
EHT20	MCS0	2	173	5865	Full	0.03	0.03			11.49	0.32	11.81	14.00	Pass
EHT20	MCS0	2	173	5865	26/4	0.10	0.10			11.11	0.32	11.43	14.00	Pass
EHT20	MCS0	2	173	5865	52/38	0.11	0.11			11.19	0.32	11.51	14.00	Pass
EHT20	MCS0	2	173	5865	106/53	0.12	0.12			11.18	0.32	11.50	14.00	Pass
EHT20	MCS0	2	173	5865	52T+26T/71	0.04	0.04			11.42	0.32	11.74	14.00	Pass
EHT20	MCS0	2	173	5865	106T+26T/83	0.09	0.08			11.29	0.32	11.61	14.00	Pass
EHT20	MCS0	2	177	5885	Full	0.03	0.03			11.84	0.32	12.17	14.00	Pass
EHT20	MCS0	2	177	5885	26/8	0.10	0.10			11.39	0.32	11.71	14.00	Pass
EHT20	MCS0	2	177	5885	52/40	0.11	0.11			11.56	0.32	11.88	14.00	Pass
EHT20	MCS0	2	177	5885	106/54	0.12	0.12			11.54	0.32	11.86	14.00	Pass
EHT20	MCS0	2	177	5885	52T+26T/72	0.04	0.04			11.70	0.32	12.02	14.00	Pass
EHT20	MCS0	2	177	5885	106T+26T/83	0.09	0.08			11.49	0.32	11.81	14.00	Pass
EHT40	MCS0	2	167	5835	Full	0.06	0.06			7.84	0.32	8.16	14.00	Pass
EHT40	MCS0	2	175	5875	Full	0.06	0.06			8.18	0.32	8.51	14.00	Pass
EHT80	MCS0	2	171	5855	Full	0.12	0.13		4.90	0.32	5.23	14.00	Pass	
EHT80	MCS0	2	171	5855	Punctured 20/1	0.09	0.09		4.66	0.32	4.99	14.00	Pass	
EHT160	MCS0	2	163	5815	Full	0.23	0.22		0.33	0.32	0.66	14.00	Pass	
EHT160	MCS0	2	163	5815	Punctured 40/3	0.18	0.18		0.29	0.32	0.62	14.00	Pass	
EHT160	MCS0	2	163	5815	Punctured 20/1	0.20	0.20		-0.06	0.32	0.27	14.00	Pass	

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**

MIMO <Ant. 4+3>


<802.11a>



Note: The occupied channel bandwidth is maintained within the band of operation.




<802.11be EHT20>



Note: The occupied channel bandwidth is maintained within the band of operation.




<802.11be EHT40>



Note: The occupied channel bandwidth is maintained within the band of operation.




<802.11be EHT80>



Note: The occupied channel bandwidth is maintained within the band of operation.




<802.11be EHT160>




Note: The occupied channel bandwidth is maintained within the band of operation.

**Test Result of Power Spectral Density**

<802.11a>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11be EHT20>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11be EHT40>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11be EHT80>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11be EHT160>



Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.





Appendix B. AC Conducted Emission Test Results


Test Engineer :	Louis Chung	Temperature :	23.1~24.8℃
		Relative Humidity :	43.3~46.7%

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

4N0920
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.153983	---	26.00	55.78	29.78	L1	FLO	20.0
0.153983	43.82	---	65.78	21.96	L1	FLO	20.0
0.186000	---	32.97	54.21	21.24	L1	FLO	20.0
0.186000	49.32	---	64.21	14.89	L1	FLO	20.0
0.190500	---	36.22	54.02	17.80	L1	FLO	20.0
0.190500	51.11	---	64.02	12.91	L1	FLO	20.0
0.273660	---	22.97	51.01	28.04	L1	FLO	20.0
0.273660	31.77	---	61.01	29.24	L1	FLO	20.0
0.386250	---	17.63	48.14	30.51	L1	FLO	20.0
0.386250	29.88	---	58.14	28.26	L1	FLO	20.0
0.548790	---	24.80	46.00	21.20	L1	FLO	20.0
0.548790	32.66	---	56.00	23.34	L1	FLO	20.0
0.690000	---	15.90	46.00	30.10	L1	FLO	20.0
0.690000	32.43	---	56.00	23.57	L1	FLO	20.0
0.780360	---	16.76	46.00	29.24	L1	FLO	20.0
0.780360	32.78	---	56.00	23.22	L1	FLO	20.0
1.092750	---	18.89	46.00	27.11	L1	FLO	20.0
1.092750	31.39	---	56.00	24.61	L1	FLO	20.0
1.180500	---	17.15	46.00	28.85	L1	FLO	20.0

1.180500	35.48	---	56.00	20.52	L1	FLO	20.0
1.304250	---	16.90	46.00	29.10	L1	FLO	20.0
1.304250	32.52	---	56.00	23.48	L1	FLO	20.0
12.846750	---	29.32	50.00	20.68	L1	FLO	20.5
12.846750	34.02	---	60.00	25.98	L1	FLO	20.5
24.626220	---	18.02	50.00	31.98	L1	FLO	20.9
24.626220	20.53	---	60.00	39.47	L1	FLO	20.9

EUT Information

Report NO : 4N0920
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.152565	---	27.08	55.86	28.78	N	FLO	20.0
0.152565	43.65	---	65.86	22.21	N	FLO	20.0
0.210750	---	19.13	53.18	34.05	N	FLO	20.0
0.210750	33.98	---	63.18	29.20	N	FLO	20.0
0.259080	---	22.38	51.46	29.08	N	FLO	20.0
0.259080	34.53	---	61.46	26.93	N	FLO	20.0
0.406500	---	29.82	47.72	17.90	N	FLO	20.0
0.406500	33.26	---	57.72	24.46	N	FLO	20.0
0.516750	---	15.37	46.00	30.63	N	FLO	20.0
0.516750	28.12	---	56.00	27.88	N	FLO	20.0
0.685320	---	24.08	46.00	21.92	N	FLO	20.0
0.685320	36.23	---	56.00	19.77	N	FLO	20.0
0.782250	---	16.86	46.00	29.14	N	FLO	20.0
0.782250	33.12	---	56.00	22.88	N	FLO	20.0
1.093290	---	18.52	46.00	27.48	N	FLO	20.0
1.093290	31.99	---	56.00	24.01	N	FLO	20.0
1.181490	---	17.18	46.00	28.82	N	FLO	20.0
1.181490	35.45	---	56.00	20.55	N	FLO	20.0
1.308480	---	16.56	46.00	29.44	N	FLO	20.0

1.308480	32.74	---	56.00	23.26	N	FLO	20.0
13.033500	---	25.21	50.00	24.79	N	FLO	20.5
13.033500	31.99	---	60.00	28.01	N	FLO	20.5
21.482430	---	20.18	50.00	29.82	N	FLO	20.9
21.482430	24.03	---	60.00	35.97	N	FLO	20.9



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Sam Pan, Quentin Liu and Bigshow Wang	Relative Humidity(%):	50~65
		Temperature(°C):	18~23

Note symbol

-L	Low channel location
-R	High channel location

C1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 63	U-NII-4	5.85-5.895	4+3	802.11a	169	5845	6Mbps	-	-
Mode 64	U-NII-4	5.85-5.895	4+3	802.11a	173	5865	6Mbps	-	-
Mode 65	U-NII-4	5.85-5.895	4+3	802.11a	177	5885	6Mbps	-	-
Mode 66	U-NII-4	5.85-5.895	4+3	802.11be EHT20	169	5845	MCS0	Full RU	-
Mode 67	U-NII-4	5.85-5.895	4+3	802.11be EHT20	169	5845	MCS0	Partial_26/0RU	-
Mode 68	U-NII-4	5.85-5.895	4+3	802.11be EHT20	169	5845	MCS0	Partial_52/37RU	-
Mode 69	U-NII-4	5.85-5.895	4+3	802.11be EHT20	169	5845	MCS0	Partial_106/53RU	-
Mode 70	U-NII-4	5.85-5.895	4+3	802.11be EHT20	173	5865	MCS0	Full RU	-
Mode 71	U-NII-4	5.85-5.895	4+3	802.11be EHT20	177	5885	MCS0	Full RU	-
Mode 72	U-NII-4	5.85-5.895	4+3	802.11be EHT20	177	5885	MCS0	Partial_26/8RU	-
Mode 73	U-NII-4	5.85-5.895	4+3	802.11be EHT20	177	5885	MCS0	Partial_52/38RU	-
Mode 74	U-NII-4	5.85-5.895	4+3	802.11be EHT20	177	5885	MCS0	Partial_106/54RU	-



Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 75	U-NII-4	5.85-5.895	4+3	802.11be EHT40	167	5835	MCS0	Full RU	-
Mode 76	U-NII-4	5.85-5.895	4+3	802.11be EHT40	175	5875	MCS0	Full RU	-
Mode 77	U-NII-4	5.85-5.895	4+3	802.11be EHT80	171	5855	MCS0	Full RU	-
Mode 78	U-NII-4	5.85-5.895	4+3	802.11be EHT160	163	5815	MCS0	Full RU	-
Mode 83	U-NII-4	5.85-5.895	4+3	802.11be EHT160	163	5815	MCS0	Full RU	LF
Mode 84	U-NII-4	5.85-5.895	4+3	802.11be EHT160	163	5815	MCS0	Full RU	SHF

C2. Summary of each worse mode




Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
63	802.11a	169	5649.56	48.46	68.20	-19.74	V	Peak	Pass	-	Band Edge
	802.11a	169	17535.00	46.22	68.20	-21.98	V	Peak	Pass	-	Harmonic
64	802.11a	173	5648.09	47.90	68.20	-20.30	H	Peak	Pass	-	Band Edge
	802.11a	173	17595.00	47.34	68.20	-20.86	H	Peak	Pass	-	Harmonic
65	802.11a	177	5641.30	47.65	68.20	-20.55	H	Peak	Pass	-	Band Edge
	802.11a	177	17655.00	47.79	68.20	-20.41	H	Peak	Pass	-	Harmonic
66	802.11be EHT20	169	5604.43	48.21	68.20	-19.99	V	Peak	Pass	Full RU	Band Edge
	802.11be EHT20	169	17535.00	46.22	68.20	-21.98	H	Peak	Pass	Full RU	Harmonic
67	802.11be EHT20	169	5644.84	49.22	68.20	-18.98	V	Peak	Pass	Partial_26/0RU	Band Edge
	802.11be EHT20	169	-	-	-	-	-	-	-	Partial_26/0RU	Harmonic
68	802.11be EHT20	169	5651.04	48.90	68.97	-20.07	H	Peak	Pass	Partial_52/37RU	Band Edge
	802.11be EHT20	169	-	-	-	-	-	-	-	Partial_52/37RU	Harmonic
69	802.11be EHT20	169	5650.74	48.68	68.75	-20.07	V	Peak	Pass	Partial_106/53RU	Band Edge
	802.11be EHT20	169	-	-	-	-	-	-	-	Partial_106/53RU	Harmonic
70	802.11be EHT20	173	5629.21	47.79	68.20	-20.41	V	Peak	Pass	Full RU	Band Edge
	802.11be EHT20	173	17595.00	49.15	68.20	-19.05	H	Peak	Pass	Full RU	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
71	802.11be EHT20	177	5629.80	48.02	68.20	-20.18	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT20	177	17655.00	56.93	68.20	-11.27	H	Peak	Pass	Full RU	Harmonic
72	802.11be EHT20	177	5895.25	91.43	110.02	-18.59	V	Avg.	Pass	Partial_26/8RU	Band Edge
	802.11be EHT20	177	-	-	-	-	-	-	-	Partial_26/8RU	Harmonic
73	802.11be EHT20	177	5641.60	47.70	68.20	-20.50	H	Peak	Pass	Partial_52/38RU	Band Edge
	802.11be EHT20	177	-	-	-	-	-	-	-	Partial_52/38RU	Harmonic
74	802.11be EHT20	177	5628.03	48.63	68.20	-19.57	V	Peak	Pass	Partial_106/54RU	Band Edge
	802.11be EHT20	177	-	-	-	-	-	-	-	Partial_106/54RU	Harmonic
75	802.11be EHT40	167	5649.86	54.58	68.20	-13.62	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT40	167	17505.00	54.58	68.20	-13.62	H	Peak	Pass	Full RU	Harmonic
76	802.11be EHT40	175	5645.43	49.23	68.20	-18.97	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT40	175	17625.00	47.88	68.20	-20.32	H	Peak	Pass	Full RU	Harmonic
77	802.11be EHT80	171	5645.14	59.25	68.20	-8.95	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT80	171	17565.00	47.50	68.20	-20.70	H	Peak	Pass	Full RU	Harmonic
78	802.11be EHT160	163	5643.96	66.31	68.20	-1.89	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT160	163	17445.00	47.82	68.20	-20.38	V	Peak	Pass	Full RU	Harmonic



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
83	LF	163	97.90	34.17	43.50	-9.33	H	Peak	Pass	-	LF
84	SHF	163	39593.36	47.51	74.00	-26.49	V	Peak	Pass	-	SHF





Mode	63																																																																																																																																											
	Band Edge - L																																																																																																																																											
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																																																																											
ANT	4+3																																																																																																																																											
Pol.	Horizontal							Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBI:3000.000kHz SWT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5647.50</td><td>48.38</td><td>68.20</td><td>-19.82</td><td>43.22</td><td>33.28</td><td>8.68</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>47.47</td><td>68.53</td><td>-21.06</td><td>42.28</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr><tr><td>3</td><td>5700.60</td><td>47.73</td><td>105.37</td><td>-57.64</td><td>42.09</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>47.36</td><td>110.95</td><td>-63.59</td><td>41.65</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5647.50	48.38	68.20	-19.82	43.22	33.28	8.68	36.80	0.00	0.00	200	33	PEAK	2	5650.45	47.47	68.53	-21.06	42.28	33.30	8.69	36.80	0.00	0.00	200	33	PEAK	3	5700.60	47.73	105.37	-57.64	42.09	33.70	8.74	36.80	0.00	0.00	200	33	PEAK	4	5720.07	47.36	110.95	-63.59	41.65	33.74	8.76	36.79	0.00	0.00	200	33	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBI:3000.000kHz SWT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>105.43</td><td>-----</td><td>-----</td><td>99.11</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5845.00	105.43	-----	-----	99.11	34.20	8.90	36.78	0.00	0.00	200	33	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5647.50	48.38	68.20	-19.82	43.22	33.28	8.68	36.80	0.00	0.00	200	33	PEAK																																																																																																																															
2	5650.45	47.47	68.53	-21.06	42.28	33.30	8.69	36.80	0.00	0.00	200	33	PEAK																																																																																																																															
3	5700.60	47.73	105.37	-57.64	42.09	33.70	8.74	36.80	0.00	0.00	200	33	PEAK																																																																																																																															
4	5720.07	47.36	110.95	-63.59	41.65	33.74	8.76	36.79	0.00	0.00	200	33	PEAK																																																																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5845.00	105.43	-----	-----	99.11	34.20	8.90	36.78	0.00	0.00	200	33	PEAK																																																																																																																															
Avg	Blank							 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBI:0.010kHz SWT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>100.19</td><td>-----</td><td>-----</td><td>93.87</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>0.00</td><td>200</td><td>33</td><td>AVERAGE</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5845.00	100.19	-----	-----	93.87	34.20	8.90	36.78	0.00	0.00	200	33	AVERAGE																																																																																				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5845.00	100.19	-----	-----	93.87	34.20	8.90	36.78	0.00	0.00	200	33	AVERAGE																																																																																																																															






FCC RADIO TEST REPORT



Report No. : FR4N0920F

Mode	63																																																																		
	Band Edge - R																																																																		
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																		
ANT	4+3																																																																		
Pol.	Horizontal											Fundamental																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.25</td><td>49.12</td><td>108.75</td><td>-59.63</td><td>42.60</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr><tr><td>2</td><td>5930.50</td><td>48.96</td><td>108.20</td><td>-59.24</td><td>42.46</td><td>34.28</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>33</td><td>PEAK</td></tr></tbody></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5924.25	49.12	108.75	-59.63	42.60	34.30	8.99	36.77	0.00	200	33	PEAK	2	5930.50	48.96	108.20	-59.24	42.46	34.28	8.99	36.77	0.00	200	33	PEAK	Blank	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																							
1	5924.25	49.12	108.75	-59.63	42.60	34.30	8.99	36.77	0.00	200	33	PEAK																																																							
2	5930.50	48.96	108.20	-59.24	42.46	34.28	8.99	36.77	0.00	200	33	PEAK																																																							
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5925.00</td><td>39.47</td><td>88.20</td><td>-48.73</td><td>32.95</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>33</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.75</td><td>39.49</td><td>88.20</td><td>-48.71</td><td>32.97</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>33</td><td>AVERAGE</td></tr></tbody></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5925.00	39.47	88.20	-48.73	32.95	34.30	8.99	36.77	0.00	200	33	AVERAGE	2	5925.75	39.49	88.20	-48.71	32.97	34.30	8.99	36.77	0.00	200	33	AVERAGE	Blank	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																							
1	5925.00	39.47	88.20	-48.73	32.95	34.30	8.99	36.77	0.00	200	33	AVERAGE																																																							
2	5925.75	39.49	88.20	-48.71	32.97	34.30	8.99	36.77	0.00	200	33	AVERAGE																																																							





Mode	63																																																																																																																																				
	Band Edge - L																																																																																																																																				
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																																																																				
ANT	4+3																																																																																																																																				
Pol.	Vertical						Fundamental																																																																																																																														
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5649.56</td><td>48.46</td><td>68.20</td><td>-19.74</td><td>43.28</td><td>33.30</td><td>8.68</td><td>36.80</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>46.36</td><td>68.31</td><td>-21.95</td><td>41.17</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr><tr><td>3</td><td>5704.43</td><td>49.59</td><td>106.44</td><td>-56.85</td><td>43.94</td><td>33.71</td><td>8.74</td><td>36.80</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>47.46</td><td>110.95</td><td>-63.49</td><td>41.75</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5649.56	48.46	68.20	-19.74	43.28	33.30	8.68	36.80	0.00	100	50	PEAK	2	5650.15	46.36	68.31	-21.95	41.17	33.30	8.69	36.80	0.00	100	50	PEAK	3	5704.43	49.59	106.44	-56.85	43.94	33.71	8.74	36.80	0.00	100	50	PEAK	4	5720.07	47.46	110.95	-63.49	41.75	33.74	8.76	36.79	0.00	100	50	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>111.23</td><td>-----</td><td>-----</td><td>104.91</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	111.23	-----	-----	104.91	34.20	8.90	36.78	0.00	100	50	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5649.56	48.46	68.20	-19.74	43.28	33.30	8.68	36.80	0.00	100	50	PEAK																																																																																																																									
2	5650.15	46.36	68.31	-21.95	41.17	33.30	8.69	36.80	0.00	100	50	PEAK																																																																																																																									
3	5704.43	49.59	106.44	-56.85	43.94	33.71	8.74	36.80	0.00	100	50	PEAK																																																																																																																									
4	5720.07	47.46	110.95	-63.49	41.75	33.74	8.76	36.79	0.00	100	50	PEAK																																																																																																																									
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5845.00	111.23	-----	-----	104.91	34.20	8.90	36.78	0.00	100	50	PEAK																																																																																																																									
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector: PEAK Mode : 63 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>104.80</td><td>-----</td><td>-----</td><td>98.48</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>100</td><td>50</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	104.80	-----	-----	98.48	34.20	8.90	36.78	0.00	100	50	AVERAGE																																																																																
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5845.00	104.80	-----	-----	98.48	34.20	8.90	36.78	0.00	100	50	AVERAGE																																																																																																																									







Mode	63																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																										
ANT	4+3																																																										
Pol.	Vertical						Fundamental																																																				
Peak							Blank																																																				
	Site : 03CH15-HY Condition: PEAK_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5922.50</td><td>50.21</td><td>110.03</td><td>-59.82</td><td>43.69</td><td>34.31</td><td>8.98</td><td>36.77</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr><tr><td>2</td><td>5932.00</td><td>49.80</td><td>108.20</td><td>-58.40</td><td>43.30</td><td>34.27</td><td>9.00</td><td>36.77</td><td>0.00</td><td>100</td><td>50</td><td>PEAK</td></tr></tbody></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5922.50	50.21	110.03	-59.82	43.69	34.31	8.98	36.77	0.00	100	50	PEAK	2	5932.00	49.80	108.20	-58.40	43.30
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																															
1	5922.50	50.21	110.03	-59.82	43.69	34.31	8.98	36.77	0.00	100	50	PEAK																																															
2	5932.00	49.80	108.20	-58.40	43.30	34.27	9.00	36.77	0.00	100	50	PEAK																																															
Avg							Blank																																																				
	Site : 03CH15-HY Condition: AVG_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 63 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5925.00</td><td>39.88</td><td>88.20</td><td>-48.32</td><td>33.36</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>100</td><td>50</td><td>AVERAGE</td></tr><tr><td>2</td><td>5927.50</td><td>40.02</td><td>88.20</td><td>-48.18</td><td>33.51</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>100</td><td>50</td><td>AVERAGE</td></tr></tbody></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5925.00	39.88	88.20	-48.32	33.36	34.30	8.99	36.77	0.00	100	50	AVERAGE	2	5927.50	40.02	88.20	-48.18	33.51
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																															
1	5925.00	39.88	88.20	-48.32	33.36	34.30	8.99	36.77	0.00	100	50	AVERAGE																																															
2	5927.50	40.02	88.20	-48.18	33.51	34.29	8.99	36.77	0.00	100	50	AVERAGE																																															






Mode	63																																																																																																					
	Harmonic																																																																																																					
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																																					
ANT	4+3																																																																																																					
Pol.	Horizontal	Vertical																																																																																																				
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 HORIZONTAL Mode : 63 Setting : 80 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11690.00</td><td>45.65</td><td>74.00</td><td>-28.35</td><td>50.73</td><td>38.60</td><td>12.71</td><td>57.32</td><td>0.93</td><td>-- -- Peak</td></tr><tr><td>2 17535.00</td><td>45.02</td><td>68.20</td><td>-23.18</td><td>48.97</td><td>38.58</td><td>15.63</td><td>59.09</td><td>0.93</td><td>-- -- Peak</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11690.00	45.65	74.00	-28.35	50.73	38.60	12.71	57.32	0.93	-- -- Peak	2 17535.00	45.02	68.20	-23.18	48.97	38.58	15.63	59.09	0.93	-- -- Peak	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 VERTICAL Mode : 63 Setting : 80 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11690.00</td><td>46.19</td><td>74.00</td><td>-27.81</td><td>51.23</td><td>38.62</td><td>12.72</td><td>57.31</td><td>0.93</td><td>-- -- Peak</td></tr><tr><td>2 17535.00</td><td>46.22</td><td>68.20</td><td>-21.98</td><td>50.17</td><td>38.58</td><td>15.63</td><td>59.09</td><td>0.93</td><td>-- -- Peak</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11690.00	46.19	74.00	-27.81	51.23	38.62	12.72	57.31	0.93	-- -- Peak	2 17535.00	46.22	68.20	-21.98	50.17	38.58	15.63	59.09	0.93	-- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																													
1 11690.00	45.65	74.00	-28.35	50.73	38.60	12.71	57.32	0.93	-- -- Peak																																																																																													
2 17535.00	45.02	68.20	-23.18	48.97	38.58	15.63	59.09	0.93	-- -- Peak																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																													
1 11690.00	46.19	74.00	-27.81	51.23	38.62	12.72	57.31	0.93	-- -- Peak																																																																																													
2 17535.00	46.22	68.20	-21.98	50.17	38.58	15.63	59.09	0.93	-- -- Peak																																																																																													



Mode	63	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL Mode : 63 Setting : 80	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL Mode : 63 Setting : 80
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL Mode : 63 Setting : 80	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL Mode : 63 Setting : 80





Mode	64																																																																																																																																																							
	Band Edge - L																																																																																																																																																							
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																																																							
ANT	4+3																																																																																																																																																							
Pol.	Horizontal																																																																																																																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5648.09</td><td>47.90</td><td>68.20</td><td>-20.30</td><td>42.73</td><td>33.29</td><td>8.68</td><td>36.80</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>5650.15</td><td>46.26</td><td>68.31</td><td>-22.05</td><td>41.07</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td><td></td></tr><tr><td>3</td><td>5700.01</td><td>48.09</td><td>105.20</td><td>-57.11</td><td>42.45</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td><td></td></tr><tr><td>4</td><td>5720.36</td><td>48.03</td><td>111.62</td><td>-63.59</td><td>42.32</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5648.09	47.90	68.20	-20.30	42.73	33.29	8.68	36.80	0.00	167	296	PEAK		2	5650.15	46.26	68.31	-22.05	41.07	33.30	8.69	36.80	0.00	167	296	PEAK		3	5700.01	48.09	105.20	-57.11	42.45	33.70	8.74	36.80	0.00	167	296	PEAK		4	5720.36	48.03	111.62	-63.59	42.32	33.74	8.76	36.79	0.00	167	296	PEAK		 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>108.51</td><td>-----</td><td>-----</td><td>102.07</td><td>34.29</td><td>8.93</td><td>36.78</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5865.00	108.51	-----	-----	102.07	34.29	8.93	36.78	0.00	167	296	PEAK	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5648.09	47.90	68.20	-20.30	42.73	33.29	8.68	36.80	0.00	167	296	PEAK																																																																																																																																												
2	5650.15	46.26	68.31	-22.05	41.07	33.30	8.69	36.80	0.00	167	296	PEAK																																																																																																																																												
3	5700.01	48.09	105.20	-57.11	42.45	33.70	8.74	36.80	0.00	167	296	PEAK																																																																																																																																												
4	5720.36	48.03	111.62	-63.59	42.32	33.74	8.76	36.79	0.00	167	296	PEAK																																																																																																																																												
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5865.00	108.51	-----	-----	102.07	34.29	8.93	36.78	0.00	167	296	PEAK																																																																																																																																												
Avg	Blank																																																																																																																																																							
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>103.01</td><td>-----</td><td>-----</td><td>96.61</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>167</td><td>296</td><td>AVERAGE</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5865.00	103.01	-----	-----	96.61	34.26	8.92	36.78	0.00	167	296	AVERAGE																																																																																																		
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5865.00	103.01	-----	-----	96.61	34.26	8.92	36.78	0.00	167	296	AVERAGE																																																																																																																																												



FCC RADIO TEST REPORT



Report No. : FR4N0920F

Mode	64																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNI 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.75</td><td>52.47</td><td>109.11</td><td>-56.64</td><td>45.94</td><td>34.31</td><td>8.99</td><td>36.77</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td></tr><tr><td>2</td><td>5933.00</td><td>51.51</td><td>108.20</td><td>-56.69</td><td>45.01</td><td>34.27</td><td>9.00</td><td>36.77</td><td>0.00</td><td>167</td><td>296</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5923.75	52.47	109.11	-56.64	45.94	34.31	8.99	36.77	0.00	167	296	PEAK	2	5933.00	51.51	108.20	-56.69	45.01	34.27	9.00	36.77	0.00	167	296	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																												
1	5923.75	52.47	109.11	-56.64	45.94	34.31	8.99	36.77	0.00	167	296	PEAK																																												
2	5933.00	51.51	108.20	-56.69	45.01	34.27	9.00	36.77	0.00	167	296	PEAK																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNI 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>41.20</td><td>88.20</td><td>-47.00</td><td>34.68</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>167</td><td>296</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.25</td><td>41.31</td><td>88.20</td><td>-46.89</td><td>34.79</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>167</td><td>296</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5925.00	41.20	88.20	-47.00	34.68	34.30	8.99	36.77	0.00	167	296	AVERAGE	2	5925.25	41.31	88.20	-46.89	34.79	34.30	8.99	36.77	0.00	167	296	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																												
1	5925.00	41.20	88.20	-47.00	34.68	34.30	8.99	36.77	0.00	167	296	AVERAGE																																												
2	5925.25	41.31	88.20	-46.89	34.79	34.30	8.99	36.77	0.00	167	296	AVERAGE																																												





Mode	64																																																																																																																																																		
	Band Edge - L																																																																																																																																																		
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																																																		
ANT	4+3																																																																																																																																																		
Pol.	Vertical																																																																																																																																																		
Peak	Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5626.26</td><td>47.83</td><td>68.20</td><td>-20.37</td><td>42.81</td><td>33.16</td><td>8.66</td><td>36.80</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr><tr><td>2</td><td>5650.74</td><td>46.63</td><td>68.75</td><td>-22.12</td><td>41.43</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr><tr><td>3</td><td>5701.48</td><td>48.14</td><td>105.62</td><td>-57.48</td><td>42.50</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>47.77</td><td>110.95</td><td>-63.18</td><td>42.06</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5626.26	47.83	68.20	-20.37	42.81	33.16	8.66	36.80	0.00	188	55	PEAK	2	5650.74	46.63	68.75	-22.12	41.43	33.31	8.69	36.80	0.00	188	55	PEAK	3	5701.48	48.14	105.62	-57.48	42.50	33.70	8.74	36.80	0.00	188	55	PEAK	4	5720.07	47.77	110.95	-63.18	42.06	33.74	8.76	36.79	0.00	188	55	PEAK	Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>109.92</td><td>-----</td><td>-----</td><td>103.52</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5865.00	109.92	-----	-----	103.52	34.26	8.92	36.78	0.00	188	55	PEAK
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5626.26	47.83	68.20	-20.37	42.81	33.16	8.66	36.80	0.00	188	55	PEAK																																																																																																																																							
2	5650.74	46.63	68.75	-22.12	41.43	33.31	8.69	36.80	0.00	188	55	PEAK																																																																																																																																							
3	5701.48	48.14	105.62	-57.48	42.50	33.70	8.74	36.80	0.00	188	55	PEAK																																																																																																																																							
4	5720.07	47.77	110.95	-63.18	42.06	33.74	8.76	36.79	0.00	188	55	PEAK																																																																																																																																							
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5865.00	109.92	-----	-----	103.52	34.26	8.92	36.78	0.00	188	55	PEAK																																																																																																																																							
Avg	Blank													Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>104.32</td><td>-----</td><td>-----</td><td>97.92</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>188</td><td>55</td><td>AVERAGE</td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5865.00	104.32	-----	-----	97.92	34.26	8.92	36.78	0.00	188	55	AVERAGE																																																																																
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																						
1	5865.00	104.32	-----	-----	97.92	34.26	8.92	36.78	0.00	188	55	AVERAGE																																																																																																																																							







Mode	64																																																															
	Band Edge - R																																																															
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																															
ANT	4+3																																																															
Pol.	Vertical					Fundamental																																																										
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5925.00</td><td>52.33</td><td>108.20</td><td>-55.87</td><td>45.81</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr><tr><td>2</td><td>5925.00</td><td>52.33</td><td>108.20</td><td>-55.87</td><td>45.81</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>55</td><td>PEAK</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5925.00	52.33	108.20	-55.87	45.81	34.30	8.99	36.77	0.00	188	55	PEAK	2	5925.00	52.33	108.20	-55.87	45.81	34.30	8.99	36.77	0.00	188	55	PEAK	Blank				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																				
1	5925.00	52.33	108.20	-55.87	45.81	34.30	8.99	36.77	0.00	188	55	PEAK																																																				
2	5925.00	52.33	108.20	-55.87	45.81	34.30	8.99	36.77	0.00	188	55	PEAK																																																				
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 64 Setting : 80 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.75</td><td>42.16</td><td>88.38</td><td>-46.22</td><td>35.64</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>55</td><td>AVERAGE</td></tr><tr><td>2</td><td>5928.00</td><td>41.95</td><td>88.20</td><td>-46.25</td><td>35.44</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>55</td><td>AVERAGE</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5924.75	42.16	88.38	-46.22	35.64	34.30	8.99	36.77	0.00	188	55	AVERAGE	2	5928.00	41.95	88.20	-46.25	35.44	34.29	8.99	36.77	0.00	188	55	AVERAGE	Blank				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																				
1	5924.75	42.16	88.38	-46.22	35.64	34.30	8.99	36.77	0.00	188	55	AVERAGE																																																				
2	5928.00	41.95	88.20	-46.25	35.44	34.29	8.99	36.77	0.00	188	55	AVERAGE																																																				






Mode	64																																																																																																																								
	Harmonic																																																																																																																								
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																								
ANT	4+3																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg																																																																																																																									
	Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_240620 HORIZONTAL Mode : 64 Setting : 80 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11730.00</td><td>46.28</td><td>74.00</td><td>-27.72</td><td>51.26</td><td>38.66</td><td>12.73</td><td>57.30</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17595.00</td><td>47.34</td><td>68.20</td><td>-20.86</td><td>50.56</td><td>39.02</td><td>15.69</td><td>58.86</td><td>0.93</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11730.00	46.28	74.00	-27.72	51.26	38.66	12.73	57.30	0.93	--	Peak	2	17595.00	47.34	68.20	-20.86	50.56	39.02	15.69	58.86	0.93	--	Peak	Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_240620 VERTICAL Mode : 64 Setting : 80 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11730.00</td><td>45.68</td><td>74.00</td><td>-28.32</td><td>50.62</td><td>38.68</td><td>12.74</td><td>57.29</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17595.00</td><td>47.32</td><td>68.20</td><td>-20.88</td><td>50.62</td><td>38.97</td><td>15.68</td><td>58.88</td><td>0.93</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11730.00	45.68	74.00	-28.32	50.62	38.68	12.74	57.29	0.93	--	Peak	2	17595.00	47.32	68.20	-20.88	50.62	38.97	15.68	58.88	0.93	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	11730.00	46.28	74.00	-27.72	51.26	38.66	12.73	57.30	0.93	--	Peak																																																																																																														
2	17595.00	47.34	68.20	-20.86	50.56	39.02	15.69	58.86	0.93	--	Peak																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	11730.00	45.68	74.00	-28.32	50.62	38.68	12.74	57.29	0.93	--	Peak																																																																																																														
2	17595.00	47.32	68.20	-20.88	50.62	38.97	15.68	58.88	0.93	--	Peak																																																																																																														



Mode	64	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 64 Setting : 80	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 64 Setting : 80
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 64 Setting : 80	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 64 Setting : 80





Mode	65																																																																																																																																											
	Band Edge - L																																																																																																																																											
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																																																																																											
ANT	4+3																																																																																																																																											
Pol.	Horizontal							Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-82294_240620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5641.30</td><td>47.65</td><td>68.20</td><td>-20.55</td><td>42.52</td><td>33.25</td><td>8.68</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr><tr><td>2</td><td>5658.74</td><td>46.04</td><td>68.75</td><td>-22.71</td><td>40.84</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr><tr><td>3</td><td>5700.89</td><td>47.12</td><td>105.45</td><td>-58.33</td><td>41.48</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>45.18</td><td>110.95</td><td>-65.77</td><td>39.47</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5641.30	47.65	68.20	-20.55	42.52	33.25	8.68	36.80	0.00	0.00	200	36	PEAK	2	5658.74	46.04	68.75	-22.71	40.84	33.31	8.69	36.80	0.00	0.00	200	36	PEAK	3	5700.89	47.12	105.45	-58.33	41.48	33.70	8.74	36.80	0.00	0.00	200	36	PEAK	4	5720.07	45.18	110.95	-65.77	39.47	33.74	8.76	36.79	0.00	0.00	200	36	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-82294_240620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>107.58</td><td>-----</td><td>-----</td><td>101.04</td><td>34.36</td><td>8.95</td><td>36.77</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	107.58	-----	-----	101.04	34.36	8.95	36.77	0.00	0.00	200	36	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5641.30	47.65	68.20	-20.55	42.52	33.25	8.68	36.80	0.00	0.00	200	36	PEAK																																																																																																																															
2	5658.74	46.04	68.75	-22.71	40.84	33.31	8.69	36.80	0.00	0.00	200	36	PEAK																																																																																																																															
3	5700.89	47.12	105.45	-58.33	41.48	33.70	8.74	36.80	0.00	0.00	200	36	PEAK																																																																																																																															
4	5720.07	45.18	110.95	-65.77	39.47	33.74	8.76	36.79	0.00	0.00	200	36	PEAK																																																																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5885.00	107.58	-----	-----	101.04	34.36	8.95	36.77	0.00	0.00	200	36	PEAK																																																																																																																															
Avg	Blank							 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-82294_240620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>101.57</td><td>-----</td><td>-----</td><td>95.06</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>0.00</td><td>200</td><td>36</td><td>AVERAGE</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	101.57	-----	-----	95.06	34.34	8.94	36.77	0.00	0.00	200	36	AVERAGE																																																																																				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5885.00	101.57	-----	-----	95.06	34.34	8.94	36.77	0.00	0.00	200	36	AVERAGE																																																																																																																															



FCC RADIO TEST REPORT



Report No. : FR4N0920F

Mode	65																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNI 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5899.25</td><td>86.58</td><td>127.08</td><td>-40.50</td><td>79.99</td><td>34.40</td><td>8.96</td><td>36.77</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr><tr><td>2</td><td>5926.25</td><td>57.91</td><td>108.20</td><td>-50.29</td><td>51.40</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>36</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5899.25	86.58	127.08	-40.50	79.99	34.40	8.96	36.77	0.00	200	36	PEAK	2	5926.25	57.91	108.20	-50.29	51.40	34.29	8.99	36.77	0.00	200	36	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																												
1	5899.25	86.58	127.08	-40.50	79.99	34.40	8.96	36.77	0.00	200	36	PEAK																																												
2	5926.25	57.91	108.20	-50.29	51.40	34.29	8.99	36.77	0.00	200	36	PEAK																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNI 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5898.00</td><td>75.51</td><td>108.00</td><td>-32.49</td><td>68.93</td><td>34.39</td><td>8.96</td><td>36.77</td><td>0.00</td><td>200</td><td>36</td><td>AVERAGE</td></tr><tr><td>2</td><td>5926.00</td><td>46.63</td><td>88.20</td><td>-41.57</td><td>40.11</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>36</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5898.00	75.51	108.00	-32.49	68.93	34.39	8.96	36.77	0.00	200	36	AVERAGE	2	5926.00	46.63	88.20	-41.57	40.11	34.30	8.99	36.77	0.00	200	36	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																												
1	5898.00	75.51	108.00	-32.49	68.93	34.39	8.96	36.77	0.00	200	36	AVERAGE																																												
2	5926.00	46.63	88.20	-41.57	40.11	34.30	8.99	36.77	0.00	200	36	AVERAGE																																												





Mode	65																																																																																																																																											
	Band Edge - L																																																																																																																																											
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																																																																																											
ANT	4+3																																																																																																																																											
Pol.	Vertical							Fundamental																																																																																																																																				
Peak	Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5629.80</td><td>47.42</td><td>68.20</td><td>-20.78</td><td>42.38</td><td>33.18</td><td>8.66</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr><tr><td>2</td><td>5651.92</td><td>46.96</td><td>69.63</td><td>-22.67</td><td>41.75</td><td>33.32</td><td>8.69</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr><tr><td>3</td><td>5705.61</td><td>48.73</td><td>106.77</td><td>-58.04</td><td>43.07</td><td>33.71</td><td>8.75</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr><tr><td>4</td><td>5728.07</td><td>47.01</td><td>110.95</td><td>-63.94</td><td>41.30</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5629.80	47.42	68.20	-20.78	42.38	33.18	8.66	36.80	0.00	0.00	201	57	PEAK	2	5651.92	46.96	69.63	-22.67	41.75	33.32	8.69	36.80	0.00	0.00	201	57	PEAK	3	5705.61	48.73	106.77	-58.04	43.07	33.71	8.75	36.80	0.00	0.00	201	57	PEAK	4	5728.07	47.01	110.95	-63.94	41.30	33.74	8.76	36.79	0.00	0.00	201	57	PEAK	Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>111.54</td><td>-----</td><td>-----</td><td>-----</td><td>105.03</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	111.54	-----	-----	-----	105.03	34.34	8.94	36.77	0.00	201	57	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5629.80	47.42	68.20	-20.78	42.38	33.18	8.66	36.80	0.00	0.00	201	57	PEAK																																																																																																																															
2	5651.92	46.96	69.63	-22.67	41.75	33.32	8.69	36.80	0.00	0.00	201	57	PEAK																																																																																																																															
3	5705.61	48.73	106.77	-58.04	43.07	33.71	8.75	36.80	0.00	0.00	201	57	PEAK																																																																																																																															
4	5728.07	47.01	110.95	-63.94	41.30	33.74	8.76	36.79	0.00	0.00	201	57	PEAK																																																																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5885.00	111.54	-----	-----	-----	105.03	34.34	8.94	36.77	0.00	201	57	PEAK																																																																																																																															
Avg	Blank							Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>105.30</td><td>-----</td><td>-----</td><td>-----</td><td>98.79</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>AVERAGE</td></tr></tbody></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	105.30	-----	-----	-----	98.79	34.34	8.94	36.77	0.00	201	57	AVERAGE																																																																																				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5885.00	105.30	-----	-----	-----	98.79	34.34	8.94	36.77	0.00	201	57	AVERAGE																																																																																																																															







Mode	65																																																																		
	Band Edge - L																																																																		
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																		
ANT	4+3																																																																		
Pol.	Vertical											Fundamental																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5898.25</td><td>91.24</td><td>127.81</td><td>-36.57</td><td>84.66</td><td>34.39</td><td>8.96</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr><tr><td>2</td><td>5926.25</td><td>60.61</td><td>108.20</td><td>-47.59</td><td>54.10</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>PEAK</td></tr></tbody></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5898.25	91.24	127.81	-36.57	84.66	34.39	8.96	36.77	0.00	201	57	PEAK	2	5926.25	60.61	108.20	-47.59	54.10	34.29	8.99	36.77	0.00	201	57	PEAK	Blank	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																							
1	5898.25	91.24	127.81	-36.57	84.66	34.39	8.96	36.77	0.00	201	57	PEAK																																																							
2	5926.25	60.61	108.20	-47.59	54.10	34.29	8.99	36.77	0.00	201	57	PEAK																																																							
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNI 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 65 Setting : 82 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5898.25</td><td>78.60</td><td>107.81</td><td>-29.21</td><td>72.02</td><td>34.39</td><td>8.96</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>AVERAGE</td></tr><tr><td>2</td><td>5926.75</td><td>49.27</td><td>88.20</td><td>-38.93</td><td>42.76</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>57</td><td>AVERAGE</td></tr></tbody></table>												Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5898.25	78.60	107.81	-29.21	72.02	34.39	8.96	36.77	0.00	201	57	AVERAGE	2	5926.75	49.27	88.20	-38.93	42.76	34.29	8.99	36.77	0.00	201	57	AVERAGE	Blank	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																						
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																							
1	5898.25	78.60	107.81	-29.21	72.02	34.39	8.96	36.77	0.00	201	57	AVERAGE																																																							
2	5926.75	49.27	88.20	-38.93	42.76	34.29	8.99	36.77	0.00	201	57	AVERAGE																																																							






Mode	65																																																																																																					
	Harmonic																																																																																																					
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																																																					
ANT	4+3																																																																																																					
Pol.	Horizontal							Vertical																																																																																														
Peak Avg																																																																																																						
	Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 HORIZONTAL Mode : 65 Setting : 82 <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11770.00</td><td>46.13</td><td>74.00</td><td>-27.87</td><td>50.96</td><td>38.75</td><td>12.76</td><td>57.27</td><td>0.93</td><td>-- -- Peak</td></tr><tr><td>2</td><td>17655.00</td><td>47.79</td><td>68.20</td><td>-20.41</td><td>50.46</td><td>39.35</td><td>15.73</td><td>58.68</td><td>0.93</td><td>-- -- Peak</td></tr></tbody></table>								Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11770.00	46.13	74.00	-27.87	50.96	38.75	12.76	57.27	0.93	-- -- Peak	2	17655.00	47.79	68.20	-20.41	50.46	39.35	15.73	58.68	0.93	-- -- Peak	Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 VERTICAL Mode : 65 Setting : 82 <table><thead><tr><th></th><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>11770.00</td><td>45.70</td><td>74.00</td><td>-28.30</td><td>50.57</td><td>38.73</td><td>12.75</td><td>57.28</td><td>0.93</td><td>-- -- Peak</td></tr><tr><td>2</td><td>17655.00</td><td>47.36</td><td>68.20</td><td>-20.84</td><td>50.03</td><td>39.35</td><td>15.73</td><td>58.68</td><td>0.93</td><td>-- -- Peak</td></tr></tbody></table>								Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11770.00	45.70	74.00	-28.30	50.57	38.73	12.75	57.28	0.93	-- -- Peak	2	17655.00	47.36	68.20	-20.84	50.03	39.35	15.73	58.68	0.93
	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																												
1	11770.00	46.13	74.00	-27.87	50.96	38.75	12.76	57.27	0.93	-- -- Peak																																																																																												
2	17655.00	47.79	68.20	-20.41	50.46	39.35	15.73	58.68	0.93	-- -- Peak																																																																																												
	Freq	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	11770.00	45.70	74.00	-28.30	50.57	38.73	12.75	57.28	0.93	-- -- Peak																																																																																												
2	17655.00	47.36	68.20	-20.84	50.03	39.35	15.73	58.68	0.93	-- -- Peak																																																																																												





Mode	65	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 65 Setting : 82	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 65 Setting : 82
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 65 Setting : 82	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 65 Setting : 82






Mode	66																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz																																																																																																																																									
ANT	4+3																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5644.55</td><td>48.00</td><td>68.20</td><td>-20.20</td><td>42.85</td><td>33.27</td><td>8.68</td><td>36.80</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>5650.45</td><td>46.38</td><td>68.53</td><td>-22.15</td><td>41.19</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td><td></td></tr><tr><td>3</td><td>5701.19</td><td>48.53</td><td>105.53</td><td>-57.00</td><td>42.89</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td><td></td></tr><tr><td>4</td><td>5720.36</td><td>47.55</td><td>111.62</td><td>-64.07</td><td>41.84</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td><td></td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5644.55	48.00	68.20	-20.20	42.85	33.27	8.68	36.80	0.00	178	303	PEAK		2	5650.45	46.38	68.53	-22.15	41.19	33.30	8.69	36.80	0.00	178	303	PEAK		3	5701.19	48.53	105.53	-57.00	42.89	33.70	8.74	36.80	0.00	178	303	PEAK		4	5720.36	47.55	111.62	-64.07	41.84	33.74	8.76	36.79	0.00	178	303	PEAK		 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>110.61</td><td>-----</td><td>-----</td><td>104.31</td><td>34.18</td><td>8.90</td><td>36.78</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td><td></td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	110.61	-----	-----	104.31	34.18	8.90	36.78	0.00	178	303	PEAK	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1	5644.55	48.00	68.20	-20.20	42.85	33.27	8.68	36.80	0.00	178	303	PEAK																																																																																																																														
2	5650.45	46.38	68.53	-22.15	41.19	33.30	8.69	36.80	0.00	178	303	PEAK																																																																																																																														
3	5701.19	48.53	105.53	-57.00	42.89	33.70	8.74	36.80	0.00	178	303	PEAK																																																																																																																														
4	5720.36	47.55	111.62	-64.07	41.84	33.74	8.76	36.79	0.00	178	303	PEAK																																																																																																																														
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1	5845.00	110.61	-----	-----	104.31	34.18	8.90	36.78	0.00	178	303	PEAK																																																																																																																														
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>102.69</td><td>-----</td><td>-----</td><td>96.39</td><td>34.18</td><td>8.90</td><td>36.78</td><td>0.00</td><td>178</td><td>303</td><td>AVERAGE</td><td></td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	102.69	-----	-----	96.39	34.18	8.90	36.78	0.00	178	303	AVERAGE																																																																																					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1	5845.00	102.69	-----	-----	96.39	34.18	8.90	36.78	0.00	178	303	AVERAGE																																																																																																																														





Mode	66																																																																	
	Band Edge - R																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz																																																																	
ANT	4+3																																																																	
Pol.	Horizontal						Fundamental																																																											
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>50.82</td><td>108.38</td><td>-57.56</td><td>44.30</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td></tr><tr><td>2</td><td>5949.75</td><td>51.77</td><td>108.20</td><td>-56.43</td><td>45.33</td><td>34.20</td><td>9.01</td><td>36.77</td><td>0.00</td><td>178</td><td>303</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5924.75	50.82	108.38	-57.56	44.30	34.30	8.99	36.77	0.00	178	303	PEAK	2	5949.75	51.77	108.20	-56.43	45.33	34.20	9.01	36.77	0.00	178	303	PEAK	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5924.75	50.82	108.38	-57.56	44.30	34.30	8.99	36.77	0.00	178	303	PEAK																																																						
2	5949.75	51.77	108.20	-56.43	45.33	34.20	9.01	36.77	0.00	178	303	PEAK																																																						
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5895.75</td><td>45.98</td><td>109.65</td><td>-63.67</td><td>39.41</td><td>34.38</td><td>8.96</td><td>36.77</td><td>0.00</td><td>178</td><td>303</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.00</td><td>41.07</td><td>88.20</td><td>-47.13</td><td>34.55</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>178</td><td>303</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5895.75	45.98	109.65	-63.67	39.41	34.38	8.96	36.77	0.00	178	303	AVERAGE	2	5925.00	41.07	88.20	-47.13	34.55	34.30	8.99	36.77	0.00	178	303	AVERAGE	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5895.75	45.98	109.65	-63.67	39.41	34.38	8.96	36.77	0.00	178	303	AVERAGE																																																						
2	5925.00	41.07	88.20	-47.13	34.55	34.30	8.99	36.77	0.00	178	303	AVERAGE																																																						





Mode	66																																																																																																																																				
	Band Edge - L																																																																																																																																				
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz																																																																																																																																				
ANT	4+3																																																																																																																																				
Pol.	Vertical						Fundamental																																																																																																																														
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5604.43</td><td>48.21</td><td>68.20</td><td>-19.99</td><td>43.36</td><td>33.03</td><td>8.63</td><td>36.81</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr><tr><td>2</td><td>5651.04</td><td>47.35</td><td>68.97</td><td>-21.62</td><td>42.15</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr><tr><td>3</td><td>5703.55</td><td>48.29</td><td>106.19</td><td>-57.90</td><td>42.64</td><td>33.71</td><td>8.74</td><td>36.80</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr><tr><td>4</td><td>5728.07</td><td>49.44</td><td>110.95</td><td>-61.51</td><td>43.73</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5604.43	48.21	68.20	-19.99	43.36	33.03	8.63	36.81	0.00	191	48	PEAK	2	5651.04	47.35	68.97	-21.62	42.15	33.31	8.69	36.80	0.00	191	48	PEAK	3	5703.55	48.29	106.19	-57.90	42.64	33.71	8.74	36.80	0.00	191	48	PEAK	4	5728.07	49.44	110.95	-61.51	43.73	33.74	8.76	36.79	0.00	191	48	PEAK	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>111.39</td><td>-----</td><td>-----</td><td>105.07</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	111.39	-----	-----	105.07	34.20	8.90	36.78	0.00	191	48	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5604.43	48.21	68.20	-19.99	43.36	33.03	8.63	36.81	0.00	191	48	PEAK																																																																																																																									
2	5651.04	47.35	68.97	-21.62	42.15	33.31	8.69	36.80	0.00	191	48	PEAK																																																																																																																									
3	5703.55	48.29	106.19	-57.90	42.64	33.71	8.74	36.80	0.00	191	48	PEAK																																																																																																																									
4	5728.07	49.44	110.95	-61.51	43.73	33.74	8.76	36.79	0.00	191	48	PEAK																																																																																																																									
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5845.00	111.39	-----	-----	105.07	34.20	8.90	36.78	0.00	191	48	PEAK																																																																																																																									
Avg	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4)_indoor Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>103.52</td><td>-----</td><td>-----</td><td>97.20</td><td>34.20</td><td>8.90</td><td>36.78</td><td>0.00</td><td>191</td><td>48</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	103.52	-----	-----	97.20	34.20	8.90	36.78	0.00	191	48	AVERAGE																																																																																
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5845.00	103.52	-----	-----	97.20	34.20	8.90	36.78	0.00	191	48	AVERAGE																																																																																																																									







Mode	66																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz																																																										
ANT	4+3																																																										
Pol.	Vertical						Fundamental																																																				
Peak							Blank																																																				
	Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.50</td><td>49.86</td><td>108.57</td><td>-58.71</td><td>43.34</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr><tr><td>2</td><td>5949.75</td><td>50.42</td><td>108.20</td><td>-57.78</td><td>43.98</td><td>34.20</td><td>9.01</td><td>36.77</td><td>0.00</td><td>191</td><td>48</td><td>PEAK</td></tr></tbody></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5924.50	49.86	108.57	-58.71	43.34	34.30	8.99	36.77	0.00	191	48	PEAK	2	5949.75	50.42	108.20	-57.78	43.98
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																															
1	5924.50	49.86	108.57	-58.71	43.34	34.30	8.99	36.77	0.00	191	48	PEAK																																															
2	5949.75	50.42	108.20	-57.78	43.98	34.20	9.01	36.77	0.00	191	48	PEAK																																															
Avg							Blank																																																				
Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 66 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5896.50</td><td>47.69</td><td>109.10</td><td>-61.41</td><td>41.11</td><td>34.39</td><td>8.96</td><td>36.77</td><td>0.00</td><td>191</td><td>48</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.50</td><td>41.11</td><td>88.20</td><td>-47.09</td><td>34.59</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>191</td><td>48</td><td>AVERAGE</td></tr></tbody></table>													Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5896.50	47.69	109.10	-61.41	41.11	34.39	8.96	36.77	0.00	191	48	AVERAGE	2	5925.50	41.11	88.20	-47.09	34.59	34.30
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																														
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																															
1	5896.50	47.69	109.10	-61.41	41.11	34.39	8.96	36.77	0.00	191	48	AVERAGE																																															
2	5925.50	41.11	88.20	-47.09	34.59	34.30	8.99	36.77	0.00	191	48	AVERAGE																																															






Mode	66																																																																																																															
	Harmonic																																																																																																															
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz																																																																																																															
ANT	4+3																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 HORIZONTAL Mode : 66 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11690.00</td><td>46.72</td><td>74.00</td><td>-27.28</td><td>51.80</td><td>38.60</td><td>12.71</td><td>57.32</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17535.00</td><td>46.22</td><td>68.20</td><td>-21.98</td><td>49.80</td><td>38.80</td><td>15.66</td><td>58.97</td><td>0.93</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11690.00	46.72	74.00	-27.28	51.80	38.60	12.71	57.32	0.93	--	Peak	2	17535.00	46.22	68.20	-21.98	49.80	38.80	15.66	58.97	0.93	--	Peak	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 VERTICAL Mode : 66 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11690.00</td><td>46.96</td><td>74.00</td><td>-27.04</td><td>52.04</td><td>38.60</td><td>12.71</td><td>57.32</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17535.00</td><td>45.31</td><td>68.20</td><td>-22.89</td><td>49.26</td><td>38.58</td><td>15.63</td><td>59.09</td><td>0.93</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11690.00	46.96	74.00	-27.04	52.04	38.60	12.71	57.32	0.93	--	Peak	2	17535.00	45.31	68.20	-22.89	49.26	38.58	15.63	59.09	0.93	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11690.00	46.72	74.00	-27.28	51.80	38.60	12.71	57.32	0.93	--	Peak																																																																																																					
2	17535.00	46.22	68.20	-21.98	49.80	38.80	15.66	58.97	0.93	--	Peak																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11690.00	46.96	74.00	-27.04	52.04	38.60	12.71	57.32	0.93	--	Peak																																																																																																					
2	17535.00	45.31	68.20	-22.89	49.26	38.58	15.63	59.09	0.93	--	Peak																																																																																																					





Mode	66	
	Harmonic	
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Full RU_5845MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 66 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 66 Setting : 84
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 66 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 66 Setting : 84






Mode	67																																																																																																																																
	Band Edge - L																																																																																																																																
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_26/0RU_5845MHz																																																																																																																																
ANT	4+3																																																																																																																																
Pol.	Horizontal						Fundamental																																																																																																																										
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5602.36</td><td>47.87</td><td>68.20</td><td>-20.33</td><td>43.04</td><td>33.01</td><td>8.63</td><td>36.81</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td></tr><tr><td>2</td><td>5658.45</td><td>46.57</td><td>68.53</td><td>-21.96</td><td>41.38</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td></tr><tr><td>3</td><td>5701.19</td><td>47.53</td><td>105.53</td><td>-58.00</td><td>41.09</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td></tr><tr><td>4</td><td>5728.07</td><td>47.52</td><td>110.95</td><td>-63.43</td><td>41.81</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5602.36	47.87	68.20	-20.33	43.04	33.01	8.63	36.81	0.00	200	292	Peak	2	5658.45	46.57	68.53	-21.96	41.38	33.30	8.69	36.80	0.00	200	292	Peak	3	5701.19	47.53	105.53	-58.00	41.09	33.70	8.74	36.80	0.00	200	292	Peak	4	5728.07	47.52	110.95	-63.43	41.81	33.74	8.76	36.79	0.00	200	292	Peak	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>113.62</td><td>-----</td><td>-----</td><td>107.34</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	113.62	-----	-----	107.34	34.17	8.89	36.78	0.00	200	292	Peak
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5602.36	47.87	68.20	-20.33	43.04	33.01	8.63	36.81	0.00	200	292	Peak																																																																																																																					
2	5658.45	46.57	68.53	-21.96	41.38	33.30	8.69	36.80	0.00	200	292	Peak																																																																																																																					
3	5701.19	47.53	105.53	-58.00	41.09	33.70	8.74	36.80	0.00	200	292	Peak																																																																																																																					
4	5728.07	47.52	110.95	-63.43	41.81	33.74	8.76	36.79	0.00	200	292	Peak																																																																																																																					
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	113.62	-----	-----	107.34	34.17	8.89	36.78	0.00	200	292	Peak																																																																																																																					
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:0.620kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>107.60</td><td>-----</td><td>-----</td><td>101.32</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>200</td><td>292</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	107.60	-----	-----	101.32	34.17	8.89	36.78	0.00	200	292	AVERAGE																																																																														
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	107.60	-----	-----	101.32	34.17	8.89	36.78	0.00	200	292	AVERAGE																																																																																																																					





Mode	67																																																									
	Band Edge - R																																																									
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_26/0RU_5845MHz																																																									
ANT	4+3																																																									
Pol.	Horizontal	Fundamental																																																								
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.50</td><td>46.44</td><td>108.57</td><td>-62.13</td><td>39.92</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td><td></td></tr><tr><td>2</td><td>5908.25</td><td>48.73</td><td>108.20</td><td>-59.47</td><td>42.24</td><td>34.20</td><td>9.05</td><td>36.76</td><td>0.00</td><td>200</td><td>292</td><td>Peak</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.50	46.44	108.57	-62.13	39.92	34.30	8.99	36.77	0.00	200	292	Peak		2	5908.25	48.73	108.20	-59.47	42.24	34.20	9.05	36.76	0.00	200	292	Peak		Blank
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																												
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5924.50	46.44	108.57	-62.13	39.92	34.30	8.99	36.77	0.00	200	292	Peak																																														
2	5908.25	48.73	108.20	-59.47	42.24	34.20	9.05	36.76	0.00	200	292	Peak																																														
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.620kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>38.73</td><td>88.20</td><td>-49.47</td><td>32.21</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>292</td><td>Average</td><td></td></tr><tr><td>2</td><td>5928.50</td><td>39.07</td><td>88.20</td><td>-49.13</td><td>32.56</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>292</td><td>Average</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	38.73	88.20	-49.47	32.21	34.30	8.99	36.77	0.00	200	292	Average		2	5928.50	39.07	88.20	-49.13	32.56	34.29	8.99	36.77	0.00	200	292	Average		Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5925.00	38.73	88.20	-49.47	32.21	34.30	8.99	36.77	0.00	200	292	Average																																														
2	5928.50	39.07	88.20	-49.13	32.56	34.29	8.99	36.77	0.00	200	292	Average																																														






Mode	67																																																																																																																																
	Band Edge - L																																																																																																																																
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_26/0RU_5845MHz																																																																																																																																
ANT	4+3																																																																																																																																
Pol.	Vertical						Fundamental																																																																																																																										
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5644.84</td><td>49.22</td><td>68.20</td><td>-18.98</td><td>44.07</td><td>33.27</td><td>8.68</td><td>36.80</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr><tr><td>2</td><td>5650.45</td><td>47.93</td><td>68.53</td><td>-20.60</td><td>42.74</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr><tr><td>3</td><td>5706.50</td><td>48.97</td><td>107.02</td><td>-58.05</td><td>43.31</td><td>33.71</td><td>8.75</td><td>36.80</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr><tr><td>4</td><td>5720.36</td><td>48.30</td><td>111.62</td><td>-63.32</td><td>42.59</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5644.84	49.22	68.20	-18.98	44.07	33.27	8.68	36.80	0.00	188	76	Peak	2	5650.45	47.93	68.53	-20.60	42.74	33.30	8.69	36.80	0.00	188	76	Peak	3	5706.50	48.97	107.02	-58.05	43.31	33.71	8.75	36.80	0.00	188	76	Peak	4	5720.36	48.30	111.62	-63.32	42.59	33.74	8.76	36.79	0.00	188	76	Peak	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>113.73</td><td>-----</td><td>-----</td><td>107.45</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	113.73	-----	-----	107.45	34.17	8.89	36.78	0.00	188	76	Peak
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5644.84	49.22	68.20	-18.98	44.07	33.27	8.68	36.80	0.00	188	76	Peak																																																																																																																					
2	5650.45	47.93	68.53	-20.60	42.74	33.30	8.69	36.80	0.00	188	76	Peak																																																																																																																					
3	5706.50	48.97	107.02	-58.05	43.31	33.71	8.75	36.80	0.00	188	76	Peak																																																																																																																					
4	5720.36	48.30	111.62	-63.32	42.59	33.74	8.76	36.79	0.00	188	76	Peak																																																																																																																					
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	113.73	-----	-----	107.45	34.17	8.89	36.78	0.00	188	76	Peak																																																																																																																					
Avg	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4)_indoor Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:0.620kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>108.58</td><td>-----</td><td>-----</td><td>102.30</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>188</td><td>76</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	108.58	-----	-----	102.30	34.17	8.89	36.78	0.00	188	76	AVERAGE																																																																														
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	108.58	-----	-----	102.30	34.17	8.89	36.78	0.00	188	76	AVERAGE																																																																																																																					





Mode	67																																																																	
	Band Edge - R																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_26/0RU_5845MHz																																																																	
ANT	4+3																																																																	
Pol.	Vertical						Fundamental																																																											
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>48.08</td><td>108.38</td><td>-60.30</td><td>41.56</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr><tr><td>2</td><td>5952.25</td><td>49.85</td><td>108.20</td><td>-58.35</td><td>43.40</td><td>34.20</td><td>9.02</td><td>36.77</td><td>0.00</td><td>188</td><td>76</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB/m	dB	dB	dB	cm	deg		1	5924.75	48.08	108.38	-60.30	41.56	34.30	8.99	36.77	0.00	188	76	Peak	2	5952.25	49.85	108.20	-58.35	43.40	34.20	9.02	36.77	0.00	188	76	Peak	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB/m	dB	dB	dB	cm	deg																																																						
1	5924.75	48.08	108.38	-60.30	41.56	34.30	8.99	36.77	0.00	188	76	Peak																																																						
2	5952.25	49.85	108.20	-58.35	43.40	34.20	9.02	36.77	0.00	188	76	Peak																																																						
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.620kHz SMT:Auto Detector : PEAK Mode : 67 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>39.44</td><td>88.38</td><td>-48.94</td><td>32.92</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>188</td><td>76</td><td>Average</td></tr><tr><td>2</td><td>5938.75</td><td>39.60</td><td>88.20</td><td>-48.60</td><td>33.12</td><td>34.25</td><td>9.00</td><td>36.77</td><td>0.00</td><td>188</td><td>76</td><td>Average</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB/m	dB	dB	dB	cm	deg		1	5924.75	39.44	88.38	-48.94	32.92	34.30	8.99	36.77	0.00	188	76	Average	2	5938.75	39.60	88.20	-48.60	33.12	34.25	9.00	36.77	0.00	188	76	Average	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB/m	dB	dB	dB	cm	deg																																																						
1	5924.75	39.44	88.38	-48.94	32.92	34.30	8.99	36.77	0.00	188	76	Average																																																						
2	5938.75	39.60	88.20	-48.60	33.12	34.25	9.00	36.77	0.00	188	76	Average																																																						






Mode	68																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_52/37RU_5845MHz																																																																																																																								
ANT	4+3																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5638.35</td><td>47.54</td><td>68.20</td><td>-20.66</td><td>42.44</td><td>33.23</td><td>8.67</td><td>36.80</td><td>0.00</td><td>173 32 Peak</td></tr><tr><td>2 5651.04</td><td>48.90</td><td>68.97</td><td>-20.07</td><td>43.70</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>173 32 Peak</td></tr><tr><td>3 5700.89</td><td>47.42</td><td>105.45</td><td>-58.03</td><td>41.78</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>173 32 Peak</td></tr><tr><td>4 5720.07</td><td>47.32</td><td>110.95</td><td>-63.63</td><td>41.61</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>173 32 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5638.35	47.54	68.20	-20.66	42.44	33.23	8.67	36.80	0.00	173 32 Peak	2 5651.04	48.90	68.97	-20.07	43.70	33.31	8.69	36.80	0.00	173 32 Peak	3 5700.89	47.42	105.45	-58.03	41.78	33.70	8.74	36.80	0.00	173 32 Peak	4 5720.07	47.32	110.95	-63.63	41.61	33.74	8.76	36.79	0.00	173 32 Peak	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5845.00</td><td>111.64</td><td>-----</td><td>-----</td><td>105.36</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>173 32 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5845.00	111.64	-----	-----	105.36	34.17	8.89	36.78	0.00	173 32 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5638.35	47.54	68.20	-20.66	42.44	33.23	8.67	36.80	0.00	173 32 Peak																																																																																																																
2 5651.04	48.90	68.97	-20.07	43.70	33.31	8.69	36.80	0.00	173 32 Peak																																																																																																																
3 5700.89	47.42	105.45	-58.03	41.78	33.70	8.74	36.80	0.00	173 32 Peak																																																																																																																
4 5720.07	47.32	110.95	-63.63	41.61	33.74	8.76	36.79	0.00	173 32 Peak																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5845.00	111.64	-----	-----	105.36	34.17	8.89	36.78	0.00	173 32 Peak																																																																																																																
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:0.600kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5845.00</td><td>106.04</td><td>-----</td><td>-----</td><td>99.76</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>173 32 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5845.00	106.04	-----	-----	99.76	34.17	8.89	36.78	0.00	173 32 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5845.00	106.04	-----	-----	99.76	34.17	8.89	36.78	0.00	173 32 AVERAGE																																																																																																																





Mode	68																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_52/37RU_5845MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.00</td><td>47.42</td><td>108.93</td><td>-61.51</td><td>40.90</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>173</td><td>32</td><td>Peak</td></tr><tr><td>2</td><td>5928.50</td><td>49.70</td><td>108.20</td><td>-58.50</td><td>43.19</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>173</td><td>32</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.00	47.42	108.93	-61.51	40.90	34.30	8.99	36.77	0.00	173	32	Peak	2	5928.50	49.70	108.20	-58.50	43.19	34.29	8.99	36.77	0.00	173	32	Peak	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.00	47.42	108.93	-61.51	40.90	34.30	8.99	36.77	0.00	173	32	Peak																																												
2	5928.50	49.70	108.20	-58.50	43.19	34.29	8.99	36.77	0.00	173	32	Peak																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.600kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>39.18</td><td>88.20</td><td>-49.02</td><td>32.66</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>173</td><td>32</td><td>Average</td></tr><tr><td>2</td><td>5928.25</td><td>39.45</td><td>88.20</td><td>-48.75</td><td>32.94</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>173</td><td>32</td><td>Average</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	39.18	88.20	-49.02	32.66	34.30	8.99	36.77	0.00	173	32	Average	2	5928.25	39.45	88.20	-48.75	32.94	34.29	8.99	36.77	0.00	173	32	Average	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5925.00	39.18	88.20	-49.02	32.66	34.30	8.99	36.77	0.00	173	32	Average																																												
2	5928.25	39.45	88.20	-48.75	32.94	34.29	8.99	36.77	0.00	173	32	Average																																												






Mode	68																																																																																																																																
	Band Edge - L																																																																																																																																
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_52/37RU_5845MHz																																																																																																																																
ANT	4+3																																																																																																																																
Pol.	Vertical						Fundamental																																																																																																																										
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5646.32</td><td>47.48</td><td>68.20</td><td>-20.72</td><td>42.32</td><td>33.28</td><td>8.68</td><td>36.80</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr><tr><td>2</td><td>5650.45</td><td>46.02</td><td>68.53</td><td>-22.51</td><td>40.83</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr><tr><td>3</td><td>5700.30</td><td>47.76</td><td>105.28</td><td>-57.52</td><td>42.12</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr><tr><td>4</td><td>5720.07</td><td>46.83</td><td>110.95</td><td>-64.12</td><td>41.12</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5646.32	47.48	68.20	-20.72	42.32	33.28	8.68	36.80	0.00	175	77	Peak	2	5650.45	46.02	68.53	-22.51	40.83	33.30	8.69	36.80	0.00	175	77	Peak	3	5700.30	47.76	105.28	-57.52	42.12	33.70	8.74	36.80	0.00	175	77	Peak	4	5720.07	46.83	110.95	-64.12	41.12	33.74	8.76	36.79	0.00	175	77	Peak	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>113.75</td><td>-----</td><td>-----</td><td>107.45</td><td>34.18</td><td>8.90</td><td>36.78</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	113.75	-----	-----	107.45	34.18	8.90	36.78	0.00	175	77	Peak
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5646.32	47.48	68.20	-20.72	42.32	33.28	8.68	36.80	0.00	175	77	Peak																																																																																																																					
2	5650.45	46.02	68.53	-22.51	40.83	33.30	8.69	36.80	0.00	175	77	Peak																																																																																																																					
3	5700.30	47.76	105.28	-57.52	42.12	33.70	8.74	36.80	0.00	175	77	Peak																																																																																																																					
4	5720.07	46.83	110.95	-64.12	41.12	33.74	8.76	36.79	0.00	175	77	Peak																																																																																																																					
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	113.75	-----	-----	107.45	34.18	8.90	36.78	0.00	175	77	Peak																																																																																																																					
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBN:0.600kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>106.83</td><td>-----</td><td>-----</td><td>100.55</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>175</td><td>77</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	106.83	-----	-----	100.55	34.17	8.89	36.78	0.00	175	77	AVERAGE																																																																														
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	106.83	-----	-----	100.55	34.17	8.89	36.78	0.00	175	77	AVERAGE																																																																																																																					





Mode	68																																																																			
	Band Edge - R																																																																			
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_52/37RU_5845MHz																																																																			
ANT	4+3																																																																			
Pol.	Vertical						Fundamental																																																													
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.75</td><td>52.78</td><td>109.11</td><td>-56.33</td><td></td><td>46.25</td><td>34.31</td><td>8.99</td><td>36.77</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr><tr><td>2</td><td>5938.50</td><td>50.22</td><td>108.20</td><td>-57.98</td><td></td><td>43.74</td><td>34.25</td><td>9.00</td><td>36.77</td><td>0.00</td><td>175</td><td>77</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5923.75	52.78	109.11	-56.33		46.25	34.31	8.99	36.77	0.00	175	77	Peak	2	5938.50	50.22	108.20	-57.98		43.74	34.25	9.00	36.77	0.00	175	77	Peak	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																								
1	5923.75	52.78	109.11	-56.33		46.25	34.31	8.99	36.77	0.00	175	77	Peak																																																							
2	5938.50	50.22	108.20	-57.98		43.74	34.25	9.00	36.77	0.00	175	77	Peak																																																							
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.600kHz SMT:Auto Detector : PEAK Mode : 68 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>39.47</td><td>88.20</td><td>-48.73</td><td></td><td>32.95</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>175</td><td>77</td><td>Average</td></tr><tr><td>2</td><td>5926.00</td><td>39.67</td><td>88.20</td><td>-48.53</td><td></td><td>33.15</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>175</td><td>77</td><td>Average</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	39.47	88.20	-48.73		32.95	34.30	8.99	36.77	0.00	175	77	Average	2	5926.00	39.67	88.20	-48.53		33.15	34.30	8.99	36.77	0.00	175	77	Average	Blank					
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																								
1	5925.00	39.47	88.20	-48.73		32.95	34.30	8.99	36.77	0.00	175	77	Average																																																							
2	5926.00	39.67	88.20	-48.53		33.15	34.30	8.99	36.77	0.00	175	77	Average																																																							






Mode	69																																																																																																																																
	Band Edge - L																																																																																																																																
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_106/53RU_5845MHz																																																																																																																																
ANT	4+3																																																																																																																																
Pol.	Horizontal						Fundamental																																																																																																																										
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5607.38</td><td>47.60</td><td>68.20</td><td>-20.60</td><td>42.73</td><td>33.04</td><td>8.64</td><td>36.81</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr><tr><td>2</td><td>5651.04</td><td>47.79</td><td>68.97</td><td>-21.18</td><td>42.59</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr><tr><td>3</td><td>5701.78</td><td>48.16</td><td>105.70</td><td>-57.54</td><td>42.52</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr><tr><td>4</td><td>5728.07</td><td>45.55</td><td>110.95</td><td>-65.40</td><td>39.84</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5607.38	47.60	68.20	-20.60	42.73	33.04	8.64	36.81	0.00	172	285	Peak	2	5651.04	47.79	68.97	-21.18	42.59	33.31	8.69	36.80	0.00	172	285	Peak	3	5701.78	48.16	105.70	-57.54	42.52	33.70	8.74	36.80	0.00	172	285	Peak	4	5728.07	45.55	110.95	-65.40	39.84	33.74	8.76	36.79	0.00	172	285	Peak	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>110.52</td><td>-----</td><td>-----</td><td>104.24</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	110.52	-----	-----	104.24	34.17	8.89	36.78	0.00	172	285	Peak
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5607.38	47.60	68.20	-20.60	42.73	33.04	8.64	36.81	0.00	172	285	Peak																																																																																																																					
2	5651.04	47.79	68.97	-21.18	42.59	33.31	8.69	36.80	0.00	172	285	Peak																																																																																																																					
3	5701.78	48.16	105.70	-57.54	42.52	33.70	8.74	36.80	0.00	172	285	Peak																																																																																																																					
4	5728.07	45.55	110.95	-65.40	39.84	33.74	8.76	36.79	0.00	172	285	Peak																																																																																																																					
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	110.52	-----	-----	104.24	34.17	8.89	36.78	0.00	172	285	Peak																																																																																																																					
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:0.828kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5845.00</td><td>102.67</td><td>-----</td><td>-----</td><td>96.37</td><td>34.18</td><td>8.90</td><td>36.78</td><td>0.00</td><td>172</td><td>285</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5845.00	102.67	-----	-----	96.37	34.18	8.90	36.78	0.00	172	285	AVERAGE																																																																														
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5845.00	102.67	-----	-----	96.37	34.18	8.90	36.78	0.00	172	285	AVERAGE																																																																																																																					





Mode	69																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_106/53RU_5845MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>48.47</td><td>108.38</td><td>-59.91</td><td>41.95</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr><tr><td>2</td><td>5999.50</td><td>48.80</td><td>108.20</td><td>-59.40</td><td>42.29</td><td>34.20</td><td>9.07</td><td>36.76</td><td>0.00</td><td>172</td><td>285</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.75	48.47	108.38	-59.91	41.95	34.30	8.99	36.77	0.00	172	285	Peak	2	5999.50	48.80	108.20	-59.40	42.29	34.20	9.07	36.76	0.00	172	285	Peak	Blank
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.75	48.47	108.38	-59.91	41.95	34.30	8.99	36.77	0.00	172	285	Peak																																												
2	5999.50	48.80	108.20	-59.40	42.29	34.20	9.07	36.76	0.00	172	285	Peak																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.020kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>38.92</td><td>88.20</td><td>-49.28</td><td>32.40</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>172</td><td>285</td><td>Average</td></tr><tr><td>2</td><td>5928.75</td><td>39.13</td><td>88.20</td><td>-49.07</td><td>32.63</td><td>34.28</td><td>8.99</td><td>36.77</td><td>0.00</td><td>172</td><td>285</td><td>Average</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	38.92	88.20	-49.28	32.40	34.30	8.99	36.77	0.00	172	285	Average	2	5928.75	39.13	88.20	-49.07	32.63	34.28	8.99	36.77	0.00	172	285	Average	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5925.00	38.92	88.20	-49.28	32.40	34.30	8.99	36.77	0.00	172	285	Average																																												
2	5928.75	39.13	88.20	-49.07	32.63	34.28	8.99	36.77	0.00	172	285	Average																																												






Mode	69																																																																																																																																								
	Band Edge - L																																																																																																																																								
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_106/53RU_5845MHz																																																																																																																																								
ANT	4+3																																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																																		
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5637.76</td><td>47.62</td><td>68.20</td><td>-20.58</td><td>42.52</td><td>33.23</td><td>8.67</td><td>36.80</td><td>0.00</td><td>200</td><td>63 Peak</td></tr><tr><td>2</td><td>5650.74</td><td>48.68</td><td>68.75</td><td>-20.07</td><td>43.48</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>200</td><td>63 Peak</td></tr><tr><td>3</td><td>5700.30</td><td>49.84</td><td>105.28</td><td>-55.44</td><td>44.20</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>200</td><td>63 Peak</td></tr><tr><td>4</td><td>5720.07</td><td>46.67</td><td>110.95</td><td>-64.28</td><td>40.96</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>200</td><td>63 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5637.76	47.62	68.20	-20.58	42.52	33.23	8.67	36.80	0.00	200	63 Peak	2	5650.74	48.68	68.75	-20.07	43.48	33.31	8.69	36.80	0.00	200	63 Peak	3	5700.30	49.84	105.28	-55.44	44.20	33.70	8.74	36.80	0.00	200	63 Peak	4	5720.07	46.67	110.95	-64.28	40.96	33.74	8.76	36.79	0.00	200	63 Peak	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4)_indoor Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>111.69</td><td>-----</td><td>-----</td><td>105.39</td><td>34.18</td><td>8.90</td><td>36.78</td><td>0.00</td><td>200</td><td>63 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	111.69	-----	-----	105.39	34.18	8.90	36.78	0.00	200	63 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5637.76	47.62	68.20	-20.58	42.52	33.23	8.67	36.80	0.00	200	63 Peak																																																																																																																														
2	5650.74	48.68	68.75	-20.07	43.48	33.31	8.69	36.80	0.00	200	63 Peak																																																																																																																														
3	5700.30	49.84	105.28	-55.44	44.20	33.70	8.74	36.80	0.00	200	63 Peak																																																																																																																														
4	5720.07	46.67	110.95	-64.28	40.96	33.74	8.76	36.79	0.00	200	63 Peak																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5845.00	111.69	-----	-----	105.39	34.18	8.90	36.78	0.00	200	63 Peak																																																																																																																														
Avg	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4)_indoor Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 VERTICAL : RBW:1000.000kHz VBN:0.828kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>103.57</td><td>-----</td><td>-----</td><td>97.29</td><td>34.17</td><td>8.89</td><td>36.78</td><td>0.00</td><td>200</td><td>63 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	103.57	-----	-----	97.29	34.17	8.89	36.78	0.00	200	63 AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5845.00	103.57	-----	-----	97.29	34.17	8.89	36.78	0.00	200	63 AVERAGE																																																																																																																														





Mode	69																																																							
	Band Edge - L																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH169_Partial_106/53RU_5845MHz																																																							
ANT	4+3																																																							
Pol.	Vertical	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.75</td><td>47.67</td><td>108.38</td><td>-60.71</td><td>41.15</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>63</td><td>Peak</td></tr><tr><td>2</td><td>5945.00</td><td>49.23</td><td>108.20</td><td>-58.97</td><td>42.77</td><td>34.22</td><td>9.01</td><td>36.77</td><td>0.00</td><td>200</td><td>63</td><td>Peak</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.75	47.67	108.38	-60.71	41.15	34.30	8.99	36.77	0.00	200	63	Peak	2	5945.00	49.23	108.20	-58.97	42.77	34.22	9.01	36.77	0.00	200	63	Peak	Blank
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.75	47.67	108.38	-60.71	41.15	34.30	8.99	36.77	0.00	200	63	Peak																																												
2	5945.00	49.23	108.20	-58.97	42.77	34.22	9.01	36.77	0.00	200	63	Peak																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.020kHz SMT:Auto Detector : PEAK Mode : 69 Setting : 80 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5925.00</td><td>39.54</td><td>88.20</td><td>-48.66</td><td>33.02</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>63</td><td>Average</td></tr><tr><td>2</td><td>5928.75</td><td>39.77</td><td>88.20</td><td>-48.43</td><td>33.27</td><td>34.28</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>63</td><td>Average</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	39.54	88.20	-48.66	33.02	34.30	8.99	36.77	0.00	200	63	Average	2	5928.75	39.77	88.20	-48.43	33.27	34.28	8.99	36.77	0.00	200	63	Average	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5925.00	39.54	88.20	-48.66	33.02	34.30	8.99	36.77	0.00	200	63	Average																																												
2	5928.75	39.77	88.20	-48.43	33.27	34.28	8.99	36.77	0.00	200	63	Average																																												






Mode	70																																																																																																																																											
	Band Edge - L																																																																																																																																											
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz																																																																																																																																											
ANT	4+3																																																																																																																																											
Pol.	Horizontal							Fundamental																																																																																																																																				
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5632.45</td><td>46.37</td><td>68.20</td><td>-21.83</td><td>41.31</td><td>33.19</td><td>8.67</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr><tr><td>2</td><td>5658.15</td><td>46.29</td><td>68.31</td><td>-22.02</td><td>41.10</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr><tr><td>3</td><td>5701.48</td><td>47.48</td><td>105.62</td><td>-58.14</td><td>41.84</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr><tr><td>4</td><td>5728.07</td><td>46.08</td><td>110.95</td><td>-64.87</td><td>40.37</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5632.45	46.37	68.20	-21.83	41.31	33.19	8.67	36.80	0.00	0.00	201	74	PEAK	2	5658.15	46.29	68.31	-22.02	41.10	33.30	8.69	36.80	0.00	0.00	201	74	PEAK	3	5701.48	47.48	105.62	-58.14	41.84	33.70	8.74	36.80	0.00	0.00	201	74	PEAK	4	5728.07	46.08	110.95	-64.87	40.37	33.74	8.76	36.79	0.00	0.00	201	74	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>101.71</td><td>-----</td><td>-----</td><td>95.31</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5865.00	101.71	-----	-----	95.31	34.26	8.92	36.78	0.00	0.00	201	74	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5632.45	46.37	68.20	-21.83	41.31	33.19	8.67	36.80	0.00	0.00	201	74	PEAK																																																																																																																															
2	5658.15	46.29	68.31	-22.02	41.10	33.30	8.69	36.80	0.00	0.00	201	74	PEAK																																																																																																																															
3	5701.48	47.48	105.62	-58.14	41.84	33.70	8.74	36.80	0.00	0.00	201	74	PEAK																																																																																																																															
4	5728.07	46.08	110.95	-64.87	40.37	33.74	8.76	36.79	0.00	0.00	201	74	PEAK																																																																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5865.00	101.71	-----	-----	95.31	34.26	8.92	36.78	0.00	0.00	201	74	PEAK																																																																																																																															
Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>95.58</td><td>-----</td><td>-----</td><td>89.18</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>0.00</td><td>201</td><td>74</td><td>AVERAGE</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5865.00	95.58	-----	-----	89.18	34.26	8.92	36.78	0.00	0.00	201	74	AVERAGE																																																																																											
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																															
1	5865.00	95.58	-----	-----	89.18	34.26	8.92	36.78	0.00	0.00	201	74	AVERAGE																																																																																																																															





Mode	70																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>49.52</td><td>108.38</td><td>-58.86</td><td>43.00</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr><tr><td>2</td><td>5926.50</td><td>50.31</td><td>108.20</td><td>-57.89</td><td>43.00</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>74</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.75	49.52	108.38	-58.86	43.00	34.30	8.99	36.77	0.00	201	74	PEAK	2	5926.50	50.31	108.20	-57.89	43.00	34.29	8.99	36.77	0.00	201	74	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.75	49.52	108.38	-58.86	43.00	34.30	8.99	36.77	0.00	201	74	PEAK																																												
2	5926.50	50.31	108.20	-57.89	43.00	34.29	8.99	36.77	0.00	201	74	PEAK																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.00</td><td>40.74</td><td>88.93</td><td>-48.19</td><td>34.22</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>74</td><td>AVERAGE</td></tr><tr><td>2</td><td>5926.50</td><td>40.25</td><td>88.20</td><td>-47.95</td><td>33.74</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>201</td><td>74</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.00	40.74	88.93	-48.19	34.22	34.30	8.99	36.77	0.00	201	74	AVERAGE	2	5926.50	40.25	88.20	-47.95	33.74	34.29	8.99	36.77	0.00	201	74	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.00	40.74	88.93	-48.19	34.22	34.30	8.99	36.77	0.00	201	74	AVERAGE																																												
2	5926.50	40.25	88.20	-47.95	33.74	34.29	8.99	36.77	0.00	201	74	AVERAGE																																												





Mode	70																																																																																																																																				
	Band Edge - L																																																																																																																																				
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz																																																																																																																																				
ANT	4+3																																																																																																																																				
Pol.	Vertical						Fundamental																																																																																																																														
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5629.21</td><td>47.79</td><td>68.20</td><td>-20.41</td><td>42.75</td><td>33.18</td><td>8.66</td><td>36.80</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr><tr><td>2</td><td>5658.15</td><td>45.84</td><td>68.31</td><td>-22.47</td><td>40.65</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr><tr><td>3</td><td>5700.01</td><td>47.78</td><td>105.20</td><td>-57.42</td><td>42.14</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr><tr><td>4</td><td>5728.07</td><td>46.99</td><td>110.95</td><td>-63.96</td><td>41.28</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5629.21	47.79	68.20	-20.41	42.75	33.18	8.66	36.80	0.00	189	36	PEAK	2	5658.15	45.84	68.31	-22.47	40.65	33.30	8.69	36.80	0.00	189	36	PEAK	3	5700.01	47.78	105.20	-57.42	42.14	33.70	8.74	36.80	0.00	189	36	PEAK	4	5728.07	46.99	110.95	-63.96	41.28	33.74	8.76	36.79	0.00	189	36	PEAK	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5865.00</td><td>108.93</td><td>-----</td><td>-----</td><td>102.53</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5865.00	108.93	-----	-----	102.53	34.26	8.92	36.78	0.00	189	36	PEAK
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5629.21	47.79	68.20	-20.41	42.75	33.18	8.66	36.80	0.00	189	36	PEAK																																																																																																																									
2	5658.15	45.84	68.31	-22.47	40.65	33.30	8.69	36.80	0.00	189	36	PEAK																																																																																																																									
3	5700.01	47.78	105.20	-57.42	42.14	33.70	8.74	36.80	0.00	189	36	PEAK																																																																																																																									
4	5728.07	46.99	110.95	-63.96	41.28	33.74	8.76	36.79	0.00	189	36	PEAK																																																																																																																									
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5865.00	108.93	-----	-----	102.53	34.26	8.92	36.78	0.00	189	36	PEAK																																																																																																																									
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector: PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5865.00</td><td>103.17</td><td>-----</td><td>-----</td><td>96.77</td><td>34.26</td><td>8.92</td><td>36.78</td><td>0.00</td><td>189</td><td>36</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5865.00	103.17	-----	-----	96.77	34.26	8.92	36.78	0.00	189	36	AVERAGE																																																																																
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																									
1	5865.00	103.17	-----	-----	96.77	34.26	8.92	36.78	0.00	189	36	AVERAGE																																																																																																																									







Mode	70																																																																	
	Band Edge - R																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz																																																																	
ANT	4+3																																																																	
Pol.	Vertical						Fundamental																																																											
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5921.50</td><td>57.88</td><td>110.76</td><td>-52.88</td><td>51.36</td><td>34.31</td><td>8.98</td><td>36.77</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr><tr><td>2</td><td>5928.50</td><td>56.12</td><td>108.20</td><td>-52.08</td><td>49.61</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>189</td><td>36</td><td>PEAK</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5921.50	57.88	110.76	-52.88	51.36	34.31	8.98	36.77	0.00	189	36	PEAK	2	5928.50	56.12	108.20	-52.08	49.61	34.29	8.99	36.77	0.00	189	36	PEAK	Blank					
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																				
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5921.50	57.88	110.76	-52.88	51.36	34.31	8.98	36.77	0.00	189	36	PEAK																																																						
2	5928.50	56.12	108.20	-52.08	49.61	34.29	8.99	36.77	0.00	189	36	PEAK																																																						
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 70 Setting : 84 Plane : <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.75</td><td>46.06</td><td>89.11</td><td>-43.05</td><td>39.53</td><td>34.31</td><td>8.99</td><td>36.77</td><td>0.00</td><td>189</td><td>36</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.75</td><td>45.50</td><td>88.20</td><td>-42.70</td><td>38.98</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>189</td><td>36</td><td>AVERAGE</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5923.75	46.06	89.11	-43.05	39.53	34.31	8.99	36.77	0.00	189	36	AVERAGE	2	5925.75	45.50	88.20	-42.70	38.98	34.30	8.99	36.77	0.00	189	36	AVERAGE	Blank					
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																				
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5923.75	46.06	89.11	-43.05	39.53	34.31	8.99	36.77	0.00	189	36	AVERAGE																																																						
2	5925.75	45.50	88.20	-42.70	38.98	34.30	8.99	36.77	0.00	189	36	AVERAGE																																																						






Mode	70																																																																																																																	
	Harmonic																																																																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz																																																																																																																	
ANT	4+3																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 HORIZONTAL Mode : 70 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11730.00</td><td>45.99</td><td>74.00</td><td>-28.01</td><td>50.89</td><td>38.70</td><td>12.75</td><td>57.28</td><td>0.93</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>17595.00</td><td>49.15</td><td>68.20</td><td>-19.05</td><td>52.45</td><td>38.97</td><td>15.68</td><td>58.88</td><td>0.93</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11730.00	45.99	74.00	-28.01	50.89	38.70	12.75	57.28	0.93	--	-- Peak	2	17595.00	49.15	68.20	-19.05	52.45	38.97	15.68	58.88	0.93	--	-- Peak	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 VERTICAL Mode : 70 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11730.00</td><td>45.68</td><td>74.00</td><td>-28.32</td><td>50.62</td><td>38.68</td><td>12.74</td><td>57.29</td><td>0.93</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>17595.00</td><td>48.44</td><td>68.20</td><td>-19.76</td><td>51.66</td><td>39.02</td><td>15.69</td><td>58.86</td><td>0.93</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11730.00	45.68	74.00	-28.32	50.62	38.68	12.74	57.29	0.93	--	-- Peak	2	17595.00	48.44	68.20	-19.76	51.66	39.02	15.69	58.86	0.93	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																							
1	11730.00	45.99	74.00	-28.01	50.89	38.70	12.75	57.28	0.93	--	-- Peak																																																																																																							
2	17595.00	49.15	68.20	-19.05	52.45	38.97	15.68	58.88	0.93	--	-- Peak																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																							
1	11730.00	45.68	74.00	-28.32	50.62	38.68	12.74	57.29	0.93	--	-- Peak																																																																																																							
2	17595.00	48.44	68.20	-19.76	51.66	39.02	15.69	58.86	0.93	--	-- Peak																																																																																																							





Mode	70	
	Harmonic	
	U-NII-4_5.85-5.895_802.11be EHT20_CH173_Full RU_5865MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 70 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 70 Setting : 84
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 70 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 70 Setting : 84






Mode	71																																																																																																																																																							
	Band Edge - L																																																																																																																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz																																																																																																																																																							
ANT	4+3																																																																																																																																																							
Pol.	Horizontal																																																																																																																																																							
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5629.00</td><td>48.02</td><td>68.20</td><td>-20.18</td><td>42.98</td><td>33.18</td><td>8.66</td><td>36.80</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>5651.04</td><td>47.25</td><td>68.97</td><td>-21.72</td><td>42.05</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td><td></td></tr><tr><td>3</td><td>5700.01</td><td>47.57</td><td>105.20</td><td>-57.63</td><td>41.93</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td><td></td></tr><tr><td>4</td><td>5720.36</td><td>47.72</td><td>111.62</td><td>-63.90</td><td>42.01</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5629.00	48.02	68.20	-20.18	42.98	33.18	8.66	36.80	0.00	164	299	PEAK		2	5651.04	47.25	68.97	-21.72	42.05	33.31	8.69	36.80	0.00	164	299	PEAK		3	5700.01	47.57	105.20	-57.63	41.93	33.70	8.74	36.80	0.00	164	299	PEAK		4	5720.36	47.72	111.62	-63.90	42.01	33.74	8.76	36.79	0.00	164	299	PEAK		 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>109.26</td><td>-----</td><td>-----</td><td>102.75</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5885.00	109.26	-----	-----	102.75	34.34	8.94	36.77	0.00	164	299	PEAK	
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5629.00	48.02	68.20	-20.18	42.98	33.18	8.66	36.80	0.00	164	299	PEAK																																																																																																																																												
2	5651.04	47.25	68.97	-21.72	42.05	33.31	8.69	36.80	0.00	164	299	PEAK																																																																																																																																												
3	5700.01	47.57	105.20	-57.63	41.93	33.70	8.74	36.80	0.00	164	299	PEAK																																																																																																																																												
4	5720.36	47.72	111.62	-63.90	42.01	33.74	8.76	36.79	0.00	164	299	PEAK																																																																																																																																												
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5885.00	109.26	-----	-----	102.75	34.34	8.94	36.77	0.00	164	299	PEAK																																																																																																																																												
Avg	Blank													 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>102.86</td><td>-----</td><td>-----</td><td>96.32</td><td>34.36</td><td>8.95</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>AVERAGE</td><td></td></tr></tbody></table>														Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5885.00	102.86	-----	-----	96.32	34.36	8.95	36.77	0.00	164	299	AVERAGE																																																																																					
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	5885.00	102.86	-----	-----	96.32	34.36	8.95	36.77	0.00	164	299	AVERAGE																																																																																																																																												





Mode	71																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5897.25</td><td>92.74</td><td>128.55</td><td>-35.81</td><td>86.16</td><td>34.39</td><td>8.96</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td></tr><tr><td>2</td><td>5927.00</td><td>62.99</td><td>108.20</td><td>-45.21</td><td>56.48</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>PEAK</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5897.25	92.74	128.55	-35.81	86.16	34.39	8.96	36.77	0.00	164	299	PEAK	2	5927.00	62.99	108.20	-45.21	56.48	34.29	8.99	36.77	0.00	164	299	PEAK	Blank
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5897.25	92.74	128.55	-35.81	86.16	34.39	8.96	36.77	0.00	164	299	PEAK																																												
2	5927.00	62.99	108.20	-45.21	56.48	34.29	8.99	36.77	0.00	164	299	PEAK																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5895.25</td><td>85.50</td><td>110.02</td><td>-24.52</td><td>78.94</td><td>34.38</td><td>8.95</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.00</td><td>51.87</td><td>88.20</td><td>-36.33</td><td>45.35</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>164</td><td>299</td><td>AVERAGE</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5895.25	85.50	110.02	-24.52	78.94	34.38	8.95	36.77	0.00	164	299	AVERAGE	2	5925.00	51.87	88.20	-36.33	45.35	34.30	8.99	36.77	0.00	164	299	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5895.25	85.50	110.02	-24.52	78.94	34.38	8.95	36.77	0.00	164	299	AVERAGE																																												
2	5925.00	51.87	88.20	-36.33	45.35	34.30	8.99	36.77	0.00	164	299	AVERAGE																																												





		71																																																																																																																																		
Mode		Band Edge - L																																																																																																																																		
		U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz																																																																																																																																		
ANT		4+3																																																																																																																																		
Pol.		Vertical						Fundamental																																																																																																																												
Peak																																																																																																																																				
	Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5613.57</td><td>47.32</td><td>68.20</td><td>-20.88</td><td>42.41</td><td>33.08</td><td>8.64</td><td>36.81</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>46.33</td><td>68.31</td><td>-21.98</td><td>41.14</td><td>33.30</td><td>8.69</td><td>36.80</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr><tr><td>3</td><td>5701.19</td><td>47.38</td><td>105.53</td><td>-58.15</td><td>41.74</td><td>33.70</td><td>8.74</td><td>36.80</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>47.25</td><td>110.95</td><td>-63.70</td><td>41.54</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5613.57	47.32	68.20	-20.88	42.41	33.08	8.64	36.81	0.00	200	44	PEAK	2	5650.15	46.33	68.31	-21.98	41.14	33.30	8.69	36.80	0.00	200	44	PEAK	3	5701.19	47.38	105.53	-58.15	41.74	33.70	8.74	36.80	0.00	200	44	PEAK	4	5720.07	47.25	110.95	-63.70	41.54	33.74	8.76	36.79	0.00	200	44	PEAK	Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>109.40</td><td>-----</td><td>-----</td><td>102.89</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	109.40	-----	-----	102.89	34.34	8.94	36.77	0.00	200	44
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																							
1	5613.57	47.32	68.20	-20.88	42.41	33.08	8.64	36.81	0.00	200	44	PEAK																																																																																																																								
2	5650.15	46.33	68.31	-21.98	41.14	33.30	8.69	36.80	0.00	200	44	PEAK																																																																																																																								
3	5701.19	47.38	105.53	-58.15	41.74	33.70	8.74	36.80	0.00	200	44	PEAK																																																																																																																								
4	5720.07	47.25	110.95	-63.70	41.54	33.74	8.76	36.79	0.00	200	44	PEAK																																																																																																																								
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																							
1	5885.00	109.40	-----	-----	102.89	34.34	8.94	36.77	0.00	200	44	PEAK																																																																																																																								
Avg	Blank																																																																																																																																			
							Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>103.61</td><td>-----</td><td>-----</td><td>97.10</td><td>34.34</td><td>8.94</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	103.61	-----	-----	97.10	34.34	8.94	36.77	0.00	200	44	AVERAGE																																																																															
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																							
1	5885.00	103.61	-----	-----	97.10	34.34	8.94	36.77	0.00	200	44	AVERAGE																																																																																																																								







Mode	71																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz																																																							
ANT	4+3																																																							
Pol.	Vertical	Fundamental																																																						
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5900.25</td><td>91.54</td><td>126.34</td><td>-34.80</td><td>84.95</td><td>34.40</td><td>8.96</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr><tr><td>2</td><td>5927.50</td><td>62.99</td><td>108.20</td><td>-45.21</td><td>56.48</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>PEAK</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5900.25	91.54	126.34	-34.80	84.95	34.40	8.96	36.77	0.00	200	44	PEAK	2	5927.50	62.99	108.20	-45.21	56.48	34.29	8.99	36.77	0.00	200	44	PEAK	Blank
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5900.25	91.54	126.34	-34.80	84.95	34.40	8.96	36.77	0.00	200	44	PEAK																																												
2	5927.50	62.99	108.20	-45.21	56.48	34.29	8.99	36.77	0.00	200	44	PEAK																																												
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto Detector : PEAK Mode : 71 Setting : 84 Plane : <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5895.25</td><td>84.39</td><td>110.02</td><td>-25.63</td><td>77.83</td><td>34.38</td><td>8.95</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.00</td><td>53.75</td><td>88.20</td><td>-34.45</td><td>47.23</td><td>34.30</td><td>8.99</td><td>36.77</td><td>0.00</td><td>200</td><td>44</td><td>AVERAGE</td></tr></tbody></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5895.25	84.39	110.02	-25.63	77.83	34.38	8.95	36.77	0.00	200	44	AVERAGE	2	5925.00	53.75	88.20	-34.45	47.23	34.30	8.99	36.77	0.00	200	44	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5895.25	84.39	110.02	-25.63	77.83	34.38	8.95	36.77	0.00	200	44	AVERAGE																																												
2	5925.00	53.75	88.20	-34.45	47.23	34.30	8.99	36.77	0.00	200	44	AVERAGE																																												






Mode	71																																																																																																															
	Harmonic																																																																																																															
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz																																																																																																															
ANT	4+3																																																																																																															
Pol.	Horizontal	Vertical																																																																																																														
Peak Avg	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 HORIZONTAL Mode : 74 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11770.00</td><td>47.97</td><td>74.00</td><td>-26.03</td><td>52.76</td><td>38.77</td><td>12.77</td><td>57.26</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17655.00</td><td>56.93</td><td>68.20</td><td>-11.27</td><td>59.60</td><td>39.35</td><td>15.73</td><td>58.68</td><td>0.93</td><td>200</td><td>334 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11770.00	47.97	74.00	-26.03	52.76	38.77	12.77	57.26	0.93	--	Peak	2	17655.00	56.93	68.20	-11.27	59.60	39.35	15.73	58.68	0.93	200	334 Peak	 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91200-02294_240620 VERTICAL Mode : 74 Setting : 84 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11770.00</td><td>46.52</td><td>74.00</td><td>-27.48</td><td>51.31</td><td>38.77</td><td>12.77</td><td>57.26</td><td>0.93</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17655.00</td><td>54.32</td><td>68.20</td><td>-13.88</td><td>56.99</td><td>39.35</td><td>15.73</td><td>58.68</td><td>0.93</td><td>248</td><td>2 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11770.00	46.52	74.00	-27.48	51.31	38.77	12.77	57.26	0.93	--	Peak	2	17655.00	54.32	68.20	-13.88	56.99	39.35	15.73	58.68	0.93	248	2 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11770.00	47.97	74.00	-26.03	52.76	38.77	12.77	57.26	0.93	--	Peak																																																																																																					
2	17655.00	56.93	68.20	-11.27	59.60	39.35	15.73	58.68	0.93	200	334 Peak																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	11770.00	46.52	74.00	-27.48	51.31	38.77	12.77	57.26	0.93	--	Peak																																																																																																					
2	17655.00	54.32	68.20	-13.88	56.99	39.35	15.73	58.68	0.93	248	2 Peak																																																																																																					





Mode	71	
	Harmonic	
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Full RU_5885MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 74 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 74 Setting : 84
	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 HORIZONTAL Mode : 74 Setting : 84	 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-02294_240620 VERTICAL Mode : 74 Setting : 84



Mode	72																																																																																																																																	
	Band Edge - L																																																																																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Partial_26/8RU_5885MHz																																																																																																																																	
ANT	4+3																																																																																																																																	
Pol.	Horizontal						Fundamental																																																																																																																											
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 72 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5634.22</td><td>47.15</td><td>68.20</td><td>-21.05</td><td>42.07</td><td>33.21</td><td>8.67</td><td>36.80</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td></tr><tr><td>2</td><td>5658.74</td><td>46.86</td><td>68.75</td><td>-21.89</td><td>41.66</td><td>33.31</td><td>8.69</td><td>36.80</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td></tr><tr><td>3</td><td>5707.09</td><td>48.30</td><td>107.19</td><td>-58.89</td><td>42.64</td><td>33.71</td><td>8.75</td><td>36.80</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td></tr><tr><td>4</td><td>5728.07</td><td>46.62</td><td>110.95</td><td>-64.33</td><td>40.91</td><td>33.74</td><td>8.76</td><td>36.79</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5634.22	47.15	68.20	-21.05	42.07	33.21	8.67	36.80	0.00	176	29	Peak	2	5658.74	46.86	68.75	-21.89	41.66	33.31	8.69	36.80	0.00	176	29	Peak	3	5707.09	48.30	107.19	-58.89	42.64	33.71	8.75	36.80	0.00	176	29	Peak	4	5728.07	46.62	110.95	-64.33	40.91	33.74	8.76	36.79	0.00	176	29	Peak	 Site : 03CH15-HY Condition: PEAK(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto Detector : PEAK Mode : 72 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5885.00</td><td>113.33</td><td>-----</td><td>-----</td><td>106.79</td><td>34.36</td><td>8.95</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td></tr></table>								Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	113.33	-----	-----	106.79	34.36	8.95	36.77	0.00	176	29	Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5634.22	47.15	68.20	-21.05	42.07	33.21	8.67	36.80	0.00	176	29	Peak																																																																																																																						
2	5658.74	46.86	68.75	-21.89	41.66	33.31	8.69	36.80	0.00	176	29	Peak																																																																																																																						
3	5707.09	48.30	107.19	-58.89	42.64	33.71	8.75	36.80	0.00	176	29	Peak																																																																																																																						
4	5728.07	46.62	110.95	-64.33	40.91	33.74	8.76	36.79	0.00	176	29	Peak																																																																																																																						
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5885.00	113.33	-----	-----	106.79	34.36	8.95	36.77	0.00	176	29	Peak																																																																																																																						
Avg	Blank						 Site : 03CH15-HY Condition: AVG(UNII 4)_indoor 3m 91280-92294_240620 HORIZONTAL : RBW:1000.000kHz VBN:0.620kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5885.00</td><td>107.40</td><td>-----</td><td>-----</td><td>100.86</td><td>34.36</td><td>8.95</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>AVERAGE</td></tr></table>								Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5885.00	107.40	-----	-----	100.86	34.36	8.95	36.77	0.00	176	29	AVERAGE																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																						
1	5885.00	107.40	-----	-----	100.86	34.36	8.95	36.77	0.00	176	29	AVERAGE																																																																																																																						



Mode	72																																																																	
	Band Edge - R																																																																	
	U-NII-4_5.85-5.895_802.11be EHT20_CH177_Partial_26/8RU_5885MHz																																																																	
ANT	4+3																																																																	
Pol.	Horizontal					Fundamental																																																												
Peak	 Site : 03CH15-HY Condition: PEAK_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto Detector : PEAK Mode : 72 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5895.25</td><td>100.06</td><td>130.02</td><td>-29.96</td><td>93.50</td><td>34.38</td><td>8.95</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td><td></td></tr><tr><td>2</td><td>5927.25</td><td>61.33</td><td>108.20</td><td>-46.87</td><td>54.82</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>Peak</td><td></td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5895.25	100.06	130.02	-29.96	93.50	34.38	8.95	36.77	0.00	176	29	Peak		2	5927.25	61.33	108.20	-46.87	54.82	34.29	8.99	36.77	0.00	176	29	Peak		Blank				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5895.25	100.06	130.02	-29.96	93.50	34.38	8.95	36.77	0.00	176	29	Peak																																																						
2	5927.25	61.33	108.20	-46.87	54.82	34.29	8.99	36.77	0.00	176	29	Peak																																																						
Avg	 Site : 03CH15-HY Condition: AVG_BE(UNII 4)_indoor 3m 91200-02294_240620 HORIZONTAL : RBW:1000.000kHz VBW:0.620kHz SMT:Auto Detector : PEAK Mode : 72 Setting : 80 <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5895.25</td><td>89.87</td><td>110.02</td><td>-20.15</td><td>83.31</td><td>34.38</td><td>8.95</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>Average</td><td></td></tr><tr><td>2</td><td>5927.00</td><td>49.67</td><td>88.20</td><td>-38.53</td><td>43.16</td><td>34.29</td><td>8.99</td><td>36.77</td><td>0.00</td><td>176</td><td>29</td><td>Average</td><td></td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg		1	5895.25	89.87	110.02	-20.15	83.31	34.38	8.95	36.77	0.00	176	29	Average		2	5927.00	49.67	88.20	-38.53	43.16	34.29	8.99	36.77	0.00	176	29	Average		Blank				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																					
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg																																																						
1	5895.25	89.87	110.02	-20.15	83.31	34.38	8.95	36.77	0.00	176	29	Average																																																						
2	5927.00	49.67	88.20	-38.53	43.16	34.29	8.99	36.77	0.00	176	29	Average																																																						