



FCC RADIO TEST REPORT

FCC ID : A4RGXQ96
Equipment : Phone
Model Name : GXQ96
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, California, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on May 21, 2024 and testing was performed from May 23, 2024 to Sep. 06, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	12
3 Test Result	13
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	13
3.2 Maximum E.I.R.P Output Power Measurement	14
3.3 Power Spectral Density Measurement	15
3.4 Unwanted Emissions Measurement.....	17
3.5 AC Conducted Emission Measurement.....	22
3.6 Antenna Requirements.....	24
4 List of Measuring Equipment.....	25
5 Measurement Uncertainty	27
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Data	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR451606F	01	Initial issue of report	Sep. 27, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.407(e)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum E.I.R.P Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	1.63 dB under the limit at 5895.25 MHz
3.5	15.207	AC Conducted Emission	Pass	12.81 dB under the limit at 0.15 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Mila Chen



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR, Bluetooth, BLE, BLE channel sounding, Wi-Fi 802.11ax, NFC, WPC Rx and GNSS.
Antenna Type WLAN: <Ant. 4>: IFA Antenna <Ant. 3>: IFA Antenna

EUT Information List	
S/N	Performed Test Item
44291JEBF05085	RF Conducted Measurement
46181JEBF10894	Radiated Spurious Emission
44291JEBF05116	Conducted Emission

Antenna information		
5850 MHz ~ 5895 MHz	Peak Gain (dBi)	Ant. 4: -2.1 Ant. 3: -3.2

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.1.1 Antenna Directional Gain

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

UNII-4			DG	DG
			for	for
	Ant 4	Ant 3	Power	PSD
	(dBi)	(dBi)	(dBi)	(dBi)
	-2.10	-3.20	-2.10	0.38

Calculation example:

If a device has two antenna, $G_{ANT4} = -2.10$ dBi; $G_{ANT3} = -3.20$ dBi

Directional gain of power measurement = $\max(-2.10, -3.20) + 0 = -2.10$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(-2.10 \text{ dBi} / 20)} + 10^{(-3.20 \text{ dBi} / 20)} \right]^2 / 2 \right\} \\ = 0.38 \text{ dBi}$$



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH12-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC KDB 291074 D02 EMC Measurement v01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Y plane with Adapter as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Bandwidth	Channel	Frequency (MHz)	Note
5850-5895 MHz (U-NII-4)	20 MHz	169	5845	Straddle
		173	5865	
		177	5885	
	40 MHz	167	5835	Straddle
		175	5875	
	80 MHz	171	5855	Straddle
	160 MHz	163	5815	Straddle

Note: The channel noted with "straddle" spans 5.725-5.850 GHz and 5.850-5.895 GHz.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The SISO mode conducted power is covered by MIMO mode per chain, so only the MIMO mode is tested.

The power for 802.11n and 802.11ac mode is smaller than 802.11ax mode, so all other conducted and radiated test is covered by 802.11ax mode.

The final test modes include the worst data rates for each modulation shown in the table below.

MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by HE20)	MCS0
802.11n HT40 (Covered by HE40)	MCS0
802.11ac VHT20 (Covered by HE20)	MCS0
802.11ac VHT40 (Covered by HE40)	MCS0
802.11ac VHT80 (Covered by HE80)	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0
802.11ax HE160	MCS0

Remark: The conducted power level of each chain in MIMO mode is equal or higher than SISO mode.


Test Cases	
AC Conducted Emission	Mode 1 : LTE Band 14 Idle + WLAN (5GHz) Link + Bluetooth Idle + USB Cable 1 (Charging from Adapter) + Battery < 50%
Remark: - For Radiated Test Cases, the tests were performed with USB Cable 1. - During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test.	


Ch. #		RF test channel of UNII-4 and UNII-3 &-4 span channels			
		802.11a	802.11ax HE20	802.11ax HE40	802.11ax HE80
L	Low	169	169	167	-
M	Middle	173	173	-	171
H	High	177	177	175	-

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>


2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	ASUS	GT-AXE11000	FCC DoC	N/A	Unshielded,1.8m
3.	Notebook	Dell	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Wireless Earphone	N/A	G1007/G1008	A4RG1007/ A4RG1008	N/A	N/A
5.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “Cmd Version 1.0.32” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

The testing follows FCC KDB 291074 D02 EMC Measurement v01 Section 2.11 Minimum Emission bandwidth

1. Set RBW = 100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold
5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum E.I.R.P Output Power Measurement

3.2.1 Limit of Maximum E.I.R.P Output Power

For client devices operating under the control of an indoor access point in the 5.850-5.895 GHz band, the maximum power spectral density must not exceed 14 dBm e.i.r.p. in any 1-megahertz band, and the maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm. Client devices operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands must not exceed an e.i.r.p. of 30 dBm.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

1. For client devices operating under the control of an indoor access point in the 5.850-5.895 GHz band, the maximum power spectral density must not exceed 14 dBm e.i.r.p. in any 1-megahertz band.
2. For client devices operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands shall meet both 15.407(a)(3)(i) 30dBm/500kHz and 15.407(a)(3)(iii) 14dBm/MHz limit, where the stringent limit 14dBm/MHz is applied.
3. For an indoor access point operating on a channel that spans the 5.725-5.850 GHz and 5.850-5.895 GHz bands shall meet both 15.407(a)(3)(ii) 36dBm limit, where the stringent limit 20dBm/MHz is applied.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points; the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

- (2) For transmitters operating solely in the 5.850-5.895 GHz band or operating on a channel that spans across 5.725-5.895 GHz:

15.407(b)(5)(ii), all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of -5 dBm/MHz and shall decrease linearly to an e.i.r.p. of -27 dBm/MHz at or above 5.925 GHz.

All emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz.

- (3) KDB789033 D02 v02r01 G)2)c)

Use guidance in KDB Publication 789033 for all measurements. Unwanted emissions outside of restricted bands are measured with an RMS detector. In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.

Unwanted band-edge emissions may be measured using the integration method as described in KDB Publication 789033 3. d) (ii). Emissions below 5725 MHz should be measured using peak-detection while emission above 5895 MHz should be measured using average.

Frequency(GHz)	EIRP (dBm)	Field Strength @3m distance (dBuV/m)	Note
Below 5.65	-27dBm/MHz	68.2	Peak
5.7	10dBm/MHz	105.2	Peak
5.72	15.6dBm/MHz	110.8	Peak
5.725	27dBm/MHz	122.2	Peak
5.895	-5dBm/MHz	90.2	Average
5.895	15dBm/MHz	110.2	Peak
Above 5.925	-27dBm/MHz	68.2	Average
Above 5.925	-7dBm/MHz	88.2	Peak

Note: Field strength at 3 m distance is converted to EIRP as the following equation:

$$\text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} - 95.2$$

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
 Section G) Unwanted emissions measurement.
 - Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
- The EUT was placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
- The EUT was placed at distance 3 meter from measurement antenna which was mounted on the top of a variable height antenna tower.


4. The measurement antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0 degree to 360 degree to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1GHz was performed by adjusting the antenna tower from 1m to 4m and by rotating the turn table from 0 degree to 360 degree to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



**3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Results of Radiated Spurious Emissions (above 18 GHz)

For frequency above 18GHz, the pre-scanned result is 20dB lower than the limit line is not reported.

3.4.7 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.8 Duty Cycle

Please refer to Appendix D.

3.4.9 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

- b) Unique (non-standard) antenna connector.
- (3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 07, 2024	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 06, 2023	Aug. 07, 2024	Dec. 05, 2024	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 26, 2023	Aug. 07, 2024	Oct. 25, 2024	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 22, 2023	Aug. 07, 2024	Nov. 21, 2024	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Aug. 07, 2024	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 30, 2024	Aug. 07, 2024	Jul. 29, 2025	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 28, 2023	Aug. 07, 2024	Dec. 27, 2024	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9kHz~30MHz	Feb. 23, 2024	Jul. 11, 2024~Sep. 06, 2024	Feb. 22, 2025	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Nov. 03, 2023	Jul. 11, 2024~Sep. 06, 2024	Nov. 02, 2024	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02114	1GHz~18GHz	Jul. 11, 2024	Jul. 11, 2024~Sep. 06, 2024	Jul. 10, 2025	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00993	18GHz~40GHz	Nov. 24, 2023	Jul. 11, 2024~Sep. 06, 2024	Nov. 23, 2024	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 20, 2024	Jul. 11, 2024~Sep. 06, 2024	Mar. 19, 2025	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	May 22, 2024	Jul. 11, 2024~Sep. 06, 2024	May 21, 2025	Radiation (03CH12-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz-18GHz	Dec. 20, 2023	Jul. 11, 2024~Sep. 06, 2024	Dec. 19, 2024	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 07, 2023	Jul. 11, 2024~Sep. 06, 2024	Dec. 06, 2024	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Jan. 10, 2024	Jul. 11, 2024~Aug. 08, 2024	Jan. 09, 2025	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Aug. 09, 2024	Aug. 09, 2024~Sep. 06, 2024	Aug. 08, 2025	Radiation (03CH12-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz~26.5GHz	Aug. 29, 2023	Jul. 11, 2024~Aug. 27, 2024	Aug. 28, 2024	Radiation (03CH12-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20Hz~8.4GHz	Apr. 17, 2024	Aug. 28, 2024~Sep. 06, 2024	Apr. 16, 2025	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12SS	SN2	1.2GHz Low Pass Filter	Mar. 13, 2024	Jul. 11, 2024~Sep. 06, 2024	Mar. 12, 2025	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN2	6.75GHz High Pass Filter	Mar. 13, 2024	Jul. 11, 2024~Sep. 06, 2024	Mar. 12, 2025	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	Jul. 11, 2024~Sep. 06, 2024	Mar. 05, 2025	Radiation (03CH12-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 18, 2023	Jul. 11, 2024~ Sep. 06, 2024	Dec. 17, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Dec. 18, 2023	Jul. 11, 2024~ Sep. 06, 2024	Dec. 17, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803953/2	30MHz~40GHz	Dec. 18, 2023	Jul. 11, 2024~ Sep. 06, 2024	Dec. 17, 2024	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP210117	N/A	Oct. 19, 2023	Jul. 11, 2024~ Sep. 06, 2024	Oct. 18, 2024	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 11, 2024~ Sep. 06, 2024	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jul. 11, 2024~ Sep. 06, 2024	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jul. 11, 2024~ Sep. 06, 2024	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Jul. 11, 2024~ Sep. 06, 2024	N/A	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	May 23, 2024~ Aug. 21, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 36 (NO:35)	10MHz~6GHz	Aug. 23, 2023	May 23, 2024~ Aug. 21, 2024	Aug. 22, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101564	10Hz ~ 40GHz	Sep. 12, 2023	May 23, 2024~ Aug. 21, 2024	Sep. 11, 2024	Conducted (TH05-HY)
Switch Box & RF Cable	E-Instument	ETF-058	EC1208382 (BOX1)	N/A	Apr. 01, 2024	May 23, 2024~ Aug. 21, 2024	Mar. 31, 2025	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version1.0	N/A	N/A	N/A	May 23, 2024~ Aug. 21, 2024	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.1 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Hank Hsu	Temperature:	21~25	°C
Test Date:	2024/5/23~2024/8/21	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

UNII-4 MIMO												
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 4	Ant 3	Ant 4	Ant 3	Ant 4	Ant 3		
11a	6Mbps	2	169	5845	27.57	25.22	43.41	39.42	16.34	15.47	0.5	Pass
11a	6Mbps	2	173	5865	25.82	23.78	40.02	38.83	16.31	16.24	0.5	Pass
11a	6Mbps	2	177	5885	25.87	24.23	40.00	37.98	16.03	15.39	0.5	Pass

TEST RESULTS DATA
Average Power Table

UNII-4 MIMO										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			DG (dBi)	E.I.R.P Power (dBm)	E.I.R.P Limit (dBm)
					Ant 4	Ant 3	SUM			
11a	6Mbps	2	169	5845	19.95	19.09	22.55	-2.10	20.45	30
11a	6Mbps	2	173	5865	19.65	18.49	22.12	-2.10	20.02	30
11a	6Mbps	2	177	5885	19.65	18.59	22.16	-2.10	20.06	30
HT20	MCS0	2	169	5845	19.75	18.99	22.40	-2.10	20.30	30
HT20	MCS0	2	173	5865	19.65	18.59	22.16	-2.10	20.06	30
HT20	MCS0	2	177	5885	18.35	17.69	21.04	-2.10	18.94	30
HT40	MCS0	2	167	5835	18.55	17.59	21.11	-2.10	19.01	30
HT40	MCS0	2	175	5875	18.65	17.39	21.08	-2.10	18.98	30
VHT20	MCS0	2	169	5845	19.75	18.99	22.40	-2.10	20.30	30
VHT20	MCS0	2	173	5865	19.65	18.59	22.16	-2.10	20.06	30
VHT20	MCS0	2	177	5885	18.35	17.69	21.04	-2.10	18.94	30
VHT40	MCS0	2	167	5835	18.55	17.59	21.11	-2.10	19.01	30
VHT40	MCS0	2	175	5875	18.65	17.39	21.08	-2.10	18.98	30
VHT80	MCS0	2	171	5855	17.25	16.59	19.94	-2.10	17.84	30

TEST RESULTS DATA
Power Spectral Density

UNII-4 MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			DG (dBi)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Pass /Fail
					Ant 1	Ant 2	Ant 4	Ant 3	SUM				
11a	6Mbps	2	169	5845	0.28	0.29			11.03	0.38	11.41	14.00	Pass
11a	6Mbps	2	173	5865	0.28	0.29			10.55	0.38	10.93	14.00	Pass
11a	6Mbps	2	177	5885	0.28	0.29			10.43	0.38	10.81	14.00	Pass

Note: PSD Sum = Max PSD(Ant. 4, Ant. 3) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

UNII-4 MIMO													
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 4	Ant 3	Ant 4	Ant 3	Ant 4	Ant 3		
HE20	MCS0	2	169	5845	Full	28.22	25.77	46.98	45.71	17.44	17.41	0.5	Pass
HE20	MCS0	2	173	5865	Full	26.52	23.93	44.54	40.61	17.55	17.77	0.5	Pass
HE20	MCS0	2	177	5885	Full	25.77	25.02	46.48	46.21	18.27	17.08	0.5	Pass
HE40	MCS0	2	167	5835	Full	41.66	39.36	84.67	70.83	36.94	36.37	0.5	Pass
HE40	MCS0	2	175	5875	Full	40.96	38.66	81.65	64.54	36.95	36.50	0.5	Pass
HE80	MCS0	2	171	5855	Full	77.32	77.20	119.68	121.38	76.13	75.76	0.5	Pass

TEST RESULTS DATA
Average Power Table

UNII-4 MIMO											
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config	Average Conducted Power (dBm)			DG (dBi)	E.I.R.P Power (dBm)	E.I.R.P Limit (dBm)
						Ant 4	Ant 3	SUM			
HE20	MCS0	2	169	5845	Full	19.85	19.09	22.50	-2.10	20.40	30
HE20	MCS0	2	169	5845	26/0	11.15	9.29	13.33	-2.10	11.23	30
HE20	MCS0	2	169	5845	52/37	13.75	12.89	16.35	-2.10	14.25	30
HE20	MCS0	2	169	5845	106/53	16.35	15.59	19.00	-2.10	16.90	30
HE20	MCS0	2	173	5865	Full	19.75	18.69	22.26	-2.10	20.16	30
HE20	MCS0	2	173	5865	26/4	11.55	10.09	13.89	-2.10	11.79	30
HE20	MCS0	2	173	5865	52/38	12.85	11.39	15.19	-2.10	13.09	30
HE20	MCS0	2	173	5865	106/53	15.55	15.19	18.38	-2.10	16.28	30
HE20	MCS0	2	177	5885	Full	18.45	17.79	21.14	-2.10	19.04	30
HE20	MCS0	2	177	5885	26/8	9.05	7.49	11.35	-2.10	9.25	30
HE20	MCS0	2	177	5885	52/40	12.55	11.09	14.89	-2.10	12.79	30
HE20	MCS0	2	177	5885	106/54	13.55	12.69	16.15	-2.10	14.05	30
HE40	MCS0	2	167	5835	Full	18.65	17.69	21.21	-2.10	19.11	30
HE40	MCS0	2	175	5875	Full	18.75	17.49	21.18	-2.10	19.08	30
HE80	MCS0	2	171	5855	Full	17.35	17.09	20.23	-2.10	18.13	30

TEST RESULTS DATA
Power Spectral Density


UNII-4 MIMO														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			DG (dBi)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Pass /Fail
						Ant 1	Ant 2	Ant 4	Ant 3	SUM				
HE20	MCS0	2	169	5845	Full	0.40	0.40			10.15	0.38	10.52	14.00	Pass
HE20	MCS0	2	169	5845	26/0	0.48	0.48			7.86	0.38	8.24	14.00	Pass
HE20	MCS0	2	169	5845	52/37	0.52	0.53			10.14	0.38	10.51	14.00	Pass
HE20	MCS0	2	169	5845	106/53	0.58	0.59			6.85	0.38	7.22	14.00	Pass
HE20	MCS0	2	173	5865	Full	0.40	0.40			9.88	0.38	10.26	14.00	Pass
HE20	MCS0	2	173	5865	26/4	0.48	0.48			9.45	0.38	9.83	14.00	Pass
HE20	MCS0	2	173	5865	52/38	0.52	0.53			9.04	0.38	9.41	14.00	Pass
HE20	MCS0	2	173	5865	106/53	0.58	0.59			9.33	0.38	9.71	14.00	Pass
HE20	MCS0	2	177	5885	Full	0.40	0.40			8.82	0.38	9.20	14.00	Pass
HE20	MCS0	2	177	5885	26/8	0.48	0.48			8.72	0.38	9.10	14.00	Pass
HE20	MCS0	2	177	5885	52/40	0.52	0.53			8.09	0.38	8.47	14.00	Pass
HE20	MCS0	2	177	5885	106/54	0.58	0.59			8.66	0.38	9.03	14.00	Pass
HE40	MCS0	2	167	5835	Full	0.40	0.40			6.08	0.38	6.46	14.00	Pass
HE40	MCS0	2	175	5875	Full	0.40	0.40			5.96	0.38	6.34	14.00	Pass
HE80	MCS0	2	171	5855	Full	0.54	0.54			2.50	0.38	2.88	14.00	Pass

Note: PSD Sum = Max PSD(Ant. 4, Ant. 3) + 10 log (n)

**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**


MIMO <Ant. 4+3>

<802.11a>

**Note:** The occupied channel bandwidth is maintained within the band of operation.




<802.11ax HE20>



Note: The occupied channel bandwidth is maintained within the band of operation.




<802.11ax HE40>



Note: The occupied channel bandwidth is maintained within the band of operation.


<802.11ax HE80>




Note: The occupied channel bandwidth is maintained within the band of operation.

**Test Result of Power Spectral Density**

<802.11a>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11ax HE20>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11ax HE40>




Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






<802.11ax HE80>



Remark: The test plot is showing a bin by bin combined result mathematically adds two traces.






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO : 451606
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	38.75	55.88	17.13	L1	OFF	19.8
0.152250	53.02	---	65.88	12.86	L1	OFF	19.8
0.170250	---	33.53	54.95	21.42	L1	OFF	19.8
0.170250	48.79	---	64.95	16.16	L1	OFF	19.8
0.183750	---	28.25	54.31	26.06	L1	OFF	19.8
0.183750	40.93	---	64.31	23.38	L1	OFF	19.8
0.228750	---	29.99	52.50	22.51	L1	OFF	19.8
0.228750	41.22	---	62.50	21.28	L1	OFF	19.8
1.315500	---	24.16	46.00	21.84	L1	OFF	19.9
1.315500	26.08	---	56.00	29.92	L1	OFF	19.9
8.565000	---	26.17	50.00	23.83	L1	OFF	20.2
8.565000	27.64	---	60.00	32.36	L1	OFF	20.2

EUT Information

Report NO : 451606
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	38.45	55.88	17.43	N	OFF	19.8
0.152250	53.07	---	65.88	12.81	N	OFF	19.8
0.172500	---	34.46	54.84	20.38	N	OFF	19.8
0.172500	49.52	---	64.84	15.32	N	OFF	19.8
0.231000	---	29.36	52.41	23.05	N	OFF	19.8
0.231000	39.94	---	62.41	22.47	N	OFF	19.8
0.269250	---	25.35	51.14	25.79	N	OFF	19.8
0.269250	31.55	---	61.14	29.59	N	OFF	19.8
0.600000	---	25.12	46.00	20.88	N	OFF	19.8
0.600000	28.11	---	56.00	27.89	N	OFF	19.8
6.693000	---	25.88	50.00	24.12	N	OFF	20.1
6.693000	27.18	---	60.00	32.82	N	OFF	20.1



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Ken Kuo, Tim Lee, and Wilson Wu	Temperature :	21.7~23.5°C
		Relative Humidity :	55.2~62.4%

Note symbol

-L	Low channel location
-R	High channel location

**C1. Radiated Spurious Emission Test Modes**

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 43	U-NII-4	5.85-5.895	4+3	802.11a	169	5845	6Mbps	-	-
Mode 44	U-NII-4	5.85-5.895	4+3	802.11a	173	5865	6Mbps	-	-
Mode 45	U-NII-4	5.85-5.895	4+3	802.11a	177	5885	6Mbps	-	-
Mode 46	U-NII-4	5.85-5.895	4+3	802.11ax HE20	169	5845	MCS0	Full RU	-
Mode 47	U-NII-4	5.85-5.895	4+3	802.11ax HE20	173	5865	MCS0	Full RU	-
Mode 48	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Full RU	-
Mode 49	U-NII-4	5.85-5.895	4+3	802.11ax HE40	167	5835	MCS0	Full RU	-
Mode 50	U-NII-4	5.85-5.895	4+3	802.11ax HE40	175	5875	MCS0	Full RU	-
Mode 51	U-NII-4	5.85-5.895	4+3	802.11ax HE80	171	5855	MCS0	Full RU	-
Mode 72	U-NII-4	5.85-5.895	4+3	802.11ax HE20	169	5845	MCS0	Partial 26/0	-
Mode 73	U-NII-4	5.85-5.895	4+3	802.11ax HE20	169	5845	MCS0	Partial 52/37	-
Mode 74	U-NII-4	5.85-5.895	4+3	802.11ax HE20	169	5845	MCS0	Partial 106/53	-
Mode 75	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Partial 26/8	-
Mode 76	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Partial 52/40	-
Mode 77	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Partial 106/54	-
Mode 78	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Partial 106/54	LF
Mode 79	U-NII-4	5.85-5.895	4+3	802.11ax HE20	177	5885	MCS0	Partial 106/54	SHF




**C2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
43	802.11a	169	5612.39	55.33	68.20	-12.87	V	Peak	Pass	-	Band Edge
	802.11a	169	11690.00	42.51	54.00	-11.49	V	Avg.	Pass	-	Harmonic
44	802.11a	173	5634.22	55.33	68.20	-12.87	H	Peak	Pass	-	Band Edge
	802.11a	173	11730.00	42.21	54.00	-11.79	H	Avg.	Pass	-	Harmonic
45	802.11a	177	5899.50	77.57	86.89	-9.32	V	Avg.	Pass	-	Band Edge
	802.11a	177	11770.00	41.89	54.00	-12.11	H	Avg.	Pass	-	Harmonic
46	802.11ax HE20	169	5632.45	55.58	68.20	-12.62	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	169	11690.00	41.10	54.00	-12.90	H	Avg.	Pass	Full RU	Harmonic
47	802.11ax HE20	173	5631.57	55.40	68.20	-12.80	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	173	11730.00	40.04	54.00	-13.96	H	Avg.	Pass	Full RU	Harmonic
48	802.11ax HE20	177	5895.25	87.84	90.02	-2.18	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE20	177	11770.00	40.70	54.00	-13.30	V	Avg.	Pass	Full RU	Harmonic
49	802.11ax HE40	167	5625.08	55.27	68.20	-12.93	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	167	11670.00	40.85	54.00	-13.15	V	Avg.	Pass	Full RU	Harmonic
50	802.11ax HE40	175	5923.50	61.00	69.30	-8.30	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE40	175	11750.00	41.64	54.00	-12.36	V	Avg.	Pass	Full RU	Harmonic
51	802.11ax HE80	171	5924.25	66.30	68.75	-2.45	H	Avg.	Pass	Full RU	Band Edge
	802.11ax HE80	171	11710.00	43.09	54.00	-10.91	H	Avg.	Pass	Full RU	Harmonic



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
72	802.11ax HE20	169	5614.46	55.60	68.20	-12.60	H	Peak	Pass	Partial 26/0	Band Edge
	802.11ax HE20	169	-	-	-	-	-	-	-	Partial 26/0	Harmonic
73	802.11ax HE20	169	5637.76	56.00	68.20	-12.20	V	Peak	Pass	Partial 52/37	Band Edge
	802.11ax HE20	169	-	-	-	-	-	-	-	Partial 52/37	Harmonic
74	802.11ax HE20	169	5635.40	56.37	68.20	-11.83	V	Peak	Pass	Partial 106/53	Band Edge
	802.11ax HE20	169	-	-	-	-	-	-	-	Partial 106/53	Harmonic
75	802.11ax HE20	177	5895.25	87.93	90.02	-2.09	H	Avg.	Pass	Partial 26/8	Band Edge
	802.11ax HE20	177	-	-	-	-	-	-	-	Partial 26/8	Harmonic
76	802.11ax HE20	177	5895.25	87.30	90.02	-2.72	H	Avg.	Pass	Partial 52/40	Band Edge
	802.11ax HE20	177	-	-	-	-	-	-	-	Partial 52/40	Harmonic
77	802.11ax HE20	177	5895.25	88.39	90.02	-1.63	H	Avg.	Pass	Partial 106/54	Band Edge
	802.11ax HE20	177	-	-	-	-	-	-	-	Partial 106/54	Harmonic
78	LF	177	713.85	38.79	46.00	-7.21	V	Peak	Pass	-	LF
79	SHF	177	31497.00	42.41	74.00	-31.59	V	Peak	Pass	-	SHF






Mode	43																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																																																								
ANT	4+3																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak																																																																																																																									
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5600.26</td><td>55.24</td><td>68.20</td><td>-12.96</td><td>44.20</td><td>33.00</td><td>11.24</td><td>33.28</td><td>0.00</td><td>100 285 PEAK</td></tr><tr><td>2 5650.15</td><td>53.29</td><td>68.31</td><td>-15.02</td><td>42.39</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>100 285 PEAK</td></tr><tr><td>3 5706.79</td><td>55.44</td><td>107.10</td><td>-51.66</td><td>44.25</td><td>33.37</td><td>11.20</td><td>33.38</td><td>0.00</td><td>100 285 PEAK</td></tr><tr><td>4 5720.07</td><td>54.33</td><td>110.95</td><td>-56.62</td><td>43.03</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>100 285 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5600.26	55.24	68.20	-12.96	44.20	33.00	11.24	33.28	0.00	100 285 PEAK	2 5650.15	53.29	68.31	-15.02	42.39	33.00	11.22	33.32	0.00	100 285 PEAK	3 5706.79	55.44	107.10	-51.66	44.25	33.37	11.20	33.38	0.00	100 285 PEAK	4 5720.07	54.33	110.95	-56.62	43.03	33.50	11.19	33.39	0.00	100 285 PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5845.00</td><td>107.45</td><td>-----</td><td>-----</td><td>95.56</td><td>34.10</td><td>11.30</td><td>33.51</td><td>0.00</td><td>100 285 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5845.00	107.45	-----	-----	95.56	34.10	11.30	33.51	0.00
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5600.26	55.24	68.20	-12.96	44.20	33.00	11.24	33.28	0.00	100 285 PEAK																																																																																																																
2 5650.15	53.29	68.31	-15.02	42.39	33.00	11.22	33.32	0.00	100 285 PEAK																																																																																																																
3 5706.79	55.44	107.10	-51.66	44.25	33.37	11.20	33.38	0.00	100 285 PEAK																																																																																																																
4 5720.07	54.33	110.95	-56.62	43.03	33.50	11.19	33.39	0.00	100 285 PEAK																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5845.00	107.45	-----	-----	95.56	34.10	11.30	33.51	0.00	100 285 PEAK																																																																																																																
Avg.	Blank																																																																																																																								
							Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 5845.00</td><td>101.34</td><td>-----</td><td>-----</td><td>89.45</td><td>34.10</td><td>11.30</td><td>33.51</td><td>0.00</td><td>100 285 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5845.00	101.34	-----	-----	89.45	34.10	11.30	33.51	0.00	100 285 AVERAGE																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5845.00	101.34	-----	-----	89.45	34.10	11.30	33.51	0.00	100 285 AVERAGE																																																																																																																





Mode	43																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																										
ANT	4+3																																																										
Pol.	Horizontal	Fundamental																																																									
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>54.67</td><td>88.20</td><td>-33.53</td><td>42.35</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>100</td><td>285</td><td>PEAK</td></tr><tr><td>2</td><td>5935.00</td><td>55.54</td><td>88.20</td><td>-32.66</td><td>43.17</td><td>34.37</td><td>11.60</td><td>33.60</td><td>0.00</td><td>100</td><td>285</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	54.67	88.20	-33.53	42.35	34.35	11.57	33.60	0.00	100	285	PEAK	2	5935.00	55.54	88.20	-32.66	43.17	34.37	11.60	33.60	0.00	100	285	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5925.00	54.67	88.20	-33.53	42.35	34.35	11.57	33.60	0.00	100	285	PEAK																																															
2	5935.00	55.54	88.20	-32.66	43.17	34.37	11.60	33.60	0.00	100	285	PEAK																																															
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5910.75</td><td>48.49</td><td>78.64</td><td>-30.15</td><td>36.23</td><td>34.32</td><td>11.52</td><td>33.58</td><td>0.00</td><td>100</td><td>285</td><td>Average</td></tr><tr><td>2</td><td>5925.00</td><td>47.15</td><td>68.20</td><td>-21.05</td><td>34.02</td><td>34.35</td><td>11.57</td><td>33.59</td><td>0.00</td><td>100</td><td>285</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5910.75	48.49	78.64	-30.15	36.23	34.32	11.52	33.58	0.00	100	285	Average	2	5925.00	47.15	68.20	-21.05	34.02	34.35	11.57	33.59	0.00	100	285	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5910.75	48.49	78.64	-30.15	36.23	34.32	11.52	33.58	0.00	100	285	Average																																															
2	5925.00	47.15	68.20	-21.05	34.02	34.35	11.57	33.59	0.00	100	285	AVERAGE																																															





Mode	43																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																																																																									
ANT	4+3																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4)						 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4)																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5612.39</td><td>55.33</td><td>68.20</td><td>-12.87</td><td>44.29</td><td>33.00</td><td>11.24</td><td>33.28</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>53.16</td><td>68.31</td><td>-15.15</td><td>42.26</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr><tr><td>3</td><td>5700.30</td><td>54.39</td><td>105.28</td><td>-50.89</td><td>43.26</td><td>33.30</td><td>11.20</td><td>33.37</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>53.75</td><td>110.95</td><td>-57.20</td><td>42.45</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5612.39	55.33	68.20	-12.87	44.29	33.00	11.24	33.28	0.00	365	0	PEAK	2	5650.15	53.16	68.31	-15.15	42.26	33.00	11.22	33.32	0.00	365	0	PEAK	3	5700.30	54.39	105.28	-50.89	43.26	33.30	11.20	33.37	0.00	365	0	PEAK	4	5720.07	53.75	110.95	-57.20	42.45	33.50	11.19	33.39	0.00	365	0	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>100.54</td><td>-----</td><td>-----</td><td>88.64</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	100.54	-----	-----	88.64	34.10	11.32	33.52	0.00	365	0
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5612.39	55.33	68.20	-12.87	44.29	33.00	11.24	33.28	0.00	365	0	PEAK																																																																																																																														
2	5650.15	53.16	68.31	-15.15	42.26	33.00	11.22	33.32	0.00	365	0	PEAK																																																																																																																														
3	5700.30	54.39	105.28	-50.89	43.26	33.30	11.20	33.37	0.00	365	0	PEAK																																																																																																																														
4	5720.07	53.75	110.95	-57.20	42.45	33.50	11.19	33.39	0.00	365	0	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5845.00	100.54	-----	-----	88.64	34.10	11.32	33.52	0.00	365	0	PEAK																																																																																																																														
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4)																																																																																																																																			
						Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>95.12</td><td>-----</td><td>-----</td><td>83.22</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>365</td><td>0</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	95.12	-----	-----	83.22	34.10	11.32	33.52	0.00	365	0	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5845.00	95.12	-----	-----	83.22	34.10	11.32	33.52	0.00	365	0	AVERAGE																																																																																																																														



Mode	43																																																																			
	Band Edge - R																																																																			
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																			
ANT	4+3																																																																			
Pol.	Vertical						Fundamental																																																													
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5923.75</td><td>55.83</td><td>89.11</td><td>-33.28</td><td>43.51</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5927.25</td><td>55.87</td><td>88.20</td><td>-32.33</td><td>43.55</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>365</td><td>0</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5923.75	55.83	89.11	-33.28	43.51	34.35	11.56	33.59	0.00	365	0	PEAK	2	5927.25	55.87	88.20	-32.33	43.55	34.35	11.57	33.60	0.00	365	0	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																										
1	5923.75	55.83	89.11	-33.28	43.51	34.35	11.56	33.59	0.00	365	0	PEAK																																																								
2	5927.25	55.87	88.20	-32.33	43.55	34.35	11.57	33.60	0.00	365	0	PEAK																																																								
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5899.50</td><td>51.08</td><td>86.89</td><td>-35.81</td><td>38.87</td><td>34.30</td><td>11.48</td><td>33.57</td><td>0.00</td><td>365</td><td>0</td><td>Average</td></tr><tr><td>2</td><td>5925.25</td><td>46.53</td><td>68.20</td><td>-21.67</td><td>34.21</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>365</td><td>0</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5899.50	51.08	86.89	-35.81	38.87	34.30	11.48	33.57	0.00	365	0	Average	2	5925.25	46.53	68.20	-21.67	34.21	34.35	11.57	33.60	0.00	365	0	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																										
1	5899.50	51.08	86.89	-35.81	38.87	34.30	11.48	33.57	0.00	365	0	Average																																																								
2	5925.25	46.53	68.20	-21.67	34.21	34.35	11.57	33.60	0.00	365	0	AVERAGE																																																								






Mode	43																																																																																		
	Harmonic																																																																																		
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz																																																																																		
ANT	4+3																																																																																		
Pol.	Horizontal						Vertical																																																																												
Peak Avg.																																																																																			
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																												
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11690.00</td><td>50.72</td><td>74.00</td><td>-23.28</td><td>59.33</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>176</td><td>97</td><td>PEAK</td></tr><tr><td>2</td><td>11690.00</td><td>41.69</td><td>54.00</td><td>-12.31</td><td>50.30</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>176</td><td>97</td><td>Average</td></tr><tr><td>3</td><td>17535.00</td><td>54.13</td><td>88.20</td><td>-34.07</td><td>59.32</td><td>38.88</td><td>23.27</td><td>67.91</td><td>0.57</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11690.00	50.72	74.00	-23.28	59.33	38.76	18.79	66.47	0.31	176	97	PEAK	2	11690.00	41.69	54.00	-12.31	50.30	38.76	18.79	66.47	0.31	176	97	Average	3	17535.00	54.13	88.20	-34.07	59.32	38.88	23.27	67.91	0.57	--	--	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																									
1	11690.00	50.72	74.00	-23.28	59.33	38.76	18.79	66.47	0.31	176	97	PEAK																																																																							
2	11690.00	41.69	54.00	-12.31	50.30	38.76	18.79	66.47	0.31	176	97	Average																																																																							
3	17535.00	54.13	88.20	-34.07	59.32	38.88	23.27	67.91	0.57	--	--	PEAK																																																																							





Mode	43	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH169_5845MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






Mode	44																																																																																																																																								
	Band Edge - L																																																																																																																																								
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																																								
ANT	4+3																																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																																		
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5634.22</td><td>55.33</td><td>68.20</td><td>-12.87</td><td>44.37</td><td>33.03</td><td>11.23</td><td>33.30</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr><tr><td>2</td><td>5651.04</td><td>54.27</td><td>68.97</td><td>-14.70</td><td>43.36</td><td>33.01</td><td>11.22</td><td>33.32</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr><tr><td>3</td><td>5700.60</td><td>55.18</td><td>105.37</td><td>-50.19</td><td>44.04</td><td>33.31</td><td>11.20</td><td>33.37</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>54.70</td><td>110.95</td><td>-56.25</td><td>43.40</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5634.22	55.33	68.20	-12.87	44.37	33.03	11.23	33.30	0.00	300	241	PEAK	2	5651.04	54.27	68.97	-14.70	43.36	33.01	11.22	33.32	0.00	300	241	PEAK	3	5700.60	55.18	105.37	-50.19	44.04	33.31	11.20	33.37	0.00	300	241	PEAK	4	5720.07	54.70	110.95	-56.25	43.40	33.50	11.19	33.39	0.00	300	241	PEAK	 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>104.44</td><td>-----</td><td>-----</td><td>92.48</td><td>34.14</td><td>11.35</td><td>33.53</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5865.00	104.44	-----	-----	92.48	34.14	11.35	33.53	0.00	300	241	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5634.22	55.33	68.20	-12.87	44.37	33.03	11.23	33.30	0.00	300	241	PEAK																																																																																																																													
2	5651.04	54.27	68.97	-14.70	43.36	33.01	11.22	33.32	0.00	300	241	PEAK																																																																																																																													
3	5700.60	55.18	105.37	-50.19	44.04	33.31	11.20	33.37	0.00	300	241	PEAK																																																																																																																													
4	5720.07	54.70	110.95	-56.25	43.40	33.50	11.19	33.39	0.00	300	241	PEAK																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5865.00	104.44	-----	-----	92.48	34.14	11.35	33.53	0.00	300	241	PEAK																																																																																																																													
Avg.	Blank						 Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>99.16</td><td>-----</td><td>-----</td><td>87.17</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>300</td><td>241</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5865.00	99.16	-----	-----	87.17	34.16	11.37	33.54	0.00	300	241	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5865.00	99.16	-----	-----	87.17	34.16	11.37	33.54	0.00	300	241	AVERAGE																																																																																																																													





Mode	44																																																					
	Band Edge - R																																																					
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																					
ANT	4+3																																																					
Pol.	Horizontal	Fundamental																																																				
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.00</td><td>57.81</td><td>89.66</td><td>-31.85</td><td>45.49</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr><tr><td>2</td><td>5928.75</td><td>56.75</td><td>88.20</td><td>-31.45</td><td>44.41</td><td>34.36</td><td>11.58</td><td>33.60</td><td>0.00</td><td>300</td><td>241</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5923.00	57.81	89.66	-31.85	45.49	34.35	11.56	33.59	0.00	300	241	PEAK	2	5928.75	56.75	88.20	-31.45	44.41	34.36	11.58	33.60	0.00	300	241	PEAK	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	5923.00	57.81	89.66	-31.85	45.49	34.35	11.56	33.59	0.00	300	241	PEAK																																										
2	5928.75	56.75	88.20	-31.45	44.41	34.36	11.58	33.60	0.00	300	241	PEAK																																										
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>47.60</td><td>68.38</td><td>-20.78</td><td>35.27</td><td>34.35</td><td>11.57</td><td>33.59</td><td>0.00</td><td>300</td><td>241</td><td>AVERAGE</td></tr><tr><td>2</td><td>5927.75</td><td>47.60</td><td>68.20</td><td>-20.60</td><td>35.26</td><td>34.36</td><td>11.58</td><td>33.60</td><td>0.00</td><td>300</td><td>241</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.75	47.60	68.38	-20.78	35.27	34.35	11.57	33.59	0.00	300	241	AVERAGE	2	5927.75	47.60	68.20	-20.60	35.26	34.36	11.58	33.60	0.00	300	241	AVERAGE	Blank
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																											
1	5924.75	47.60	68.38	-20.78	35.27	34.35	11.57	33.59	0.00	300	241	AVERAGE																																										
2	5927.75	47.60	68.20	-20.60	35.26	34.36	11.58	33.60	0.00	300	241	AVERAGE																																										





		44																																																																																																																							
Mode	Band Edge - L																																																																																																																								
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																								
ANT	4+3																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5637.47</td><td>54.72</td><td>68.20</td><td>-13.48</td><td>43.77</td><td>33.03</td><td>11.23</td><td>33.31</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>54.29</td><td>68.53</td><td>-14.24</td><td>43.39</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr><tr><td>3</td><td>5700.01</td><td>54.01</td><td>105.20</td><td>-51.19</td><td>42.88</td><td>33.30</td><td>11.20</td><td>33.37</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr><tr><td>4</td><td>5720.36</td><td>54.25</td><td>111.62</td><td>-57.37</td><td>42.95</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5637.47	54.72	68.20	-13.48	43.77	33.03	11.23	33.31	0.00	253	0	PEAK	2	5650.45	54.29	68.53	-14.24	43.39	33.00	11.22	33.32	0.00	253	0	PEAK	3	5700.01	54.01	105.20	-51.19	42.88	33.30	11.20	33.37	0.00	253	0	PEAK	4	5720.36	54.25	111.62	-57.37	42.95	33.50	11.19	33.39	0.00	253	0	PEAK	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>97.67</td><td>-----</td><td>-----</td><td>85.71</td><td>34.14</td><td>11.35</td><td>33.53</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5865.00	97.67	-----	-----	85.71	34.14	11.35	33.53	0.00	253	0	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5637.47	54.72	68.20	-13.48	43.77	33.03	11.23	33.31	0.00	253	0	PEAK																																																																																																													
2	5650.45	54.29	68.53	-14.24	43.39	33.00	11.22	33.32	0.00	253	0	PEAK																																																																																																													
3	5700.01	54.01	105.20	-51.19	42.88	33.30	11.20	33.37	0.00	253	0	PEAK																																																																																																													
4	5720.36	54.25	111.62	-57.37	42.95	33.50	11.19	33.39	0.00	253	0	PEAK																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5865.00	97.67	-----	-----	85.71	34.14	11.35	33.53	0.00	253	0	PEAK																																																																																																													
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5865.00</td><td>90.70</td><td>-----</td><td>-----</td><td>78.71</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>253</td><td>0</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5865.00	90.70	-----	-----	78.71	34.16	11.37	33.54	0.00	253	0	AVERAGE																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5865.00	90.70	-----	-----	78.71	34.16	11.37	33.54	0.00	253	0	AVERAGE																																																																																																													







Mode	44																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																										
ANT	4+3																																																										
Pol.	Vertical	Fundamental																																																									
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.25</td><td>55.52</td><td>88.75</td><td>-33.23</td><td>43.20</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5976.75</td><td>56.09</td><td>88.20</td><td>-32.11</td><td>43.72</td><td>34.29</td><td>11.73</td><td>33.65</td><td>0.00</td><td>253</td><td>0</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.25	55.52	88.75	-33.23	43.20	34.35	11.56	33.59	0.00	253	0	PEAK	2	5976.75	56.09	88.20	-32.11	43.72	34.29	11.73	33.65	0.00	253	0	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5924.25	55.52	88.75	-33.23	43.20	34.35	11.56	33.59	0.00	253	0	PEAK																																															
2	5976.75	56.09	88.20	-32.11	43.72	34.29	11.73	33.65	0.00	253	0	PEAK																																															
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>46.46</td><td>68.20</td><td>-21.74</td><td>34.14</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>253</td><td>0</td><td>AVERAGE</td></tr><tr><td>2</td><td>5926.75</td><td>46.67</td><td>68.20</td><td>-21.53</td><td>34.35</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>253</td><td>0</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	46.46	68.20	-21.74	34.14	34.35	11.57	33.60	0.00	253	0	AVERAGE	2	5926.75	46.67	68.20	-21.53	34.35	34.35	11.57	33.60	0.00	253	0	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5925.00	46.46	68.20	-21.74	34.14	34.35	11.57	33.60	0.00	253	0	AVERAGE																																															
2	5926.75	46.67	68.20	-21.53	34.35	34.35	11.57	33.60	0.00	253	0	AVERAGE																																															






Mode	44																																																																																																																																																																																		
	Harmonic																																																																																																																																																																																		
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz																																																																																																																																																																																		
ANT	4+3																																																																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																																																																												
Peak Avg.																																																																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																																																																																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11730.00</td><td>51.21</td><td>74.00</td><td>-22.79</td><td>59.69</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>211</td><td>73</td><td>PEAK</td></tr><tr><td>2</td><td>11730.00</td><td>42.21</td><td>54.00</td><td>-11.79</td><td>50.69</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>211</td><td>73</td><td>Average</td></tr><tr><td>3</td><td>17595.00</td><td>54.70</td><td>88.20</td><td>-33.50</td><td>59.73</td><td>39.09</td><td>23.34</td><td>68.04</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11730.00	51.21	74.00	-22.79	59.69	38.80	18.87	66.46	0.31	211	73	PEAK	2	11730.00	42.21	54.00	-11.79	50.69	38.80	18.87	66.46	0.31	211	73	Average	3	17595.00	54.70	88.20	-33.50	59.73	39.09	23.34	68.04	0.58	--	--	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11730.00</td><td>50.65</td><td>74.00</td><td>-23.35</td><td>59.13</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>177</td><td>46</td><td>PEAK</td></tr><tr><td>2</td><td>11730.00</td><td>41.65</td><td>54.00</td><td>-12.35</td><td>50.13</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>177</td><td>46</td><td>Average</td></tr><tr><td>3</td><td>17595.00</td><td>53.93</td><td>88.20</td><td>-34.27</td><td>58.96</td><td>39.09</td><td>23.34</td><td>68.04</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11730.00	50.65	74.00	-23.35	59.13	38.80	18.87	66.46	0.31	177	46	PEAK	2	11730.00	41.65	54.00	-12.35	50.13	38.80	18.87	66.46	0.31	177	46	Average	3	17595.00	53.93	88.20	-34.27	58.96	39.09	23.34	68.04	0.58	--	--	PEAK
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11730.00	51.21	74.00	-22.79	59.69	38.80	18.87	66.46	0.31	211	73	PEAK																																																																																																																																																																							
2	11730.00	42.21	54.00	-11.79	50.69	38.80	18.87	66.46	0.31	211	73	Average																																																																																																																																																																							
3	17595.00	54.70	88.20	-33.50	59.73	39.09	23.34	68.04	0.58	--	--	PEAK																																																																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11730.00	50.65	74.00	-23.35	59.13	38.80	18.87	66.46	0.31	177	46	PEAK																																																																																																																																																																							
2	11730.00	41.65	54.00	-12.35	50.13	38.80	18.87	66.46	0.31	177	46	Average																																																																																																																																																																							
3	17595.00	53.93	88.20	-34.27	58.96	39.09	23.34	68.04	0.58	--	--	PEAK																																																																																																																																																																							





Mode	44	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH173_5865MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






Mode	45																																																																																																																																														
	Band Edge - L																																																																																																																																														
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																																																																																														
ANT	4+3																																																																																																																																														
Pol.	Horizontal						Fundamental																																																																																																																																								
Peak																																																																																																																																															
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5617.11</td><td>55.12</td><td>68.20</td><td>-13.08</td><td>44.11</td><td>33.07</td><td>11.23</td><td>33.29</td><td>0.00</td><td>206</td><td>360 PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>53.91</td><td>68.53</td><td>-14.62</td><td>43.01</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>206</td><td>360 PEAK</td></tr><tr><td>3</td><td>5701.19</td><td>53.86</td><td>105.53</td><td>-51.67</td><td>42.72</td><td>33.31</td><td>11.20</td><td>33.37</td><td>0.00</td><td>206</td><td>360 PEAK</td></tr><tr><td>4</td><td>5720.36</td><td>53.67</td><td>111.62</td><td>-57.95</td><td>42.37</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>206</td><td>360 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5617.11	55.12	68.20	-13.08	44.11	33.07	11.23	33.29	0.00	206	360 PEAK	2	5650.45	53.91	68.53	-14.62	43.01	33.00	11.22	33.32	0.00	206	360 PEAK	3	5701.19	53.86	105.53	-51.67	42.72	33.31	11.20	33.37	0.00	206	360 PEAK	4	5720.36	53.67	111.62	-57.95	42.37	33.50	11.19	33.39	0.00	206	360 PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>102.30</td><td>-----</td><td>-----</td><td>90.23</td><td>34.21</td><td>11.41</td><td>33.55</td><td>0.00</td><td>206</td><td>360 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5885.00	102.30	-----	-----	90.23	34.21	11.41	33.55	0.00	206
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5617.11	55.12	68.20	-13.08	44.11	33.07	11.23	33.29	0.00	206	360 PEAK																																																																																																																																				
2	5650.45	53.91	68.53	-14.62	43.01	33.00	11.22	33.32	0.00	206	360 PEAK																																																																																																																																				
3	5701.19	53.86	105.53	-51.67	42.72	33.31	11.20	33.37	0.00	206	360 PEAK																																																																																																																																				
4	5720.36	53.67	111.62	-57.95	42.37	33.50	11.19	33.39	0.00	206	360 PEAK																																																																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5885.00	102.30	-----	-----	90.23	34.21	11.41	33.55	0.00	206	360 PEAK																																																																																																																																				
Avg.	Blank																																																																																																																																														
							Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>96.47</td><td>-----</td><td>-----</td><td>84.35</td><td>34.24</td><td>11.43</td><td>33.55</td><td>0.00</td><td>206</td><td>360 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5885.00	96.47	-----	-----	84.35	34.24	11.43	33.55	0.00	206	360 AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																					
1	5885.00	96.47	-----	-----	84.35	34.24	11.43	33.55	0.00	206	360 AVERAGE																																																																																																																																				



Mode	45																																																																			
	Band Edge - R																																																																			
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																			
ANT	4+3																																																																			
Pol.	Horizontal						Fundamental																																																													
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5895.25</td><td>87.04</td><td>110.02</td><td>-22.98</td><td>74.06</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>206</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5925.25</td><td>62.62</td><td>88.20</td><td>-25.58</td><td>50.30</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>206</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5895.25	87.04	110.02	-22.98	74.06	34.28	11.47	33.57	0.00	206	360	PEAK	2	5925.25	62.62	88.20	-25.58	50.30	34.35	11.57	33.60	0.00	206	360	PEAK	Blank				
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																										
1	5895.25	87.04	110.02	-22.98	74.06	34.28	11.47	33.57	0.00	206	360	PEAK																																																								
2	5925.25	62.62	88.20	-25.58	50.30	34.35	11.57	33.60	0.00	206	360	PEAK																																																								
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5895.25</td><td>77.24</td><td>90.02</td><td>-12.78</td><td>65.06</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>206</td><td>360</td><td>AVERAGE</td></tr><tr><td>2</td><td>5926.00</td><td>53.28</td><td>68.20</td><td>-14.92</td><td>40.96</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>206</td><td>360</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	5895.25	77.24	90.02	-12.78	65.06	34.28	11.47	33.57	0.00	206	360	AVERAGE	2	5926.00	53.28	68.20	-14.92	40.96	34.35	11.57	33.60	0.00	206	360	AVERAGE	Blank				
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																										
1	5895.25	77.24	90.02	-12.78	65.06	34.28	11.47	33.57	0.00	206	360	AVERAGE																																																								
2	5926.00	53.28	68.20	-14.92	40.96	34.35	11.57	33.60	0.00	206	360	AVERAGE																																																								





Mode	45																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																																																																																																									
ANT	4+3																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5639.83</td><td>55.16</td><td>68.20</td><td>-13.04</td><td>44.23</td><td>33.02</td><td>11.22</td><td>33.31</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>54.33</td><td>68.31</td><td>-13.98</td><td>43.43</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr><tr><td>3</td><td>5701.19</td><td>54.02</td><td>105.53</td><td>-51.51</td><td>42.88</td><td>33.31</td><td>11.20</td><td>33.37</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>53.80</td><td>110.95</td><td>-57.15</td><td>42.50</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5639.83	55.16	68.20	-13.04	44.23	33.02	11.22	33.31	0.00	200	25	PEAK	2	5650.15	54.33	68.31	-13.98	43.43	33.00	11.22	33.32	0.00	200	25	PEAK	3	5701.19	54.02	105.53	-51.51	42.88	33.31	11.20	33.37	0.00	200	25	PEAK	4	5720.07	53.80	110.95	-57.15	42.50	33.50	11.19	33.39	0.00	200	25	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>104.89</td><td>-----</td><td>-----</td><td>92.77</td><td>34.24</td><td>11.43</td><td>33.55</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5885.00	104.89	-----	-----	92.77	34.24	11.43	33.55	0.00	200	25
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																
1	5639.83	55.16	68.20	-13.04	44.23	33.02	11.22	33.31	0.00	200	25	PEAK																																																																																																																														
2	5650.15	54.33	68.31	-13.98	43.43	33.00	11.22	33.32	0.00	200	25	PEAK																																																																																																																														
3	5701.19	54.02	105.53	-51.51	42.88	33.31	11.20	33.37	0.00	200	25	PEAK																																																																																																																														
4	5720.07	53.80	110.95	-57.15	42.50	33.50	11.19	33.39	0.00	200	25	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																
1	5885.00	104.89	-----	-----	92.77	34.24	11.43	33.55	0.00	200	25	PEAK																																																																																																																														
Avg.	Blank																																																																																																																																									
							Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5885.00</td><td>99.23</td><td>-----</td><td>-----</td><td>87.11</td><td>34.24</td><td>11.43</td><td>33.55</td><td>0.00</td><td>200</td><td>25</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5885.00	99.23	-----	-----	87.11	34.24	11.43	33.55	0.00	200	25	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																
1	5885.00	99.23	-----	-----	87.11	34.24	11.43	33.55	0.00	200	25	AVERAGE																																																																																																																														







Mode	45																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz																																																										
ANT	4+3																																																										
Pol.	Vertical	Fundamental																																																									
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5904.50</td><td>83.01</td><td>103.22</td><td>-20.21</td><td>70.77</td><td>34.31</td><td>11.50</td><td>33.57</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr><tr><td>2</td><td>5925.00</td><td>63.09</td><td>88.20</td><td>-25.11</td><td>50.77</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>200</td><td>25</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5904.50	83.01	103.22	-20.21	70.77	34.31	11.50	33.57	0.00	200	25	PEAK	2	5925.00	63.09	88.20	-25.11	50.77	34.35	11.57	33.60	0.00	200	25	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5904.50	83.01	103.22	-20.21	70.77	34.31	11.50	33.57	0.00	200	25	PEAK																																															
2	5925.00	63.09	88.20	-25.11	50.77	34.35	11.57	33.60	0.00	200	25	PEAK																																															
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5899.50</td><td>77.57</td><td>86.89</td><td>-9.32</td><td>65.36</td><td>34.30</td><td>11.48</td><td>33.57</td><td>0.00</td><td>200</td><td>25</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.00</td><td>54.11</td><td>68.20</td><td>-14.09</td><td>41.79</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>200</td><td>25</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5899.50	77.57	86.89	-9.32	65.36	34.30	11.48	33.57	0.00	200	25	AVERAGE	2	5925.00	54.11	68.20	-14.09	41.79	34.35	11.57	33.60	0.00	200	25	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5899.50	77.57	86.89	-9.32	65.36	34.30	11.48	33.57	0.00	200	25	AVERAGE																																															
2	5925.00	54.11	68.20	-14.09	41.79	34.35	11.57	33.60	0.00	200	25	AVERAGE																																															






Mode	45																																																																																																																																																																																		
	Harmonic																																																																																																																																																																																		
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHZ																																																																																																																																																																																		
ANT	4+3																																																																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																																																																												
Peak Avg.																																																																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																																																																																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11770.00</td><td>51.71</td><td>74.00</td><td>-22.29</td><td>60.12</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>135</td><td>26</td><td>PEAK</td></tr><tr><td>2</td><td>11770.00</td><td>41.89</td><td>54.00</td><td>-12.11</td><td>50.30</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>135</td><td>26</td><td>Average</td></tr><tr><td>3</td><td>17655.00</td><td>54.18</td><td>88.20</td><td>-34.02</td><td>58.90</td><td>39.46</td><td>23.42</td><td>68.18</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11770.00	51.71	74.00	-22.29	60.12	38.76	18.96	66.44	0.31	135	26	PEAK	2	11770.00	41.89	54.00	-12.11	50.30	38.76	18.96	66.44	0.31	135	26	Average	3	17655.00	54.18	88.20	-34.02	58.90	39.46	23.42	68.18	0.58	--	--	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11770.00</td><td>51.29</td><td>74.00</td><td>-22.71</td><td>59.70</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>205</td><td>162</td><td>PEAK</td></tr><tr><td>2</td><td>11770.00</td><td>41.79</td><td>54.00</td><td>-12.21</td><td>50.20</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>205</td><td>162</td><td>Average</td></tr><tr><td>3</td><td>17655.00</td><td>53.86</td><td>88.20</td><td>-34.34</td><td>58.58</td><td>39.46</td><td>23.42</td><td>68.18</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11770.00	51.29	74.00	-22.71	59.70	38.76	18.96	66.44	0.31	205	162	PEAK	2	11770.00	41.79	54.00	-12.21	50.20	38.76	18.96	66.44	0.31	205	162	Average	3	17655.00	53.86	88.20	-34.34	58.58	39.46	23.42	68.18	0.58	--	--	PEAK
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11770.00	51.71	74.00	-22.29	60.12	38.76	18.96	66.44	0.31	135	26	PEAK																																																																																																																																																																							
2	11770.00	41.89	54.00	-12.11	50.30	38.76	18.96	66.44	0.31	135	26	Average																																																																																																																																																																							
3	17655.00	54.18	88.20	-34.02	58.90	39.46	23.42	68.18	0.58	--	--	PEAK																																																																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11770.00	51.29	74.00	-22.71	59.70	38.76	18.96	66.44	0.31	205	162	PEAK																																																																																																																																																																							
2	11770.00	41.79	54.00	-12.21	50.20	38.76	18.96	66.44	0.31	205	162	Average																																																																																																																																																																							
3	17655.00	53.86	88.20	-34.34	58.58	39.46	23.42	68.18	0.58	--	--	PEAK																																																																																																																																																																							



Mode	45	
	Harmonic	
	U-NII-4_5.85-5.895_802.11a_CH177_5885MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






Mode	46																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz																																																																																																																																										
ANT	4+3																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5600.26</td><td>55.55</td><td>68.20</td><td>-12.65</td><td>44.47</td><td>33.12</td><td>11.24</td><td>33.28</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>53.29</td><td>68.53</td><td>-15.24</td><td>42.19</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr><tr><td>3</td><td>5700.30</td><td>54.03</td><td>105.28</td><td>-51.25</td><td>42.60</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>53.33</td><td>110.95</td><td>-57.62</td><td>41.85</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5600.26	55.55	68.20	-12.65	44.47	33.12	11.24	33.28	0.00	400	217	PEAK	2	5650.45	53.29	68.53	-15.24	42.19	33.20	11.22	33.32	0.00	400	217	PEAK	3	5700.30	54.03	105.28	-51.25	42.60	33.60	11.20	33.37	0.00	400	217	PEAK	4	5720.07	53.33	110.95	-57.62	41.85	33.68	11.19	33.39	0.00	400	217	PEAK	 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>107.10</td><td>-----</td><td>-----</td><td>95.20</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5845.00	107.10	-----	-----	95.20	34.10	11.32	33.52	0.00	400	217	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5600.26	55.55	68.20	-12.65	44.47	33.12	11.24	33.28	0.00	400	217	PEAK																																																																																																																															
2	5650.45	53.29	68.53	-15.24	42.19	33.20	11.22	33.32	0.00	400	217	PEAK																																																																																																																															
3	5700.30	54.03	105.28	-51.25	42.60	33.60	11.20	33.37	0.00	400	217	PEAK																																																																																																																															
4	5720.07	53.33	110.95	-57.62	41.85	33.68	11.19	33.39	0.00	400	217	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5845.00	107.10	-----	-----	95.20	34.10	11.32	33.52	0.00	400	217	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>100.57</td><td>-----</td><td>-----</td><td>88.67</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>400</td><td>217</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5845.00	100.57	-----	-----	88.67	34.10	11.32	33.52	0.00	400	217	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5845.00	100.57	-----	-----	88.67	34.10	11.32	33.52	0.00	400	217	AVERAGE																																																																																																																															





Mode	46																																																																				
	Band Edge - R																																																																				
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz																																																																				
ANT	4+3																																																																				
Pol.	Horizontal						Fundamental																																																														
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.75</td><td>55.63</td><td>88.38</td><td>-32.75</td><td>43.35</td><td>34.30</td><td>11.57</td><td>33.59</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr><tr><td>2</td><td>5945.50</td><td>55.90</td><td>88.20</td><td>-32.30</td><td>43.59</td><td>34.30</td><td>11.63</td><td>33.62</td><td>0.00</td><td>400</td><td>217</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.75	55.63	88.38	-32.75	43.35	34.30	11.57	33.59	0.00	400	217	PEAK	2	5945.50	55.90	88.20	-32.30	43.59	34.30	11.63	33.62	0.00	400	217	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																											
1	5924.75	55.63	88.38	-32.75	43.35	34.30	11.57	33.59	0.00	400	217	PEAK																																																									
2	5945.50	55.90	88.20	-32.30	43.59	34.30	11.63	33.62	0.00	400	217	PEAK																																																									
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.75</td><td>47.50</td><td>68.38</td><td>-20.88</td><td>35.22</td><td>34.30</td><td>11.57</td><td>33.59</td><td>0.00</td><td>400</td><td>217</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.25</td><td>47.45</td><td>68.20</td><td>-20.75</td><td>35.18</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>400</td><td>217</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.75	47.50	68.38	-20.88	35.22	34.30	11.57	33.59	0.00	400	217	AVERAGE	2	5925.25	47.45	68.20	-20.75	35.18	34.30	11.57	33.60	0.00	400	217	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																											
1	5924.75	47.50	68.38	-20.88	35.22	34.30	11.57	33.59	0.00	400	217	AVERAGE																																																									
2	5925.25	47.45	68.20	-20.75	35.18	34.30	11.57	33.60	0.00	400	217	AVERAGE																																																									





		46																																																																																																																																		
Mode	Band Edge - L																																																																																																																																			
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz																																																																																																																																			
ANT	4+3																																																																																																																																			
Pol.	Vertical						Fundamental																																																																																																																													
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5632.45</td><td>55.58</td><td>68.20</td><td>-12.62</td><td>44.49</td><td>33.16</td><td>11.23</td><td>33.30</td><td>0.00</td><td>300 201 PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>53.38</td><td>68.53</td><td>-15.15</td><td>42.28</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>300 201 PEAK</td></tr><tr><td>3</td><td>5701.19</td><td>53.76</td><td>105.53</td><td>-51.77</td><td>42.33</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>300 201 PEAK</td></tr><tr><td>4</td><td>5720.36</td><td>54.16</td><td>111.62</td><td>-57.46</td><td>42.68</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>300 201 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5632.45	55.58	68.20	-12.62	44.49	33.16	11.23	33.30	0.00	300 201 PEAK	2	5650.45	53.38	68.53	-15.15	42.28	33.20	11.22	33.32	0.00	300 201 PEAK	3	5701.19	53.76	105.53	-51.77	42.33	33.60	11.20	33.37	0.00	300 201 PEAK	4	5720.36	54.16	111.62	-57.46	42.68	33.68	11.19	33.39	0.00	300 201 PEAK	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>108.51</td><td>-----</td><td>-----</td><td>96.61</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>300 201 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	108.51	-----	-----	96.61	34.10	11.32	33.52	0.00	300 201 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	5632.45	55.58	68.20	-12.62	44.49	33.16	11.23	33.30	0.00	300 201 PEAK																																																																																																																										
2	5650.45	53.38	68.53	-15.15	42.28	33.20	11.22	33.32	0.00	300 201 PEAK																																																																																																																										
3	5701.19	53.76	105.53	-51.77	42.33	33.60	11.20	33.37	0.00	300 201 PEAK																																																																																																																										
4	5720.36	54.16	111.62	-57.46	42.68	33.68	11.19	33.39	0.00	300 201 PEAK																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	5845.00	108.51	-----	-----	96.61	34.10	11.32	33.52	0.00	300 201 PEAK																																																																																																																										
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>101.76</td><td>-----</td><td>-----</td><td>89.86</td><td>34.10</td><td>11.32</td><td>33.52</td><td>0.00</td><td>300 201 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	101.76	-----	-----	89.86	34.10	11.32	33.52	0.00	300 201 AVERAGE																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	5845.00	101.76	-----	-----	89.86	34.10	11.32	33.52	0.00	300 201 AVERAGE																																																																																																																										



Mode	46																																																																			
	Band Edge - R																																																																			
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz																																																																			
ANT	4+3																																																																			
Pol.	Vertical						Fundamental																																																													
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.00</td><td>56.67</td><td>88.93</td><td>-32.26</td><td>44.40</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>300</td><td>201</td><td>PEAK</td></tr><tr><td>2</td><td>5925.25</td><td>56.39</td><td>88.20</td><td>-31.81</td><td>44.12</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>201</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.00	56.67	88.93	-32.26	44.40	34.30	11.56	33.59	0.00	300	201	PEAK	2	5925.25	56.39	88.20	-31.81	44.12	34.30	11.57	33.60	0.00	300	201	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																										
1	5924.00	56.67	88.93	-32.26	44.40	34.30	11.56	33.59	0.00	300	201	PEAK																																																								
2	5925.25	56.39	88.20	-31.81	44.12	34.30	11.57	33.60	0.00	300	201	PEAK																																																								
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>48.07</td><td>68.20</td><td>-20.13</td><td>35.00</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>201</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.00</td><td>48.07</td><td>68.20</td><td>-20.13</td><td>35.00</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>201</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	48.07	68.20	-20.13	35.00	34.30	11.57	33.60	0.00	300	201	AVERAGE	2	5925.00	48.07	68.20	-20.13	35.00	34.30	11.57	33.60	0.00	300	201	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																										
1	5925.00	48.07	68.20	-20.13	35.00	34.30	11.57	33.60	0.00	300	201	AVERAGE																																																								
2	5925.00	48.07	68.20	-20.13	35.00	34.30	11.57	33.60	0.00	300	201	AVERAGE																																																								






Mode	46																																																																																																																																																																																		
	Harmonic																																																																																																																																																																																		
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz																																																																																																																																																																																		
ANT	4+3																																																																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																																																																												
Peak Avg.																																																																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																																																																																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>11690.00</td><td>50.85</td><td>74.00</td><td>-23.15</td><td>59.46</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>133</td><td>26</td><td>PEAK</td></tr><tr><td>2</td><td>11690.00</td><td>41.10</td><td>54.00</td><td>-12.90</td><td>49.71</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>133</td><td>26</td><td>Average</td></tr><tr><td>3</td><td>17535.00</td><td>54.08</td><td>88.20</td><td>-34.12</td><td>59.27</td><td>38.88</td><td>23.27</td><td>67.91</td><td>0.57</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg			1	11690.00	50.85	74.00	-23.15	59.46	38.76	18.79	66.47	0.31	133	26	PEAK	2	11690.00	41.10	54.00	-12.90	49.71	38.76	18.79	66.47	0.31	133	26	Average	3	17535.00	54.08	88.20	-34.12	59.27	38.88	23.27	67.91	0.57	--	--	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>11690.00</td><td>50.59</td><td>74.00</td><td>-23.41</td><td>59.20</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>207</td><td>165</td><td>PEAK</td></tr><tr><td>2</td><td>11690.00</td><td>40.76</td><td>54.00</td><td>-13.24</td><td>49.37</td><td>38.76</td><td>18.79</td><td>66.47</td><td>0.31</td><td>207</td><td>165</td><td>Average</td></tr><tr><td>3</td><td>17535.00</td><td>53.88</td><td>88.20</td><td>-34.32</td><td>59.07</td><td>38.88</td><td>23.27</td><td>67.91</td><td>0.57</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg			1	11690.00	50.59	74.00	-23.41	59.20	38.76	18.79	66.47	0.31	207	165	PEAK	2	11690.00	40.76	54.00	-13.24	49.37	38.76	18.79	66.47	0.31	207	165	Average	3	17535.00	53.88	88.20	-34.32	59.07	38.88	23.27	67.91	0.57	--	--	PEAK
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																									
1	11690.00	50.85	74.00	-23.15	59.46	38.76	18.79	66.47	0.31	133	26	PEAK																																																																																																																																																																							
2	11690.00	41.10	54.00	-12.90	49.71	38.76	18.79	66.47	0.31	133	26	Average																																																																																																																																																																							
3	17535.00	54.08	88.20	-34.12	59.27	38.88	23.27	67.91	0.57	--	--	PEAK																																																																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																									
1	11690.00	50.59	74.00	-23.41	59.20	38.76	18.79	66.47	0.31	207	165	PEAK																																																																																																																																																																							
2	11690.00	40.76	54.00	-13.24	49.37	38.76	18.79	66.47	0.31	207	165	Average																																																																																																																																																																							
3	17535.00	53.88	88.20	-34.32	59.07	38.88	23.27	67.91	0.57	--	--	PEAK																																																																																																																																																																							



Mode	46	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Full RU_5845MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL



Mode	47																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz																																																																																																																																										
ANT	4+3																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5611.21</td><td>54.88</td><td>68.20</td><td>-13.32</td><td>43.00</td><td>33.12</td><td>11.24</td><td>33.28</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>54.38</td><td>68.53</td><td>-14.15</td><td>43.28</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr><tr><td>3</td><td>5700.89</td><td>54.84</td><td>105.45</td><td>-50.61</td><td>43.41</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>54.14</td><td>110.95</td><td>-56.81</td><td>42.66</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5611.21	54.88	68.20	-13.32	43.00	33.12	11.24	33.28	0.00	296	360	PEAK	2	5650.45	54.38	68.53	-14.15	43.28	33.20	11.22	33.32	0.00	296	360	PEAK	3	5700.89	54.84	105.45	-50.61	43.41	33.60	11.20	33.37	0.00	296	360	PEAK	4	5720.07	54.14	110.95	-56.81	42.66	33.68	11.19	33.39	0.00	296	360	PEAK	 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>103.16</td><td>-----</td><td>-----</td><td>91.17</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5865.00	103.16	-----	-----	91.17	34.16	11.37	33.54	0.00	296	360	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5611.21	54.88	68.20	-13.32	43.00	33.12	11.24	33.28	0.00	296	360	PEAK																																																																																																																															
2	5650.45	54.38	68.53	-14.15	43.28	33.20	11.22	33.32	0.00	296	360	PEAK																																																																																																																															
3	5700.89	54.84	105.45	-50.61	43.41	33.60	11.20	33.37	0.00	296	360	PEAK																																																																																																																															
4	5720.07	54.14	110.95	-56.81	42.66	33.68	11.19	33.39	0.00	296	360	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5865.00	103.16	-----	-----	91.17	34.16	11.37	33.54	0.00	296	360	PEAK																																																																																																																															
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>97.29</td><td>-----</td><td>-----</td><td>85.30</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>296</td><td>360</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5865.00	97.29	-----	-----	85.30	34.16	11.37	33.54	0.00	296	360	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5865.00	97.29	-----	-----	85.30	34.16	11.37	33.54	0.00	296	360	AVERAGE																																																																																																																															





Mode	47																																																															
	Band Edge - R																																																															
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz																																																															
ANT	4+3																																																															
Pol.	Horizontal					Fundamental																																																										
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.00</td><td>58.17</td><td>88.93</td><td>-30.76</td><td>45.90</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5933.00</td><td>57.39</td><td>88.20</td><td>-30.81</td><td>45.10</td><td>34.30</td><td>11.59</td><td>33.60</td><td>0.00</td><td>296</td><td>360</td><td>PEAK</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.00	58.17	88.93	-30.76	45.90	34.30	11.56	33.59	0.00	296	360	PEAK	2	5933.00	57.39	88.20	-30.81	45.10	34.30	11.59	33.60	0.00	296	360	PEAK	Blank				
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																				
1	5924.00	58.17	88.93	-30.76	45.90	34.30	11.56	33.59	0.00	296	360	PEAK																																																				
2	5933.00	57.39	88.20	-30.81	45.10	34.30	11.59	33.60	0.00	296	360	PEAK																																																				
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5924.50</td><td>48.58</td><td>68.57</td><td>-19.99</td><td>36.31</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>296</td><td>360</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.50</td><td>48.59</td><td>68.20</td><td>-19.61</td><td>36.32</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>296</td><td>360</td><td>AVERAGE</td></tr></tbody></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.50	48.58	68.57	-19.99	36.31	34.30	11.56	33.59	0.00	296	360	AVERAGE	2	5925.50	48.59	68.20	-19.61	36.32	34.30	11.57	33.60	0.00	296	360	AVERAGE	Blank				
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																				
1	5924.50	48.58	68.57	-19.99	36.31	34.30	11.56	33.59	0.00	296	360	AVERAGE																																																				
2	5925.50	48.59	68.20	-19.61	36.32	34.30	11.57	33.60	0.00	296	360	AVERAGE																																																				





		47																																																																																																																																																							
Mode	Band Edge - L																																																																																																																																																								
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz																																																																																																																																																								
ANT	4+3																																																																																																																																																								
Pol.	Vertical																																																																																																																																																								
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5631.57</td><td>55.40</td><td>68.20</td><td>-12.80</td><td>44.31</td><td>33.16</td><td>11.23</td><td>33.30</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>53.83</td><td>68.31</td><td>-14.48</td><td>42.73</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td></tr><tr><td>3</td><td>5701.19</td><td>53.94</td><td>105.53</td><td>-51.59</td><td>42.51</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>53.06</td><td>110.95</td><td>-57.89</td><td>41.58</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5631.57	55.40	68.20	-12.80	44.31	33.16	11.23	33.30	0.00	300	189	PEAK	2	5650.15	53.83	68.31	-14.48	42.73	33.20	11.22	33.32	0.00	300	189	PEAK	3	5701.19	53.94	105.53	-51.59	42.51	33.60	11.20	33.37	0.00	300	189	PEAK	4	5720.07	53.06	110.95	-57.89	41.58	33.68	11.19	33.39	0.00	300	189	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>109.94</td><td>-----</td><td>-----</td><td>97.95</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5865.00	109.94	-----	-----	97.95	34.16	11.37	33.54	0.00	300	189	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5631.57	55.40	68.20	-12.80	44.31	33.16	11.23	33.30	0.00	300	189	PEAK																																																																																																																																													
2	5650.15	53.83	68.31	-14.48	42.73	33.20	11.22	33.32	0.00	300	189	PEAK																																																																																																																																													
3	5701.19	53.94	105.53	-51.59	42.51	33.60	11.20	33.37	0.00	300	189	PEAK																																																																																																																																													
4	5720.07	53.06	110.95	-57.89	41.58	33.68	11.19	33.39	0.00	300	189	PEAK																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5865.00	109.94	-----	-----	97.95	34.16	11.37	33.54	0.00	300	189	PEAK																																																																																																																																													
Avg.	Blank											Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5865.00</td><td>101.71</td><td>-----</td><td>-----</td><td>89.72</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>300</td><td>189</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5865.00	101.71	-----	-----	89.72	34.16	11.37	33.54	0.00	300	189	AVERAGE																																																																																					
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5865.00	101.71	-----	-----	89.72	34.16	11.37	33.54	0.00	300	189	AVERAGE																																																																																																																																													



Mode	47																																																									
	Band Edge - R																																																									
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz																																																									
ANT	4+3																																																									
Pol.	Vertical	Fundamental																																																								
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.50</td><td>60.04</td><td>88.57</td><td>-28.53</td><td>47.77</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td><td></td></tr><tr><td>2</td><td>5926.25</td><td>59.94</td><td>88.20</td><td>-28.26</td><td>47.67</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>189</td><td>PEAK</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.50	60.04	88.57	-28.53	47.77	34.30	11.56	33.59	0.00	300	189	PEAK		2	5926.25	59.94	88.20	-28.26	47.67	34.30	11.57	33.60	0.00	300	189	PEAK		Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5924.50	60.04	88.57	-28.53	47.77	34.30	11.56	33.59	0.00	300	189	PEAK																																														
2	5926.25	59.94	88.20	-28.26	47.67	34.30	11.57	33.60	0.00	300	189	PEAK																																														
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.75</td><td>50.68</td><td>68.38</td><td>-17.70</td><td>38.40</td><td>34.30</td><td>11.57</td><td>33.59</td><td>0.00</td><td>300</td><td>189</td><td>AVERAGE</td><td></td></tr><tr><td>2</td><td>5925.00</td><td>50.40</td><td>68.20</td><td>-17.00</td><td>38.13</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>189</td><td>AVERAGE</td><td></td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.75	50.68	68.38	-17.70	38.40	34.30	11.57	33.59	0.00	300	189	AVERAGE		2	5925.00	50.40	68.20	-17.00	38.13	34.30	11.57	33.60	0.00	300	189	AVERAGE		Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5924.75	50.68	68.38	-17.70	38.40	34.30	11.57	33.59	0.00	300	189	AVERAGE																																														
2	5925.00	50.40	68.20	-17.00	38.13	34.30	11.57	33.60	0.00	300	189	AVERAGE																																														



Mode	47																																																																																																																																																											
	Harmonic																																																																																																																																																											
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz																																																																																																																																																											
ANT	4+3																																																																																																																																																											
Pol.	Horizontal	Vertical																																																																																																																																																										
Peak Avg.	 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 11730.00</td><td>49.55</td><td>74.00</td><td>-24.45</td><td>58.03</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>135</td><td>28</td><td>PEAK</td><td></td></tr><tr><td>2 11730.00</td><td>40.04</td><td>54.00</td><td>-13.96</td><td>48.52</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>135</td><td>28</td><td>Average</td><td></td></tr><tr><td>3 17595.00</td><td>53.74</td><td>88.20</td><td>-34.46</td><td>58.77</td><td>39.09</td><td>23.34</td><td>68.04</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td><td></td></tr></table>			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg			1 11730.00	49.55	74.00	-24.45	58.03	38.80	18.87	66.46	0.31	135	28	PEAK		2 11730.00	40.04	54.00	-13.96	48.52	38.80	18.87	66.46	0.31	135	28	Average		3 17595.00	53.74	88.20	-34.46	58.77	39.09	23.34	68.04	0.58	--	--	PEAK		 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1 11730.00</td><td>49.47</td><td>74.00</td><td>-24.53</td><td>57.95</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>209</td><td>166</td><td>PEAK</td><td></td></tr><tr><td>2 11730.00</td><td>39.65</td><td>54.00</td><td>-14.35</td><td>48.13</td><td>38.80</td><td>18.87</td><td>66.46</td><td>0.31</td><td>209</td><td>166</td><td>Average</td><td></td></tr><tr><td>3 17595.00</td><td>54.03</td><td>88.20</td><td>-34.17</td><td>59.06</td><td>39.09</td><td>23.34</td><td>68.04</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td><td></td></tr></table>			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg			1 11730.00	49.47	74.00	-24.53	57.95	38.80	18.87	66.46	0.31	209	166	PEAK		2 11730.00	39.65	54.00	-14.35	48.13	38.80	18.87	66.46	0.31	209	166	Average		3 17595.00	54.03	88.20	-34.17	59.06	39.09	23.34	68.04	0.58	--	--	PEAK	
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																		
1 11730.00	49.55	74.00	-24.45	58.03	38.80	18.87	66.46	0.31	135	28	PEAK																																																																																																																																																	
2 11730.00	40.04	54.00	-13.96	48.52	38.80	18.87	66.46	0.31	135	28	Average																																																																																																																																																	
3 17595.00	53.74	88.20	-34.46	58.77	39.09	23.34	68.04	0.58	--	--	PEAK																																																																																																																																																	
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																		
1 11730.00	49.47	74.00	-24.53	57.95	38.80	18.87	66.46	0.31	209	166	PEAK																																																																																																																																																	
2 11730.00	39.65	54.00	-14.35	48.13	38.80	18.87	66.46	0.31	209	166	Average																																																																																																																																																	
3 17595.00	54.03	88.20	-34.17	59.06	39.09	23.34	68.04	0.58	--	--	PEAK																																																																																																																																																	





Mode	47	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE20_CH173_Full RU_5865MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






		48									
Mode	Band Edge - L										
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz										
ANT	4+3										
Pol.	Horizontal										
Peak	</										





Mode	48																																																														
	Band Edge - R																																																														
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz																																																														
ANT	4+3																																																														
Pol.	Horizontal						Fundamental																																																								
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5895.25</td><td>96.01</td><td>110.02</td><td>-14.01</td><td>83.83</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>135</td><td>27</td><td>PEAK</td></tr><tr><td>2</td><td>5925.00</td><td>66.36</td><td>88.20</td><td>-21.84</td><td>54.09</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>135</td><td>27</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5895.25	96.01	110.02	-14.01	83.83	34.28	11.47	33.57	0.00	135	27	PEAK	2	5925.00	66.36	88.20	-21.84	54.09	34.30	11.57	33.60	0.00	135	27	PEAK	Blank				
		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																				
1	5895.25	96.01	110.02	-14.01	83.83	34.28	11.47	33.57	0.00	135	27	PEAK																																																			
2	5925.00	66.36	88.20	-21.84	54.09	34.30	11.57	33.60	0.00	135	27	PEAK																																																			
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>5895.25</td><td>87.84</td><td>90.02</td><td>-2.18</td><td>75.66</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>135</td><td>27</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.25</td><td>58.13</td><td>68.20</td><td>-10.07</td><td>45.06</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>135</td><td>27</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5895.25	87.84	90.02	-2.18	75.66	34.28	11.47	33.57	0.00	135	27	AVERAGE	2	5925.25	58.13	68.20	-10.07	45.06	34.30	11.57	33.60	0.00	135	27	AVERAGE	Blank				
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																				
1	5895.25	87.84	90.02	-2.18	75.66	34.28	11.47	33.57	0.00	135	27	AVERAGE																																																			
2	5925.25	58.13	68.20	-10.07	45.06	34.30	11.57	33.60	0.00	135	27	AVERAGE																																																			





Mode	48																																																																																																																																															
	Band Edge - L																																																																																																																																															
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz																																																																																																																																															
ANT	4+3																																																																																																																																															
Pol.	Vertical						Fundamental																																																																																																																																									
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5629.21</td><td>55.38</td><td>68.20</td><td>-12.82</td><td>44.29</td><td>33.16</td><td>11.23</td><td>33.30</td><td>0.00</td><td>312</td><td>199 PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>54.37</td><td>68.53</td><td>-14.16</td><td>43.27</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>312</td><td>199 PEAK</td></tr><tr><td>3</td><td>5703.84</td><td>56.16</td><td>106.28</td><td>-50.12</td><td>44.71</td><td>33.62</td><td>11.20</td><td>33.37</td><td>0.00</td><td>312</td><td>199 PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>54.26</td><td>110.95</td><td>-56.69</td><td>42.78</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>312</td><td>199 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5629.21	55.38	68.20	-12.82	44.29	33.16	11.23	33.30	0.00	312	199 PEAK	2	5650.45	54.37	68.53	-14.16	43.27	33.20	11.22	33.32	0.00	312	199 PEAK	3	5703.84	56.16	106.28	-50.12	44.71	33.62	11.20	33.37	0.00	312	199 PEAK	4	5720.07	54.26	110.95	-56.69	42.78	33.68	11.19	33.39	0.00	312	199 PEAK	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5885.00</td><td>108.68</td><td>-----</td><td>-----</td><td>96.56</td><td>34.24</td><td>11.43</td><td>33.55</td><td>0.00</td><td>312</td><td>199 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5885.00	108.68	-----	-----	96.56	34.24	11.43	33.55	0.00	312	199 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5629.21	55.38	68.20	-12.82	44.29	33.16	11.23	33.30	0.00	312	199 PEAK																																																																																																																																					
2	5650.45	54.37	68.53	-14.16	43.27	33.20	11.22	33.32	0.00	312	199 PEAK																																																																																																																																					
3	5703.84	56.16	106.28	-50.12	44.71	33.62	11.20	33.37	0.00	312	199 PEAK																																																																																																																																					
4	5720.07	54.26	110.95	-56.69	42.78	33.68	11.19	33.39	0.00	312	199 PEAK																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5885.00	108.68	-----	-----	96.56	34.24	11.43	33.55	0.00	312	199 PEAK																																																																																																																																					
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="3">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5885.00</td><td>101.00</td><td>-----</td><td>-----</td><td>89.68</td><td>34.24</td><td>11.43</td><td>33.55</td><td>0.00</td><td>312</td><td>199 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	5885.00	101.00	-----	-----	89.68	34.24	11.43	33.55	0.00	312	199 AVERAGE																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																						
1	5885.00	101.00	-----	-----	89.68	34.24	11.43	33.55	0.00	312	199 AVERAGE																																																																																																																																					







Mode	48																																																			
	Band Edge - R																																																			
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz																																																			
ANT	4+3																																																			
Pol.	Vertical	Fundamental																																																		
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5895.25</td><td>91.40</td><td>110.02</td><td>-18.62</td><td>79.22</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>312 199 PEAK</td></tr><tr><td>2 5926.50</td><td>65.66</td><td>88.20</td><td>-22.54</td><td>53.39</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>312 199 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5895.25	91.40	110.02	-18.62	79.22	34.28	11.47	33.57	0.00	312 199 PEAK	2 5926.50	65.66	88.20	-22.54	53.39	34.30	11.57	33.60	0.00	312 199 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																											
1 5895.25	91.40	110.02	-18.62	79.22	34.28	11.47	33.57	0.00	312 199 PEAK																																											
2 5926.50	65.66	88.20	-22.54	53.39	34.30	11.57	33.60	0.00	312 199 PEAK																																											
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5895.25</td><td>84.18</td><td>90.02</td><td>-5.84</td><td>72.00</td><td>34.28</td><td>11.47</td><td>33.57</td><td>0.00</td><td>312 199 AVERAGE</td></tr><tr><td>2 5926.25</td><td>56.88</td><td>68.20</td><td>-11.32</td><td>44.61</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>312 199 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5895.25	84.18	90.02	-5.84	72.00	34.28	11.47	33.57	0.00	312 199 AVERAGE	2 5926.25	56.88	68.20	-11.32	44.61	34.30	11.57	33.60	0.00	312 199 AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																											
1 5895.25	84.18	90.02	-5.84	72.00	34.28	11.47	33.57	0.00	312 199 AVERAGE																																											
2 5926.25	56.88	68.20	-11.32	44.61	34.30	11.57	33.60	0.00	312 199 AVERAGE																																											






Mode	48																																																																																			
	Harmonic																																																																																			
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz																																																																																			
ANT	4+3																																																																																			
Pol.	Horizontal						Vertical																																																																													
Peak Avg.																																																																																				
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																													
<table><tr><th></th><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11770.00</td><td>50.21</td><td>74.00</td><td>-23.79</td><td>58.62</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>140</td><td>29</td><td>PEAK</td></tr><tr><td>2</td><td>11770.00</td><td>40.51</td><td>54.00</td><td>-13.49</td><td>48.92</td><td>38.76</td><td>18.96</td><td>66.44</td><td>0.31</td><td>140</td><td>29</td><td>Average</td></tr><tr><td>3</td><td>17655.00</td><td>53.40</td><td>88.20</td><td>-34.80</td><td>58.12</td><td>39.46</td><td>23.42</td><td>68.18</td><td>0.58</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	11770.00	50.21	74.00	-23.79	58.62	38.76	18.96	66.44	0.31	140	29	PEAK	2	11770.00	40.51	54.00	-13.49	48.92	38.76	18.96	66.44	0.31	140	29	Average	3	17655.00	53.40	88.20	-34.80	58.12	39.46	23.42	68.18	0.58	--	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																										
1	11770.00	50.21	74.00	-23.79	58.62	38.76	18.96	66.44	0.31	140	29	PEAK																																																																								
2	11770.00	40.51	54.00	-13.49	48.92	38.76	18.96	66.44	0.31	140	29	Average																																																																								
3	17655.00	53.40	88.20	-34.80	58.12	39.46	23.42	68.18	0.58	--	--	PEAK																																																																								





Mode	48	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE20_CH177_Full RU_5885MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






Mode	49																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz																																																																																																																																									
ANT	4+3																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5604.72</td><td>55.10</td><td>68.20</td><td>-13.10</td><td>44.04</td><td>33.09</td><td>11.24</td><td>33.27</td><td>0.00</td><td>100</td><td>240</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>53.88</td><td>68.31</td><td>-14.43</td><td>42.98</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>100</td><td>240</td><td>PEAK</td></tr><tr><td>3</td><td>5704.14</td><td>56.04</td><td>106.36</td><td>-50.32</td><td>44.87</td><td>33.34</td><td>11.20</td><td>33.37</td><td>0.00</td><td>100</td><td>240</td><td>PEAK</td></tr><tr><td>4</td><td>5720.36</td><td>55.75</td><td>111.62</td><td>-55.87</td><td>44.45</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>100</td><td>240</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5604.72	55.10	68.20	-13.10	44.04	33.09	11.24	33.27	0.00	100	240	PEAK	2	5650.15	53.88	68.31	-14.43	42.98	33.00	11.22	33.32	0.00	100	240	PEAK	3	5704.14	56.04	106.36	-50.32	44.87	33.34	11.20	33.37	0.00	100	240	PEAK	4	5720.36	55.75	111.62	-55.87	44.45	33.50	11.19	33.39	0.00	100	240	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5835.00</td><td>103.25</td><td>-----</td><td>-----</td><td>91.39</td><td>34.10</td><td>11.26</td><td>33.50</td><td>0.00</td><td>100</td><td>240</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5835.00	103.25	-----	-----	91.39	34.10	11.26	33.50	0.00	100	240
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5604.72	55.10	68.20	-13.10	44.04	33.09	11.24	33.27	0.00	100	240	PEAK																																																																																																																														
2	5650.15	53.88	68.31	-14.43	42.98	33.00	11.22	33.32	0.00	100	240	PEAK																																																																																																																														
3	5704.14	56.04	106.36	-50.32	44.87	33.34	11.20	33.37	0.00	100	240	PEAK																																																																																																																														
4	5720.36	55.75	111.62	-55.87	44.45	33.50	11.19	33.39	0.00	100	240	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5835.00	103.25	-----	-----	91.39	34.10	11.26	33.50	0.00	100	240	PEAK																																																																																																																														
Avg.	Blank																																																																																																																																									
						Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5835.00</td><td>97.47</td><td>-----</td><td>-----</td><td>85.61</td><td>34.10</td><td>11.26</td><td>33.50</td><td>0.00</td><td>100</td><td>240</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5835.00	97.47	-----	-----	85.61	34.10	11.26	33.50	0.00	100	240	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5835.00	97.47	-----	-----	85.61	34.10	11.26	33.50	0.00	100	240	AVERAGE																																																																																																																														



Mode	49																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz																																																										
ANT	4+3																																																										
Pol.	Horizontal	Fundamental																																																									
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5897.75</td><td>65.00</td><td>108.18</td><td>-43.18</td><td>52.00</td><td>34.29</td><td>11.48</td><td>33.57</td><td>0.00</td><td>100</td><td>240</td><td>Peak</td></tr><tr><td>2</td><td>5932.75</td><td>58.60</td><td>88.20</td><td>-29.60</td><td>46.24</td><td>34.37</td><td>11.59</td><td>33.60</td><td>0.00</td><td>100</td><td>240</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5897.75	65.00	108.18	-43.18	52.00	34.29	11.48	33.57	0.00	100	240	Peak	2	5932.75	58.60	88.20	-29.60	46.24	34.37	11.59	33.60	0.00	100	240	Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5897.75	65.00	108.18	-43.18	52.00	34.29	11.48	33.57	0.00	100	240	Peak																																															
2	5932.75	58.60	88.20	-29.60	46.24	34.37	11.59	33.60	0.00	100	240	Peak																																															
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5897.25</td><td>56.67</td><td>88.55</td><td>-31.88</td><td>44.47</td><td>34.29</td><td>11.48</td><td>33.57</td><td>0.00</td><td>100</td><td>240</td><td>Average</td></tr><tr><td>2</td><td>5927.50</td><td>49.67</td><td>68.20</td><td>-18.53</td><td>37.35</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>100</td><td>240</td><td>Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5897.25	56.67	88.55	-31.88	44.47	34.29	11.48	33.57	0.00	100	240	Average	2	5927.50	49.67	68.20	-18.53	37.35	34.35	11.57	33.60	0.00	100	240	Average	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5897.25	56.67	88.55	-31.88	44.47	34.29	11.48	33.57	0.00	100	240	Average																																															
2	5927.50	49.67	68.20	-18.53	37.35	34.35	11.57	33.60	0.00	100	240	Average																																															





		49																																																																																																																							
Mode	Band Edge - L																																																																																																																								
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz																																																																																																																								
ANT	4+3																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5625.00</td><td>55.27</td><td>68.20</td><td>-12.93</td><td>44.29</td><td>33.05</td><td>11.23</td><td>33.30</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>53.19</td><td>68.31</td><td>-15.12</td><td>42.29</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr><tr><td>3</td><td>5700.60</td><td>54.76</td><td>105.37</td><td>-50.61</td><td>43.62</td><td>33.31</td><td>11.20</td><td>33.37</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr><tr><td>4</td><td>5720.36</td><td>54.88</td><td>111.62</td><td>-56.74</td><td>43.58</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5625.00	55.27	68.20	-12.93	44.29	33.05	11.23	33.30	0.00	200	262	PEAK	2	5650.15	53.19	68.31	-15.12	42.29	33.00	11.22	33.32	0.00	200	262	PEAK	3	5700.60	54.76	105.37	-50.61	43.62	33.31	11.20	33.37	0.00	200	262	PEAK	4	5720.36	54.88	111.62	-56.74	43.58	33.50	11.19	33.39	0.00	200	262	PEAK	 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5835.00</td><td>97.33</td><td>-----</td><td>-----</td><td>85.46</td><td>34.10</td><td>11.28</td><td>33.51</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5835.00	97.33	-----	-----	85.46	34.10	11.28	33.51	0.00	200	262	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5625.00	55.27	68.20	-12.93	44.29	33.05	11.23	33.30	0.00	200	262	PEAK																																																																																																													
2	5650.15	53.19	68.31	-15.12	42.29	33.00	11.22	33.32	0.00	200	262	PEAK																																																																																																													
3	5700.60	54.76	105.37	-50.61	43.62	33.31	11.20	33.37	0.00	200	262	PEAK																																																																																																													
4	5720.36	54.88	111.62	-56.74	43.58	33.50	11.19	33.39	0.00	200	262	PEAK																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5835.00	97.33	-----	-----	85.46	34.10	11.28	33.51	0.00	200	262	PEAK																																																																																																													
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4) Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5835.00</td><td>91.36</td><td>-----</td><td>-----</td><td>79.50</td><td>34.10</td><td>11.26</td><td>33.50</td><td>0.00</td><td>200</td><td>262</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg	1	5835.00	91.36	-----	-----	79.50	34.10	11.26	33.50	0.00	200	262	AVERAGE																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																															
1	5835.00	91.36	-----	-----	79.50	34.10	11.26	33.50	0.00	200	262	AVERAGE																																																																																																													







Mode	49																																																													
	Band Edge - R																																																													
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz																																																													
ANT	4+3																																																													
Pol.	Vertical					Fundamental																																																								
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5923.50</td><td>54.92</td><td>89.30</td><td>-34.38</td><td>42.60</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr><tr><td>2</td><td>5953.00</td><td>56.20</td><td>88.20</td><td>-32.00</td><td>43.77</td><td>34.39</td><td>11.66</td><td>33.62</td><td>0.00</td><td>200</td><td>262</td><td>PEAK</td></tr></table>						Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5923.50	54.92	89.30	-34.38	42.60	34.35	11.56	33.59	0.00	200	262	PEAK	2	5953.00	56.20	88.20	-32.00	43.77	34.39	11.66	33.62	0.00	200	262	PEAK	Blank				
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	5923.50	54.92	89.30	-34.38	42.60	34.35	11.56	33.59	0.00	200	262	PEAK																																																		
2	5953.00	56.20	88.20	-32.00	43.77	34.39	11.66	33.62	0.00	200	262	PEAK																																																		
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>46.28</td><td>68.20</td><td>-21.92</td><td>33.96</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>200</td><td>262</td><td>AVERAGE</td></tr><tr><td>2</td><td>5928.50</td><td>46.62</td><td>68.20</td><td>-21.58</td><td>34.28</td><td>34.36</td><td>11.58</td><td>33.60</td><td>0.00</td><td>200</td><td>262</td><td>AVERAGE</td></tr></table>						Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	46.28	68.20	-21.92	33.96	34.35	11.57	33.60	0.00	200	262	AVERAGE	2	5928.50	46.62	68.20	-21.58	34.28	34.36	11.58	33.60	0.00	200	262	AVERAGE	Blank				
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																			
1	5925.00	46.28	68.20	-21.92	33.96	34.35	11.57	33.60	0.00	200	262	AVERAGE																																																		
2	5928.50	46.62	68.20	-21.58	34.28	34.36	11.58	33.60	0.00	200	262	AVERAGE																																																		






Mode	49																																																																																				
	Harmonic																																																																																				
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz																																																																																				
ANT	4+3																																																																																				
Pol.	Horizontal						Vertical																																																																														
Peak Avg.																																																																																					
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																														
<table><tr><th></th><th></th><th>Limit</th><th></th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11670.00</td><td>49.51</td><td>74.00</td><td>-24.49</td><td>58.25</td><td>38.68</td><td>18.75</td><td>66.48</td><td>0.31</td><td>139</td><td>30 PEAK</td></tr><tr><td>2</td><td>11670.00</td><td>40.59</td><td>54.00</td><td>-13.41</td><td>49.33</td><td>38.68</td><td>18.75</td><td>66.48</td><td>0.31</td><td>139</td><td>30 Average</td></tr><tr><td>3</td><td>17505.00</td><td>55.34</td><td>88.20</td><td>-32.86</td><td>60.74</td><td>38.64</td><td>23.24</td><td>67.84</td><td>0.56</td><td>--</td><td>-- PEAK</td></tr></table>																Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11670.00	49.51	74.00	-24.49	58.25	38.68	18.75	66.48	0.31	139	30 PEAK	2	11670.00	40.59	54.00	-13.41	49.33	38.68	18.75	66.48	0.31	139	30 Average	3	17505.00	55.34	88.20	-32.86	60.74	38.64	23.24	67.84	0.56	--	-- PEAK
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			Remark																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1	11670.00	49.51	74.00	-24.49	58.25	38.68	18.75	66.48	0.31	139	30 PEAK																																																																										
2	11670.00	40.59	54.00	-13.41	49.33	38.68	18.75	66.48	0.31	139	30 Average																																																																										
3	17505.00	55.34	88.20	-32.86	60.74	38.64	23.24	67.84	0.56	--	-- PEAK																																																																										





Mode	49	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE40_CH167_Full RU_5835MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL



Mode	50																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz																																																																																																																																										
ANT	4+3																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5603.54</td><td>55.71</td><td>68.20</td><td>-12.49</td><td>44.65</td><td>33.09</td><td>11.24</td><td>33.27</td><td>0.00</td><td>301</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5651.33</td><td>54.05</td><td>69.19</td><td>-15.14</td><td>43.14</td><td>33.01</td><td>11.22</td><td>33.32</td><td>0.00</td><td>301</td><td>0</td><td>PEAK</td></tr><tr><td>3</td><td>5701.78</td><td>54.86</td><td>105.70</td><td>-50.84</td><td>43.71</td><td>33.32</td><td>11.20</td><td>33.37</td><td>0.00</td><td>301</td><td>0</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>53.17</td><td>110.95</td><td>-57.78</td><td>41.87</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>301</td><td>0</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5603.54	55.71	68.20	-12.49	44.65	33.09	11.24	33.27	0.00	301	0	PEAK	2	5651.33	54.05	69.19	-15.14	43.14	33.01	11.22	33.32	0.00	301	0	PEAK	3	5701.78	54.86	105.70	-50.84	43.71	33.32	11.20	33.37	0.00	301	0	PEAK	4	5720.07	53.17	110.95	-57.78	41.87	33.50	11.19	33.39	0.00	301	0	PEAK	 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5875.00</td><td>100.99</td><td>-----</td><td>-----</td><td>88.92</td><td>34.21</td><td>11.41</td><td>33.55</td><td>0.00</td><td>301</td><td>0</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5875.00	100.99	-----	-----	88.92	34.21	11.41	33.55	0.00	301	0	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5603.54	55.71	68.20	-12.49	44.65	33.09	11.24	33.27	0.00	301	0	PEAK																																																																																																																															
2	5651.33	54.05	69.19	-15.14	43.14	33.01	11.22	33.32	0.00	301	0	PEAK																																																																																																																															
3	5701.78	54.86	105.70	-50.84	43.71	33.32	11.20	33.37	0.00	301	0	PEAK																																																																																																																															
4	5720.07	53.17	110.95	-57.78	41.87	33.50	11.19	33.39	0.00	301	0	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5875.00	100.99	-----	-----	88.92	34.21	11.41	33.55	0.00	301	0	PEAK																																																																																																																															
Avg.	Blank						 Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5875.00</td><td>95.89</td><td>-----</td><td>-----</td><td>83.82</td><td>34.21</td><td>11.41</td><td>33.55</td><td>0.00</td><td>301</td><td>0</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5875.00	95.89	-----	-----	83.82	34.21	11.41	33.55	0.00	301	0	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5875.00	95.89	-----	-----	83.82	34.21	11.41	33.55	0.00	301	0	AVERAGE																																																																																																																															





Mode	50																																																					
	Band Edge - R																																																					
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz																																																					
ANT	4+3																																																					
Pol.	Horizontal					Fundamental																																																
Peak						Blank																																																
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5922.75</td><td>71.83</td><td>89.85</td><td>-18.02</td><td>59.51</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>301 0 PEAK</td></tr><tr><td>2 5925.75</td><td>69.61</td><td>88.20</td><td>-18.59</td><td>57.29</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>301 0 PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5922.75	71.83	89.85	-18.02	59.51	34.35	11.56	33.59	0.00	301 0 PEAK	2 5925.75	69.61	88.20	-18.59
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																													
1 5922.75	71.83	89.85	-18.02	59.51	34.35	11.56	33.59	0.00	301 0 PEAK																																													
2 5925.75	69.61	88.20	-18.59	57.29	34.35	11.57	33.60	0.00	301 0 PEAK																																													
Avg.						Blank																																																
Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5923.50</td><td>61.00</td><td>69.30</td><td>-8.30</td><td>48.68</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>301 0 AVERAGE</td></tr><tr><td>2 5925.25</td><td>59.87</td><td>68.20</td><td>-8.33</td><td>47.55</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>301 0 AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5923.50	61.00	69.30	-8.30	48.68	34.35	11.56	33.59	0.00	301 0 AVERAGE	2 5925.25	59.87	68.20	-8.33	47.55
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																													
1 5923.50	61.00	69.30	-8.30	48.68	34.35	11.56	33.59	0.00	301 0 AVERAGE																																													
2 5925.25	59.87	68.20	-8.33	47.55	34.35	11.57	33.60	0.00	301 0 AVERAGE																																													



Mode	50																																																																																																															
	Band Edge - L																																																																																																															
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz																																																																																																															
ANT	4+3																																																																																																															
Pol.	Vertical	Fundamental																																																																																																														
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5641.01</td><td>56.04</td><td>68.20 -12.16</td><td>45.11</td><td>33.02</td><td>11.22</td><td>33.31</td><td>0.00</td><td>205</td><td>0 PEAK</td></tr><tr><td>2 5650.45</td><td>53.39</td><td>68.53 -15.14</td><td>42.49</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>205</td><td>0 PEAK</td></tr><tr><td>3 5701.19</td><td>55.42</td><td>105.53 -50.11</td><td>44.28</td><td>33.31</td><td>11.20</td><td>33.37</td><td>0.00</td><td>205</td><td>0 PEAK</td></tr><tr><td>4 5720.07</td><td>54.15</td><td>110.95 -56.80</td><td>42.85</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>205</td><td>0 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5641.01	56.04	68.20 -12.16	45.11	33.02	11.22	33.31	0.00	205	0 PEAK	2 5650.45	53.39	68.53 -15.14	42.49	33.00	11.22	33.32	0.00	205	0 PEAK	3 5701.19	55.42	105.53 -50.11	44.28	33.31	11.20	33.37	0.00	205	0 PEAK	4 5720.07	54.15	110.95 -56.80	42.85	33.50	11.19	33.39	0.00	205	0 PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5875.00</td><td>103.16</td><td>-----</td><td>91.12</td><td>34.19</td><td>11.39</td><td>33.54</td><td>0.00</td><td>205</td><td>0 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5875.00	103.16	-----	91.12	34.19	11.39	33.54	0.00	205	0 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5641.01	56.04	68.20 -12.16	45.11	33.02	11.22	33.31	0.00	205	0 PEAK																																																																																																							
2 5650.45	53.39	68.53 -15.14	42.49	33.00	11.22	33.32	0.00	205	0 PEAK																																																																																																							
3 5701.19	55.42	105.53 -50.11	44.28	33.31	11.20	33.37	0.00	205	0 PEAK																																																																																																							
4 5720.07	54.15	110.95 -56.80	42.85	33.50	11.19	33.39	0.00	205	0 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5875.00	103.16	-----	91.12	34.19	11.39	33.54	0.00	205	0 PEAK																																																																																																							
Avg.	Blank	Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5875.00</td><td>96.51</td><td>-----</td><td>84.47</td><td>34.19</td><td>11.39</td><td>33.54</td><td>0.00</td><td>205</td><td>0 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5875.00	96.51	-----	84.47	34.19	11.39	33.54	0.00	205	0 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																							
1 5875.00	96.51	-----	84.47	34.19	11.39	33.54	0.00	205	0 AVERAGE																																																																																																							







Mode	50																																																																
	Band Edge - R																																																																
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz																																																																
ANT	4+3																																																																
Pol.	Vertical					Fundamental																																																											
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5897.25</td><td>82.40</td><td>108.55</td><td>-26.15</td><td>70.20</td><td>34.29</td><td>11.48</td><td>33.57</td><td>0.00</td><td>205</td><td>0 Peak</td></tr><tr><td>2</td><td>5929.00</td><td>67.77</td><td>88.20</td><td>-20.43</td><td>55.43</td><td>34.36</td><td>11.58</td><td>33.60</td><td>0.00</td><td>205</td><td>0 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5897.25	82.40	108.55	-26.15	70.20	34.29	11.48	33.57	0.00	205	0 Peak	2	5929.00	67.77	88.20	-20.43	55.43	34.36	11.58	33.60	0.00	205	0 Peak	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	5897.25	82.40	108.55	-26.15	70.20	34.29	11.48	33.57	0.00	205	0 Peak																																																						
2	5929.00	67.77	88.20	-20.43	55.43	34.36	11.58	33.60	0.00	205	0 Peak																																																						
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5897.25</td><td>72.69</td><td>88.55</td><td>-15.86</td><td>60.49</td><td>34.29</td><td>11.48</td><td>33.57</td><td>0.00</td><td>205</td><td>0 Average</td></tr><tr><td>2</td><td>5927.00</td><td>59.64</td><td>68.20</td><td>-8.56</td><td>47.32</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>205</td><td>0 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5897.25	72.69	88.55	-15.86	60.49	34.29	11.48	33.57	0.00	205	0 Average	2	5927.00	59.64	68.20	-8.56	47.32	34.35	11.57	33.60	0.00	205	0 Average	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																							
1	5897.25	72.69	88.55	-15.86	60.49	34.29	11.48	33.57	0.00	205	0 Average																																																						
2	5927.00	59.64	68.20	-8.56	47.32	34.35	11.57	33.60	0.00	205	0 Average																																																						






Mode	50																																																																																																																																						
	Harmonic																																																																																																																																						
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz																																																																																																																																						
ANT	4+3																																																																																																																																						
Pol.	Horizontal								Vertical																																																																																																																														
Peak Avg.																																																																																																																																							
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 11750.00</td><td>51.54</td><td>74.00</td><td>-22.46</td><td>59.96</td><td>38.00</td><td>18.92</td><td>66.45</td><td>0.31</td><td>142 31 PEAK</td></tr><tr><td>2 11750.00</td><td>41.48</td><td>54.00</td><td>-12.52</td><td>49.90</td><td>38.00</td><td>18.92</td><td>66.45</td><td>0.31</td><td>142 31 Average</td></tr><tr><td>3 17625.00</td><td>54.43</td><td>88.20</td><td>-33.77</td><td>59.33</td><td>39.25</td><td>23.38</td><td>68.11</td><td>0.58</td><td>-- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 11750.00	51.54	74.00	-22.46	59.96	38.00	18.92	66.45	0.31	142 31 PEAK	2 11750.00	41.48	54.00	-12.52	49.90	38.00	18.92	66.45	0.31	142 31 Average	3 17625.00	54.43	88.20	-33.77	59.33	39.25	23.38	68.11	0.58	-- -- PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr></thead><tbody><tr><td>1 11750.00</td><td>51.58</td><td>74.00</td><td>-22.42</td><td>60.00</td><td>38.00</td><td>18.92</td><td>66.45</td><td>0.31</td><td>215 152 PEAK</td></tr><tr><td>2 11750.00</td><td>41.64</td><td>54.00</td><td>-12.36</td><td>50.06</td><td>38.00</td><td>18.92</td><td>66.45</td><td>0.31</td><td>215 152 Average</td></tr><tr><td>3 17625.00</td><td>54.17</td><td>88.20</td><td>-34.03</td><td>59.07</td><td>39.25</td><td>23.38</td><td>68.11</td><td>0.58</td><td>-- -- PEAK</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 11750.00	51.58	74.00	-22.42	60.00	38.00	18.92	66.45	0.31	215 152 PEAK	2 11750.00	41.64	54.00	-12.36	50.06	38.00	18.92	66.45	0.31	215 152 Average	3 17625.00	54.17	88.20	-34.03	59.07	39.25	23.38	68.11	0.58
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																														
1 11750.00	51.54	74.00	-22.46	59.96	38.00	18.92	66.45	0.31	142 31 PEAK																																																																																																																														
2 11750.00	41.48	54.00	-12.52	49.90	38.00	18.92	66.45	0.31	142 31 Average																																																																																																																														
3 17625.00	54.43	88.20	-33.77	59.33	39.25	23.38	68.11	0.58	-- -- PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																														
1 11750.00	51.58	74.00	-22.42	60.00	38.00	18.92	66.45	0.31	215 152 PEAK																																																																																																																														
2 11750.00	41.64	54.00	-12.36	50.06	38.00	18.92	66.45	0.31	215 152 Average																																																																																																																														
3 17625.00	54.17	88.20	-34.03	59.07	39.25	23.38	68.11	0.58	-- -- PEAK																																																																																																																														





Mode	50	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE40_CH175_Full RU_5875MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL



Mode	51																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																																										
ANT	4+3																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5612.98</td><td>57.17</td><td>68.20</td><td>-11.03</td><td>46.15</td><td>33.07</td><td>11.23</td><td>33.28</td><td>0.00</td><td>100</td><td>29</td><td>PEAK</td></tr><tr><td>2</td><td>5651.63</td><td>56.41</td><td>69.41</td><td>-13.00</td><td>45.50</td><td>33.01</td><td>11.22</td><td>33.32</td><td>0.00</td><td>100</td><td>29</td><td>PEAK</td></tr><tr><td>3</td><td>5709.45</td><td>64.33</td><td>107.85</td><td>-43.52</td><td>53.12</td><td>33.39</td><td>11.20</td><td>33.38</td><td>0.00</td><td>100</td><td>29</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>61.81</td><td>110.95</td><td>-49.14</td><td>50.51</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>100</td><td>29</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5612.98	57.17	68.20	-11.03	46.15	33.07	11.23	33.28	0.00	100	29	PEAK	2	5651.63	56.41	69.41	-13.00	45.50	33.01	11.22	33.32	0.00	100	29	PEAK	3	5709.45	64.33	107.85	-43.52	53.12	33.39	11.20	33.38	0.00	100	29	PEAK	4	5720.07	61.81	110.95	-49.14	50.51	33.50	11.19	33.39	0.00	100	29	PEAK	 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5855.00</td><td>103.68</td><td>-----</td><td>-----</td><td>91.79</td><td>34.10</td><td>11.30</td><td>33.51</td><td>0.00</td><td>100</td><td>29</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5855.00	103.68	-----	-----	91.79	34.10	11.30	33.51	0.00	100	29	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5612.98	57.17	68.20	-11.03	46.15	33.07	11.23	33.28	0.00	100	29	PEAK																																																																																																																															
2	5651.63	56.41	69.41	-13.00	45.50	33.01	11.22	33.32	0.00	100	29	PEAK																																																																																																																															
3	5709.45	64.33	107.85	-43.52	53.12	33.39	11.20	33.38	0.00	100	29	PEAK																																																																																																																															
4	5720.07	61.81	110.95	-49.14	50.51	33.50	11.19	33.39	0.00	100	29	PEAK																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5855.00	103.68	-----	-----	91.79	34.10	11.30	33.51	0.00	100	29	PEAK																																																																																																																															
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5855.00</td><td>97.23</td><td>-----</td><td>-----</td><td>85.34</td><td>34.10</td><td>11.30</td><td>33.51</td><td>0.00</td><td>100</td><td>29</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5855.00	97.23	-----	-----	85.34	34.10	11.30	33.51	0.00	100	29	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	5855.00	97.23	-----	-----	85.34	34.10	11.30	33.51	0.00	100	29	AVERAGE																																																																																																																															





Mode	51																																																			
	Band Edge - R																																																			
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																			
ANT	4+3																																																			
Pol.	Horizontal	Fundamental																																																		
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5924.50</td><td>73.39</td><td>88.57</td><td>-15.18</td><td>61.07</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>100 29 PEAK</td></tr><tr><td>2 5927.00</td><td>74.67</td><td>88.20</td><td>-13.53</td><td>62.35</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>100 29 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5924.50	73.39	88.57	-15.18	61.07	34.35	11.56	33.59	0.00	100 29 PEAK	2 5927.00	74.67	88.20	-13.53	62.35	34.35	11.57	33.60	0.00	100 29 PEAK	Blank
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																											
1 5924.50	73.39	88.57	-15.18	61.07	34.35	11.56	33.59	0.00	100 29 PEAK																																											
2 5927.00	74.67	88.20	-13.53	62.35	34.35	11.57	33.60	0.00	100 29 PEAK																																											
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 HORIZONTAL : RBW:1000.000kHz VBW:3.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5924.25</td><td>66.30</td><td>68.75</td><td>-2.45</td><td>53.98</td><td>34.35</td><td>11.56</td><td>33.59</td><td>0.00</td><td>100 29 AVERAGE</td></tr><tr><td>2 5925.00</td><td>65.34</td><td>68.20</td><td>-2.86</td><td>53.02</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>100 29 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5924.25	66.30	68.75	-2.45	53.98	34.35	11.56	33.59	0.00	100 29 AVERAGE	2 5925.00	65.34	68.20	-2.86	53.02	34.35	11.57	33.60	0.00	100 29 AVERAGE	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																											
1 5924.25	66.30	68.75	-2.45	53.98	34.35	11.56	33.59	0.00	100 29 AVERAGE																																											
2 5925.00	65.34	68.20	-2.86	53.02	34.35	11.57	33.60	0.00	100 29 AVERAGE																																											





Mode	51																																																																																																																																					
	Band Edge - L																																																																																																																																					
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																																					
ANT	4+3																																																																																																																																					
Pol.	Vertical						Fundamental																																																																																																																															
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5649.86</td><td>55.47</td><td>68.20</td><td>-12.73</td><td>44.57</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>239</td><td>0 PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>54.13</td><td>68.31</td><td>-14.18</td><td>43.23</td><td>33.00</td><td>11.22</td><td>33.32</td><td>0.00</td><td>239</td><td>0 PEAK</td></tr><tr><td>3</td><td>5719.18</td><td>64.98</td><td>110.57</td><td>-45.59</td><td>53.69</td><td>33.49</td><td>11.19</td><td>33.39</td><td>0.00</td><td>239</td><td>0 PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>59.20</td><td>110.95</td><td>-51.75</td><td>47.90</td><td>33.50</td><td>11.19</td><td>33.39</td><td>0.00</td><td>239</td><td>0 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5649.86	55.47	68.20	-12.73	44.57	33.00	11.22	33.32	0.00	239	0 PEAK	2	5650.15	54.13	68.31	-14.18	43.23	33.00	11.22	33.32	0.00	239	0 PEAK	3	5719.18	64.98	110.57	-45.59	53.69	33.49	11.19	33.39	0.00	239	0 PEAK	4	5720.07	59.20	110.95	-51.75	47.90	33.50	11.19	33.39	0.00	239	0 PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5855.00</td><td>99.73</td><td>-----</td><td>-----</td><td>87.84</td><td>34.10</td><td>11.30</td><td>33.51</td><td>0.00</td><td>239</td><td>0 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	99.73	-----	-----	87.84	34.10	11.30	33.51	0.00	239	0 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5649.86	55.47	68.20	-12.73	44.57	33.00	11.22	33.32	0.00	239	0 PEAK																																																																																																																											
2	5650.15	54.13	68.31	-14.18	43.23	33.00	11.22	33.32	0.00	239	0 PEAK																																																																																																																											
3	5719.18	64.98	110.57	-45.59	53.69	33.49	11.19	33.39	0.00	239	0 PEAK																																																																																																																											
4	5720.07	59.20	110.95	-51.75	47.90	33.50	11.19	33.39	0.00	239	0 PEAK																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5855.00	99.73	-----	-----	87.84	34.10	11.30	33.51	0.00	239	0 PEAK																																																																																																																											
Avg.	Blank						Site : 03CH12-HY Condition: AVG(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5855.00</td><td>93.01</td><td>-----</td><td>-----</td><td>81.02</td><td>34.16</td><td>11.37</td><td>33.54</td><td>0.00</td><td>239</td><td>0 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	93.01	-----	-----	81.02	34.16	11.37	33.54	0.00	239	0 AVERAGE																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5855.00	93.01	-----	-----	81.02	34.16	11.37	33.54	0.00	239	0 AVERAGE																																																																																																																											







Mode	51																																																			
	Band Edge - R																																																			
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																			
ANT	4+3																																																			
Pol.	Vertical	Fundamental																																																		
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5924.75</td><td>70.09</td><td>88.38</td><td>-18.29</td><td>57.76</td><td>34.35</td><td>11.57</td><td>33.59</td><td>0.00</td><td>239 0 PEAK</td></tr><tr><td>2 5930.25</td><td>69.97</td><td>88.20</td><td>-18.23</td><td>57.63</td><td>34.36</td><td>11.58</td><td>33.60</td><td>0.00</td><td>239 0 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5924.75	70.09	88.38	-18.29	57.76	34.35	11.57	33.59	0.00	239 0 PEAK	2 5930.25	69.97	88.20	-18.23	57.63	34.36	11.58	33.60	0.00	239 0 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																											
1 5924.75	70.09	88.38	-18.29	57.76	34.35	11.57	33.59	0.00	239 0 PEAK																																											
2 5930.25	69.97	88.20	-18.23	57.63	34.36	11.58	33.60	0.00	239 0 PEAK																																											
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m BBHA 9120 D_91200-02038 VERTICAL : RBW:1000.000kHz VBW:3.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5900.00</td><td>65.60</td><td>86.53</td><td>-20.93</td><td>53.38</td><td>34.30</td><td>11.49</td><td>33.57</td><td>0.00</td><td>239 0 Average</td></tr><tr><td>2 5927.00</td><td>61.58</td><td>68.20</td><td>-6.62</td><td>49.26</td><td>34.35</td><td>11.57</td><td>33.60</td><td>0.00</td><td>239 0 Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5900.00	65.60	86.53	-20.93	53.38	34.30	11.49	33.57	0.00	239 0 Average	2 5927.00	61.58	68.20	-6.62	49.26	34.35	11.57	33.60	0.00	239 0 Average	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																											
1 5900.00	65.60	86.53	-20.93	53.38	34.30	11.49	33.57	0.00	239 0 Average																																											
2 5927.00	61.58	68.20	-6.62	49.26	34.35	11.57	33.60	0.00	239 0 Average																																											



Mode	51																																																																																																																																																																																		
	Harmonic																																																																																																																																																																																		
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz																																																																																																																																																																																		
ANT	4+3																																																																																																																																																																																		
Pol.	Horizontal						Vertical																																																																																																																																																																												
Peak Avg.																																																																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 HORIZONTAL						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91280-02114-240711 VERTICAL																																																																																																																																																																												
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11710.00</td><td>52.25</td><td>74.00</td><td>-21.75</td><td>60.77</td><td>38.00</td><td>18.83</td><td>66.46</td><td>0.31</td><td>171</td><td>58</td><td>PEAK</td></tr><tr><td>2</td><td>11710.00</td><td>43.09</td><td>54.00</td><td>-10.91</td><td>51.61</td><td>38.00</td><td>18.83</td><td>66.46</td><td>0.31</td><td>171</td><td>58</td><td>Average</td></tr><tr><td>3</td><td>17565.00</td><td>54.12</td><td>88.20</td><td>-34.08</td><td>59.19</td><td>39.03</td><td>23.31</td><td>67.98</td><td>0.57</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11710.00	52.25	74.00	-21.75	60.77	38.00	18.83	66.46	0.31	171	58	PEAK	2	11710.00	43.09	54.00	-10.91	51.61	38.00	18.83	66.46	0.31	171	58	Average	3	17565.00	54.12	88.20	-34.08	59.19	39.03	23.31	67.98	0.57	--	--	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11710.00</td><td>51.64</td><td>74.00</td><td>-22.36</td><td>60.16</td><td>38.00</td><td>18.83</td><td>66.46</td><td>0.31</td><td>188</td><td>124</td><td>PEAK</td></tr><tr><td>2</td><td>11710.00</td><td>42.64</td><td>54.00</td><td>-11.36</td><td>51.16</td><td>38.00</td><td>18.83</td><td>66.46</td><td>0.31</td><td>188</td><td>124</td><td>Average</td></tr><tr><td>3</td><td>17565.00</td><td>53.75</td><td>88.20</td><td>-34.45</td><td>58.82</td><td>39.03</td><td>23.31</td><td>67.98</td><td>0.57</td><td>--</td><td>--</td><td>PEAK</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	11710.00	51.64	74.00	-22.36	60.16	38.00	18.83	66.46	0.31	188	124	PEAK	2	11710.00	42.64	54.00	-11.36	51.16	38.00	18.83	66.46	0.31	188	124	Average	3	17565.00	53.75	88.20	-34.45	58.82	39.03	23.31	67.98	0.57	--	--	PEAK
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11710.00	52.25	74.00	-21.75	60.77	38.00	18.83	66.46	0.31	171	58	PEAK																																																																																																																																																																							
2	11710.00	43.09	54.00	-10.91	51.61	38.00	18.83	66.46	0.31	171	58	Average																																																																																																																																																																							
3	17565.00	54.12	88.20	-34.08	59.19	39.03	23.31	67.98	0.57	--	--	PEAK																																																																																																																																																																							
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																								
1	11710.00	51.64	74.00	-22.36	60.16	38.00	18.83	66.46	0.31	188	124	PEAK																																																																																																																																																																							
2	11710.00	42.64	54.00	-11.36	51.16	38.00	18.83	66.46	0.31	188	124	Average																																																																																																																																																																							
3	17565.00	53.75	88.20	-34.45	58.82	39.03	23.31	67.98	0.57	--	--	PEAK																																																																																																																																																																							





Mode	51	
	Harmonic	
	U-NII-4_5.85-5.895_802.11ax HE80_CH171_Full RU_5855MHz	
ANT	4+3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL
	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL	 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL






		72									
Mode	Band Edge - L										
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 26/0_5845MHz										
ANT	4+3										
Pol.	Horizontal										
Peak	</										





Mode	72																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 26/0_5845MHz																																																										
ANT	4+3																																																										
Pol.	Horizontal	Fundamental																																																									
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.25</td><td>54.65</td><td>88.75</td><td>-34.10</td><td>42.38</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>101</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>5999.00</td><td>55.69</td><td>88.20</td><td>-32.51</td><td>43.35</td><td>34.20</td><td>11.81</td><td>33.67</td><td>0.00</td><td>101</td><td>360</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.25	54.65	88.75	-34.10	42.38	34.30	11.56	33.59	0.00	101	360	PEAK	2	5999.00	55.69	88.20	-32.51	43.35	34.20	11.81	33.67	0.00	101	360	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5924.25	54.65	88.75	-34.10	42.38	34.30	11.56	33.59	0.00	101	360	PEAK																																															
2	5999.00	55.69	88.20	-32.51	43.35	34.20	11.81	33.67	0.00	101	360	PEAK																																															
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>45.96</td><td>68.20</td><td>-22.24</td><td>33.69</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>101</td><td>360</td><td>AVERAGE</td></tr><tr><td>2</td><td>5999.00</td><td>46.40</td><td>68.20</td><td>-21.80</td><td>34.06</td><td>34.20</td><td>11.81</td><td>33.67</td><td>0.00</td><td>101</td><td>360</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	45.96	68.20	-22.24	33.69	34.30	11.57	33.60	0.00	101	360	AVERAGE	2	5999.00	46.40	68.20	-21.80	34.06	34.20	11.81	33.67	0.00	101	360	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5925.00	45.96	68.20	-22.24	33.69	34.30	11.57	33.60	0.00	101	360	AVERAGE																																															
2	5999.00	46.40	68.20	-21.80	34.06	34.20	11.81	33.67	0.00	101	360	AVERAGE																																															






Mode	72																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 26/0_5845MHz																																																																																																																																									
ANT	4+3																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE(UNII 4)						 Level (dBuV/m) Frequency (MHz) PEAK(UNII 4)																																																																																																																																			
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto						Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto																																																																																																																																			
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5635.40</td><td>55.12</td><td>68.20</td><td>-13.08</td><td>44.03</td><td>33.17</td><td>11.23</td><td>33.31</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>55.36</td><td>68.53</td><td>-13.17</td><td>44.26</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr><tr><td>3</td><td>5702.66</td><td>55.76</td><td>105.95</td><td>-50.19</td><td>44.32</td><td>33.61</td><td>11.20</td><td>33.37</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>55.40</td><td>110.95</td><td>-55.55</td><td>43.92</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5635.40	55.12	68.20	-13.08	44.03	33.17	11.23	33.31	0.00	383	0	PEAK	2	5650.45	55.36	68.53	-13.17	44.26	33.20	11.22	33.32	0.00	383	0	PEAK	3	5702.66	55.76	105.95	-50.19	44.32	33.61	11.20	33.37	0.00	383	0	PEAK	4	5720.07	55.40	110.95	-55.55	43.92	33.68	11.19	33.39	0.00	383	0	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>103.22</td><td>-----</td><td>-----</td><td>91.38</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	103.22	-----	-----	91.38	34.07	11.28	33.51	0.00	383	0
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5635.40	55.12	68.20	-13.08	44.03	33.17	11.23	33.31	0.00	383	0	PEAK																																																																																																																														
2	5650.45	55.36	68.53	-13.17	44.26	33.20	11.22	33.32	0.00	383	0	PEAK																																																																																																																														
3	5702.66	55.76	105.95	-50.19	44.32	33.61	11.20	33.37	0.00	383	0	PEAK																																																																																																																														
4	5720.07	55.40	110.95	-55.55	43.92	33.68	11.19	33.39	0.00	383	0	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5845.00	103.22	-----	-----	91.38	34.07	11.28	33.51	0.00	383	0	PEAK																																																																																																																														
Avg.	Blank						 Level (dBuV/m) Frequency (MHz) AVG(UNII 4)																																																																																																																																			
							Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto																																																																																																																																			
							<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>97.85</td><td>-----</td><td>-----</td><td>86.01</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>383</td><td>0</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	97.85	-----	-----	86.01	34.07	11.28	33.51	0.00	383	0	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5845.00	97.85	-----	-----	86.01	34.07	11.28	33.51	0.00	383	0	AVERAGE																																																																																																																														



Mode	72																																																										
	Band Edge - R																																																										
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 26/0_5845MHz																																																										
ANT	4+3																																																										
Pol.	Vertical	Fundamental																																																									
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.25</td><td>53.51</td><td>88.75</td><td>-35.24</td><td>41.24</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr><tr><td>2</td><td>5973.25</td><td>56.50</td><td>88.20</td><td>-31.70</td><td>44.17</td><td>34.25</td><td>11.72</td><td>33.64</td><td>0.00</td><td>383</td><td>0</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.25	53.51	88.75	-35.24	41.24	34.30	11.56	33.59	0.00	383	0	PEAK	2	5973.25	56.50	88.20	-31.70	44.17	34.25	11.72	33.64	0.00	383	0	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5924.25	53.51	88.75	-35.24	41.24	34.30	11.56	33.59	0.00	383	0	PEAK																																															
2	5973.25	56.50	88.20	-31.70	44.17	34.25	11.72	33.64	0.00	383	0	PEAK																																															
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>45.90</td><td>68.20</td><td>-22.30</td><td>33.63</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>383</td><td>0</td><td>AVERAGE</td></tr><tr><td>2</td><td>5998.25</td><td>46.35</td><td>68.20</td><td>-21.85</td><td>34.02</td><td>34.20</td><td>11.80</td><td>33.67</td><td>0.00</td><td>383</td><td>0</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	45.90	68.20	-22.30	33.63	34.30	11.57	33.60	0.00	383	0	AVERAGE	2	5998.25	46.35	68.20	-21.85	34.02	34.20	11.80	33.67	0.00	383	0	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	5925.00	45.90	68.20	-22.30	33.63	34.30	11.57	33.60	0.00	383	0	AVERAGE																																															
2	5998.25	46.35	68.20	-21.85	34.02	34.20	11.80	33.67	0.00	383	0	AVERAGE																																															



Mode	73																																																																																																																																								
	Band Edge - L																																																																																																																																								
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 52/37_5845MHz																																																																																																																																								
ANT	4+3																																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																																		
Peak																																																																																																																																									
	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5647.50</td><td>55.26</td><td>68.20</td><td>-12.94</td><td></td><td>44.17</td><td>33.19</td><td>11.22</td><td>33.32</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr><tr><td>2</td><td>5650.45</td><td>54.46</td><td>68.53</td><td>-14.07</td><td></td><td>43.36</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr><tr><td>3</td><td>5700.01</td><td>55.26</td><td>105.20</td><td>-49.94</td><td></td><td>43.83</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>54.39</td><td>110.95</td><td>-56.56</td><td></td><td>42.91</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5647.50	55.26	68.20	-12.94		44.17	33.19	11.22	33.32	0.00	200	35	PEAK	2	5650.45	54.46	68.53	-14.07		43.36	33.20	11.22	33.32	0.00	200	35	PEAK	3	5700.01	55.26	105.20	-49.94		43.83	33.60	11.20	33.37	0.00	200	35	PEAK	4	5720.07	54.39	110.95	-56.56		42.91	33.68	11.19	33.39	0.00	200	35	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>109.77</td><td>-----</td><td>-----</td><td></td><td>97.93</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5845.00	109.77	-----	-----		97.93	34.07	11.28	33.51	0.00	200	35
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																												
1	5647.50	55.26	68.20	-12.94		44.17	33.19	11.22	33.32	0.00	200	35	PEAK																																																																																																																												
2	5650.45	54.46	68.53	-14.07		43.36	33.20	11.22	33.32	0.00	200	35	PEAK																																																																																																																												
3	5700.01	55.26	105.20	-49.94		43.83	33.60	11.20	33.37	0.00	200	35	PEAK																																																																																																																												
4	5720.07	54.39	110.95	-56.56		42.91	33.68	11.19	33.39	0.00	200	35	PEAK																																																																																																																												
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																												
1	5845.00	109.77	-----	-----		97.93	34.07	11.28	33.51	0.00	200	35	PEAK																																																																																																																												
Avg.	Blank																																																																																																																																								
							Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>103.60</td><td>-----</td><td>-----</td><td></td><td>91.76</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>200</td><td>35</td><td>AVERAGE</td></tr></tbody></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	5845.00	103.60	-----	-----		91.76	34.07	11.28	33.51	0.00	200	35	AVERAGE																																																																																			
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																												
1	5845.00	103.60	-----	-----		91.76	34.07	11.28	33.51	0.00	200	35	AVERAGE																																																																																																																												





Mode	73																																																									
	Band Edge - R																																																									
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 52/37_5845MHz																																																									
ANT	4+3																																																									
Pol.	Horizontal	Fundamental																																																								
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.25</td><td>54.32</td><td>88.75</td><td>-34.43</td><td></td><td>42.05</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr><tr><td>2</td><td>5951.25</td><td>55.90</td><td>88.20</td><td>-32.30</td><td></td><td>43.57</td><td>34.30</td><td>11.65</td><td>33.62</td><td>0.00</td><td>200</td><td>35</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.25	54.32	88.75	-34.43		42.05	34.30	11.56	33.59	0.00	200	35	PEAK	2	5951.25	55.90	88.20	-32.30		43.57	34.30	11.65	33.62	0.00	200	35	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5924.25	54.32	88.75	-34.43		42.05	34.30	11.56	33.59	0.00	200	35	PEAK																																													
2	5951.25	55.90	88.20	-32.30		43.57	34.30	11.65	33.62	0.00	200	35	PEAK																																													
Avg.	Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>46.20</td><td>68.20</td><td>-22.00</td><td></td><td>33.93</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>200</td><td>35</td><td>AVERAGE</td></tr><tr><td>2</td><td>5925.75</td><td>46.40</td><td>68.20</td><td>-21.80</td><td></td><td>34.13</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>200</td><td>35</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	46.20	68.20	-22.00		33.93	34.30	11.57	33.60	0.00	200	35	AVERAGE	2	5925.75	46.40	68.20	-21.80		34.13	34.30	11.57	33.60	0.00	200	35	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5925.00	46.20	68.20	-22.00		33.93	34.30	11.57	33.60	0.00	200	35	AVERAGE																																													
2	5925.75	46.40	68.20	-21.80		34.13	34.30	11.57	33.60	0.00	200	35	AVERAGE																																													






		73																																																																																																																																																							
Mode	Band Edge - L																																																																																																																																																								
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 52/37_5845MHz																																																																																																																																																								
ANT	4+3																																																																																																																																																								
Pol.	Vertical																																																																																																																																																								
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5637.76</td><td>56.00</td><td>68.20</td><td>-12.20</td><td>44.91</td><td>33.18</td><td>11.22</td><td>33.31</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>54.78</td><td>68.31</td><td>-13.53</td><td>43.68</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr><tr><td>3</td><td>5700.01</td><td>54.52</td><td>105.20</td><td>-50.68</td><td>43.09</td><td>33.60</td><td>11.20</td><td>33.37</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr><tr><td>4</td><td>5720.66</td><td>55.14</td><td>112.29</td><td>-57.15</td><td>43.66</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5637.76	56.00	68.20	-12.20	44.91	33.18	11.22	33.31	0.00	400	112	PEAK	2	5650.15	54.78	68.31	-13.53	43.68	33.20	11.22	33.32	0.00	400	112	PEAK	3	5700.01	54.52	105.20	-50.68	43.09	33.60	11.20	33.37	0.00	400	112	PEAK	4	5720.66	55.14	112.29	-57.15	43.66	33.68	11.19	33.39	0.00	400	112	PEAK	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>100.30</td><td>-----</td><td>-----</td><td>88.46</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	100.30	-----	-----	88.46	34.07	11.28	33.51	0.00	400	112	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5637.76	56.00	68.20	-12.20	44.91	33.18	11.22	33.31	0.00	400	112	PEAK																																																																																																																																													
2	5650.15	54.78	68.31	-13.53	43.68	33.20	11.22	33.32	0.00	400	112	PEAK																																																																																																																																													
3	5700.01	54.52	105.20	-50.68	43.09	33.60	11.20	33.37	0.00	400	112	PEAK																																																																																																																																													
4	5720.66	55.14	112.29	-57.15	43.66	33.68	11.19	33.39	0.00	400	112	PEAK																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5845.00	100.30	-----	-----	88.46	34.07	11.28	33.51	0.00	400	112	PEAK																																																																																																																																													
Avg.	Blank											Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5845.00</td><td>94.11</td><td>-----</td><td>-----</td><td>82.27</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>400</td><td>112</td><td>AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5845.00	94.11	-----	-----	82.27	34.07	11.28	33.51	0.00	400	112	AVERAGE																																																																																					
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	cm	deg																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																															
1	5845.00	94.11	-----	-----	82.27	34.07	11.28	33.51	0.00	400	112	AVERAGE																																																																																																																																													





Mode	73																																																																				
	Band Edge - R																																																																				
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 52/37_5845MHz																																																																				
ANT	4+3																																																																				
Pol.	Vertical						Fundamental																																																														
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.75</td><td>54.70</td><td>88.38</td><td>-33.68</td><td>42.42</td><td>34.30</td><td>11.57</td><td>33.59</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr><tr><td>2</td><td>5950.75</td><td>55.67</td><td>88.20</td><td>-32.53</td><td>43.34</td><td>34.30</td><td>11.65</td><td>33.62</td><td>0.00</td><td>400</td><td>112</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.75	54.70	88.38	-33.68	42.42	34.30	11.57	33.59	0.00	400	112	PEAK	2	5950.75	55.67	88.20	-32.53	43.34	34.30	11.65	33.62	0.00	400	112	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																											
1	5924.75	54.70	88.38	-33.68	42.42	34.30	11.57	33.59	0.00	400	112	PEAK																																																									
2	5950.75	55.67	88.20	-32.53	43.34	34.30	11.65	33.62	0.00	400	112	PEAK																																																									
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5925.00</td><td>45.98</td><td>68.20</td><td>-22.22</td><td>33.71</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>400</td><td>112</td><td>AVERAGE</td></tr><tr><td>2</td><td>5942.75</td><td>46.33</td><td>68.20</td><td>-21.87</td><td>34.02</td><td>34.30</td><td>11.62</td><td>33.61</td><td>0.00</td><td>400</td><td>112</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5925.00	45.98	68.20	-22.22	33.71	34.30	11.57	33.60	0.00	400	112	AVERAGE	2	5942.75	46.33	68.20	-21.87	34.02	34.30	11.62	33.61	0.00	400	112	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																											
1	5925.00	45.98	68.20	-22.22	33.71	34.30	11.57	33.60	0.00	400	112	AVERAGE																																																									
2	5942.75	46.33	68.20	-21.87	34.02	34.30	11.62	33.61	0.00	400	112	AVERAGE																																																									



Mode	74																																																																																																																																				
	Band Edge - L																																																																																																																																				
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 106/53_5845MHz																																																																																																																																				
ANT	4+3																																																																																																																																				
Pol.	Horizontal						Fundamental																																																																																																																														
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5614.16</td><td>56.16</td><td>68.20</td><td>-12.04</td><td>45.00</td><td>33.13</td><td>11.23</td><td>33.28</td><td>0.00</td><td>203 35 PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>53.85</td><td>68.31</td><td>-14.46</td><td>42.75</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>203 35 PEAK</td></tr><tr><td>3</td><td>5701.48</td><td>55.44</td><td>105.62</td><td>-50.18</td><td>44.00</td><td>33.61</td><td>11.20</td><td>33.37</td><td>0.00</td><td>203 35 PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>54.10</td><td>110.95</td><td>-56.85</td><td>42.62</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>203 35 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5614.16	56.16	68.20	-12.04	45.00	33.13	11.23	33.28	0.00	203 35 PEAK	2	5650.15	53.85	68.31	-14.46	42.75	33.20	11.22	33.32	0.00	203 35 PEAK	3	5701.48	55.44	105.62	-50.18	44.00	33.61	11.20	33.37	0.00	203 35 PEAK	4	5720.07	54.10	110.95	-56.85	42.62	33.68	11.19	33.39	0.00	203 35 PEAK	 Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>110.54</td><td>-----</td><td>-----</td><td>98.67</td><td>34.08</td><td>11.30</td><td>33.51</td><td>0.00</td><td>203 35 PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5845.00	110.54	-----	-----	98.67	34.08	11.30	33.51	0.00	203 35 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																											
1	5614.16	56.16	68.20	-12.04	45.00	33.13	11.23	33.28	0.00	203 35 PEAK																																																																																																																											
2	5650.15	53.85	68.31	-14.46	42.75	33.20	11.22	33.32	0.00	203 35 PEAK																																																																																																																											
3	5701.48	55.44	105.62	-50.18	44.00	33.61	11.20	33.37	0.00	203 35 PEAK																																																																																																																											
4	5720.07	54.10	110.95	-56.85	42.62	33.68	11.19	33.39	0.00	203 35 PEAK																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																											
1	5845.00	110.54	-----	-----	98.67	34.08	11.30	33.51	0.00	203 35 PEAK																																																																																																																											
Avg.	Blank						 Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>103.47</td><td>-----</td><td>-----</td><td>91.60</td><td>34.08</td><td>11.30</td><td>33.51</td><td>0.00</td><td>203 35 AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5845.00	103.47	-----	-----	91.60	34.08	11.30	33.51	0.00	203 35 AVERAGE																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																											
1	5845.00	103.47	-----	-----	91.60	34.08	11.30	33.51	0.00	203 35 AVERAGE																																																																																																																											





Mode	74																																																							
	Band Edge - R																																																							
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 106/53_5845MHz																																																							
ANT	4+3																																																							
Pol.	Horizontal	Fundamental																																																						
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.25</td><td>55.17</td><td>88.75</td><td>-33.58</td><td>42.90</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>203</td><td>35</td><td>PEAK</td></tr><tr><td>2</td><td>5974.75</td><td>56.00</td><td>88.20</td><td>-32.20</td><td>43.66</td><td>34.25</td><td>11.73</td><td>33.64</td><td>0.00</td><td>203</td><td>35</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.25	55.17	88.75	-33.58	42.90	34.30	11.56	33.59	0.00	203	35	PEAK	2	5974.75	56.00	88.20	-32.20	43.66	34.25	11.73	33.64	0.00	203	35	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5924.25	55.17	88.75	-33.58	42.90	34.30	11.56	33.59	0.00	203	35	PEAK																																												
2	5974.75	56.00	88.20	-32.20	43.66	34.25	11.73	33.64	0.00	203	35	PEAK																																												
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 HORIZONTAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>46.19</td><td>68.20</td><td>-22.01</td><td>33.92</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>203</td><td>35</td><td>AVERAGE</td></tr><tr><td>2</td><td>5935.50</td><td>46.47</td><td>68.20</td><td>-21.73</td><td>34.18</td><td>34.30</td><td>11.60</td><td>33.61</td><td>0.00</td><td>203</td><td>35</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	46.19	68.20	-22.01	33.92	34.30	11.57	33.60	0.00	203	35	AVERAGE	2	5935.50	46.47	68.20	-21.73	34.18	34.30	11.60	33.61	0.00	203	35	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																												
1	5925.00	46.19	68.20	-22.01	33.92	34.30	11.57	33.60	0.00	203	35	AVERAGE																																												
2	5935.50	46.47	68.20	-21.73	34.18	34.30	11.60	33.61	0.00	203	35	AVERAGE																																												



		74																																																																											
Mode	Band Edge - L																																																																												
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 106/53_5845MHz																																																																												
ANT	4+3																																																																												
Pol.	Vertical																																																																												
Peak	Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5635.40</td><td>56.37 68.20 -11.83</td><td>45.28</td><td>33.17</td><td>11.23</td><td>33.31</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr><tr><td>2</td><td>5650.15</td><td>54.06 68.31 -14.25</td><td>42.96</td><td>33.20</td><td>11.22</td><td>33.32</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr><tr><td>3</td><td>5701.78</td><td>55.36 105.70 -50.34</td><td>43.92</td><td>33.61</td><td>11.20</td><td>33.37</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>55.31 110.95 -55.64</td><td>43.83</td><td>33.68</td><td>11.19</td><td>33.39</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg	1	5635.40	56.37 68.20 -11.83	45.28	33.17	11.23	33.31	0.00	300	227	PEAK	2	5650.15	54.06 68.31 -14.25	42.96	33.20	11.22	33.32	0.00	300	227	PEAK	3	5701.78	55.36 105.70 -50.34	43.92	33.61	11.20	33.37	0.00	300	227	PEAK	4	5720.07	55.31 110.95 -55.64	43.83	33.68	11.19	33.39	0.00	300	227	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																			
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg																																																																			
1	5635.40	56.37 68.20 -11.83	45.28	33.17	11.23	33.31	0.00	300	227	PEAK																																																																			
2	5650.15	54.06 68.31 -14.25	42.96	33.20	11.22	33.32	0.00	300	227	PEAK																																																																			
3	5701.78	55.36 105.70 -50.34	43.92	33.61	11.20	33.37	0.00	300	227	PEAK																																																																			
4	5720.07	55.31 110.95 -55.64	43.83	33.68	11.19	33.39	0.00	300	227	PEAK																																																																			
Fundamental	Site : 03CH12-HY Condition: PEAK(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>103.32 -----</td><td>91.48</td><td>34.07</td><td>11.28</td><td>33.51</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg	1	5845.00	103.32 -----	91.48	34.07	11.28	33.51	0.00	300	227	PEAK																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																			
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg																																																																			
1	5845.00	103.32 -----	91.48	34.07	11.28	33.51	0.00	300	227	PEAK																																																																			
Avg.	Blank																																																																												
	Site : 03CH12-HY Condition: AVG(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SWT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5845.00</td><td>96.51 -----</td><td>84.64</td><td>34.08</td><td>11.30</td><td>33.51</td><td>0.00</td><td>300</td><td>227</td><td>AVERAGE</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg	1	5845.00	96.51 -----	84.64	34.08	11.30	33.51	0.00	300	227	AVERAGE																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																				
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			cm	deg																																																																			
1	5845.00	96.51 -----	84.64	34.08	11.30	33.51	0.00	300	227	AVERAGE																																																																			



Mode	74																																																									
	Band Edge - R																																																									
	U-NII-4_5.85-5.895_802.11ax HE20_CH169_Partial 106/53_5845MHz																																																									
ANT	4+3																																																									
Pol.	Vertical	Fundamental																																																								
Peak	 Site : 03CH12-HY Condition: PEAK_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5924.00</td><td>55.52</td><td>88.93</td><td>-33.41</td><td></td><td>43.25</td><td>34.30</td><td>11.56</td><td>33.59</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr><tr><td>2</td><td>5978.50</td><td>56.20</td><td>88.20</td><td>-32.00</td><td></td><td>43.87</td><td>34.26</td><td>11.71</td><td>33.64</td><td>0.00</td><td>300</td><td>227</td><td>PEAK</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	5924.00	55.52	88.93	-33.41		43.25	34.30	11.56	33.59	0.00	300	227	PEAK	2	5978.50	56.20	88.20	-32.00		43.87	34.26	11.71	33.64	0.00	300	227	PEAK	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5924.00	55.52	88.93	-33.41		43.25	34.30	11.56	33.59	0.00	300	227	PEAK																																													
2	5978.50	56.20	88.20	-32.00		43.87	34.26	11.71	33.64	0.00	300	227	PEAK																																													
Avg.	 Site : 03CH12-HY Condition: AVG_BE(UNII 4) 3m 91200-02114-240711 VERTICAL : RBW:1000.000kHz VBW:1.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>5925.00</td><td>46.03</td><td>68.20</td><td>-22.17</td><td></td><td>33.76</td><td>34.30</td><td>11.57</td><td>33.60</td><td>0.00</td><td>300</td><td>227</td><td>AVERAGE</td></tr><tr><td>2</td><td>5948.25</td><td>46.46</td><td>68.20</td><td>-21.74</td><td></td><td>34.14</td><td>34.30</td><td>11.64</td><td>33.62</td><td>0.00</td><td>300</td><td>227</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	5925.00	46.03	68.20	-22.17		33.76	34.30	11.57	33.60	0.00	300	227	AVERAGE	2	5948.25	46.46	68.20	-21.74		34.14	34.30	11.64	33.62	0.00	300	227	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	5925.00	46.03	68.20	-22.17		33.76	34.30	11.57	33.60	0.00	300	227	AVERAGE																																													
2	5948.25	46.46	68.20	-21.74		34.14	34.30	11.64	33.62	0.00	300	227	AVERAGE																																													