



FCC RF Test Report

APPLICANT : Mobile Devices Ingénierie
EQUIPMENT : Telematics embedded system
BRAND NAME : Mobile Devices Ingenierie
MODEL NAME : C4DONGLE-3GNA-WBT
MARKETING NAME : C4DONGLE-3GNA-WBT
FCC ID : A6G-C4DONGLE3G
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jul. 14, 2015 and testing was completed on Aug. 06, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant.....	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test	5
1.4	Product Specification subjective to this standard.....	6
1.5	Modification of EUT	6
1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7	Testing Location	8
1.8	Applicable Standards	8
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1	Test Mode.....	9
2.2	Connection Diagram of Test System	11
2.3	Support Unit used in test configuration	12
2.4	Measurement Results Explanation Example	12
3	TEST RESULT	13
3.1	Conducted Output Power Measurement.....	13
3.2	Peak-to-Average Ratio	15
3.3	Effective Radiated Power and Effective Isotropic Radiated Power Measurement	29
3.4	99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	33
3.5	Band Edge Measurement.....	53
3.6	Conducted Spurious Emission Measurement.....	60
3.7	Field Strength of Spurious Radiation Measurement	79
3.8	Frequency Stability Measurement.....	105
4	LIST OF MEASURING EQUIPMENT	110
5	UNCERTAINTY OF EVALUATION	111
APPENDIX A. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG571402	Rev. 01	Initial issue of report	Aug. 21, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	RSS-132 (5.4) RSS-133(6.4)	Peak-to-Average Ratio	<13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049	RSS-GEN(6.6) RSS-133(2.3)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 12.57 dB at 1648.4 MHz
3.8	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22 Within Authorized Band	PASS	-
	§2.1055 §24.235	RSS-GEN(6.11) RSS-133 (6.3)				

1 General Description

1.1 Applicant

Mobile Devices Ingénierie

100 Avenue de Stalingrad 94800 Villejuif FRANCE

1.2 Manufacturer

Mobile Devices Ingénierie

100 Avenue de Stalingrad 94800 Villejuif FRANCE

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Telematics embedded system
Brand Name	Mobile Devices Ingenierie
Model Name	C4DONGLE-3GNA-WBT
Marketing Name	C4DONGLE-3GNA-WBT
FCC ID	A6G-C4DONGLE3G
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v2.1+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 354676055000409 Radiation: Sample1:354676055001597 Sample2:354676055002421 ERP&EIRP: 354676055001597
HW Version	SAP00266
SW Version	V1944
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences is that sample 1 with battery and sample 2 without battery.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 31.50 dBm GSM1900 : 29.05 dBm WCDMA Band V : 22.99 dBm WCDMA Band II : 22.82 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.8974	0.0132 ppm	243KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.2685	0.0407 ppm	249KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1143	0.0120 ppm	4M07F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.5105	0.0048 ppm	243KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.1972	0.0048 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.1618	0.0043 ppm	4M05F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595
Test Site No.	Sporton Site No.
	TH01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH01-SZ	831040/4086F

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- ♦ IC RSS-132 Issue 3
- ♦ IC RSS-133 Issue 6
- ♦ IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:


Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Conducted Power Measurement Results:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	31.50	31.48	31.46	29.04	28.98	29.05
GPRS class 10	31.49	31.47	31.45	29.03	28.97	29.04
EGPRS class 8	26.01	26.00	26.02	25.12	25.07	25.16
EGPRS class 10	25.99	25.98	26.00	25.10	25.05	25.14

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
AMR 12.2K	22.98	22.80	22.42	22.81	22.22	22.30
RMC 12.2K	22.99	22.81	22.43	22.82	22.23	22.31
HSDPA Subtest-1	22.60	22.48	22.08	22.20	21.72	21.71
HSDPA Subtest-2	21.84	21.70	21.32	21.47	20.91	20.94
HSDPA Subtest-3	21.60	21.46	21.10	21.23	20.65	20.70
HSDPA Subtest-4	21.34	21.22	20.85	20.98	20.39	20.44
HSUPA Subtest-1	21.61	21.46	21.10	21.36	20.66	20.67
HSUPA Subtest-2	19.80	19.61	19.25	19.25	18.73	18.86
HSUPA Subtest-3	20.81	20.59	20.26	20.15	19.61	19.65
HSUPA Subtest-4	19.99	19.81	19.44	19.64	18.92	19.02
HSUPA Subtest-5	22.00	21.90	21.40	21.60	21.00	21.00

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	Solite	36B20L	Fcc DoC	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	31.50	31.48	31.46	26.01	26.00	26.02	22.99	22.81	22.43

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.04	28.98	29.05	25.12	25.07	25.16	22.82	22.23	22.31

Note: maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector on spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector on spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator has synchronized with the spectrum analyzer.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option on the spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.27	0.27	0.27	2.52	2.45	2.53	3.36	3.51	3.51


PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.26	0.26	0.26	2.88	2.82	2.92	3.30	3.33	3.22




3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Peak-to-Average Ratio on Channel 189 (836.4 MHz)






Peak-to-Average Ratio on Channel 251 (848.8 MHz)






Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Peak-to-Average Ratio on Channel 128 (824.2 MHz)




Peak-to-Average Ratio on Channel 189 (836.4 MHz)






Peak-to-Average Ratio on Channel 251 (848.8 MHz)






Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)






Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 4132 (826.4 MHz)




Peak-to-Average Ratio on Channel 4182 (836.4 MHz)





Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Date: 6.AUG.2015 03:57:28




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 6.AUG.2015 04:09:03

Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 6.AUG.2015 04:09:31



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 6.AUG.2015 04:09:54

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

3.3.4 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	28.09	0.6442	27.98	0.6281
Middle	836.4	28.20	0.6607	28.09	0.6442
Highest	848.8	29.53	0.8974	28.52	0.7112
Limit	ERP < 7W	Result		PASS	

GSM850 (EDGE class 8) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	824.2	22.74	0.1879	22.70	0.1862
Middle	836.4	22.81	0.1910	22.77	0.1892
Highest	848.8	24.29	0.2685	23.15	0.2065
Limit	ERP < 7W	Result		PASS	

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	826.4	20.58	0.1143	20.50	0.1122
Middle	836.4	19.63	0.0918	19.51	0.0893
Highest	846.6	20.22	0.1052	19.38	0.0867
Limit	ERP < 7W	Result		PASS	

3.3.5 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	26.29	0.4256	27.07	0.5093
Middle	1880.0	26.35	0.4315	27.08	0.5105
Highest	1909.8	26.96	0.4966	26.89	0.4887
Limit	EIRP < 2W	Result		PASS	

GSM1900 (EDGE class 8) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1850.2	22.15	0.1641	22.90	0.1950
Middle	1880.0	22.36	0.1722	22.95	0.1972
Highest	1909.8	22.90	0.1950	22.92	0.1959
Limit	EIRP < 2W	Result		PASS	

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Channel	Frequency (MHz)	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	1852.4	21.18	0.1312	22.09	0.1618
Middle	1880.0	20.68	0.1169	21.21	0.1321
Highest	1907.6	20.30	0.1072	20.16	0.1038
Limit	EIRP < 2W	Result		PASS	

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	240.23	243.13	241.68	240.23	246.02	248.91
26dB BW (kHz)	321.30	316.90	318.40	309.70	303.90	302.50

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	243.13	241.68	241.68	244.57	247.47	250.36
26dB BW (kHz)	316.90	318.40	321.30	314.00	311.10	312.60

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.07	4.05	4.05
26dB BW (MHz)	4.60	4.60	4.59


PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.05	4.05	4.05
26dB BW (MHz)	4.59	4.59	4.60




3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth

Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




26dB Bandwidth Plot on Channel 128 (824.2 MHz)






99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)





Date: 6.AUG.2015 03:38:14

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 6.AUG.2015 03:33:40

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)

26dB Bandwidth Plot on Channel 251 (848.8 MHz)





Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




26dB Bandwidth Plot on Channel 128 (824.2 MHz)






99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 6.AUG.2015 03:02:21


26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 6.AUG.2015 02:58:57



99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




26dB Bandwidth Plot on Channel 251 (848.8 MHz)






Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



26dB Bandwidth Plot on Channel 512 (1850.2 MHz)






99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 6.AUG.2015 02:52:22


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 6.AUG.2015 02:49:20




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 6.AUG.2015 02:51:27

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 6.AUG.2015 02:50:20




Band : GSM 1900 Test Mode : EDGE class 8 Link (8PSK)

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 6.AUG.2015 02:11:28


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 6.AUG.2015 02:07:13




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 6.AUG.2015 02:10:20


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 6.AUG.2015 02:07:57



99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



26dB Bandwidth Plot on Channel 810 (1909.8 MHz)






Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



26dB Bandwidth Plot on Channel 4132 (826.4 MHz)






99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 6.AUG.2015 03:45:48


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 6.AUG.2015 03:54:08



99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)




26dB Bandwidth Plot on Channel 4233 (846.6 MHz)






Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 6.AUG.2015 04:23:16


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)




Date: 6.AUG.2015 04:16:57



99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)






99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 6.AUG.2015 04:21:39

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 6.AUG.2015 04:19:53

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.5.4 Test Setup

<Conducted Band Edge >







3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Higher Band Edge Plot on Channel 251 (848.8 MHz)






Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)




Higher Band Edge Plot on Channel 251 (848.8 MHz)






Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Higher Band Edge Plot on Channel 810 (1909.8 MHz)






Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Higher Band Edge Plot on Channel 810 (1909.8 MHz)





Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)




Higher Band Edge Plot on Channel 4233 (846.6 MHz)





Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Higher Band Edge Plot on Channel 9538 (1907.6 MHz)



3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.6.4 Test Setup






3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH128
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	824.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 6.AUG.2015 03:20:41



Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 6.AUG.2015 03:20:02



Band :	GSM850	Channel :	CH251
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	848.8 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 6.AUG.2015 03:21:04



Band :	GSM850	Channel :	CH128
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	824.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 6.AUG.2015 03:18:22



Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz



Date: 6.AUG.2015 03:17:59



Band :	GSM850	Channel :	CH251
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	848.8 MHz


Conducted Spurious Emission Plot between 30MHz ~ 9GHz

Date: 6.AUG.2015 03:17:18



Band :	GSM1900	Channel :	CH512
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1850.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 6.AUG.2015 02:32:40




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 6.AUG.2015 02:33:25



Band :	GSM1900	Channel :	CH810
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1909.8 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 6.AUG.2015 02:34:51



Band :	GSM1900	Channel :	CH512
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1850.2 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 6.AUG.2015 02:30:23




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 6.AUG.2015 02:28:28



Band :	GSM1900	Channel :	CH810
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1909.8 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 6.AUG.2015 02:27:06



Band :	WCDMA Band V	Channel :	CH4132
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	826.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 6.AUG.2015 04:00:52



Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 6.AUG.2015 05:30:05



Band :	WCDMA Band V	Channel :	CH4233
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	846.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 9GHz




Date: 6.AUG.2015 03:58:30



Band :	WCDMA Band II	Channel :	CH9262
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1852.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz




Date: 6.AUG.2015 04:05:00



Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz



Date: 6.AUG.2015 04:03:00



Band :	WCDMA Band II	Channel :	CH9538
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1907.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 19.1GHz

Date: 6.AUG.2015 04:07:42

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures


1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.7.5 Test Result of Field Strength of Spurious Radiated

Sample 1

Band :	GSM850 for CH128					Temperature :	21~25℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-34.56	-13	-21.56	-38.35	-41.25	0.56	9.40	H	Pass
2472.6	-42.66	-13	-29.66	-48.50	-50.36	0.75	10.60	H	Pass
3296.8	-41.90	-13	-28.90	-52.54	-51.50	0.85	12.60	H	Pass
4120	-45.13	-13	-32.13	-55.95	-54.69	0.89	12.60	H	Pass
4944	-37.03	-13	-24.03	-51.23	-46.64	0.94	12.70	H	Pass
5768	-49.34	-13	-36.34	-62.57	-59.08	1.11	13.00	H	Pass
6592	-45.65	-13	-32.65	-62.85	-53.98	1.22	11.70	H	Pass
7416	-45.28	-13	-32.28	-63.90	-52.74	1.69	11.30	H	Pass
8242	-44.67	-13	-31.67	-64.62	-52.19	1.63	11.30	H	Pass

Band :	GSM850 for CH128	Temperature :	21~25℃						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-31.01	-13	-18.01	-36.98	-37.70	0.56	9.40	V	Pass
2472.6	-49.59	-13	-36.59	-55.33	-57.29	0.75	10.60	V	Pass
3296.8	-45.95	-13	-32.95	-54.51	-55.55	0.85	12.60	V	Pass
4120	-45.53	-13	-32.53	-55.91	-55.09	0.89	12.60	V	Pass
4944	-35.45	-13	-22.45	-50.70	-45.06	0.94	12.70	V	Pass
5768	-47.16	-13	-34.16	-62.81	-56.90	1.11	13.00	V	Pass
6592	-45.32	-13	-32.32	-61.95	-53.65	1.22	11.70	V	Pass
7416	-42.88	-13	-29.88	-60.86	-50.34	1.69	11.30	V	Pass
8242	-45.79	-13	-32.79	-64.02	-53.31	1.63	11.30	V	Pass



Band :	GSM850 for CH189					Temperature :	21~25℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-35.68	-13	-22.68	-39.45	-42.37	0.56	9.40	H	Pass
2510	-45.27	-13	-32.27	-50.80	-52.97	0.75	10.60	H	Pass
3346	-42.71	-13	-29.71	-53.40	-52.31	0.85	12.60	H	Pass
4182	-43.48	-13	-30.48	-54.45	-53.04	0.89	12.60	H	Pass
5018	-39.34	-13	-26.34	-53.24	-48.95	0.94	12.70	H	Pass
5854	-50.81	-13	-37.81	-64.04	-60.55	1.11	13.00	H	Pass
6691	-42.52	-13	-29.52	-59.72	-50.85	1.22	11.70	H	Pass
7528	-40.69	-13	-27.69	-59.31	-48.15	1.69	11.30	H	Pass

Band :	GSM850 for CH189					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-33.30	-13	-20.30	-39.28	-39.99	0.56	9.40	V	Pass
2510	-50.25	-13	-37.25	-55.66	-57.95	0.75	10.60	V	Pass
3346	-42.40	-13	-29.40	-51.70	-52.00	0.85	12.60	V	Pass
4182	-43.54	-13	-30.54	-54.49	-53.10	0.89	12.60	V	Pass
5018	-39.75	-13	-26.75	-54.16	-49.36	0.94	12.70	V	Pass
5854	-47.86	-13	-34.86	-63.51	-57.60	1.11	13.00	V	Pass
6691	-44.19	-13	-31.19	-60.82	-52.52	1.22	11.70	V	Pass
7528	-40.45	-13	-27.45	-58.43	-47.91	1.69	11.30	V	Pass



Band :	GSM850 for CH251					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-35.45	-13	-22.45	-39.23	-42.14	0.56	9.40	H	Pass
2546.4	-34.90	-13	-21.90	-41.25	-42.60	0.75	10.60	H	Pass
3395.2	-43.96	-13	-30.96	-54.42	-53.56	0.85	12.60	H	Pass
4244	-31.74	-13	-18.74	-44.52	-41.30	0.89	12.60	H	Pass
5092.8	-40.63	-13	-27.63	-54.27	-50.24	0.94	12.70	H	Pass
5941.6	-52.46	-13	-39.46	-65.69	-62.20	1.11	13.00	H	Pass
6790.4	-36.13	-13	-23.13	-53.36	-44.46	1.22	11.70	H	Pass
7639.2	-45.76	-13	-32.76	-64.38	-53.22	1.69	11.30	H	Pass

Band :	GSM850 for CH251					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-30.15	-13	-17.15	-36.23	-36.84	0.56	9.40	V	Pass
2546.4	-32.62	-13	-19.62	-41.17	-40.32	0.75	10.60	V	Pass
3395.2	-51.30	-13	-38.30	-58.16	-60.90	0.85	12.60	V	Pass
4244	-36.78	-13	-23.78	-49.32	-46.34	0.89	12.60	V	Pass
5092.8	-41.83	-13	-28.83	-55.38	-51.44	0.94	12.70	V	Pass
5941.6	-46.54	-13	-33.54	-62.19	-56.28	1.11	13.00	V	Pass
6790.4	-33.81	-13	-20.81	-51.41	-42.14	1.22	11.70	V	Pass
7639.2	-47.72	-13	-34.72	-65.70	-55.18	1.69	11.30	V	Pass



Band :	GSM850 for CH128					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-37.69	-13	-24.69	-41.38	-44.38	0.56	9.40	H	Pass
2472.6	-48.88	-13	-35.88	-53.77	-56.58	0.75	10.60	H	Pass
3296.8	-47.81	-13	-34.81	-57.11	-57.41	0.85	12.60	H	Pass

Band :	GSM850 for CH128					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1648.4	-34.80	-13	-21.80	-40.75	-41.49	0.56	9.40	V	Pass
2472.6	-55.18	-13	-42.18	-59.56	-62.88	0.75	10.60	V	Pass
3296.8	-50.25	-13	-37.25	-57.11	-59.85	0.85	12.60	V	Pass



Band :	GSM850 for CH189					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-38.77	-13	-25.77	-42.46	-45.46	0.56	9.40	H	Pass
2510	-54.03	-13	-41.03	-57.93	-61.73	0.75	10.60	H	Pass
3346	-48.92	-13	-35.92	-58.22	-58.52	0.85	12.60	H	Pass

Band :	GSM850 for CH189					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-36.61	-13	-23.61	-42.45	-43.30	0.56	9.40	V	Pass
2510	-54.33	-13	-41.33	-58.71	-62.03	0.75	10.60	V	Pass
3346	-51.87	-13	-38.87	-58.73	-61.47	0.85	12.60	V	Pass



Band :	GSM850 for CH251					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-43.29	-13	-30.29	-46.66	-49.98	0.56	9.40	H	Pass
2546.4	-56.83	-13	-43.83	-60.73	-64.53	0.75	10.60	H	Pass
3395.2	-53.79	-13	-40.79	-63.09	-63.39	0.85	12.60	H	Pass

Band :	GSM850 for CH251					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-40.00	-13	-27.00	-45.58	-46.69	0.56	9.40	V	Pass
2546.4	-54.40	-13	-41.40	-58.78	-62.10	0.75	10.60	V	Pass
3395.2	-53.01	-13	-40.01	-59.87	-62.61	0.85	12.60	V	Pass



Band :	GSM1900 for CH512					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-35.74	-13	-22.74	-48.02	-47.47	0.87	12.60	H	Pass
5550.6	-44.74	-13	-31.74	-60.62	-56.77	1.07	13.10	H	Pass
7400.8	-35.35	-13	-22.35	-55.35	-44.96	1.69	11.30	H	Pass

Band :	GSM1900 for CH512					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-36.34	-13	-23.34	-50.26	-48.07	0.87	12.6	V	Pass
5550.6	-45.57	-13	-32.57	-61.89	-57.60	1.07	13.1	V	Pass
7400.8	-32.32	-13	-19.32	-52.65	-41.93	1.69	11.3	V	Pass



Band :	GSM1900 for CH661					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-45.08	-13	-32.08	-56.33	-56.81	0.87	12.60	H	Pass
5640	-38.36	-13	-25.36	-54.83	-50.39	1.07	13.10	H	Pass
7520	-35.85	-13	-22.85	-55.66	-45.46	1.69	11.30	H	Pass

Band :	GSM1900 for CH661					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-39.68	-13	-26.68	-52.9	-51.41	0.87	12.6	V	Pass
5640	-39.82	-13	-26.82	-56.17	-51.85	1.07	13.1	V	Pass
7520	-31.82	-13	-18.82	-52.22	-41.43	1.69	11.3	V	Pass



Band :	GSM1900 for CH810	Temperature :	21~25°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3819.6	-45.80	-13	-32.80	-57.05	-57.53	0.87	12.60	H	Pass
5729.4	-45.24	-13	-32.24	-61.12	-57.27	1.07	13.10	H	Pass
7639.2	-33.46	-13	-20.46	-53.67	-43.07	1.69	11.30	H	Pass

Band :	GSM1900 for CH810	Temperature :	21~25°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-39.54	-13	-26.54	-52.79	-51.27	0.87	12.6	V	Pass
5729.4	-44.24	-13	-31.24	-60.56	-56.27	1.07	13.1	V	Pass
7639.2	-30.57	-13	-17.57	-51.35	-40.18	1.69	11.3	V	Pass



Band :	GSM1900 for CH512	Temperature :	21~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-48.97	-13	-35.97	-60.22	-60.70	0.87	12.60	H	Pass
5550.6	-52.01	-13	-39.01	-67.89	-64.04	1.07	13.10	H	Pass
7400.8	-49.68	-13	-36.68	-68.00	-59.29	1.69	11.30	H	Pass

Band :	GSM1900 for CH512	Temperature :	21~25°C						
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-46.18	-13	-33.18	-58.65	-57.91	0.87	12.6	V	Pass
5550.6	-51.29	-13	-38.29	-67.61	-63.32	1.07	13.1	V	Pass
7400.8	-48.95	-13	-35.95	-67.17	-58.56	1.69	11.3	V	Pass



Band :	GSM1900 for CH661					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-51.78	-13	-38.78	-63.03	-63.51	0.87	12.60	H	Pass
5640	-49.71	-13	-36.71	-65.59	-61.74	1.07	13.10	H	Pass
7520	-49.29	-13	-36.29	-67.61	-58.90	1.69	11.30	H	Pass

Band :	GSM1900 for CH661					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3760	-49.76	-13	-36.76	-62.23	-61.49	0.87	12.6	V	Pass
5640	-50.70	-13	-37.70	-67.02	-62.73	1.07	13.1	V	Pass
7520	-49.33	-13	-36.33	-67.55	-58.94	1.69	11.3	V	Pass



Band :	GSM1900 for CH810					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-51.79	-13	-38.79	-63.04	-63.52	0.87	12.60	H	Pass
5729.4	-51.84	-13	-38.84	-67.72	-63.87	1.07	13.10	H	Pass
7639.2	-48.94	-13	-35.94	-67.26	-58.55	1.69	11.30	H	Pass

Band :	GSM1900 for CH810					Temperature :	21~25°C		
Test Mode :	EDGE class 8 Link (8PSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3819.6	-53.74	-13	-40.74	-66.21	-65.47	0.87	12.6	V	Pass
5729.4	-51.82	-13	-38.82	-68.14	-63.85	1.07	13.1	V	Pass
7639.2	-49.85	-13	-36.85	-68.07	-59.46	1.69	11.3	V	Pass



Band :	WCDMA Band V for CH4132	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1652.8	-48.26	-13	-35.26	-50.99	-54.95	0.56	9.40	H	Pass
2479.2	-57.34	-13	-44.34	-61.24	-65.04	0.75	10.60	H	Pass
3305.6	-55.26	-13	-42.26	-64.56	-64.86	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4132	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
1652.8	-47.57	-13	-34.57	-51.97	-54.26	0.56	9.40	V	Pass
2479.2	-59.61	-13	-46.61	-63.99	-67.31	0.75	10.60	V	Pass
3305.6	-56.39	-13	-43.39	-63.25	-65.99	0.85	12.60	V	Pass



Band :	WCDMA Band V for CH4182	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-44.82	-13	-31.82	-47.95	-51.51	0.56	9.40	H	Pass
2510	-58.79	-13	-45.79	-62.69	-66.49	0.75	10.60	H	Pass
3346	-55.69	-13	-42.69	-64.99	-65.29	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4182	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
1672	-44.20	-13	-31.20	-49.21	-50.89	0.56	9.40	V	Pass
2510	-60.23	-13	-47.23	-64.61	-67.93	0.75	10.60	V	Pass
3346	-58.79	-13	-45.79	-65.65	-68.39	0.85	12.60	V	Pass



Band :	WCDMA Band V for CH4233	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1693.2	-47.64	-13	-34.64	-50.42	-54.33	0.56	9.40	H	Pass
2539.8	-59.23	-13	-46.23	-63.13	-66.93	0.75	10.60	H	Pass
3386.4	-55.88	-13	-42.88	-65.18	-65.48	0.85	12.60	H	Pass

Band :	WCDMA Band V for CH4233	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1693.2	-44.63	-13	-31.63	-49.58	-51.32	0.56	9.40	V	Pass
2539.8	-60.28	-13	-47.28	-64.66	-67.98	0.75	10.60	V	Pass
3386.4	-58.74	-13	-45.74	-65.60	-68.34	0.85	12.60	V	Pass



Band :	WCDMA Band II for CH9262	Temperature :	21~25℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3704.8	-42.24	-13	-29.24	-53.49	-53.97	0.87	12.60	H	Pass
5557.2	-46.12	-13	-33.12	-62.00	-58.15	1.07	13.10	H	Pass
7409.6	-45.83	-13	-32.83	-64.15	-55.44	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9262	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3704.8	-39.38	-13	-26.38	-52.66	-51.11	0.87	12.6	V	Pass
5557.2	-47.24	-13	-34.24	-63.56	-59.27	1.07	13.1	V	Pass
7409.6	-41.58	-13	-28.58	-59.8	-51.19	1.69	11.3	V	Pass



Band :	WCDMA Band II for CH9400	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain	(H/V)	
(dB)			(dB)	(dBm)	(dBm)	(dB)	(dBi)		
3760	-42.71	-13	-29.71	-53.96	-54.44	0.87	12.60	H	Pass
5640	-48.24	-13	-35.24	-64.12	-60.27	1.07	13.10	H	Pass
7520	-48.20	-13	-35.20	-66.52	-57.81	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9400	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3760	-33.56	-13	-20.56	-47.87	-45.29	0.87	12.6	V	Pass
5640	-48.96	-13	-35.96	-65.28	-60.99	1.07	13.1	V	Pass
7520	-45.18	-13	-32.18	-63.4	-54.79	1.69	11.3	V	Pass



Band :	WCDMA Band II for CH9538	Temperature :	21~25℃						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3815.2	-37.92	-13	-24.92	-49.90	-49.65	0.87	12.60	H	Pass
5722.8	-46.99	-13	-33.99	-62.87	-59.02	1.07	13.10	H	Pass
7630.4	-45.46	-13	-32.46	-63.78	-55.07	1.69	11.30	H	Pass

Band :	WCDMA Band II for CH9538	Temperature :	21~25°C						
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	loss	Gain	(H/V)	
3815.2	-34.50	-13	-21.50	-48.68	-46.23	0.87	12.6	V	Pass
5722.8	-46.89	-13	-33.89	-63.21	-58.92	1.07	13.1	V	Pass
7630.4	-41.73	-13	-28.73	-59.95	-51.34	1.69	11.3	V	Pass



Sample 2

Band :	GSM850 for CH128	Temperature :	21~25℃						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Horizontal						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648.4	-37.60	-13	-24.60	-41.28	-44.29	0.56	9.40	H	Pass
2472.6	-33.84	-13	-20.84	-40.16	-41.54	0.75	10.60	H	Pass
3296.8	-52.02	-13	-39.02	-61.32	-61.62	0.85	12.60	H	Pass
4120	-29.38	-13	-16.38	-42.28	-38.94	0.89	12.60	H	Pass
4944	-31.41	-13	-18.41	-46.60	-41.02	0.94	12.70	H	Pass
5768	-41.69	-13	-28.69	-55.01	-51.43	1.11	13.00	H	Pass
6592	-38.96	-13	-25.96	-56.16	-47.29	1.22	11.70	H	Pass
7416	-38.59	-13	-25.59	-57.21	-46.05	1.69	11.30	H	Pass

Band :	GSM850 for CH128	Temperature :	21~25℃						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1648.4	-25.57	-13	-12.57	-31.63	-32.26	0.56	9.40	V	Pass
2472.6	-38.37	-13	-25.37	-46.43	-46.07	0.75	10.60	V	Pass
3296.8	-56.52	-13	-43.52	-63.38	-66.12	0.85	12.60	V	Pass
4120	-29.63	-13	-16.63	-42.93	-39.19	0.89	12.60	V	Pass
4944	-30.82	-13	-17.82	-46.65	-40.43	0.94	12.70	V	Pass
5768	-41.45	-13	-28.45	-57.05	-51.19	1.11	13.00	V	Pass
6592	-41.77	-13	-28.77	-58.40	-50.10	1.22	11.70	V	Pass
7416	-39.70	-13	-26.70	-57.68	-47.16	1.69	11.30	V	Pass



Band :	GSM850 for CH189					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-35.35	-13	-22.35	-39.13	-42.04	0.56	9.40	H	Pass
2510	-34.28	-13	-21.28	-40.60	-41.98	0.75	10.60	H	Pass
3346	-39.96	-13	-26.96	-51.07	-49.56	0.85	12.60	H	Pass
4182	-29.96	-13	-16.96	-42.85	-39.52	0.89	12.60	H	Pass
5018	-31.72	-13	-18.72	-46.93	-41.33	0.94	12.70	H	Pass
5854	-41.72	-13	-28.72	-55.03	-51.46	1.11	13.00	H	Pass
6691	-40.24	-13	-27.24	-57.44	-48.57	1.22	11.70	H	Pass
7528	-40.36	-13	-27.36	-58.98	-47.82	1.69	11.30	H	Pass

Band :	GSM850 for CH189					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1672	-26.60	-13	-13.60	-32.66	-33.29	0.56	9.40	V	Pass
2510	-37.03	-13	-24.03	-45.24	-44.73	0.75	10.60	V	Pass
3346	-43.84	-13	-30.84	-52.87	-53.44	0.85	12.60	V	Pass
4182	-30.32	-13	-17.32	-43.55	-39.88	0.89	12.60	V	Pass
5018	-35.83	-13	-22.83	-51.11	-45.44	0.94	12.70	V	Pass
5854	-41.30	-13	-28.30	-56.83	-51.04	1.11	13.00	V	Pass
6691	-41.41	-13	-28.41	-58.04	-49.74	1.22	11.70	V	Pass
7528	-39.72	-13	-26.72	-57.70	-47.18	1.69	11.30	V	Pass



Band :	GSM850 for CH251					Temperature :	21~25℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-38.51	-13	-25.51	-42.21	-45.20	0.56	9.40	H	Pass
2546.4	-34.27	-13	-21.27	-40.59	-41.97	0.75	10.60	H	Pass
3395.2	-34.00	-13	-21.00	-45.59	-43.60	0.85	12.60	H	Pass
4244	-35.24	-13	-22.24	-47.74	-44.80	0.89	12.60	H	Pass
5092.8	-33.74	-13	-20.74	-48.61	-43.35	0.94	12.70	H	Pass
5941.6	-48.15	-13	-35.15	-61.38	-57.89	1.11	13.00	H	Pass
6790.4	-40.46	-13	-27.46	-57.66	-48.79	1.22	11.70	H	Pass
7639.2	-41.59	-13	-28.59	-60.21	-49.05	1.69	11.30	H	Pass

Band :	GSM850 for CH251					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
1697.6	-29.74	-13	-16.74	-35.82	-36.43	0.56	9.40	V	Pass
2546.4	-36.93	-13	-23.93	-45.15	-44.63	0.75	10.60	V	Pass
3395.2	-38.21	-13	-25.21	-48.16	-47.81	0.85	12.60	V	Pass
4244	-32.10	-13	-19.10	-45.22	-41.66	0.89	12.60	V	Pass
5092.8	-35.53	-13	-22.53	-50.78	-45.14	0.94	12.70	V	Pass
5941.6	-44.62	-13	-31.62	-60.27	-54.36	1.11	13.00	V	Pass
6790.4	-40.47	-13	-27.47	-57.10	-48.80	1.22	11.70	V	Pass
7639.2	-44.23	-13	-31.23	-62.21	-51.69	1.69	11.30	V	Pass



Band :	GSM1900 for CH512					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit (dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-38.51	-13	-25.51	-50.38	-50.24	0.87	12.60	H	Pass
5550.6	-47.35	-13	-34.35	-63.23	-59.38	1.07	13.10	H	Pass
7400.8	-32.59	-13	-19.59	-52.88	-42.20	1.69	11.30	H	Pass

Band :	GSM1900 for CH512					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Vertical		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over Limit	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	Reading (dBm)	Power (dBm)	loss (dB)	Gain (dBi)	(H/V)	
3700.4	-40.58	-13	-27.58	-53.52	-52.31	0.87	12.6	V	Pass
5550.6	-50.15	-13	-37.15	-66.47	-62.18	1.07	13.1	V	Pass
7400.8	-31.07	-13	-18.07	-51.79	-40.68	1.69	11.3	V	Pass



Band :	GSM1900 for CH661					Temperature :	21~25℃		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-37.93	-13	-24.93	-49.91	-49.66	0.87	12.60	H	Pass
5640	-44.05	-13	-31.05	-59.93	-56.08	1.07	13.10	H	Pass
7520	-33.43	-13	-20.43	-53.63	-43.04	1.69	11.30	H	Pass

Band :	GSM1900 for CH661	Temperature :	21~25°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-39.35	-13	-26.35	-52.63	-51.08	0.87	12.6	V	Pass
5640	-44.03	-13	-31.03	-60.35	-56.06	1.07	13.1	V	Pass
7520	-29.72	-13	-16.72	-50.55	-39.33	1.69	11.3	V	Pass



Band :	GSM1900 for CH810					Temperature :	21~25°C		
Test Mode :	GPRS class 8 Link (GMSK)					Relative Humidity :	42~45%		
Test Engineer :	Jack Tian					Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819.6	-38.74	-13	-25.74	-50.56	-50.47	0.87	12.60	H	Pass
5729.4	-47.15	-13	-34.15	-63.03	-59.18	1.07	13.10	H	Pass
7639.2	-34.78	-13	-21.78	-54.93	-44.39	1.69	11.30	H	Pass

Band :	GSM1900 for CH810	Temperature :	21~25°C						
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	42~45%						
Test Engineer :	Jack Tian	Polarization :	Vertical						
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
(MHz)	(dBm)	(dBm)	Limit	Reading	Power	loss	Gain		
			(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3819.6	-36.98	-13	-23.98	-50.83	-48.71	0.87	12.6	V	Pass
5729.4	-49.74	-13	-36.74	-66.06	-61.77	1.07	13.1	V	Pass
7639.2	-35.30	-13	-22.30	-55.03	-44.91	1.69	11.3	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0084	0.0072	PASS
40	0.0048	0.0048	
30	0.0024	0.0036	
20(Ref.)	0.0000	0.0000	
10	0.0012	0.0024	
0	0.0036	0.0311	
-10	0.0048	0.0335	
-20	0.0084	0.0359	
-30	0.0132	0.0407	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0021	0.0032	PASS
40	0.0016	0.0021	
30	0.0005	0.0011	
20(Ref.)	0.0000	0.0000	
10	0.0005	0.0011	
0	0.0011	0.0027	
-10	0.0021	0.0043	
-20	0.0032	0.0048	
-30	0.0048	0.0037	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0072	PASS
40	0.0048	
30	0.0024	
20(Ref.)	0.0000	
10	0.0024	
0	0.0036	
-10	0.0060	
-20	0.0084	
-30	0.0120	

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	within authorized band	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0016	PASS
40	0.0011	
30	0.0005	
20(Ref.)	0.0000	
10	0.0005	
0	0.0016	
-10	0.0021	
-20	0.0027	
-30	0.0043	

Note: The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	32	0.0012	2.5	PASS
		12	0.0000		
		BEP	0.0012		
	EDGE class 8	32	0.0012		
		12	0.0000		
		BEP	0.0012		
GSM 1900 CH661	GPRS class 8	32	0.0005	(Note 3.)	
		12	0.0000		
		BEP	0.0005		
	EDGE class 8	32	0.0011		
		12	0.0000		
		BEP	0.0005		
WCDMA Band V CH4182	RMC 12.2Kbps	32	0.0036	2.5	
		12	0.0024		
		BEP	0.0012		
WCDMA Band II CH9400	RMC 12.2Kbps	32	0.0005	(Note 3.)	
		12	0.0000		
		BEP	0.0005		

Note:

1. Normal Voltage = 12V.
2. Battery End Point (BEP) = 8 V.
3. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 05, 2015	Aug. 06, 2015	May 04, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Aug. 06, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Sep. 16, 2014	Aug. 06, 2015	Sep. 15, 2015	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Aug. 03, 2015	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz;Max 30dBm	Sep. 25, 2014	Aug. 03, 2015	Sep. 24, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Aug. 03, 2015	Nov. 06, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Oct. 15, 2014	Aug. 03, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Sep. 04, 2014	Aug. 03, 2015	Sep. 03, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan. 28, 2015	Aug. 03, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Aug. 03, 2015	May 04, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Aug. 03, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Aug. 03, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 03, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 03, 2015	NCR	Radiation (03CH01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.9dB
--	-------