



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



Certificate #6613.01

# FCC TEST REPORT

## (Part 15, Subpart C)

Applicant:	MUNIC
Address:	39 Avenue de Paris 94800 Villejuif – France

Manufacturer or Supplier:	MUNIC
Address:	39 Avenue de Paris 94800 Villejuif – France
Product:	telematics embedded system ALARM.COM CAR CONNECTOR
Brand Name:	MUNIC ALARM.COM
Model Name:	C4D-4MUSAC_V8 ADC-CC110
FCC ID:	A6GC4D-4MUSACV8
Date of tests:	Aug. 23, 2024 ~ Sep. 20, 2024

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.247  
 ANSI C63.10-2020

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department

Date: Sep. 20, 2024      Date: Sep. 20, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	5
1 SUMMARY OF TEST RESULTS .....	6
1.1 MEASUREMENT UNCERTAINTY .....	7
2 GENERAL INFORMATION .....	8
2.2 GENERAL DESCRIPTION OF EUT .....	8
2.3 DESCRIPTION OF TEST MODES .....	10
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	11
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	11
2.4 DUTY CYCLE OF TEST SIGNAL .....	15
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	16
2.6 DESCRIPTION OF SUPPORT UNITS .....	16
3 TEST TYPES AND RESULTS .....	17
3.1 RADIATED EMISSION MEASUREMENT .....	17
3.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	17
3.1.2 TEST INSTRUMENTS .....	18
3.1.3 TEST PROCEDURES .....	20
3.1.4 DEVIATION FROM TEST STANDARD .....	20
3.1.5 TEST SETUP .....	21
3.1.6 EUT OPERATING CONDITIONS .....	22
3.1.7 TEST RESULTS .....	23
3.2 6 DB BANDWIDTH MEASUREMENT .....	77
3.2.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT .....	77
3.2.2 TEST INSTRUMENTS .....	77
3.2.3 TEST PROCEDURE .....	78
3.2.4 DEVIATION FROM TEST STANDARD .....	79
3.2.5 TEST SETUP .....	79
3.2.6 EUT OPERATING CONDITIONS .....	79
3.2.7 TEST RESULTS .....	80
3.3 CONDUCTED OUTPUT POWER .....	81
3.3.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	81
3.3.2 TEST SETUP .....	81
3.3.3 TEST INSTRUMENTS .....	81
3.3.4 TEST PROCEDURES .....	81
3.3.5 DEVIATION FROM TEST STANDARD .....	81
3.3.6 EUT OPERATING CONDITIONS .....	81

**Test Report No.: PSU-QBJ2408220111RF05**

3.3.7 TEST RESULTS .....	82
3.4.7.1 MAXIMUM PEAK OUTPUT POWER .....	82
3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE).....	83
3.4 POWER SPECTRAL DENSITY MEASUREMENT .....	84
3.4.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	84
3.4.2 TEST SETUP .....	84
3.4.3 TEST INSTRUMENTS.....	84
3.4.4 TEST PROCEDURE .....	84
3.4.5 DEVIATION FROM TEST STANDARD .....	84
3.4.6 EUT OPERATING CONDITION .....	84
3.4.7 TEST RESULTS .....	85
3.5 OUT OF BAND EMISSION MEASUREMENT .....	86
3.5.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	86
3.5.2 TEST SETUP .....	86
3.5.3 TEST INSTRUMENTS.....	86
3.5.4 TEST PROCEDURE .....	86
3.5.5 DEVIATION FROM TEST STANDARD .....	87
3.5.6 EUT OPERATING CONDITION .....	87
3.5.7 TEST RESULTS .....	87
3.6 ANTENNA REQUIREMENTS .....	88
3.6.1 STANDARD APPLICABLE .....	88
3.6.2 ANTENNA CONNECTED CONSTRUCTION.....	88
3.6.3 ANTENNA GAIN .....	88
4 PHOTOGRAPHS OF THE TEST CONFIGURATION .....	89
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB ..	90
6 APPENDIX .....	91
WLAN.....	91
DTS BANDWIDTH.....	91
TEST RESULT .....	91
TEST GRAPHS.....	92
OCCUPIED CHANNEL BANDWIDTH.....	98
TEST RESULT .....	98
TEST GRAPHS.....	99
MAXIMUM CONDUCTED OUTPUT POWER .....	105
TEST RESULT .....	105
MAXIMUM POWER SPECTRAL DENSITY .....	105



**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05

TEST RESULT .....	105
TEST GRAPHS.....	107
BAND EDGE MEASUREMENTS .....	114
TEST RESULT.....	114
TEST GRAPHS.....	115
CONDUCTED SPURIOUS EMISSION .....	119
TEST RESULT.....	119
TEST GRAPHS.....	121
DUTY CYCLE .....	139
TEST RESULT .....	139
TEST GRAPHS.....	140
BLE 146	
DTS BANDWIDTH.....	146
TEST RESULT.....	146
TEST GRAPHS.....	146
OCCUPIED CHANNEL BANDWIDTH.....	148
TEST RESULT .....	148
TEST GRAPHS.....	148
MAXIMUM CONDUCTED OUTPUT POWER .....	150
TEST RESULT .....	150
MAXIMUM POWER SPECTRAL DENSITY .....	151
TEST RESULT .....	151
TEST GRAPHS.....	151
BAND EDGE MEASUREMENTS .....	153
TEST RESULT .....	153
TEST GRAPHS.....	153
CONDUCTED SPURIOUS EMISSION .....	154
TEST RESULT .....	154
TEST GRAPHS.....	154
DUTY CYCLE .....	158
TEST RESULT .....	158
TEST GRAPHS.....	159



**Test Report No.: PSU-QBJ2408220111RF05**

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QBJ2408220111RF05	Original release	Sep. 20, 2024



**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	Compliance	A
15.247(a)(2)	6dB bandwidth	Compliance	A
15.247(b)	Conducted Output power	Compliance	A
15.247(e)	Power Spectral Density	Compliance	A
15.203	Antenna Requirement	Compliance	A

Note : Except RSE and AC Power Conducted Emission, other data please refer to Appendix.

**\*Test Lab Information Reference**

**Lab A:**

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

**Lab Address:**

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

**Accredited Test Lab Cert 6613.01**

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



## 2 GENERAL INFORMATION

### 2.2 GENERAL DESCRIPTION OF EUT

<b>PRODUCT*</b>	telematics embedded system ALARM.COM CAR CONNECTOR
<b>BRAND NAME*</b>	MUNIC ALARM.COM
<b>MODEL NAME*</b>	C4D-4MUSAC_V8 ADC-CC110
<b>NOMINAL VOLTAGE*</b>	DC 13.5V/27V
<b>MODULATION *</b>	DSSS, OFDM, GFSK
<b>TRANSMISSION RATE*</b>	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n(HT20): up to 72.2 Mbps 802.11n(HT40): up to 150 Mbps BT_LE: 1 Mbps
<b>OPERATING FREQUENCY</b>	2412-2462MHz for 11b/g/n(HT20/40) 2402-2480MHz for BT-LE(GFSK)
<b>MAX. OUTPUT POWER</b>	WLAN: 106.91mW (Maximum) BT-LE: 5.83mW (Maximum)
<b>ANTENNA TYPE*</b>	Stamped metal antenna, SMD with 0.17dBi gain for WIFI/ BLE
<b>HW VERSION*</b>	HC4D-4MUSAC_V8.01
<b>SW VERSION*</b>	SC4D-4MUSAC_V8.01
<b>I/O PORTS*</b>	Refer to user's manual
<b>CABLE SUPPLIED*</b>	N/A

**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05**NOTE:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. EUT operating function.:

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n(HT20)	1TX /1RX
802.11n(HT40)	1TX /1RX
BT_LE(1MHz)	1TX /1RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
5. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.
6. The differences between model C4D-4MUSAC\_V8 and ADC-CC110 are as following.

Description	1st	2nd
Product name	Telematic Embedded System	ALARM.COM CAR CONNECTOR
Brand Name	MUNIC	ALARM.COM
Model Name	C4D-4MUSAC_V8	ADC-CC110
Differences	/	Use of a different product name (ALARM.COM CAR CONNECTOR), model name (ADC-CC110) and a different trademark (ALARM.COM) for marketing and client requirements.

**7. List of Accessory:**

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery	Howell	Li-polymer 552535H	Capacity : Li-ion, 450mAh



## 2.3 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE:** No need to concern of Conducted Emission due to the EUT is powered by battery.

### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	6.0
BT-LE	0 to 39	19	GFSK	1.0



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05

**RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

**POWER LINE CONDUCTED EMISSION TEST**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05

**BANDEdge MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

**TEST CONDITION:**



**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 13.5V/27V By DC Source	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 13.5V/27V By DC Source	Hanwen Xu
PLC	25deg. C, 52%RH	DC 13.5V/27V By DC Source	Hanwen Xu
APCM	25deg. C, 60%RH	DC 13.5V/27V By DC Source	Hanwen Xu



**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05

## 2.4 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix Of this test report.



## 2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C, Section 15.247**

**KDB 558074 D01 DTS Meas Guidance v05r02**

**ANSI C63.10-2020**

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC Source	HYELEC	HY3010B	551016	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable, 1.0m;



### 3 TEST TYPES AND RESULTS

#### 3.1 RADIATED EMISSION MEASUREMENT

##### 3.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>uV</sub>/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,22	Aug.29,24
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBEC K	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,22	Aug.21,24
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,22	Aug.21,24
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,22	Aug.30,24
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.06,22	Sep.05,24
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CA BLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CA BLE)	R&S	HF290-NMNM-	N/A	N/A	N/A



**BUREAU  
VERITAS** Test Report No.: PSU-QBJ2408220111RF05

		4.00M			
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,25

**NOTE:**

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GRRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



### 3.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation




### 3.1.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





**<Frequency Range above 1GHz>**



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.

**BUREAU  
VERITAS****Test Report No.: PSU-QBJ2408220111RF05**

### 3.1.7 TEST RESULTS


NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

#### BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

802.11g:

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		




#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value- Emission level.

BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		



## REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value- Emission level.



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05


#### ABOVE 1GHz WORST-CASE DATA:

**Note:** 1. For radiated emissions testing, the full testing range of different modes have been scanned, only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

#### 802.11B:


CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05






BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05






**REMARKS:**

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Limit value - Emission level.
2. 2412MHz: Fundamental frequency.




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



#### REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2437MHz: Fundamental frequency.




BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)









BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05






#### REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2462MHz: Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)








BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



#### REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2412MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05


CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05





#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)









BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05






#### REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)









BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



**BUREAU  
VERITAS****Test Report No.: PSU-QBJ2408220111RF05****REMARKS:**


3. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
4. 2412MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05


CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05





#### REMARKS:

3. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
4. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)








BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05




#### REMARKS:


3. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
4. 2462MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)








BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



#### REMARKS:


5. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
6. 2412MHz: Fundamental frequency.



BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05


CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05





#### REMARKS:

5. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
6. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)









BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05





#### REMARKS:

5. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
6. 2452MHz: Fundamental frequency.




**BELOW 1GHz WORST-CASE DATA:**

30 MHz – 1GHz data:

BT-LE\_1M

CHANNEL	TX Channel 19	0DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		




**REMARKS:**

1. Emission Level(dB $\mu$ V/m) = Raw Value(dB $\mu$ V) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		



### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




### ABOVE 1GHz TEST DATA

**Note:** 1. For radiated emissions testing, the full testing range of different modes have been scanned, only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

#### BT-LE \_1M


CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)





BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05





BUREAU  
VERITAS


Test Report No.: PSU-QBJ2408220111RF05





BUREAU  
VERITAS

Test Report No.: PSU-QBJ2408220111RF05



#### REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor  
Margin value = Limit value-Emission level.
2. 2402MHz: Fundamental frequency.



BUREAU  
VERITAS Test Report No.: PSU-QBJ2408220111RF05

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

